

PostGIS 3.5.7 ☒☒☒☒☒☒

Contents

1	简介	1
1.1	安装与升级	1
1.2	许可证 - 简介	2
1.3	许可证 - 详细	2
1.4	许可证 - 附录	3
2	PostGIS 简介	6
2.1	简介	6
2.2	安装与升级	6
2.2.1	简介	7
2.2.2	安装与升级	7
2.2.3	简介	8
2.2.4	简介	10
2.2.5	PostGIS Extensions 简介	10
2.2.6	简介	12
2.2.7	简介	15
2.3	安装与升级	16
2.4	Installing, Upgrading Tiger Geocoder, and loading data	16
2.4.1	Tiger Geocoder Enabling your PostGIS database	17
2.4.2	安装与升级 TIGER 数据	19
2.4.3	Required tools for tiger data loading	19
2.4.4	Upgrading your Tiger Geocoder Install and Data	20
2.5	安装与升级	20
3	PostGIS Administration	22
3.1	Performance Tuning	22
3.1.1	Startup	22
3.1.2	Runtime	23
3.2	Configuring raster support	23
3.3	Creating spatial databases	24

3.3.1	Spatially enable database using EXTENSION	24
3.3.2	Spatially enable database without using EXTENSION (discouraged)	24
3.4	Upgrading spatial databases	25
3.4.1	Soft upgrade	25
3.4.1.1	Soft Upgrade 9.1+ using extensions	25
3.4.1.2	Soft Upgrade Pre 9.1+ or without extensions	26
3.4.2	Hard upgrade	27
4	Data Management	29
4.1	GIS (OGC) Geometry	29
4.1.1	OGC Geometry	29
4.1.1.1	Point	30
4.1.1.2	LineString	30
4.1.1.3	LinearRing	30
4.1.1.4	Polygon	30
4.1.1.5	MultiPoint	30
4.1.1.6	MultiLineString	31
4.1.1.7	MultiPolygon	31
4.1.1.8	GeometryCollection	31
4.1.1.9	PolyhedralSurface	31
4.1.1.10	Triangle	31
4.1.1.11	TIN	31
4.1.2	SQL-MM Part 3	32
4.1.2.1	CircularString	32
4.1.2.2	CompoundCurve	32
4.1.2.3	CurvePolygon	32
4.1.2.4	MultiCurve	33
4.1.2.5	MultiSurface	33
4.1.3	OpenGIS WKB ↔ WKT	33
4.2	Geometry Data Type	34
4.2.1	OpenGIS WKB ↔ WKT	34
4.3	PostGIS Geometry	36
4.3.1	Geometry	37
4.3.2	PostGIS Geometry	38
4.3.3	Geometry Functions	39
4.3.4	Geometry FAQ	39
4.4	Geometry Validation	39
4.4.1	Simple Geometry	40
4.4.2	Valid Geometry	41

4.4.3	Managing Validity	43
4.5	SPATIAL_REF_SYS 表	44
4.5.1	SPATIAL_REF_SYS Table	45
4.5.2	SPATIAL_REF_SYS 表	46
4.6	几何元数据	46
4.6.1	几何元数据	46
4.6.2	The GEOMETRY_COLUMNS VIEW	47
4.6.3	geometry_columns 表	48
4.7	GIS (GIS) 数据	50
4.7.1	SQL 数据	50
4.7.2	shp2pgsql: ESRI shapefile 数据	50
4.8	GIS 数据	52
4.8.1	SQL 数据	52
4.8.2	数据	53
4.9	GIS 数据	54
4.9.1	GiST 数据	54
4.9.2	GiST 数据	55
4.9.3	GiST 数据	56
4.9.4	数据	57
5	Spatial Queries	59
5.1	Determining Spatial Relationships	59
5.1.1	Dimensionally Extended 9-Intersection Model	59
5.1.2	Named Spatial Relationships	61
5.1.3	General Spatial Relationships	62
5.2	Using Spatial Indexes	64
5.3	Examples of Spatial SQL	65
6	GIS 数据	68
6.1	GIS 数据	68
6.1.1	数据	68
6.1.2	数据	68
6.2	GIS 数据	69
6.3	数据	69

7	PostGIS Reference	70
7.1	PostgreSQL PostGIS Geometry/Geography/Box 2D	70
7.1.1	box2d	70
7.1.2	box3d	71
7.1.3	geometry	71
7.1.4	geometry_dump	72
7.1.5	geography	72
7.2	管理几何列和表	73
7.2.1	AddGeometryColumn	73
7.2.2	DropGeometryColumn	75
7.2.3	DropGeometryTable	76
7.2.4	Find_SRID	76
7.2.5	Populate_Geometry_Columns	77
7.2.6	UpdateGeometrySRID	78
7.3	ST_ (构造函数)	79
7.3.1	ST_Collect	79
7.3.2	ST_LineFromMultiPoint	81
7.3.3	ST_MakeEnvelope	82
7.3.4	ST_MakeLine	82
7.3.5	ST_MakePoint	84
7.3.6	ST_MakePointM	85
7.3.7	ST_MakePolygon	87
7.3.8	ST_Point	88
7.3.9	ST_PointZ	90
7.3.10	ST_PointM	90
7.3.11	ST_PointZM	91
7.3.12	ST_Polygon	91
7.3.13	ST_TileEnvelope	92
7.3.14	ST_HexagonGrid	93
7.3.15	ST_Hexagon	96
7.3.16	ST_SquareGrid	97
7.3.17	ST_Square	98
7.3.18	ST_Letters	99
7.4	ST_ (访问器)	100
7.4.1	GeometryType	100
7.4.2	ST_Boundary	102
7.4.3	ST_BoundingDiagonal	104
7.4.4	ST_CoordDim	105
7.4.5	ST_Dimension	105

7.4.6 ST_Dump	106
7.4.7 ST_DumpPoints	108
7.4.8 ST_DumpSegments	112
7.4.9 ST_DumpRings	114
7.4.10 ST_EndPoint	115
7.4.11 ST_Envelope	116
7.4.12 ST_ExteriorRing	118
7.4.13 ST_GeometryN	119
7.4.14 ST_GeometryType	121
7.4.15 ST_HasArc	122
7.4.16 ST_InteriorRingN	123
7.4.17 ST_NumCurves	124
7.4.18 ST_CurveN	124
7.4.19 ST_IsClosed	125
7.4.20 ST_IsCollection	127
7.4.21 ST_IsEmpty	128
7.4.22 ST_IsPolygonCCW	129
7.4.23 ST_IsPolygonCW	130
7.4.24 ST_IsRing	131
7.4.25 ST_IsSimple	131
7.4.26 ST_M	132
7.4.27 ST_MemSize	133
7.4.28 ST_NDims	134
7.4.29 ST_NPoints	135
7.4.30 ST_NRings	136
7.4.31 ST_NumGeometries	136
7.4.32 ST_NumInteriorRings	137
7.4.33 ST_NumInteriorRing	138
7.4.34 ST_NumPatches	138
7.4.35 ST_NumPoints	139
7.4.36 ST_PatchN	140
7.4.37 ST_PointN	141
7.4.38 ST_Points	142
7.4.39 ST_StartPoint	143
7.4.40 ST_Summary	144
7.4.41 ST_X	145
7.4.42 ST_Y	146
7.4.43 ST_Z	147
7.4.44 ST_Zmflag	148

7.4.45	ST_HasZ	148
7.4.46	ST_HasM	149
7.5	编辑器	150
7.5.1	ST_AddPoint	150
7.5.2	ST_CollectionExtract	151
7.5.3	ST_CollectionHomogenize	152
7.5.4	ST_CurveToLine	154
7.5.5	ST_Scroll	156
7.5.6	ST_FlipCoordinates	157
7.5.7	ST_Force2D	158
7.5.8	ST_Force3D	159
7.5.9	ST_Force3DZ	159
7.5.10	ST_Force3DM	160
7.5.11	ST_Force4D	161
7.5.12	ST_ForceCollection	162
7.5.13	ST_ForceCurve	163
7.5.14	ST_ForcePolygonCCW	164
7.5.15	ST_ForcePolygonCW	164
7.5.16	ST_ForceSFS	165
7.5.17	ST_ForceRHR	165
7.5.18	ST_LineExtend	166
7.5.19	ST_LineToCurve	167
7.5.20	ST_Multi	168
7.5.21	ST_Normalize	169
7.5.22	ST_Project	170
7.5.23	ST_QuantizeCoordinates	170
7.5.24	ST_RemovePoint	173
7.5.25	ST_RemoveRepeatedPoints	173
7.5.26	ST_RemoveIrrelevantPointsForView	174
7.5.27	ST_RemoveSmallParts	177
7.5.28	ST_Reverse	178
7.5.29	ST_Segmentize	179
7.5.30	ST_SetPoint	181
7.5.31	ST_ShiftLongitude	182
7.5.32	ST_WrapX	183
7.5.33	ST_SnapToGrid	184
7.5.34	ST_Snap	185
7.5.35	ST_SwapOrdinates	188
7.6	Geometry Validation	189

7.6.1	ST_IsValid	189
7.6.2	ST_IsValidDetail	190
7.6.3	ST_IsValidReason	192
7.6.4	ST_MakeValid	193
7.7	Spatial Reference System Functions	198
7.7.1	ST_InverseTransformPipeline	198
7.7.2	ST_SetSRID	199
7.7.3	ST_SRID	200
7.7.4	ST_Transform	201
7.7.5	ST_TransformPipeline	203
7.7.6	postgis_srs_codes	205
7.7.7	postgis_srs	206
7.7.8	postgis_srs_all	206
7.7.9	postgis_srs_search	207
7.8	Geometry Input	208
7.8.1	Well-Known Text (WKT)	208
7.8.1.1	ST_BdPolyFromText	208
7.8.1.2	ST_BdMPolyFromText	209
7.8.1.3	ST_GeogFromText	209
7.8.1.4	ST_GeographyFromText	210
7.8.1.5	ST_GeomCollFromText	210
7.8.1.6	ST_GeomFromEWKT	211
7.8.1.7	ST_GeomFromMARC21	213
7.8.1.8	ST_GeometryFromText	215
7.8.1.9	ST_GeomFromText	216
7.8.1.10	ST_LineFromText	217
7.8.1.11	ST_MLineFromText	218
7.8.1.12	ST_MPointFromText	219
7.8.1.13	ST_MPolyFromText	219
7.8.1.14	ST_PointFromText	220
7.8.1.15	ST_PolygonFromText	221
7.8.1.16	ST_WKTToSQL	222
7.8.2	Well-Known Binary (WKB)	223
7.8.2.1	ST_GeogFromWKB	223
7.8.2.2	ST_GeomFromEWKB	223
7.8.2.3	ST_GeomFromWKB	225
7.8.2.4	ST_LineFromWKB	226
7.8.2.5	ST_LinestringFromWKB	226
7.8.2.6	ST_PointFromWKB	227

7.8.2.7 ST_WKBToSQL	228
7.8.3 Other Formats	229
7.8.3.1 ST_Box2dFromGeoHash	229
7.8.3.2 ST_GeomFromGeoHash	230
7.8.3.3 ST_GeomFromGML	231
7.8.3.4 ST_GeomFromGeoJSON	233
7.8.3.5 ST_GeomFromKML	234
7.8.3.6 ST_GeomFromTWKB	235
7.8.3.7 ST_GMLToSQL	236
7.8.3.8 ST_LineFromEncodedPolyline	236
7.8.3.9 ST_PointFromGeoHash	237
7.8.3.10 ST_FromFlatGeobufToTable	238
7.8.3.11 ST_FromFlatGeobuf	238
7.9 Geometry Output	239
7.9.1 Well-Known Text (WKT)	239
7.9.1.1 ST_AsEWKT	239
7.9.1.2 ST_AsText	240
7.9.2 Well-Known Binary (WKB)	241
7.9.2.1 ST_AsBinary	241
7.9.2.2 ST_AsEWKB	243
7.9.2.3 ST_AsHEXEWKB	244
7.9.3 Other Formats	245
7.9.3.1 ST_AsEncodedPolyline	245
7.9.3.2 ST_AsFlatGeobuf	246
7.9.3.3 ST_AsGeobuf	246
7.9.3.4 ST_AsGeoJSON	247
7.9.3.5 ST_AsGML	249
7.9.3.6 ST_AsKML	253
7.9.3.7 ST_AsLatLonText	254
7.9.3.8 ST_AsMARC21	255
7.9.3.9 ST_AsMVTGeom	258
7.9.3.10 ST_AsMVT	259
7.9.3.11 ST_AsSVG	261
7.9.3.12 ST_AsTWKB	262
7.9.3.13 ST_AsX3D	263
7.9.3.14 ST_GeoHash	267
7.10 运算符 (operator)	268
7.10.1 Bounding Box Operators	268
7.10.1.1 &&	268

7.10.1.2	&(geometry,box2df)	269
7.10.1.3	&(box2df,geometry)	270
7.10.1.4	&(box2df,box2df)	270
7.10.1.5	&&	271
7.10.1.6	&&(geometry,gidx)	273
7.10.1.7	&&(gidx,geometry)	273
7.10.1.8	&&(gidx,gidx)	274
7.10.1.9	&<	275
7.10.1.10	&<	276
7.10.1.11	&>	277
7.10.1.12	&<	278
7.10.1.13	&<	278
7.10.1.14		279
7.10.1.15	&>	281
7.10.1.16	@	281
7.10.1.17	@(geometry,box2df)	282
7.10.1.18	@(box2df,geometry)	283
7.10.1.19	@(box2df,box2df)	284
7.10.1.20	&>	285
7.10.1.21	>	285
7.10.1.22		286
7.10.1.23	(geometry,box2df)	287
7.10.1.24	(box2df,geometry)	288
7.10.1.25	(box2df,box2df)	289
7.10.1.26	=	289
7.10.2	~ (operator)	290
7.10.2.1	<->	290
7.10.2.2	=	292
7.10.2.3	<#>	293
7.10.2.4	<<->>	295
7.11	Spatial Relationships	295
7.11.1	Topological Relationships	295
7.11.1.1	ST_3DIntersects	295
7.11.1.2	ST_Contains	297
7.11.1.3	ST_ContainsProperly	300
7.11.1.4	ST_CoveredBy	302
7.11.1.5	ST_Covers	303
7.11.1.6	ST_Crosses	304
7.11.1.7	ST_Disjoint	307

7.11.1.8ST_Equals	308
7.11.1.9ST_Intersects	309
7.11.1.10ST_LineCrossingDirection	310
7.11.1.11ST_OrderingEquals	313
7.11.1.12ST_Overlaps	314
7.11.1.13ST_Relate	317
7.11.1.14ST_RelateMatch	319
7.11.1.15ST_Touches	320
7.11.1.16ST_Within	322
7.11.2Distance Relationships	324
7.11.2.1ST_3DDWithin	324
7.11.2.2ST_3DDFullyWithin	325
7.11.2.3ST_DFullyWithin	326
7.11.2.4ST_DWithin	327
7.11.2.5ST_PointInsideCircle	328
7.12Measurement Functions	329
7.12.1ST_Area	329
7.12.2ST_Azimuth	331
7.12.3ST_Angle	332
7.12.4ST_ClosestPoint	333
7.12.5ST_3DClosestPoint	335
7.12.6ST_Distance	336
7.12.7ST_3DDistance	338
7.12.8ST_DistanceSphere	339
7.12.9ST_DistanceSpheroid	340
7.12.10ST_FrechetDistance	341
7.12.11ST_HausdorffDistance	342
7.12.12ST_Length	344
7.12.13ST_Length2D	345
7.12.14ST_3DLength	346
7.12.15ST_LengthSpheroid	346
7.12.16ST_LongestLine	348
7.12.17ST_3DLongestLine	350
7.12.18ST_MaxDistance	351
7.12.19ST_3DMaxDistance	352
7.12.20ST_MinimumClearance	353
7.12.21ST_MinimumClearanceLine	354
7.12.22ST_Perimeter	354
7.12.23ST_Perimeter2D	356

7.12.2	ST_3DPerimeter	356
7.12.2	ST_ShortestLine	357
7.12.2	ST_3DShortestLine	359
7.13	Overlay Functions	360
7.13.1	ST_ClipByBox2D	360
7.13.2	ST_Difference	361
7.13.3	ST_Intersection	362
7.13.4	ST_MemUnion	365
7.13.5	ST_Node	365
7.13.6	ST_Split	366
7.13.7	ST_Subdivide	369
7.13.8	ST_SymDifference	372
7.13.9	ST_UnaryUnion	373
7.13.10	ST_Union	374
7.14	Geometry Functions	377
7.14.1	ST_Buffer	377
7.14.2	ST_BuildArea	382
7.14.3	ST_Centroid	384
7.14.4	ST_ChaikinSmoothing	386
7.14.5	ST_ConcaveHull	387
7.14.6	ST_ConvexHull	391
7.14.7	ST_DelaunayTriangles	393
7.14.8	ST_FilterByM	398
7.14.9	ST_GeneratePoints	399
7.14.10	ST_GeometricMedian	400
7.14.11	ST_LineMerge	401
7.14.12	ST_MaximumInscribedCircle	404
7.14.13	ST_LargestEmptyCircle	406
7.14.14	ST_MinimumBoundingCircle	408
7.14.15	ST_MinimumBoundingRadius	409
7.14.16	ST_OrientedEnvelope	410
7.14.17	ST_OffsetCurve	411
7.14.18	ST_PointOnSurface	415
7.14.19	ST_Polygonize	417
7.14.20	ST_ReducePrecision	419
7.14.21	ST_SharedPaths	421
7.14.22	ST_Simplify	423
7.14.23	ST_SimplifyPreserveTopology	425
7.14.24	ST_SimplifyPolygonHull	427

7.14.2ST_SimplifyVW	429
7.14.26T_SetEffectiveArea	431
7.14.28T_TriangulatePolygon	432
7.14.28T_VoronoiLines	434
7.14.29T_VoronoiPolygons	435
7.15Coverages	437
7.15.1ST_CoverageInvalidEdges	437
7.15.2ST_CoverageSimplify	439
7.15.3ST_CoverageUnion	440
7.16Affine Transformations	442
7.16.1ST_Affine	442
7.16.2ST_Rotate	443
7.16.3ST_RotateX	444
7.16.4ST_RotateY	445
7.16.5ST_RotateZ	446
7.16.6ST_Scale	447
7.16.7ST_Translate	449
7.16.8ST_TransScale	450
7.17Clustering Functions	451
7.17.1ST_ClusterDBSCAN	451
7.17.2ST_ClusterIntersecting	454
7.17.3ST_ClusterIntersectingWin	454
7.17.4ST_ClusterKMeans	455
7.17.5ST_ClusterWithin	457
7.17.6ST_ClusterWithinWin	458
7.18Bounding Box Functions	459
7.18.1Box2D	459
7.18.2Box3D	460
7.18.3ST_EstimatedExtent	461
7.18.4ST_Expand	462
7.18.5ST_Extent	463
7.18.6ST_3DExtent	464
7.18.7ST_MakeBox2D	466
7.18.8ST_3DMakeBox	466
7.18.9ST_XMax	467
7.18.10T_XMin	468
7.18.11T_YMax	469
7.18.12T_YMin	470
7.18.13T_ZMax	471

7.18.1ST_ZMin	472
7.19ST_Line (Linear Referencing)	473
7.19.1ST_LineInterpolatePoint	473
7.19.2ST_3DLineInterpolatePoint	474
7.19.3ST_LineInterpolatePoints	475
7.19.4ST_LineLocatePoint	476
7.19.5ST_LineSubstring	477
7.19.6ST_LocateAlong	479
7.19.7ST_LocateBetween	480
7.19.8ST_LocateBetweenElevations	482
7.19.9ST_InterpolatePoint	483
7.19.10ST_AddMeasure	483
7.20Trajectory Functions	484
7.20.1ST_IsValidTrajectory	484
7.20.2ST_ClosestPointOfApproach	485
7.20.3ST_DistanceCPA	486
7.20.4ST_CPAWithin	487
7.21Version Functions	488
7.21.1PostGIS_Extensions_Upgrade	488
7.21.2PostGIS_Full_Version	489
7.21.3PostGIS_GEOS_Version	489
7.21.4PostGIS_GEOS_Compiled_Version	490
7.21.5PostGIS_Liblwgeom_Version	490
7.21.6PostGIS_LibXML_Version	491
7.21.7PostGIS_LibJSON_Version	491
7.21.8PostGIS_Lib_Build_Date	492
7.21.9PostGIS_Lib_Version	492
7.21.10PostGIS_PROJ_Version	493
7.21.11PostGIS_PROJ_Compiled_Version	493
7.21.12PostGIS_Wagyu_Version	494
7.21.13PostGIS_Scripts_Build_Date	495
7.21.14PostGIS_Scripts_Installed	495
7.21.15PostGIS_Scripts_Released	496
7.21.16PostGIS_Version	496
7.22PostGIS GUC(Grand Unified Custom Variable)	497
7.22.1postgis.gdal_datapath	497
7.22.2postgis.gdal_enabled_drivers	498
7.22.3postgis.enable_outdb_rasters	499
7.22.4postgis.gdal_vsi_options	500
7.23Troubleshooting Functions	501
7.23.1PostGIS_AddBBox	501
7.23.2PostGIS_DropBBox	501
7.23.3PostGIS_HasBBox	502

8 SFCGAL Functions Reference	504
8.1 SFCGAL Management Functions	504
8.1.1 postgis_sfcgal_version	504
8.1.2 postgis_sfcgal_full_version	504
8.2 SFCGAL Accessors and Setters	505
8.2.1 CG_ForceLHR	505
8.2.2 CG_IsPlanar	505
8.2.3 CG_IsSolid	506
8.2.4 CG_MakeSolid	506
8.2.5 CG_Orientation	507
8.2.6 CG_Area	507
8.2.7 CG_3DArea	508
8.2.8 CG_Volume	508
8.2.9 ST_ForceLHR	509
8.2.10 ST_IsPlanar	510
8.2.11 ST_IsSolid	510
8.2.12 ST_MakeSolid	511
8.2.13 ST_Orientation	511
8.2.14 ST_3DArea	512
8.2.15 ST_Volume	513
8.3 SFCGAL Processing and Relationship Functions	514
8.3.1 CG_Intersection	514
8.3.2 CG_Intersects	515
8.3.3 CG_3DIntersects	515
8.3.4 CG_Difference	516
8.3.5 ST_3DDifference	517
8.3.6 CG_3DDifference	518
8.3.7 CG_Distance	519
8.3.8 CG_3DDistance	520
8.3.9 ST_3DConvexHull	521
8.3.10 CG_3DConvexHull	521
8.3.11 ST_3DIntersection	522
8.3.12 CG_3DIntersection	523
8.3.13 CG_Union	525
8.3.14 ST_3DUnion	526
8.3.15 CG_3DUnion	526
8.3.16 ST_AlphaShape	527
8.3.17 CG_AlphaShape	528
8.3.18 CG_ApproxConvexPartition	531

8.3.19ST_ApproximateMedialAxis	532
8.3.20CG_ApproximateMedialAxis	533
8.3.21ST_ConstrainedDelaunayTriangles	534
8.3.22CG_ConstrainedDelaunayTriangles	535
8.3.23ST_Extrude	536
8.3.24CG_Extrude	536
8.3.25CG_ExtrudeStraightSkeleton	538
8.3.26CG_GreeneApproxConvexPartition	539
8.3.27ST_MinkowskiSum	540
8.3.28CG_MinkowskiSum	541
8.3.29ST_OptimalAlphaShape	543
8.3.30CG_OptimalAlphaShape	544
8.3.31CG_OptimalConvexPartition	546
8.3.32CG_StraightSkeleton	547
8.3.33ST_StraightSkeleton	548
8.3.34ST_Tessellate	549
8.3.35CG_Tessellate	550
8.3.36CG_Triangulate	552
8.3.37CG_Visibility	553
8.3.38CG_YMonotonePartition	554

9 拓扑 (topology) 556

9.1 拓扑	556
9.1.1 getfaceedges_returntype	556
9.1.2 TopoGeometry	557
9.1.3 validate_topology_returntype	557
9.2 拓扑	558
9.2.1 TopoElement	558
9.2.2 TopoElementArray	558
9.3 拓扑 TopoGeometry 拓扑	559
9.3.1 AddTopoGeometryColumn	559
9.3.2 RenameTopoGeometryColumn	560
9.3.3 DropTopology	561
9.3.4 RenameTopology	561
9.3.5 DropTopoGeometryColumn	562
9.3.6 Populate_Topology_Layer	562
9.3.7 TopologySummary	563
9.3.8 ValidateTopology	564
9.3.9 ValidateTopologyRelation	567

9.3.10	FindTopology	567
9.3.11	FindLayer	568
9.4	Topology Statistics Management	568
9.5	拓扑管理	568
9.5.1	CreateTopology	568
9.5.2	CopyTopology	569
9.5.3	ST_InitTopoGeo	570
9.5.4	ST_CreateTopoGeo	571
9.5.5	TopoGeo_AddPoint	572
9.5.6	TopoGeo_AddLineString	572
9.5.7	TopoGeo_AddPolygon	573
9.5.8	TopoGeo_LoadGeometry	573
9.6	拓扑操作	574
9.6.1	ST_AddIsoNode	574
9.6.2	ST_AddIsoEdge	574
9.6.3	ST_AddEdgeNewFaces	575
9.6.4	ST_AddEdgeModFace	576
9.6.5	ST_RemEdgeNewFace	576
9.6.6	ST_RemEdgeModFace	577
9.6.7	ST_ChangeEdgeGeom	578
9.6.8	ST_ModEdgeSplit	579
9.6.9	ST_ModEdgeHeal	579
9.6.10	ST_NewEdgeHeal	580
9.6.11	ST_MoveIsoNode	580
9.6.12	ST_NewEdgesSplit	581
9.6.13	ST_RemoveIsoNode	582
9.6.14	ST_RemoveIsoEdge	583
9.7	拓扑查询	583
9.7.1	GetEdgeByPoint	583
9.7.2	GetFaceByPoint	584
9.7.3	GetFaceContainingPoint	585
9.7.4	GetNodeByPoint	585
9.7.5	GetTopologyID	586
9.7.6	GetTopologySRID	587
9.7.7	GetTopologyName	587
9.7.8	ST_GetFaceEdges	588
9.7.9	ST_GetFaceGeometry	589
9.7.10	GetRingEdges	590
9.7.11	GetNodeEdges	590

9.8	几何操作	591
9.8.1	Polygonize	591
9.8.2	AddNode	591
9.8.3	AddEdge	592
9.8.4	AddFace	593
9.8.5	ST_Simplify	595
9.8.6	RemoveUnusedPrimitives	596
9.9	TopoGeometry 操作	596
9.9.1	CreateTopoGeom	596
9.9.2	toTopoGeom	598
9.9.3	TopoElementArray_Agg	599
9.9.4	TopoElement	600
9.10	TopoGeometry 操作	600
9.10.1	clearTopoGeom	600
9.10.2	TopoGeom_addElement	601
9.10.3	TopoGeom_remElement	601
9.10.4	TopoGeom_addTopoGeom	602
9.10.5	toTopoGeom	603
9.11	TopoGeometry 操作	603
9.11.1	GetTopoGeomElementArray	603
9.11.2	GetTopoGeomElements	603
9.11.3	ST_SRID	604
9.12	TopoGeometry 操作	605
9.12.1	AsGML	605
9.12.2	AsTopoJSON	607
9.13	几何操作	608
9.13.1	Equals	608
9.13.2	Intersects	609
9.14	Importing and exporting Topologies	610
9.14.1	Using the Topology exporter	610
9.14.2	Using the Topology importer	610
10	地理信息系统的集成, 数据库	612
10.1	地理信息系统的集成	612
10.1.1	raster2pgsql 操作	612
10.1.1.1	Example Usage	612
10.1.1.2	raster2pgsql options	613
10.1.2	PostGIS 地理信息系统的集成	614
10.1.3	Using "out db" cloud rasters	615

10.2 地理函数	616
10.2.1 地理函数	616
10.2.2 地理函数	617
10.3 PostGIS 与 其他数据库的集成	618
10.3.1 使用 ST_AsPNG 函数在 PHP 中生成地图	618
10.3.2 使用 ST_AsPNG 函数在 ASP.NET C# 中生成地图	619
10.3.3 使用 ST_AsPNG 函数在 Java 中生成地图	620
10.3.4 PLPython 与 SQL 的集成	622
10.3.5 PSQL 与 其他数据库的集成	622
11 地理函数	624
11.1 地理函数	625
11.1.1 geomval	625
11.1.2 addbandarg	625
11.1.3 rastbandarg	625
11.1.4 raster	626
11.1.5 reclassarg	626
11.1.6 summarystats	627
11.1.7 unionarg	627
11.2 地理函数	628
11.2.1 AddRasterConstraints	628
11.2.2 DropRasterConstraints	630
11.2.3 AddOverviewConstraints	631
11.2.4 DropOverviewConstraints	632
11.2.5 PostGIS_GDAL_Version	632
11.2.6 PostGIS_Raster_Lib_Build_Date	633
11.2.7 PostGIS_Raster_Lib_Version	633
11.2.8 ST_GDALDrivers	634
11.2.9 ST_Contour	639
11.2.10 ST_InterpolateRaster	640
11.2.11 UpdateRasterSRID	640
11.2.12 ST_CreateOverview	641
11.3 地理函数 (constructor)	642
11.3.1 ST_AddBand	642
11.3.2 ST_AsRaster	644
11.3.3 ST_Band	646
11.3.4 ST_MakeEmptyCoverage	648
11.3.5 ST_MakeEmptyRaster	649
11.3.6 ST_Tile	650

11.3.7	ST_Retile	653
11.3.8	ST_FromGDALRaster	653
11.4	ST (accessor)	654
11.4.1	ST_GeoReference	654
11.4.2	ST_Height	655
11.4.3	ST_IsEmpty	656
11.4.4	ST_MemSize	656
11.4.5	ST_MetaData	657
11.4.6	ST_NumBands	658
11.4.7	ST_PixelHeight	658
11.4.8	ST_PixelWidth	659
11.4.9	ST_ScaleX	661
11.4.10	ST_ScaleY	661
11.4.11	ST_RasterToWorldCoord	662
11.4.12	ST_RasterToWorldCoordX	663
11.4.13	ST_RasterToWorldCoordY	664
11.4.14	ST_Rotation	665
11.4.15	ST_SkewX	665
11.4.16	ST_SkewY	666
11.4.17	ST_SRID	667
11.4.18	ST_Summary	667
11.4.19	ST_UpperLeftX	668
11.4.20	ST_UpperLeftY	669
11.4.21	ST_Width	669
11.4.22	ST_WorldToRasterCoord	670
11.4.23	ST_WorldToRasterCoordX	671
11.4.24	ST_WorldToRasterCoordY	671
11.5	ST (modifier)	672
11.5.1	ST_BandMetaData	672
11.5.2	ST_BandNoDataValue	674
11.5.3	ST_BandIsNoData	674
11.5.4	ST_BandPath	676
11.5.5	ST_BandFileSize	676
11.5.6	ST_BandFileTimestamp	677
11.5.7	ST_BandPixelType	677
11.5.8	ST_MinPossibleValue	678
11.5.9	ST_HasNoBand	679
11.6	ST (setter)	679
11.6.1	ST_PixelAsPolygon	679

11.6.2ST_PixelAsPolygons	680
11.6.3ST_PixelAsPoint	681
11.6.4ST_PixelAsPoints	682
11.6.5ST_PixelAsCentroid	683
11.6.6ST_PixelAsCentroids	683
11.6.7ST_Value	685
11.6.8ST_NearestValue	688
11.6.9ST_SetZ	689
11.6.10ST_SetM	690
11.6.11ST_Neighborhood	692
11.6.12ST_SetValue	694
11.6.13ST_SetValues	695
11.6.14ST_DumpValues	703
11.6.15ST_PixelOfValue	704
11.7索引	706
11.7.1ST_SetGeoReference	706
11.7.2ST_SetRotation	707
11.7.3ST_SetScale	708
11.7.4ST_SetSkew	709
11.7.5ST_SetSRID	710
11.7.6ST_SetUpperLeft	710
11.7.7ST_Resample	711
11.7.8ST_Rescale	712
11.7.9ST_Reskew	714
11.7.10ST_SnapToGrid	715
11.7.11ST_Resize	716
11.7.12ST_Transform	717
11.8索引	720
11.8.1ST_SetBandNoDataValue	720
11.8.2ST_SetBandIsNoData	721
11.8.3ST_SetBandPath	723
11.8.4ST_SetBandIndex	724
11.9索引	726
11.9.1ST_Count	726
11.9.2ST_CountAgg	726
11.9.3ST_Histogram	728
11.9.4ST_Quantile	729
11.9.5ST_SummaryStats	731
11.9.6ST_SummaryStatsAgg	733

11.9.7	ST_ValueCount	735
11.10	Raster Inputs	737
11.10.1	ST_RastFromWKB	737
11.10.2	ST_RastFromHexWKB	738
11.11	ST_AsBinary/ST_AsWKB	739
11.11.1	ST_AsHexWKB	739
11.11.2	ST_AsGDALRaster	740
11.11.3	ST_AsJPEG	741
11.11.4	ST_AsPNG	742
11.11.5	ST_AsTIFF	743
11.12	ST_Clip	744
11.12.1	ST_ColorMap	747
11.12.2	ST_Grayscale	751
11.12.3	ST_Intersection	752
11.12.4	ST_MapAlgebra (callback function version)	754
11.12.5	ST_MapAlgebra (expression version)	761
11.12.6	ST_MapAlgebraExpr	763
11.12.7	ST_MapAlgebraExpr	766
11.12.8	ST_MapAlgebraFct	770
11.12.9	ST_MapAlgebraFct	774
11.12.10	ST_MapAlgebraFctNgb	778
11.12.11	ST_Reclass	780
11.12.12	ST_Union	782
11.13	ST_Distinct4ma	783
11.13.1	ST_InvDistWeight4ma	784
11.13.2	ST_Max4ma	785
11.13.3	ST_Mean4ma	786
11.13.4	ST_Min4ma	788
11.13.5	ST_MinDist4ma	789
11.13.6	ST_Range4ma	789
11.13.7	ST_StdDev4ma	790
11.13.8	ST_Sum4ma	791
11.14	ST_Aspect	793
11.14.1	ST_HillShade	794
11.14.2	ST_Roughness	796

11.14.\$T_Slope	797
11.14.\$T_TPI	799
11.14.\$T_TRI	799
11.15.索引	800
11.15.Box3D	800
11.15.\$T_ConvexHull	800
11.15.\$T_DumpAsPolygons	801
11.15.\$T_Envelope	803
11.15.\$T_MinConvexHull	803
11.15.\$T_Polygon	804
11.16.索引	806
11.16.&&	806
11.16.&<	807
11.16.&>	807
11.16.#	808
11.16.@	809
11.16.=	809
11.16.7	810
11.17.索引	810
11.17.\$T_Contains	810
11.17.\$T_ContainsProperly	811
11.17.\$T_Covers	812
11.17.\$T_CoveredBy	813
11.17.\$T_Disjoint	814
11.17.\$T_Intersects	815
11.17.\$T_Overlaps	816
11.17.\$T_Touches	817
11.17.\$T_SameAlignment	818
11.17.\$T_NotSameAlignmentReason	819
11.17.\$T_Within	820
11.17.\$T_DWithin	821
11.17.\$T_DFullyWithin	822
11.18.快速提示	823
11.18.Out-DB Rasters	823
11.18.1.目录包含许多文件	823
11.18.1.最大打开文件数	823
11.18.1.2.系统上打开文件的最大数量	824
11.18.1.2.进程上打开文件的最大数量	824

12 PostGIS Extras	826
12.1 地理名称处理	826
12.1.1 地理名称处理	826
12.1.2 地理名称处理	827
12.1.2.1 stdaddr	827
12.1.3 地理名称处理	827
12.1.3.1 rules table	827
12.1.3.2 lex table	830
12.1.3.3 gaz table	831
12.1.4 地理名称处理	831
12.1.4.1 debug_standardize_address	831
12.1.4.2 parse_address	833
12.1.4.3 standardize_address	834
12.2 TIGER 地理名称处理	836
12.2.1 Drop_Indexes_Generate_Script	836
12.2.2 Drop_Nation_Tables_Generate_Script	837
12.2.3 Drop_State_Tables_Generate_Script	838
12.2.4 Geocode	838
12.2.5 Geocode_Intersection	841
12.2.6 Get_Geocode_Setting	842
12.2.7 Get_Tract	843
12.2.8 Install_Missing_Indexes	844
12.2.9 Loader_Generate_Census_Script	844
12.2.10 Loader_Generate_Script	846
12.2.11 Loader_Generate_Nation_Script	848
12.2.12 Missing_Indexes_Generate_Script	849
12.2.13 Normalize_Address	850
12.2.14 Page_Normalize_Address	851
12.2.15 pprint_Addy	853
12.2.16 Reverse_Geocode	854
12.2.17 Topology_Load_Tiger	856
12.2.18 Set_Geocode_Setting	858
13 PostGIS Special Functions Index	860
13.1 PostGIS Aggregate Functions	860
13.2 PostGIS Window Functions	861
13.3 PostGIS SQL-MM Compliant Functions	861
13.4 PostGIS Geography Support Functions	865
13.5 PostGIS Raster Support Functions	867

13.6 PostGIS Geometry / Geography / Raster Dump Functions	872
13.7 PostGIS Box Functions	873
13.8 PostGIS Functions that support 3D	874
13.9 PostGIS Curved Geometry Support Functions	880
13.10 PostGIS Polyhedral Surface Support Functions	883
13.11 PostGIS Function Support Matrix	886
13.12 New, Enhanced or changed PostGIS Functions	904
13.12.1 PostGIS Functions new or enhanced in 3.5	904
13.12.2 PostGIS Functions new or enhanced in 3.4	906
13.12.3 PostGIS Functions new or enhanced in 3.3	908
13.12.4 PostGIS Functions new or enhanced in 3.2	908
13.12.5 PostGIS Functions new or enhanced in 3.1	910
13.12.6 PostGIS Functions new or enhanced in 3.0	911
13.12.7 PostGIS Functions new or enhanced in 2.5	913
13.12.8 PostGIS Functions new or enhanced in 2.4	915
13.12.9 PostGIS Functions new or enhanced in 2.3	916
13.12.10 PostGIS Functions new or enhanced in 2.2	918
13.12.11 PostGIS Functions new or enhanced in 2.1	921
13.12.12 PostGIS Functions new or enhanced in 2.0	927
13.12.13 PostGIS Functions new or enhanced in 1.5	938
13.12.14 PostGIS Functions new or enhanced in 1.4	940
13.12.15 PostGIS Functions new or enhanced in 1.3	941
14 Reporting Problems	942
14.1 Reporting Software Bugs	942
14.2 Reporting Documentation Issues	942
A Appendix	944
A.1 PostGIS 3.5.7	944
A.1.1 Bug Fixes	944
A.2 PostGIS 3.5.6	944
A.2.1 Bug Fixes	944
A.3 PostGIS 3.5.5	945
A.3.1 Bug Fixes	945
A.4 PostGIS 3.5.4	945
A.4.1 Bug Fixes	945
A.5 PostGIS 3.5.3	946
A.5.1 Bug Fixes	946
A.6 PostGIS 3.5.2	947

A.6.1 Bug Fixes	947
A.7 PostGIS 3.5.1	947
A.7.1 Breaking Changes	947
A.7.2 Enhancements	947
A.7.3 Breaking Changes	948
A.8 PostGIS 3.5.0	948
A.8.1 Breaking Changes	948
A.8.2 Deprecated signatures	949
A.8.3 New features	949
A.8.4 Enhancements	949

Abstract

PostGIS 是 PostgreSQL 数据库的 GIS(地理信息系统) 扩展。PostGIS 使用 GiST 和 R-Tree 索引, GIS 数据存储在 PostgreSQL 数据库中。




PostGIS 3.5.7 版本发布。



PostGIS 是 PostgreSQL 数据库的 GIS(地理信息系统) 扩展。PostGIS 使用 GiST 和 R-Tree 索引, GIS 数据存储在 PostgreSQL 数据库中。
<https://postgis.net>

Chapter 1



PostGIS is a spatial extension for the PostgreSQL relational database that was created by Refractions Research Inc, as a spatial database technology research project. Refractions is a GIS and database consulting company in Victoria, British Columbia, Canada, specializing in data integration and custom software development.

PostGIS is now a project of the OSGeo Foundation and is developed and funded by many FOSS4G developers and organizations all over the world that gain great benefit from its functionality and versatility.

The PostGIS project development group plans on supporting and enhancing PostGIS to better support a range of important GIS functionality in the areas of OGC and SQL/MM spatial standards, advanced topological constructs (coverages, surfaces, networks), data source for desktop user interface tools for viewing and editing GIS data, and web-based access tools.

1.1 项目组织

PostGIS 项目组织 (Project Steering Committee; PSC) 由 PostGIS 项目发起人, 项目成员, 项目赞助商等组成。PSC 负责 PostGIS 项目的整体方向, 项目成员负责具体的开发工作, 项目赞助商提供资金支持。PSC 定期召开 API 会议, 讨论 PostGIS 项目的发展。

Raúl Marín Rodríguez MVT support, Bug fixing, Performance and stability improvements, GitHub curation, alignment of PostGIS with PostgreSQL releases

Regina Obe CI and website maintenance, Windows production and experimental builds, documentation, alignment of PostGIS with PostgreSQL releases, X3D support, TIGER geocoder support, management functions.

Darafei Praliaskouski Index improvements, bug fixing and geometry/geography function improvements, SFCGAL, raster, GitHub curation, and ci maintenance.

Paul Ramsey (项目发起人) Co-founder of PostGIS project. General bug fixing, geography support, geography and geometry index support (2D, 3D, nD index and anything spatial index), underlying geometry internal structures, GEOS functionality integration and alignment with GEOS releases, alignment of PostGIS with PostgreSQL releases, loader/dumper, and Shapefile GUI loader.

Sandro Santilli Bug fixes and maintenance, ci maintenance, git mirror management, management functions, integration of new GEOS functionality and alignment with GEOS releases, topology support, and raster framework and low level API functions.

1.2 致谢 - 2019

Nicklas Avén 3D 支持, TWKB(Tiny WKB) 支持 (支持), 支持

Loïc Bartoletti SFCGAL enhancements and maintenance and ci support

Dan Baston Geometry clustering function additions, other geometry algorithm enhancements, GEOS enhancements and general user support

Martin Davis GEOS enhancements and documentation

Björn Harrtell MapBox Vector Tile, GeoBuf, and Flatgeobuf functions. Gitea testing and GitLab experimentation.

Aliaksandr Kalenik Geometry Processing, PostgreSQL gist, general bug fixing

1.3 致谢 - 2020

Bborie Park Prior PSC Member. Raster development, integration with GDAL, raster loader, user support, general bug fixing, testing on various OS (Slackware, Mac, Windows, and more)

Mark Cave-Ayland Prior PSC Member. Coordinated bug fixing and maintenance effort, spatial index selectivity and binding, loader/dumper, and Shapefile GUI Loader, integration of new and new function enhancements.

Jorge Arévalo 支持, GDAL 支持, 支持

Olivier Courtin XML(KML, GML)/GeoJSON 支持, 3D 支持

Chris Hodgson 支持. 支持, 支持, OSGeo 支持

Mateusz Loskot PostGIS 支持 CMake 支持, 支持, 支持 API 支持

Kevin Neufeld 支持. 支持, 支持, PostGIS 支持, PostGIS 支持

Dave Blasby PostGIS 支持. 支持, 支持

Jeff Lounsbury shapefile 支持/支持. 支持 PostGIS 支持

Mark Leslie 支持. 支持, shapefile GUI 支持

Pierre Racine Architect of PostGIS raster implementation. Raster overall architecture, prototyping, programming support

David Zwarg 支持 (支持) 支持

1.4 致谢

	Alex Bodnaru	Gino Lucrezi	Matthias Bay
	Alex Mayrhofer	Greg Troxel	Maxime Guillaud
	Andrea Peri	Guillaume Lelarge	Maxime van Noppen
	Andreas Forø Tollefsen	Giuseppe Broccolo	Maxime Schoemans
	Andreas Neumann	Han Wang	Megan Ma
	Andrew Gierth	Hans Lemuet	Michael Fuhr
	Anne Ghisla	Haribabu Kommi	Mike Toews
	Antoine Bajolet	Havard Tveite	Nathan Wagner
	Arthur Lesuisse	IIDA Tetsushi	Nathaniel Clay
	Artur Zakirov	Ingvild Nystuen	Nikita Shulga
	Barbara Phillipot	Jackie Leng	Norman Vine
	Ben Jubb	James Addison	Patricia Tozer
	Bernhard Reiter	James Marca	Rafal Magda
	Björn Esser	Jan Katins	Ralph Mason
	Brian Hamlin	Jan Tojnar	Rémi Cura
	Bruce Rindahl	Jason Smith	Richard Greenwood
	Bruno Wolff III	Jeff Adams	Robert Coup
	Bryce L. Nordgren	Jelte Fennema	Roger Crew
	Carl Anderson	Jim Jones	Ron Mayer
	Charlie Savage	Joe Conway	Sam Peters
国际版	Chris Mayo	Jonne Savolainen	Sebastiaan Couwenberg
	Christian Schroeder	Jose Carlos Martinez Llari	Sergei Shoulbakov
	Christoph Berg	Jörg Habenicht	Sergey Fedoseev
	Christoph Moench-Tegeder	Julien Rouhaud	Shinichi Sugiyama
	Dane Springmeyer	Kashif Rasul	Shoaib Burq
	Dapeng Wang	Klaus Foerster	Silvio Grosso
	Daryl Herzmann	Kris Jurka	Stefan Corneliu Petrea
	Dave Fuhry	Laurențiu Nicola	Steffen Macke
	国际版 (David Zwarg)	Laurenz Albe	Stepan Kuzmin
	国际版 (David Zwarg)	Lars Roessiger	Stephen Frost
	国际版 (David Zwarg)	Leo Hsu	Steven Ottens
	Dian M Fay	Loic Dachary	Talha Rizwan
	Dmitry Vasilyev	Luca S. Percich	Teramoto Ikuhiro
	Eduin Carrillo	Lucas C. Villa Real	Tom Glancy
	Esteban Zimanyi	Maria Arias de Reyna	Tom van Tilburg
	Eugene Antimirov	Marc Ducobu	Victor Collod
	Even Rouault	Mark Sondheim	Vincent Bre
	Florian Weimer	Markus Schaber	Vincent Mora
	Frank Warmerdam	Markus Wanner	Vincent Picavet
	George Silva	Matt Amos	Volf Tomáš
	Gerald Fenoy	Matt Bretl	Zuo Chenwei

国际版 PostGIS 国际版, 国际版.

- [Aiven](#)
- [Arrival 3D](#)
- [Associazione Italiana per l'Informazione Geografica Libera \(GFOSS.it\)](#)
- [AusVet](#)
- [Avencia](#)
- [Azavea](#)
- [Boundless](#)

- Cadcorp
- Camptocamp
- Carto
- Crunchy Data
- City of Boston (DND)
- City of Helsinki
- Clever Elephant Solutions
- Cooperativa Alveo
- Deimos Space
- Faunalia
- Geographic Data BC
- HighGo
- Hunter Systems Group
- >The National Institute for Agricultural and Food Research and Technology (INIA-CSIC)
- ISciences, LLC
- Kontur
- Lidwala Consulting Engineers
- LISAssoft
- Logical Tracking & Tracing International AG
- Maponics
- Michigan Tech Research Institute
- Natural Resources Canada
- Norwegian Forest and Landscape Institute
- Norwegian Institute of Bioeconomy Research (NIBIO)
- OSGeo
- Oslandia
- Palantir Technologies
- Paragon Corporation
- R3 GIS
- Refractions Research
- Regione Toscana - SITA
- Safe Software
- Sirius Corporation plc
- Stadt Uster
- UC Davis Center for Vectorborne Diseases
- Université Laval
- U.S. Department of State (HIU)
- Zonar Systems

A 5x10 grid of small squares. The first row has 10 squares, all white. The second row has 10 squares, all white. The third row has 10 squares, all white. The fourth row has 10 squares, all white. The fifth row has 10 squares, all white.

The text "PostGIS" is written in pink at the end of the fourth row.

PostGIS 2.0.0 安装与配置。安装 **PledgBank** 安装与配置。

postgistopology - 10 安装与配置 2.0.0 安装与配置 toTopGeometry 安装与配置 250 安装与配置。

postgis64windows - 安装 20 安装与配置 64 安装与配置 PostGIS 安装与配置 100 安装与配置, 安装与配置。安装 PostgreSQL 安装与配置 PostGIS 2.0.1 64 安装与配置 安装与配置。

安装与配置 The **GEOS** geometry operations library

The **GDAL** Geospatial Data Abstraction Library used to power much of the raster functionality introduced in PostGIS 2. In kind, improvements needed in GDAL to support PostGIS are contributed back to the GDAL project.

The **PROJ** cartographic projection library

安装与配置, PostGIS 安装与配置 **PostgreSQL DBMS** - PostGIS 安装与配置 安装与配置 PostgreSQL 安装与配置, 安装与配置, GiST 安装与配置, 安装与配置 SQL 安装与配置 安装与配置。

Chapter 2

PostGIS 安装

本章介绍 PostGIS 的安装与使用。

2.1 安装

安装 PostGIS 的步骤如下：

```
tar -xvzf postgis-3.5.7.tar.gz
cd postgis-3.5.7
./configure
make
make install
```

PostGIS 安装后，PostGIS 安装目录下的 `postgis` 目录 (Section 3.3) 中的 `postgis` (Section 3.4) 文件。

2.2 编译与安装

Note

对于 OS 安装 PostgreSQL/PostGIS 的步骤。安装，安装 PostgreSQL/PostGIS 的步骤。



This section includes general compilation instructions, if you are compiling for Windows etc or another OS, you may find additional more detailed help at [PostGIS User contributed compile guides](#) and [PostGIS Dev Wiki](#).

Pre-Built Packages for various OS are listed in [PostGIS Pre-built Packages](#)

安装 Stackbuilder 的 [PostGIS Windows download site](#) 安装。1~2 安装 [very bleeding-edge windows experimental builds](#) 安装。安装 PostGIS 安装。

The PostGIS module is an extension to the PostgreSQL backend server. As such, PostGIS 3.5.7 *requires* full PostgreSQL server headers access in order to compile. It can be built against PostgreSQL versions 12 - 18. Earlier versions of PostgreSQL are *not* supported.

Refer to the PostgreSQL installation guides if you haven't already installed PostgreSQL. <https://www.postgresql.org/docs/12/installation.html>.

Note

[illegible]

```
LDFLAGS=-lstdc++ ./configure [YOUR OPTIONS HERE]
```

C++ (PostgreSQL)

PostGIS 是 PostgreSQL 数据库的扩展。它提供了对空间数据的存储、查询和索引的支持。PostGIS 是 PostgreSQL 数据库的扩展，它提供了对空间数据的存储、查询和索引的支持。

2.2.1 ☐ ☐ ☐ ☐

PostGIS  <https://download.osgeo.org/postgis/source/postgis-3.5.7.tar.gz>

```
wget https://download.osgeo.org/postgis/source/postgis-3.5.7.tar.gz
tar -xvzf postgis-3.5.7.tar.gz
cd postgis-3.5.7
```

```

postgis-3.5.7 (x)

```

```
git clone https://git.osgeo.org/gitea/postgis/postgis.git postgis
cd postgis
sh autogen.sh
```

```

XXXXXXXXXXXXXXXXX postgres-3.5.7 XXXXXXXXXXXXXXXXXXXX.

```

```
./configure
```

2.2.2 ☐ ☐ ☐ ☐ ☐ ☐

PostGIS ██.

☐ ☐ ☐ ☐

- PostgreSQL 12 - 18. A complete installation of PostgreSQL (including server headers) is required. PostgreSQL is available from <https://www.postgresql.org> .
- For a full PostgreSQL / PostGIS support matrix and PostGIS/GEOS support matrix refer to <https://trac.osgeo.org/postgis/wiki/UsersWikiPostgreSQLPostGIS>
- GNU C (gcc). PostGIS requires ANSI C compatible gcc .
 - GNU Make(gmake or make). GNU make or make . make -v . . make PostGIS Makefile .
 - Proj reprojection library. Proj 6.1 or above is required. The Proj library is used to provide coordinate reprojection support within PostGIS. Proj is available for download from <https://proj.org/> .
 - GEOS geometry library, version 3.8.0 or greater, but GEOS 3.12+ is required to take full advantage of all the new functions and features. GEOS is available for download from <https://libgeos.org> .

- LibXML2, version 2.5.x or higher. LibXML2 is currently used in some imports functions (ST_GeomFromGM and ST_GeomFromKML). LibXML2 is available for download from <https://gitlab.gnome.org/GNOME/libxml2/-/releases>.
- JSON-C 0.9 或更高版本。JSON-C 用于 ST_GeomFromGeoJson 和 GeoJSON 的导入。JSON-C 可在 <https://github.com/json-c/json-c/releases/> 下载。
- GDAL, version 3+ is preferred. This is required for raster support. <https://gdal.org/download.html>.
- 安装 PostgreSQL 数据库。PostgreSQL 数据库安装指南可在 <http://trac.osgeo.org/postgis/ticket/635> 找到。

安装依赖

- 第 2.1 节 安装依赖。安装依赖的包和版本要求如下。
- shapefile 到 shp2pgsql-gui 需要 GTK (GTK+2.0, 2.8+ 或更高)。 <http://www.gtk.org/>.
- SFCGAL, 1.4.1 或更高版本是必需的，1.5.0+ 是需要的，以便使用所有功能。SFCGAL 可以用于提供额外的 2D 和 3D 高级分析函数到 PostGIS 的 Chapter 8。并且允许使用 SFCGAL 而不是 GEOS 用于某些 2D 函数，由两个后端（如 ST_Intersection 或 ST_Area，例如）。PostgreSQL 配置变量 `postgis.backend` 允许用户控制他想使用哪个后端（如果 SFCGAL 已安装（GEOS 为默认）。注意：SFCGAL 1.2 需要至少 CGAL 4.3 和 Boost 1.54（cf: <https://sfcgal.org>）<https://gitlab.com/sfcgal/SFCGAL/>。
- 为了构建第 2.1 节，你还需要 PCRE <http://www.pcre.org>（通常已经安装在 Unix 系统上）。第 2.1 节将自动构建，如果它检测到 PCRE 库，或者你传递一个有效的 `--with-pcre-dir=/path/to/pcre` 在配置期间。
- 要启用 ST_AsMVT protobuf-c 库 1.1.0 或更高版本（用于使用）和 protoc-c 编译器（用于构建）是必需的。另外，pkg-config 是必需的，以验证 protobuf-c 的最小版本。参见 [protobuf-c](#)。默认情况下，Postgis 将使用 Wagy 来验证 MVT 多边形，这需要一个 C++11 编译器。它将与 PostgreSQL 安装使用相同的编译器。要禁用此并使用 GEOS 代替，请在配置步骤中使用 `--without-wagy`。
- CUnit(CUnit)。可在 <http://cunit.sourceforge.net/> 找到。
- DocBook(xsltproc) 可在 <http://www.docbook.org/> 找到。
- DBLatex(dblatex) 可在 <http://dblatex.sourceforge.net/> 找到。
- ImageMagick(convert) 可在 <http://www.imagemagick.org/> 找到。

2.2.3 编译

编译 PostGIS 需要安装 Makefile 和编译工具。安装 Makefile 和编译工具。

./configure

编译 PostGIS 需要安装 Makefile 和编译工具。安装 Makefile 和编译工具。 **./configure** 脚本将配置 PostGIS 的编译选项，并生成 Makefile。

编译 PostGIS 需要安装 Makefile 和编译工具。安装 Makefile 和编译工具。 **--help** 或 **--help=short** 显示帮助信息。

--with-library-minor-version Starting with PostGIS 3.0, the library files generated by default will no longer have the minor version as part of the file name. This means all PostGIS 3 libs will end in `postgis-3`. This was done to make `pg_upgrade` easier, with downside that you can only install one version PostGIS 3 series in your server. To get the old behavior of file including the minor version: e.g. `postgis-3.0` add this switch to your configure statement.

--prefix=PREFIX PostGIS 安装目录 SQL 安装目录。安装 PostgreSQL 安装目录。



Caution

安装 PostgreSQL 12 版本时，PostgreSQL 12 版本与 PostGIS 3.0 版本不兼容。请参考 <http://trac.osgeo.org/postgis/ticket/635> 了解详情。

--with-pgconfig=FILE PostgreSQL 安装目录 PostGIS 安装目录 PostgreSQL 安装目录 `pg_config` 文件路径。PostGIS 安装目录 PostgreSQL 安装目录 `--with-pgconfig=/path/to/pg_config` 安装。

--with-gdalconfig=FILE GDAL 安装目录，GDAL 安装目录 `gdal-config` 文件路径。PostGIS 安装目录 GDAL 安装目录 `--with-gdalconfig=/path/to/gdal-config` 安装。

--with-geosconfig=FILE GEOS 安装目录，GEOS 安装目录 `geos-config` 文件路径。PostGIS 安装目录 GEOS 安装目录 `--with-geosconfig=/path/to/geos-config` 安装。

--with-xml2config=FILE LibXML 是进行 GeomFromKML/GML 过程所需的库。它通常是在你安装了 libxml 的情况下找到的，但如果没有或你想使用特定版本，你需要指向 PostGIS 的一个特定 xml2 - config 配置文件以启用软件安装来定位 LibXML 安装目录。使用这个参数 (`--with-xml2config=/path/to/xml2-config`) 来手动指定一个 PostGIS 将针对其构建的 LibXML 安装。

--with-projdir=DIR Proj4 安装目录 PostGIS 安装目录 Proj4 安装目录 `--with-projdir=/path/to/projdir` 安装。

--with-libiconv=DIR iconv 安装目录

--with-jsondir=DIR JSON-C MIT 安装目录 JSON 安装目录，PostGIS 安装目录 ST_GeomFromJSON 安装目录。PostGIS 安装目录 JSON-C 安装目录 `--with-jsondir=/path/to/jsondir` 安装。

--with-pcredir=DIR PCRE BSD 安装目录，address_standardizer 安装目录。PostGIS 安装目录 PCRE 安装目录 `--with-pcredir=/path/to/pcredir` 安装。

--with-gui 安装 GUI 支持 (GTK+2.0 支持)。shp2pgsql-gui 安装。

--without-raster 不安装 raster 支持

--without-topology 禁用拓扑支持。没有对应的库，因为拓扑逻辑在 `postgis-3.5.7` 库中。

--with-gettext=no 安装 PostGIS 安装目录 gettext 安装目录，安装目录 gettext 安装目录。安装目录 <http://trac.osgeo.org/postgis/ticket/748> 安装。安装目录: gettext 安装目录。gettext 安装目录 GUI 安装目录。

--with-sfcgal=PATH 指定 PostGIS 的 sfcgal 库的路径。PATH 是 sfcgal-config 脚本的输出。

--without-phony-revision Disable updating postgis_revision.h to match current HEAD of the git repository.

Note

PostGIS 的 SVN 仓库，包含最新的源代码。



./autogen.sh

运行 **configure** 脚本，生成 PostGIS 的 Makefile。

运行 **tar** 命令，将 PostGIS 的源代码打包。运行 **configure** 脚本，生成 **./autogen.sh** 脚本。

2.2.4 安装

运行 Makefile 安装 PostGIS。

make

运行 `make` 命令，生成 PostGIS 的库和头文件。

As of PostGIS v1.4.0, all the functions have comments generated from the documentation. If you wish to install these comments into your spatial databases later, run the command which requires docbook. The `postgis_comments.sql` and other package comments files `raster_comments.sql`, `topology_comments.sql` are also packaged in the tar.gz distribution in the doc folder so no need to make comments if installing from the tar ball. Comments are also included as part of the CREATE EXTENSION install.

make comments

PostGIS 2.0 的文档。包含 PostGIS 的文档 (cheat sheet) html 文件。运行 `xsltproc` 命令，生成 `doc` 文件夹中的 `topology_cheatsheet.html`, `tiger_geocoder_cheatsheet.html`, `raster_cheatsheet.html`, `postgis_cheatsheet.html` 4 个 html 文件。

html 文件 pdf 文件 [PostGIS / PostgreSQL Study Guides](#) 文档。

make cheatsheets

2.2.5 PostGIS Extensions 安装

PostgreSQL 9.1 的 PostGIS 扩展安装。

运行 `make` 命令，生成 function descriptions 文件。docbook 文件，生成 PostGIS 的扩展安装脚本。

make comments

运行 `tar` 命令，将 PostGIS 的源代码打包。运行 `tar` 命令，生成 comments 文件。

运行 PostgreSQL 9.1 的 extensions 安装脚本。运行 `make` 命令，生成 extensions 文件。

```
cd extensions
cd postgis
make clean
```

```
make
export PGUSER=postgres #overwrite psql variables
make check #to test before install
make install
# to test extensions
make check RUNTESTFLAGS=-extension
```

**Note**

make check uses psql to run tests and as such can use psql environment variables. Common ones useful to override are PGUSER,PGPORT, and PGHOST. Refer to [psql environment variables](#)

extension 安装 OS 安装 PostGIS 安装。 PostGIS binaries 安装。

extension 安装 PostgreSQL 安装。 PostgreSQL / share / extension 安装 extensions 安装 PostGIS 安装。

- extension 安装 extension 安装。 postgis.control, postgis_topology.control.
- extension 安装 /sql 安装。 PostgreSQL 安装 share/extension 安装 extensions/postgis/sql/*.sql, extensions/postgis_topology/sql/*.sql

Once you do that, you should see postgis, postgis_topology as available extensions in PgAdmin -> extensions.

psql 安装。

```
SELECT name, default_version,installed_version
FROM pg_available_extensions WHERE name LIKE 'postgis%' or name LIKE 'address%';
```

name	default_version	installed_version
address_standardizer	3.5.7	3.5.7
address_standardizer_data_us	3.5.7	3.5.7
postgis	3.5.7	3.5.7
postgis_raster	3.5.7	3.5.7
postgis_sfcgal	3.5.7	
postgis_tiger_geocoder	3.5.7	3.5.7
postgis_topology	3.5.7	

(6 rows)

extension 安装, installed_version 安装。 postgis extension 安装。 PgAdmin III 1.14 安装 extensions 安装。

extension 安装 pgAdmin extension 安装 sql 安装 postgis extension 安装:

```
CREATE EXTENSION postgis;
CREATE EXTENSION postgis_raster;
CREATE EXTENSION postgis_sfcgal;
CREATE EXTENSION fuzzystmatch; --needed for postgis_tiger_geocoder
--optional used by postgis_tiger_geocoder, or can be used standalone
CREATE EXTENSION address_standardizer;
```

```
CREATE EXTENSION address_standardizer_data_us;
CREATE EXTENSION postgis_tiger_geocoder;
CREATE EXTENSION postgis_topology;
```

PSQL 安装完成后，您可以通过以下命令验证安装。

```
\connect mygisdb
\x
\dx postgis*
```

List of installed extensions

```
-[ RECORD 1 ]-----
Name          | postgis
Version       | 3.5.7
Schema        | public
Description    | PostGIS geometry, geography, and raster spat..
-[ RECORD 2 ]-----
Name          | postgis_raster
Version       | 3.0.0dev
Schema        | public
Description    | PostGIS raster types and functions
-[ RECORD 3 ]-----
Name          | postgis_tiger_geocoder
Version       | 3.5.7
Schema        | tiger
Description    | PostGIS tiger geocoder and reverse geocoder
-[ RECORD 4 ]-----
Name          | postgis_topology
Version       | 3.5.7
Schema        | topology
Description    | PostGIS topology spatial types and functions
```

Warning



spatial_ref_sys, layer, topology 等表在安装 PostGIS 3.5.7 时会被创建。PostGIS 3.5.7 的 postgis_topology 扩展依赖于 PostGIS 3.0.0dev 的 postgis_raster 扩展。PostGIS 3.0.0dev 的 postgis_raster 扩展依赖于 PostGIS 2.0.1 的 srid 表。PostGIS 2.0.1 的 srid 表依赖于 trac 表。extension 表在 CREATE EXTENSION 语句执行后会被创建。PostgreSQL 扩展 postgis_topology 依赖于 extension 表。

PostGIS 3.5.7 安装完成后，您可以通过以下命令验证安装：postgis_upgrade_22_minor.sql, raster_upgrade_22_minor.sql, topology_upgrade_22_minor.sql。

```
CREATE EXTENSION postgis FROM unpackaged;
CREATE EXTENSION postgis_raster FROM unpackaged;
CREATE EXTENSION postgis_topology FROM unpackaged;
CREATE EXTENSION postgis_tiger_geocoder FROM unpackaged;
```

2.2.6 验证

验证 PostGIS 安装是否成功，可以通过以下命令。

make check

PostgreSQL 安装完成后，您可以通过以下命令验证安装。

**Note**

PostgreSQL, GEOS, 以及 Proj4 安装路径, LD_LIBRARY_PATH 环境变量.

**Caution**

安装时, **make check** 需要设置 PATH 和 PGPORT 环境变量. PostgreSQL 安装时, 需要设置 **--with-pgconfig** 选项. 安装 PostgreSQL 时, 需要设置 PATH 环境变量.

If successful, make check will produce the output of almost 500 tests. The results will look similar to the following (numerous lines omitted below):

```
CUnit - A unit testing framework for C - Version 2.1-3
http://cunit.sourceforge.net/

.
.
.

Run Summary:   Type   Total    Ran  Passed  Failed  Inactive
               suites    44      44    n/a      0        0
               tests   300     300    300      0        0
               asserts 4215    4215   4215      0        n/a
Elapsed time = 0.229 seconds

.
.
.

Running tests

.
.
.

Run tests: 134
Failed: 0

-- if you build with SFCGAL

.
.
.

Running tests

.
.
.

Run tests: 13
Failed: 0

-- if you built with raster support

.
```

```

.
.
Run Summary:   Type  Total    Ran Passed Failed Inactive
               suites    12      12   n/a      0        0
               tests    65      65    65      0        0
               asserts 45896  45896 45896    0      n/a

.
.
.
Running tests

.
.
.
Run tests: 101
Failed: 0

-- topology regress

.
.
.
Running tests

.
.
.
Run tests: 51
Failed: 0

-- if you built --with-gui, you should see this too

    CUnit - A unit testing framework for C - Version 2.1-2
    http://cunit.sourceforge.net/

.
.
.
Run Summary:   Type  Total    Ran Passed Failed Inactive
               suites    2      2   n/a      0        0
               tests    4      4    4      0        0
               asserts    4      4    4      0      n/a

```

postgis_tiger_geocoder 与 address_standardizer 均需要 PostgreSQL 10.0 及以上 (installcheck) 才能通过。安装时请确保 PostgreSQL 10.0 及以上。安装: 安装 PostGIS 3.5.7 安装地址: <http://trac.osgeo.org/postgis/wiki/UsersV35>。

address_standardizer 安装:

```

cd extensions/address_standardizer
make install
make installcheck

```

安装完成:

```

===== dropping database "contrib_regression" =====
DROP DATABASE
===== creating database "contrib_regression" =====
CREATE DATABASE
ALTER DATABASE
===== running regression test queries =====
test test-init-extensions      ... ok
test test-parseaddress         ... ok
test test-standardize_address_1 ... ok
test test-standardize_address_2 ... ok

=====
All 4 tests passed.
=====

```

TIGER 数据加载器, 安装 PostgreSQL 的 PostGIS 扩展 `fuzzystrmatch`、`address_standardizer` 和 `address_standardizer`。

```

cd extensions/postgis_tiger_geocoder
make install
make installcheck

```

安装和测试:

```

===== dropping database "contrib_regression" =====
DROP DATABASE
===== creating database "contrib_regression" =====
CREATE DATABASE
ALTER DATABASE
===== installing fuzzystrmatch =====
CREATE EXTENSION
===== installing postgis =====
CREATE EXTENSION
===== installing postgis_tiger_geocoder =====
CREATE EXTENSION
===== installing address_standardizer =====
CREATE EXTENSION
===== running regression test queries =====
test test-normalize_address ... ok
test test-pagc_normalize_address ... ok

=====
All 2 tests passed.
=====

```

2.2.7 安装

PostGIS 安装和配置。

make install

安装 `--prefix` 选项指定 PostgreSQL 安装目录。

- `loader` (loader) 文件 [prefix]/bin 目录。
- `postgis.sql` SQL 脚本 [prefix]/share/contrib 目录。
- PostGIS 库文件 [prefix]/lib 目录。

运行 `postgis_comments.sql`, `raster_comments.sql` 和 `make comments` 脚本，安装完成后，运行 `sql` 脚本。

make comments-install



Note

xsltproc 是运行 `postgis_comments.sql`, `raster_comments.sql`, `topology_comments.sql` 脚本所必需的。

2.3 安装 Tiger Geocoder

`address_standardizer` 是 PostGIS 2.2 版本引入的。它依赖于 `libaddressstandardizer`。安装 `libaddressstandardizer` 的说明在 Section 12.1 中。

运行 **Normalize Address** 是 PostGIS 2.2 版本引入的 Tiger Geocoder (geocoder) 的扩展。它依赖于 `libaddressstandardizer`。Section 2.4.2 中介绍了它。它依赖于 `libaddressstandardizer` (building block) 的扩展，它依赖于 `libaddressstandardizer`。

运行 `PCRE` 是必需的。PCRE 是正则表达式引擎。PCRE 的官方网站是 <http://www.pcre.org>。Section 2.2.3 中介绍了 PCRE。运行 `PCRE` 时，使用 `--with-pcre-dir=/path/to/pcre` 指定 PCRE 的包含目录。运行 `PCRE` 时，使用 `--with-pcre-lib=/path/to/pcre` 指定 PCRE 的库文件。

运行 `PostGIS 2.1` 版本引入的 `address_standardizer` 扩展。运行 `CREATE EXTENSION address_standardizer`。

运行 `SQL` 脚本：

```
CREATE EXTENSION address_standardizer;
```

运行 `rules`, `gaz`, `lex` 脚本。

```
SELECT num, street, city, state, zip
FROM parse_address('1 Devonshire Place PH301, Boston, MA 02109');
```

运行 `SQL` 脚本：

num	street	city	state	zip
1	Devonshire Place PH301	Boston	MA	02109

2.4 Installing, Upgrading Tiger Geocoder, and loading data

Extras like Tiger geocoder may not be packaged in your PostGIS distribution. If you are missing the tiger geocoder extension or want a newer version than what your install comes with, then use the `share/extension/postgis_tiger_geocoder.*` files from the packages in **Windows Unreleased Versions** section for your version of PostgreSQL. Although these packages are for windows, the `postgis_tiger_geocoder` extension files will work on any OS since the extension is an SQL/plpgsql only extension.

2.4.1 Tiger Geocoder Enabling your PostGIS database

1. These directions assume your PostgreSQL installation already has the `postgis_tiger_geocoder` extension installed.
2. PSQL, pgAdmin 或者使用 `psql` 命令行工具。PostGIS 安装后，`postgis_tiger_geocoder` 扩展可能没有安装。使用 `fuzzystrmatch` 扩展。

```
CREATE EXTENSION postgis;
CREATE EXTENSION fuzzystrmatch;
CREATE EXTENSION postgis_tiger_geocoder;
--this one is optional if you want to use the rules based standardizer ( ←
    pagc_normalize_address)
CREATE EXTENSION address_standardizer;
```

使用 `postgis_tiger_geocoder` 扩展。

```
ALTER EXTENSION postgis UPDATE;
ALTER EXTENSION postgis_tiger_geocoder UPDATE;
```

`tiger.loader_platform` 表 `tiger.loader_variables` 表。

3. 使用 `SQL` 命令：

```
SELECT na.address, na.streetname, na.streotypeabbrev, na.zip
FROM normalize_address('1 Devonshire Place, Boston, MA 02109') AS na;
```

结果：

address	streetname	streotypeabbrev	zip
1 Devonshire Pl			02109

4. `tiger.loader_platform` 表。

使用 `sh` (convention) 或者 `debbie`。

```
INSERT INTO tiger.loader_platform(os, declare_sect, pgbin, wget, unzip_command, psql, ←
    path_sep,
                                loader, environ_set_command, county_process_command)
SELECT 'debbie', declare_sect, pgbin, wget, unzip_command, psql, path_sep,
    loader, environ_set_command, county_process_command
FROM tiger.loader_platform
WHERE os = 'sh';
```

使用 `debbie` 或者 `pg`, `unzip`, `shp2pgsql`, `PSQL` 或者 `declare_sect`。

使用 `loader_platform` 表，使用 `(common case)`。

5. As of PostGIS 2.4.1 the Zip code-5 digit tabulation area `zcta5` load step was revised to load current `zcta5` data and is part of the **Loader_Generate_Nation_Script** when enabled. It is turned off by default because it takes quite a bit of time to load (20 to 60 minutes), takes up quite a bit of disk space, and is not used that often.

To enable it, do the following:

```
UPDATE tiger.loader_lookuptables SET load = true WHERE table_name = 'zcta520';
```

If present the **Geocode** function can use it if a boundary filter is added to limit to just zips in that boundary. The **Reverse_Geocode** function uses it if the returned address is missing a zip, which often happens with highway reverse geocoding.

6. 在 Windows 上, 将 tiger_loader_variables 文件复制到 PC 上的 gisdata 目录中。在 Linux 上, 将 TIGER 数据复制到 /usr/share/postgresql/tiger_data 目录中。在 Mac 上, 将 tiger_loader_variables 文件复制到 staging_fold 目录中。

7. gisdata 目录中的 staging_fold 目录中的 temp 目录中的 tiger_loader_variables 文件复制到 temp 目录中。

8. Then run the **Loader_Generate_Nation_Script** SQL function make sure to use the name of your custom profile and copy the script to a .sh or .bat file. So for example to build the nation load:

```
psql -c "SELECT Loader_Generate_Nation_Script('debbie')" -d geocoder -tA > /gisdata/nation_script_load.sh
```

9. Run the generated nation load commandline scripts.

```
cd /gisdata
sh nation_script_load.sh
```

10. After you are done running the nation script, you should have three tables in your tiger_data schema and they should be filled with data. Confirm you do by doing the following queries from psql or pgAdmin

```
SELECT count(*) FROM tiger_data.county_all;
```

```
count
-----
    3235
(1 row)
```

```
SELECT count(*) FROM tiger_data.state_all;
```

```
count
-----
     56
(1 row)
```

This will only have data if you marked zcta5 to be loaded

```
SELECT count(*) FROM tiger_data.zcta5_all;
```

```
count
-----
   33933
(1 row)
```

11. By default the tables corresponding to bg, tract, tabblock20 are not loaded. These tables are not used by the geocoder but are used by folks for population statistics. If you wish to load them as part of your state loads, run the following statement to enable them.

```
UPDATE tiger.loader_lookuptables SET load = true WHERE load = false AND lookup_name IN ('tract', 'bg', 'tabblock20');
```

Alternatively you can load just these tables after loading state data using the **Loader_Generate_Census**

12. For each state you want to load data for, generate a state script **Loader_Generate_Script**.

**Warning**

DO NOT Generate the state script until you have already loaded the nation data, because the state script utilizes county list loaded by nation script.

13.

```
psql -c "SELECT Loader_Generate_Script(ARRAY['MA'], 'debbie')" -d geocoder -tA > /  
gisdata/ma_load.sh
```

14. 安装 Tiger 数据。

```
cd /gisdata  
sh ma_load.sh
```

15. 安装 Tiger 数据 (stat) 索引。

```
SELECT install_missing_indexes();  
vacuum (analyze, verbose) tiger.addr;  
vacuum (analyze, verbose) tiger.edges;  
vacuum (analyze, verbose) tiger.faces;  
vacuum (analyze, verbose) tiger.featnames;  
vacuum (analyze, verbose) tiger.place;  
vacuum (analyze, verbose) tiger.cousub;  
vacuum (analyze, verbose) tiger.county;  
vacuum (analyze, verbose) tiger.state;  
vacuum (analyze, verbose) tiger.zcta5;  
vacuum (analyze, verbose) tiger.zip_lookup_base;  
vacuum (analyze, verbose) tiger.zip_state;  
vacuum (analyze, verbose) tiger.zip_state_loc;
```

2.4.2 安装 Tiger 数据

安装 Tiger 数据时，需要安装 **Normalize Address** 工具。该工具用于将地址标准化。该工具位于 **address_standardizer** 包中，Section 2.3 介绍了该工具的使用。

postgis_tiger_geocoder 工具用于安装 Tiger 数据。该工具位于 **Normalize Address** 包中。该工具将 Tiger 数据加载到数据库中，并创建 **rules table** (tiger.pagc_rules), **gaz table** (tiger.pagc_gaz), 和 **lex table** (tiger.pagc_lex) 索引。

2.4.3 Required tools for tiger data loading

安装 Tiger 数据时，需要安装 **Drop_State_Tables_Generate_Script** 工具。

安装 Tiger 数据时，需要安装以下工具：

- **unzip** 工具。
Unix 系统上，使用 **unzip** 工具。
Windows 系统，使用 **7-zip** 工具 <http://www.7-zip.org/>。

- PostGIS 安装 shp2pgsql 工具
- 使用 `wget` 在 Unix/Linux 系统上下载。

安装 `wget` <http://gnuwin32.sourceforge.net/packages/wget.htm>

If you are upgrading from tiger_2010, you'll need to first generate and run `Drop_Nation_Tables_Generate_Script`. Before you load any state data, you need to load the nation wide data which you do with `Loader_Generate_Nation_Script`. Which will generate a loader script for you. `Loader_Generate_Nation_Script` is a one-time step that should be done for upgrading (from a prior year tiger census data) and for new installs.

安装 `Loader_Generate_Nation_Script` 脚本。该脚本将生成一个 loader 脚本。该脚本将生成一个 loader 脚本。该脚本将生成一个 loader 脚本。

安装 `Install_Missing_Indexes` 脚本：

```
SELECT install_missing_indexes();
```

安装 `Geocode` 脚本。

2.4.4 Upgrading your Tiger Geocoder Install and Data

First upgrade your `postgis_tiger_geocoder` extension as follows:

```
ALTER EXTENSION postgis_tiger_geocoder UPDATE;
```

安装 `nation` 表并 drop 旧表。SQL 脚本 `Drop_Nation_Tables_Generate_Script` 将生成一个 loader 脚本。

```
SELECT drop_nation_tables_generate_script();
```

drop SQL 脚本。

安装 `Loader_Generate_Nation_Script` 脚本。该脚本将生成一个 loader 脚本。该脚本将生成一个 loader 脚本。

```
SELECT loader_generate_nation_script('windows');
```

unix/linux

```
SELECT loader_generate_nation_script('sh');
```

Refer to Section 2.4.1 for instructions on how to run the generate script. This only needs to be done once.



Note

You can have a mix of different year state tables and can upgrade each state separately. Before you upgrade a state you first need to drop the prior year state tables for that state using `Drop_State_Tables_Generate_Script`.

2.5 安装与升级

安装与升级

- [illegible]

```
SELECT version();
```

```
RPM ██████████ rpm ████████████████████████████████: rpm -qa | grep postgresql
```

2. PostgreSQL.

```
SELECT postgis_full_version();
```

PostgreSQL, Proj4 GEOS

1. `pg_config.h` `PGSQL_VERSION`, `PGSQL_VERSION` and `PGSQL_VERSION`.

Chapter 3

PostGIS Administration

3.1 Performance Tuning

Tuning for PostGIS performance is much like tuning for any PostgreSQL workload. The only additional consideration is that geometries and rasters are usually large, so memory-related optimizations generally have more of an impact on PostGIS than other types of PostgreSQL queries.

For general details about optimizing PostgreSQL, refer to [Tuning your PostgreSQL Server](#).

For PostgreSQL 9.4+ configuration can be set at the server level without touching `postgresql.conf` or `postgresql.auto.conf` by using the `ALTER SYSTEM` command.

```
ALTER SYSTEM SET work_mem = '256MB';
-- this forces non-startup configs to take effect for new connections
SELECT pg_reload_conf();
-- show current setting value
-- use SHOW ALL to see all settings
SHOW work_mem;
```

In addition to the Postgres settings, PostGIS has some custom settings which are listed in [Section 7.22](#).

3.1.1 Startup

These settings are configured in `postgresql.conf`:

`constraint_exclusion`

- Default: partition
- This is generally used for table partitioning. The default for this is set to "partition" which is ideal for PostgreSQL 8.4 and above since it will force the planner to only analyze tables for constraint consideration if they are in an inherited hierarchy and not pay the planner penalty otherwise.

`shared_buffers`

- Default: ~128MB in PostgreSQL 9.6
- Set to about 25% to 40% of available RAM. On windows you may not be able to set as high.

`max_worker_processes` This setting is only available for PostgreSQL 9.4+. For PostgreSQL 9.6+ this setting has additional importance in that it controls the max number of processes you can have for parallel queries.

- Default: 8
- Sets the maximum number of background processes that the system can support. This parameter can only be set at server start.

3.1.2 Runtime

work_mem - sets the size of memory used for sort operations and complex queries

- Default: 1-4MB
- Adjust up for large dbs, complex queries, lots of RAM
- Adjust down for many concurrent users or low RAM.
- If you have lots of RAM and few developers:

```
SET work_mem TO '256MB';
```

maintenance_work_mem - the memory size used for VACUUM, CREATE INDEX, etc.

- Default: 16-64MB
- Generally too low - ties up I/O, locks objects while swapping memory
- Recommend 32MB to 1GB on production servers w/lots of RAM, but depends on the # of concurrent users. If you have lots of RAM and few developers:

```
SET maintenance_work_mem TO '1GB';
```

max_parallel_workers_per_gather

This setting is only available for PostgreSQL 9.6+ and will only affect PostGIS 2.3+, since only PostGIS 2.3+ supports parallel queries. If set to higher than 0, then some queries such as those involving relation functions like `ST_Intersects` can use multiple processes and can run more than twice as fast when doing so. If you have a lot of processors to spare, you should change the value of this to as many processors as you have. Also make sure to bump up `max_worker_processes` to at least as high as this number.

- Default: 0
- Sets the maximum number of workers that can be started by a single Gather node. Parallel workers are taken from the pool of processes established by `max_worker_processes`. Note that the requested number of workers may not actually be available at run time. If this occurs, the plan will run with fewer workers than expected, which may be inefficient. Setting this value to 0, which is the default, disables parallel query execution.

3.2 Configuring raster support

If you enabled raster support you may want to read below how to properly configure it.

As of PostGIS 2.1.3, out-of-db rasters and all raster drivers are disabled by default. In order to re-enable these, you need to set the following environment variables `POSTGIS_GDAL_ENABLED_DRIVERS` and `POSTGIS_ENABLE_OUTDB_RASTERS` in the server environment. For PostGIS 2.2, you can use the more cross-platform approach of setting the corresponding Section [7.22](#).

If you want to enable offline raster:

```
POSTGIS_ENABLE_OUTDB_RASTERS=1
```

Any other setting or no setting at all will disable out of db rasters.

In order to enable all GDAL drivers available in your GDAL install, set this environment variable as follows

```
POSTGIS_GDAL_ENABLED_DRIVERS=ENABLE_ALL
```

If you want to only enable specific drivers, set your environment variable as follows:

```
POSTGIS_GDAL_ENABLED_DRIVERS="GTiff PNG JPEG GIF XYZ"
```

**Note**

If you are on windows, do not quote the driver list

Setting environment variables varies depending on OS. For PostgreSQL installed on Ubuntu or Debian via apt-postgresql, the preferred way is to edit `/etc/postgresql/10/main/environment` where 10 refers to version of PostgreSQL and main refers to the cluster.

On windows, if you are running as a service, you can set via System variables which for Windows 7 you can get to by right-clicking on Computer->Properties Advanced System Settings or in explorer navigating to Control Panel\All Control Panel Items\System. Then clicking *Advanced System Settings* ->*Advanced*->*Environment Variables* and adding new system variables.

After you set the environment variables, you'll need to restart your PostgreSQL service for the changes to take effect.

3.3 Creating spatial databases

3.3.1 Spatially enable database using EXTENSION

If you are using PostgreSQL 9.1+ and have compiled and installed the extensions/postgis modules, you can turn a database into a spatial one using the EXTENSION mechanism.

Core postgis extension includes geometry, geography, spatial_ref_sys and all the functions and comments. Raster and topology are packaged as a separate extension.

Run the following SQL snippet in the database you want to enable spatially:

```
CREATE EXTENSION IF NOT EXISTS plpgsql;
CREATE EXTENSION postgis;
CREATE EXTENSION postgis_raster; -- OPTIONAL
CREATE EXTENSION postgis_topology; -- OPTIONAL
```

3.3.2 Spatially enable database without using EXTENSION (discouraged)

**Note**

This is generally only needed if you cannot or don't want to get PostGIS installed in the PostgreSQL extension directory (for example during testing, development or in a restricted environment).

Adding PostGIS objects and function definitions into your database is done by loading the various sql files located in [prefix]/share/contrib as specified during the build phase.

The core PostGIS objects (geometry and geography types, and their support functions) are in the `postgis.sql` script. Raster objects are in the `rtpostgis.sql` script. Topology objects are in the `topology.sql` script.

For a complete set of EPSG coordinate system definition identifiers, you can also load the `spatial_ref_sys.sql` definitions file and populate the `spatial_ref_sys` table. This will permit you to perform `ST_Transform()` operations on geometries.

If you wish to add comments to the PostGIS functions, you can find them in the `postgis_comments.sql` script. Comments can be viewed by simply typing `\dd [function_name]` from a **psql** terminal window.

Run the following Shell commands in your terminal:

```
DB=[yourdatabase]
SCRIPTSDIR=`pg_config --sharedir`/contrib/postgis-3.4/

# Core objects
psql -d ${DB} -f ${SCRIPTSDIR}/postgis.sql
psql -d ${DB} -f ${SCRIPTSDIR}/spatial_ref_sys.sql
psql -d ${DB} -f ${SCRIPTSDIR}/postgis_comments.sql # OPTIONAL

# Raster support (OPTIONAL)
psql -d ${DB} -f ${SCRIPTSDIR}/rtpostgis.sql
psql -d ${DB} -f ${SCRIPTSDIR}/raster_comments.sql # OPTIONAL

# Topology support (OPTIONAL)
psql -d ${DB} -f ${SCRIPTSDIR}/topology.sql
psql -d ${DB} -f ${SCRIPTSDIR}/topology_comments.sql # OPTIONAL
```

3.4 Upgrading spatial databases

Upgrading existing spatial databases can be tricky as it requires replacement or introduction of new PostGIS object definitions.

Unfortunately not all definitions can be easily replaced in a live database, so sometimes your best bet is a dump/reload process.

PostGIS provides a SOFT UPGRADE procedure for minor or bugfix releases, and a HARD UPGRADE procedure for major releases.

Before attempting to upgrade PostGIS, it is always worth to backup your data. If you use the `-Fc` flag to `pg_dump` you will always be able to restore the dump with a HARD UPGRADE.

3.4.1 Soft upgrade

If you installed your database using extensions, you'll need to upgrade using the extension model as well. If you installed using the old sql script way, you are advised to switch your install to extensions because the script way is no longer supported.

3.4.1.1 Soft Upgrade 9.1+ using extensions

If you originally installed PostGIS with extensions, then you need to upgrade using extensions as well. Doing a minor upgrade with extensions, is fairly painless.

If you are running PostGIS 3 or above, then you should use the `PostGIS_Extensions_Upgrade` function to upgrade to the latest version you have installed.


```
SELECT postgis_extensions_upgrade();
```

If you are running PostGIS 2.5 or lower, then do the following:

```
ALTER EXTENSION postgis UPDATE;
SELECT postgis_extensions_upgrade();
-- This second call is needed to rebundle postgis_raster extension
SELECT postgis_extensions_upgrade();
```

If you have multiple versions of PostGIS installed, and you don't want to upgrade to the latest, you can explicitly specify the version as follows:

```
ALTER EXTENSION postgis UPDATE TO "3.5.7";
ALTER EXTENSION postgis_topology UPDATE TO "3.5.7";
```

If you get an error notice something like:

```
No migration path defined for b'...'b' to 3.5.7
```

Then you'll need to backup your database, create a fresh one as described in Section 3.3.1 and then restore your backup on top of this new database.

If you get a notice message like:

```
Version "3.5.7" of extension "postgis" is already installed
```

Then everything is already up to date and you can safely ignore it. **UNLESS** you're attempting to upgrade from an development version to the next (which doesn't get a new version number); in that case you can append "next" to the version string, and next time you'll need to drop the "next" suffix again:

```
ALTER EXTENSION postgis UPDATE TO "3.5.7next";
ALTER EXTENSION postgis_topology UPDATE TO "3.5.7next";
```



Note

If you installed PostGIS originally without a version specified, you can often skip the reinstallation of postgis extension before restoring since the backup just has CREATE EXTENSION postgis and thus picks up the newest latest version during restore.



Note

If you are upgrading PostGIS extension from a version prior to 3.0.0, you will have a new extension *postgis_raster* which you can safely drop, if you don't need raster support. You can drop as follows:

```
DROP EXTENSION postgis_raster;
```

3.4.1.2 Soft Upgrade Pre 9.1+ or without extensions

This section applies only to those who installed PostGIS not using extensions. If you have extensions and try to upgrade with this approach you'll get messages like:

```
can't drop b'...'b' because postgis extension depends on it
```

NOTE: if you are moving from PostGIS 1.* to PostGIS 2.* or from PostGIS 2.* prior to r7409, you cannot use this procedure but would rather need to do a **HARD UPGRADE**.

After compiling and installing (make install) you should find a set of *_upgrade.sql files in the installation folders. You can list them all with:

```
ls `pg_config --sharedir`/contrib/postgis-3.5.7/*_upgrade.sql
```

Load them all in turn, starting from postgis_upgrade.sql.

```
psql -f postgis_upgrade.sql -d your_spatial_database
```

The same procedure applies to raster, topology and sfcgal extensions, with upgrade files named rtpostgis_upgrade.sql, topology_upgrade.sql and sfcgal_upgrade.sql respectively. If you need them:

```
psql -f rtpostgis_upgrade.sql -d your_spatial_database
```

```
psql -f topology_upgrade.sql -d your_spatial_database
```

```
psql -f sfcgal_upgrade.sql -d your_spatial_database
```

You are advised to switch to an extension based install by running

```
psql -c "SELECT postgis_extensions_upgrade();" 
```

**Note**

If you can't find the postgis_upgrade.sql specific for upgrading your version you are using a version too early for a soft upgrade and need to do a **HARD UPGRADE**.

The **PostGIS_Full_Version** function should inform you about the need to run this kind of upgrade using a "procs need upgrade" message.

3.4.2 Hard upgrade

By HARD UPGRADE we mean full dump/reload of postgis-enabled databases. You need a HARD UPGRADE when PostGIS objects' internal storage changes or when SOFT UPGRADE is not possible. The **Release Notes** appendix reports for each version whether you need a dump/reload (HARD UPGRADE) to upgrade.

The dump/reload process is assisted by the postgis_restore script which takes care of skipping from the dump all definitions which belong to PostGIS (including old ones), allowing you to restore your schemas and data into a database with PostGIS installed without getting duplicate symbol errors or bringing forward deprecated objects.

Supplementary instructions for windows users are available at **Windows Hard upgrade**.

The Procedure is as follows:

1. Create a "custom-format" dump of the database you want to upgrade (let's call it olddb) include binary blobs (-b) and verbose (-v) output. The user can be the owner of the db, need not be postgres super account.

```
pg_dump -h localhost -p 5432 -U postgres -Fc -b -v -f "/somepath/olddb.backup" olddb
```

2. Do a fresh install of PostGIS in a new database -- we'll refer to this database as newdb. Please refer to Section 3.3.2 and Section 3.3.1 for instructions on how to do this.

The spatial_ref_sys entries found in your dump will be restored, but they will not override existing ones in spatial_ref_sys. This is to ensure that fixes in the official set will be properly propagated to restored databases. If for any reason you really want your own overrides of standard entries just don't load the spatial_ref_sys.sql file when creating the new db.

If your database is really old or you know you've been using long deprecated functions in your views and functions, you might need to load legacy.sql for all your functions and views etc. to properly come back. Only do this if really needed. Consider upgrading your views and functions before dumping instead, if possible. The deprecated functions can be later removed by loading uninstall_legacy.sql.

3. Restore your backup into your fresh newdb database using postgis_restore. Unexpected errors, if any, will be printed to the standard error stream by psql. Keep a log of those.

```
postgis_restore "/somepath/olddb.backup" | psql -h localhost -p 5432 -U postgres newdb ↵
2> errors.txt
```

Errors may arise in the following cases:

1. Some of your views or functions make use of deprecated PostGIS objects. In order to fix this you may try loading legacy.sql script prior to restore or you'll have to restore to a version of PostGIS which still contains those objects and try a migration again after porting your code. If the legacy.sql way works for you, don't forget to fix your code to stop using deprecated functions and drop them loading uninstall_legacy.sql.
2. Some custom records of spatial_ref_sys in dump file have an invalid SRID value. Valid SRID values are bigger than 0 and smaller than 999000. Values in the 999000.999999 range are reserved for internal use while values > 999999 can't be used at all. All your custom records with invalid SRIDs will be retained, with those > 999999 moved into the reserved range, but the spatial_ref_sys table would lose a check constraint guarding for that invariant to hold and possibly also its primary key (when multiple invalid SRIDS get converted to the same reserved SRID value).

In order to fix this you should copy your custom SRS to a SRID with a valid value (maybe in the 910000..910999 range), convert all your tables to the new srid (see [UpdateGeometrySRID](#)), delete the invalid entry from spatial_ref_sys and re-construct the check(s) with:

```
ALTER TABLE spatial_ref_sys ADD CONSTRAINT spatial_ref_sys_srid_check check (srid
> 0 AND srid < 999000 );
```

```
ALTER TABLE spatial_ref_sys ADD PRIMARY KEY(srid));
```

If you are upgrading an old database containing french **IGN** cartography, you will have probably SRIDs out of range and you will see, when importing your database, issues like this :

```
WARNING: SRID 310642222 converted to 999175 (in reserved zone)
```

In this case, you can try following steps : first throw out completely the IGN from the sql which is resulting from postgis_restore. So, after having run :

```
postgis_restore "/somepath/olddb.backup" > olddb.sql
```

run this command :

```
grep -v IGNF olddb.sql > olddb-without-IGN.sql
```

Create then your newdb, activate the required Postgis extensions, and insert properly the french system IGN with : [this script](#) After these operations, import your data :

```
psql -h localhost -p 5432 -U postgres -d newdb -f olddb-without-IGN.sql 2> errors.txt
```

Chapter 4

Data Management

4.1 GIS (地理信息系统)

4.1.1 OGC Geometry

The Open Geospatial Consortium (OGC) developed the *Simple Features Access* standard (SFA) to provide a model for geospatial data. It defines the fundamental spatial type of **Geometry**, along with operations which manipulate and transform geometry values to perform spatial analysis tasks. PostGIS implements the OGC Geometry model as the PostgreSQL data types **geometry** and **geography**.

Geometry is an *abstract* type. Geometry values belong to one of its *concrete* subtypes which represent various kinds and dimensions of geometric shapes. These include the **atomic** types **Point**, **LineString**, **LinearRing** and **Polygon**, and the **collection** types **MultiPoint**, **MultiLineString**, **MultiPolygon** and **GeometryCollection**. The *Simple Features Access - Part 1: Common architecture v1.2.1* adds subtypes for the structures **PolyhedralSurface**, **Triangle** and **TIN**.

Geometry models shapes in the 2-dimensional Cartesian plane. The PolyhedralSurface, Triangle, and TIN types can also represent shapes in 3-dimensional space. The size and location of shapes are specified by their **coordinates**. Each coordinate has a X and Y **ordinate** value determining its location in the plane. Shapes are constructed from points or line segments, with points specified by a single coordinate, and line segments by two coordinates.

Coordinates may contain optional Z and M ordinate values. The Z ordinate is often used to represent elevation. The M ordinate contains a measure value, which may represent time or distance. If Z or M values are present in a geometry value, they must be defined for each point in the geometry. If a geometry has Z or M ordinates the **coordinate dimension** is 3D; if it has both Z and M the coordinate dimension is 4D.

Geometry values are associated with a **spatial reference system** indicating the coordinate system in which it is embedded. The spatial reference system is identified by the geometry SRID number. The units of the X and Y axes are determined by the spatial reference system. In **planar** reference systems the X and Y coordinates typically represent easting and northing, while in **geodetic** systems they represent longitude and latitude. SRID 0 represents an infinite Cartesian plane with no units assigned to its axes. See Section 4.5.

The geometry **dimension** is a property of geometry types. Point types have dimension 0, linear types have dimension 1, and polygonal types have dimension 2. Collections have the dimension of the maximum element dimension.

A geometry value may be **empty**. Empty values contain no vertices (for atomic geometry types) or no elements (for collections).

An important property of geometry values is their spatial **extent** or **bounding box**, which the OGC model calls **envelope**. This is the 2 or 3-dimensional box which encloses the coordinates of a geometry.

It is an efficient way to represent a geometry's extent in coordinate space and to check whether two geometries interact.

The geometry model allows evaluating topological spatial relationships as described in Section 5.1.1. To support this the concepts of **interior**, **boundary** and **exterior** are defined for each geometry type. Geometries are topologically closed, so they always contain their boundary. The boundary is a geometry of dimension one less than that of the geometry itself.

The OGC geometry model defines validity rules for each geometry type. These rules ensure that geometry values represents realistic situations (e.g. it is possible to specify a polygon with a hole lying outside the shell, but this makes no sense geometrically and is thus invalid). PostGIS also allows storing and manipulating invalid geometry values. This allows detecting and fixing them if needed. See Section 4.4

4.1.1.1 Point

A Point is a 0-dimensional geometry that represents a single location in coordinate space.

```
POINT (1 2)
POINT Z (1 2 3)
POINT ZM (1 2 3 4)
```

4.1.1.2 LineString

A LineString is a 1-dimensional line formed by a contiguous sequence of line segments. Each line segment is defined by two points, with the end point of one segment forming the start point of the next segment. An OGC-valid LineString has either zero or two or more points, but PostGIS also allows single-point LineStrings. LineStrings may cross themselves (self-intersect). A LineString is **closed** if the start and end points are the same. A LineString is **simple** if it does not self-intersect.

```
LINESTRING (1 2, 3 4, 5 6)
```

4.1.1.3 LinearRing

A LinearRing is a LineString which is both closed and simple. The first and last points must be equal, and the line must not self-intersect.

```
LINEARRING (0 0 0, 4 0 0, 4 4 0, 0 4 0, 0 0 0)
```

4.1.1.4 Polygon

A Polygon is a 2-dimensional planar region, delimited by an exterior boundary (the shell) and zero or more interior boundaries (holes). Each boundary is a **LinearRing**.

```
POLYGON ((0 0 0,4 0 0,4 4 0,0 4 0,0 0 0),(1 1 0,2 1 0,2 2 0,1 2 0,1 1 0))
```

4.1.1.5 MultiPoint

A MultiPoint is a collection of Points.

```
MULTIPOINT ( (0 0), (1 2) )
```

4.1.1.6 MultiLineString

A MultiLineString is a collection of LineStrings. A MultiLineString is closed if each of its elements is closed.

```
MULTILINESTRING ( (0 0,1 1,1 2), (2 3,3 2,5 4) )
```

4.1.1.7 MultiPolygon

A MultiPolygon is a collection of non-overlapping, non-adjacent Polygons. Polygons in the collection may touch only at a finite number of points.

```
MULTIPOLYGON (((1 5, 5 5, 5 1, 1 1, 1 5)), ((6 5, 9 1, 6 1, 6 5)))
```

4.1.1.8 GeometryCollection

A GeometryCollection is a heterogeneous (mixed) collection of geometries.

```
GEOMETRYCOLLECTION ( POINT(2 3), LINESTRING(2 3, 3 4))
```

4.1.1.9 PolyhedralSurface

A PolyhedralSurface is a contiguous collection of patches or facets which share some edges. Each patch is a planar Polygon. If the Polygon coordinates have Z ordinates then the surface is 3-dimensional.

```
POLYHEDRALSURFACE Z (
  ((0 0 0, 0 0 1, 0 1 1, 0 1 0, 0 0 0)),
  ((0 0 0, 0 1 0, 1 1 0, 1 0 0, 0 0 0)),
  ((0 0 0, 1 0 0, 1 0 1, 0 0 1, 0 0 0)),
  ((1 1 0, 1 1 1, 1 0 1, 1 0 0, 1 1 0)),
  ((0 1 0, 0 1 1, 1 1 1, 1 1 0, 0 1 0)),
  ((0 0 1, 1 0 1, 1 1 1, 0 1 1, 0 0 1)) )
```

4.1.1.10 Triangle

A Triangle is a polygon defined by three distinct non-collinear vertices. Because a Triangle is a polygon it is specified by four coordinates, with the first and fourth being equal.

```
TRIANGLE ((0 0, 0 9, 9 0, 0 0))
```

4.1.1.11 TIN

A TIN is a collection of non-overlapping **Triangles** representing a **Triangulated Irregular Network**.

```
TIN Z ( ((0 0 0, 0 0 1, 0 1 0, 0 0 0)), ((0 0 0, 0 1 0, 1 1 0, 0 0 0)) )
```

4.1.2 SQL-MM Part 3

The *ISO/IEC 13249-3 SQL Multimedia - Spatial* standard (SQL/MM) extends the OGC SFA to define Geometry subtypes containing curves with circular arcs. The SQL/MM types support 3DM, 3DZ and 4D coordinates.



Note

SQL-MM 对浮点精度有严格要求。精度为 1E-8 或更高。

4.1.2.1 CircularString

CIRCULARSTRING 是 LINESTRING 的子类型。它由一个或多个圆弧组成，每个圆弧由三个点定义。第一个点是起始点，第二个点是结束点，第三个点是圆弧上的一个点。CIRCULARSTRING 的坐标列表以 1 开始，以 1 结束。

```
CIRCULARSTRING(0 0, 1 1, 1 0)
```

```
CIRCULARSTRING(0 0, 4 0, 4 4, 0 4, 0 0)
```

4.1.2.2 CompoundCurve

COMPOUNDCURVE (compound curve) 是由一个或多个 CIRCULARSTRING 组成的。它由一个或多个 CIRCULARSTRING 组成，每个 CIRCULARSTRING 由三个点定义。COMPOUNDCURVE 的坐标列表以 1 开始，以 1 结束。

```
COMPOUNDCURVE( CIRCULARSTRING(0 0, 1 1, 1 0),(1 0, 0 1))
```

4.1.2.3 CurvePolygon

CURVEPOLYGON 是由一个或多个 COMPOUNDCURVE 组成的。它由一个或多个 COMPOUNDCURVE 组成，每个 COMPOUNDCURVE 由三个点定义。CURVEPOLYGON 的坐标列表以 1 开始，以 1 结束。

PostGIS 1.4 支持 CURVEPOLYGON。

```
CURVEPOLYGON(
  CIRCULARSTRING(0 0, 4 0, 4 4, 0 4, 0 0),
  (1 1, 3 3, 3 1, 1 1) )
```

Example: A CurvePolygon with the shell defined by a CompoundCurve containing a CircularString and a LineString, and a hole defined by a CircularString

```
CURVEPOLYGON(
  COMPOUNDCURVE( CIRCULARSTRING(0 0,2 0, 2 1, 2 3, 4 3),
    (4 3, 4 5, 1 4, 0 0)),
  CIRCULARSTRING(1.7 1, 1.4 0.4, 1.6 0.4, 1.6 0.5, 1.7 1) )
```

4.1.2.4 MultiCurve

MULTICURVE 数据类型, 存储多曲线, 由一个或多个曲线组成。

```
MULTICURVE( (0 0, 5 5), CIRCULARSTRING(4 0, 4 4, 8 4))
```

4.1.2.5 MultiSurface

MULTISURFACE 数据类型, (几何) 存储多曲面, 由一个或多个曲面组成。

```
MULTISURFACE(
  CURVEPOLYGON(
    CIRCULARSTRING( 0 0, 4 0, 4 4, 0 4, 0 0),
    (1 1, 3 3, 3 1, 1 1)),
  ((10 10, 14 12, 11 10, 10 10), (11 11, 11.5 11, 11 11.5, 11 11)))
```

4.1.3 OpenGIS WKB 与 WKT

OpenGIS 规范定义了两种数据格式: Well-Known Text (WKT) 和 Well-Known Binary (WKB)。WKT 是 WKB 的文本表示形式。

WKT(Well-Known Text) 格式。WKT SRS 格式:

- POINT(0 0)
- POINT(0 0)
- POINT(0 0)
- POINT EMPTY
- LINESTRING(0 0,1 1,1 2)
- LINESTRING
- POLYGON(((0 0,4 0,4 4,0 4,0 0),(1 1, 2 1, 2 2, 1 2,1 1)))
- MULTIPOINT((0 0),(1 2))
- MULTIPOINT((0 0),(1 2))
- MULTIPOINT
- MULTILINESTRING((0 0,1 1,1 2),(2 3,3 2,5 4))
- MULTIPOLYGON((((0 0,4 0,4 4,0 4,0 0),(1 1,2 1,2 2,1 2,1 1)), ((-1 -1,-1 -2,-2 -2,-2 -1,-1 -1)))
- GEOMETRYCOLLECTION(POINT(2 3),LINESTRING(2 3,3 4))
- GEOMETRYCOLLECTION

Input and output of WKT is provided by the functions **ST_AsText** and **ST_GeomFromText**:

```
text WKT = ST_AsText(geometry);
geometry = ST_GeomFromText(text WKT, SRID);
```

OGC 规范定义了两种数据格式:


```
INSERT INTO geotable ( geom, name )
VALUES ( ST_GeomFromText('POINT(-126.4 45.32)', 312), 'A Place');
```

Well-Known Binary (WKB) provides a portable, full-precision representation of spatial data as binary data (arrays of bytes). Examples of the WKB representations of spatial objects are:

- POINT(0 0)

WKB: 010100000000000000000000F03F000000000000F03

- LINESTRING(0 0,1 1,1 2)

WKB: 01020000000200000000000000000000004000000000000000040000000000000022400000000000002

Input and output of WKB is provided by the functions `ST_AsBinary` and `ST_GeomFromWKB`:

```
bytea WKB = ST_AsBinary(geometry);  
geometry = ST_GeomFromWKB(bytea WKB, SRID);
```

OGC

```
INSERT INTO geotable ( geom, name )
VALUES ( ST_GeomFromWKB('\x0101000000000000000000f03f000000000000f03f', 312), 'A Place');
```

4.2 Geometry Data Type

PostGIS implements the OGC Simple Features model by defining a PostgreSQL data type called `geometry`. It represents all of the geometry subtypes by using an internal type code (see [GeometryType](#) and [ST_GeometryType](#)). This allows modelling spatial features as rows of tables defined with a column of type `geometry`.

The geometry data type is *opaque*, which means that all access is done via invoking functions on geometry values. Functions allow creating geometry objects, accessing or updating all internal fields, and compute new geometry values. PostGIS supports all the functions specified in the OGC *Simple feature access - Part 2: SQL option* (SFS) specification, as well many others. See Chapter 7 for the full list of functions.



Note

PostGIS follows the SFA standard by prefixing spatial functions with "ST_". This was intended to stand for "Spatial and Temporal", but the temporal part of the standard was never developed. Instead it can be interpreted as "Spatial Type".

OpenGIS 几何数据类型 (SRID) 指定。 指定 SRID 值。

To make querying geometry efficient PostGIS defines various kinds of spatial indexes, and spatial operators to use them. See [Section 4.9](#) and [Section 5.2](#) for details.

4.2.1 OpenGIS WKB ☒ WKT

OGC SFA specifications initially supported only 2D geometries, and the geometry SRID is not included in the input/output representations. The OGC SFA specification 1.2.1 (which aligns with the ISO 19125 standard) adds support for 3D (ZYZ) and measured (XYM and XYZM) coordinates, but still does not include the SRID value.

Because of these limitations PostGIS defined extended EWKB and EWKT formats. They provide 3D (XYZ and XYM) and 4D (XYZM) coordinate support and include SRID information. Including all geometry information allows PostGIS to use EWKB as the format of record (e.g. in DUMP files).

EWKB and EWKT are used for the “canonical forms” of PostGIS data objects. For input, the canonical form for binary data is EWKB, and for text data either EWKB or EWKT is accepted. This allows geometry values to be created by casting a text value in either HEXEWKB or EWKT to a geometry value using `::geometry`. For output, the canonical form for binary is EWKB, and for text it is HEXEWKB (hex-encoded EWKB).

For example this statement creates a geometry by casting from an EWKT text value, and outputs it using the canonical form of HEXEWKB:

```
SELECT 'SRID=4;POINT(0 0) '::geometry;
 geometry
-----
0101000020040000000000000000000000000000000000000000000000000000
```

PostGIS EWKT output has a few differences to OGC WKT:

- For 3DZ geometries the Z qualifier is omitted:
POINT(0 0)
POINT(0 0)
- For 3DM geometries the M qualifier is included:
POINT(0 0)
POINT(0 0)
- For 4D geometries the ZM qualifier is omitted:
POINT(0 0)
POINT(0 0)

EWKT avoids over-specifying dimensionality and the inconsistencies that can occur with the OGC/ISO format, such as:

- POINT(0 0)
- POINT(0 0)
- POINT(0 0)



Caution

PostGIS 国际化 OGC 国际化 (国际化 WKB/WKT 国际化 EWKB/EWKT 国际化). 国际化. 国际化 OGC 国际化 PostGIS 国际化 国际化. 国际化!

国际化 (WKT) 国际化:

- POINT(0 0 0) -- XYZ
- SRID=32632;POINT(0 0) -- SRID 国际化 XY
- POINTM(0 0 0) -- XYM
- POINT(0 0 0 0) -- XYZM
- SRID=4326;MULTIPOINTM(0 0 0,1 2 1) -- SRID 国际化 XYM

- MULTILINESTRING((0 0 0,1 1 0,1 2 1),(2 3 1,3 2 1,5 4 1))
- POLYGON((0 0 0,4 0 0,4 4 0,0 4 0,0 0 0),(1 1 0,2 1 0,2 2 0,1 2 0,1 1 0))
- MULTIPOLYGON(((0 0 0,4 0 0,4 4 0,0 4 0,0 0 0),(1 1 0,2 1 0,2 2 0,1 2 0,1 1 0)),((-1 -1 0,-1 -2 0,-2 -2 0,-2 -1 0,-1 -1 0)))
- GEOMETRYCOLLECTIONM(POINTM(2 3 9), LINESTRINGM(2 3 4, 3 4 5))
- MULTICURVE((0 0, 5 5), CIRCULARSTRING(4 0, 4 4, 8 4))
- POLYHEDRALSURFACE(((0 0 0, 0 0 1, 0 1 1, 0 1 0, 0 0 0)), ((0 0 0, 0 1 0, 1 1 0, 1 0 0, 0 0 0)), ((0 0 0, 1 0 0, 1 0 1, 0 0 1, 0 0 0)), ((1 1 0, 1 1 1, 1 0 1, 1 0 0, 1 1 0)), ((0 1 0, 0 1 1, 1 1 1, 1 1 0, 0 1 0)), ((0 0 1, 1 0 1, 1 1 1, 0 1 1, 0 0 1)))
- TRIANGLE ((0 0, 0 9, 9 0, 0 0))
- TIN(((0 0 0, 0 0 1, 0 1 0, 0 0 0)), ((0 0 0, 0 1 0, 1 1 0, 0 0 0)))

PostGIS 提供了多种几何数据类型，用于存储和查询地理数据。

```
bytea EWKB = ST_AsEWKB(geometry);
text EWKT = ST_AsEWKT(geometry);
geometry = ST_GeomFromEWKB(bytea EWKB);
geometry = ST_GeomFromEWKT(text EWKT);
```

PostGIS 提供了多种几何数据类型，用于存储和查询地理数据。

```
INSERT INTO geotable ( geom, name )
VALUES ( ST_GeomFromEWKT('SRID=312;POINTM(-126.4 45.32 15)'), 'A Place' )
```

4.3 PostGIS 地理数据类型

PostGIS 提供了多种地理数据类型，用于存储和查询地理数据。这些数据类型可以分为点、线、面、体、集合等。

PostGIS 提供了多种地理数据类型，用于存储和查询地理数据。这些数据类型可以分为点、线、面、体、集合等。

PostGIS 提供了多种地理数据类型，用于存储和查询地理数据。这些数据类型可以分为点、线、面、体、集合等。

PostGIS 提供了多种地理数据类型，用于存储和查询地理数据。这些数据类型可以分为点、线、面、体、集合等。

Like the geometry data type, geography data is associated with a spatial reference system via a spatial reference system identifier (SRID). Any geodetic (long/lat based) spatial reference system defined in the `spatial_ref_sys` table can be used. (Prior to PostGIS 2.2, the geography type supported only WGS 84 geodetic (SRID:4326)). You can add your own custom geodetic spatial reference system as described in Section 4.5.2.

For all spatial reference systems the units returned by measurement functions (e.g. `ST_Distance`, `ST_Length`, `ST_Perimeter`, `ST_Area`) and for the distance argument of `ST_DWithin` are in meters.

4.3.2 PostGIS 国际化

You can insert data into geography tables in the same way as geometry. Geometry data will autocast to the geography type if it has SRID 4326. The **EWKT** and **EWKB** formats can also be used to specify geography values.

```
-- Add some data into the test table
INSERT INTO global_points (name, location) VALUES ('Town', 'SRID=4326;POINT(-110 30)');
INSERT INTO global_points (name, location) VALUES ('Forest', 'SRID=4326;POINT(-109 29)');
INSERT INTO global_points (name, location) VALUES ('London', 'SRID=4326;POINT(0 49)');
```

Any geodetic (long/lat) spatial reference system listed in `spatial_ref_sys` table may be specified as a geography SRID. Non-geodetic coordinate systems raise an error if used.

```
-- NAD 83 lon/lat
SELECT 'SRID=4269;POINT(-123 34)::geography;
        geography
-----
0101000020AD100000000000000000C05EC000000000000004140
```

```
-- NAD27 lon/lat
SELECT 'SRID=4267;POINT(-123 34)::geography;
        geography
-----
0101000020AB100000000000000000C05EC000000000000004140
```

```
-- NAD83 UTM zone meters - gives an error since it is a meter-based planar projection
SELECT 'SRID=26910;POINT(-123 34)::geography;
```

ERROR: Only lon/lat coordinate systems are supported in geography.

PostGIS 3.5.7 国际化. 国际化, 国际化 (国际化 国际化) 国际化.

```
-- A distance query using a 1000km tolerance
SELECT name FROM global_points WHERE ST_DWithin(location, 'SRID=4326;POINT(-110 29)::
        geography, 1000000);
```

PostGIS 3.5.7 国际化 (LINESTRING(-122.33 47.606, 0.0 51.5)) 国际化 (POINT(-21.96 64.15)) 国际化, 国际化.

国际化.

```
-- Distance calculation using GEOGRAPHY
SELECT ST_Distance('LINESTRING(-122.33 47.606, 0.0 51.5)::geography, 'POINT(-21.96 64.15) ←
        '::geography);
        st_distance
-----
122235.23815667
```

Great Circle mapper 国际化. 国际化 (degree) 国际化, 国际化.

```
-- Distance calculation using GEOMETRY
SELECT ST_Distance('LINESTRING(-122.33 47.606, 0.0 51.5)::geometry, 'POINT(-21.96 64.15) ←
        '::geometry);
        st_distance
-----
13.342271221453624
```

4.3.3 性能优化建议

PostGIS 的性能很大程度上依赖于底层的数据库和操作系统。以下是一些基本的性能优化建议。

1. 确保数据库和操作系统都使用最新的版本。2. 确保数据库的内存配置合理。3. 确保数据库的索引配置合理。4. 确保数据库的日志配置合理。5. 确保数据库的备份策略合理。6. 确保数据库的恢复策略合理。7. 确保数据库的监控策略合理。8. 确保数据库的维护策略合理。9. 确保数据库的升级策略合理。10. 确保数据库的迁移策略合理。

- 确保数据库的内存配置合理。1. 确保数据库的内存配置合理。2. 确保数据库的内存配置合理。3. 确保数据库的内存配置合理。4. 确保数据库的内存配置合理。5. 确保数据库的内存配置合理。6. 确保数据库的内存配置合理。7. 确保数据库的内存配置合理。8. 确保数据库的内存配置合理。9. 确保数据库的内存配置合理。10. 确保数据库的内存配置合理。
- 确保数据库的索引配置合理。1. 确保数据库的索引配置合理。2. 确保数据库的索引配置合理。3. 确保数据库的索引配置合理。4. 确保数据库的索引配置合理。5. 确保数据库的索引配置合理。6. 确保数据库的索引配置合理。7. 确保数据库的索引配置合理。8. 确保数据库的索引配置合理。9. 确保数据库的索引配置合理。10. 确保数据库的索引配置合理。
- 确保数据库的日志配置合理。1. 确保数据库的日志配置合理。2. 确保数据库的日志配置合理。3. 确保数据库的日志配置合理。4. 确保数据库的日志配置合理。5. 确保数据库的日志配置合理。6. 确保数据库的日志配置合理。7. 确保数据库的日志配置合理。8. 确保数据库的日志配置合理。9. 确保数据库的日志配置合理。10. 确保数据库的日志配置合理。

对于更详细的性能优化建议，请参考 Section 13.11 和 Section 13.4。

4.3.4 常见问题 FAQ

1. 为什么 PostGIS 会报错？

PostGIS 的报错信息通常包含错误代码和错误描述。请仔细阅读错误信息，并根据错误代码查找相应的解决方案。常见的错误代码包括：1. 数据库连接错误。2. 权限不足。3. 数据格式错误。4. 索引冲突。5. 内存不足。6. 磁盘空间不足。7. 网络问题。8. 硬件故障。9. 软件冲突。10. 配置错误。
2. 如何安装 PostGIS？

PostGIS 的安装步骤如下：1. 下载 PostGIS 安装包。2. 运行安装程序。3. 选择安装选项。4. 完成安装。5. 验证安装结果。6. 配置环境变量。7. 重启数据库服务。8. 测试 PostGIS 功能。9. 备份数据库。10. 更新 PostGIS 版本。
3. 如何创建 PostGIS 数据库？

创建 PostGIS 数据库的步骤如下：1. 创建数据库。2. 创建 PostGIS 扩展。3. 创建表。4. 创建索引。5. 插入数据。6. 查询数据。7. 更新数据。8. 删除数据。9. 备份数据库。10. 恢复数据库。
4. 如何查询 PostGIS 数据库？

查询 PostGIS 数据库的步骤如下：1. 连接数据库。2. 编写 SQL 查询语句。3. 执行查询。4. 获取查询结果。5. 处理查询结果。6. 关闭数据库连接。7. 备份数据库。8. 恢复数据库。9. 更新 PostGIS 版本。10. 测试 PostGIS 功能。

4.4 Geometry Validation

PostGIS 是符合 Open Geospatial Consortium (OGC) Simple Features 规范的。该规范定义了几何体的概念，包括 *simple* 和 *valid*。这些定义允许我们验证几何体的有效性。

Simple Features geometry model to represent spatial objects in a consistent and unambiguous way that supports efficient computation. (Note: the OGC SF and SQL/MM have the same definitions for simple and valid.)

4.4.1 Simple Geometry


A *simple* geometry is one that has no anomalous geometric points, such as self intersection or self tangency.

POINT 0 个坐标轴上的点。

MULTIPOINT 个坐标轴上的点 (POINT) 个坐标轴上的点 (个坐标轴上的点) 个坐标轴上的点。


A LINESTRING is *simple* if it does not pass through the same point twice, except for the endpoints. If the endpoints of a simple LineString are identical it is called *closed* and referred to as a Linear Ring.

(a) and **(c)** are simple LINESTRINGs. **(b)** and **(d)** are not simple. **(c)** is a closed Linear Ring.



A **MULTILINESTRING** is *simple* only if all of its elements are simple and the only intersection between any two elements occurs at points that are on the boundaries of both elements.

(e) and **(f)** are simple **MULTILINESTRING**s. **(g)** is not simple.



POLYGONs are formed from linear rings, so valid polygonal geometry is always *simple*.

To test if a geometry is simple use the **ST_IsSimple** function:

```
SELECT
  ST_IsSimple('LINESTRING(0 0, 100 100)') AS straight,
  ST_IsSimple('LINESTRING(0 0, 100 100, 100 0, 0 100)') AS crossing;

straight | crossing
-----+-----
t        | f
```

Generally, PostGIS functions do not require geometric arguments to be simple. Simplicity is primarily used as a basis for defining geometric validity. It is also a requirement for some kinds of spatial data models (for example, linear networks often disallow lines that cross). Multipoint and linear geometry can be made simple using **ST_UnaryUnion**.


4.4.2 Valid Geometry

Geometry validity primarily applies to 2-dimensional geometries (**POLYGON**s and **MULTIPOLYGON**s). Validity is defined by rules that allow polygonal geometry to model planar areas unambiguously.

A **POLYGON** is *valid* if:

1. the polygon boundary rings (the exterior shell ring and interior hole rings) are *simple* (do not cross or self-touch). Because of this a polygon cannot have cut lines, spikes or loops. This implies that polygon holes must be represented as interior rings, rather than by the exterior ring self-touching (a so-called "inverted hole").
2. boundary rings do not cross
3. boundary rings may touch at points but only as a tangent (i.e. not in a line)
4. interior rings are contained in the exterior ring
5. the polygon interior is simply connected (i.e. the rings must not touch in a way that splits the polygon into more than one part)


(h) and **(i)** are valid *POLYGON*s. **(j-m)** are invalid. **(j)** can be represented as a valid *MULTIPOLYGON*.



A *MULTIPOLYGON* is *valid* if:

1. its element *POLYGON*s are valid
2. elements do not overlap (i.e. their interiors must not intersect)
3. elements touch only at points (i.e. not along a line)

(n) is a valid *MULTIPOLYGON*. **(o)** and **(p)** are invalid.



These rules mean that valid polygonal geometry is also *simple*.

For linear geometry the only validity rule is that LINESTRINGS must have at least two points and have non-zero length (or equivalently, have at least two distinct points.) Note that non-simple (self-intersecting) lines are valid.

```
SELECT
  ST_IsValid('LINESTRING(0 0, 1 1)') AS len_nonzero,
  ST_IsValid('LINESTRING(0 0, 0 0, 0 0)') AS len_zero,
  ST_IsValid('LINESTRING(10 10, 150 150, 180 50, 20 130)') AS self_int;
```

len_nonzero	len_zero	self_int
t	f	t

POINT and MULTIPOINT geometries have no validity rules.

4.4.3 Managing Validity

PostGIS allows creating and storing both valid and invalid Geometry. This allows invalid geometry to be detected and flagged or fixed. There are also situations where the OGC validity rules are stricter than desired (examples of this are zero-length linestrings and polygons with inverted holes.)

Many of the functions provided by PostGIS rely on the assumption that geometry arguments are valid. For example, it does not make sense to calculate the area of a polygon that has a hole defined outside of the polygon, or to construct a polygon from a non-simple boundary line. Assuming valid geometric inputs allows functions to operate more efficiently, since they do not need to check for topological correctness. (Notable exceptions are that zero-length lines and polygons with inversions are generally handled correctly.) Also, most PostGIS functions produce valid geometry output if the inputs are valid. This allows PostGIS functions to be chained together safely.

If you encounter unexpected error messages when calling PostGIS functions (such as "GEOS Intersection() threw an error!"), you should first confirm that the function arguments are valid. If they are not, then consider using one of the techniques below to ensure the data you are processing is valid.

 **Note**

If a function reports an error with valid inputs, then you may have found an error in either PostGIS or one of the libraries it uses, and you should report this to the PostGIS project. The same is true if a PostGIS function returns an invalid geometry for valid input.

To test if a geometry is valid use the `ST_IsValid` function:

```
SELECT ST_IsValid('POLYGON ((20 180, 180 180, 180 20, 20 20, 20 180))');
-----
t
```

Information about the nature and location of an geometry invalidity are provided by the `ST_IsValidDetail` function:

```
SELECT valid, reason, ST_AsText(location) AS location
FROM ST_IsValidDetail('POLYGON ((20 20, 120 190, 50 190, 170 50, 20 20))') AS t;
```

valid	reason	location
f	Self-intersection	POINT(91.51162790697674 141.56976744186045)

In some situations it is desirable to correct invalid geometry automatically. Use the `ST_MakeValid` function to do this. (`ST_MakeValid` is a case of a spatial function that *does* allow invalid input!)

By default, PostGIS does not check for validity when loading geometry, because validity testing can take a lot of CPU time for complex geometries. If you do not trust your data sources, you can enforce a validity check on your tables by adding a check constraint:

```
ALTER TABLE mytable
ADD CONSTRAINT geometry_valid_check
CHECK (ST_IsValid(geom));
```

4.5 SPATIAL_REF_SYS 简体中文

A **Spatial Reference System** (SRS) (also called a Coordinate Reference System (CRS)) defines how geometry is referenced to locations on the Earth's surface. There are three types of SRS:

- A **geodetic** SRS uses angular coordinates (longitude and latitude) which map directly to the surface of the earth.
- A **projected** SRS uses a mathematical projection transformation to "flatten" the surface of the spheroidal earth onto a plane. It assigns location coordinates in a way that allows direct measurement of quantities such as distance, area, and angle. The coordinate system is Cartesian, which means it has a defined origin point and two perpendicular axes (usually oriented North and East). Each projected SRS uses a stated length unit (usually metres or feet). A projected SRS may be limited in its area of applicability to avoid distortion and fit within the defined coordinate bounds.
- A **local** SRS is a Cartesian coordinate system which is not referenced to the earth's surface. In PostGIS this is specified by a SRID value of 0.

There are many different spatial reference systems in use. Common SRSEs are standardized in the European Petroleum Survey Group **EPSG database**. For convenience PostGIS (and many other spatial systems) refers to SRS definitions using an integer identifier called a SRID.

A geometry is associated with a Spatial Reference System by its SRID value, which is accessed by `ST_SRID`. The SRID for a geometry can be assigned using `ST_SetSRID`. Some geometry constructor functions allow supplying a SRID (such as `ST_Point` and `ST_MakeEnvelope`). The **EWKT** format supports SRIDs with the `SRID=n;` prefix.

Spatial functions processing pairs of geometries (such as **overlay** and **relationship** functions) require that the input geometries are in the same spatial reference system (have the same SRID). Geometry data can be transformed into a different spatial reference system using `ST_Transform` and `ST_TransformPipe`. Geometry returned from functions has the same SRS as the input geometries.

4.5.1 SPATIAL_REF_SYS Table

The SPATIAL_REF_SYS table used by PostGIS is an OGC-compliant database table that defines the available spatial reference systems. It holds the numeric SRIDs and textual descriptions of the coordinate systems.

SPATIAL_REF_SYS 表结构:

```
CREATE TABLE spatial_ref_sys (
  srid          INTEGER NOT NULL PRIMARY KEY,
  auth_name     VARCHAR(256),
  auth_srid     INTEGER,
  srtext        VARCHAR(2048),
  proj4text     VARCHAR(2048)
)
```

字段描述:

srid 空间参考系统标识符 (SRS) 的数值。

auth_name 权威名称。如果为 "EPSG"，则 AUTH_NAME 为 EPSG 代码。

auth_srid 权威名称中定义的 SRS 的 ID。在 EPSG 的情况下，这是 EPSG 代码。

srtext WKT (Well-Known Text) 表示的 SRS。

```
PROJCS["NAD83 / UTM Zone 10N",
  GEOGCS["NAD83",
    DATUM["North_American_Datum_1983",
      SPHEROID["GRS 1980",6378137,298.257222101]
    ],
    PRIMEM["Greenwich",0],
    UNIT["degree",0.0174532925199433]
  ],
  PROJECTION["Transverse_Mercator"],
  PARAMETER["latitude_of_origin",0],
  PARAMETER["central_meridian",-123],
  PARAMETER["scale_factor",0.9996],
  PARAMETER["false_easting",500000],
  PARAMETER["false_northing",0],
  UNIT["metre",1]
]
```

For a discussion of SRS WKT, see the OGC standard [Well-known text representation of coordinate reference systems](#).

proj4text PostGIS 存储的 proj4 字符串。PROJ4TEXT 列存储 SRID 对应的 proj4 字符串。

```
+proj=utm +zone=10 +ellps=clrk66 +datum=NAD27 +units=m
```

有关 proj4 字符串的更多信息，请访问 <http://trac.osgeo.org/proj/>。spatial_ref_sys.sql 文件中包含 EPSG 到 SRTEXT 和 PROJ4TEXT 的映射。

When retrieving spatial reference system definitions for use in transformations, PostGIS uses the following strategy:

- If auth_name and auth_srid are present (non-NULL) use the PROJ SRS based on those entries (if one exists).
- If srtext is present create a SRS using it, if possible.
- If proj4text is present create a SRS using it, if possible.

4.5.2 SPATIAL_REF_SYS 国际化

PostGIS 的 `SPATIAL_REF_SYS` 表存储 `proj` 文本，描述坐标系统。SRID 3000 使用 `proj4` 文本描述坐标系统。SRID 3000 使用 `proj4` 文本描述坐标系统。SRID 3000 使用 `proj4` 文本描述坐标系统。

在 `SPATIAL_REF_SYS` 表中，`http://spatialreference.org/` 提供坐标系统信息。

例如，SRID 4326 - WGS 84 Long Lat, 4269 - NAD 83 Long Lat, 3395 - WGS 84 World Mercator, 2163 - US National Atlas Equal Area, SRID 3000 NAD 83 与 WGS 84 UTM (带; zone) 使用 UTM 投影。UTM 投影使用 6 度带。

PostGIS 支持非地球坐标系 (例如 Mars 2000)。PostGIS 支持非地球坐标系 (例如 Mars 2000)。PostGIS 支持非地球坐标系 (例如 Mars 2000)。

You can even define non-Earth-based coordinate systems, such as **Mars 2000**. This Mars coordinate system is non-planar (it's in degrees spheroidal), but you can use it with the `geography` type to obtain length and proximity measurements in meters instead of degrees.

Here is an example of loading a custom coordinate system using an unassigned SRID and the PROJ definition for a US-centric Lambert Conformal projection:

```
INSERT INTO spatial_ref_sys (srid, proj4text)
VALUES ( 990000,
        '+proj=lcc +lon_0=-95 +lat_0=25 +lat_1=25 +lat_2=25 +x_0=0 +y_0=0 +datum=WGS84 +units=m ←
        +no_defs'
);
```

4.6 几何数据类型

4.6.1 创建几何表

You can create a table to store geometry data using the **CREATE TABLE** SQL statement with a column of type `geometry`. The following example creates a table with a geometry column storing 2D (XY) LineStrings in the BC-Albers coordinate system (SRID 3005):

```
CREATE TABLE roads (
    id SERIAL PRIMARY KEY,
    name VARCHAR(64),
    geom geometry(LINESTRING,3005)
);
```

The geometry type supports two optional **type modifiers**:

- **SRID modifier**: `POINT`, `LINESTRING`, `POLYGON`, `MULTIPOINT`, `MULTILINESTRING`, `MULTIPOLYGON`. 例如，`POINT Z`, `M ZM` 表示 3D 点。例如，`'LINESTRINGM'` 表示 3D 线。例如，`'POINTZM'` 表示 3D 点。
- the **SRID modifier** restricts the **spatial reference system** SRID to a particular number. If omitted, the SRID defaults to 0.

Examples of creating tables with geometry columns:

- Create a table holding any kind of geometry with the default SRID:

```
CREATE TABLE geoms(gid serial PRIMARY KEY, geom geometry );
```

- Create a table with 2D POINT geometry with the default SRID:

```
CREATE TABLE pts(gid serial PRIMARY KEY, geom geometry(POINT) );
```

- Create a table with 3D (XYZ) POINTs and an explicit SRID of 3005:

```
CREATE TABLE pts(gid serial PRIMARY KEY, geom geometry(POINTZ,3005) );
```

- Create a table with 4D (XYZM) LINESTRING geometry with the default SRID:

```
CREATE TABLE lines(gid serial PRIMARY KEY, geom geometry(LINESTRINGZM) );
```

- Create a table with 2D POLYGON geometry with the SRID 4267 (NAD 1927 long lat):

```
CREATE TABLE polys(gid serial PRIMARY KEY, geom geometry(POLYGON,4267) );
```

It is possible to have more than one geometry column in a table. This can be specified when the table is created, or a column can be added using the **ALTER TABLE** SQL statement. This example adds a column that can hold 3D LineStrings:

```
ALTER TABLE roads ADD COLUMN geom2 geometry(LINESTRINGZ,4326);
```

4.6.2 The GEOMETRY_COLUMNS VIEW

OpenGIS “SQL 扩展规范 (Simple Features Specification for SQL)” 定义了 GIS 数据, 包括
 数据类型, 函数, 运算符, 以及 SQL 语句. 该规范是 OpenGIS 标准的一部分.

```
\d geometry_columns
```

Column	Type	Modifiers
f_table_catalog	character varying(256)	
f_table_schema	character varying(256)	
f_table_name	character varying(256)	
f_geometry_column	character varying(256)	
coord_dimension	integer	
srid	integer	
type	character varying(30)	

[illegible]

```
f_table_catalog, f_table_schema, f_table_name || '
'|| '
'|| 'PostgreSQL ' || '
'|| '
'|| '(public ' || '
'
```

```
f geometry column ████████████████████████████████████████.
```

coord dimension $(2, 3, 4)$.

srid 国际化 ID 值, SPATIAL_REF_SYS 国际化 (foreign key) 值。

type 国际化。 POINT, LINESTRING, POLYGON, MULTIPOINT, MULTILINESTRING, MULTIPOLYGON, GEOMETRYCOLLECTION 国际化 XYM 国际化 POINTM, LINESTRINGM, POLYGONM, MULTIPOINTM, MULTILINESTRINGM, MULTIPOLYGONM, GEOMETRYCOLLECTIONM. 国际化 "GEOMETRY" 国际化。

4.6.3 geometry_columns 国际化

AddGeometryColumn() 国际化, SQL 国际化 (bulk insert) 国际化。 国际化, 国际化 geometry_columns 国际化。 PostGIS 2.0 国际化, 国际化 typmod 国际化。

```
-- Lets say you have a view created like this
CREATE VIEW public.vwmytablemercator AS
    SELECT gid, ST_Transform(geom, 3395) As geom, f_name
    FROM public.mytable;

-- For it to register correctly
-- You need to cast the geometry
--
DROP VIEW public.vwmytablemercator;
CREATE VIEW public.vwmytablemercator AS
    SELECT gid, ST_Transform(geom, 3395)::geometry(Geometry, 3395) As geom, f_name
    FROM public.mytable;

-- If you know the geometry type for sure is a 2D POLYGON then you could do
DROP VIEW public.vwmytablemercator;
CREATE VIEW public.vwmytablemercator AS
    SELECT gid, ST_Transform(geom,3395)::geometry(Polygon, 3395) As geom, f_name
    FROM public.mytable;
```

```
-- Lets say you created a derivative table by doing a bulk insert
SELECT poi.gid, poi.geom, citybounds.city_name
INTO myschema.my_special_pois
FROM poi INNER JOIN citybounds ON ST_Intersects(citybounds.geom, poi.geom);

-- Create 2D index on new table
CREATE INDEX idx_myschema_myspecialpois_geom_gist
ON myschema.my_special_pois USING gist(geom);

-- If your points are 3D points or 3M points,
-- then you might want to create an nd index instead of a 2D index
CREATE INDEX my_special_pois_geom_gist_nd
ON my_special_pois USING gist(geom gist_geometry_ops_nd);

-- To manually register this new table's geometry column in geometry_columns.
-- Note it will also change the underlying structure of the table to
-- to make the column typmod based.
SELECT populate_geometry_columns('myschema.my_special_pois'::regclass);

-- If you are using PostGIS 2.0 and for whatever reason, you
-- you need the constraint based definition behavior
-- (such as case of inherited tables where all children do not have the same type and srid)
-- set optional use_typmod argument to false
SELECT populate_geometry_columns('myschema.my_special_pois'::regclass, false);
```

PostGIS 3.5.7 安装与使用, 安装与使用 typmod 安装
geometry_columns 安装与使用. typmod 安装与使用
安装与使用.

```
CREATE TABLE pois_ny(gid SERIAL PRIMARY KEY, poi_name text, cat text, geom geometry(POINT ↵
,4326));
SELECT AddGeometryColumn('pois_ny', 'geom_2160', 2160, 'POINT', 2, false);
```

PSQL 安装与使用

```
\d pois_ny;
```

安装与使用. typmod, 安装与使用.

```
Table "public.pois_ny"
  Column |          Type          | Modifiers
-----+-----+-----
gid      | integer                | not null default nextval('pois_ny_gid_seq'::regclass)
poi_name | text                   |
cat      | character varying(20) |
geom     | geometry(Point,4326)   |
geom_2160| geometry               |
Indexes:
    "pois_ny_pkey" PRIMARY KEY, btree (gid)
Check constraints:
    "enforce_dims_geom_2160" CHECK (st_ndims(geom_2160) = 2)
    "enforce_geotype_geom_2160" CHECK (geometrytype(geom_2160) = 'POINT'::text
    OR geom_2160 IS NULL)
    "enforce_srid_geom_2160" CHECK (st_srid(geom_2160) = 2160)
```

geometry_columns 安装与使用.

```
SELECT f_table_name, f_geometry_column, srid, type
FROM geometry_columns
WHERE f_table_name = 'pois_ny';
```

```
f_table_name | f_geometry_column | srid | type
-----+-----+-----+-----
pois_ny      | geom              | 4326 | POINT
pois_ny      | geom_2160         | 2160 | POINT
```

-- 安装与使用

```
CREATE VIEW vw_pois_ny_parks AS
SELECT *
FROM pois_ny
WHERE cat='park';
```

```
SELECT f_table_name, f_geometry_column, srid, type
FROM geometry_columns
WHERE f_table_name = 'vw_pois_ny_parks';
```

typmod 安装与使用, 安装与使用.

```
f_table_name | f_geometry_column | srid | type
-----+-----+-----+-----
vw_pois_ny_parks | geom              | 4326 | POINT
vw_pois_ny_parks | geom_2160         | 0    | GEOMETRY
```

PostGIS 安装与使用, 安装与使用
安装与使用:


```

DROP VIEW vw_pois_ny_parks;
CREATE VIEW vw_pois_ny_parks AS
SELECT gid, poi_name, cat,
       geom,
       geom_2160::geometry(POINT,2160) As geom_2160
FROM pois_ny
WHERE cat = 'park';
SELECT f_table_name, f_geometry_column, srid, type
FROM geometry_columns
WHERE f_table_name = 'vw_pois_ny_parks';

```

f_table_name	f_geometry_column	srid	type
vw_pois_ny_parks	geom	4326	POINT
vw_pois_ny_parks	geom_2160	2160	POINT

4.7 GIS (安装) 安装与使用

安装与使用, 安装与使用 GIS 安装与使用。安装, 安装 SQL 安装与使用 shapefile 安装与使用 PostgreSQL 安装与使用。

4.7.1 SQL 安装与使用

安装与使用, PostgreSQL 安装与使用 (formatted) SQL 安装与使用。Oracle 安装与使用 SQL 安装与使用, SQL 安装与使用 SQL "INSERT" 安装与使用 (piping) 安装与使用。

安装与使用 (安装与使用 roads.sql) 安装与使用:

```

BEGIN;
INSERT INTO roads (road_id, roads_geom, road_name)
VALUES (1, 'LINESTRING(191232 243118,191108 243242)', 'Jeff Rd');
INSERT INTO roads (road_id, roads_geom, road_name)
VALUES (2, 'LINESTRING(189141 244158,189265 244817)', 'Geordie Rd');
INSERT INTO roads (road_id, roads_geom, road_name)
VALUES (3, 'LINESTRING(192783 228138,192612 229814)', 'Paul St');
INSERT INTO roads (road_id, roads_geom, road_name)
VALUES (4, 'LINESTRING(189412 252431,189631 259122)', 'Graeme Ave');
INSERT INTO roads (road_id, roads_geom, road_name)
VALUES (5, 'LINESTRING(190131 224148,190871 228134)', 'Phil Tce');
INSERT INTO roads (road_id, roads_geom, road_name)
VALUES (6, 'LINESTRING(198231 263418,198213 268322)', 'Dave Cres');
COMMIT;

```

"psql" SQL 安装与使用 PostgreSQL 安装与使用。

```
psql -d [database] -f roads.sql
```

4.7.2 shp2pgsql: ESRI shapefile 安装与使用

shp2pgsql 安装与使用 ESRI shapefile 安装与使用, PostgreSQL 安装与使用 SQL 安装与使用。安装与使用 (command line) 安装与使用。

- n DBF 格式。shapefile 格式, 输出 DBF 格式。shapefile 格式输出到 PostgreSQL 数据库。
- G (x/y/z) 指定 WGS84 坐标 (SRID=4326) 输出。
- T <tablespace> 指定表空间。-X 指定主键 (primary key) 索引, -I 指定 GiST 索引。
- Z When used, this flag will prevent the generation of ANALYZE statements. Without the -Z flag (default behavior), the ANALYZE statements will be generated.

安装示例:

```
# shp2pgsql -c -D -s 4269 -i -I shaperoads.shp myschema.roadstable
> roads.sql
# psql -d roadsdb -f roads.sql
```

UNIX 管道 (pipe) 安装示例:

```
# shp2pgsql shaperoads.shp myschema.roadstable | psql -d roadsdb
```

4.8 数据导入

SQL 格式 shapefile 数据导入。SQL 格式数据导入。

4.8.1 SQL 数据导入

安装示例 SQL (select) 数据导入:

```
db=# SELECT road_id, ST_AsText(road_geom) AS geom, road_name FROM roads;
```

road_id	geom	road_name
1	LINESTRING(191232 243118,191108 243242)	Jeff Rd
2	LINESTRING(189141 244158,189265 244817)	Geordie Rd
3	LINESTRING(192783 228138,192612 229814)	Paul St
4	LINESTRING(189412 252431,189631 259122)	Graeme Ave
5	LINESTRING(190131 224148,190871 228134)	Phil Tce
6	LINESTRING(198231 263418,198213 268322)	Dave Cres
7	LINESTRING(218421 284121,224123 241231)	Chris Way

(6 rows)

安装示例 SQL 数据导入。安装示例, 安装示例。

ST_Intersects This function tells whether two geometries share any space.

= 安装示例。安装示例, 'POLYGON((0 0,1 1,1 0,0 0))' 安装示例。

SQL 语句如下，"ST_GeomFromText()" 函数用于将文本转换为几何对象。该函数需要两个参数：SRID 和几何文本。SRID 312 表示平面坐标系。该函数返回一个几何对象。

```
SELECT road_id, road_name
FROM roads
WHERE roads_geom='SRID=312;LINESTRING(191232 243118,191108 243242)>::geometry;
```

该语句将返回所有与指定几何对象相交的道路名称。该函数返回一个布尔值，表示是否相交。

To check whether some of the roads passes in the area defined by a polygon:

```
SELECT road_id, road_name
FROM roads
WHERE ST_Intersects(roads_geom, 'SRID=312;POLYGON((...))');
```

该语句将返回所有与指定多边形相交的道路名称。该函数返回一个布尔值，表示是否相交。

"&&" 运算符，用于 BOX3D 对象。该运算符返回一个布尔值，表示是否相交。

Using a "BOX3D" object for the frame, such a query looks like this:

```
SELECT ST_AsText(roads_geom) AS geom
FROM roads
WHERE
roads_geom && ST_MakeEnvelope(191232, 243117,191232, 243119,312);
```

该语句将返回所有与指定 BOX3D 对象相交的道路名称。该函数返回一个布尔值，表示是否相交。

4.8.2 安装与使用

pgsql2shp 是一个用于将 PostgreSQL 数据库中的几何数据导出为 shapefile 的工具。该工具需要安装 PostgreSQL 和 shapelib 库。

```
pgsql2shp [<options>
>] <database>
> [<schema>
>.]<table>
```

```
pgsql2shp [<options>
>] <database>
> <query>
```

该工具支持以下选项：

- f <filename> 指定输出文件的名称。
- h <host> 指定数据库主机地址。
- p <port> 指定数据库端口。
- P <password> 指定数据库密码。
- u <user> 指定数据库用户名。
- g <geometry column> 指定要导出的几何列名。shapefile 只能存储一个几何列。
- b 指定要导出的几何类型。该选项可以指定为 POINT、POLYGON 或 GEOMETRY。默认值为 GEOMETRY。该选项可以指定为 POINT、POLYGON 或 GEOMETRY。默认值为 GEOMETRY。

Building a spatial index is a computationally intensive exercise. It also blocks write access to your table for the time it creates, so on a production system you may want to do in a slower CONCURRENTLY-aware way:

```
CREATE INDEX CONCURRENTLY [indexname] ON [tablename] USING GIST ( [geometryfield] );
```

After building an index, it is sometimes helpful to force PostgreSQL to collect table statistics, which are used to optimize query plans:

```
VACUUM ANALYZE [table_name] [(column_name)];
```

4.9.2 GiST 索引

BRIN stands for “Block Range Index”. It is a general-purpose index method introduced in PostgreSQL 9.5. BRIN is a *lossy* index method, meaning that a secondary check is required to confirm that a record matches a given search condition (which is the case for all provided spatial indexes). It provides much faster index creation and much smaller index size, with reasonable read performance. Its primary purpose is to support indexing very large tables on columns which have a correlation with their physical location within the table. In addition to spatial indexing, BRIN can speed up searches on various kinds of attribute data structures (integer, arrays etc). For more information see the [PostgreSQL manual](#).

GIS 索引使用几何对象的边界框 (bounding box) 来索引数据。它通过存储每个几何对象的边界框来索引数据。边界框是包围几何对象的最小矩形。索引使用边界框来快速查找可能包含查询结果的表块。索引的大小通常比 GiST 索引小得多。

A BRIN index stores the bounding box enclosing all the geometries contained in the rows in a contiguous set of table blocks, called a *block range*. When executing a query using the index the block ranges are scanned to find the ones that intersect the query extent. This is efficient only if the data is physically ordered so that the bounding boxes for block ranges have minimal overlap (and ideally are mutually exclusive). The resulting index is very small in size, but is typically less performant for read than a GiST index over the same data.

Building a BRIN index is much less CPU-intensive than building a GiST index. It’s common to find that a BRIN index is ten times faster to build than a GiST index over the same data. And because a BRIN index stores only one bounding box for each range of table blocks, it’s common to use up to a thousand times less disk space than a GiST index.

You can choose the number of blocks to summarize in a range. If you decrease this number, the index will be bigger but will probably provide better performance.

For BRIN to be effective, the table data should be stored in a physical order which minimizes the amount of block extent overlap. It may be that the data is already sorted appropriately (for instance, if it is loaded from another dataset that is already sorted in spatial order). Otherwise, this can be accomplished by sorting the data by a one-dimensional spatial key. One way to do this is to create a new table sorted by the geometry values (which in recent PostGIS versions uses an efficient Hilbert curve ordering):

```
CREATE TABLE table_sorted AS
SELECT * FROM table ORDER BY geom;
```

Alternatively, data can be sorted in-place by using a GeoHash as a (temporary) index, and clustering on that index:

```
CREATE INDEX idx_temp_geohash ON table
USING btree (ST_GeoHash( ST_Transform( geom, 4326 ), 20));
CLUSTER table USING idx_temp_geohash;
```

“ 索引 ” 使用 GiST 索引:

```
CREATE INDEX [indexname] ON [tablename] USING BRIN ( [geome_col] );
```

PostGIS 2D 索引。PostGIS 2.0 引入 n 维索引，索引，索引：

```
CREATE INDEX [indexname] ON [tablename]
    USING BRIN ([geome_col] brin_geometry_inclusion_ops_3d);
```

You can also get a 4D-dimensional index using the 4D operator class:

```
CREATE INDEX [indexname] ON [tablename]
    USING BRIN ([geome_col] brin_geometry_inclusion_ops_4d);
```

The above commands use the default number of blocks in a range, which is 128. To specify the number of blocks to summarise in a range, use this syntax

```
CREATE INDEX [indexname] ON [tablename]
    USING BRIN ( [geome_col] ) WITH (pages_per_range = [number]);
```

Keep in mind that a BRIN index only stores one index entry for a large number of rows. If your table stores geometries with a mixed number of dimensions, it's likely that the resulting index will have poor performance. You can avoid this performance penalty by choosing the operator class with the least number of dimensions of the stored geometries

" " GiST 索引：

```
CREATE INDEX [indexname] ON [tablename] USING BRIN ( [geog_col] );
```

PostGIS 2D 索引。PostGIS 2.0 引入 n 维索引，索引，索引：

Currently, only "inclusion support" is provided, meaning that just the &&, ~ and @ operators can be used for the 2D cases (for both geometry and geography), and just the &&& operator for 3D geometries. There is currently no support for kNN searches.

An important difference between BRIN and other index types is that the database does not maintain the index dynamically. Changes to spatial data in the table are simply appended to the end of the index. This will cause index search performance to degrade over time. The index can be updated by performing a VACUUM, or by using a special function `brin_summarize_new_values(regclass)`. For this reason BRIN may be most appropriate for use with data that is read-only, or only rarely changing. For more information refer to the [manual](#).

To summarize using BRIN for spatial data:

- Index build time is very fast, and index size is very small.
- Index query time is slower than GiST, but can still be very acceptable.
- Requires table data to be sorted in a spatial ordering.
- Requires manual index maintenance.
- Most appropriate for very large tables, with low or no overlap (e.g. points), which are static or change infrequently.
- More effective for queries which return relatively large numbers of data records.

4.9.3 GiST 索引

SP-GiST stands for "Space-Partitioned Generalized Search Tree" and is a generic form of indexing for multi-dimensional data types that supports partitioned search trees, such as quad-trees, k-d trees, and radix trees (tries). The common feature of these data structures is that they repeatedly divide the search space into partitions that need not be of equal size. In addition to spatial indexing, SP-GiST is

used to speed up searches on many kinds of data, such as phone routing, ip routing, substring search, etc. For more information see the [PostgreSQL manual](#).

As it is the case for GiST indexes, SP-GiST indexes are lossy, in the sense that they store the bounding box enclosing spatial objects. SP-GiST indexes can be considered as an alternative to GiST indexes.

GIS 索引是用于加速空间数据查询的。SP-GiST 索引是 GiST 索引的一种变体，它使用包围盒来近似存储空间对象。SP-GiST 索引可以被认为是 GiST 索引的替代方案。SP-GiST 索引是“有损”的，因为它们存储的是包围盒，而不是精确的空间对象。在 PostgreSQL 中，SP-GiST 索引通常用于加速 2D 和 3D 几何数据的查询。

```
CREATE INDEX [indexname] ON [tablename] USING SPGIST ( [geometryfield] );
```

SP-GiST 索引是 2D 索引。在 PostgreSQL 2.0 之前，SP-GiST 索引只能用于 2D 几何数据。从 PostgreSQL 2.0 开始，SP-GiST 索引可以用于 3D 几何数据。在 PostgreSQL 3.5.7 中，SP-GiST 索引可以用于 2D 和 3D 几何数据。

```
CREATE INDEX [indexname] ON [tablename] USING SPGIST ([geometryfield] ↔
    spgist_geometry_ops_3d);
```

Building a spatial index is a computationally intensive operation. It also blocks write access to your table for the time it creates, so on a production system you may want to do in a slower CONCURRENTLY-aware way:

```
CREATE INDEX CONCURRENTLY [indexname] ON [tablename] USING SPGIST ( [geometryfield] );
```

After building an index, it is sometimes helpful to force PostgreSQL to collect table statistics, which are used to optimize query plans:

```
VACUUM ANALYZE [table_name] [(column_name)];
```

An SP-GiST index can accelerate queries involving the following operators:

- <<, &<, &>, >>, <<|, &<|, |&>, |>>, &&, @>, <@, and ~=, for 2-dimensional indexes,
- &/&, ~=, @>>, and <<@, for 3-dimensional indexes.

There is no support for kNN searches at the moment.

4.9.4 性能调优

在 PostgreSQL 中，性能调优是一个复杂的过程。以下是一些常见的性能调优技巧：1. 检查查询计划：使用 EXPLAIN 命令查看查询计划，了解数据库是如何执行查询的。2. 收集统计信息：使用 VACUUM ANALYZE 命令收集表的统计信息，帮助数据库优化器做出更好的决策。3. 使用索引：索引可以加速查询，但也会增加写入的开销。合理使用索引可以提高查询性能。

以下是一些常见的性能调优技巧：1. 检查查询计划：使用 EXPLAIN 命令查看查询计划，了解数据库是如何执行查询的。2. 收集统计信息：使用 VACUUM ANALYZE 命令收集表的统计信息，帮助数据库优化器做出更好的决策。3. 使用索引：索引可以加速查询，但也会增加写入的开销。合理使用索引可以提高查询性能。

- Examine the query plan and check your query actually computes the thing you need. An erroneous JOIN, either forgotten or to the wrong table, can unexpectedly retrieve table records multiple times. To get the query plan, execute with EXPLAIN in front of the query.
- Make sure statistics are gathered about the number and distributions of values in a table, to provide the query planner with better information to make decisions around index usage. **VACUUM ANALYZE** will compute both.

You should regularly vacuum your databases anyways. Many PostgreSQL DBAs run **VACUUM** as an off-peak cron job on a regular basis.

- 通常, 数据库系统默认使用 **SET ENABLE_SEQSCAN=OFF** 来禁用顺序扫描。这通常是一个好的做法, 因为它可以防止数据库系统使用低效的扫描方法。然而, 在某些情况下, 顺序扫描可能是更优的选择。例如, 当查询涉及大量的数据, 或者当查询涉及大量的连接时, 顺序扫描可能会比索引扫描更高效。在这种情况下, 你可以使用 **SET ENABLE_SEQSCAN=ON** 来启用顺序扫描。
- 数据库系统默认使用 (cost) 来估计扫描的成本, postgresql.conf 中的 random_page_cost 参数控制着这个成本。默认值是 4, 1 到 2 之间的值可能会更合适。你可以使用 **SET random_page_cost=#** 来设置这个值。
- If **SET ENABLE_SEQSCAN TO OFF;** does not help your query, the query may be using a SQL construct that the Postgres planner is not yet able to optimize. It may be possible to rewrite the query in a way that the planner is able to handle. For example, a subquery with an inline SELECT may not produce an efficient plan, but could possibly be rewritten using a LATERAL JOIN.

For more information see the Postgres manual section on [Query Planning](#).

Chapter 5

Spatial Queries

The *raison d'être* of spatial databases is to perform queries inside the database which would ordinarily require desktop GIS functionality. Using PostGIS effectively requires knowing what spatial functions are available, how to use them in queries, and ensuring that appropriate indexes are in place to provide good performance.

5.1 Determining Spatial Relationships

Spatial relationships indicate how two geometries interact with one another. They are a fundamental capability for querying geometry.

5.1.1 Dimensionally Extended 9-Intersection Model

According to the [OpenGIS Simple Features Implementation Specification for SQL](#), “the basic approach to comparing two geometries is to make pair-wise tests of the intersections between the Interiors, Boundaries and Exteriors of the two geometries and to classify the relationship between the two geometries based on the entries in the resulting ‘intersection’ matrix.”

In the theory of point-set topology, the points in a geometry embedded in 2-dimensional space are categorized into three sets:

Boundary

The boundary of a geometry is the set of geometries of the next lower dimension. For POINTs, which have a dimension of 0, the boundary is the empty set. The boundary of a LINESTRING is the two endpoints. For POLYGONS, the boundary is the linework of the exterior and interior rings.

Interior

The interior of a geometry are those points of a geometry that are not in the boundary. For POINTs, the interior is the point itself. The interior of a LINESTRING is the set of points between the endpoints. For POLYGONS, the interior is the areal surface inside the polygon.

Exterior

The exterior of a geometry is the rest of the space in which the geometry is embedded; in other words, all points not in the interior or on the boundary of the geometry. It is a 2-dimensional non-closed surface.

The **Dimensionally Extended 9-Intersection Model** (DE-9IM) describes the spatial relationship between two geometries by specifying the dimensions of the 9 intersections between the above sets for each geometry. The intersection dimensions can be formally represented in a 3x3 **intersection matrix**.


For a geometry g the *Interior*, *Boundary*, and *Exterior* are denoted using the notation $I(g)$, $B(g)$, and $E(g)$. Also, $dim(s)$ denotes the dimension of a set s with the domain of $\{0, 1, 2, F\}$:









- 0 => point
- 1 => line
- 2 => area
- F => empty set

Using this notation, the intersection matrix for two geometries a and b is:

	Interior	Boundary	Exterior
Interior	$dim(I(a) \cap I(b))$	$dim(I(a) \cap B(b))$	$dim(I(a) \cap E(b))$
Boundary	$dim(B(a) \cap I(b))$	$dim(B(a) \cap B(b))$	$dim(B(a) \cap E(b))$
Exterior	$dim(E(a) \cap I(b))$	$dim(E(a) \cap B(b))$	$dim(E(a) \cap E(b))$

Visually, for two overlapping polygonal geometries, this looks like:



		Interior	Boundary	Exterior
	Interior	 $\dim(I(a) \cap I(b)) = 2$	 $\dim(I(a) \cap B(b)) = 1$	 $\dim(I(a) \cap E(b)) = 2$
	Boundary	 $\dim(B(a) \cap I(b)) = 1$	 $\dim(B(a) \cap B(b)) = 0$	 $\dim(B(a) \cap E(b)) = 1$
	Exterior	 $\dim(E(a) \cap I(b)) = 2$	 $\dim(E(a) \cap B(b)) = 1$	 $\dim(E(a) \cap E(b)) = 2$

Reading from left to right and top to bottom, the intersection matrix is represented as the text string **'212101212'**.

For more information, refer to:

- [OpenGIS Simple Features Implementation Specification for SQL](#) (version 1.1, section 2.1.13.2)
- [Wikipedia: Dimensionally Extended Nine-Intersection Model \(DE-9IM\)](#)
- [GeoTools: Point Set Theory and the DE-9IM Matrix](#)

5.1.2 Named Spatial Relationships

To make it easy to determine common spatial relationships, the OGC SFS defines a set of *named spatial relationship predicates*. PostGIS provides these as the functions **ST_Contains**, **ST_Crosses**, **ST_Disjoint**, **ST_Equals**, **ST_Intersects**, **ST_Overlaps**, **ST_Touches**, **ST_Within**. It also defines the non-standard relationship predicates **ST_Covers**, **ST_CoveredBy**, and **ST_ContainsProperly**.

Spatial predicates are usually used as conditions in SQL WHERE or JOIN clauses. The named spatial predicates automatically use a spatial index if one is available, so there is no need to use the bounding box operator && as well. For example:

```
SELECT city.name, state.name, city.geom
FROM city JOIN state ON ST_Intersects(city.geom, state.geom);
```

For more details and illustrations, see the [PostGIS Workshop](#).

5.1.3 General Spatial Relationships


In some cases the named spatial relationships are insufficient to provide a desired spatial filter condition.



For example, consider a linear dataset representing a road network. It may be required to identify all road segments that cross each other, not at a point, but in a line (perhaps to validate some business rule). In this case **ST_Crosses** does not provide the necessary spatial filter, since for linear features it returns true only where they cross at a point.

A two-step solution would be to first compute the actual intersection (**ST_Intersection**) of pairs of road lines that spatially intersect (**ST_Intersects**), and then check if the intersection's **ST_GeometryType** is 'LINESTRING' (properly dealing with cases that return GEOMETRYCOLLECTIONs of [MULTI]POINTS, [MULTI]LINESTRINGs, etc.).

Clearly, a simpler and faster solution is desirable.



A second example is locating wharves that intersect a lake's boundary on a line and where one end of the wharf is up on shore. In other words, where a wharf is within but not completely contained by a lake, intersects the boundary of a lake on a line, and where exactly one of the wharf's endpoints is within or on the boundary of the lake. It is possible to use a combination of spatial predicates to find the required features:

- `ST_Contains(lake, wharf) = TRUE`
 - `ST_ContainsProperly(lake, wharf) = FALSE`
 - `ST_GeometryType(ST_Intersection(wharf, lake)) = 'LINESTRING'`
 - `ST_NumGeometries(ST_Multi(ST_Intersection(ST_Boundary(wharf), ST_Boundary(lake)))) = 1`
- ... but needless to say, this is quite complicated.

These requirements can be met by computing the full DE-9IM intersection matrix. PostGIS provides the `ST_Relate` function to do this:

```
SELECT ST_Relate( 'LINESTRING (1 1, 5 5)',
                  'POLYGON ((3 3, 3 7, 7 7, 7 3, 3 3))' );
st_relate
-----
1010F0212
```

To test a particular spatial relationship, an **intersection matrix pattern** is used. This is the matrix representation augmented with the additional symbols {T,*}:

- T => intersection dimension is non-empty; i.e. is in {0,1,2}
- * => don't care

Using intersection matrix patterns, specific spatial relationships can be evaluated in a more succinct way. The `ST_Relate` and the `ST_RelateMatch` functions can be used to test intersection matrix patterns. For the first example above, the intersection matrix pattern specifying two lines intersecting in a line is `'1*1***1**'`:

```
-- Find road segments that intersect in a line
SELECT a.id
FROM roads a, roads b
WHERE a.id != b.id
```

```
AND a.geom && b.geom
AND ST_Relate(a.geom, b.geom, '1*1**1**');
```

For the second example, the intersection matrix pattern specifying a line partly inside and partly outside a polygon is '**102101FF2**':

```
-- Find wharves partly on a lake's shoreline
SELECT a.lake_id, b.wharf_id
FROM lakes a, wharfs b
WHERE a.geom && b.geom
      AND ST_Relate(a.geom, b.geom, '102101FF2');
```

5.2 Using Spatial Indexes

When constructing queries using spatial conditions, for best performance it is important to ensure that a spatial index is used, if one exists (see Section 4.9). To do this, a spatial operator or index-aware function must be used in a `WHERE` or `ON` clause of the query.

Spatial operators include the bounding box operators (of which the most commonly used is `&&`; see Section 7.10.1 for the full list) and the distance operators used in nearest-neighbor queries (the most common being `<->`; see Section 7.10.2 for the full list.)

Index-aware functions automatically add a bounding box operator to the spatial condition. Index-aware functions include the named spatial relationship predicates `ST_Contains`, `ST_ContainsProperly`, `ST_CoveredBy`, `ST_Covers`, `ST_Crosses`, `ST_Intersects`, `ST_Overlaps`, `ST_Touches`, `ST_Within`, `ST_Within`, and `ST_3DIntersects`, and the distance predicates `ST_DWithin`, `ST_DFullyWithin`, `ST_3DDFullyWithin`, and `ST_3DDWithin`.)

Functions such as `ST_Distance` do *not* use indexes to optimize their operation. For example, the following query would be quite slow on a large table:

```
SELECT geom
FROM geom_table
WHERE ST_Distance( geom, 'SRID=312;POINT(100000 200000)' ) < 100
```

This query selects all the geometries in `geom_table` which are within 100 units of the point (100000, 200000). It will be slow because it is calculating the distance between each point in the table and the specified point, ie. one `ST_Distance()` calculation is computed for **every** row in the table.

The number of rows processed can be reduced substantially by using the index-aware function `ST_DWithin`:

```
SELECT geom
FROM geom_table
WHERE ST_DWithin( geom, 'SRID=312;POINT(100000 200000)', 100 )
```

This query selects the same geometries, but it does it in a more efficient way. This is enabled by `ST_DWithin()` using the `&&` operator internally on an expanded bounding box of the query geometry. If there is a spatial index on `geom`, the query planner will recognize that it can use the index to reduce the number of rows scanned before calculating the distance. The spatial index allows retrieving only records with geometries whose bounding boxes overlap the expanded extent and hence which *might* be within the required distance. The actual distance is then computed to confirm whether to include the record in the result set.

For more information and examples see the [PostGIS Workshop](#).

5.3 Examples of Spatial SQL

The examples in this section make use of a table of linear roads, and a table of polygonal municipality boundaries. The definition of the `bc_roads` table is:

Column	Type	Description
gid	integer	Unique ID
name	character varying	Road Name
geom	geometry	Location Geometry (Linestring)

The definition of the `bc_municipality` table is:

Column	Type	Description
gid	integer	Unique ID
code	integer	Unique ID
name	character varying	City / Town Name
geom	geometry	Location Geometry (Polygon)

1. *What is the total length of all roads, expressed in kilometers?*

You can answer this question with a very simple piece of SQL:

```
SELECT sum(ST_Length(geom))/1000 AS km_roads FROM bc_roads;
```

```
km_roads
-----
70842.1243039643
```

2. *How large is the city of Prince George, in hectares?*

This query combines an attribute condition (on the municipality name) with a spatial calculation (of the polygon area):

```
SELECT
  ST_Area(geom)/10000 AS hectares
FROM bc_municipality
WHERE name = 'PRINCE GEORGE';
```

```
hectares
-----
32657.9103824927
```

3. *What is the largest municipality in the province, by area?*

This query uses a spatial measurement as an ordering value. There are several ways of approaching this problem, but the most efficient is below:

```
SELECT
  name,
  ST_Area(geom)/10000 AS hectares
FROM bc_municipality
ORDER BY hectares DESC
LIMIT 1;
```

```
name          | hectares
-----+-----
TUMBLER RIDGE | 155020.02556131
```


Note that in order to answer this query we have to calculate the area of every polygon. If we were doing this a lot it would make sense to add an area column to the table that could be indexed for performance. By ordering the results in a descending direction, and then using the PostgreSQL "LIMIT" command we can easily select just the largest value without using an aggregate function like MAX().

4. *What is the length of roads fully contained within each municipality?*

This is an example of a "spatial join", which brings together data from two tables (with a join) using a spatial interaction ("contained") as the join condition (rather than the usual relational approach of joining on a common key):

```
SELECT
  m.name,
  sum(ST_Length(r.geom))/1000 as roads_km
FROM bc_roads AS r
JOIN bc_municipality AS m
  ON ST_Contains(m.geom, r.geom)
GROUP BY m.name
ORDER BY roads_km;
```

name	roads_km
SURREY	1539.47553551242
VANCOUVER	1450.33093486576
LANGLEY DISTRICT	833.793392535662
BURNABY	773.769091404338
PRINCE GEORGE	694.37554369147
...	

This query takes a while, because every road in the table is summarized into the final result (about 250K roads for the example table). For smaller datasets (several thousand records on several hundred) the response can be very fast.

5. *Create a new table with all the roads within the city of Prince George.*

This is an example of an "overlay", which takes in two tables and outputs a new table that consists of spatially clipped or cut resultants. Unlike the "spatial join" demonstrated above, this query creates new geometries. An overlay is like a turbo-charged spatial join, and is useful for more exact analysis work:

```
CREATE TABLE pg_roads as
SELECT
  ST_Intersection(r.geom, m.geom) AS intersection_geom,
  ST_Length(r.geom) AS rd_orig_length,
  r.*
FROM bc_roads AS r
JOIN bc_municipality AS m
  ON ST_Intersects(r.geom, m.geom)
WHERE
  m.name = 'PRINCE GEORGE';
```

6. *What is the length in kilometers of "Douglas St" in Victoria?*

```
SELECT
  sum(ST_Length(r.geom))/1000 AS kilometers
FROM bc_roads r
JOIN bc_municipality m
  ON ST_Intersects(m.geom, r.geom)
WHERE
  r.name = 'Douglas St'
  AND m.name = 'VICTORIA';
```

```
kilometers
-----
4.89151904172838
```

7. *What is the largest municipality polygon that has a hole?*

```
SELECT gid, name, ST_Area(geom) AS area
FROM bc_municipality
WHERE ST_NRings(geom)
> 1
ORDER BY area DESC LIMIT 1;
```

gid	name	area
12	SPALLUMCHEEN	257374619.430216

6.1.1 ☐ ☐ ☐ ☐ ☐

[illegible]

XXXXXXXXXXXXXXXXXXXXXXXXX, "EXPLAIN ANALYZE" PostgreSQL XXXXXXXXXXXXXXX. XX
XXXXXXXXXXXXXXXXXXXXXXXXX, PostgreSQL XXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXX:
<http://archives.postgresql.org/pgsql-performance/2005-02/msg00030.php>

6.1.2 ☐ ☐ ☐ ☐

[illegible]

```
SELECT AddGeometryColumn('myschema','mytable','bbox','4326','GEOMETRY','2');
UPDATE mytable SET bbox = ST_Envelope(ST_Force2D(geom));
```

```
geom_column bbox && [REDACTED]:
```

```
SELECT geom_column
FROM mytable
WHERE bbox && ST_SetSRID('BOX3D(0 0,1 1) '::box3d,4326);
```

`mytable`, mytable `trigger` `bbox` " " `trigger` `bbox` `UPDATE`

6.2 ☒☒☒☒☒☒☒☒☒☒☒☒☒☒

[illegible]

PostgreSQL 12.1 (Ubuntu 12.1-1)
 PostGIS 2.5.3 (Ubuntu 2.5.3-1)
 GiST 1.5.8 (Ubuntu 1.5.8-1)
 NULL 1.5.8 (Ubuntu 1.5.8-1)

```
lwgeom=# CLUSTER my_geom_index ON my_table;
ERROR: cannot cluster when index access method does not handle null values
HINT: You may be able to work around this by marking column "geom" NOT NULL.
```

HINT `isnull()`, `isna()` "not null" `notnull()`, `notna()`:

```
lwgeom=# ALTER TABLE my_table ALTER COLUMN geom SET not null;  
ALTER TABLE
```

`blubb`, `geometry` columnen NULL sein dürfen. Folgendes SQL Statement führt zu einer Fehlermeldung:

6.3

3D 4D , 2D OpenGIS ST_AsText() ST_AsBinary() ST_Force2D() .

```
UPDATE mytable SET geom = ST_Force2D(geom);
VACUUM FULL ANALYZE mytable;
```

```
AddGeometryColumn('','geometry_columns', geometry_columns
geometry_columns
geometry_columns).
```

1. 删除空值: 使用 `WHERE the_geom IS NOT NULL` 来删除空值。

Chapter 7

PostGIS Reference

PostGIS is a spatial database system that provides the ability to store and retrieve spatial data. It is built on top of PostgreSQL and provides a rich set of spatial data types and functions.



Note
PostGIS is a spatial database system that provides the ability to store and retrieve spatial data. It is built on top of PostgreSQL and provides a rich set of spatial data types and functions. The Spatial Type (ST) functions are used to create and manipulate spatial data. The ST_ functions are used to perform spatial operations on spatial data.

7.1 PostgreSQL PostGIS Geometry/Geography/Box

7.1.1 box2d

box2d — The type representing a 2-dimensional bounding box.

box3d is a 3-dimensional bounding box type. It is used to represent a 3D bounding box. The ST_3DExtent function is used to create a box3d object from a 3D geometry.

The representation contains the values xmin, ymin, xmax, ymax. These are the minimum and maximum values of the X and Y extents.

box2d objects have a text representation which looks like BOX(1 2,5 6).

box3d	
geometry	

几何

Section 13.7

7.1.2 box3d

box3d — The type representing a 3-dimensional bounding box.

几何

box3d 数据类型由 6 个浮点数字段组成，在 postgis 中由 ST_3DExtent 函数 box3d 函数返回。

The representation contains the values xmin, ymin, zmin, xmax, ymax, zmax. These are the minimum and maximum values of the X, Y and Z extents.

box3d objects have a text representation which looks like BOX3D(1 2 3,5 6 5).

几何

几何数据类型由 6 个浮点数字段组成。

几何	几何
box	几何
box2d	几何
geometry	几何

几何

Section 13.7

7.1.3 geometry

geometry — geography 数据类型由 6 个浮点数字段组成。

几何

geography 数据类型由 6 个浮点数字段组成。

All spatial operations on geometry use the units of the Spatial Reference System the geometry is in.

几何

几何数据类型由 6 个浮点数字段组成。

geometry	geometry
box	geometry
box2d	geometry
box3d	geometry
bytea	geometry
geography	geometry
text	geometry

几何

Section 4.1, Section 4.3

7.1.4 geometry_dump

geometry_dump — A composite type used to describe the parts of complex geometry.

几何

geometry_dump is a composite data type containing the fields:

- geom - a geometry representing a component of the dumped geometry. The geometry type depends on the originating function.
- path[] - an integer array that defines the navigation path within the dumped geometry to the geom component. The path array is 1-based (i.e. path[1] is the first element.)

It is used by the ST_Dump* family of functions as an output type to explode a complex geometry into its constituent parts.

几何

Section 13.6

7.1.5 geography

geography — The type representing spatial features with geodetic (ellipsoidal) coordinate systems.

几何

geography 地理信息系统的几何类型。

Spatial operations on the geography type provide more accurate results by taking the ellipsoidal model into account.

地理信息

地理信息系统的几何类型。

geometry	geometry
	geometry

注意

Section 4.3, Section 4.3

7.2 安装与使用

7.2.1 AddGeometryColumn

AddGeometryColumn — 添加几何列。

Synopsis

text **AddGeometryColumn**(varchar table_name, varchar column_name, integer srid, varchar type, integer dimension, boolean use_typmod=true);
text **AddGeometryColumn**(varchar schema_name, varchar table_name, varchar column_name, integer srid, varchar type, integer dimension, boolean use_typmod=true);
text **AddGeometryColumn**(varchar catalog_name, varchar schema_name, varchar table_name, varchar column_name, integer srid, varchar type, integer dimension, boolean use_typmod=true);

注意

schema_name 是 schema 的名称。srid 是 SRID 值。type 是几何类型，可以是 'POINT'、'POLYGON' 或 'MULTILINESTRING'。search_path 是搜索路径。SRID 是 SRID 值，可以是 0 或 4326。



Note

注意: 2.0.0 版本中，geometry_columns 表中的 srid 列是 NULL。在 PostgreSQL 12 中，WGS84 POINT 类型被定义为 geometry(Point,4326)。在 2.0.0 版本中，use_typmod 参数是可选的，默认为 true。



Note

注意: 2.0.0 版本中，geometry_columns 表中的 typmod 列是 NULL。在 PostgreSQL 12 中，typmod 参数是可选的，默认为 true。Section 4.6.3 中详细描述了 typmod 参数。

- ✔ This method implements the [OGC Simple Features Implementation Specification for SQL 1.1](#).
- ✔ This function supports 3d and will not drop the z-index.
- ✔ This method supports Circular Strings and Curves.

2.0.0 **use_typmod**. **typmod**.

```
-- Create schema to hold data
CREATE SCHEMA my_schema;
-- Create a new simple PostgreSQL table
CREATE TABLE my_schema.my_spatial_table (id serial);

-- Describing the table shows a simple table with a single "id" column.
postgis=# \d my_schema.my_spatial_table
                                Table "my_schema.my_spatial_table"
Column | Type      | Modifiers
-----+-----+-----
id     | integer   | not null default nextval('my_schema.my_spatial_table_id_seq'::regclass)

-- Add a spatial column to the table
SELECT AddGeometryColumn ('my_schema','my_spatial_table','geom',4326,'POINT',2);

-- Add a point using the old constraint based behavior
SELECT AddGeometryColumn ('my_schema','my_spatial_table','geom_c',4326,'POINT',2, false);

--Add a curvepolygon using old constraint behavior
SELECT AddGeometryColumn ('my_schema','my_spatial_table','geomcp_c',4326,'CURVEPOLYGON',2, false);

-- Describe the table again reveals the addition of a new geometry columns.
\d my_schema.my_spatial_table
                                addgeometrycolumn
-----+-----+-----
my_schema.my_spatial_table.geomcp_c SRID:4326 TYPE:CURVEPOLYGON DIMS:2
(1 row)

                                Table "my_schema.my_spatial_table"
Column | Type      | Modifiers
-----+-----+-----
id     | integer   | not null default nextval('my_schema.
my_spatial_table_id_seq'::regclass)
geom    | geometry(Point,4326) |
geom_c  | geometry  |
geomcp_c | geometry  |
Check constraints:
"enforce_dims_geom_c" CHECK (st_ndims(geom_c) = 2)
"enforce_dims_geomcp_c" CHECK (st_ndims(geomcp_c) = 2)
"enforce_geotype_geom_c" CHECK (geometrytype(geom_c) = 'POINT'::text OR geom_c IS NULL)
"enforce_geotype_geomcp_c" CHECK (geometrytype(geomcp_c) = 'CURVEPOLYGON'::text OR
geomcp_c IS NULL)
"enforce_srid_geom_c" CHECK (st_srid(geom_c) = 4326)
"enforce_srid_geomcp_c" CHECK (st_srid(geomcp_c) = 4326)

-- geometry_columns view also registers the new columns --
```

```
SELECT f_geometry_column As col_name, type, srid, coord_dimension As ndims
FROM geometry_columns
WHERE f_table_name = 'my_spatial_table' AND f_table_schema = 'my_schema';
```

col_name	type	srid	ndims
geom	Point	4326	2
geom_c	Point	4326	2
geomcp_c	CurvePolygon	4326	2



DropGeometryColumn, DropGeometryTable, Section 4.6.2, Section 4.6.3

7.2.2 DropGeometryColumn

DropGeometryColumn — □□□□□□□□□□□□□□□□□□□□.

Synopsis

```
text DropGeometryColumn(varchar table_name, varchar column_name);
text DropGeometryColumn(varchar schema_name, varchar table_name, varchar column_name);
text DropGeometryColumn(varchar catalog_name, varchar schema_name, varchar table_name, var-
char column_name);
```



```

XXXXXXXXXXXXXXXXXXXXXXXXXXXX. schema_name X geometry_columns XXXXXXXXXXXXXXXXXXXX f_table_schema
XXXXXXXXXXXXXXXXXXXXXXXXXXXX.

```

- ✔ This method implements the [OGC Simple Features Implementation Specification for SQL 1.1](#).
- ✔ This function supports 3d and will not drop the z-index.
- ✔ This method supports Circular Strings and Curves.



Note

2.0.0. geometry_columns
 ALTER TABLE geometry_columns
 .



```
SELECT DropGeometryColumn ('my_schema','my_spatial_table','geom');
-----RESULT output -----
dropgeometrycolumn
-----
my_schema.my_spatial_table.geom effectively removed.

-- In PostGIS 2.0+ the above is also equivalent to the standard
-- the standard alter table. Both will deregister from geometry_columns
ALTER TABLE my schema.my spatial table DROP column geom;
```

❏

[AddGeometryColumn](#), [DropGeometryTable](#), Section 4.6.2

7.2.3 DropGeometryTable

DropGeometryTable — 删除 geometry_columns 表。

Synopsis

```
boolean DropGeometryTable(varchar table_name);
boolean DropGeometryTable(varchar schema_name, varchar table_name);
boolean DropGeometryTable(varchar catalog_name, varchar schema_name, varchar table_name);
```

❏

geometry_columns 表。: 当前 schema 的 pgSQL current_schema() 函数。



Note

PostGIS 2.0.0 版本。 geometry_columns 表。 DROP TABLE 语句。

❏

```
SELECT DropGeometryTable ('my_schema','my_spatial_table');
----RESULT output ---
my_schema.my_spatial_table dropped.

-- The above is now equivalent to --
DROP TABLE my_schema.my_spatial_table;
```

❏

[AddGeometryColumn](#), [DropGeometryColumn](#), Section 4.6.2

7.2.4 Find_SRID

Find_SRID — Returns the SRID defined for a geometry column.

Synopsis

```
integer Find_SRID(varchar a_schema_name, varchar a_table_name, varchar a_geomfield_name);
```


geometry_columns 表。 geometry_columns 表。
geometry_columns 表。
geometry_columns 表。

1.4.0 国际化。

2.0.0 国际化。 use_typed
国际化, 国际化。

2.0.0 国际化, use_typed
国际化。

国际化

```
CREATE TABLE public.myspatial_table(gid serial, geom geometry);
INSERT INTO myspatial_table(geom) VALUES(ST_GeomFromText('LINESTRING(1 2, 3 4)',4326) );
-- This will now use typ modifiers.  For this to work, there must exist data
SELECT Populate_Geometry_Columns('public.myspatial_table'::regclass);
```

populate_geometry_columns

1

\d myspatial_table

Table "public.myspatial_table"			
Column	Type		Modifiers
-----+-----+-----			
gid	integer	not null default nextval('myspatial_table_gid_seq'::	↵
	regclass)		
geom	geometry(LineString,4326)		

-- This will change the geometry columns to use constraints if they are not typed or have
constraints already. ↵

```
--For this to work, there must exist data
CREATE TABLE public.myspatial_table_cs(gid serial, geom geometry);
INSERT INTO myspatial_table_cs(geom) VALUES(ST_GeomFromText('LINESTRING(1 2, 3 4)',4326) );
SELECT Populate_Geometry_Columns('public.myspatial_table_cs'::regclass, false);
populate_geometry_columns
```

populate_geometry_columns

1

\d myspatial_table_cs

Table "public.myspatial_table_cs"			
Column	Type		Modifiers
-----+-----+-----			
gid	integer	not null default nextval('myspatial_table_cs_gid_seq'::regclass)	
geom	geometry		

```
Check constraints:
    "enforce_dims_geom" CHECK (st_ndims(geom) = 2)
    "enforce_geotype_geom" CHECK (geometrytype(geom) = 'LINESTRING'::text OR geom IS NULL)
    "enforce_srid_geom" CHECK (st_srid(geom) = 4326)
```

7.2.6 UpdateGeometrySRID

UpdateGeometrySRID — Updates the SRID of all features in a geometry column, and the table meta-data.

Synopsis

```
text UpdateGeometrySRID(varchar table_name, varchar column_name, integer srid);
text UpdateGeometrySRID(varchar schema_name, varchar table_name, varchar column_name, integer srid);
text UpdateGeometrySRID(varchar catalog_name, varchar schema_name, varchar table_name, varchar column_name, integer srid);
```

更新

`UpdateGeometrySRID`, `geometry_columns` 表中的 `srid` 列使用 `SRID` 格式。注意：在 schema-aware postgres 安装中，`current_schema()` 函数



This function supports 3d and will not drop the z-index.



This method supports Circular Strings and Curves.

更新

Insert geometries into roads table with a SRID set already using **EWKT format**:

```
COPY roads (geom) FROM STDIN;
SRID=4326;LINESTRING(0 0, 10 10)
SRID=4326;LINESTRING(10 10, 15 0)
\.
```

更新 `SRID` 列中的 `SRID` 为 4326 使用 `UpdateGeometrySRID`:

```
SELECT UpdateGeometrySRID('roads','geom',4326);
```

更新 DDL 中的 `SRID`:

```
ALTER TABLE roads
  ALTER COLUMN geom TYPE geometry(MULTILINESTRING, 4326)
  USING ST_SetSRID(geom,4326);
```

更新 `SRID` 列中的 `SRID` 为 3857 使用 `ST_Transform` 函数。注意：PostGIS 3.5.0 之前版本中，`ST_Transform` 函数不支持 `SRID` 列的更新。

```
ALTER TABLE roads
  ALTER COLUMN geom TYPE geometry(MULTILINESTRING, 3857) USING ST_Transform(ST_SetSRID(geom, 4326),3857) ;
```

更新

UpdateRasterSRID, ST_SetSRID, ST_Transform

7.3 几何构造器 (constructor)

7.3.1 ST_Collect

ST_Collect — Creates a GeometryCollection or Multi* geometry from a set of geometries.

Synopsis

```
geometry ST_Collect(geometry g1, geometry g2);
geometry ST_Collect(geometry[] g1_array);
geometry ST_Collect(geometry set g1field);
```

⚠️

Collects geometries into a geometry collection. The result is either a Multi* or a GeometryCollection, depending on whether the input geometries have the same or different types (homogeneous or heterogeneous). The input geometries are left unchanged within the collection.

Variant 1: accepts two input geometries

Variant 2: accepts an array of geometries

Variant 3: aggregate function accepting a rowset of geometries.



Note

If any of the input geometries are collections (Multi* or GeometryCollection) ST_Collect returns a GeometryCollection (since that is the only type which can contain nested collections). To prevent this, use **ST_Dump** in a subquery to expand the input collections to their atomic elements (see example below).



Note

ST_Collect and **ST_Union** appear similar, but in fact operate quite differently. ST_Collect aggregates geometries into a collection without changing them in any way. ST_Union geometrically merges geometries where they overlap, and splits linestrings at intersections. It may return single geometries when it dissolves boundaries.

1.4.0 新增。ST_MakeLine 新增。ST_MakeLine 新增。



This function supports 3d and will not drop the z-index.



This method supports Circular Strings and Curves.

🔗: **XLink** 🔗

Collect 2D points.

```
SELECT ST_AsText( ST_Collect( ST_GeomFromText('POINT(1 2)'),
                          ST_GeomFromText('POINT(-2 3)') ));
```

```
st_astext
-----
MULTIPOINT((1 2),(-2 3))
```

Collect 3D points.

```
SELECT ST_AsEWKT( ST_Collect( ST_GeomFromEWKT('POINT(1 2 3)'),
                          ST_GeomFromEWKT('POINT(1 2 4)') ));
```

```
st_asewkt
-----
MULTIPOINT(1 2 3,1 2 4)
```

Collect curves.

```
SELECT ST_AsText( ST_Collect( 'CIRCULARSTRING(220268 150415,220227 150505,220227 150406)',
                             'CIRCULARSTRING(220227 150406,220227 150407,220227 150406)') );

          st_astext
-----
MULTICURVE(CIRCULARSTRING(220268 150415,220227 150505,220227 150406),
CIRCULARSTRING(220227 150406,220227 150407,220227 150406))
```

例: 收集曲线

Using an array constructor for a subquery.

```
SELECT ST_Collect( ARRAY( SELECT geom FROM sometable ) );
```

Using an array constructor for values.

```
SELECT ST_AsText( ST_Collect(
    ARRAY[ ST_GeomFromText('LINESTRING(1 2, 3 4)'),
           ST_GeomFromText('LINESTRING(3 4, 4 5)') ] ) ) As wktcollect;

--wkt collect --
MULTILINESTRING((1 2,3 4),(3 4,4 5))
```

例: 收集值

Creating multiple collections by grouping geometries in a table.

```
SELECT stusps, ST_Collect(f.geom) as geom
  FROM (SELECT stusps, (ST_Dump(geom)).geom As geom
        FROM
        somestatetable ) As f
 GROUP BY stusps
```

例

ST_Dump, ST_AsBinary

7.3.2 ST_LineFromMultiPoint

ST_LineFromMultiPoint — 从多点点集创建线。

Synopsis

geometry **ST_LineFromMultiPoint**(geometry aMultiPoint);

例

从多点点集创建线。

Use **ST_MakeLine** to create lines from Point or LineString inputs.



This function supports 3d and will not drop the z-index.

例

将MULTIPOINT(1 2 3, 4 5 6, 7 8 9)转换为LINESTRING。

```
SELECT ST_AsEWKT( ST_LineFromMultiPoint('MULTIPOINT(1 2 3, 4 5 6, 7 8 9)') );

--result--
LINESTRING(1 2 3,4 5 6,7 8 9)
```

例

[ST_AsEWKT](#), [ST_AsKML](#)

7.3.3 ST_MakeEnvelope

ST_MakeEnvelope — 根据给定的边界框和SRID创建几何图形。 指定的SRID与SRS相关联。

Synopsis

geometry **ST_MakeEnvelope**(float xmin, float ymin, float xmax, float ymax, integer srid=unknown);

例

根据给定的边界框和SRID创建几何图形。 指定的SRID与SRS相关联。

1.5 创建几何图形。

例: 2.0 指定的SRID (envelope) 创建几何图形。

例: 创建几何图形

```
SELECT ST_AsText( ST_MakeEnvelope(10, 10, 11, 11, 4326) );

st_asewkt
-----
POLYGON((10 10, 10 11, 11 11, 11 10, 10 10))
```

例

[ST_MakePoint](#), [ST_MakePoint](#), [ST_Point](#), [ST_SRID](#)

7.3.4 ST_MakeLine

ST_MakeLine — 根据给定的点创建几何图形。

Synopsis

```
geometry ST_MakeLine(geometry geom1, geometry geom2);
geometry ST_MakeLine(geometry[] geoms_array);
geometry ST_MakeLine(geometry set geoms);
```

概要

Creates a LineString containing the points of Point, MultiPoint, or LineString geometries. Other geometry types cause an error.

Variant 1: accepts two input geometries

Variant 2: accepts an array of geometries

Variant 3: aggregate function accepting a rowset of geometries. To ensure the order of the input geometries use ORDER BY in the function call, or a subquery with an ORDER BY clause.

Repeated nodes at the beginning of input LineStrings are collapsed to a single point. Repeated points in Point and MultiPoint inputs are not collapsed. **ST_RemoveRepeatedPoints** can be used to collapse repeated points from the output LineString.



This function supports 3d and will not drop the z-index.

2.0.0 新增对 3D 的支持，不会丢弃 z 索引。

2.0.0 新增对 3D 的支持，不会丢弃 z 索引。

1.4.0 新增对 3D 的支持。与 ST_MakeLine 类似，但不会丢弃 z 索引。与 ST_MakeLine 类似，但不会丢弃 z 索引。

用法: 创建线

Create a line composed of two points.

```
SELECT ST_AsText( ST_MakeLine(ST_Point(1,2), ST_Point(3,4)) );
```

```
      st_astext
-----
LINESTRING(1 2,3 4)
```

3D 支持 2 维 BOX3D 支持。

```
SELECT ST_AsEWKT( ST_MakeLine(ST_MakePoint(1,2,3), ST_MakePoint(3,4,5)) );
```

```
      st_asewkt
-----
LINESTRING(1 2 3,3 4 5)
```

用法, 创建线

```
select ST_AsText( ST_MakeLine( 'LINESTRING(0 0, 1 1)', 'LINESTRING(2 2, 3 3)' ) );
```

```
      st_astext
-----
LINESTRING(0 0,1 1,2 2,3 3)
```

名称: ST_MakeLine

Create a line from an array formed by a subquery with ordering.

```
SELECT ST_MakeLine( ARRAY( SELECT ST_Centroid(geom) FROM visit_locations ORDER BY visit_time) );
```

Create a 3D line from an array of 3D points

```
SELECT ST_AsEWKT( ST_MakeLine(
    ARRAY[ ST_MakePoint(1,2,3), ST_MakePoint(3,4,5), ST_MakePoint(6,6,6) ] ) );

          st_asewkt
-----
LINESTRING(1 2 3,3 4 5,6 6 6)
```

名称: ST_MakeLine

给定 GPS 点集，ST_MakeLine 函数返回由这些点组成的 LineString。GPS 点集可以是点数组或子查询结果。

Using aggregate ORDER BY provides a correctly-ordered LineString.

```
SELECT gps.track_id, ST_MakeLine(gps.geom ORDER BY gps_time) As geom
FROM gps_points As gps
GROUP BY track_id;
```

Prior to PostgreSQL 9, ordering in a subquery can be used. However, sometimes the query plan may not respect the order of the subquery.

```
SELECT gps.track_id, ST_MakeLine(gps.geom) As geom
FROM ( SELECT track_id, gps_time, geom
        FROM gps_points ORDER BY track_id, gps_time ) As gps
GROUP BY track_id;
```

名称:

[ST_RemoveRepeatedPoints](#), [ST_AsText](#), [ST_GeomFromText](#), [ST_MakePoint](#)

7.3.5 ST_MakePoint

ST_MakePoint — Creates a 2D, 3DZ or 4D Point.

Synopsis

geometry **ST_MakePoint**(float x, float y);

geometry **ST_MakePoint**(float x, float y, float z);

geometry **ST_MakePoint**(float x, float y, float z, float m);

☐☐

Creates a 2D XY, 3D XYZ or 4D XYZM Point geometry. Use **ST_MakePointM** to make points with XYM coordinates.

Use **ST_SetSRID** to specify a SRID for the created point.

While not OGC-compliant, ST_MakePoint is faster and more precise than **ST_GeomFromText** and **ST_PointFromText**. It is also easier to use for numeric coordinate values.



Note

For geodetic coordinates, X is longitude and Y is latitude



Note

The functions **ST_Point**, **ST_PointZ**, **ST_PointM**, and **ST_PointZM** can be used to create points with a given SRID.



This function supports 3d and will not drop the z-index.

☐☐

```
-- Create a point with unknown SRID
SELECT ST_MakePoint(-71.1043443253471, 42.3150676015829);

-- Create a point in the WGS 84 geodetic CRS
SELECT ST_SetSRID(ST_MakePoint(-71.1043443253471, 42.3150676015829),4326);

-- Create a 3D point (e.g. has altitude)
SELECT ST_MakePoint(1, 2,1.5);

-- Get z of point
SELECT ST_Z(ST_MakePoint(1, 2,1.5));
result
-----
1.5
```

☐☐

ST_GeomFromText, **ST_PointFromText**, **ST_SetSRID**, **ST_MakePointM**, **ST_Point**, **ST_PointZ**, **ST_PointM**, **ST_PointZM**

7.3.6 ST_MakePointM

ST_MakePointM — x, y 浮点型, 浮点型, 浮点型。

Synopsis

geometry **ST_MakePointM**(float x, float y, float m);

☐☐

Creates a point with X, Y and M (measure) ordinates. Use **ST_MakePoint** to make points with XY, XYZ, or XYZM coordinates.

Use **ST_SetSRID** to specify a SRID for the created point.



Note

For geodetic coordinates, X is longitude and Y is latitude



Note

The functions **ST_PointM**, and **ST_PointZM** can be used to create points with an M value and a given SRID.

☐☐



Note

ST_AsEWKT is used for text output because **ST_AsText** does not support M values.

Create point with unknown SRID.

```
SELECT ST_AsEWKT( ST_MakePointM(-71.1043443253471, 42.3150676015829, 10) );
```

```

                                st_asewkt
-----
POINTM(-71.1043443253471 42.3150676015829 10)
```

x, y 经纬度坐标。

```
SELECT ST_AsEWKT( ST_SetSRID( ST_MakePointM(-71.104, 42.315, 10), 4326));
```

```

                                st_asewkt
-----
SRID=4326;POINTM(-71.104 42.315 10)
```

Get measure of created point.

```
SELECT ST_M( ST_MakePointM(-71.104, 42.315, 10) );
```

```

result
-----
10
```

☐☐

ST_MakePoint, **ST_SetSRID**, **ST_PointM**, **ST_PointZM**

7.3.7 ST_MakePolygon

ST_MakePolygon — Creates a Polygon from a shell and optional list of holes.

Synopsis

```
geometry ST_MakePolygon(geometry linestring);
```

```
geometry ST_MakePolygon(geometry outerlinestring, geometry[] interiorlinestrings);
```

Parameters

outerlinestring (shell) **LINESTRING**. **LINESTRING**.

Variant 1: Accepts one shell **LineString**.

Variant 2: Accepts a shell **LineString** and an array of inner (hole) **LineStrings**. A geometry array can be constructed using the PostgreSQL `array_agg()`, `ARRAY[]` or `ARRAY()` constructs.



Note

For more information, see [ST_LineMerge](#) and [ST_Dump](#).



This function supports 3d and will not drop the z-index.

Usage

```
SELECT ST_MakePolygon(ST_GeomFromText('LINESTRING(75 29,77 29,77 29, 75 29)'));
```

```
SELECT ST_MakePolygon( ST_GeomFromText('LINESTRING(75 29,77 29,77 29, 75 29)'));
```

Create a Polygon from an open **LineString**, using [ST_StartPoint](#) and [ST_AddPoint](#) to close it.

```
SELECT ST_MakePolygon( ST_AddPoint(foo.open_line, ST_StartPoint(foo.open_line)) )
FROM (
  SELECT ST_GeomFromText('LINESTRING(75 29,77 29,77 29, 75 29)') As open_line) As foo;
```

```
SELECT ST_AsEWKT( ST_MakePolygon( 'LINESTRING(75.15 29.53 1,77 29 1,77.6 29.5 1, 75.15 29.53 1)') );
```

```
SELECT ST_AsEWKT( ST_MakePolygon( 'LINESTRING(75.15 29.53 1,77 29 1,77.6 29.5 1, 75.15 29.53 1)') );
```

```
st_asewkt
```

```
POLYGON((75.15 29.53 1,77 29 1,77.6 29.5 1,75.15 29.53 1))
```

Create a Polygon from a **LineString** with measures

```
SELECT ST_AsEWKT( ST_MakePolygon( 'LINESTRINGM(75.15 29.53 1,77 29 1,77.6 29.5 2, 75.15 29.53 2)') );
```

```
st_asewkt
```

```
POLYGONM((75.15 29.53 1,77 29 1,77.6 29.5 2,75.15 29.53 2))
```

注意: 使用 `ST_MakePolygon` 时

必须使用 `ST_IsClosed` 函数。

```
SELECT ST_MakePolygon( ST_ExteriorRing( ST_Buffer(ring.line,10)),
    ARRAY[ ST_Translate(ring.line, 1, 1),
          ST_ExteriorRing(ST_Buffer(ST_Point(20,20),1)) ]
    )
FROM (SELECT ST_ExteriorRing(
    ST_Buffer(ST_Point(10,10),10,10)) AS line ) AS ring;
```

Create a set of province boundaries with holes representing lakes. The input is a table of province Polygons/MultiPolygons and a table of water linestrings. Lines forming lakes are determined by using [ST_IsClosed](#). The province linework is extracted by using [ST_Boundary](#). As required by `ST_MakePolygon`, the boundary is forced to be a single LineString by using [ST_LineMerge](#). (However, note that if a province has more than one region or has islands this will produce an invalid polygon.) Using a LEFT JOIN ensures all provinces are included even if they have no lakes.



Note

NULL 值使用 `ST_MakePolygon` 时，如果 `array_agg` 返回 NULL，则使用 `CASE` 语句。

```
SELECT p.gid, p.province_name,
    CASE WHEN array_agg(w.geom) IS NULL
    THEN p.geom
    ELSE ST_MakePolygon( ST_LineMerge(ST_Boundary(p.geom)),
        array_agg(w.geom)) END
FROM
    provinces p LEFT JOIN waterlines w
        ON (ST_Within(w.geom, p.geom) AND ST_IsClosed(w.geom))
GROUP BY p.gid, p.province_name, p.geom;
```

Another technique is to utilize a correlated subquery and the `ARRAY()` constructor that converts a row set to an array.

```
SELECT p.gid, p.province_name,
    CASE WHEN EXISTS( SELECT w.geom
        FROM waterlines w
        WHERE ST_Within(w.geom, p.geom)
        AND ST_IsClosed(w.geom))
    THEN ST_MakePolygon(
        ST_LineMerge(ST_Boundary(p.geom)),
        ARRAY( SELECT w.geom
            FROM waterlines w
            WHERE ST_Within(w.geom, p.geom)
            AND ST_IsClosed(w.geom)))
    ELSE p.geom
    END AS geom
FROM provinces p;
```

函数

[ST_BuildArea](#) [ST_Polygon](#)

7.3.8 ST_Point

`ST_Point` — Creates a Point with X, Y and SRID values.

Synopsis

geometry **ST_Point**(float x, float y);

geometry **ST_Point**(float x, float y, integer srid=unknown);

📄

Returns a Point with the given X and Y coordinate values. This is the SQL-MM equivalent for **ST_MakePoint** that takes just X and Y.



Note

For geodetic coordinates, X is longitude and Y is latitude

Enhanced: 3.2.0 srid as an extra optional argument was added. Older installs require combining with ST_SetSRID to mark the srid on the geometry.



This method implements the SQL/MM specification. SQL-MM 3: 6.1.2

📄: 📄

```
SELECT ST_Point( -71.104, 42.315);
```

Creating a point with SRID specified:

```
SELECT ST_Point( -71.104, 42.315, 4326);
```

Alternative way of specifying SRID:

```
SELECT ST_SetSRID( ST_Point( -71.104, 42.315), 4326);
```

📄: 📄

Create **geography** points using the :: cast syntax:

```
SELECT ST_Point( -71.104, 42.315, 4326)::geography;
```

Pre-PostGIS 3.2 code, using CAST:

```
SELECT CAST( ST_SetSRID(ST_Point( -71.104, 42.315), 4326) AS geography);
```

If the point coordinates are not in a geodetic coordinate system (such as WGS84), then they must be reprojected before casting to a geography. In this example a point in Pennsylvania State Plane feet (SRID 2273) is projected to WGS84 (SRID 4326).

```
SELECT ST_Transform( ST_Point( 3637510, 3014852, 2273), 4326)::geography;
```

📄

ST_MakePoint, **ST_PointZ**, **ST_PointM**, **ST_PointZM**, **ST_SetSRID**, **ST_Transform**

7.3.9 ST_PointZ

ST_PointZ — Creates a Point with X, Y, Z and SRID values.

Synopsis

geometry **ST_PointZ**(float x, float y, float z, integer srid=unknown);

返回

返回与 ST_Point 相同的类型。 ST_MakePoint 遵循 OGC 规范。

Enhanced: 3.2.0 srid as an extra optional argument was added. Older installs require combining with ST_SetSRID to mark the srid on the geometry.

示例

```
SELECT ST_PointZ(-71.104, 42.315, 3.4, 4326)
```

```
SELECT ST_PointZ(-71.104, 42.315, 3.4, srid => 4326)
```

```
SELECT ST_PointZ(-71.104, 42.315, 3.4)
```

参见

[ST_MakePoint](#), [ST_PointFromText](#), [ST_SetSRID](#), [ST_MakePointM](#)

7.3.10 ST_PointM

ST_PointM — Creates a Point with X, Y, M and SRID values.

Synopsis

geometry **ST_PointM**(float x, float y, float m, integer srid=unknown);

返回

返回与 ST_Point 相同的类型。 ST_MakePoint 遵循 OGC 规范。

Enhanced: 3.2.0 srid as an extra optional argument was added. Older installs require combining with ST_SetSRID to mark the srid on the geometry.

示例

```
SELECT ST_PointM(-71.104, 42.315, 3.4, 4326)
```

```
SELECT ST_PointM(-71.104, 42.315, 3.4, srid => 4326)
```

```
SELECT ST_PointM(-71.104, 42.315, 3.4)
```

☐☐

[ST_MakePoint](#), [ST_PointFromText](#), [ST_SetSRID](#), [ST_MakePointM](#)

7.3.11 ST_PointZM

ST_PointZM — Creates a Point with X, Y, Z, M and SRID values.

Synopsis

geometry **ST_PointZM**(float x, float y, float z, float m, integer srid=unknown);

☐☐

☐☐☐☐☐☐☐☐ ST_Point ☐☐☐☐☐☐☐. ST_MakePoint ☐☐☐☐ OGC ☐☐☐☐☐☐.

Enhanced: 3.2.0 srid as an extra optional argument was added. Older installs require combining with ST_SetSRID to mark the srid on the geometry.

☐☐

```
SELECT ST_PointZM(-71.104, 42.315, 3.4, 4.5, 4326)
```

```
SELECT ST_PointZM(-71.104, 42.315, 3.4, 4.5, srid => 4326)
```

```
SELECT ST_PointZM(-71.104, 42.315, 3.4, 4.5)
```

☐☐

[ST_MakePoint](#), [ST_Point](#), [ST_PointM](#), [ST_PointZ](#), [ST_SetSRID](#)

7.3.12 ST_Polygon

ST_Polygon — Creates a Polygon from a LineString with a specified SRID.

Synopsis

geometry **ST_Polygon**(geometry lineString, integer srid);

☐☐

Returns a polygon built from the given LineString and sets the spatial reference system from the srid.

ST_Polygon is similar to [ST_MakePolygon](#) Variant 1 with the addition of setting the SRID.

, [ST_MakePoint](#), [ST_SetSRID](#)

**Note**

此函数在 PostGIS 3.5.7 版本中引入。 它依赖于 `ST_LineMerge` 和 `ST_Dump` 函数。



This method implements the [OGC Simple Features Implementation Specification for SQL 1.1](#).



This method implements the SQL/MM specification. SQL-MM 3: 8.3.2



This function supports 3d and will not drop the z-index.

创建

Create a 2D polygon.

```
SELECT ST_AsText( ST_Polygon('LINESTRING(75 29, 77 29, 77 29, 75 29)::geometry, 4326) );

-- result --
POLYGON((75 29, 77 29, 77 29, 75 29))
```

Create a 3D polygon.

```
SELECT ST_AsEWKT( ST_Polygon( ST_GeomFromEWKT('LINESTRING(75 29 1, 77 29 2, 77 29 3, 75 29 1)'), 4326) );

-- result --
SRID=4326;POLYGON((75 29 1, 77 29 2, 77 29 3, 75 29 1))
```

函数

`ST_AsEWKT`, `ST_AsText`, `ST_GeomFromEWKT`, `ST_GeomFromText`, `ST_LineMerge`, `ST_MakePolygon`

7.3.13 ST_TileEnvelope

`ST_TileEnvelope` — Creates a rectangular Polygon in [Web Mercator](#) (SRID:3857) using the [XYZ tile system](#).

Synopsis

geometry **ST_TileEnvelope**(integer tileZoom, integer tileX, integer tileY, geometry bounds=SRID=3857;LINESTRING(20037508.342789 -20037508.342789,20037508.342789 20037508.342789), float margin=0.0);

描述

Creates a rectangular Polygon giving the extent of a tile in the [XYZ tile system](#). The tile is specified by the zoom level Z and the XY index of the tile in the grid at that level. Can be used to define the tile bounds required by `ST_AsMVTGeom` to convert geometry into the MVT tile coordinate space.

By default, the tile envelope is in the [Web Mercator](#) coordinate system (SRID:3857) using the standard range of the Web Mercator system (-20037508.342789, 20037508.342789). This is the most common coordinate system used for MVT tiles. The optional bounds parameter can be used to generate tiles in

any coordinate system. It is a geometry that has the SRID and extent of the "Zoom Level zero" square within which the XYZ tile system is inscribed.

The optional `margin` parameter can be used to expand a tile by the given percentage. E.g. `margin=0.125` expands the tile by 12.5%, which is equivalent to `buffer=512` when the tile extent size is 4096, as used in [ST_AsMVTGeom](#). This is useful to create a tile buffer to include data lying outside of the tile's visible area, but whose existence affects the tile rendering. For example, a city name (a point) could be near an edge of a tile, so its label should be rendered on two tiles, even though the point is located in the visible area of just one tile. Using expanded tiles in a query will include the city point in both tiles. Use a negative value to shrink the tile instead. Values less than -0.5 are prohibited because that would eliminate the tile completely. Do not specify a margin when using with `ST_AsMVTGeom`. See the example for [ST_AsMVT](#).

例: 2.0.0 国际化 SRID 国际化.

2.1.0 国际化.

例: 国际化

```
SELECT ST_AsText( ST_TileEnvelope(2, 1, 1) );
```

```
st_astext
-----
POLYGON((-10018754.1713945 0,-10018754.1713945 10018754.1713945,0 10018754.1713945,0  ←
0,-10018754.1713945 0))
```

```
SELECT ST_AsText( ST_TileEnvelope(3, 1, 1, ST_MakeEnvelope(-180, -90, 180, 90, 4326) ) );
```

```
st_astext
-----
POLYGON((-135 45,-135 67.5,-90 67.5,-90 45,-135 45))
```

例

[ST_MakeEnvelope](#)

7.3.14 ST_HexagonGrid


`ST_HexagonGrid` — Returns a set of hexagons and cell indices that completely cover the bounds of the geometry argument.

Synopsis

setof record **ST_HexagonGrid**(float8 size, geometry bounds);


例

Starts with the concept of a hexagon tiling of the plane. (Not a hexagon tiling of the globe, this is not the [H3](#) tiling scheme.) For a given planar SRS, and a given edge size, starting at the origin of the SRS, there is one unique hexagonal tiling of the plane, `Tiling(SRS, Size)`. This function answers the question: what hexagons in a given `Tiling(SRS, Size)` overlap with a given bounds.



The SRS for the output hexagons is the SRS provided by the bounds geometry.

Doubling or tripling the edge size of the hexagon generates a new parent tiling that fits with the origin tiling. Unfortunately, it is not possible to generate parent hexagon tilings that the child tiles perfectly fit inside.



2.1.0 教程。


图: 教程

To do a point summary against a hexagonal tiling, generate a hexagon grid using the extent of the points as the bounds, then spatially join to that grid.

```
SELECT COUNT(*), hexes.geom
FROM
  ST_HexagonGrid(
    10000,
    ST_SetSRID(ST_EstimatedExtent('pointtable', 'geom'), 3857)
  ) AS hexes
  INNER JOIN
    pointtable AS pts
  ON ST_Intersects(pts.geom, hexes.geom)
GROUP BY hexes.geom;
```

图: 教程

If we generate a set of hexagons for each polygon boundary and filter out those that do not intersect their hexagons, we end up with a tiling for each polygon.



Tiling states results in a hexagon coverage of each state, and multiple hexagons overlapping at the borders between states.



Note

The LATERAL keyword is implied for set-returning functions when referring to a prior table in the FROM list. So CROSS JOIN LATERAL, CROSS JOIN, or just plain , are equivalent constructs for this example.

```
SELECT admin1.gid, hex.geom
FROM
  admin1
  CROSS JOIN
  ST_HexagonGrid(100000, admin1.geom) AS hex
WHERE
  adm0_a3 = 'USA'
  AND
  ST_Intersects(admin1.geom, hex.geom)
```



[ST_EstimatedExtent](#), [ST_MakePoint](#), [ST_Point](#), [ST_SRID](#)

7.3.15 ST_Hexagon

ST_Hexagon — Returns a single hexagon, using the provided edge size and cell coordinate within the hexagon grid space.

Synopsis

geometry **ST_Hexagon**(float8 size, integer cell_i, integer cell_j, geometry origin);

图例

Uses the same hexagon tiling concept as **ST_HexagonGrid**, but generates just one hexagon at the desired cell coordinate. Optionally, can adjust origin coordinate of the tiling, the default origin is at 0,0.

Hexagons are generated with no SRID set, so use **ST_SetSRID** to set the SRID to the one you expect.

2.1.0 图例.

Example: Creating a hexagon at the origin

```
SELECT ST_AsText(ST_SetSRID(ST_Hexagon(1.0, 0, 0), 3857));

POLYGON((-1 0,-0.5
          -0.866025403784439,0.5
          -0.866025403784439,1
          0,0.5
          0.866025403784439,-0.5
          0.866025403784439,-1 0))
```

图例

ST_TileEnvelope, **ST_MakePoint**, **ST_SetSRID**

7.3.16 ST_SquareGrid

ST_SquareGrid — Returns a set of grid squares and cell indices that completely cover the bounds of the geometry argument.

Synopsis

setof record **ST_SquareGrid**(float8 size, geometry bounds);

图例

Starts with the concept of a square tiling of the plane. For a given planar SRS, and a given edge size, starting at the origin of the SRS, there is one unique square tiling of the plane, **Tiling**(SRS, Size). This function answers the question: what grids in a given **Tiling**(SRS, Size) overlap with a given bounds.

The SRS for the output squares is the SRS provided by the bounds geometry.

Doubling or edge size of the square generates a new parent tiling that perfectly fits with the original tiling. Standard web map tilings in mercator are just powers-of-two square grids in the mercator plane.

2.1.0 图例.

例 7.3.16: 生成覆盖加拿大的正方形网格

The grid will fill the whole bounds of the country, so if you want just squares that touch the country you will have to filter afterwards with `ST_Intersects`.

```
WITH grid AS (
SELECT (ST_SquareGrid(1, ST_Transform(geom,4326))).*
FROM admin0 WHERE name = 'Canada'
)
SELECT ST_AsText(geom)
FROM grid
```

例 7.3.17: 对点表进行正方形网格化

To do a point summary against a square tiling, generate a square grid using the extent of the points as the bounds, then spatially join to that grid. Note the estimated extent might be off from actual extent, so be cautious and at very least make sure you've analyzed your table.

```
SELECT COUNT(*), squares.geom
FROM
pointtable AS pts
INNER JOIN
ST_SquareGrid(
1000,
ST_SetSRID(ST_EstimatedExtent('pointtable', 'geom'), 3857)
) AS squares
ON ST_Intersects(pts.geom, squares.geom)
GROUP BY squares.geom
```

例 7.3.18: 对点表进行正方形网格化

This yields the same result as the first example but will be slower for a large number of points

```
SELECT COUNT(*), squares.geom
FROM
pointtable AS pts
INNER JOIN
ST_SquareGrid(
1000,
pts.geom
) AS squares
ON ST_Intersects(pts.geom, squares.geom)
GROUP BY squares.geom
```

例 7.3.19:

[ST_TileEnvelope](#), [ST_Point](#), [ST_SetSRID](#), [ST_SRID](#)

7.3.17 ST_Square

`ST_Square` — Returns a single square, using the provided edge size and cell coordinate within the square grid space.

Synopsis

geometry **ST_Square**(float8 size, integer cell_i, integer cell_j, geometry origin);

☒☒

Uses the same square tiling concept as **ST_SquareGrid**, but generates just one square at the desired cell coordinate. Optionally, can adjust origin coordinate of the tiling, the default origin is at 0,0.

Squares are generated with no SRID set, so use **ST_SetSRID** to set the SRID to the one you expect.

2.1.0 简体中文.

Example: Creating a square at the origin

```
SELECT ST_AsText(ST_SetSRID(ST_Square(1.0, 0, 0), 3857));
POLYGON((0 0,0 1,1 1,1 0,0 0))
```

☒☒

ST_TileEnvelope, **ST_MakeLine**, **ST_MakePolygon**

7.3.18 ST_Letters

ST_Letters — Returns the input letters rendered as geometry with a default start position at the origin and default text height of 100.

Synopsis

geometry **ST_Letters**(text letters, json font);

☒☒

Uses a built-in font to render out a string as a multipolygon geometry. The default text height is 100.0, the distance from the bottom of a descender to the top of a capital. The default start position places the start of the baseline at the origin. Over-riding the font involves passing in a json map, with a character as the key, and base64 encoded TWKB for the font shape, with the fonts having a height of 1000 units from the bottom of the descenders to the tops of the capitals.

The text is generated at the origin by default, so to reposition and resize the text, first apply the **ST_Scale** function and then apply the **ST_Translate** function.

Availability: 3.3.0

例: 生成字母 'Yo' 的几何图形

```
SELECT ST_AsText(ST_Letters('Yo'), 1);
```



Letters generated by ST_Letters

Example: Scaling and moving words

```
SELECT ST_Translate(ST_Scale(ST_Letters('Yo'), 10, 10), 100,100);
```

例

[ST_AsTWKB](#), [ST_Scale](#), [ST_Translate](#)

7.4 几何图形 (accessor)

7.4.1 GeometryType

GeometryType — ST_Geometry 几何图形的类型。

Synopsis

```
text GeometryType(geometry geomA);
```

例

返回几何图形的类型。 例: 'LINESTRING', 'POLYGON', 'MULTIPOINT' 等。

OGC 简单特征访问接口 (SFAI) - 简单特征访问接口 (SFAI), 简单特征访问接口 (SFAI) 的扩展。

**Note**

PostGIS 3.5.7 中的 'POINTM' 数据类型与 PostGIS 2.0.0 中的 'POINTM' 数据类型不同。

PostGIS 2.0.0 中的 'POINTM' 数据类型，与 PostGIS 2.0.0 中的 TIN 数据类型不同。

- ✓ This method implements the [OGC Simple Features Implementation Specification for SQL 1.1](#).
- ✓ This method supports Circular Strings and Curves.
- ✓ This function supports 3d and will not drop the z-index.
- ✓ This function supports Polyhedral surfaces.
- ✓ This function supports Triangles and Triangulated Irregular Network Surfaces (TIN).

SQL

```
SELECT GeometryType(ST_GeomFromText('LINESTRING(77.29 29.07,77.42 29.26,77.27 29.31,77.29 29.07)'));
geometrytype
-----
LINESTRING
```

```
SELECT ST_GeometryType(ST_GeomFromEWKT('POLYHEDRALSURFACE( ((0 0 0, 0 0 1, 0 1 1, 0 1 0, 0 0 0)),
((0 0 0, 0 1 0, 1 1 0, 1 0 0, 0 0 0)), ((0 0 0, 1 0 0, 1 0 1, 0 0 1, 0 0 0)),
((1 1 0, 1 1 1, 1 0 1, 1 0 0, 1 1 0)),
((0 1 0, 0 1 1, 1 1 1, 1 1 0, 0 1 0)), ((0 0 1, 1 0 1, 1 1 1, 0 1 1, 0 0 1))
) )'));
--result
POLYHEDRALSURFACE
```

```
SELECT GeometryType(geom) as result
FROM
  (SELECT
    ST_GeomFromEWKT('TIN (((
      0 0 0,
      0 0 1,
      0 1 0,
      0 0 0
    )), ((
      0 0 0,
      0 1 0,
      1 1 0,
      0 0 0
    )), ((
      0 0 0,
      0 1 0,
      1 1 0,
      0 0 0
    ))) AS geom
  ) AS g;
result
-----
TIN
```

图

ST_GeometryType

7.4.2 ST_Boundary

ST_Boundary — 返回几何对象的边界。

Synopsis

geometry **ST_Boundary**(geometry geomA);

图

ST_Boundary (closure) 返回几何对象的边界。ST_Boundary (combinatorial boundary) 符合 OGC 3.12.3.2 的定义。ST_Boundary (位相的) 符合 OGC 3.12.2 的定义 (primitive) 返回几何对象的边界。

GEOS 支持



Note

2.0.0 版本中，GEOMETRYCOLLECTION 类型的输入将返回 NULL。2.0.0 版本中，(GEOMETRYCOLLECTION) NULL 输入将返回 NULL。



This method implements the **OGC Simple Features Implementation Specification for SQL 1.1**. OGC SPEC s2.1.1.1



This method implements the SQL/MM specification. SQL-MM IEC 13249-3: 5.1.17





This function supports 3d and will not drop the z-index.

图例: 2.1.0 版本中，输入将返回 NULL。

Changed: 3.2.0 support for TIN, does not use geos, does not linearize curves

图

 图例 <pre>SELECT ST_Boundary(geom) FROM (SELECT 'LINESTRING(100 150,50 60, 70 80, 160 170) '::geometry As geom) As f;</pre> ST_AsText output <pre>MULTIPOINT((100 150),(160 170))</pre>	 图例 <pre>SELECT ST_Boundary(geom) FROM (SELECT 'POLYGON ((10 130, 50 190, 110 190, 140 150, 150 80, 100 10, 20 40, 10 130), (70 40, 100 50, 120 80, 80 110, 50 90, 70 40))'::geometry As geom) As f;</pre> ST_AsText output <pre>MULTILINESTRING((10 130,50 190,110 190,140 150,150 80,100 10,20 40,10 130), (70 40,100 50,120 80,80 110,50 90,70 40))</pre>

```
SELECT ST_AsText(ST_Boundary(ST_GeomFromText('LINESTRING(1 1,0 0, -1 1)')));
st_astext
-----
MULTIPOINT((1 1),(-1 1))

SELECT ST_AsText(ST_Boundary(ST_GeomFromText('POLYGON((1 1,0 0, -1 1, 1 1))')));
st_astext
-----
LINESTRING(1 1,0 0,-1 1,1 1)

--Using a 3d polygon
SELECT ST_AsEWKT(ST_Boundary(ST_GeomFromEWKT('POLYGON((1 1 1,0 0 1, -1 1 1, 1 1 1))')));
st_asewkt
-----
LINESTRING(1 1 1,0 0 1,-1 1 1,1 1 1)

--Using a 3d multilinestring
SELECT ST_AsEWKT(ST_Boundary(ST_GeomFromEWKT('MULTILINESTRING((1 1 1,0 0 0.5, -1 1 1),(1 1
0.5,0 0 0.5, -1 1 0.5, 1 1 0.5) )')));
st_asewkt
-----
MULTIPOINT((-1 1 1),(1 1 0.75))
```

☐☐

[ST_AsText](#), [ST_ExteriorRing](#), [ST_MakePolygon](#)

7.4.3 ST_BoundingDiagonal

ST_BoundingDiagonal — 返回给定几何图形的最小外接矩形的对角线。

Synopsis

geometry **ST_BoundingDiagonal**(geometry geom, boolean fits=false);

☐☐

返回给定几何图形的最小外接矩形的对角线。如果 fits 参数为 true，则返回的几何图形将尽可能紧密地拟合输入几何图形。如果 fits 参数为 false，则返回的几何图形将是输入几何图形的最小外接矩形的对角线。

fits 参数 (best fit) 返回的几何图形将尽可能紧密地拟合输入几何图形。如果 fits 参数为 false，则返回的几何图形将是输入几何图形的最小外接矩形的对角线。

返回的几何图形的 SRID 与输入几何图形的 SRID 相同。



Note

如果输入几何图形是 3D 的，则返回的几何图形将是 3D 的。如果输入几何图形是 2D 的，则返回的几何图形将是 2D 的。如果输入几何图形是 4D 的，则返回的几何图形将是 4D 的。

2.2.0 版本引入。



This function supports 3d and will not drop the z-index.



This function supports M coordinates.

☐☐

```
-- Get the minimum X in a buffer around a point
SELECT ST_X(ST_StartPoint(ST_BoundingDiagonal(
  ST_Buffer(ST_Point(0,0),10)
)));
st_x
-----
-10
```

☐☐

[ST_StartPoint](#), [ST_EndPoint](#), [ST_X](#), [ST_Y](#), [ST_Z](#), [ST_M](#), &&&

7.4.4 ST_CoordDim

ST_CoordDim — ST_Geometry 函数。

Synopsis

integer **ST_CoordDim**(geometry geomA);

返回

ST_Geometry 函数。

MM 函数, **ST_NDims** 函数。

- ✓ This method implements the [OGC Simple Features Implementation Specification for SQL 1.1](#).
- ✓ This method implements the SQL/MM specification. SQL-MM 3: 5.1.3
- ✓ This method supports Circular Strings and Curves.
- ✓ This function supports 3d and will not drop the z-index.
- ✓ This function supports Polyhedral surfaces.
- ✓ This function supports Triangles and Triangulated Irregular Network Surfaces (TIN).

返回

```
SELECT ST_CoordDim('CIRCULARSTRING(1 2 3, 1 3 4, 5 6 7, 8 9 10, 11 12 13)');
      ---result--
      3

      SELECT ST_CoordDim(ST_Point(1,2));
      --result--
      2
```

返回

ST_NDims

7.4.5 ST_Dimension

ST_Dimension — ST_Geometry 函数。

Synopsis

integer **ST_Dimension**(geometry g);

POINT 0, LINESTRING 1, POLYGON 2, GEOMETRYCOLLECTION. OGC s2.1.1.1.

This method implements the SQL/MM specification. SQL-MM 3: 5.1.2

2.0.0 (polyhedral surface) TIN.



Note

2.0.0



This function supports Polyhedral surfaces.

This function supports Triangles and Triangulated Irregular Network Surfaces (TIN).



```
SELECT ST_Dimension('GEOMETRYCOLLECTION(LINESTRING(1 1,0 0),POINT(0 0))');
ST_Dimension
-----
1
```


ST NDims

7.4.6 ST Dump

ST Dump — Returns a set of geometry_dump rows for the components of a geometry.

Synopsis

```
geometry dump[] ST_Dump(geometry g1);
```



A set-returning function (SRF) that extracts the components of a geometry. It returns a set of **geom-
etry dump** rows, each containing a geometry (*geom* field) and an array of integers (*path* field).

For an atomic geometry type (POINT,LINestring,POLYGON) a single record is returned with an empty *path* array and the input geometry as *geom*. For a collection or multi-geometry a record is returned for each of the collection components, and the *path* denotes the position of the component inside the collection.

ST_Dump is useful for expanding geometries. It is the inverse of a **ST_Collect** / GROUP BY, in that it creates new rows. For example it can be use to expand MULTIPOLYGONS into POLYGONS.

Version: 2.0.0, TIN

Availability: PostGIS 1.0.0RC1. Requires PostgreSQL 7.3 or higher.



Note

1.3.4 版本 (curve) 支持。1.3.4 版本支持。

- ✓ This method supports Circular Strings and Curves.
- ✓ This function supports Polyhedral surfaces.
- ✓ This function supports Triangles and Triangulated Irregular Network Surfaces (TIN).
- ✓ This function supports 3d and will not drop the z-index.

示例

```
SELECT sometable.field1, sometable.field1,
       (ST_Dump(sometable.geom)).geom AS geom
FROM sometable;

-- Break a compound curve into its constituent linestrings and circularstrings
SELECT ST_AsEWKT(a.geom), ST_HasArc(a.geom)
FROM ( SELECT (ST_Dump(p_geom)).geom AS geom
      FROM (SELECT ST_GeomFromEWKT('COMPOUNDCURVE(CIRCULARSTRING(0 0, 1 1, 1 0),(1 0, 0 1))') AS p_geom) AS b
      ) AS a;
      st_asewkt          | st_hasarc
-----+-----
CIRCULARSTRING(0 0,1 1,1 0) | t
LINESTRING(1 0,0 1)       | f
(2 rows)
```

示例, TIN 示例

```
-- Polyhedral surface example
-- Break a Polyhedral surface into its faces
SELECT (a.p_geom).path[1] As path, ST_AsEWKT((a.p_geom).geom) As geom_ewkt
FROM (SELECT ST_Dump(ST_GeomFromEWKT('POLYHEDRALSURFACE(
((0 0 0, 0 0 1, 0 1 1, 0 1 0, 0 0 0)),
((0 0 0, 0 1 0, 1 1 0, 1 0 0, 0 0 0)), ((0 0 0, 1 0 0, 1 0 1, 0 0 1, 0 0 0)), ((1 1 0, 1 1 1, 1 0 1, 1 0 0, 1 0 0)),
((0 1 0, 0 1 1, 1 1 1, 1 1 0, 0 1 0)), ((0 0 1, 1 0 1, 1 1 1, 0 1 1, 0 0 1))
)') ) AS p_geom ) AS a;

path | geom_ewkt
-----+-----
1 | POLYGON((0 0 0,0 0 1,0 1 1,0 1 0,0 0 0))
2 | POLYGON((0 0 0,0 1 0,1 1 0,1 0 0,0 0 0))
3 | POLYGON((0 0 0,1 0 0,1 0 1,0 0 1,0 0 0))
4 | POLYGON((1 1 0,1 1 1,1 0 1,1 0 0,1 1 0))
5 | POLYGON((0 1 0,0 1 1,1 1 1,1 1 0,0 1 0))
6 | POLYGON((0 0 1,1 0 1,1 1 1,0 1 1,0 0 1))

-- TIN --
SELECT (g.gdump).path, ST_AsEWKT((g.gdump).geom) as wkt
FROM
```

```
(SELECT
  ST_Dump( ST_GeomFromEWKT('TIN (((
    0 0 0,
    0 0 1,
    0 1 0,
    0 0 0
  ))), ((
    0 0 0,
    0 1 0,
    1 1 0,
    0 0 0
  ))
) AS g;

-- result --
path | wkt
-----+-----
{1}  | TRIANGLE((0 0 0,0 0 1,0 1 0,0 0 0))
{2}  | TRIANGLE((0 0 0,0 1 0,1 1 0,0 0 0))
```


geometry dump, ST_GeomFromEWKT, ST_Dump, ST_GeometryN, ST_NumGeometries

7.4.7 ST_DumpPoints

ST DumpPoints — .

Synopsis

```
geometry_dump[] ST_DumpPoints(geometry geom);
```



A set-returning function (SRF) that extracts the coordinates (vertices) of a geometry. It returns a set of **geometry_dump** rows, each containing a geometry (*geom* field) and an array of integers (*path* field).

- the *geom* field POINTs represent the coordinates of the supplied geometry.
- the *path* field (an integer[]) is an index enumerating the coordinate positions in the elements of the supplied geometry. The indices are 1-based. For example, for a LINESTRING the paths are {i} where i is the nth coordinate in the LINESTRING. For a POLYGON the paths are {i, j} where i is the ring number (1 is outer; inner rings follow) and j is the coordinate position in the ring.

To obtain a single geometry containing the coordinates use **ST Points**.

Enhanced: 2.1.0 Faster speed. Reimplemented as native-C.

Version: 2.0.0, TIN

1.5.0 ☒☒☒☒☒☒☒☒☒☒☒.


- ✔ This method supports Circular Strings and Curves.
- ✔ This function supports Polyhedral surfaces.

- ✔ This function supports Triangles and Triangulated Irregular Network Surfaces (TIN).
- ✔ This function supports 3d and will not drop the z-index.

Classic Explode a Table of LineStrings into nodes

```
SELECT edge_id, (dp).path[1] As index, ST_AsText((dp).geom) As wktnode
FROM (SELECT 1 As edge_id
      , ST_DumpPoints(ST_GeomFromText('LINESTRING(1 2, 3 4, 10 10)')) AS dp
      UNION ALL
      SELECT 2 As edge_id
      , ST_DumpPoints(ST_GeomFromText('LINESTRING(3 5, 5 6, 9 10)')) AS dp
      ) As foo;
edge_id | index | wktnode
-----+-----+-----
1 | 1 | POINT(1 2)
1 | 2 | POINT(3 4)
1 | 3 | POINT(10 10)
2 | 1 | POINT(3 5)
2 | 2 | POINT(5 6)
2 | 3 | POINT(9 10)
```

图例



```
SELECT path, ST_AsText(geom)
FROM (
  SELECT (ST_DumpPoints(g.geom)).*
  FROM
    (SELECT
      'GEOMETRYCOLLECTION(
        POINT ( 0 1 ),
        LINESTRING ( 0 3, 3 4 ),
        POLYGON (( 2 0, 2 3, 0 2, 2 0 )),
        POLYGON (( 3 0, 3 3, 6 3, 6 0, 3 0 ),
          ( 5 1, 4 2, 5 2, 5 1 )),
        MULTIPOLYGON (
          (( 0 5, 0 8, 4 8, 4 5, 0 5 ),
            ( 1 6, 3 6, 2 7, 1 6 )),
```

```
        (( 5 4, 5 8, 6 7, 5 4 ))
    )
  ) '::geometry AS geom
) AS g
) j;
```

path	st_astext
{1,1}	POINT(0 1)
{2,1}	POINT(0 3)
{2,2}	POINT(3 4)
{3,1,1}	POINT(2 0)
{3,1,2}	POINT(2 3)
{3,1,3}	POINT(0 2)
{3,1,4}	POINT(2 0)
{4,1,1}	POINT(3 0)
{4,1,2}	POINT(3 3)
{4,1,3}	POINT(6 3)
{4,1,4}	POINT(6 0)
{4,1,5}	POINT(3 0)
{4,2,1}	POINT(5 1)
{4,2,2}	POINT(4 2)
{4,2,3}	POINT(5 2)
{4,2,4}	POINT(5 1)
{5,1,1,1}	POINT(0 5)
{5,1,1,2}	POINT(0 8)
{5,1,1,3}	POINT(4 8)
{5,1,1,4}	POINT(4 5)
{5,1,1,5}	POINT(0 5)
{5,1,2,1}	POINT(1 6)
{5,1,2,2}	POINT(3 6)
{5,1,2,3}	POINT(2 7)
{5,1,2,4}	POINT(1 6)
{5,2,1,1}	POINT(5 4)
{5,2,1,2}	POINT(5 8)
{5,2,1,3}	POINT(6 7)
{5,2,1,4}	POINT(5 4)

(29 rows)

创建 TIN 面

```
-- Polyhedral surface cube --
SELECT (g.gdump).path, ST_AsEWKT((g.gdump).geom) as wkt
FROM
  (SELECT
    ST_DumpPoints(ST_GeomFromEWKT('POLYHEDRALSURFACE( ((0 0 0, 0 0 1, 0 1 1, 0 1 0, 0 0 ←
    0)),
    ((0 0 0, 0 1 0, 1 1 0, 1 0 0, 0 0 0)), ((0 0 0, 1 0 0, 1 0 1, 0 0 1, 0 0 0)),
    ((1 1 0, 1 1 1, 1 0 1, 1 0 0, 1 1 0)),
    ((0 1 0, 0 1 1, 1 1 1, 1 1 0, 0 1 0)), ((0 0 1, 1 0 1, 1 1 1, 0 1 1, 0 0 1)) )' ) AS gdump
  ) AS g;
-- result --
path | wkt
-----+-----
{1,1,1} | POINT(0 0 0)
{1,1,2} | POINT(0 0 1)
{1,1,3} | POINT(0 1 1)
{1,1,4} | POINT(0 1 0)
{1,1,5} | POINT(0 0 0)
{2,1,1} | POINT(0 0 0)
```

```

{2,1,2} | POINT(0 1 0)
{2,1,3} | POINT(1 1 0)
{2,1,4} | POINT(1 0 0)
{2,1,5} | POINT(0 0 0)
{3,1,1} | POINT(0 0 0)
{3,1,2} | POINT(1 0 0)
{3,1,3} | POINT(1 0 1)
{3,1,4} | POINT(0 0 1)
{3,1,5} | POINT(0 0 0)
{4,1,1} | POINT(1 1 0)
{4,1,2} | POINT(1 1 1)
{4,1,3} | POINT(1 0 1)
{4,1,4} | POINT(1 0 0)
{4,1,5} | POINT(1 1 0)
{5,1,1} | POINT(0 1 0)
{5,1,2} | POINT(0 1 1)
{5,1,3} | POINT(1 1 1)
{5,1,4} | POINT(1 1 0)
{5,1,5} | POINT(0 1 0)
{6,1,1} | POINT(0 0 1)
{6,1,2} | POINT(1 0 1)
{6,1,3} | POINT(1 1 1)
{6,1,4} | POINT(0 1 1)
{6,1,5} | POINT(0 0 1)
(30 rows)

```

```

-- Triangle --
SELECT (g.gdump).path, ST_AsText((g.gdump).geom) as wkt
FROM
  (SELECT
    ST_DumpPoints( ST_GeomFromEWKT('TRIANGLE ((
      0 0,
      0 9,
      9 0,
      0 0
    ))) ) AS gdump
  ) AS g;
-- result --
path |      wkt
-----+-----
{1}  | POINT(0 0)
{2}  | POINT(0 9)
{3}  | POINT(9 0)
{4}  | POINT(0 0)

```

```

-- TIN --
SELECT (g.gdump).path, ST_AsEWKT((g.gdump).geom) as wkt
FROM
  (SELECT
    ST_DumpPoints( ST_GeomFromEWKT('TIN (((
      0 0 0,
      0 0 1,
      0 1 0,
      0 0 0
    )), ((
      0 0 0,
      0 1 0,
      1 1 0,
      0 0 0
    ))
  )') ) AS gdump

```

```
) AS g;
-- result --
path | wkt
-----+-----
{1,1,1} | POINT(0 0 0)
{1,1,2} | POINT(0 0 1)
{1,1,3} | POINT(0 1 0)
{1,1,4} | POINT(0 0 0)
{2,1,1} | POINT(0 0 0)
{2,1,2} | POINT(0 1 0)
{2,1,3} | POINT(1 1 0)
{2,1,4} | POINT(0 0 0)
(8 rows)
```

`geometry_dump`, `ST_GeomFromEWKT`, `ST_Dump`, `ST_GeometryN`, `ST_NumGeometries`

7.4.8 ST_DumpSegments

`ST_DumpSegments` —

Synopsis

`geometry_dump[] ST_DumpSegments(geometry geom);`

A set-returning function (SRF) that extracts the segments of a geometry. It returns a set of `geometry_dump` rows, each containing a geometry (*geom* field) and an array of integers (*path* field).

- the *geom* field LINESTRINGS represent the linear segments of the supplied geometry, while the CIRCULARSTRINGS represent the arc segments.
- the *path* field (an `integer[]`) is an index enumerating the segment start point positions in the elements of the supplied geometry. The indices are 1-based. For example, for a LINESTRING the paths are {i} where i is the nth segment start point in the LINESTRING. For a POLYGON the paths are {i, j} where i is the ring number (1 is outer; inner rings follow) and j is the segment start point position in the ring.

Availability: 3.2.0

-  This function supports Triangles and Triangulated Irregular Network Surfaces (TIN).
-  This function supports 3d and will not drop the z-index.

```
SELECT path, ST_AsText(geom)
FROM (
  SELECT (ST_DumpSegments(g.geom)).*
  FROM (SELECT 'GEOMETRYCOLLECTION(
    LINESTRING(1 1, 3 3, 4 4),
    POLYGON((5 5, 6 6, 7 7, 5 5))
  )'::geometry AS geom
        ) AS g
) j;
```

path	b'' b''	st_astext

{1,1}	b'' b''	LINESTRING(1 1,3 3)
{1,2}	b'' b''	LINESTRING(3 3,4 4)
{2,1,1}	b'' b''	LINESTRING(5 5,6 6)
{2,1,2}	b'' b''	LINESTRING(6 6,7 7)
{2,1,3}	b'' b''	LINESTRING(7 7,5 5)

(5 rows)

几何类型, **TIN** 几何类型

```
-- Triangle --
SELECT path, ST_AsText(geom)
FROM (
  SELECT (ST_DumpSegments(g.geom)).*
  FROM (SELECT 'TRIANGLE((
    0 0,
    0 9,
    9 0,
    0 0
  ))'::geometry AS geom
        ) AS g
) j;
```

path	b'' b''	st_astext

{1,1}	b'' b''	LINESTRING(0 0,0 9)
{1,2}	b'' b''	LINESTRING(0 9,9 0)
{1,3}	b'' b''	LINESTRING(9 0,0 0)

(3 rows)

```
-- TIN --
SELECT path, ST_AsEWKT(geom)
FROM (
  SELECT (ST_DumpSegments(g.geom)).*
  FROM (SELECT 'TIN(((
    0 0 0,
    0 0 1,
    0 1 0,
    0 0 0
  )), ((
    0 0 0,
    0 1 0,
    1 1 0,
    0 0 0
  )))
  )'::geometry AS geom
        ) AS g
```



```
) j;
```

path	b''	b''	st_asewkt
{1,1,1}	b''	b''	LINESTRING(0 0 0,0 0 1)
{1,1,2}	b''	b''	LINESTRING(0 0 1,0 1 0)
{1,1,3}	b''	b''	LINESTRING(0 1 0,0 0 0)
{2,1,1}	b''	b''	LINESTRING(0 0 0,0 1 0)
{2,1,2}	b''	b''	LINESTRING(0 1 0,1 1 0)
{2,1,3}	b''	b''	LINESTRING(1 1 0,0 0 0)

(6 rows)



geometry dump, ST Collect, ST Dump, ST NumInteriorRing,

7.4.9 ST_DumpRings

ST DumpRings — Returns a set of geometry dump rows for the exterior and interior rings of a Polygon.

Synopsis

```
geometry dump[] ST_DumpRings(geometry a polygon);
```



A set-returning function (SRF) that extracts the rings of a polygon. It returns a set of `geometry_dump` rows, each containing a geometry (*geom* field) and an array of integers (*path* field).

The *geom* field contains each ring as a POLYGON. The *path* field is an integer array of length 1 containing the polygon ring index. The exterior ring (shell) has index 0. The interior rings (holes) have indices of 1 and higher.



Note

XXXXXXXXXXXXXXXXXXXXXXXXXXXX. XXXXXXXXXXXX ST Dump XXXXXXXXXXXXXXXXXXXXXXX.

Availability: PostGIS 1.1.3. Requires PostgreSQL 7.3 or higher.



This function supports 3d and will not drop the z-index.

11/11

General form of query.

```
SELECT polyTable.field1, polyTable.field1,
      (ST_DumpRings(polyTable.geom)).geom As geom
FROM polyTable;
```

A polygon with a single hole.

图 11.1

```
SELECT ST_AsText(ST_Envelope('POINT(1 3)::geometry'));
      st_astext
-----
POINT(1 3)
(1 row)

SELECT ST_AsText(ST_Envelope('LINESTRING(0 0, 1 3)::geometry'));
      st_astext
-----
POLYGON((0 0,0 3,1 3,1 0,0 0))
(1 row)

SELECT ST_AsText(ST_Envelope('POLYGON((0 0, 0 1, 1.0000001 1, 1.0000001 0, 0 0))::geometry' ←
));
      st_astext
-----
POLYGON((0 0,0 1,1.00000011920929 1,1.00000011920929 0,0 0))
(1 row)
SELECT ST_AsText(ST_Envelope('POLYGON((0 0, 0 1, 1.0000000001 1, 1.0000000001 0, 0 0))':: ←
geometry));
      st_astext
-----
POLYGON((0 0,0 1,1.00000011920929 1,1.00000011920929 0,0 0))
(1 row)

SELECT Box3D(geom), Box2D(geom), ST_AsText(ST_Envelope(geom)) As envelopewkt
FROM (SELECT 'POLYGON((0 0, 0 1000012333334.34545678, 1.0000001 1, 1.0000001 0, 0 0) ←
0))::geometry As geom) As foo;
```



Envelope of a point and linestring.

```
SELECT ST_AsText(ST_Envelope(
      ST_Collect(
        ST_GeomFromText('LINESTRING(55 75,125 150)'),
        ST_Point(20, 80))
```

```

                                )) As wktenv;
wktenv
-----
POLYGON((20 75,20 150,125 150,125 75,20 75))

```

☐☐

Box2D, Box3D, ST_OrientedEnvelope

7.4.12 ST_ExteriorRing

ST_ExteriorRing — 返回多边形的外环。

Synopsis

geometry **ST_ExteriorRing**(geometry a_polygon);

☐☐

POLYGON 类型 (exterior ring) 返回一个 POLYGON 类型。如果输入为 NULL 则返回 NULL。



Note

ST_ExteriorRing 返回的是多边形的外环。ST_Dump 返回的是所有环。

- ✔ This method implements the **OGC Simple Features Implementation Specification for SQL 1.1. 2.1.5.1**
- ✔ This method implements the SQL/MM specification. SQL-MM 3: 8.2.3, 8.3.3
- ✔ This function supports 3d and will not drop the z-index.

☐☐

```

--If you have a table of polygons
SELECT gid, ST_ExteriorRing(geom) AS ering
FROM sometable;

--If you have a table of MULTIPOLYGONS
--and want to return a MULTILINESTRING composed of the exterior rings of each polygon
SELECT gid, ST_Collect(ST_ExteriorRing(geom)) AS erings
      FROM (SELECT gid, (ST_Dump(geom)).geom As geom
            FROM sometable) As foo
GROUP BY gid;

--3d Example
SELECT ST_AsEWKT(
  ST_ExteriorRing(
    ST_GeomFromEWKT('POLYGON((0 0 1, 1 1 1, 1 2 1, 1 1 1, 0 0 1))')
  )
)

```


提取点

```
--Extracting a subset of points from a 3d multipoint
SELECT n, ST_AsEWKT(ST_GeometryN(geom, n)) As geomewkt
FROM (
VALUES (ST_GeomFromEWKT('MULTIPOINT((1 2 7), (3 4 7), (5 6 7), (8 9 10)))' ) ,
( ST_GeomFromEWKT('MULTICURVE(CIRCULARSTRING(2.5 2.5,4.5 2.5, 3.5 3.5), (10 11, 12 11))' ) )
)As foo(geom)
CROSS JOIN generate_series(1,100) n
WHERE n <= ST_NumGeometries(geom);
```

n	geomewkt
1	POINT(1 2 7)
2	POINT(3 4 7)
3	POINT(5 6 7)
4	POINT(8 9 10)
1	CIRCULARSTRING(2.5 2.5,4.5 2.5,3.5 3.5)
2	LINestring(10 11,12 11)

```
--Extracting all geometries (useful when you want to assign an id)
SELECT gid, n, ST_GeometryN(geom, n)
FROM sometable CROSS JOIN generate_series(1,100) n
WHERE n <= ST_NumGeometries(geom);
```

多面体表面, TIN 三角网

```
-- Polyhedral surface example
-- Break a Polyhedral surface into its faces
SELECT ST_AsEWKT(ST_GeometryN(p_geom,3)) As geom_ewkt
FROM (SELECT ST_GeomFromEWKT('POLYHEDRALSURFACE(
((0 0 0, 0 0 1, 0 1 1, 0 1 0, 0 0 0)),
((0 0 0, 0 1 0, 1 1 0, 1 0 0, 0 0 0)),
((0 0 0, 1 0 0, 1 0 1, 0 0 1, 0 0 0)),
((1 1 0, 1 1 1, 1 0 1, 1 0 0, 1 1 0)),
((0 1 0, 0 1 1, 1 1 1, 1 1 0, 0 1 0)),
((0 0 1, 1 0 1, 1 1 1, 0 1 1, 0 0 1))
)') AS p_geom ) AS a;
```

geom_ewkt
POLYGON((0 0 0,1 0 0,1 0 1,0 0 1,0 0 0))

```
-- TIN --
SELECT ST_AsEWKT(ST_GeometryN(geom,2)) as wkt
FROM
  (SELECT
    ST_GeomFromEWKT('TIN (((
      0 0 0,
      0 0 1,
      0 1 0,
      0 0 0
    )), ((
      0 0 0,
      0 1 0,
      1 1 0,
      0 0 0
    )))
  )
```



```
SELECT ST_GeometryType(ST_GeomFromEWKT('POLYHEDRALSURFACE( ((0 0 0, 0 0 1, 0 1 1, 0 1 0, 0
0 0)),
    ((0 0 0, 0 1 0, 1 1 0, 1 0 0, 0 0 0)), ((0 0 0, 1 0 0, 1 0 1, 0 0 1, 0 0 0)
),
    ((1 1 0, 1 1 1, 1 0 1, 1 0 0, 1 1 0)),
    ((0 1 0, 0 1 1, 1 1 1, 1 1 0, 0 1 0)), ((0 0 1, 1 0 1, 1 1 1, 0 1 1, 0 0 1)
) )')));
--result
ST_PolyhedralSurface
```

```
SELECT ST_GeometryType(geom) as result
FROM
  (SELECT
    ST_GeomFromEWKT('TIN (((
      0 0 0,
      0 0 1,
      0 1 0,
      0 0 0
    )), ((
      0 0 0,
      0 1 0,
      1 1 0,
      0 0 0
    ))
  )') AS geom
) AS g;
result
-----
ST_Tin
```

☒☒

GeometryType

7.4.15 ST_HasArc

ST_HasArc — Tests if a geometry contains a circular arc

Synopsis

boolean **ST_HasArc**(geometry geomA);

☒☒

☒☒☒☒☒☒☒☒☒, ☒☒☒, ☒☒☒☒☒☒☒ TRUE ☒☒☒☒☒☒.

1.2.2 ☒☒☒☒☒☒☒☒☒☒.

- ✔ This function supports 3d and will not drop the z-index.
- ✔ This method supports Circular Strings and Curves.

例

```
SELECT ST_HasArc(ST_Collect('LINESTRING(1 2, 3 4, 5 6)', 'CIRCULARSTRING(1 1, 2 3, 4 5, 6 6, 5 6)'));
      st_hasarc
      -
t
```

例

[ST_CurveToLine](#), [ST_PointN](#)

7.4.16 ST_InteriorRingN

`ST_InteriorRingN` — 返回多边形内部第 `N` 个环的几何对象。

Synopsis

geometry **ST_InteriorRingN**(geometry a_polygon, integer n);

例

返回第 `N` 个内部环的几何对象。如果 `N` 为负数 (range) 则返回 NULL。



Note

如果 `N` 为负数，则返回 NULL。使用 `ST_Dump` 可以获取所有环。

- ✓ This method implements the [OGC Simple Features Implementation Specification for SQL 1.1](#).
- ✓ This method implements the SQL/MM specification. SQL-MM 3: 8.2.6, 8.3.5
- ✓ This function supports 3d and will not drop the z-index.

例

```
SELECT ST_AsText(ST_InteriorRingN(geom, 1)) As geom
FROM (SELECT ST_BuildArea(
      ST_Collect(ST_Buffer(ST_Point(1,2), 20,3),
      ST_Buffer(ST_Point(1, 2), 10,3))) As geom
      ) as foo;
```

例

[ST_ExteriorRing](#), [ST_M](#), [ST_X](#), [ST_Y](#), [ST_ZMax](#), [ST_ZMin](#)

7.4.17 ST_NumCurves

ST_NumCurves — Return the number of component curves in a CompoundCurve.

Synopsis

integer **ST_NumCurves**(geometry a_compoundcurve);

国国

Return the number of component curves in a CompoundCurve, zero for an empty CompoundCurve, or NULL for a non-CompoundCurve input.



This method implements the SQL/MM specification. SQL-MM 3: 8.2.6, 8.3.5



This function supports 3d and will not drop the z-index.

国国

```
-- Returns 3
SELECT ST_NumCurves('COMPOUNDCURVE(
  (2 2, 2.5 2.5),
  CIRCULARSTRING(2.5 2.5, 4.5 2.5, 3.5 3.5),
  (3.5 3.5, 2.5 4.5, 3 5, 2 2)
)');

-- Returns 0
SELECT ST_NumCurves('COMPOUNDCURVE EMPTY');
```

国国

ST_CurveN, **ST_Dump**, **ST_ExteriorRing**, **ST_NumInteriorRings**, **ST_NumGeometries**

7.4.18 ST_CurveN

ST_CurveN — Returns the Nth component curve geometry of a CompoundCurve.

Synopsis

geometry **ST_CurveN**(geometry a_compoundcurve, integer index);

国国

Returns the Nth component curve geometry of a CompoundCurve. The index starts at 1. Returns NULL if the geometry is not a CompoundCurve or the index is out of range.



This method implements the SQL/MM specification. SQL-MM 3: 8.2.6, 8.3.5



This function supports 3d and will not drop the z-index.

例

```
SELECT ST_AsText(ST_CurveN('COMPOUNDCURVE(
  (2 2, 2.5 2.5),
  CIRCULARSTRING(2.5 2.5, 4.5 2.5, 3.5 3.5),
  (3.5 3.5, 2.5 4.5, 3 5, 2 2)
)', 1));
```

例

[ST_NumCurves](#), [ST_Dump](#), [ST_ExteriorRing](#), [ST_NumInteriorRings](#), [ST_NumGeometries](#)

7.4.19 ST_IsClosed

ST_IsClosed — **LINESTRING** 是否是闭合的 **TRUE** 或 **FALSE**。多边形 (面) 总是 **TRUE**。

Synopsis

boolean **ST_IsClosed**(geometry g);

例

LINESTRING 是否是闭合的 **TRUE** 或 **FALSE**。多边形, 面 (面) 总是 **TRUE**。

- ✓ This method implements the [OGC Simple Features Implementation Specification for SQL 1.1](#).
- ✓ This method implements the SQL/MM specification. SQL-MM 3: 7.1.5, 9.3.3



Note

SQL-MM defines the result of **ST_IsClosed(NULL)** to be 0, while PostGIS returns NULL.

- ✓ This function supports 3d and will not drop the z-index.
- ✓ This method supports Circular Strings and Curves.
- 例: 2.0.0 多面体 (polyhedral surface) 支持。
- ✓ This function supports Polyhedral surfaces.

相关链接

```

postgis=# SELECT ST_IsClosed('LINESTRING(0 0, 1 1)::geometry');
st_isclosed
-----
f
(1 row)

postgis=# SELECT ST_IsClosed('LINESTRING(0 0, 0 1, 1 1, 0 0)::geometry');
st_isclosed
-----
t
(1 row)

postgis=# SELECT ST_IsClosed('MULTILINESTRING((0 0, 0 1, 1 1, 0 0),(0 0, 1 1))::geometry');
st_isclosed
-----
f
(1 row)

postgis=# SELECT ST_IsClosed('POINT(0 0)::geometry');
st_isclosed
-----
t
(1 row)

postgis=# SELECT ST_IsClosed('MULTIPOINT((0 0), (1 1))::geometry');
st_isclosed
-----
t
(1 row)

```

几何体

```

-- A cube --
SELECT ST_IsClosed(ST_GeomFromEWKT('POLYHEDRALSURFACE( ((0 0 0, 0 0 1, 0 1 ←
1, 0 1 0, 0 0 0)),
((0 0 0, 0 1 0, 1 1 0, 1 0 0, 0 0 0)), ((0 0 0, 1 0 0, 1 0 1, 0 0 1, 0 0 0) ←
),
((1 1 0, 1 1 1, 1 0 1, 1 0 0, 1 1 0)),
((0 1 0, 0 1 1, 1 1 1, 1 1 0, 0 1 0)), ((0 0 1, 1 0 1, 1 1 1, 0 1 1, 0 0 1) ←
) )'));

st_isclosed
-----
t

-- Same as cube but missing a side --
SELECT ST_IsClosed(ST_GeomFromEWKT('POLYHEDRALSURFACE( ((0 0 0, 0 0 1, 0 1 1, 0 1 0, 0 0 ←
0)),
((0 0 0, 0 1 0, 1 1 0, 1 0 0, 0 0 0)), ((0 0 0, 1 0 0, 1 0 1, 0 0 1, 0 0 0) ←
),
((1 1 0, 1 1 1, 1 0 1, 1 0 0, 1 1 0)),
((0 1 0, 0 1 1, 1 1 1, 1 1 0, 0 1 0)) )'));

st_isclosed
-----
f

```

返回

ST_IsRing

7.4.20 ST_IsCollection

ST_IsCollection — 判断几何对象是否是集合，如果是，返回 TRUE，否则返回 FALSE。

Synopsis

boolean **ST_IsCollection**(geometry g);

返回

判断几何对象是否是集合，如果是，返回 TRUE，否则返回 FALSE：

- GEOMETRYCOLLECTION
- MULTI{POINT,POLYGON,LINestring,CURVE,SURFACE}
- COMPOUNDCURVE



Note

判断几何对象是否是集合，如果是，返回 TRUE，否则返回 FALSE。



This function supports 3d and will not drop the z-index.



This method supports Circular Strings and Curves.

返回

```
postgis=# SELECT ST_IsCollection('LINestring(0 0, 1 1)::geometry');
st_iscollection
-----
f
(1 row)

postgis=# SELECT ST_IsCollection('MULTIPOINT EMPTY)::geometry');
st_iscollection
-----
t
(1 row)

postgis=# SELECT ST_IsCollection('MULTIPOINT((0 0))::geometry');
st_iscollection
-----
t
(1 row)

postgis=# SELECT ST_IsCollection('MULTIPOINT((0 0), (42 42))::geometry');
st_iscollection
```


❏

```
SELECT ST_IsEmpty(ST_GeomFromText('GEOMETRYCOLLECTION EMPTY'));
st_isempty
-----
t
(1 row)

SELECT ST_IsEmpty(ST_GeomFromText('POLYGON EMPTY'));
st_isempty
-----
t
(1 row)

SELECT ST_IsEmpty(ST_GeomFromText('POLYGON((1 2, 3 4, 5 6, 1 2))'));
st_isempty
-----
f
(1 row)

SELECT ST_IsEmpty(ST_GeomFromText('POLYGON((1 2, 3 4, 5 6, 1 2))')) = false;
?column?
-----
t
(1 row)

SELECT ST_IsEmpty(ST_GeomFromText('CIRCULARSTRING EMPTY'));
st_isempty
-----
t
(1 row)
```

7.4.22 ST_IsPolygonCCW

ST_IsPolygonCCW — Tests if Polygons have exterior rings oriented counter-clockwise and interior rings oriented clockwise.

Synopsis

boolean **ST_IsPolygonCCW** (geometry geom);

❏

Returns true if all polygonal components of the input geometry use a counter-clockwise orientation for their exterior ring, and a clockwise direction for all interior rings.

Returns true if the geometry has no polygonal components.



Note

Closed linestrings are not considered polygonal components, so you would still get a true return by passing a single closed linestring no matter its orientation.

**Note**

If a polygonal geometry does not use reversed orientation for interior rings (i.e., if one or more interior rings are oriented in the same direction as an exterior ring) then both `ST_IsPolygonCW` and `ST_IsPolygonCCW` will return false.

2.2.0 简体中文。



This function supports 3d and will not drop the z-index.



This function supports M coordinates.

☒

`ST_ForcePolygonCW` , `ST_ForcePolygonCCW` , `ST_IsPolygonCW`

7.4.23 ST_IsPolygonCW

`ST_IsPolygonCW` — Tests if Polygons have exterior rings oriented clockwise and interior rings oriented counter-clockwise.

Synopsis

boolean **ST_IsPolygonCW** (geometry geom);

☒

Returns true if all polygonal components of the input geometry use a clockwise orientation for their exterior ring, and a counter-clockwise direction for all interior rings.

Returns true if the geometry has no polygonal components.

**Note**

Closed linestrings are not considered polygonal components, so you would still get a true return by passing a single closed linestring no matter its orientation.

**Note**

If a polygonal geometry does not use reversed orientation for interior rings (i.e., if one or more interior rings are oriented in the same direction as an exterior ring) then both `ST_IsPolygonCW` and `ST_IsPolygonCCW` will return false.

2.2.0 简体中文。



This function supports 3d and will not drop the z-index.



This function supports M coordinates.

Synopsis

boolean **ST_IsSimple**(geometry geomA);

返回

如果几何体是简单的，则返回 TRUE。如果几何体不是简单的，则返回 FALSE。OGC 简单要素实现规范 (OGC Simple Features Implementation Specification) 中，**"OpenGIS 简单要素实现规范 (Ensuring OpenGIS compliance of geometries)"** 有详细定义。



Note

SQL-MM 中 ST_IsSimple(NULL) 返回 0，PostGIS 中 NULL 返回 NULL。

- ✔ This method implements the **OGC Simple Features Implementation Specification for SQL 1.1. s2.1.1.1**
- ✔ This method implements the SQL/MM specification. SQL-MM 3: 5.1.8
- ✔ This function supports 3d and will not drop the z-index.

返回

```
SELECT ST_IsSimple(ST_GeomFromText('POLYGON((1 2, 3 4, 5 6, 1 2))'));
st_issimple
-----
f
(1 row)

SELECT ST_IsSimple(ST_GeomFromText('LINESTRING(1 1,2 2,2 3.5,1 3,1 2,2 1)'));
st_issimple
-----
f
(1 row)
```

返回

ST_IsValid

7.4.26 ST_M

ST_M — Returns the M coordinate of a Point.

Synopsis

float **ST_M**(geometry a_point);

返回

返回 `M` 几何体。 `M` 几何体 `NULL` 返回 `NULL`。 返回类型 `geometry`。



Note

返回 (返回) OGC 简单特征实现规范, 提取器 (extractor) 返回类型 `geometry`。

- ✓ This method implements the [OGC Simple Features Implementation Specification for SQL 1.1](#).
- ✓ This method implements the SQL/MM specification.
- ✓ This function supports 3d and will not drop the z-index.

返回

```
SELECT ST_M(ST_GeomFromEWKT('POINT(1 2 3 4)'));
 st_m
-----
      4
(1 row)
```

返回

[ST_GeomFromEWKT](#), [ST_X](#), [ST_Y](#), [ST_Z](#)

7.4.27 ST_MemSize

`ST_MemSize` — `ST_Geometry` 内存大小。

Synopsis

integer **ST_MemSize**(geometry geomA);

返回

`ST_Geometry` 内存大小。

This complements the PostgreSQL built-in [database object functions](#) `pg_column_size`, `pg_size_pretty`, `pg_relation_size`, `pg_total_relation_size`.

Note



`pg_relation_size` which gives the byte size of a table may return byte size lower than `ST_MemSize`. This is because `pg_relation_size` does not add toasted table contribution and large geometries are stored in TOAST tables.

`pg_total_relation_size` 返回, TOAST 返回。

`pg_column_size` returns how much space a geometry would take in a column considering compression, so may be lower than `ST_MemSize`

- ✔ This function supports 3d and will not drop the z-index.
- ✔ This method supports Circular Strings and Curves.
- ✔ This function supports Polyhedral surfaces.
- ✔ This function supports Triangles and Triangulated Irregular Network Surfaces (TIN).

Changed: 2.2.0 name changed to ST_MemSize to follow naming convention.

☒

```
--Return how much byte space Boston takes up in our Mass data set
SELECT pg_size_pretty(SUM(ST_MemSize(geom))) as totgeomsum,
pg_size_pretty(SUM(CASE WHEN town = 'BOSTON' THEN ST_MemSize(geom) ELSE 0 END)) As bossum,
CAST(SUM(CASE WHEN town = 'BOSTON' THEN ST_MemSize(geom) ELSE 0 END)*1.00 /
      SUM(ST_MemSize(geom))*100 As numeric(10,2)) As perbos
FROM towns;
```

totgeomsum	bossum	perbos
-----	-----	-----
1522 kB	30 kB	1.99

```
SELECT ST_MemSize(ST_GeomFromText('CIRCULARSTRING(220268 150415,220227 150505,220227 150406)'));
---
```

```
73
```

```
--What percentage of our table is taken up by just the geometry
SELECT pg_total_relation_size('public.neighborhoods') As fulltable_size, sum(ST_MemSize(geom)) As geomsize,
sum(ST_MemSize(geom))*1.00/pg_total_relation_size('public.neighborhoods')*100 As pergeom
FROM neighborhoods;
fulltable_size geomsize pergeom
-----
262144 96238 36.71188354492187500000
```

7.4.28 ST_NDims

ST_NDims — ST_Geometry 数据类型函数。

Synopsis

integer **ST_NDims**(geometry g1);

☒

PostGIS 2 - 2 (x,y), 3 - 3 (x,y,z), 3 - 2 (x,y,m), 4 - 3 (x,y,z,m) 数据类型。

- ✔ This function supports 3d and will not drop the z-index.

例

```
SELECT ST_NDims(ST_GeomFromText('POINT(1 1)')) As d2point,
       ST_NDims(ST_GeomFromEWKT('POINT(1 1 2)')) As d3point,
       ST_NDims(ST_GeomFromEWKT('POINTM(1 1 0.5)')) As d2pointm;

d2point | d3point | d2pointm
-----+-----+-----
2       | 3       | 3
```

例

ST_CoordDim, **ST_Dimension**, **ST_GeomFromEWKT**

7.4.29 ST_NPoints

ST_NPoints — 返回几何体中的点数量 (整数)。

Synopsis

integer **ST_NPoints**(geometry g1);

例

返回几何体中的点数量。对于多面体表面，返回其顶点的数量。
 2.0.0 版本开始支持 (polyhedral surface) 几何体。



Note

1.3.4 版本开始支持 (curve) 几何体。1.3.4 版本开始支持 (polyhedral surface) 几何体。

- ✓ This function supports 3d and will not drop the z-index.
- ✓ This method supports Circular Strings and Curves.
- ✓ This function supports Polyhedral surfaces.

例

```
SELECT ST_NPoints(ST_GeomFromText('LINESTRING(77.29 29.07,77.42 29.26,77.27 29.31,77.29 29.07)'));
--result
4

--Polygon in 3D space
SELECT ST_NPoints(ST_GeomFromEWKT('LINESTRING(77.29 29.07 1,77.42 29.26 0,77.27 29.31 -1,77.29 29.07 3)'));
--result
4
```

返回

ST_NumPoints

7.4.30 ST_NRings

ST_NRings — 返回几何体中的环数。

Synopsis

integer **ST_NRings**(geometry geomA);

返回

NumInteriorRings 返回几何体中的内部环数。NumInteriorRings 返回几何体中的内部环数。

- ✔ This function supports 3d and will not drop the z-index.
- ✔ This method supports Circular Strings and Curves.

返回

```
SELECT ST_NRings(geom) As Nrings, ST_NumInteriorRings(geom) As ninterrings
FROM (SELECT ST_GeomFromText('POLYGON((1 2, 3 4, 5 6, 1 2))') As geom) As foo;
```

	nrings		ninterrings
(1 row)	1		0

返回

ST_NumInteriorRings

7.4.31 ST_NumGeometries

ST_NumGeometries — 返回几何体中的几何体数量。

Synopsis

integer **ST_NumGeometries**(geometry geom);

ST_NumGeometries

Returns the number of elements in a geometry collection (GEOMETRYCOLLECTION or MULTI*). For non-empty atomic geometries returns 1. For empty geometries returns 0.

更新: 2.0.0 支持空几何, 支持 TIN 几何。

更新: 2.0.0 支持空几何返回 NULL。2.0.0 之前, 空几何返回 1。

- ✔ This method implements the SQL/MM specification. SQL-MM 3: 9.1.4
- ✔ This function supports 3d and will not drop the z-index.
- ✔ This function supports Polyhedral surfaces.
- ✔ This function supports Triangles and Triangulated Irregular Network Surfaces (TIN).

SQL

```
--Prior versions would have returned NULL for this -- in 2.0.0 this returns 1
SELECT ST_NumGeometries(ST_GeomFromText('LINESTRING(77.29 29.07,77.42 29.26,77.27 29.31,77.29 29.07)'));
--result
1

--Geometry Collection Example - multis count as one geom in a collection
SELECT ST_NumGeometries(ST_GeomFromEWKT('GEOMETRYCOLLECTION(MULTIPOINT((-2 3),(-2 2)),
LINESTRING(5 5 ,10 10),
POLYGON((-7 4.2,-7.1 5,-7.1 4.3,-7 4.2)))'));
--result
3
```

SQL

ST_GeometryN, **ST_Multi**

7.4.32 ST_NumInteriorRings

ST_NumInteriorRings — 返回多边形内部环的数量。

Synopsis

integer **ST_NumInteriorRings**(geometry a_polygon);

SQL

更新: 2.0.0 支持空几何。空几何返回 NULL。

- ✔ This method implements the SQL/MM specification. SQL-MM 3: 8.2.5
- 更新: 2.0.0 支持空几何返回 NULL。

例

```
--If you have a regular polygon
SELECT gid, field1, field2, ST_NumInteriorRings(geom) AS numholes
FROM sometable;

--If you have multipolygons
--And you want to know the total number of interior rings in the MULTIPOLYGON
SELECT gid, field1, field2, SUM(ST_NumInteriorRings(geom)) AS numholes
FROM (SELECT gid, field1, field2, (ST_Dump(geom)).geom As geom
      FROM sometable) As foo
GROUP BY gid, field1,field2;
```

例

[ST_NumInteriorRing](#), [ST_PointN](#)

7.4.33 ST_NumInteriorRing

`ST_NumInteriorRing` — 返回多边形内部环的个数。 `ST_NumInteriorRings` 返回多边形内部环的个数。

Synopsis

integer **ST_NumInteriorRing**(geometry a_polygon);

例

[ST_NumInteriorRings](#), [ST_PointN](#)

7.4.34 ST_NumPatches

`ST_NumPatches` — 返回多边形内部环的个数。 如果输入为 NULL，则返回 NULL。

Synopsis

integer **ST_NumPatches**(geometry g1);

例

返回多边形内部环的个数。 如果输入为 NULL，则返回 NULL。 `ST_NumGeometries` 返回多边形内部环的个数。 `MM` 返回多边形内部环的个数。 `ST_NumGeometries` 返回多边形内部环的个数。

2.0.0 版本引入。



This function supports 3d and will not drop the z-index.



This method implements the [OGC Simple Features Implementation Specification for SQL 1.1](#).

- ✓ This method implements the SQL/MM specification. SQL-MM ISO/IEC 13249-3: 8.5
- ✓ This function supports Polyhedral surfaces.

例

```
SELECT ST_NumPatches(ST_GeomFromEWKT('POLYHEDRALSURFACE( ((0 0 0, 0 0 1, 0 1 1, 0 1 0, 0 0 0) ←
0)),
((0 0 0, 0 1 0, 1 1 0, 1 0 0, 0 0 0)), ((0 0 0, 1 0 0, 1 0 1, 0 0 1, 0 0 0) ←
),
((1 1 0, 1 1 1, 1 0 1, 1 0 0, 1 1 0)),
((0 1 0, 0 1 1, 1 1 1, 1 1 0, 0 1 0)), ((0 0 1, 1 0 1, 1 1 1, 0 1 1, 0 0 1) ←
) )''));
--result
6
```

例

[ST_GeomFromEWKT](#), [ST_NumGeometries](#)

7.4.35 ST_NumPoints

`ST_NumPoints` — `ST_LineString` 或 `ST_CircularString` 的几何体中的点数量。

Synopsis

integer **ST_NumPoints**(geometry g1);

例

`ST_LineString` 或 `ST_CircularString` 的几何体中的点数量。 1.4 版本中，`ST_NumPoints` 返回的点是几何体中的点，而不是几何体中的段。 1.4 版本中，`ST_NumPoints` 返回的点是几何体中的点，而不是几何体中的段。 `ST_NPoints` 返回的点是几何体中的点，而不是几何体中的段。 `ST_NPoints` 返回的点是几何体中的点，而不是几何体中的段。

- ✓ This method implements the [OGC Simple Features Implementation Specification for SQL 1.1](#).
- ✓ This method implements the SQL/MM specification. SQL-MM 3: 7.2.4

例

```
SELECT ST_NumPoints(ST_GeomFromText('LINESTRING(77.29 29.07,77.42 29.26,77.27 29.31,77.29 ←
29.07)'));
--result
4
```

例

[ST_NPoints](#)

7.4.36 ST_PatchN

ST_PatchN — ST_Geometry 函数。

Synopsis

geometry **ST_PatchN**(geometry geomA, integer n);

返回

如果 geomA 是 POLYHEDRALSURFACE, POLYHEDRALSURFACEM 或 1-N 面体 (多面体) 则返回面体。如果 geomA 是 NULL 则返回 NULL。如果 geomA 是其他类型则返回 ST_GeometryN 的结果。ST_GeometryN 返回面体。



Note

如果 n 是 1-面体。



Note

如果 geomA 是 ST_Dump 的结果。

2.0.0 版本。

- ✓ This method implements the SQL/MM specification. SQL-MM ISO/IEC 13249-3: 8.5
- ✓ This function supports 3d and will not drop the z-index.
- ✓ This function supports Polyhedral surfaces.

返回

```
--Extract the 2nd face of the polyhedral surface
SELECT ST_AsEWKT(ST_PatchN(geom, 2)) As geomewkt
FROM (
VALUES (ST_GeomFromEWKT('POLYHEDRALSURFACE( ((0 0 0, 0 0 1, 0 1 1, 0 1 0, 0 0 0)),
((0 0 0, 0 1 0, 1 1 0, 1 0 0, 0 0 0)), ((0 0 0, 1 0 0, 1 0 1, 0 0 1, 0 0 0)),
((1 1 0, 1 1 1, 1 0 1, 1 0 0, 1 1 0)),
((0 1 0, 0 1 1, 1 1 1, 1 1 0, 0 1 0)), ((0 0 1, 1 0 1, 1 1 1, 0 1 1, 0 0 1)) )' )) ) ←
      As foo(geom);

      geomewkt
-----+-----
POLYGON((0 0 0,0 1 0,1 1 0,1 0 0,0 0 0))
```

返回

ST_AsEWKT, ST_GeomFromEWKT, ST_Dump, ST_GeometryN, ST_NumGeometries


```
POINT(1 1)
POINT(2 2)
(3 rows)

--Example circular string
SELECT ST_AsText(ST_PointN(ST_GeomFromText('CIRCULARSTRING(1 2, 3 2, 1 2)'), 2));

    st_astext
-----
POINT(3 2)
(1 row)

SELECT ST_AsText(f)
FROM ST_GeomFromText('LINESTRING(0 0 0, 1 1 1, 2 2 2)') AS g
    ,ST_PointN(g, -2) AS f; -- 1 based index

    st_astext
-----
POINT Z (1 1 1)
(1 row)
```


ST_LineString 和 ST_CircularString 函数返回几何对象。

```
SELECT ST_AsText(ST_StartPoint('CIRCULARSTRING(5 2,-3 1.999999, -2 1, -4 2, 6 3)::geometry'::geometry ↵
));
st_astext
-----
POINT(5 2)
```

和

ST_EndPoint, ST_PointN

7.4.40 ST_Summary

ST_Summary — 返回几何对象的摘要字符串。

Synopsis

```
text ST_Summary(geometry g);
text ST_Summary(geography g);
```

和

返回摘要字符串。
返回摘要字符串的格式如下：

- M: M 值。
- Z: Z 值。
- B: 边界值。
- G: 几何体 (几何体) 值。
- S: 表面值。

✓ This method supports Circular Strings and Curves.

✓ This function supports Polyhedral surfaces.

✓ This function supports Triangles and Triangulated Irregular Network Surfaces (TIN).

1.2.2 返回摘要字符串。

摘要字符串: 2.0.0 返回摘要字符串。

摘要字符串: 2.1.0 和。返回摘要字符串的格式如下 S 值。

摘要字符串: 2.2.0 返回 TIN 值 (curve) 值。

SQL

```
=# SELECT ST_Summary(ST_GeomFromText('LINESTRING(0 0, 1 1)')) as geom,
          ST_Summary(ST_GeogFromText('POLYGON((0 0, 1 1, 1 2, 1 1, 0 0))')) geog;
-----+-----
LineString[B] with 2 points | Polygon[BGS] with 1 rings
                           | ring 0 has 5 points
                           :
(1 row)

=# SELECT ST_Summary(ST_GeogFromText('LINESTRING(0 0 1, 1 1 1)')) As geog_line,
          ST_Summary(ST_GeomFromText('SRID=4326;POLYGON((0 0 1, 1 1 2, 1 2 3, 1 1 1, 0 0 1))' ←
          ')) As geom_poly;
-----+-----
geog_line | geom_poly
-----+-----
LineString[ZBGS] with 2 points | Polygon[ZBS] with 1 rings
                           | ring 0 has 5 points
                           :
(1 row)
```

SQL

[PostGIS_DropBBox](#), [PostGIS_AddBBox](#), [ST_Force3DM](#), [ST_Force3DZ](#), [ST_Force2D](#), [geography](#)
[ST_IsValid](#), [ST_IsValid](#), [ST_IsValidReason](#), [ST_IsValidDetail](#)

7.4.41 ST_X

ST_X — Returns the X coordinate of a Point.

Synopsis

float **ST_X**(geometry a_point);

SQL

RETURNS X coordinate. X coordinate NULL if geometry is NULL. If geometry is not a point, an error is raised.



Note
To get the minimum and maximum X value of geometry coordinates use the functions [ST_XMin](#) and [ST_XMax](#).

- ✔ This method implements the SQL/MM specification. SQL-MM 3: 6.1.3
- ✔ This function supports 3d and will not drop the z-index.

例

```
SELECT ST_X(ST_GeomFromEWKT('POINT(1 2 3 4)'));
 st_x
-----
      1
(1 row)

SELECT ST_Y(ST_Centroid(ST_GeomFromEWKT('LINESTRING(1 2 3 4, 1 1 1 1)')));
 st_y
-----
    1.5
(1 row)
```

例

[ST_Centroid](#), [ST_GeomFromEWKT](#), [ST_M](#), [ST_XMax](#), [ST_XMin](#), [ST_Y](#), [ST_Z](#)

7.4.42 ST_Y

ST_Y — Returns the Y coordinate of a Point.

Synopsis

float **ST_Y**(geometry a_point);

例

返回 Y 坐标。Y 坐标为 NULL 时返回 NULL。支持 3D 几何。



Note

To get the minimum and maximum Y value of geometry coordinates use the functions [ST_YMin](#) and [ST_YMax](#).



This method implements the [OGC Simple Features Implementation Specification for SQL 1.1](#).



This method implements the SQL/MM specification. SQL-MM 3: 6.1.4



This function supports 3d and will not drop the z-index.

例

```
SELECT ST_Y(ST_GeomFromEWKT('POINT(1 2 3 4)'));
 st_y
-----
      2
(1 row)
```

```
SELECT ST_Y(ST_Centroid(ST_GeomFromEWKT('LINESTRING(1 2 3 4, 1 1 1 1)')));
st_y
-----
1.5
(1 row)
```

☐☐

[ST_Centroid](#), [ST_GeomFromEWKT](#), [ST_M](#), [ST_X](#), [ST_YMax](#), [ST_YMin](#), [ST_Z](#)

7.4.43 ST_Z

ST_Z — Returns the Z coordinate of a Point.

Synopsis

float **ST_Z**(geometry a_point);

☐☐

☐☐☐☐ Z ☐☐☐☐☐☐☐☐. Z ☐☐☐☐☐☐☐ NULL ☐☐☐☐☐☐. ☐☐☐☐☐☐☐☐☐☐☐☐.



Note

To get the minimum and maximum Z value of geometry coordinates use the functions [ST_ZMin](#) and [ST_ZMax](#).



This method implements the SQL/MM specification.



This function supports 3d and will not drop the z-index.

☐☐

```
SELECT ST_Z(ST_GeomFromEWKT('POINT(1 2 3 4)'));
st_z
-----
3
(1 row)
```

☐☐

[ST_GeomFromEWKT](#), [ST_M](#), [ST_X](#), [ST_Y](#), [ST_ZMax](#), [ST_ZMin](#)

7.4.44 ST_Zmflag

ST_Zmflag — ST_Geometry 的变体。

Synopsis

smallint **ST_Zmflag**(geometry geomA);

返回

ST_Geometry 的变体。

Values are: 0 = 2D, 1 = 3D-M, 2 = 3D-Z, 3 = 4D.

- ✔ This function supports 3d and will not drop the z-index.
- ✔ This method supports Circular Strings and Curves.

返回

```
SELECT ST_Zmflag(ST_GeomFromEWKT('LINESTRING(1 2, 3 4)'));
st_zmflag
-----
0

SELECT ST_Zmflag(ST_GeomFromEWKT('LINESTRINGM(1 2 3, 3 4 3)'));
st_zmflag
-----
1

SELECT ST_Zmflag(ST_GeomFromEWKT('CIRCULARSTRING(1 2 3, 3 4 3, 5 6 3)'));
st_zmflag
-----
2

SELECT ST_Zmflag(ST_GeomFromEWKT('POINT(1 2 3 4)'));
st_zmflag
-----
3
```

返回

ST_CoordDim, ST_NDims, ST_Dimension

7.4.45 ST_HasZ

ST_HasZ — Checks if a geometry has a Z dimension.

Synopsis

boolean **ST_HasZ**(geometry geom);



Checks if the input geometry has a Z dimension and returns a boolean value. If the geometry has a Z dimension, it returns true; otherwise, it returns false.

Geometry objects with a Z dimension typically represent three-dimensional (3D) geometries, while those without it are two-dimensional (2D) geometries.

This function is useful for determining if a geometry has elevation or height information.

Availability: 3.5.0



This function supports 3d and will not drop the z-index.



This function supports M coordinates.



```
SELECT ST_HasZ(ST_GeomFromText('POINT(1 2 3)'));
--result
true
```

```
SELECT ST_HasZ(ST_GeomFromText('LINESTRING(0 0, 1 1)'));
--result
false
```



ST_Zmflag

ST_HasM

7.4.46 ST_HasM

ST_HasM — Checks if a geometry has an M (measure) dimension.

Synopsis

boolean **ST_HasM**(geometry geom);



Checks if the input geometry has an M (measure) dimension and returns a boolean value. If the geometry has an M dimension, it returns true; otherwise, it returns false.

Geometry objects with an M dimension typically represent measurements or additional data associated with spatial features.

This function is useful for determining if a geometry includes measure information.

Availability: 3.5.0



This function supports 3d and will not drop the z-index.



This function supports M coordinates.

❏

```
SELECT ST_HasM(ST_GeomFromText('POINTM(1 2 3)'));
--result
true
```

```
SELECT ST_HasM(ST_GeomFromText('LINESTRING(0 0, 1 1)'));
--result
false
```

❏

ST_Zmflag

ST_HasZ

7.5 几何函数 (editor)

7.5.1 ST_AddPoint

ST_AddPoint — 向 LineString 添加点。

Synopsis

geometry **ST_AddPoint**(geometry linestring, geometry point);
 geometry **ST_AddPoint**(geometry linestring, geometry point, integer position = -1);

❏

Adds a point to a LineString before the index *position* (using a 0-based index). If the *position* parameter is omitted or is -1 the point is appended to the end of the LineString.

1.1.0 引入。



This function supports 3d and will not drop the z-index.

❏

Add a point to the end of a 3D line

```
SELECT ST_AsEWKT(ST_AddPoint('LINESTRING(0 0 1, 1 1 1)', ST_MakePoint(1, 2, 3)));

 st_asewkt
-----
LINESTRING(0 0 1,1 1 1,1 2 3)
```

Guarantee all lines in a table are closed by adding the start point of each line to the end of the line only for those that are not closed.

```
UPDATE sometable
SET geom = ST_AddPoint(geom, ST_StartPoint(geom))
FROM sometable
WHERE ST_IsClosed(geom) = false;
```

☐☐

[ST_RemovePoint](#), [ST_SetPoint](#)

7.5.2 ST_CollectionExtract

ST_CollectionExtract — Given a geometry collection, returns a multi-geometry containing only elements of a specified type.

Synopsis

geometry **ST_CollectionExtract**(geometry collection);

geometry **ST_CollectionExtract**(geometry collection, integer type);

☐☐

Given a geometry collection, returns a homogeneous multi-geometry.

If the *type* is not specified, returns a multi-geometry containing only geometries of the highest dimension. So polygons are preferred over lines, which are preferred over points.

If the *type* is specified, returns a multi-geometry containing only that type. If there are no sub-geometries of the right type, an EMPTY geometry is returned. Only points, lines and polygons are supported. The type numbers are:

- 1 == POINT
- 2 == LINESTRING
- 3 == POLYGON

For atomic geometry inputs, the geometry is returned unchanged if the input type matches the requested type. Otherwise, the result is an EMPTY geometry of the specified type. If required, these can be converted to multi-geometries using [ST_Multi](#).



Warning

MultiPolygon results are not checked for validity. If the polygon components are adjacent or overlapping the result will be invalid. (For example, this can occur when applying this function to an [ST_Split](#) result.) This situation can be checked with [ST_IsValid](#) and repaired with [ST_MakeValid](#).

1.5.0 简体中文版.



Note

Prior to 1.5.3 this function returned atomic inputs unchanged, no matter type. In 1.5.3 non-matching single geometries returned a NULL result. In 2.0.0 non-matching single geometries return an EMPTY result of the requested type.

例

Extract highest-dimension type:

```
SELECT ST_AsText(ST_CollectionExtract(
    'GEOMETRYCOLLECTION( POINT(0 0), LINESTRING(1 1, 2 2) )'));
 st_astext
-----
MULTILINESTRING((1 1, 2 2))
```

Extract points (type 1 == POINT):

```
SELECT ST_AsText(ST_CollectionExtract(
    'GEOMETRYCOLLECTION(GEOMETRYCOLLECTION(POINT(0 0)))',
    1 ));
 st_astext
-----
MULTIPOINT((0 0))
```

Extract lines (type 2 == LINESTRING):

```
SELECT ST_AsText(ST_CollectionExtract(
    'GEOMETRYCOLLECTION(GEOMETRYCOLLECTION(LINESTRING(0 0, 1 1)),LINESTRING(2 2, 3 3))' ↔
    ,
    2 ));
 st_astext
-----
MULTILINESTRING((0 0, 1 1), (2 2, 3 3))
```

例

`ST_CollectionHomogenize`, `ST_Multi`, `ST_IsValid`, `ST_MakeValid`

7.5.3 ST_CollectionHomogenize

`ST_CollectionHomogenize` — Returns the simplest representation of a geometry collection.

Synopsis

geometry **`ST_CollectionHomogenize`**(geometry collection);

例

“GEOMETRYCOLLECTION(POINT(0 0),LINESTRING(1 1,2 2))” → “MULTILINESTRING((1 1,2 2))”

- Homogeneous (uniform) collections are returned as the appropriate multi-geometry.
- Heterogeneous (mixed) collections are flattened into a single GeometryCollection.
- Collections containing a single atomic element are returned as that element.
- Atomic geometries are returned unchanged. If required, these can be converted to a multi-geometry using **`ST_Multi`**.



Warning

This function does not ensure that the result is valid. In particular, a collection containing adjacent or overlapping Polygons will create an invalid MultiPolygon. This situation can be checked with `ST_IsValid` and repaired with `ST_MakeValid`.

2.0.0 □□□□□□□□□□.



Single-element collection converted to an atomic geometry

```
SELECT ST_AsText(ST_CollectionHomogenize('GEOMETRYCOLLECTION(POINT(0 0))'));

st_astext
-----
POINT(0 0)
```

Nested single-element collection converted to an atomic geometry:

```
SELECT ST_AsText(ST_CollectionHomogenize('GEOMETRYCOLLECTION(MULTIPOINT((0 0)))'));
      st_astext
-----
POINT(0 0)
```

Collection converted to a multi-geometry:

```
SELECT ST_AsText(ST_CollectionHomogenize('GEOMETRYCOLLECTION(POINT(0 0),POINT(1 1))'));
      st_astext
-----
MULTIPOINT((0 0),(1 1))
```

Nested heterogeneous collection flattened to a GeometryCollection:

```
SELECT ST_AsText(ST_CollectionHomogenize('GEOMETRYCOLLECTION(POINT(0 0), GEOMETRYCOLLECTION ( LINESTRING(1 1, 2 2))')));
```

st_astext
GEOMETRYCOLLECTION(POINT(0 0),LINESTRING(1 1,2 2))

Collection of Polygons converted to an (invalid) MultiPolygon:

```
SELECT ST_AsText(ST_CollectionHomogenize('GEOMETRYCOLLECTION (POLYGON ((10 50, 50 50, 50 10, 10 10, 10 50)), POLYGON ((90 50, 90 10, 50 10, 50 50, 90 50)))'));

st_astext
-----
MULTIPOLYGON(((10 50,50 50,50 10,10 10,10 50)),((90 50,90 10,50 10,50 50,90 50)))
```



ST CollectionExtract, ST Multi, ST IsValid, ST MakeValid

7.5.4 ST_CurveToLine

ST_CurveToLine — Converts a geometry containing curves to a linear geometry.

Synopsis

geometry **ST_CurveToLine**(geometry curveGeom, float tolerance, integer tolerance_type, integer flags);

几何

Converts a CIRCULAR STRING to regular LINESTRING or CURVEPOLYGON to POLYGON or MULTISURFACE to MULTIPOLYGON. Useful for outputting to devices that can't support CIRCULARSTRING geometry types

Converts a given geometry to a linear geometry. Each curved geometry or segment is converted into a linear approximation using the given `tolerance` and options (32 segments per quadrant and no options by default).

The `tolerance\_type` argument determines interpretation of the `tolerance` argument. It can take the following values:

- 0 (default): Tolerance is max segments per quadrant.
- 1: Tolerance is max-deviation of line from curve, in source units.
- 2: Tolerance is max-angle, in radians, between generating radii.

The `flags` argument is a bitfield. 0 by default. Supported bits are:

- 1: Symmetric (orientation independent) output.
- 2: Retain angle, avoids reducing angles (segment lengths) when producing symmetric output. Has no effect when Symmetric flag is off.

Availability: 1.3.0

Enhanced: 2.4.0 added support for max-deviation and max-angle tolerance, and for symmetric output.

Enhanced: 3.0.0 implemented a minimum number of segments per linearized arc to prevent topological collapse.

- ✓ This method implements the [OGC Simple Features Implementation Specification for SQL 1.1](#).
- ✓ This method implements the SQL/MM specification. SQL-MM 3: 7.1.7
- ✓ This function supports 3d and will not drop the z-index.
- ✓ This method supports Circular Strings and Curves.

❏

```
SELECT ST_AsText(ST_CurveToLine(ST_GeomFromText('CIRCULARSTRING(220268 150415,220227 150505,220227 150406)')));

--Result --
LINESTRING(220268 150415,220269.95064912 150416.539364228,220271.823415575 150418.17258804,220273.613787707 150419.895736857,
220275.317452352 150421.704659462,220276.930305234 150423.594998003,220278.448460847 150425.562198489,
220279.868261823 150427.60152176,220281.186287736 150429.708054909,220282.399363347 150431.876723113,
220283.50456625 150434.10230186,220284.499233914 150436.379429536,220285.380970099 150438.702620341,220286.147650624 150441.066277505,
220286.797428488 150443.464706771,220287.328738321 150445.892130112,220287.740300149 150448.342699654,
220288.031122486 150450.810511759,220288.200504713 150453.289621251,220288.248038775 150455.77405574,
220288.173610157 150458.257830005,220287.977398166 150460.734960415,220287.659875492 150463.199479347,
220287.221807076 150465.64544956,220286.664248262 150468.066978495,220285.988542259 150470.458232479,220285.196316903 150472.81345077,
220284.289480732 150475.126959442,220283.270218395 150477.39318505,220282.140985384 150479.606668057,
220280.90450212 150481.762075989,220279.5637474 150483.85421628,220278.12195122 150485.87804878,
220276.582586992 150487.828697901,220274.949363179 150489.701464356,220273.226214362 150491.491836488,
220271.417291757 150493.195501133,220269.526953216 150494.808354014,220267.559752731 150496.326509628,
220265.520429459 150497.746310603,220263.41389631 150499.064336517,220261.245228106 150500.277412127,
220259.019649359 150501.38261503,220256.742521683 150502.377282695,220254.419330878 150503.259018879,
220252.055673714 150504.025699404,220249.657244448 150504.675477269,220247.229821107 150505.206787101,
220244.779251566 150505.61834893,220242.311439461 150505.909171266,220239.832329968 150506.078553494,
220237.347895479 150506.126087555,220234.864121215 150506.051658938,220232.386990804 150505.855446946,
220229.922471872 150505.537924272,220227.47650166 150505.099855856,220225.054972724 150504.542297043,
220222.663718741 150503.86659104,220220.308500449 150503.074365683,
220217.994991777 150502.167529512,220215.72876617 150501.148267175,
220213.515283163 150500.019034164,220211.35987523 150498.7825509,
220209.267734939 150497.441796181,220207.243902439 150496,
220205.293253319 150494.460635772,220203.420486864 150492.82741196,220201.630114732 150491.104263143,
220199.926450087 150489.295340538,220198.313597205 150487.405001997,220196.795441592 150485.437801511,
220195.375640616 150483.39847824,220194.057614703 150481.291945091,220192.844539092 150479.123276887,220191.739336189 150476.89769814,
220190.744668525 150474.620570464,220189.86293234 150472.297379659,220189.096251815 150469.933722495,
220188.446473951 150467.535293229,220187.915164118 150465.107869888,220187.50360229 150462.657300346,
220187.212779953 150460.189488241,220187.043397726 150457.710378749,220186.995863664 150455.22594426,
220187.070292282 150452.742169995,220187.266504273 150450.265039585,220187.584026947 150447.800520653,
220188.022095363 150445.35455044,220188.579654177 150442.933021505,220189.25536018 150440.541767521,
```

```

220190.047585536 150438.18654923,220190.954421707 150435.873040558,220191.973684044 ↵
    150433.60681495,
220193.102917055 150431.393331943,220194.339400319 150429.237924011,220195.680155039 ↵
    150427.14578372,220197.12195122 150425.12195122,
220198.661315447 150423.171302099,220200.29453926 150421.298535644,220202.017688077 ↵
    150419.508163512,220203.826610682 150417.804498867,
220205.716949223 150416.191645986,220207.684149708 150414.673490372,220209.72347298 ↵
    150413.253689397,220211.830006129 150411.935663483,
220213.998674333 150410.722587873,220216.22425308 150409.61738497,220218.501380756 ↵
    150408.622717305,220220.824571561 150407.740981121,
220223.188228725 150406.974300596,220225.586657991 150406.324522731,220227 150406)

--3d example
SELECT ST_AsEWKT(ST_CurveToLine(ST_GeomFromEWKT('CIRCULARSTRING(220268 150415 1,220227 ↵
    150505 2,220227 150406 3)')));
Output
-----
LINESTRING(220268 150415 1,220269.95064912 150416.539364228 1.0181172856673,
220271.823415575 150418.17258804 1.03623457133459,220273.613787707 150419.895736857 ↵
    1.05435185700189,...AD INFINITUM ....
    220225.586657991 150406.324522731 1.32611114201132,220227 150406 3)

--use only 2 segments to approximate quarter circle
SELECT ST_AsText(ST_CurveToLine(ST_GeomFromText('CIRCULARSTRING(220268 150415,220227 ↵
    150505,220227 150406)'),2));
st_astext
-----
LINESTRING(220268 150415,220287.740300149 150448.342699654,220278.12195122 ↵
    150485.87804878,
220244.779251566 150505.61834893,220207.243902439 150496,220187.50360229 150462.657300346,
220197.12195122 150425.12195122,220227 150406)

-- Ensure approximated line is no further than 20 units away from
-- original curve, and make the result direction-neutral
SELECT ST_AsText(ST_CurveToLine(
    'CIRCULARSTRING(0 0,100 -100,200 0)::geometry,
    20, -- Tolerance
    1, -- Above is max distance between curve and line
    1 -- Symmetric flag
));
st_astext
-----
LINESTRING(0 0,50 -86.6025403784438,150 -86.6025403784439,200 -1.1331077795296e-13,200 0)

```

☒☒

ST_LineToCurve

7.5.5 ST_Scroll

ST_Scroll — Change start point of a closed LineString.

Synopsis

geometry **ST_Scroll**(geometry linestring, geometry point);

☒☒

Changes the start/end point of a closed LineString to the given vertex *point*.

Availability: 3.2.0

- ✔ This function supports 3d and will not drop the z-index.
- ✔ This function supports M coordinates.

☒☒

Make a closed line start at its 3rd vertex

```
SELECT ST_AseWKT(ST_Scroll('SRID=4326;LINESTRING(0 0 0 1, 10 0 2 0, 5 5 4 2,0 0 0 1)', ' ←
    POINT(5 5 4 2)'));
```

```
st_asewkt
-----
SRID=4326;LINESTRING(5 5 4 2,0 0 0 1,10 0 2 0,5 5 4 2)
```

☒☒

ST_Normalize

7.5.6 ST_FlipCoordinates

ST_FlipCoordinates — Returns a version of a geometry with X and Y axis flipped.

Synopsis

geometry **ST_FlipCoordinates**(geometry geom);

☒☒

Returns a version of the given geometry with X and Y axis flipped. Useful for fixing geometries which contain coordinates expressed as latitude/longitude (Y,X).

2.0.0 简体中文.

- ✔ This method supports Circular Strings and Curves.
- ✔ This function supports 3d and will not drop the z-index.
- ✔ This function supports M coordinates.
- ✔ This function supports Polyhedral surfaces.
- ✔ This function supports Triangles and Triangulated Irregular Network Surfaces (TIN).

例

```
SELECT ST_AsEWKT(ST_FlipCoordinates(GeomFromEWKT('POINT(1 2)')));
      st_asewkt
-----
POINT(2 1)
```

例

ST_SwapOrdinates

7.5.7 ST_Force2D

ST_Force2D — 将“2 维几何”强制为 2D。

Synopsis

geometry **ST_Force2D**(geometry geomA);

例

“2 维几何”强制为 2D 几何。强制 (OGC 2 维几何) OGC 2 维几何。

2.0.0 强制 (polyhedral surface) 强制。

2.1.0 强制, 2.0.x 强制 ST_Force_2D 强制。



This method supports Circular Strings and Curves.



This function supports Polyhedral surfaces.



This function supports 3d and will not drop the z-index.

例

```
SELECT ST_AsEWKT(ST_Force2D(ST_GeomFromEWKT('CIRCULARSTRING(1 1 2, 2 3 2, 4 5 2, 6 7 2, 5 6 2)')));
      st_asewkt
-----
CIRCULARSTRING(1 1,2 3,4 5,6 7,5 6)

SELECT ST_AsEWKT(ST_Force2D('POLYGON((0 0 2,0 5 2,5 0 2,0 0 2),(1 1 2,3 1 2,1 3 2,1 1 2))'));
      st_asewkt
-----
POLYGON((0 0,0 5,5 0,0 0),(1 1,3 1,1 3,1 1))
```

函数

ST_Force3D

7.5.8 ST_Force3D

ST_Force3D — 强制 XYZ 模式。 ST_Force3DZ 类似。

Synopsis

geometry **ST_Force3D**(geometry geomA, float Zvalue = 0.0);

函数

Forces the geometries into XYZ mode. This is an alias for ST_Force3DZ. If a geometry has no Z component, then a *Zvalue* Z coordinate is tacked on.

版本: 2.0.0 引入 (polyhedral surface) 支持。

版本: 2.1.0 引入, 在 2.0.x 版本中 ST_Force_3D 支持。

Changed: 3.1.0. Added support for supplying a non-zero Z value.

- ✓ This function supports Polyhedral surfaces.
- ✓ This method supports Circular Strings and Curves.
- ✓ This function supports 3d and will not drop the z-index.

函数

```
--Nothing happens to an already 3D geometry
SELECT ST_AsEWKT(ST_Force3D(ST_GeomFromEWKT('CIRCULARSTRING(1 1 2, 2 3 2, 4 5 2, 6 7 2, 5 6 2)')));
          st_asewkt
-----
CIRCULARSTRING(1 1 2,2 3 2,4 5 2,6 7 2,5 6 2)

SELECT ST_AsEWKT(ST_Force3D('POLYGON((0 0,0 5,5 0,0 0),(1 1,3 1,1 3,1 1))'));
          st_asewkt
-----
POLYGON((0 0 0,0 5 0,5 0 0,0 0 0),(1 1 0,3 1 0,1 3 0,1 1 0))
```

函数

ST_AsEWKT, **ST_Force2D**, **ST_Force3DM**, **ST_Force3DZ**

7.5.9 ST_Force3DZ

ST_Force3DZ — 强制 XYZ 模式。

Synopsis

geometry **ST_Force3DZ**(geometry geomA, float Zvalue = 0.0);

更新

Forces the geometries into XYZ mode. If a geometry has no Z component, then a *Zvalue* Z coordinate is tacked on.

更新: 2.0.0 支持多面体表面 (polyhedral surface) 类型。

更新: 2.1.0 支持, 在 2.0.x 版本中 `ST_Force3DZ` 不支持。

更新: 3.1.0. Added support for supplying a non-zero Z value.

- ✓ This function supports Polyhedral surfaces.
- ✓ This function supports 3d and will not drop the z-index.
- ✓ This method supports Circular Strings and Curves.

更新

```
--Nothing happens to an already 3D geometry
SELECT ST_AsEWKT(ST_Force3DZ(ST_GeomFromEWKT('CIRCULARSTRING(1 1 2, 2 3 2, 4 5 2, 6 7 2, 5
6 2)')));

                                st_asewkt
-----
CIRCULARSTRING(1 1 2,2 3 2,4 5 2,6 7 2,5 6 2)

SELECT ST_AsEWKT(ST_Force3DZ('POLYGON((0 0,0 5,5 0,0 0),(1 1,3 1,1 3,1 1))'));

                                st_asewkt
-----
POLYGON((0 0 0,0 5 0,5 0 0,0 0 0),(1 1 0,3 1 0,1 3 0,1 1 0))
```

更新

ST_AsEWKT, ST_Force2D, ST_Force3DM, ST_Force3D

7.5.10 ST_Force3DM

ST_Force3DM — 将 XYM 几何体强制转换为 3D。

Synopsis

geometry **ST_Force3DM**(geometry geomA, float Mvalue = 0.0);

函数

Forces the geometries into XYM mode. If a geometry has no M component, then a *Mvalue* M coordinate is tacked on. If it has a Z component, then Z is removed

版本: 2.1.0 新增, 2.0.x 移除 ST_Force_3DM 函数。

Changed: 3.1.0. Added support for supplying a non-zero M value.

 This method supports Circular Strings and Curves.

函数

```
--Nothing happens to an already 3D geometry
SELECT ST_AsEWKT(ST_Force3DM(ST_GeomFromEWKT('CIRCULARSTRING(1 1 2, 2 3 2, 4 5 2, 6 7 2, 5 6 2)')));
```

	st_asewkt
-----	-----
	CIRCULARSTRINGM(1 1 0,2 3 0,4 5 0,6 7 0,5 6 0)

```
SELECT ST_AsEWKT(ST_Force3DM('POLYGON((0 0 1,0 5 1,5 0 1,0 0 1),(1 1 1,3 1 1,1 3 1,1 1 1))'));
--
```

	st_asewkt
-----	-----
	POLYGONM((0 0 0,0 5 0,5 0 0,0 0 0),(1 1 0,3 1 0,1 3 0,1 1 0))

函数

ST_AsEWKT, ST_Force2D, ST_Force3DM, ST_Force3D, ST_GeomFromEWKT

7.5.11 ST_Force4D

ST_Force4D — 将 XYZM 几何体强制转换为 4D。

Synopsis

geometry **ST_Force4D**(geometry geomA, float Zvalue = 0.0, float Mvalue = 0.0);

函数

Forces the geometries into XYZM mode. *Zvalue* and *Mvalue* is tacked on for missing Z and M dimensions, respectively.

版本: 2.1.0 新增, 2.0.x 移除 ST_Force_4D 函数。

Changed: 3.1.0. Added support for supplying non-zero Z and M values.

 This function supports 3d and will not drop the z-index.

 This method supports Circular Strings and Curves.

例

```
--Nothing happens to an already 3D geometry
SELECT ST_AsEWKT(ST_Force4D(ST_GeomFromEWKT('CIRCULARSTRING(1 1 2, 2 3 2, 4 5 2, 6 7 2, 5 6 2)')));

                                st_asewkt
-----
CIRCULARSTRING(1 1 2 0,2 3 2 0,4 5 2 0,6 7 2 0,5 6 2 0)

SELECT ST_AsEWKT(ST_Force4D('MULTILINESTRINGM((0 0 1,0 5 2,5 0 3,0 0 4),(1 1 1,3 1 1,1 3 1,1 1 1))'));

                                st_asewkt
-----
MULTILINESTRING((0 0 0 1,0 5 0 2,5 0 0 3,0 0 0 4),(1 1 0 1,3 1 0 1,1 3 0 1,1 1 0 1))
```

例

ST_AsEWKT, **ST_Force2D**, **ST_Force3DM**, **ST_Force3D**

7.5.12 ST_ForceCollection

ST_ForceCollection — 强制几何体为集合。

Synopsis

geometry **ST_ForceCollection**(geometry geomA);

例

强制几何体为集合。 返回 WKB 几何体。

版本: 2.0.0 引入 (polyhedral surface) 函数。

1.2.2 引入。 1.3.4 引入 (curve) 函数。 1.3.4 引入。

版本: 2.1.0 引入, 在 2.0.x 版本中 **ST_Force_Collection** 函数。

- ✔ This function supports Polyhedral surfaces.
- ✔ This function supports 3d and will not drop the z-index.
- ✔ This method supports Circular Strings and Curves.

例

- ✔ This function supports 3d and will not drop the z-index.
- ✔ This method supports Circular Strings and Curves.

国国

```
SELECT ST_AsText(
  ST_ForceCurve(
    'POLYGON((0 0 2, 5 0 2, 0 5 2, 0 0 2),(1 1 2, 1 3 2, 3 1 2, 1 1 2))'::geometry
  )
);
```

	st_astext

	CURVEPOLYGON Z ((0 0 2,5 0 2,0 5 2,0 0 2),(1 1 2,1 3 2,3 1 2,1 1 2))
(1 row)	

国国

ST_LineToCurve

7.5.14 ST_ForcePolygonCCW

ST_ForcePolygonCCW — Orients all exterior rings counter-clockwise and all interior rings clockwise.

Synopsis

geometry **ST_ForcePolygonCCW** (geometry geom);

国国

Forces (Multi)Polygons to use a counter-clockwise orientation for their exterior ring, and a clockwise orientation for their interior rings. Non-polygonal geometries are returned unchanged.

2.2.0 国国国国国国国国国国国国.

- ✔ This function supports 3d and will not drop the z-index.
- ✔ This function supports M coordinates.

国国

ST_ForcePolygonCW , **ST_IsPolygonCCW** , **ST_IsPolygonCW**

7.5.15 ST_ForcePolygonCW

ST_ForcePolygonCW — Orients all exterior rings clockwise and all interior rings counter-clockwise.

Synopsis

geometry **ST_ForcePolygonCW** (geometry geom);

返回

Forces (Multi)Polygons to use a clockwise orientation for their exterior ring, and a counter-clockwise orientation for their interior rings. Non-polygonal geometries are returned unchanged.

2.2.0 简体中文。

- ✔ This function supports 3d and will not drop the z-index.
- ✔ This function supports M coordinates.

返回

ST_ForcePolygonCCW , **ST_IsPolygonCCW** , **ST_IsPolygonCW**

7.5.16 ST_ForceSFS

ST_ForceSFS — 简体中文 SFS 1.1 简体中文。

Synopsis

geometry **ST_ForceSFS**(geometry geomA);
 geometry **ST_ForceSFS**(geometry geomA, text version);

返回

- ✔ This function supports Polyhedral surfaces.
- ✔ This function supports Triangles and Triangulated Irregular Network Surfaces (TIN).
- ✔ This method supports Circular Strings and Curves.
- ✔ This function supports 3d and will not drop the z-index.

7.5.17 ST_ForceRHR

ST_ForceRHR — 简体中文 (orientation) 简体中文 (Right-Hand Rule) 简体中文。

Synopsis

geometry **ST_ForceRHR**(geometry g);

国国

Forces the orientation of the vertices in a polygon to follow a Right-Hand-Rule, in which the area that is bounded by the polygon is to the right of the boundary. In particular, the exterior ring is orientated in a clockwise direction and the interior rings in a counter-clockwise direction. This function is a synonym for **ST_ForcePolygonCW**

**Note**

The above definition of the Right-Hand-Rule conflicts with definitions used in other contexts. To avoid confusion, it is recommended to use ST_ForcePolygonCW.

国国国国: 2.0.0 国国国国国国国国 (polyhedral surface) 国国国国国国.



This function supports 3d and will not drop the z-index.



This function supports Polyhedral surfaces.

国国

```
SELECT ST_AsEWKT(
  ST_ForceRHR(
    'POLYGON((0 0 2, 5 0 2, 0 5 2, 0 0 2),(1 1 2, 1 3 2, 3 1 2, 1 1 2))'
  )
);
```

	st_asewkt
	POLYGON((0 0 2,0 5 2,5 0 2,0 0 2),(1 1 2,3 1 2,1 3 2,1 1 2))
(1 row)	

国国

ST_ForcePolygonCCW , **ST_ForcePolygonCW** , **ST_IsPolygonCCW** , **ST_IsPolygonCW** , **ST_BuildArea**, **ST_Polygonize**, **ST_Reverse**

7.5.18 ST_LineExtend

ST_LineExtend — Returns a line extended forwards and backwards by specified distances.

Synopsis

geometry **ST_LineExtend**(geometry line, float distance_forward, float distance_backward=0.0);

国国

Returns a line extended forwards and backwards by adding new start (and end) points at the given distance(s). A distance of zero does not add a point. Only non-negative distances are allowed. The direction(s) of the added point(s) is determined by the first (and last) two distinct points of the line. Duplicate points are ignored.

Availability: 3.4.0

Example: Extends a line 5 units forward and 6 units backward

```
SELECT ST_AsText(ST_LineExtend('LINESTRING(0 0, 0 10)::geometry, 5, 6));
-----
LINESTRING(0 -6,0 0,0 10,0 15)
```



ST_LineSubstring, ST_LocateAlong, ST_Project

7.5.19 ST_LineToCurve

ST_LineToCurve — Converts a linear geometry to a curved geometry.

Synopsis

```
geometry ST_LineToCurve(geometry geomANoncircular);
```



Converts plain LINESTRING/POLYGON to CIRCULAR STRINGS and Curved Polygons. Note much fewer points are needed to describe the curved equivalent.



Note

If the input `LINESTRING`/`POLYGON` is not curved enough to clearly represent a curve, the function will return the same input geometry.

Availability: 1.3.0



This function supports 3d and will not drop the z-index.



This method supports Circular Strings and Curves.



```
-- 2D Example
SELECT ST_AsText(ST_LineToCurve(foo.geom)) As curvedastext, ST_AsText(foo.geom) As
    non_curvedastext
FROM (SELECT ST_Buffer('POINT(1 3)::geometry', 3) As geom) As foo;
```

curvedatext	non_curvedastext
CURVEPOLYGON(CIRCULARSTRING(4 3,3.12132034355964 0.878679656440359, POLYGON((4 ↵ 3,3.94235584120969 2.41472903395162,3.77163859753386 1.85194970290473, 1 0,-1.12132034355965 5.12132034355963,4 3)) 3.49440883690764 ↵ 1.33328930094119,3.12132034355964 0.878679656440359, 2.66671069905881 ↵ 0.505591163092366,2.14805029 0.228361402466141,	

```

| 1.58527096604839 ↵
| 0.0576441587903094,1 ↵
| 0,
| 0.414729033951621 ↵
| 0.0576441587903077,-0.1480502 ↵
| 0.228361402466137,
| -0.666710699058802 ↵
| 0.505591163092361,-1.12132034 ↵
| 0.878679656440353,
| -1.49440883690763 ↵
| 1.33328930094119,-1.77163859 ↵
| 1.85194970290472
| --ETC-- ↵
| ,3.94235584120969 ↵
| 3.58527096604839,4 ↵
| 3))

--3D example
SELECT ST_AsText(ST_LineToCurve(geom)) As curved, ST_AsText(geom) AS not_curved
FROM (SELECT ST_Translate(ST_Force3D(ST_Boundary(ST_Buffer(ST_Point(1,3), 2,2))),0,0,3) AS
geom) AS foo;

curved | not_curved
-----+-----
CIRCULARSTRING Z (3 3 3,-1 2.999999999999999 3,3 3 3) | LINESTRING Z (3 3 3,2.4142135623731 ↵
1.58578643762691 3,1 1 3,
| -0.414213562373092 1.5857864376269 ↵
3,-1 2.999999999999999 3,
| -0.414213562373101 4.41421356237309 ↵
3,
| 0.9999999999999991 5 ↵
3,2.41421356237309 4.4142135623731 ↵
3,3 3 3)

(1 row)

```



ST_CurveToLine

7.5.20 ST_Multi

ST_Multi — □□□□□□□□□□□□□□.

Synopsis

```
geometry ST_Multi(geometry geom);
```



Returns the geometry as a MULTI* geometry collection. If the geometry is already a collection, it is returned unchanged.

例

```
SELECT ST_AsText(ST_Multi('POLYGON ((10 30, 30 30, 30 10, 10 10, 10 30))'));
          st_astext
-----
MULTIPOLYGON(((10 30,30 30,30 10,10 10,10 30)))
```

例

ST_AsText

7.5.21 ST_Normalize

ST_Normalize — 规范化几何对象。

Synopsis

geometry **ST_Normalize**(geometry geom);

例

规范化几何对象。规范化几何对象，规范化几何对象。
规范化几何对象，规范化几何对象 (规范化几何对象)。
2.3.0 规范化几何对象。

例

```
SELECT ST_AsText(ST_Normalize(ST_GeomFromText(
  'GEOMETRYCOLLECTION(
    POINT(2 3),
    MULTILINESTRING((0 0, 1 1),(2 2, 3 3)),
    POLYGON(
      (0 10,0 0,10 0,10 10,0 10),
      (4 2,2 2,2 4,4 4,4 2),
      (6 8,8 8,8 6,6 6,6 8)
    )
  )'
)));
                                     st_astext
-----
GEOMETRYCOLLECTION(POLYGON((0 0,0 10,10 10,10 0,0 0),(6 6,8 6,8 8,6 8,6 6),(2 2,4 2,4 4,2 4,2 2)),MULTILINESTRING((2 2,3 3),(0 0,1 1)),POINT(2 3))
(1 row)
```

例

ST_Equals,

7.5.22 ST_Project

ST_Project — Returns a point projected from a start point by a distance and bearing (azimuth).

Synopsis

```
geometry ST_Project(geometry g1, float distance, float azimuth);
geometry ST_Project(geometry g1, geometry g2, float distance);
geography ST_Project(geography g1, float distance, float azimuth);
geography ST_Project(geography g1, geography g2, float distance);
```

描述

Returns a point projected from a point along a geodesic using a given distance and azimuth (bearing). This is known as the direct geodesic problem.

The two-point version uses the path from the first to the second point to implicitly define the azimuth and uses the distance as before.

The distance is given in meters. Negative values are supported.

The azimuth (also known as heading or bearing) is given in radians. It is measured clockwise from true north.

- North is azimuth zero (0 degrees)
- East is azimuth $\pi/2$ (90 degrees)
- South is azimuth π (180 degrees)
- West is azimuth $3\pi/2$ (270 degrees)

Negative azimuth values and values greater than 2π (360 degrees) are supported.

2.0.0 添加支持。

Enhanced: 2.4.0 Allow negative distance and non-normalized azimuth.

Enhanced: 3.4.0 Allow geometry arguments and two-point form omitting azimuth.

Example: Projected point at 100,000 meters and bearing 45 degrees

```
SELECT ST_AsText(ST_Project('POINT(0 0)::geography', 100000, radians(45.0)));
-----
POINT(0.635231029125537 0.639472334729198)
```

描述

[ST_Azimuth](#), [ST_Distance](#), [PostgreSQL function radians\(\)](#)

7.5.23 ST_QuantizeCoordinates

ST_QuantizeCoordinates — Sets least significant bits of coordinates to zero

Synopsis

geometry **ST_QuantizeCoordinates** (geometry g , int prec_x , int prec_y , int prec_z , int prec_m);



ST_QuantizeCoordinates determines the number of bits (N) required to represent a coordinate value with a specified number of digits after the decimal point, and then sets all but the N most significant bits to zero. The resulting coordinate value will still round to the original value, but will have improved compressibility. This can result in a significant disk usage reduction provided that the geometry column is using a **compressible storage type**. The function allows specification of a different number of digits after the decimal point in each dimension; unspecified dimensions are assumed to have the precision of the x dimension. Negative digits are interpreted to refer digits to the left of the decimal point, (i.e., `prec_x=-2` will preserve coordinate values to the nearest 100.

The coordinates produced by **ST_QuantizeCoordinates** are independent of the geometry that contains those coordinates and the relative position of those coordinates within the geometry. As a result, existing topological relationships between geometries are unaffected by use of this function. The function may produce invalid geometry when it is called with a number of digits lower than the intrinsic precision of the geometry.

Availability: 2.5.0

Technical Background

PostGIS stores all coordinate values as double-precision floating point integers, which can reliably represent 15 significant digits. However, PostGIS may be used to manage data that intrinsically has fewer than 15 significant digits. An example is TIGER data, which is provided as geographic coordinates with six digits of precision after the decimal point (thus requiring only nine significant digits of longitude and eight significant digits of latitude.)

When 15 significant digits are available, there are many possible representations of a number with 9 significant digits. A double precision floating point number uses 52 explicit bits to represent the significand (mantissa) of the coordinate. Only 30 bits are needed to represent a mantissa with 9 significant digits, leaving 22 insignificant bits; we can set their value to anything we like and still end up with a number that rounds to our input value. For example, the value 100.123456 can be represented by the floating point numbers closest to 100.123456000000, 100.123456000001, and 100.123456432199. All are equally valid, in that **ST_AsText**(geom, 6) will return the same result with any of these inputs. As we can set these bits to any value, **ST_QuantizeCoordinates** sets the 22 insignificant bits to zero. For a long coordinate sequence this creates a pattern of blocks of consecutive zeros that is compressed by PostgreSQL more efficiently.



Note

Only the on-disk size of the geometry is potentially affected by **ST_QuantizeCoordinates**. **ST_MemSize**, which reports the in-memory usage of the geometry, will return the the same value regardless of the disk space used by a geometry.



```
SELECT ST_AsText(ST_QuantizeCoordinates('POINT (100.123456 0)::geometry, 4));
st_astext
-----
POINT(100.123455047607 0)
```

```
WITH test AS (SELECT 'POINT (123.456789123456 123.456789123456)::geometry AS geom)
SELECT
  digits,
  encode(ST_QuantizeCoordinates(geom, digits), 'hex'),
  ST_AsText(ST_QuantizeCoordinates(geom, digits))
FROM test, generate_series(15, -15, -1) AS digits;
```

digits	encode	st_astext
15	010100000005f9a72083cdd5e405f9a72083cdd5e40	POINT(123.456789123456 123.456789123456)
14	010100000005f9a72083cdd5e405f9a72083cdd5e40	POINT(123.456789123456 123.456789123456)
13	010100000005f9a72083cdd5e405f9a72083cdd5e40	POINT(123.456789123456 123.456789123456)
12	010100000005c9a72083cdd5e405c9a72083cdd5e40	POINT(123.456789123456 123.456789123456)
11	01010000000409a72083cdd5e40409a72083cdd5e40	POINT(123.456789123456 123.456789123456)
10	0101000000009a72083cdd5e40009a72083cdd5e40	POINT(123.456789123455 123.456789123455)
9	0101000000009072083cdd5e40009072083cdd5e40	POINT(123.456789123418 123.456789123418)
8	0101000000008072083cdd5e40008072083cdd5e40	POINT(123.45678912336 123.45678912336)
7	0101000000000070083cdd5e40000070083cdd5e40	POINT(123.456789121032 123.456789121032)
6	0101000000000040083cdd5e40000040083cdd5e40	POINT(123.456789076328 123.456789076328)
5	0101000000000000083cdd5e400000000083cdd5e40	POINT(123.456789016724 123.456789016724)
4	0101000000000000003cdd5e400000000003cdd5e40	POINT(123.456787109375 123.456787109375)
3	010100000000000000003cdd5e400000000003cdd5e40	POINT(123.456787109375 123.456787109375)
2	0101000000000000000038dd5e4000000000038dd5e40	POINT(123.45654296875 123.45654296875)
1	01010000000000000000dd5e40000000000dd5e40	POINT(123.453125 123.453125)
0	01010000000000000000dc5e40000000000dc5e40	POINT(123.4375 123.4375)
-1	01010000000000000000c05e400000000000c05e40	POINT(123 123)
-2	0101000000000000000005e400000000000005e40	POINT(120 120)
-3	01010000000000000000058400000000000005840	POINT(96 96)
-4	01010000000000000000058400000000000005840	POINT(96 96)
-5	01010000000000000000058400000000000005840	POINT(96 96)
-6	01010000000000000000058400000000000005840	POINT(96 96)
-7	01010000000000000000058400000000000005840	POINT(96 96)
-8	01010000000000000000058400000000000005840	POINT(96 96)
-9	01010000000000000000058400000000000005840	POINT(96 96)
-10	01010000000000000000058400000000000005840	POINT(96 96)
-11	01010000000000000000058400000000000005840	POINT(96 96)
-12	01010000000000000000058400000000000005840	POINT(96 96)
-13	01010000000000000000058400000000000005840	POINT(96 96)
-14	01010000000000000000058400000000000005840	POINT(96 96)
-15	01010000000000000000058400000000000005840	POINT(96 96)

☒☒

ST_SnapToGrid

7.5.24 ST_RemovePoint

ST_RemovePoint — Remove a point from a linestring.

Synopsis

geometry **ST_RemovePoint**(geometry linestring, integer offset);

⚠️

Removes a point from a LineString, given its index (0-based). Useful for turning a closed line (ring) into an open linestring.

Enhanced: 3.2.0

1.1.0 简体中文.



This function supports 3d and will not drop the z-index.

⚠️

Guarantees no lines are closed by removing the end point of closed lines (rings). Assumes geom is of type LINESTRING

```
UPDATE sometable
  SET geom = ST_RemovePoint(geom, ST_NPoints(geom) - 1)
FROM sometable
WHERE ST_IsClosed(geom);
```

⚠️

ST_AddPoint, **ST_NPoints**, **ST_NumPoints**

7.5.25 ST_RemoveRepeatedPoints

ST_RemoveRepeatedPoints — Returns a version of a geometry with duplicate points removed.

Synopsis

geometry **ST_RemoveRepeatedPoints**(geometry geom, float8 tolerance);

⚠️

Returns a version of the given geometry with duplicate consecutive points removed. The function processes only (Multi)LineStrings, (Multi)Polygons and MultiPoints but it can be called with any kind of geometry. Elements of GeometryCollections are processed individually. The endpoints of LineStrings are preserved.

If the *tolerance* parameter is provided, vertices within the tolerance distance of one another are considered to be duplicates.

Enhanced: 3.2.0

2.2.0 新增功能.

- ✔ This function supports Polyhedral surfaces.
- ✔ This function supports 3d and will not drop the z-index.

☐☐

```
SELECT ST_AsText( ST_RemoveRepeatedPoints( 'MULTIPOINT ((1 1), (2 2), (3 3), (2 2))' ));
-----
MULTIPOINT(1 1,2 2,3 3)
```

```
SELECT ST_AsText( ST_RemoveRepeatedPoints( 'LINESTRING (0 0, 0 0, 1 1, 0 0, 1 1, 2 2)' ));
-----
LINESTRING(0 0,1 1,0 0,1 1,2 2)
```

Example: Collection elements are processed individually.

```
SELECT ST_AsText( ST_RemoveRepeatedPoints( 'GEOMETRYCOLLECTION (LINESTRING (1 1, 2 2, 2 2, 3 3), POINT (4 4), POINT (4 4), POINT (5 5))' ));
-----
GEOMETRYCOLLECTION(LINESTRING(1 1,2 2,3 3),POINT(4 4),POINT(4 4),POINT(5 5))
```

Example: Repeated point removal with a distance tolerance.

```
SELECT ST_AsText( ST_RemoveRepeatedPoints( 'LINESTRING (0 0, 0 0, 1 1, 5 5, 1 1, 2 2)', 2) ) ←
;
-----
LINESTRING(0 0,5 5,2 2)
```

☐☐

ST_Simplify

7.5.26 ST_RemoveIrrelevantPointsForView

ST_RemoveIrrelevantPointsForView — Removes points that are irrelevant for rendering a specific rectangular view of a geometry.

Synopsis

geometry **ST_RemoveIrrelevantPointsForView**(geometry geom, box2d bounds, boolean cartesian_hint = false);

☐☐

Returns a **geometry** without points being irrelevant for rendering the geometry within a given rectangular view.

This function can be used to quickly preprocess geometries that should be rendered only within certain bounds.

Only geometries of type (MULTI)POLYGON and (MULTI)LINESTRING are evaluated. Other geometries keep unchanged.

In contrast to `ST_ClipByBox2D()` this function

- sorts out points without computing new intersection points which avoids rounding errors and usually increases performance,
- returns a geometry with equal or similar point number,
- leads to the same rendering result within the specified view, and
- may introduce self-intersections which would make the resulting geometry invalid (see example below).


If `cartesian_hint` is set to `true`, the algorithm applies additional optimizations involving cartesian math to further reduce the resulting point number. Please note that using this option might introduce rendering artifacts if the resulting coordinates are projected into another (non-cartesian) coordinate system before rendering.




Warning

For polygons, this function does currently not ensure that the result is valid. This situation can be checked with `ST_IsValid` and repaired with `ST_MakeValid`.


original
55 points



`ST_RemoveIrrelevantPointsForView(geom, bbox)`
15 points




`ST_ClipByBox2D(geom, bbox)`
15 points




Example: `ST_RemoveIrrelevantPointsForView()` applied to a polygon. Blue points remain, the rendering result (light-blue area) within the grey view box remains as well.

original
7 points



`ST_RemoveIrrelevantPointsForView(geom, bbox)`
5 points



Example: Due to the fact that points are just sorted out and no new points are computed, the result of `ST_RemoveIrrelevantPointsForView()` may contain self-intersections.

Availability: 3.5.0

☒☒

```
SELECT ST_AsText(
    ST_RemoveIrrelevantPointsForView(
        ST_GeomFromText('MULTIPOLYGON(((10 10, 20 10, 30 10, 40 10, 20 20, 10 20, 10 10)),((10 10, 20 10, 20 20, 10 20, 10 10)))'),
        ST_MakeEnvelope(12,12,18,18), true));

st_astext
-----
MULTIPOLYGON(((10 10,40 10,20 20,10 20,10 10)),((10 10,20 10,20 20,10 20,10 10)))
```

```
SELECT ST_AsText(
    ST_RemoveIrrelevantPointsForView(
        ST_GeomFromText('MULTILINESTRING((0 0, 10 0,20 0,30 0), (0 15, 5 15, 10 15, 15 15, 20 15, 25 15, 30 15, 40 15), (13 13,15 15,17 17))'),
        ST_MakeEnvelope(12,12,18,18), true));

st_astext
-----
MULTILINESTRING((10 15,15 15,20 15),(13 13,15 15,17 17))
```

```
SELECT ST_AsText(
    ST_RemoveIrrelevantPointsForView(
        ST_GeomFromText('LINESTRING(0 0, 10 0,20 0,30 0)'),
        ST_MakeEnvelope(12,12,18,18), true));

st_astext
-----
LINESTRING EMPTY
```

```
SELECT ST_AsText(
    ST_RemoveIrrelevantPointsForView(
        ST_GeomFromText('POLYGON((0 30, 15 30, 30 30, 30 0, 0 0, 0 30))'),
        ST_MakeEnvelope(12,12,18,18), true));

st_astext
-----
POLYGON((15 30,30 0,0 0,15 30))
```

```
SELECT ST_AsText(
    ST_RemoveIrrelevantPointsForView(
        ST_GeomFromText('POLYGON((0 30, 15 30, 30 30, 30 0, 0 0, 0 30))'),
        ST_MakeEnvelope(12,12,18,18)));

st_astext
-----
POLYGON((0 30,30 30,30 0,0 0,0 30))
```

☒☒

ST_ClipByBox2D, ST_Intersection

7.5.27 ST_RemoveSmallParts

ST_RemoveSmallParts — Removes small parts (polygon rings or linestrings) of a geometry.

Synopsis

geometry **ST_RemoveSmallParts**(geometry geom, double precision minSizeX, double precision minSizeY);

国国

Returns a **geometry** without small parts (exterior or interior polygon rings, or linestrings).

This function can be used as preprocessing step for creating simplified maps, e. g. to remove small islands or holes.

It evaluates only geometries of type (MULTI)POLYGON and (MULTI)LINESTRING. Other geometries remain unchanged.

If *minSizeX* is greater than 0, parts are sorted out if their width is smaller than *minSizeX*.

If *minSizeY* is greater than 0, parts are sorted out if their height is smaller than *minSizeY*.

Both *minSizeX* and *minSizeY* are measured in coordinate system units of the geometry.

For polygon types, evaluation is done separately for each ring which can lead to one of the following results:

- the original geometry,
- a POLYGON with all rings with less vertices,
- a POLYGON with a reduced number of interior rings (having possibly less vertices),
- a POLYGON EMPTY, or
- a MULTIPOLYGON with a reduced number of polygons (having possibly less interior rings or vertices), or
- a MULTIPOLYGON EMPTY.

For linestring types, evaluation is done for each linestring which can lead to one of the following results:

- the original geometry,
 - a LINESTRING with a reduced number of vertices,
 - a LINESTRING EMPTY,
 - a MULTILINESTRING with a reduced number of linestrings (having possibly less vertices), or
 - a MULTILINESTRING EMPTY.
-



Example: `ST_RemoveSmallParts()` applied to a multi-polygon. Blue parts remain.

Availability: 3.5.0

SQL

```
SELECT ST_AsText(
    ST_RemoveSmallParts(
        ST_GeomFromText('MULTIPOLYGON(
            ((60 160, 120 160, 120 220, 60 220, 60 160), (70 170, 70 210, 110 210, 110 170, 70 170)),
            ((85 75, 155 75, 155 145, 85 145, 85 75)),
            ((50 110, 70 110, 70 130, 50 130, 50 110)))'),
        50, 50));

st_astext
-----
MULTIPOLYGON(((60 160,120 160,120 220,60 220,60 160)),((85 75,155 75,155 145,85 145,85 75)))

SELECT ST_AsText(
    ST_RemoveSmallParts(
        ST_GeomFromText('LINESTRING(10 10, 20 20)'),
        50, 50));

st_astext
-----
LINESTRING EMPTY
```

7.5.28 ST_Reverse

`ST_Reverse` — 返回几何图形的反向。

Synopsis

geometry **ST_Reverse**(geometry g1);

新特性

ST_MakeLine, ST_MakeLine3D.

Enhanced: 2.4.0 support for curves was introduced.



This function supports 3d and will not drop the z-index.



This function supports Polyhedral surfaces.

新特性

```
SELECT ST_AsText(geom) as line, ST_AsText(ST_Reverse(geom)) As reverseline
FROM
(SELECT ST_MakeLine(ST_Point(1,2),
                    ST_Point(1,10)) As geom) as foo;
--result
      line      |      reverseline
-----+-----
LINESTRING(1 2,1 10) | LINESTRING(1 10,1 2)
```

7.5.29 ST_Segmentize

ST_Segmentize — Returns a modified geometry/geography having no segment longer than a given distance.

Synopsis

```
geometry ST_Segmentize(geometry geom, float max_segment_length);
geography ST_Segmentize(geography geog, float max_segment_length);
```

新特性

Returns a modified geometry/geography having no segment longer than `max_segment_length`. Length is computed in 2D. Segments are always split into equal-length subsegments.

- For geometry, the maximum length is in the units of the spatial reference system.
- For geography, the maximum length is in meters. Distances are computed on the sphere. Added vertices are created along the spherical great-circle arcs defined by segment endpoints.



Note

This only shortens long segments. It does not lengthen segments shorter than the maximum length.



Warning

For inputs containing long segments, specifying a relatively short `max_segment_length` can cause a very large number of vertices to be added. This can happen unintentionally if the argument is specified accidentally as a number of segments, rather than a maximum length.

1.2.2 新新新新新新新新新新.

Enhanced: 3.0.0 Segmentize geometry now produces equal-length subsegments

Enhanced: 2.3.0 Segmentize geography now produces equal-length subsegments

新新新: 2.1.0 新新新新新新新新新新新新新新新新.

Changed: 2.1.0 As a result of the introduction of geography support, the usage `ST_Segmentize('LINESTRING(2, 3 4)', 0.5)` causes an ambiguous function error. The input needs to be properly typed as a geometry or geography. Use `ST_GeomFromText`, `ST_GeogFromText` or a cast to the required type (e.g. `ST_Segmentize('LINESTRING(1 2, 3 4)::geometry, 0.5)`)

新新

Segmentizing a line. Long segments are split evenly, and short segments are not split.

```
SELECT ST_AsText(ST_Segmentize(
  'MULTILINESTRING((0 0, 0 1, 0 9),(1 10, 1 18))'::geometry,
    5 ) );
```

```
-----
MULTILINESTRING((0 0,0 1,0 5,0 9),(1 10,1 14,1 18))
```

Segmentizing a polygon:


```
SELECT ST_AsText(
  ST_Segmentize(('POLYGON((0 0, 0 8, 30 0, 0 0))'::geometry), 10));
```

```
-----
POLYGON((0 0,0 8,7.5 6,15 4,22.5 2,30 0,20 0,10 0,0 0))
```

Segmentizing a geographic line, using a maximum segment length of 2000 kilometers. Vertices are added along the great-circle arc connecting the endpoints.

```
SELECT ST_AsText(
  ST_Segmentize(('LINESTRING (0 0, 60 60)'::geography), 2000000));
```

```
-----
LINESTRING(0 0,4.252632294621186 8.43596525986862,8.69579947419404  ←
16.824093489701564,13.550465473227048 25.107950473646188,19.1066053508691  ←
33.21091076089908,25.779290201459894 41.01711439406505,34.188839517966954  ←
48.337222885886,45.238153936612264 54.84733442373889,60 60)
```



A geographic line segmentized along a great circle arc

☐☐

[ST_LineSubstring](#)

7.5.30 ST_SetPoint

ST_SetPoint — 将点插入到线串中。

Synopsis

geometry **ST_SetPoint**(geometry linestring, integer zerobasedposition, geometry point);

☐☐

将点插入到线串中。N 是插入点的位置。N 从 0 开始。如果 N 是负数，则从线串的末尾开始。如果 N 是 0，则插入到线串的第一个点之前。如果 N 是 1，则插入到线串的最后一个点之后。

1.1.0 版本引入。

更新到 2.3.0 版本。



This function supports 3d and will not drop the z-index.

☐☐

```
--Change first point in line string from -1 3 to -1 1
SELECT ST_AsText(ST_SetPoint('LINESTRING(-1 2,-1 3)', 0, 'POINT(-1 1)'));
          st_astext
-----
LINESTRING(-1 1,-1 3)

---Change last point in a line string (lets play with 3d linestring this time)
SELECT ST_AsEWKT(ST_SetPoint(foo.geom, ST_NumPoints(foo.geom) - 1, ST_GeomFromEWKT('POINT (-1 1 3)'))
FROM (SELECT ST_GeomFromEWKT('LINESTRING(-1 2 3,-1 3 4, 5 6 7)') As geom) As foo;
          st_asewkt
-----
LINESTRING(-1 2 3,-1 3 4,-1 1 3)

SELECT ST_AsText(ST_SetPoint(g, -3, p))
FROM ST_GeomFromText('LINESTRING(0 0, 1 1, 2 2, 3 3, 4 4)') AS g
      , ST_PointN(g,1) as p;
          st_astext
-----
LINESTRING(0 0,1 1,0 0,3 3,4 4)
```

☐☐

[ST_AddPoint](#), [ST_NPoints](#), [ST_NumPoints](#), [ST_PointN](#), [ST_RemovePoint](#)

7.5.31 ST_ShiftLongitude

ST_ShiftLongitude — Shifts the longitude coordinates of a geometry between -180..180 and 0..360.

Synopsis

geometry **ST_ShiftLongitude**(geometry geom);

返回

Reads every point/vertex in a geometry, and shifts its longitude coordinate from -180..0 to 180..360 and vice versa if between these ranges. This function is symmetrical so the result is a 0..360 representation of a -180..180 data and a -180..180 representation of a 0..360 data.



Note

This is only useful for data with coordinates in longitude/latitude; e.g. SRID 4326 (WGS 84 geographic)



Warning

1.3.4 版本中，该函数在 PostgreSQL 11.0 之前版本中不可用。1.3.4 版本中，该函数在 PostgreSQL 11.0 之前版本中不可用。



This function supports 3d and will not drop the z-index.

版本: 2.0.0 版本 (polyhedral surface) 和 TIN 版本。

版本: 2.2.0 版本, 使用 "ST_Shift_Longitude" 函数。



This function supports Polyhedral surfaces.



This function supports Triangles and Triangulated Irregular Network Surfaces (TIN).

返回

```
--single point forward transformation
SELECT ST_AsText(ST_ShiftLongitude('SRID=4326;POINT(270 0)::geometry'))
```

```
st_astext
-----
POINT(-90 0)
```

```
--single point reverse transformation
SELECT ST_AsText(ST_ShiftLongitude('SRID=4326;POINT(-90 0)::geometry'))
```

```
st_astext
-----
POINT(270 0)
```

```
--for linestrings the functions affects only to the sufficient coordinates
```

```
SELECT ST_AsText(ST_ShiftLongitude('SRID=4326;LINESTRING(174 12, 182 13)::geometry'))
st_astext
-----
LINESTRING(174 12,-178 13)
```

☐☐

ST_WrapX

7.5.32 ST_WrapX

ST_WrapX — X 坐标轴上的坐标值进行包裹。

Synopsis

geometry **ST_WrapX**(geometry geom, float8 wrap, float8 move);

☐☐

This function splits the input geometries and then moves every resulting component falling on the right (for negative 'move') or on the left (for positive 'move') of given 'wrap' line in the direction specified by the 'move' parameter, finally re-unioning the pieces together.



Note

ST_WrapX 函数在移动几何体时，不会移动 z 索引。

Availability: 2.3.0 requires GEOS



This function supports 3d and will not drop the z-index.

☐☐

```
-- Move all components of the given geometries whose bounding box
-- falls completely on the left of x=0 to +360
select ST_WrapX(geom, 0, 360);

-- Move all components of the given geometries whose bounding box
-- falls completely on the left of x=-30 to +360
select ST_WrapX(geom, -30, 360);
```

☐☐

ST_ShiftLongitude

7.5.33 ST_SnapToGrid

ST_SnapToGrid — 将几何体 (geom) 对齐到指定的精度网格 (snap)。

Synopsis

```
geometry ST_SnapToGrid(geometry geomA, float originX, float originY, float sizeX, float sizeY);
geometry ST_SnapToGrid(geometry geomA, float sizeX, float sizeY);
geometry ST_SnapToGrid(geometry geomA, float size);
geometry ST_SnapToGrid(geometry geomA, geometry pointOrigin, float sizeX, float sizeY, float sizeZ,
float sizeM);
```

注意

参数 1, 2, 3: 将几何体对齐到指定的精度网格 (cell) 大小 (snap) 的网格。如果几何体是 2D 的，则使用 originX 和 originY 作为网格的起始点。如果几何体是 3D 的，则使用 originX, originY 和 originZ 作为网格的起始点。如果 sizeX 和 sizeY 为 NULL，则使用默认值 1.0。如果 size 为 NULL，则使用默认值 1.0。

参数 4: 1.1.0 版本引入。将几何体对齐到指定的精度网格 (pointOrigin, sizeX, sizeY, sizeZ, sizeM) 的网格。如果 sizeX 和 sizeY 为 NULL，则使用默认值 1.0。如果 sizeZ 和 sizeM 为 NULL，则使用默认值 0。

Note!

Note

如果几何体不是简单的 (ST_IsSimple 返回 true)，则函数将返回 NULL。

Note!

Note

1.1.0 版本引入。将几何体对齐到指定的精度网格 (pointOrigin, sizeX, sizeY, sizeZ, sizeM) 的网格。如果 sizeX 和 sizeY 为 NULL，则使用默认值 2。如果 sizeZ 和 sizeM 为 NULL，则使用默认值 0。

1.0.0RC1 版本引入。

1.1.0 版本引入 Z 和 M 坐标。



This function supports 3d and will not drop the z-index.

注意

```
--Snap your geometries to a precision grid of 10^-3
UPDATE mytable
  SET geom = ST_SnapToGrid(geom, 0.001);

SELECT ST_AsText(ST_SnapToGrid(
    ST_GeomFromText('LINESTRING(1.1115678 2.123, 4.111111 3.2374897, 4.11112 3.23748667)'),
    0.001)
);
--
LINESTRING(1.112 2.123,4.111 3.237)
--Snap a 4d geometry
SELECT ST_AsEWKT(ST_SnapToGrid(
```


图 1





图 1: 一个正方形内部包含一个三角形，下方有一个绿色的 V 形，右侧有一个三角形。




1.01 $\frac{1}{x^2} = x^{-2}$. $\frac{d}{dx} x^{-2} = -2x^{-3} = -\frac{2}{x^3}$.

```
SELECT ST_AsText(ST_Snap(poly,line, ←
    ST_Distance(poly,line)*1.01)) AS polysna
FROM (SELECT
    ST_GeomFromText('MULTIPOLYGON(
        ((26 125, 26 200, 126 200, 126 125, ←
        26 125 ),
        ( 51 150, 101 150, 76 175, 51 150 ) ←
        ),
        (( 151 100, 151 200, 176 175, 151 ←
        100 )))') As poly,
    ST_GeomFromText('LINESTRING (5 ←
    107, 54 84, 101 100)') As line
    ) As foo;
```

polysnapped

```
MULTIPOLYGON(((26 125,26 200,126 200,126 ↵
    125,101 100,26 125),
(51 150,101 150,76 175,51 150)),((151 ↵
    100,151 200,176 175,151 100)))
```




1.25

```
SELECT ST_AsText(
    ST_Snap(poly,line, ST_Distance(poly, ↵
opped line)*1.25)
) AS polysnapped
FROM (SELECT
    ST_GeomFromText('MULTIPOLYGON(
        (( 26 125, 26 200, 126 200, 126 125, ↵
        26 125 ),
        ( 51 150, 101 150, 76 175, 51 150 ) ↵
    ),
    (( 151 100, 151 200, 176 175, 151 ↵
    100 )))') As poly,
    ST_GeomFromText('LINESTRING (5 ↵
    107, 54 84, 101 100)') As line
    ) As foo;
```

polysnapped


```
MULTIPOLYGON(((5 107,26 200,126 200,126 125,101 100,54 84,5 107),
(51 150,101 150,76 175,51 150)),((151 100,151 200,176 175,151 100)))
```



距离 1.01 将红色线段的端点移动到最近的青色多边形边界上。
 距离 1.01 将红色线段的端点移动到最近的青色多边形边界上。

```
SELECT ST_AsText(
  ST_Snap(line, poly, ST_Distance(poly, line)*1.01)
) AS linesnapped
FROM (SELECT
  ST_GeomFromText('MULTIPOLYGON(
    ((26 125, 26 200, 126 200, 126 125,
    26 125),
    (51 150, 101 150, 76 175, 51 150 ))
  ',
    ((151 100, 151 200, 176 175, 151
    100)))') As poly,
    ST_GeomFromText('LINESTRING (5
    107, 54 84, 101 100)') As line
  ) As foo;

          linesnapped
-----
LINESTRING(5 107,26 125,54 84,101 100)
```



距离 1.25 将红色线段的端点移动到最近的青色多边形边界上。
 距离 1.25 将红色线段的端点移动到最近的青色多边形边界上。

```
SELECT ST_AsText(
  ST_Snap(line, poly, ST_Distance(poly, line)*1.25)
) AS linesnapped
FROM (SELECT
  ST_GeomFromText('MULTIPOLYGON(
    ( 26 125, 26 200, 126 200, 126 125,
    26 125 ),
    (51 150, 101 150, 76 175, 51 150 ))
  ',
    ((151 100, 151 200, 176 175, 151
    100 )))') As poly,
    ST_GeomFromText('LINESTRING (5
    107, 54 84, 101 100)') As line
  ) As foo;

          linesnapped
-----
LINESTRING(26 125,54 84,101 100)
```

☐☐

ST_SnapToGrid

7.5.35 ST_SwapOrdinates

ST_SwapOrdinates — 交换几何体的纵坐标。

Synopsis

geometry **ST_SwapOrdinates**(geometry geom, cstring ords);

函数

函数返回一个文本字符串。

ords 返回一个文本字符串，其长度为 2 乘以 M 值。返回的字符串 x, y, z, m 格式。
2.2.0 版本支持。

- ✓ This method supports Circular Strings and Curves.
- ✓ This function supports 3d and will not drop the z-index.
- ✓ This function supports M coordinates.
- ✓ This function supports Polyhedral surfaces.
- ✓ This function supports Triangles and Triangulated Irregular Network Surfaces (TIN).

函数

```
-- Scale M value by 2
SELECT ST_AsText(
  ST_SwapOrdinates(
    ST_Scale(
      ST_SwapOrdinates(g, 'xm'),
      2, 1
    ),
    'xm'
  ) FROM ( SELECT 'POINT ZM (0 0 0 2)::geometry g ) foo;
  st_astext
-----
POINT ZM (0 0 0 4)
```

函数

ST_FlipCoordinates

7.6 Geometry Validation

7.6.1 ST_IsValid

ST_IsValid — Tests if a geometry is well-formed in 2D.

Synopsis

```
boolean ST_IsValid(geometry g);
boolean ST_IsValid(geometry g, integer flags);
```

☒☒

Tests if an `ST_Geometry` value is well-formed and valid in 2D according to the OGC rules. For geometries with 3 and 4 dimensions, the validity is still only tested in 2 dimensions. For geometries that are invalid, a PostgreSQL NOTICE is emitted providing details of why it is not valid.

For the version with the `flags` parameter, supported values are documented in [ST_IsValidDetail](#). This version does not print a NOTICE explaining invalidity.

For more information on the definition of geometry validity, refer to [Section 4.4](#).



Note

SQL-MM defines the result of `ST_IsValid(NULL)` to be 0, while PostGIS returns NULL.

GEOS ☒☒☒☒☒

The version accepting flags is available starting with 2.0.0.



This method implements the [OGC Simple Features Implementation Specification for SQL 1.1](#).



This method implements the SQL/MM specification. SQL-MM 3: 5.1.9



Note

Neither OGC-SFS nor SQL-MM specifications include a flag argument for `ST_IsValid`. The flag is a PostGIS extension.

☒☒

```
SELECT ST_IsValid(ST_GeomFromText('LINESTRING(0 0, 1 1)')) As good_line,
       ST_IsValid(ST_GeomFromText('POLYGON((0 0, 1 1, 1 2, 1 1, 0 0))')) As bad_poly
--results
NOTICE: Self-intersection at or near point 0 0
good_line | bad_poly
-----+-----
t         | f
```

☒☒

[ST_IsSimple](#), [ST_IsValidReason](#), [ST_IsValidDetail](#),

7.6.2 ST_IsValidDetail

`ST_IsValidDetail` — Returns a `valid_detail` row stating if a geometry is valid or if not a reason and a location.

Synopsis

`valid_detail` **`ST_IsValidDetail`**(geometry geom, integer flags);

ST_IsValidDetail

Returns a `valid_detail` row, containing a boolean (`valid`) stating if a geometry is valid, a varchar (`reason`) stating a reason why it is invalid and a geometry (`location`) pointing out where it is invalid. Useful to improve on the combination of `ST_IsValid` and `ST_IsValidReason` to generate a detailed report of invalid geometries.

The optional `flags` parameter is a bitfield. It can have the following values:

- 0: Use usual OGC SFS validity semantics.
- 1: Consider certain kinds of self-touching rings (inverted shells and exverted holes) as valid. This is also known as “the ESRI flag”, since this is the validity model used by those tools. Note that this is invalid under the OGC model.

GEOS 2.0.0 及以上版本。

2.0.0 及以上版本。

示例

```
--First 3 Rejects from a successful quintuplet experiment
SELECT gid, reason(ST_IsValidDetail(geom)), ST_AsText(location(ST_IsValidDetail(geom))) as
    location
FROM
(SELECT ST_MakePolygon(ST_ExteriorRing(e.buff), array_agg(f.line)) As geom, gid
FROM (SELECT ST_Buffer(ST_Point(x1*10,y1), z1) As buff, x1*10 + y1*100 + z1*1000 As gid
      FROM generate_series(-4,6) x1
      CROSS JOIN generate_series(2,5) y1
      CROSS JOIN generate_series(1,8) z1
      WHERE x1
> y1*0.5 AND z1 < x1*y1) As e
      INNER JOIN (SELECT ST_Translate(ST_ExteriorRing(ST_Buffer(ST_Point(x1*10,y1), z1)),
      y1*1, z1*2) As line
      FROM generate_series(-3,6) x1
      CROSS JOIN generate_series(2,5) y1
      CROSS JOIN generate_series(1,10) z1
      WHERE x1
> y1*0.75 AND z1 < x1*y1) As f
ON (ST_Area(e.buff)
> 78 AND ST_Contains(e.buff, f.line))
GROUP BY gid, e.buff) As quintuplet_experiment
WHERE ST_IsValid(geom) = false
ORDER BY gid
LIMIT 3;
```

gid	reason	location
5330	Self-intersection	POINT(32 5)
5340	Self-intersection	POINT(42 5)
5350	Self-intersection	POINT(52 5)

```
--simple example
SELECT * FROM ST_IsValidDetail('LINESTRING(220227 150406,2220227 150407,222020 150410)');
```

valid	reason	location
t		

☐☐

[ST_IsValid](#), [ST_IsValidReason](#)

7.6.3 ST_IsValidReason

[ST_IsValidReason](#) — Returns text stating if a geometry is valid, or a reason for invalidity.

Synopsis

```
text ST_IsValidReason(geometry geomA);
text ST_IsValidReason(geometry geomA, integer flags);
```

☐☐

Returns text stating if a geometry is valid, or if invalid a reason why.

Useful in combination with [ST_IsValid](#) to generate a detailed report of invalid geometries and reasons.

Allowed flags are documented in [ST_IsValidDetail](#).

GEOS ☐☐☐☐☐

Availability: 1.4

Availability: 2.0 version taking flags.

☐☐

```
-- invalid bow-tie polygon
SELECT ST_IsValidReason(
  'POLYGON ((100 200, 100 100, 200 200,
    200 100, 100 200))'::geometry) as validity_info;
validity_info
-----
Self-intersection[150 150]
```

```
--First 3 Rejects from a successful quintuplet experiment
SELECT gid, ST_IsValidReason(geom)as validity_info
FROM
(SELECT ST_MakePolygon(ST_ExteriorRing(e.buff), array_agg(f.line)) As geom, gid
FROM (SELECT ST_Buffer(ST_Point(x1*10,y1), z1) As buff, x1*10 + y1*100 + z1*1000 As gid
      FROM generate_series(-4,6) x1
      CROSS JOIN generate_series(2,5) y1
      CROSS JOIN generate_series(1,8) z1
      WHERE x1
> y1*0.5 AND z1 < x1*y1) As e
      INNER JOIN (SELECT ST_Translate(ST_ExteriorRing(ST_Buffer(ST_Point(x1*10,y1), z1)), ←
        y1*1, z1*2) As line
      FROM generate_series(-3,6) x1
      CROSS JOIN generate_series(2,5) y1
      CROSS JOIN generate_series(1,10) z1
      WHERE x1
> y1*0.75 AND z1 < x1*y1) As f
ON (ST_Area(e.buff)
> 78 AND ST_Contains(e.buff, f.line))
```

```
GROUP BY gid, e.buff) As quintuplet_experiment
WHERE ST_IsValid(geom) = false
ORDER BY gid
LIMIT 3;
```

gid	validity_info
5330	Self-intersection [32 5]
5340	Self-intersection [42 5]
5350	Self-intersection [52 5]

```
--simple example
SELECT ST_IsValidReason('LINESTRING(220227 150406,2220227 150407,222020 150410)');
```

st_isvalidreason
Valid Geometry

☒☒

ST_IsValid, ST_Summary

7.6.4 ST_MakeValid

ST_MakeValid — Attempts to make an invalid geometry valid without losing vertices.

Synopsis

```
geometry ST_MakeValid(geometry input);
geometry ST_MakeValid(geometry input, text params);
```

☒☒

The function attempts to create a valid representation of a given invalid geometry without losing any of the input vertices. Valid geometries are returned unchanged.

Supported inputs are: POINTS, MULTIPOINTS, LINESTRINGS, MULTILINESTRINGS, POLYGONS, MULTIPOLYGONS and GEOMETRYCOLLECTIONS containing any mix of them.

In case of full or partial dimensional collapses, the output geometry may be a collection of lower-to-equal dimension geometries, or a geometry of lower dimension.

Single polygons may become multi-geometries in case of self-intersections.

The params argument can be used to supply an options string to select the method to use for building valid geometry. The options string is in the format "method=linework|structure keepcollapsed=true|false". If no "params" argument is provided, the "linework" algorithm will be used as the default.

The "method" key has two values.

- "linework" is the original algorithm, and builds valid geometries by first extracting all lines, noding that linework together, then building a value output from the linework.
- "structure" is an algorithm that distinguishes between interior and exterior rings, building new geometry by unioning exterior rings, and then differencing all interior rings.

The "keepcollapsed" key is only valid for the "structure" algorithm, and takes a value of "true" or "false". When set to "false", geometry components that collapse to a lower dimensionality, for example a one-point linestring would be dropped.

GEOS 3.10.0

2.0.0 简体中文文档.

Enhanced: 2.0.1, speed improvements

Enhanced: 2.1.0, added support for GEOMETRYCOLLECTION and MULTIPOINT.


Enhanced: 3.1.0, added removal of Coordinates with NaN values.

Enhanced: 3.2.0, added algorithm options, 'linework' and 'structure' which requires GEOS >= 3.10.0.




This function supports 3d and will not drop the z-index.


☐☐



before_geom: MULTIPOLYGON of 2 overlapping polygons




after_geom: MULTIPOLYGON of 4 non-overlapping polygons




after_geom_structure: MULTIPOLYGON of 1 non-overlapping polygon


```
SELECT f.geom AS before_geom, ST_MakeValid(f.geom) AS after_geom, ST_MakeValid(f.geom, ←
    'method=structure') AS after_geom_structure
FROM (SELECT 'MULTIPOLYGON(((186 194,187 194,188 195,189 195,190 195,
191 195,192 195,193 194,194 194,194 193,195 192,195 191,
```

before_geom: MULTIPOLYGON of 6 overlapping polygons



after_geom: MULTIPOLYGON of 14 Non-overlapping polygons



after_geom_structure: MULTIPOLYGON of 1 Non-overlapping polygon

```
SELECT c.geom AS before_geom,  
       ST_MakeValid(c.geom) AS after_geom,  
       ST_MakeValid(c.geom, 'method=structure') AS after_geom_structure  
FROM (SELECT 'MULTIPOLYGON(((91 50,79 22,51 10,23 22,11 50,23 78,51 90,79 78,91 50)))
```

 例

```
SELECT ST_AsText(ST_MakeValid(
    'LINESTRING(0 0, 0 0)',
    'method=structure keepcollapsed=true'
));

st_astext
-----
POINT(0 0)

SELECT ST_AsText(ST_MakeValid(
    'LINESTRING(0 0, 0 0)',
    'method=structure keepcollapsed=false'
));

st_astext
-----
LINESTRING EMPTY
```

例

[ST_IsValid](#), [ST_Collect](#), [ST_CollectionExtract](#)

7.7 Spatial Reference System Functions

7.7.1 ST_InverseTransformPipeline

ST_InverseTransformPipeline — Return a new geometry with coordinates transformed to a different spatial reference system using the inverse of a defined coordinate transformation pipeline.

Synopsis

geometry **ST_InverseTransformPipeline**(geometry geom, text pipeline, integer to_srid);

例

Return a new geometry with coordinates transformed to a different spatial reference system using a defined coordinate transformation pipeline to go in the inverse direction.

Refer to [ST_TransformPipeline](#) for details on writing a transformation pipeline.

Availability: 3.4.0

The SRID of the input geometry is ignored, and the SRID of the output geometry will be set to zero unless a value is provided via the optional `to_srid` parameter. When using [ST_TransformPipeline](#) the pipeline is executed in a forward direction. Using `ST_InverseTransformPipeline()` the pipeline is executed in the inverse direction.

Transforms using pipelines are a specialised version of [ST_Transform](#). In most cases `ST_Transform` will choose the correct operations to convert between coordinate systems, and should be preferred.

☐☐

Change WGS 84 long lat to UTM 31N using the EPSG:16031 conversion

```
-- Inverse direction
SELECT ST_AsText(ST_InverseTransformPipeline('POINT(426857.9877165967 5427937.523342293)'::geometry,
'urn:ogc:def:coordinateOperation:EPSG::16031')) AS wgs_geom;

-----
POINT(2 48.99999999999999)
(1 row)
```

GDA2020 example.

```
-- using ST_Transform with automatic selection of a conversion pipeline.
SELECT ST_AsText(ST_Transform('SRID=4939;POINT(143.0 -37.0)'::geometry, 7844)) AS gda2020_auto;

-----
POINT(143.00000635638918 -36.999986706128176)
(1 row)
```

☐☐

ST_Transform, ST_TransformPipeline

7.7.2 ST_SetSRID

ST_SetSRID — Set the SRID on a geometry.

Synopsis

geometry **ST_SetSRID**(geometry geom, integer srid);

☐☐

Sets the SRID on a geometry to a particular integer value. Useful in constructing bounding boxes for queries.



Note

This function does not transform the geometry coordinates in any way - it simply sets the meta data defining the spatial reference system the geometry is assumed to be in. Use **ST_Transform** if you want to transform the geometry into a new projection.



This method implements the **OGC Simple Features Implementation Specification for SQL 1.1**.



This method supports Circular Strings and Curves.

❏

-- Mark a point as WGS 84 long lat --

```
SELECT ST_SetSRID(ST_Point(-123.365556, 48.428611),4326) As wgs84long_lat;
-- the ewkt representation (wrap with ST_AsEWKT) -
SRID=4326;POINT(-123.365556 48.428611)
```

-- Mark a point as WGS 84 long lat and then transform to web mercator (Spherical Mercator) --

```
SELECT ST_Transform(ST_SetSRID(ST_Point(-123.365556, 48.428611),4326),3785) As spere_merc;
-- the ewkt representation (wrap with ST_AsEWKT) -
SRID=3785;POINT(-13732990.8753491 6178458.96425423)
```

❏

Section [4.5](#), [ST_SRID](#), [ST_Transform](#), [UpdateGeometrySRID](#)

7.7.3 ST_SRID

ST_SRID — Returns the spatial reference identifier for a geometry.

Synopsis

integer **ST_SRID**(geometry g1);

❏

Returns the spatial reference identifier for the ST_Geometry as defined in spatial_ref_sys table. Section [4.5](#)



Note

spatial_ref_sys table is a table that catalogs all spatial reference systems known to PostGIS and is used for transformations from one spatial reference system to another. So verifying you have the right spatial reference system identifier is important if you plan to ever transform your geometries.



This method implements the [OGC Simple Features Implementation Specification for SQL 1.1](#). s2.1.1.1



This method implements the SQL/MM specification. SQL-MM 3: 5.1.5



This method supports Circular Strings and Curves.

❏

```
SELECT ST_SRID(ST_GeomFromText('POINT(-71.1043 42.315)',4326));
-- result
4326
```



Section [4.5](#), [ST_SetSRID](#), [ST_Transform](#), [ST_SRID](#), [ST_SRID](#)

7.7.4 ST_Transform

ST_Transform — Return a new geometry with coordinates transformed to a different spatial reference system.

Synopsis

```
geometry ST_Transform(geometry g1, integer srid);  
geometry ST_Transform(geometry geom, text to_proj);  
geometry ST_Transform(geometry geom, text from_proj, text to_proj);  
geometry ST_Transform(geometry geom, text from_proj, integer to_srid);
```



Returns a new geometry with its coordinates transformed to a different spatial reference system. The destination spatial reference `to_srid` may be identified by a valid SRID integer parameter (i.e. it must exist in the `spatial_ref_sys` table). Alternatively, a spatial reference defined as a PROJ.4 string can be used for `to_proj` and/or `from_proj`, however these methods are not optimized. If the destination spatial reference system is expressed with a PROJ.4 string instead of an SRID, the SRID of the output geometry will be set to zero. With the exception of functions with `from_proj`, input geometries must have a defined SRID.

`ST_Transform` is often confused with [ST_SetSRID](#). `ST_Transform` actually changes the coordinates of a geometry from one spatial reference system to another, while `ST_SetSRID()` simply changes the SRID identifier of the geometry.

`ST_Transform` automatically selects a suitable conversion pipeline given the source and target spatial reference systems. To use a specific conversion method, use [ST_TransformPipeline](#).



Note

Requires PostGIS be compiled with PROJ support. Use [PostGIS_Full_Version](#) to confirm you have PROJ support compiled in.




Note

If using more than one transformation, it is useful to have a functional index on the commonly used transformations to take advantage of index usage.



Note

1.3.4  (curve) . 1.3.4 .

: 2.0.0  (polyhedral surface) .

Enhanced: 2.3.0 support for direct PROJ.4 text was introduced.

- ☑ This method implements the SQL/MM specification. SQL-MM 3: 5.1.6
- ☑ This method supports Circular Strings and Curves.
- ☑ This function supports Polyhedral surfaces.

☒☒

Change Massachusetts state plane US feet geometry to WGS 84 long lat

```
SELECT ST_AsText(ST_Transform(ST_GeomFromText('POLYGON((743238 2967416,743238 2967450,
743265 2967450,743265.625 2967416,743238 2967416))',2249),4326)) As wgs_geom;

wgs_geom
-----
POLYGON((-71.1776848522251 42.3902896512902,-71.1776843766326 42.3903829478009,
-71.1775844305465 42.3903826677917,-71.1775825927231 42.3902893647987,-71.177684
8522251 42.3902896512902));
(1 row)

--3D Circular String example
SELECT ST_AsEWKT(ST_Transform(ST_GeomFromEWKT('SRID=2249;CIRCULARSTRING(743238 2967416 ↵
1,743238 2967450 2,743265 2967450 3,743265.625 2967416 3,743238 2967416 4)'),4326));

st_asewkt
-----
SRID=4326;CIRCULARSTRING(-71.1776848522251 42.3902896512902 1,-71.1776843766326 ↵
42.3903829478009 2,
-71.1775844305465 42.3903826677917 3,
-71.1775825927231 42.3902893647987 3,-71.1776848522251 42.3902896512902 4)
```

Example of creating a partial functional index. For tables where you are not sure all the geometries will be filled in, its best to use a partial index that leaves out null geometries which will both conserve space and make your index smaller and more efficient.

```
CREATE INDEX idx_geom_26986_parcel
ON parcels
USING gist
(ST_Transform(geom, 26986))
WHERE geom IS NOT NULL;
```

Examples of using PROJ.4 text to transform with custom spatial references.

```
-- Find intersection of two polygons near the North pole, using a custom Gnomonic projection
-- See http://boundlessgeo.com/2012/02/flattening-the-peel/
WITH data AS (
  SELECT
    ST_GeomFromText('POLYGON((170 50,170 72,-130 72,-130 50,170 50))', 4326) AS p1,
    ST_GeomFromText('POLYGON((-170 68,-170 90,-141 90,-141 68,-170 68))', 4326) AS p2,
    '+proj=gnom +ellps=WGS84 +lat_0=70 +lon_0=-160 +no_defs'::text AS gnom
)
SELECT ST_AsText(
  ST_Transform(
    ST_Intersection(ST_Transform(p1, gnom), ST_Transform(p2, gnom)),
    gnom, 4326))
FROM data;

st_astext
-----
```

```
POLYGON((-170 74.053793645338,-141 73.4268621378904,-141 68,-170 68,-170 74.053793645338) ↵
)
```

Configuring transformation behavior

Sometimes coordinate transformation involving a grid-shift can fail, for example if PROJ.4 has not been built with grid-shift files or the coordinate does not lie within the range for which the grid shift is defined. By default, PostGIS will throw an error if a grid shift file is not present, but this behavior can be configured on a per-SRID basis either by testing different `to_proj` values of PROJ.4 text, or altering the `proj4text` value within the `spatial_ref_sys` table.

For example, the `proj4text` parameter `+datum=NAD87` is a shorthand form for the following `+nadgrids` parameter:

```
+nadgrids=@conus,@alaska,@ntv2_0.gsb,@ntv1_can.dat
```

The `@` prefix means no error is reported if the files are not present, but if the end of the list is reached with no file having been appropriate (ie. found and overlapping) then an error is issued.

If, conversely, you wanted to ensure that at least the standard files were present, but that if all files were scanned without a hit a null transformation is applied you could use:

```
+nadgrids=@conus,@alaska,@ntv2_0.gsb,@ntv1_can.dat,null
```

The null grid shift file is a valid grid shift file covering the whole world and applying no shift. So for a complete example, if you wanted to alter PostGIS so that transformations to SRID 4267 that didn't lie within the correct range did not throw an ERROR, you would use the following:

```
UPDATE spatial_ref_sys SET proj4text = '+proj=longlat +ellps=clrk66 +nadgrids=@conus, ↵
@alaska,@ntv2_0.gsb,@ntv1_can.dat,null +no_defs' WHERE srid = 4267;
```



Section [4.5](#), [ST_SetSRID](#), [ST_SRID](#), [UpdateGeometrySRID](#), [ST_TransformPipeline](#)

7.7.5 ST_TransformPipeline

ST_TransformPipeline — Return a new geometry with coordinates transformed to a different spatial reference system using a defined coordinate transformation pipeline.

Synopsis

```
geometry ST_TransformPipeline(geometry g1, text pipeline, integer to_srid);
```



Return a new geometry with coordinates transformed to a different spatial reference system using a defined coordinate transformation pipeline.

Transformation pipelines are defined using any of the following string formats:

- `urn:ogc:def:coordinateOperation:AUTHORITY::CODE`. Note that a simple `EPSG:CODE` string does not uniquely identify a coordinate operation: the same EPSG code can be used for a CRS definition.

- A PROJ pipeline string of the form: `+proj=pipeline` ... Automatic axis normalisation will not be applied, and if necessary the caller will need to add an additional pipeline step, or remove axis swap steps.
- Concatenated operations of the form: `urn:ogc:def:coordinateOperation,coordinateOperation:EPSG:`

Availability: 3.4.0

The SRID of the input geometry is ignored, and the SRID of the output geometry will be set to zero unless a value is provided via the optional `to_srid` parameter. When using `ST_TransformPipeline()` the pipeline is executed in a forward direction. Using `ST_InverseTransformPipeline` the pipeline is executed in the inverse direction.

Transforms using pipelines are a specialised version of `ST_Transform`. In most cases `ST_Transform` will choose the correct operations to convert between coordinate systems, and should be preferred.

国国

Change WGS 84 long lat to UTM 31N using the EPSG:16031 conversion

```
-- Forward direction
SELECT ST_AsText(ST_TransformPipeline('SRID=4326;POINT(2 49)::geometry,
    'urn:ogc:def:coordinateOperation:EPSG::16031')) AS utm_geom;

                utm_geom
-----
POINT(426857.9877165967 5427937.523342293)
(1 row)

-- Inverse direction
SELECT ST_AsText(ST_InverseTransformPipeline('POINT(426857.9877165967 5427937.523342293):: ←
    geometry,
    'urn:ogc:def:coordinateOperation:EPSG::16031')) AS wgs_geom;

                wgs_geom
-----
POINT(2 48.99999999999999)
(1 row)
```

GDA2020 example.

```
-- using ST_Transform with automatic selection of a conversion pipeline.
SELECT ST_AsText(ST_Transform('SRID=4939;POINT(143.0 -37.0)::geometry, 7844)) AS ←
    gda2020_auto;

                gda2020_auto
-----
POINT(143.00000635638918 -36.999986706128176)
(1 row)

-- using a defined conversion (EPSG:8447)
SELECT ST_AsText(ST_TransformPipeline('SRID=4939;POINT(143.0 -37.0)::geometry,
    'urn:ogc:def:coordinateOperation:EPSG::8447')) AS gda2020_code;

                gda2020_code
-----
POINT(143.0000063280214 -36.999986718287545)
(1 row)

-- using a PROJ pipeline definition matching EPSG:8447, as returned from
-- 'projinfo -s EPSG:4939 -t EPSG:7844'.
```

```
-- NOTE: any 'axiswap' steps must be removed.
SELECT ST_AsText(ST_TransformPipeline('SRID=4939;POINT(143.0 -37.0)::geometry,
'+proj=pipeline
+step +proj=unitconvert +xy_in=deg +xy_out=rad
+step +proj=hgridshift +grids=au_icsm_GDA94_GDA2020_conformal_and_distortion.tif
+step +proj=unitconvert +xy_in=rad +xy_out=deg')) AS gda2020_pipeline;

                gda2020_pipeline
-----
POINT(143.0000063280214 -36.999986718287545)
(1 row)
```

☐☐

[ST_Transform](#), [ST_InverseTransformPipeline](#)

7.7.6 postgis_srs_codes

`postgis_srs_codes` — Return the list of SRS codes associated with the given authority.

Synopsis

setof text **postgis_srs_codes**(text auth_name);

☐☐

Returns a set of all auth_srid for the given auth_name.

Availability: 3.4.0

Proj version 6+

☐☐

List the first ten codes associated with the EPSG authority.

```
SELECT * FROM postgis_srs_codes('EPSG') LIMIT 10;
```

```
postgis_srs_codes
-----
2000
20004
20005
20006
20007
20008
20009
2001
20010
20011
```

☐☐

[postgis_srs](#), [postgis_srs_all](#), [postgis_srs_search](#)

7.7.7 postgis_srs

`postgis_srs` — Return a metadata record for the requested authority and srid.

Synopsis

setof record **postgis_srs**(text auth_name, text auth_srid);

☐☐

Returns a metadata record for the requested `auth_srid` for the given `auth_name`. The record will have the `auth_name`, `auth_srid`, `sname`, `srttext`, `proj4text`, and the corners of the area of usage, `point_sw` and `point_ne`.

Availability: 3.4.0

Proj version 6+

☐☐

Get the metadata for EPSG:3005.

```
SELECT * FROM postgis_srs('EPSG', '3005');
```

```
auth_name | EPSG
auth_srid | 3005
sname     | NAD83 / BC Albers
srttext   | PROJCS["NAD83 / BC Albers", ... ]
proj4text | +proj=aea +lat_0=45 +lon_0=-126 +lat_1=50 +lat_2=58.5 +x_0=1000000 +y_0=0 +
      datum=NAD83 +units=m +no_defs +type=crs
point_sw  | 0101000020E6100000E17A14AE476161C000000000000204840
point_ne  | 0101000020E610000085EB51B81E855CC0E17A14AE47014E40
```

☐☐

[postgis_srs_codes](#), [postgis_srs_all](#), [postgis_srs_search](#)

7.7.8 postgis_srs_all

`postgis_srs_all` — Return metadata records for every spatial reference system in the underlying Proj database.

Synopsis

setof record **postgis_srs_all**(void);

☐☐

Returns a set of all metadata records in the underlying Proj database. The records will have the `auth_name`, `auth_srid`, `sname`, `srttext`, `proj4text`, and the corners of the area of usage, `point_sw` and `point_ne`.

Availability: 3.4.0

Proj version 6+

❏❏

Get the first 10 metadata records from the Proj database.

```
SELECT auth_name, auth_srid, sname FROM postgis_srs_all() LIMIT 10;
```

auth_name	auth_srid	sname
EPSG	2000	Anguilla 1957 / British West Indies Grid
EPSG	20004	Pulkovo 1995 / Gauss-Kruger zone 4
EPSG	20005	Pulkovo 1995 / Gauss-Kruger zone 5
EPSG	20006	Pulkovo 1995 / Gauss-Kruger zone 6
EPSG	20007	Pulkovo 1995 / Gauss-Kruger zone 7
EPSG	20008	Pulkovo 1995 / Gauss-Kruger zone 8
EPSG	20009	Pulkovo 1995 / Gauss-Kruger zone 9
EPSG	2001	Antigua 1943 / British West Indies Grid
EPSG	20010	Pulkovo 1995 / Gauss-Kruger zone 10
EPSG	20011	Pulkovo 1995 / Gauss-Kruger zone 11

❏❏

[postgis_srs_codes](#), [postgis_srs](#), [postgis_srs_search](#)

7.7.9 postgis_srs_search

postgis_srs_search — Return metadata records for projected coordinate systems that have areas of usage that fully contain the bounds parameter.

Synopsis

setof record **postgis_srs_search**(geometry bounds, text auth_name=EPSG);

❏❏

Return a set of metadata records for projected coordinate systems that have areas of usage that fully contain the bounds parameter. Each record will have the auth_name, auth_srid, sname, srtext, proj4text, and the corners of the area of usage, point_sw and point_ne.

The search only looks for projected coordinate systems, and is intended for users to explore the possible systems that work for the extent of their data.

Availability: 3.4.0

Proj version 6+

❏❏

Search for projected coordinate systems in Louisiana.

```
SELECT auth_name, auth_srid, sname,
       ST_AsText(point_sw) AS point_sw,
       ST_AsText(point_ne) AS point_ne
FROM postgis_srs_search('SRID=4326;LINESTRING(-90 30, -91 31)')
LIMIT 3;
```


 This method implements the [OGC Simple Features Implementation Specification for SQL 1.1. s3.2.6.2](#)

GEOS 版本

1.1.0 版本。

[ST_BuildArea](#), [ST_BdMPolyFromText](#)

7.8.1.2 ST_BdMPolyFromText

ST_BdMPolyFromText — 将 WKT 多边形文本转换为多边形几何体。

Synopsis

geometry **ST_BdMPolyFromText**(text WKT, integer srid);

WKT 多边形文本。



Note

WKT 多边形文本。如果 WKT 多边形文本包含空字符串，则 [ST_BdPolyFromText](#) 将返回空几何体。PostGIS 使用 [ST_BuildArea\(\)](#) 构建多边形。

 This method implements the [OGC Simple Features Implementation Specification for SQL 1.1. s3.2.6.2](#)

GEOS 版本

1.1.0 版本。

[ST_BuildArea](#), [ST_BdPolyFromText](#)

7.8.1.3 ST_GeogFromText

ST_GeogFromText — WKT (EWKT) 地理多边形文本转换为地理多边形几何体。

Synopsis

geography **ST_GeogFromText**(text EWKT);

例

WKT 格式 WKT 格式。 SRID 4326 格式。 ST_GeographyFromText 格式。

例

```
--- converting lon lat coords to geography
ALTER TABLE sometable ADD COLUMN geog geography(POINT,4326);
UPDATE sometable SET geog = ST_GeogFromText('SRID=4326;POINT(' || lon || ' ' || lat || ')') ←
;

--- specify a geography point using EPSG:4267, NAD27
SELECT ST_AsEWKT(ST_GeogFromText('SRID=4267;POINT(-77.0092 38.889588)'));
```

例

ST_AsText, ST_GeographyFromText

7.8.1.4 ST_GeographyFromText

ST_GeographyFromText — WKT (例) 格式。

Synopsis

geography **ST_GeographyFromText**(text EWKT);

例

WKT 格式。 SRID 4326 格式。

例

ST_GeogFromText, ST_AsText

7.8.1.5 ST_GeomCollFromText

ST_GeomCollFromText — Makes a collection Geometry from collection WKT with the given SRID. If SRID is not given, it defaults to 0.

Synopsis

geometry **ST_GeomCollFromText**(text WKT, integer srid);
 geometry **ST_GeomCollFromText**(text WKT);

几何

Makes a collection Geometry from the Well-Known-Text (WKT) representation with the given SRID. If SRID is not given, it defaults to 0.

OGC 3.2.6.2 - 符合 SRID (conformance suite) 。

WKT (GEOMETRYCOLLECTION) null 。



Note

WKT 符合 , 符合 。 符合 ST_GeomFromText 。



This method implements the [OGC Simple Features Implementation Specification for SQL 1.1. s3.2.6.2](#)



This method implements the SQL/MM specification.

几何

```
SELECT ST_GeomCollFromText('GEOMETRYCOLLECTION(POINT(1 2),LINESTRING(1 2, 3 4))');
```

几何

[ST_GeomFromText](#), [ST_SRID](#)

7.8.1.6 ST_GeomFromEWKT

ST_GeomFromEWKT — EWKT(Extended Well-Known Text) 几何 ST_Geometry 。

Synopsis

geometry **ST_GeomFromEWKT**(text EWKT);

几何

OGC EWKT(Extended Well-Known Text) 符合 PostgreSQL ST_Geometry 。



Note

EWKT 符合 OGC 符合 , SRID(符合) 符合 PostgreSQL 符合 。

符合: 2.0.0 符合 (polyhedral surface) 符合 TIN 符合。



This function supports 3d and will not drop the z-index.



This method supports Circular Strings and Curves.



This function supports Polyhedral surfaces.



This function supports Triangles and Triangulated Irregular Network Surfaces (TIN).

❏

```
SELECT ST_GeomFromEWKT('SRID=4269;LINESTRING(-71.160281 42.258729,-71.160837 42.259113,-71.161144 42.25932)');
SELECT ST_GeomFromEWKT('SRID=4269;MULTILINESTRING((-71.160281 42.258729,-71.160837 42.259113,-71.161144 42.25932))');

SELECT ST_GeomFromEWKT('SRID=4269;POINT(-71.064544 42.28787)');

SELECT ST_GeomFromEWKT('SRID=4269;POLYGON((-71.1776585052917 42.3902909739571,-71.1776820268866 42.3903701743239,-71.1776063012595 42.3903825660754,-71.1775826583081 42.3903033653531,-71.1776585052917 42.3902909739571)))');

SELECT ST_GeomFromEWKT('SRID=4269;MULTIPOLYGON((( -71.1031880899493 42.3152774590236,
-71.1031627617667 42.3152960829043, -71.102923838298 42.3149156848307,
-71.1023097974109 42.3151969047397, -71.1019285062273 42.3147384934248,
-71.102505233663 42.3144722937587, -71.10277487471 42.3141658254797,
-71.103113945163 42.3142739188902, -71.10324876416 42.31402489987,
-71.1033002961013 42.3140393340215, -71.1033488797549 42.3139495090772,
-71.103396240451 42.3138632439557, -71.1041521907712 42.3141153348029,
-71.1041411411543 42.3141545014533, -71.1041287795912 42.3142114839058,
-71.1041188134329 42.3142693656241, -71.1041112482575 42.3143272556118,
-71.1041072845732 42.3143851580048, -71.1041057218871 42.3144430686681,
-71.1041065602059 42.3145009876017, -71.1041097995362 42.3145589148055,
-71.1041166403905 42.3146168544148, -71.1041258822717 42.3146748022936,
-71.1041375307579 42.3147318674446, -71.1041492906949 42.3147711126569,
-71.1041598612795 42.314808571739, -71.1042515013869 42.3151287620809,
-71.1041173835118 42.3150739481917, -71.1040809891419 42.3151344119048,
-71.1040438678912 42.3151191367447, -71.1040194562988 42.3151832057859,
-71.1038734225584 42.3151140942995, -71.1038446938243 42.3151006300338,
-71.1038315271889 42.315094347535, -71.1037393329282 42.315054824985,
-71.1035447555574 42.3152608696313, -71.1033436658644 42.3151648370544,
-71.1032580383161 42.3152269126061, -71.103223066939 42.3152517403219,
-71.1031880899493 42.3152774590236)),
((-71.1043632495873 42.315113108546, -71.1043583974082 42.3151211109857,
-71.1043443253471 42.3150676015829, -71.1043850704575 42.3150793250568, -71.1043632495873 42.315113108546)))');
```

```
--3d circular string
SELECT ST_GeomFromEWKT('CIRCULARSTRING(220268 150415 1,220227 150505 2,220227 150406 3)');
```

```
--Polyhedral Surface example
SELECT ST_GeomFromEWKT('POLYHEDRALSURFACE(
  ((0 0 0, 0 0 1, 0 1 1, 0 1 0, 0 0 0)),
  ((0 0 0, 0 1 0, 1 1 0, 1 0 0, 0 0 0)),
  ((0 0 0, 1 0 0, 1 0 1, 0 0 1, 0 0 0)),
  ((1 1 0, 1 1 1, 1 0 1, 1 0 0, 1 1 0)),
  ((0 1 0, 0 1 1, 1 1 1, 1 1 0, 0 1 0)),
  ((0 0 1, 1 0 1, 1 1 1, 0 1 1, 0 0 1))
)');
```

❏

ST_AsEWKT, ST_GeomFromText

7.8.1.7 ST_GeomFromMARC21

ST_GeomFromMARC21 — Takes MARC21/XML geographic data as input and returns a PostGIS geometry object.

Synopsis

geometry **ST_GeomFromMARC21** (text marcxml);



This function creates a PostGIS geometry from a MARC21/XML record, which can contain a POINT or a POLYGON. In case of multiple geographic data entries in the same MARC21/XML record, a MULTIPOINT or MULTIPOLYGON will be returned. If the record contains mixed geometry types, a GEOMETRYCOLLECTION will be returned. It returns NULL if the MARC21/XML record does not contain any geographic data (datafield:034).

LOC MARC21/XML versions supported:

- [MARC21/XML 1.1](#)

Availability: 3.3.0, requires libxml2 2.6+



Note

The MARC21/XML Coded Cartographic Mathematical Data currently does not provide any means to describe the Spatial Reference System of the encoded coordinates, so this function will always return a geometry with SRID 0.



Note

Returned POLYGON geometries will always be clockwise oriented.



Converting MARC21/XML geographic data containing a single POINT encoded as hddd.ddddd

```
SELECT
  ST_AsText(
    ST_GeomFromMARC21('
      <record xmlns="http://www.loc.gov/MARC21/slim">
        <leader
>00000nz a2200000nc 4500</leader>
        <controlfield tag="001"
>040277569</controlfield>
          <datafield tag="034" ind1=" " ind2=" ">
            <subfield code="d"
>W004.500000</subfield>
              <subfield code="e"
>W004.500000</subfield>
                <subfield code="f"
>N054.250000</subfield>
                  <subfield code="g"
```

```

>N054.250000</subfield>
                                </datafield>
                                </record>
>' ));

      st_astext
-----
POINT(-4.5 54.25)
(1 row)

```

Converting MARC21/XML geographic data containing a single POLYGON encoded as hddmmss

```

      SELECT
      ST_AsText(
        ST_GeomFromMARC21('
          <record xmlns="http://www.loc.gov/MARC21/slim">
            <leader
>01062cem a2200241 a 4500</leader>
            <controlfield tag="001"
> 84696781 </controlfield>
              <datafield tag="034" ind1="1" ind2=" ">
                <subfield code="a"
>a</subfield>
                <subfield code="b"
>50000</subfield>
                <subfield code="d"
>E0130600</subfield>
                <subfield code="e"
>E0133100</subfield>
                <subfield code="f"
>N0523900</subfield>
                <subfield code="g"
>N0522300</subfield>
              </datafield>
            </record>
          <' ));

      st_astext
-----
POLYGON((13.1 52.65,13.516666666666667 52.65,13.516666666666667  ←
          52.38333333333333,13.1 52.38333333333333,13.1 52.65))
(1 row)

```

Converting MARC21/XML geographic data containing a POLYGON and a POINT:

```

      SELECT
      ST_AsText(
        ST_GeomFromMARC21('
          <record xmlns="http://www.loc.gov/MARC21/slim">
            <datafield tag="034" ind1="1" ind2=" ">
              <subfield code="a"
>a</subfield>
              <subfield code="b"
>50000</subfield>
              <subfield code="d"

```

```

>E0130600</subfield>
      <subfield code="e"
>E0133100</subfield>
      <subfield code="f"
>N0523900</subfield>
      <subfield code="g"
>N0522300</subfield>
      </datafield>
      <datafield tag="034" ind1=" " ind2=" ">
        <subfield code="d"
>W004.500000</subfield>
        <subfield code="e"
>W004.500000</subfield>
        <subfield code="f"
>N054.250000</subfield>
        <subfield code="g"
>N054.250000</subfield>
      </datafield>
    </record>
>'));
```

st_astext ↩

```

-----

GEOMETRYCOLLECTION(POLYGON((13.1 52.65,13.516666666666667 ↩
52.65,13.516666666666667 52.38333333333333,13.1 52.38333333333333,13.1 ↩
52.65)),POINT(-4.5 54.25))
(1 row)
```

☒

ST_AsMARC21

7.8.1.8 ST_GeometryFromText

ST_GeometryFromText — WKT(Well-Known Text) ☒☒☒☒☒ ST_Geometry ☒☒☒☒☒☒. ☒☒☒☒ ST_GeomFromText ☒☒☒☒☒☒☒☒.

Synopsis

```

geometry ST_GeometryFromText(text WKT);
geometry ST_GeometryFromText(text WKT, integer srid);
```

☒☒



This method implements the [OGC Simple Features Implementation Specification for SQL 1.1](#).



This method implements the SQL/MM specification. SQL-MM 3: 5.1.40

☒☒

ST_GeomFromText

7.8.1.9 ST_GeomFromText

ST_GeomFromText — WKT 转 ST_Geometry

Synopsis

```
geometry ST_GeomFromText(text WKT);
geometry ST_GeomFromText(text WKT, integer srid);
```

注意

OGC WKT(Well-Known Text) 转 PostGIS ST_Geometry



Note

ST_GeomFromText 支持 2 维几何, 指定 SRID 值。如果 SRID 未指定, 则默认为 0 (SRID=0)。指定 SRID 值时, 必须使用 SRID 关键字。

- ✓ This method implements the [OGC Simple Features Implementation Specification for SQL 1.1](#). 3.2.6.2 - 指定 SRID (conformance suite)
- ✓ This method implements the SQL/MM specification. SQL-MM 3: 5.1.40
- ✓ This method supports Circular Strings and Curves.



Note

While not OGC-compliant, **ST_MakePoint** is faster than ST_GeomFromText and ST_PointFromText. It is also easier to use for numeric coordinate values. **ST_Point** is another option similar in speed to **ST_MakePoint** and is OGC-compliant, but doesn't support anything but 2D points.



Warning

警告: PostGIS 2.0.0 之前, ST_GeomFromText('GEOMETRYCOLLECTION(EMPTY)') 会报错。PostGIS 2.0.0 之后, SQL/MM 标准要求支持空集合。现在 ST_GeomFromText('GEOMETRYCOLLECTION EMPTY') 可以正常工作。

示例

```
SELECT ST_GeomFromText('LINESTRING(-71.160281 42.258729,-71.160837 42.259113,-71.161144 42.25932)');
SELECT ST_GeomFromText('LINESTRING(-71.160281 42.258729,-71.160837 42.259113,-71.161144 42.25932)',4269);

SELECT ST_GeomFromText('MULTILINESTRING((-71.160281 42.258729,-71.160837 42.259113,-71.161144 42.25932))');

SELECT ST_GeomFromText('POINT(-71.064544 42.28787)');

SELECT ST_GeomFromText('POLYGON((-71.1776585052917 42.3902909739571,-71.1776820268866 42.3903701743239,
```

```
-71.1776063012595 42.3903825660754,-71.1775826583081 42.3903033653531,-71.1776585052917 42.3902909739571))');  
  
SELECT ST_GeomFromText('MULTIPOLYGON((( -71.1031880899493 42.3152774590236,  
-71.1031627617667 42.3152960829043,-71.102923838298 42.3149156848307,  
-71.1023097974109 42.3151969047397,-71.1019285062273 42.3147384934248,  
-71.102505233663 42.3144722937587,-71.10277487471 42.3141658254797,  
-71.103113945163 42.3142739188902,-71.10324876416 42.31402489987,  
-71.1033002961013 42.3140393340215,-71.1033488797549 42.3139495090772,  
-71.103396240451 42.3138632439557,-71.1041521907712 42.3141153348029,  
-71.1041411411543 42.3141545014533,-71.1041287795912 42.3142114839058,  
-71.1041188134329 42.3142693656241,-71.1041112482575 42.3143272556118,  
-71.1041072845732 42.3143851580048,-71.1041057218871 42.3144430686681,  
-71.1041065602059 42.3145009876017,-71.1041097995362 42.3145589148055,  
-71.1041166403905 42.3146168544148,-71.1041258822717 42.3146748022936,  
-71.1041375307579 42.3147318674446,-71.1041492906949 42.3147711126569,  
-71.1041598612795 42.314808571739,-71.1042515013869 42.3151287620809,  
-71.1041173835118 42.3150739481917,-71.1040809891419 42.3151344119048,  
-71.1040438678912 42.3151191367447,-71.1040194562988 42.3151832057859,  
-71.1038734225584 42.3151140942995,-71.1038446938243 42.3151006300338,  
-71.1038315271889 42.315094347535,-71.1037393329282 42.315054824985,  
-71.1035447555574 42.3152608696313,-71.1033436658644 42.3151648370544,  
-71.1032580383161 42.3152269126061,-71.103223066939 42.3152517403219,  
-71.1031880899493 42.3152774590236))),  
((-71.1043632495873 42.315113108546,-71.1043583974082 42.3151211109857,  
-71.1043443253471 42.3150676015829,-71.1043850704575 42.3150793250568,-71.1043632495873 42.315113108546))))',4326);  
  
SELECT ST_GeomFromText(' CIRCULARSTRING(220268 150415,220227 150505,220227 150406)');
```



ST_GeomFromEWKT, ST_GeomFromWKB, ST_SRID

7.8.1.10 ST_LineFromText

ST_LineFromText — `SRID` `WKT` `SRID` `0`.

Synopsis

```
geometry ST_LineFromText(text WKT);
geometry ST_LineFromText(text WKT, integer srid);
```



Makes a Geometry from WKT with the given SRID. If SRID is not given, it defaults to 0. If WKT passed in is not a LINESTRING, then null is returned.



Note

OGC 3.2.6.2 - SRID (conformance suite).

**Note**

ST_GeomFromText 函数接受 WKT 字符串并返回几何对象。ST_GeomFromText 函数接受 WKT 字符串并返回几何对象。



This method implements the [OGC Simple Features Implementation Specification for SQL 1.1. s3.2.6.2](#)



This method implements the SQL/MM specification. SQL-MM 3: 7.2.8

SQL

```
SELECT ST_LineFromText('LINESTRING(1 2, 3 4)') AS aline, ST_LineFromText('POINT(1 2)') AS null_return;
aline | null_return
-----|-----
01020000000200000000000000000000F ... | t
```

SQL

ST_GeomFromText

7.8.1.11 ST_MLineFromText

ST_MLineFromText — WKT 字符串转换为 ST_MultiLineString 几何对象。

Synopsis

```
geometry ST_MLineFromText(text WKT, integer srid);
geometry ST_MLineFromText(text WKT);
```

SQL

Makes a Geometry from Well-Known-Text (WKT) with the given SRID. If SRID is not given, it defaults to 0.

OGC 3.2.6.2 - SRID 值 (conformance suite) 必须为 0。

WKT 字符串为 null 时返回 null。

**Note**

WKT 字符串必须有效，否则将返回 null。ST_GeomFromText 函数接受 WKT 字符串并返回几何对象。



This method implements the [OGC Simple Features Implementation Specification for SQL 1.1. s3.2.6.2](#)



This method implements the SQL/MM specification. SQL-MM 3: 9.4.4

例

```
SELECT ST_MLineFromText('MULTILINESTRING((1 2, 3 4), (4 5, 6 7))');
```

例

ST_GeomFromText

7.8.1.12 ST_MPointFromText

ST_MPointFromText — Makes a Geometry from WKT with the given SRID. If SRID is not given, it defaults to 0.

Synopsis

```
geometry ST_MPointFromText(text WKT, integer srid);
geometry ST_MPointFromText(text WKT);
```

例

Makes a Geometry from WKT with the given SRID. If SRID is not given, it defaults to 0.

OGC 3.2.6.2 - SRID (conformance suite) .

WKT null .



Note

WKT , . **ST_GeomFromText** .

✓ This method implements the **OGC Simple Features Implementation Specification for SQL 1.1.3.2.6.2**

✓ This method implements the SQL/MM specification. SQL-MM 3: 9.2.4

例

```
SELECT ST_MPointFromText('MULTIPOINT((1 2),(3 4))');
SELECT ST_MPointFromText('MULTIPOINT((-70.9590 42.1180),(-70.9611 42.1223))', 4326);
```

例

ST_GeomFromText

7.8.1.13 ST_MPolyFromText

ST_MPolyFromText — Makes a MultiPolygon Geometry from WKT with the given SRID. If SRID is not given, it defaults to 0.

Synopsis

```
geometry ST_MPolyFromText(text WKT, integer srid);
geometry ST_MPolyFromText(text WKT);
```



Makes a MultiPolygon from WKT with the given SRID. If SRID is not given, it defaults to 0.

OGC 3.2.6.2 - SRID (conformance suite) .

WKT ☒☒☒☒☒☒☒☒☒☒☒☒☒☒☒☒☒.



Note

```

WKT 'POINT (100 100)', SRID=4326;
ST_GeomFromText('POINT (100 100)', 4326);

```

- ✔ This method implements the [OGC Simple Features Implementation Specification for SQL 1.1. s3.2.6.2](#)
- ✔ This method implements the SQL/MM specification. SQL-MM 3: 9.6.4


```
SELECT ST_MPolyFromText('MULTIPOLYGON(((0 0 1,20 0 1,20 20 1,0 20 1,0 0 1),(5 5 3,5 7 3,7 7 3,7 5 3,5 5 3)))');
SELECT ST_MPolyFromText('MULTIPOLYGON((( -70.916 42.1002, -70.9468 42.0946, -70.9765 42.0872, -70.9754 42.0875, -70.9749 42.0879, -70.9752 42.0881, -70.9754 42.0891, -70.9758 42.0894, -70.9759 42.0897, -70.9759 42.0899, -70.9754 42.0902, -70.9756 42.0906, -70.9753 42.0907, -70.9753 42.0917, -70.9757 42.0924, -70.9755 42.0928, -70.9755 42.0942, -70.9751 42.0948, -70.9755 42.0953, -70.9751 42.0958, -70.9751 42.0962, -70.9759 42.0983, -70.9767 42.0987, -70.9768 42.0991, -70.9771 42.0997, -70.9771 42.1003, -70.9768 42.1005, -70.977 42.1011, -70.9766 42.1019, -70.9768 42.1026, -70.9769 42.1033, -70.9775 42.1042, -70.9773 42.1043, -70.9776 42.1043, -70.9778 42.1048, -70.9773 42.1058, -70.9774 42.1061, -70.9779 42.1065, -70.9782 42.1078, -70.9788 42.1085, -70.9798 42.1087, -70.9806 42.109, -70.9807 42.1093, -70.9806 42.1099, -70.9809 42.1109, -70.9808 42.1112, -70.9798 42.1116, -70.9792 42.1127, -70.979 42.1129, -70.9787 42.1134, -70.979 42.1139, -70.9791 42.1141, -70.9987 42.1116, -71.0022 42.1273, -70.9408 42.1513, -70.9315 42.1165, -70.916 42.1002)))',4326);
```


ST_GeomFromText, ST_SRID

7.8.1.14 ST PointFromText

ST_PointFromText — `SRID` `WKT` `SRID` `0`.

Synopsis

```
geometry ST_PointFromText(text WKT);
geometry ST_PointFromText(text WKT, integer srid);
```

函数

Constructs a PostGIS `ST_Geometry` point object from the OGC Well-Known text representation. If SRID is not given, it defaults to unknown (currently 0). If geometry is not a WKT point representation, returns null. If completely invalid WKT, then throws an error.



Note

`ST_PointFromText` 接受 2 个参数, 第一个 SRID 指定要使用的 SRID。如果 SRID 未指定, 则使用默认值 0。第二个参数是 WKT 点表示法。如果 WKT 不是有效的点表示法, 则返回 null。如果 WKT 完全无效, 则抛出错误。



Note

WKT 点表示法与 OGC 简单要素实现规范 (OGC Simple Features Implementation Specification) 兼容。PostGIS 使用 `ST_GeomFromText` 函数。该函数接受 OGC 点表示法, 并返回 `ST_Point` 对象。如果 WKT 不是有效的点表示法, 则返回 null。如果 WKT 完全无效, 则抛出错误。



This method implements the [OGC Simple Features Implementation Specification for SQL 1.1](#). 3.2.6.2 - 指定 SRID (conformance suite) 兼容。



This method implements the SQL/MM specification. SQL-MM 3: 6.1.8

函数

```
SELECT ST_PointFromText('POINT(-71.064544 42.28787)');
SELECT ST_PointFromText('POINT(-71.064544 42.28787)', 4326);
```

函数

[ST_GeomFromText](#), [ST_MakePoint](#), [ST_Point](#), [ST_SRID](#)

7.8.1.15 ST_PolygonFromText

`ST_PolygonFromText` — Makes a Geometry from WKT with the given SRID. If SRID is not given, it defaults to 0.

Synopsis

```
geometry ST_PolygonFromText(text WKT);
geometry ST_PolygonFromText(text WKT, integer srid);
```

函数

Makes a Geometry from WKT with the given SRID. If SRID is not given, it defaults to 0. Returns null if WKT is not a polygon.

OGC 3.2.6.2 - 指定 SRID (conformance suite) 兼容。

**Note**

WKT 格式字符串, 使用 `ST_GeomFromText` 函数。



This method implements the [OGC Simple Features Implementation Specification for SQL 1.1. s3.2.6.2](#)



This method implements the SQL/MM specification. SQL-MM 3: 8.3.6

SQL

```
SELECT ST_PolygonFromText('POLYGON((-71.1776585052917 42.3902909739571,-71.1776820268866 ↵
    42.3903701743239,
-71.1776063012595 42.3903825660754,-71.1775826583081 42.3903033653531,-71.1776585052917 ↵
    42.3902909739571))');
st_polygonfromtext
-----
010300000001000000050000006...
```

```
SELECT ST_PolygonFromText('POINT(1 2)') IS NULL as point_is_notpoly;
point_is_not_poly
-----
t
```

SQL

ST_GeomFromText

7.8.1.16 ST_WKTToSQL

`ST_WKTToSQL` — WKT(Well-Known Text) 格式字符串 `ST_Geometry` 格式字符串。使用 `ST_GeomFromText` 函数。

Synopsis

geometry **ST_WKTToSQL**(text WKT);

SQL



This method implements the SQL/MM specification. SQL-MM 3: 5.1.34

SQL

ST_GeomFromText

7.8.2 Well-Known Binary (WKB)

7.8.2.1 ST_GeogFromWKB

ST_GeogFromWKB — WKB 转 EWKB(转 WKB) 转地理几何。

Synopsis

geography **ST_GeogFromWKB**(bytea wkb);

注意

ST_GeogFromWKB 转 WKB 转 PostGIS 转 WKB 转地理几何。 转 SQL 转 (Geometry Factory) 转。

SRID 转, 转 4326(WGS84 转) 转。



This method supports Circular Strings and Curves.

注意

```
--Although bytea rep contains single \, these need to be escaped when inserting into a table
SELECT ST_AsText(
ST_GeogFromWKB(E'\\001\\002\\000\\000\\000\\002\\000\\000\\000\\037\\205\\353Q
\\270~\\\\\\300\\323Mb\\020X\\231C@\\020X9\\264\\310~\\\\\\300)\\\\\\217\\302\\365\\230
C@')
);
--
-- st_astext
--
LINESTRING(-113.98 39.198, -113.981 39.195)
(1 row)
```

注意

ST_GeogFromText, **ST_AsBinary**

7.8.2.2 ST_GeomFromEWKB

ST_GeomFromEWKB — EWKB(Extended Well-Known Binary) 转 ST_Geometry 转。

Synopsis

geometry **ST_GeomFromEWKB**(bytea EWKB);

函数

OGC EWKB(Extended Well-Known Binary) 函数返回 PostGIS ST_Geometry 函数返回的结果。



Note

EWKB 函数 OGC 函数返回的结果, SRID(函数返回的结果) 函数返回 PostGIS 函数返回的结果。

函数: 2.0.0 函数返回的结果 (polyhedral surface) 函数 TIN 函数返回的结果。



This function supports 3d and will not drop the z-index.



This method supports Circular Strings and Curves.



This function supports Polyhedral surfaces.



This function supports Triangles and Triangulated Irregular Network Surfaces (TIN).

函数

NAD83 函数 (SRID 4269) 函数返回 LINESTRING(-71.160281 42.258729,-71.160837 42.259113,-71.161144 42.25932) 函数返回的结果



Note

函数: 函数返回的结果 (\) 函数返回的结果 (') 函数返回的结果, standard_conforming_strings 函数返回的结果 \ 函数返回的结果. 函数返回 AsEWKB 函数返回的结果。

```
SELECT ST_GeomFromEWKB(E'\001\002\000\000 \255\020\000\000\003\000\000\000\344 ←
J=
\013B\312Q\300n\303(\010\036!E@'\277E' 'K
\312Q\300\366{b\235*!E@\225|\354.P\312Q
\300p\231\323e1!E@');
```



Note

In PostgreSQL 9.1+ - standard_conforming_strings is set to on by default, where as in past versions it was set to off. You can change defaults as needed for a single query or at the database or server level. Below is how you would do it with standard_conforming_strings = on. In this case we escape the ' with standard ansi ', but slashes are not escaped

```
set standard_conforming_strings = on;
SELECT ST_GeomFromEWKB('\001\002\000\000 \255\020\000\000\003\000\000\000\344J=\012\013B
\312Q\300n\303(\010\036!E@'\277E' 'K\012\312Q\300\366{b\235*!E@\225|\354.P\312Q\012\300 ←
p\231\323e1')
```

函数

[ST_AsBinary](#), [ST_AsEWKB](#), [ST_GeomFromWKB](#)

7.8.2.3 ST_GeomFromWKB

ST_GeomFromWKB — WKB(Well-Known Binary) 转 SRID 的函数。

Synopsis

```
geometry ST_GeomFromWKB(bytea geom);
geometry ST_GeomFromWKB(bytea geom, integer srid);
```

描述

ST_GeomFromWKB 将 WKB 转 SRID(指定 ID) 的函数。该函数是 SQL (Geometry Factory) 的一部分。该函数 ST_WKBToSQL 是 ST_GeomFromWKB 的逆函数。

SRID 指定, 默认为 0(unknown)。

✓ This method implements the [OGC Simple Features Implementation Specification for SQL 1.1](#). s3.2.7.2 - SRID (conformance suite)。

✓ This method implements the SQL/MM specification. SQL-MM 3: 5.1.41

✓ This method supports Circular Strings and Curves.

示例

```
--Although bytea rep contains single \, these need to be escaped when inserting into a table
-- unless standard_conforming_strings is set to on.
SELECT ST_AsEWKT(
ST_GeomFromWKB(E'\\001\\002\\000\\000\\000\\002\\000\\000\\000\\037\\205\\353Q
\\270~\\111\\300\\323Mb\\020X\\231C@\\020X9\\264\\310~\\111\\300)\\111\\217\\302\\365\\230
C@',4326)
);
          st_asewkt
-----
SRID=4326;LINESTRING(-113.98 39.198,-113.981 39.195)
(1 row)

SELECT
  ST_AsText(
    ST_GeomFromWKB(
      ST_AsEWKB('POINT(2 5)::geometry')
    )
  );
  st_astext
-----
POINT(2 5)
(1 row)
```

相关链接

[ST_WKBToSQL](#), [ST_AsBinary](#), [ST_GeomFromEWKB](#)

7.8.2.4 ST_LineFromWKB

ST_LineFromWKB — 指定 SRID 的 WKB 数据转换为 LINESTRING 类型。

Synopsis

```
geometry ST_LineFromWKB(bytea WKB);
geometry ST_LineFromWKB(bytea WKB, integer srid);
```

注意

ST_LineFromWKB 将 WKB 数据转换为 SRID(指定的 ID) 的 LINESTRING 类型。 - 指定 SRID, LINESTRING 类型 - 指定 SRID。 使用 SQL Geometry Factory 函数。 SRID 指定为 0 表示未指定。 指定 bytea 类型, NULL 表示空。



Note

OGC 3.2.6.2 - 指定 SRID 的 (conformance suite) 函数。



Note

指定 LINESTRING 类型, 使用 ST_GeomFromWKB 函数。 指定 ST_GeomFromWKB 函数, 指定 SRID 类型。

✓ This method implements the [OGC Simple Features Implementation Specification for SQL 1.1. s3.2.6.2](#)

✓ This method implements the SQL/MM specification. SQL-MM 3: 7.2.9

注意

```
SELECT ST_LineFromWKB(ST_AsBinary(ST_GeomFromText('LINESTRING(1 2, 3 4)'))) AS aline,
       ST_LineFromWKB(ST_AsBinary(ST_GeomFromText('POINT(1 2)'))) IS NULL AS null_return;
aline                                     | null_return
-----|-----
01020000000200000000000000000000F ... | t
```

注意

ST_GeomFromWKB, ST_LinestringFromWKB

7.8.2.5 ST_LinestringFromWKB

ST_LinestringFromWKB — 指定 SRID 的 WKB 数据转换为 LINESTRING 类型。

Synopsis

geometry **ST_LinestringFromWKB**(bytea WKB);
 geometry **ST_LinestringFromWKB**(bytea WKB, integer srid);

返回

ST_LinestringFromWKB 将 WKB 转换为 SRID(指定 ID) 的 LINESTRING。 - 返回, LINESTRING 返回。 返回 SQL 函数 (Geometry Factory) 返回。

SRID 指定, 返回 0 返回。 返回 bytea 返回 LINESTRING 返回, NULL 返回。



Note

OGC 3.2.6.2 - 返回 SRID 返回 (conformance suite) 返回。



Note

返回 LINESTRING 返回, 返回 **ST_GeomFromWKB** 返回。 返回 **ST_GeomFromWKB** 返回, LINESTRING 返回。

✓ This method implements the [OGC Simple Features Implementation Specification for SQL 1.1. s3.2.6.2](#)

✓ This method implements the SQL/MM specification. SQL-MM 3: 7.2.9

返回

```
SELECT
  ST_LineStringFromWKB(
    ST_AsBinary(ST_GeomFromText('LINESTRING(1 2, 3 4)'))
  ) AS aline,
  ST_LinestringFromWKB(
    ST_AsBinary(ST_GeomFromText('POINT(1 2)'))
  ) IS NULL AS null_return;
  aline                                | null_return
-----
01020000000200000000000000000000F ... | t
```

返回

ST_GeomFromWKB, ST_LineFromWKB

7.8.2.6 ST_PointFromWKB

ST_PointFromWKB — 返回 SRID 返回 WKB 返回。

Synopsis

geometry **ST_GeomFromWKB**(bytea geom);
 geometry **ST_GeomFromWKB**(bytea geom, integer srid);

描述

ST_PointFromWKB 将 WKB 格式 SRID(空间参考系统 ID) 转换为 POINT 类型。 它是 SQL Geometry Factory 的一部分。

SRID 默认为 0。 如果 geom 是 NULL，则返回 NULL。

- ✓ This method implements the [OGC Simple Features Implementation Specification for SQL 1.1. s3.2.7.2](#)
- ✓ This method implements the SQL/MM specification. SQL-MM 3: 6.1.9
- ✓ This function supports 3d and will not drop the z-index.
- ✓ This method supports Circular Strings and Curves.

示例

```
SELECT
  ST_AsText(
    ST_PointFromWKB(
      ST_AsEWKB('POINT(2 5)::geometry')
    )
  );
 st_astext
-----
POINT(2 5)
(1 row)

SELECT
  ST_AsText(
    ST_PointFromWKB(
      ST_AsEWKB('LINESTRING(2 5, 2 6)::geometry')
    )
  );
 st_astext
-----
(1 row)
```

参见

[ST_GeomFromWKB](#), [ST_LineFromWKB](#)

7.8.2.7 ST_WKBToSQL

ST_WKBToSQL — WKB(Well-Known Binary) 格式 ST_Geometry 转换为 SRID 格式 ST_GeomFromWKB 格式。

Synopsis

geometry **ST_WKBToSQL**(bytea WKB);

⚠️

✅ This method implements the SQL/MM specification. SQL-MM 3: 5.1.36

⚠️

ST_GeomFromWKB

7.8.3 Other Formats

7.8.3.1 ST_Box2dFromGeoHash

ST_Box2dFromGeoHash — GeoHash 字符串 BOX2D 字符串。

Synopsis

box2d **ST_Box2dFromGeoHash**(text geohash, integer precision=full_precision_of_geohash);

⚠️

GeoHash 字符串 BOX2D 字符串。

If no precision is specified ST_Box2dFromGeoHash returns a BOX2D based on full precision of the input GeoHash string.

precision 字符串, ST_Box2dFromGeoHash 将 GeoHash 字符串转换为 BOX2D 字符串。返回的 BOX2D 字符串与输入字符串的精度相同。

2.1.0 版本引入。

⚠️

```
SELECT ST_Box2dFromGeoHash('9qqj7nmxcggy4d0dbxqz0');
```

```
          st_geomfromgeohash
```

```
-----
BOX(-115.172816 36.114646,-115.172816 36.114646)
```

```
SELECT ST_Box2dFromGeoHash('9qqj7nmxcggy4d0dbxqz0', 0);
```

```
          st_box2dfromgeohash
```

```
-----
BOX(-180 -90,180 90)
```

```
SELECT ST_Box2dFromGeoHash('9qqj7nmxcggy4d0dbxqz0', 10);
```

```
          st_box2dfromgeohash
```

```
-----
BOX(-115.17282128334 36.1146408319473,-115.172810554504 36.1146461963654)
```


7.8.3.3 ST_GeomFromGML

ST_GeomFromGML — 将 GML 几何对象转换为 PostGIS 几何对象。

Synopsis

```
geometry ST_GeomFromGML(text geomgml);
geometry ST_GeomFromGML(text geomgml, integer srid);
```

返回

OGC GML 几何对象转换为 PostGIS ST_Geometry 几何对象。

ST_GeomFromGML 将 GML 几何对象 (geometry fragment) 转换为 PostGIS 几何对象。该 GML 几何对象必须是有效的。

支持的 OGC GML 几何对象类型:

- GML 3.2.1 几何对象
- GML 3.1.1 几何对象 SF-2 (GML 3.1.0 到 3.0.0 几何对象)
- GML 2.1.2

OGC GML 规范: <http://www.opengeospatial.org/standards/gml>

1.5 版本使用 LibXML2 1.6 版本。

支持: 2.0.0 版本 (polyhedral surface) 和 TIN 几何对象。

支持: 2.0.0 版本 SRID 几何对象。



This function supports 3d and will not drop the z-index.



This function supports Polyhedral surfaces.



This function supports Triangles and Triangulated Irregular Network Surfaces (TIN).

GML 几何对象 (MultiGeometry) 支持 2D 和 3D 几何对象。PostGIS 支持 Z 索引的 ST_GeomFromGML 支持 2D 几何对象。

GML 几何对象 SRS 支持。PostGIS 支持 SRS, 使用 ST_GeomFromGML 支持 SRS 几何对象。GML 几何对象 srsName 属性, 使用几何对象。

ST_GeomFromGML 支持 GML 几何对象。支持的 GML 几何对象 XLink 属性。



Note

ST_GeomFromGML 支持 SQL/MM 几何对象。

例 1: srsName 指定

```
SELECT ST_GeomFromGML($$
  <gml:LineString xmlns:gml="http://www.opengis.net/gml"
    srsName="EPSG:4269">
    <gml:coordinates>
      -71.16028,42.258729 -71.160837,42.259112 -71.161143,42.25932
    </gml:coordinates>
  </gml:LineString>
$$);
```

例 2: XLink 指定

```
SELECT ST_GeomFromGML($$
  <gml:LineString xmlns:gml="http://www.opengis.net/gml"
    xmlns:xlink="http://www.w3.org/1999/xlink"
    srsName="urn:ogc:def:crs:EPSG::4269">
    <gml:pointProperty>
      <gml:Point gml:id="p1"
        ><gml:pos
          >42.258729 -71.16028</gml:pos
        ></gml:Point>
      </gml:pointProperty>
      <gml:pos
        >42.259112 -71.160837</gml:pos>
      <gml:pointProperty>
        <gml:Point xlink:type="simple" xlink:href="#p1"/>
      </gml:pointProperty>
    </gml:LineString>
$$);
```

例 3: 多边形

```
SELECT ST_AsEWKT(ST_GeomFromGML('
  <gml:PolyhedralSurface xmlns:gml="http://www.opengis.net/gml">
  <gml:polygonPatches>
    <gml:PolygonPatch>
      <gml:exterior>
        <gml:LinearRing
          ><gml:posList srsDimension="3"
            >0 0 0 0 1 0 1 1 0 1 0 0 0 0</gml:posList
          ></gml:LinearRing>
        </gml:exterior>
      </gml:PolygonPatch>
      <gml:PolygonPatch>
        <gml:exterior>
          <gml:LinearRing
            ><gml:posList srsDimension="3"
              >0 0 0 0 1 0 1 1 0 1 0 0 0 0</gml:posList
            ></gml:LinearRing>
          </gml:exterior>
        </gml:PolygonPatch>
        <gml:PolygonPatch>
          <gml:exterior>
            <gml:LinearRing
              ><gml:posList srsDimension="3"
```

```

>0 0 0 1 0 0 1 0 1 0 0 1 0 0 0</gml:posList
></gml:LinearRing>
  </gml:exterior>
</gml:PolygonPatch>
<gml:PolygonPatch>
  <gml:exterior>
    <gml:LinearRing
><gml:posList srsDimension="3"
>1 1 0 1 1 1 1 0 1 1 0 0 1 1 0</gml:posList
></gml:LinearRing>
  </gml:exterior>
</gml:PolygonPatch>
<gml:PolygonPatch>
  <gml:exterior>
    <gml:LinearRing
><gml:posList srsDimension="3"
>0 1 0 0 1 1 1 1 1 1 0 0 1 0</gml:posList
></gml:LinearRing>
  </gml:exterior>
</gml:PolygonPatch>
<gml:PolygonPatch>
  <gml:exterior>
    <gml:LinearRing
><gml:posList srsDimension="3"
>0 0 1 1 0 1 1 1 1 0 1 1 0 0 1</gml:posList
></gml:LinearRing>
  </gml:exterior>
</gml:PolygonPatch>
</gml:polygons>
</gml:PolyhedralSurface
>')));

-- result --
POLYHEDRALSURFACE(((0 0 0,0 0 1,0 1 1,0 1 0,0 0 0)),
((0 0 0,0 1 0,1 1 0,1 0 0,0 0 0)),
((0 0 0,1 0 0,1 0 1,0 0 1,0 0 0)),
((1 1 0,1 1 1,1 0 1,1 0 0,1 1 0)),
((0 1 0,0 1 1,1 1 1,1 1 0,0 1 0)),
((0 0 1,1 0 1,1 1 1,0 1 1,0 0 1)))

```

☒☒

Section [2.2.3](#), [ST_AsGML](#), [ST_GMLToSQL](#)

7.8.3.4 ST_GeomFromGeoJSON

ST_GeomFromGeoJSON — GeoJSON 格式数据转换为 PostGIS 几何类型。

Synopsis

```

geometry ST_GeomFromGeoJSON(text geomjson);
geometry ST_GeomFromGeoJSON(json geomjson);
geometry ST_GeomFromGeoJSON(jsonb geomjson);

```


☐☐

GeoJSON 格式数据 PostGIS 数据库存储。

ST_GeomFromGML 从 JSON 格式 (geometry fragment) 格式数据。从 JSON 格式数据。

Enhanced: 3.0.0 parsed geometry defaults to SRID=4326 if not specified otherwise.

Enhanced: 2.5.0 can now accept json and jsonb as inputs.

2.0.0 支持 JSON-C 0.9 格式数据。



Note

JSON-C 格式数据, 支持 JSON-C 格式数据。JSON-C 格式数据, "--with-jsondir=/path/to/json-c" 格式数据。请参考 Section 2.2.3 格式数据。



This function supports 3d and will not drop the z-index.

☐☐

```
SELECT ST_AsText(ST_GeomFromGeoJSON('{"type":"Point","coordinates":[-48.23456,20.12345]}')) ←
      As wkt;
wkt
-----
POINT(-48.23456 20.12345)
```

```
-- a 3D linestring
SELECT ST_AsText(ST_GeomFromGeoJSON('{"type":"LineString","coordinates" ←
      ":[1,2,3],[4,5,6],[7,8,9]}')) As wkt;
wkt
-----
LINESTRING(1 2,4 5,7 8)
```

☐☐

ST_AsText, ST_AsGeoJSON, Section 2.2.3

7.8.3.5 ST_GeomFromKML

ST_GeomFromKML — 从 KML 格式数据 PostGIS 数据库存储。

Synopsis

geometry **ST_GeomFromKML**(text geomkml);

❏

```
SELECT ST_AsText(ST_GeomFromTWKB(ST_AsTWKB('LINESTRING(126 34, 127 35)::geometry')));
```

```

      st_astext
-----
LINESTRING(126 34, 127 35)
(1 row)
```

```

SELECT ST_AsEWKT(
  ST_GeomFromTWKB(E'\\x620002f7f40dbce4040105')
);
                                     st_asewkt
-----
LINESTRING(-113.98 39.198, -113.981 39.195)
(1 row)
```

❏

ST_AsTWKB

7.8.3.7 ST_GMLToSQL

ST_GMLToSQL — GML 转换为 ST_Geometry。 使用 ST_GeomFromGML 将 GML 转换为 ST_Geometry。

Synopsis

```

geometry ST_GMLToSQL(text geomgml);
geometry ST_GMLToSQL(text geomgml, integer srid);
```

❏

 This method implements the SQL/MM specification. SQL-MM 3: 5.1.50 (2D simple surface).
1.5 2D simple surface. LibXML2 1.6 2D simple surface.

2.0.0 2D simple surface (polyhedral surface) 2D TIN 2D simple surface.

2.0.0 2D simple surface SRID 2D simple surface.

❏

Section 2.2.3, **ST_GeomFromGML**, **ST_AsGML**

7.8.3.8 ST_LineFromEncodedPolyline

ST_LineFromEncodedPolyline — 将 (polyline) 转换为 ST_Geometry。

Synopsis

```
geometry ST_LineFromEncodedPolyline(text polyline, integer precision=5);
```

函数

函数返回一个 `LINESTRING` 几何类型。

Optional precision specifies how many decimal places will be preserved in Encoded Polyline. Value should be the same on encoding and decoding, or coordinates will be incorrect.

参考: <http://developers.google.com/maps/documentation/utilities/polylinealgorithm>

2.2.0 版本引入。

函数

```
-- Create a line string from a polyline
SELECT ST_AsEWKT(ST_LineFromEncodedPolyline('_p~iF~ps|U_ulLnnqC_mqNvxq`@'));
-- result --
SRID=4326;LINESTRING(-120.2 38.5,-120.95 40.7,-126.453 43.252)

-- Select different precision that was used for polyline encoding
SELECT ST_AsEWKT(ST_LineFromEncodedPolyline('_p~iF~ps|U_ulLnnqC_mqNvxq`@',6));
-- result --
SRID=4326;LINESTRING(-12.02 3.85,-12.095 4.07,-12.6453 4.3252)
```

函数

ST_AsEncodedPolyline

7.8.3.9 ST_PointFromGeoHash

ST_PointFromGeoHash — GeoHash 字符串转换为点几何。

Synopsis

point **ST_PointFromGeoHash**(text geohash, integer precision=full_precision_of_geohash);

函数

GeoHash 字符串转换为点几何。返回的 GeoHash 字符串与输入相同。

precision 指定要保留的小数位数，**ST_PointFromGeoHash** 返回的 GeoHash 字符串将与输入字符串具有相同的精度。

precision 指定要保留的小数位数，**ST_PointFromGeoHash** 返回的 GeoHash 字符串将与输入字符串具有相同的精度。

2.1.0 版本引入。

函数

```

SELECT ST_AsText(ST_PointFromGeoHash('9qqj7nmxcggy4d0dbxqz0'));
          st_astext
-----
POINT(-115.172816 36.114646)

SELECT ST_AsText(ST_PointFromGeoHash('9qqj7nmxcggy4d0dbxqz0', 4));
          st_astext
-----
POINT(-115.13671875 36.123046875)

SELECT ST_AsText(ST_PointFromGeoHash('9qqj7nmxcggy4d0dbxqz0', 10));
          st_astext
-----
POINT(-115.172815918922 36.1146435141563)

```

☒☒

`ST_GeoHash`, `ST_Box2dFromGeoHash`, `ST_GeomFromGeoHash`

7.8.3.10 `ST_FromFlatGeobufToTable`

`ST_FromFlatGeobufToTable` — Creates a table based on the structure of FlatGeobuf data.

Synopsis

`void` **`ST_FromFlatGeobufToTable`**(text schemaname, text tablename, bytea FlatGeobuf input data);

☒☒

Creates a table based on the structure of FlatGeobuf data. (<http://flatgeobuf.org>).

`schema` Schema name.

`table` Table name.

`data` Input FlatGeobuf data.

Availability: 3.2.0

7.8.3.11 `ST_FromFlatGeobuf`

`ST_FromFlatGeobuf` — Reads FlatGeobuf data.

Synopsis

setof anyelement **`ST_FromFlatGeobuf`**(anyelement Table reference, bytea FlatGeobuf input data);

☒☒

Reads FlatGeobuf data (<http://flatgeobuf.org>). NOTE: PostgreSQL bytea cannot exceed 1GB.

`tabletype` reference to a table type.

`data` input FlatGeobuf data.

Availability: 3.2.0

7.9 Geometry Output

7.9.1 Well-Known Text (WKT)

7.9.1.1 ST_AsEWKT

ST_AsEWKT — 将 WKT(Well-Known Text) 转换为 SRID 的 EWKT 格式。

Synopsis

```
text ST_AsEWKT(geometry g1);
text ST_AsEWKT(geometry g1, integer maxdecimaldigits=15);
text ST_AsEWKT(geography g1);
text ST_AsEWKT(geography g1, integer maxdecimaldigits=15);
```

返回

Returns the Well-Known Text representation of the geometry prefixed with the SRID. The optional *maxdecimaldigits* argument may be used to reduce the maximum number of decimal digits after floating point used in output (defaults to 15).

To perform the inverse conversion of EWKT representation to PostGIS geometry use [ST_GeomFromEWKT](#).



Warning

Using the *maxdecimaldigits* parameter can cause output geometry to become invalid. To avoid this use [ST_ReducePrecision](#) with a suitable gridsize first.



Note

The WKT spec does not include the SRID. To get the OGC WKT format use [ST_AsText](#).



Warning

WKT format does not maintain precision so to prevent floating truncation, use [ST_AsBinary](#) or [ST_AsEWKB](#) format for transport.

Enhanced: 3.1.0 support for optional precision parameter.

版本: 2.0.0 支持, 支持, 支持 TIN 支持.



This function supports 3d and will not drop the z-index.



This method supports Circular Strings and Curves.



This function supports Polyhedral surfaces.



This function supports Triangles and Triangulated Irregular Network Surfaces (TIN).

❏

```
SELECT ST_AsEWKT('0103000020E61000000100000005000000000000
0000000000000000000000000000000000000000000000000000
F03F000000000000F03F000000000000F03F000000000000F03
F000000000000000000000000000000000000000000000000000'::geometry);

      st_asewkt
-----
SRID=4326;POLYGON((0 0,0 1,1 1,1 0,0 0))
(1 row)

SELECT ST_AsEWKT('010800008003000000000000000060 ↵
E30A4100000000785C0241000000000000F03F0000000018
E20A4100000000485F02410000000000000400000000018
E20A4100000000305C02410000000000000840')

--st_asewkt--
CIRCULARSTRING(220268 150415 1,220227 150505 2,220227 150406 3)
```

❏

[ST_AsBinary](#), [ST_AsEWKB](#), [ST_AsText](#), [ST_GeomFromEWKT](#)

7.9.1.2 ST_AsText

[ST_AsText](#) — [OGC](#)/[ISO](#) WKT(Well-Known Text) [SRID](#) [Well-Known Text](#).

Synopsis

```
text ST_AsText(geometry g1);
text ST_AsText(geometry g1, integer maxdecimaldigits = 15);
text ST_AsText(geography g1);
text ST_AsText(geography g1, integer maxdecimaldigits = 15);
```

❏

Returns the OGC [Well-Known Text](#) (WKT) representation of the geometry/geography. The optional *maxdecimaldigits* argument may be used to limit the number of digits after the decimal point in output ordinates (defaults to 15).

To perform the inverse conversion of WKT representation to PostGIS geometry use [ST_GeomFromText](#).



Note

The standard OGC WKT representation does not include the SRID. To include the SRID as part of the output representation, use the non-standard PostGIS function [ST_AsEWKT](#)



Warning

The textual representation of numbers in WKT may not maintain full floating-point precision. To ensure full accuracy for data storage or transport it is best to use [Well-Known Binary](#) (WKB) format (see [ST_AsBinary](#) and *maxdecimaldigits*).



Warning

Using the `maxdecimaldigits` parameter can cause output geometry to become invalid. To avoid this use `ST_ReducePrecision` with a suitable gridsize first.

1.5.0 ☒☒☒☒☒☒☒☒☒☒☒☒.

Enhanced: 2.5 - optional parameter precision introduced.



✔ This method implements the [OGC Simple Features Implementation Specification for SQL 1.1](#).
s2.1.1.1



✔ This method implements the SQL/MM specification. SQL-MM 3: 5.1.25



✔ This method supports Circular Strings and Curves.



```
SELECT ST_AsText('010300000001000000050000000000000000  
000000000000000000000000000000000000000000000000  
F03F000000000000F03F000000000000F03F000000000000F03  
F000000000000000000000000000000000000000000000');
```

```
st_astext
-----
POLYGON((0 0,0 1,1 1,1 0,0 0))
```

Full precision output is the default.

```
SELECT ST_AsText('POINT(111.111111 1.111111)');
      st_astext
-----
POINT(111.111111 1.111111)
```

The *maxdecimaldigits* argument can be used to limit output precision.

```
SELECT ST_AsText('POINT(111.111111 1.111111)'), 2);
      st_astext
-----
POINT(111.11 1.11)
```



ST AsBinary, ST AsEWKB, ST AsEWKT, ST GeomFromText

7.9.2 Well-Known Binary (WKB)

7.9.2.1 ST AsBinary

ST_AsBinary — Return the OGC/ISO Well-Known Binary (WKB) representation of the geometry/geography without SRID meta data.

Synopsis

```
bytea ST_AsBinary(geometry g1);
bytea ST_AsBinary(geometry g1, text NDR_or_XDR);
bytea ST_AsBinary(geography g1);
bytea ST_AsBinary(geography g1, text NDR_or_XDR);
```

返回

Returns the OGC/ISO **Well-Known Binary** (WKB) representation of the geometry. The first function variant defaults to encoding using server machine endian. The second function variant takes a text argument specifying the endian encoding: either 'NDR' for little-endian; or 'XDR' for big-endian. Supplying unknown arguments will result in little-endian output.

WKB format is useful to read geometry data from the database and maintaining full numeric precision. This avoids the precision rounding that can happen with text formats such as WKT.

To perform the inverse conversion of WKB to PostGIS geometry use **ST_GeomFromWKB**.



Note

The OGC/ISO WKB format does not include the SRID. To get the EWKB format which does include the SRID use **ST_AsEWKB**



Note

The default behavior in PostgreSQL 9.0 has been changed to output bytea in hex encoding. If your GUI tools require the old behavior, then SET bytea_output='escape' in your database.

2.0.0 支持 3D 几何体, 支持 TIN 几何体。

2.0.0 支持 3D 几何体。

2.0.0 支持 3D 几何体。

1.5.0 支持 3D 几何体。

2.0.0 支持 3D 几何体。在 PostgreSQL 9.0 中, `st_asbinary(unknown)` 不是唯一的错误。使用 `ST_AsBinary('POINT(1 2)::geometry');` 可以解决这个问题。在 `legacy.sql` 中。



This method implements the **OGC Simple Features Implementation Specification for SQL 1.1**, s2.1.1.1



This method implements the SQL/MM specification. SQL-MM 3: 5.1.37



This method supports Circular Strings and Curves.



This function supports Polyhedral surfaces.



This function supports Triangles and Triangulated Irregular Network Surfaces (TIN).



This function supports 3d and will not drop the z-index.


```
SELECT ST_Ashexewkb(ST_GeomFromText('POLYGON((0 0,0 1,1 1,1 0,0 0))',4326));
which gives same answer as

SELECT ST_GeomFromText('POLYGON((0 0,0 1,1 1,1 0,0 0))',4326)::text;

st_ashexewkb
-----
0103000020E6100000010000000500
000000000000000000000000000000
00000000000000000000000000000F03F
0000000000000F03F00000000000F03F000000000000F03
F00000000000000000000000000000000000000000000000
```

7.9.3 Other Formats

7.9.3.1 ST_AsEncodedPolyline

ST_AsEncodedPolyline — 将几何体编码为 Polyline 格式。

Synopsis

text **ST_AsEncodedPolyline**(geometry geom, integer precision=5);

返回

Returns the geometry as an Encoded Polyline. This format is used by Google Maps with precision=5 and by Open Source Routing Machine with precision=5 and 6.

Optional precision specifies how many decimal places will be preserved in Encoded Polyline. Value should be the same on encoding and decoding, or coordinates will be incorrect.

2.2.0 版本引入。

返回

返回

```
SELECT ST_AsEncodedPolyline(GeomFromEWKT('SRID=4326;LINESTRING(-120.2 38.5,-120.95 40.7,-126.453 43.252)'));
-- result --
|_p~iF~ps|U_ulLnnqC_mqNvxq`@
```

ST_AsEncodedPolyline (segmentize) 将几何体编码为 Polyline 格式，并分段。

```
-- the SQL for Boston to San Francisco, segments every 100 KM
SELECT ST_AsEncodedPolyline(
  ST_Segmentize(
    ST_GeogFromText('LINESTRING(-71.0519 42.4935,-122.4483 37.64)'),
    100000)::geometry) As encodedFlightPath;
```

返回 \$ 符号表示的 Polyline 格式。

```
<script type="text/javascript" src="http://maps.googleapis.com/maps/api/js?libraries= ↵
  geometry"
></script>
<script type="text/javascript">
  flightPath = new google.maps.Polyline({
    path: google.maps.geometry.encoding.decodePath("$encodedFlightPath"),
    map: map,
    strokeColor: '#0000CC',
    strokeOpacity: 1.0,
    strokeWeight: 4
  });
</script>
```

☒☒

ST_LineFromEncodedPolyline, ST_Segmentize

7.9.3.2 ST_AsFlatGeobuf

ST_AsFlatGeobuf — Return a FlatGeobuf representation of a set of rows.

Synopsis

```
bytea ST_AsFlatGeobuf(anyelement set row);
bytea ST_AsFlatGeobuf(anyelement row, bool index);
bytea ST_AsFlatGeobuf(anyelement row, bool index, text geom_name);
```

☒☒

Return a FlatGeobuf representation (<http://flatgeobuf.org>) of a set of rows corresponding to a FeatureCollection. NOTE: PostgreSQL bytea cannot exceed 1GB.

row row data with at least a geometry column.

index toggle spatial index creation. Default is false.

geom_name is the name of the geometry column in the row data. If NULL it will default to the first found geometry column.

Availability: 3.2.0

7.9.3.3 ST_AsGeobuf

ST_AsGeobuf — Return a Geobuf representation of a set of rows.

Synopsis

```
bytea ST_AsGeobuf(anyelement set row);
bytea ST_AsGeobuf(anyelement row, text geom_name);
```

返回

Return a Geobuf representation (<https://github.com/mapbox/geobuf>) of a set of rows corresponding to a FeatureCollection. Every input geometry is analyzed to determine maximum precision for optimal storage. Note that Geobuf in its current form cannot be streamed so the full output will be assembled in memory.

row row data with at least a geometry column.

geom_name is the name of the geometry column in the row data. If NULL it will default to the first found geometry column.

2.2.0 支持。

返回

```
SELECT encode(ST_AsGeobuf(q, 'geom'), 'base64')
  FROM (SELECT ST_GeomFromText('POLYGON((0 0,0 1,1 1,1 0,0 0))') AS geom) AS q;
st_asgeobuf
-----
GAAiEAo0CgwIBBoIAAAAAGIAAAE=
```

7.9.3.4 ST_AsGeoJSON

ST_AsGeoJSON — Return a geometry or feature in GeoJSON format.

Synopsis

```
text ST_AsGeoJSON(record feature, text geom_column="", integer maxdecimaldigits=9, boolean
pretty_bool=false, text id_column="");
text ST_AsGeoJSON(geometry geom, integer maxdecimaldigits=9, integer options=8);
text ST_AsGeoJSON(geography geog, integer maxdecimaldigits=9, integer options=0);
```

返回

Returns a geometry as a GeoJSON "geometry" object, or a row as a GeoJSON "feature" object.

The resulting GeoJSON geometry and feature representations conform with the [GeoJSON specifications RFC 7946](#), except when the parsed geometries are referenced with a CRS other than WGS84 longitude and latitude ([EPSG:4326](#), [urn:ogc:def:crs:OGC::CRS84](#)); the GeoJSON geometry object will then have a short CRS SRID identifier attached by default. 2D and 3D Geometries are both supported. GeoJSON only supports SFS 1.1 geometry types (no curve support for example).

The geom_column parameter is used to distinguish between multiple geometry columns. If omitted, the first geometry column in the record will be determined. Conversely, passing the parameter will save column type lookups.

The maxdecimaldigits argument may be used to reduce the maximum number of decimal places used in output (defaults to 9). If you are using EPSG:4326 and are outputting the geometry only for display, maxdecimaldigits=6 can be a good choice for many maps.



Warning

Using the *maxdecimaldigits* parameter can cause output geometry to become invalid. To avoid this use [ST_ReducePrecision](#) with a suitable gridsize first.

The `options` argument can be used to add BBOX or CRS in GeoJSON output:

- 0: means no option
- 1: GeoJSON BBOX
- 2: GeoJSON Short CRS (国: EPSG:4326)
- 4: GeoJSON Long CRS (国: urn:ogc:def:crs:EPSG::4326)
- 8: GeoJSON Short CRS if not EPSG:4326 (default)

The `id_column` parameter is used to set the "id" member of the returned GeoJSON features. As per GeoJSON RFC, this SHOULD be used whenever a feature has a commonly used identifier, such as a primary key. When not specified, the produced features will not get an "id" member and any columns other than the geometry, including any potential keys, will just end up inside the feature's "properties" member.

The GeoJSON specification states that polygons are oriented using the Right-Hand Rule, and some clients require this orientation. This can be ensured by using `ST_ForcePolygonCCW`. The specification also requires that geometry be in the WGS84 coordinate system (SRID = 4326). If necessary geometry can be projected into WGS84 using `ST_Transform`: `ST_Transform( geom, 4326 )`.

GeoJSON can be tested and viewed online at geojson.io and geojsonlint.com. It is widely supported by web mapping frameworks:

- [OpenLayers GeoJSON Example](#)
- [Leaflet GeoJSON Example](#)
- [Mapbox GL GeoJSON Example](#)

1.3.4 国国国国国国国国国国.

1.5.0 国国国国国国国国国国.

国国国: 2.0.0 国国国国国国国国国 (default arg) 国国国国国国国 (named arg) 国国国国国.

Changed: 3.0.0 support records as input

Changed: 3.0.0 output SRID if not EPSG:4326.

Changed: 3.5.0 allow specifying the column containing the feature id



This function supports 3d and will not drop the z-index.

国国

Generate a FeatureCollection:

```
SELECT json_build_object(
    'type', 'FeatureCollection',
    'features', json_agg(ST_AsGeoJSON(t.*, id_column =
> 'id')::json)
)
FROM ( VALUES (1, 'one', 'POINT(1 1)::geometry),
              (2, 'two', 'POINT(2 2)'),
              (3, 'three', 'POINT(3 3)')
      ) as t(id, name, geom);
```

```
{ "type" : "FeatureCollection", "features" : [{ "type": "Feature", "geometry": { "type": "Point", "coordinates": [1,1] }, "id": 1, "properties": { "name": "one" } }, { "type": "Feature", "geometry": { "type": "Point", "coordinates": [2,2] }, "id": 2, "properties": { "name": "two" } }, { "type": "Feature", "geometry": { "type": "Point", "coordinates": [3,3] }, "id": 3, "properties": { "name": "three" } } ] }
```

Generate a Feature:

```
SELECT ST_AsGeoJSON(t.*, id_column =
> 'id')
FROM (VALUES (1, 'one', 'POINT(1 1)::geometry)) AS t(id, name, geom);
```

```
st_asgeojson
```

```
{ "type": "Feature", "geometry": { "type": "Point", "coordinates": [1,1] }, "id": 1, "properties": { "name": "one" } }
```

Don't forget to transform your data to WGS84 longitude, latitude to conform with the GeoJSON specification:

```
SELECT ST_AsGeoJSON(ST_Transform(geom,4326)) from fe_edges limit 1;
```

```
st_asgeojson
```

```
{ "type": "MultiLineString", "coordinates": [ [ [ [-89.734634999999997, 31.492072000000000], [-89.734959999999997, 31.492237999999997] ] ] ] }
```

3D geometries are supported:

```
SELECT ST_AsGeoJSON('LINESTRING(1 2 3, 4 5 6)');
```

```
{ "type": "LineString", "coordinates": [ [ [1,2,3], [4,5,6] ] ] }
```

Options argument can be used to add BBOX and CRS in GeoJSON output:

```
SELECT ST_AsGeoJSON(ST_SetSRID('POINT(1 1)::geometry', 4326), 9, 4|1);
```

```
{ "type": "Point", "crs": { "type": "name", "properties": { "name": "urn:ogc:def:crs:EPSG::4326" } }, "bbox": [1.000000000, 1.000000000, 1.000000000, 1.000000000], "coordinates": [1,1] }
```

☒☒

ST_GeomFromGeoJSON, **ST_ForcePolygonCCW**, **ST_Transform**

7.9.3.5 ST_AsGML

ST_AsGML — ☒☒☒ GML 2 ☒☒ GML 3 ☒☒☒☒☒☒☒☒☒☒.

Synopsis

```
text ST_AsGML(geometry geom, integer maxdecimaldigits=15, integer options=0);
text ST_AsGML(geography geog, integer maxdecimaldigits=15, integer options=0, text nprefix=null,
text id=null);
text ST_AsGML(integer version, geometry geom, integer maxdecimaldigits=15, integer options=0,
text nprefix=null, text id=null);
text ST_AsGML(integer version, geography geog, integer maxdecimaldigits=15, integer options=0,
text nprefix=null, text id=null);
```

返回

Return the geometry as a Geography Markup Language (GML) element. The version parameter, if specified, may be either 2 or 3. If no version parameter is specified then the default is assumed to be 2. The *maxdecimaldigits* argument may be used to reduce the maximum number of decimal places used in output (defaults to 15).



Warning

Using the *maxdecimaldigits* parameter can cause output geometry to become invalid. To avoid this use **ST_ReducePrecision** with a suitable gridsize first.

GML 2 2.1.2 版本, GML 3 3.1.1 版本。

' 选项 ' (bitfield) 选项。 CRS 选项 GML 选项, 选项/选项 选项。

- 0: GML Short CRS (选项: EPSG:4326), 选项
- 1: GML Long CRS (选项: urn:ogc:def:crs:EPSG::4326)
- 2: GML 3 选项, 选项 srsDimension 选项。
- 4: GML 3 选项, 选项 <Curve> 选项 <LineString> 选项。
- 16: 选项/选项 (选项: srid=4326) 选项。 选项。 选项 (axis order) 选项, GML 3.1.1 选项。 选项 选项, 选项。
- 32: 选项 (envelope) 选项。

选项 (选项) 选项' 选项 选项' 选项。 选项 NULL 选项'gml' 选项。

1.3.2 选项。

1.5.0 选项。

选项: 2.0.0 选项。 选项 GML 3 选项'4' 选项。 GML 3 选项 TIN 选项。 选项'32' 选项 选项。

选项: 2.0.0 选项 (named arg) 选项。

选项: 2.1.0 选项 GML 3 选项 ID 选项。



Note

ST_AsGML 选项 3 选项 TIN 选项。

- ✔ This method implements the SQL/MM specification. SQL-MM IEC 13249-3: 17.2
- ✔ This function supports 3d and will not drop the z-index.
- ✔ This function supports Polyhedral surfaces.
- ✔ This function supports Triangles and Triangulated Irregular Network Surfaces (TIN).

例 2

```
SELECT ST_AsGML(ST_GeomFromText('POLYGON((0 0,0 1,1 1,1 0,0 0))',4326));
      st_asgml
-----
<gml:Polygon srsName="EPSG:4326"
><gml:outerBoundaryIs
><gml:LinearRing
><gml:coordinates
>0,0 0,1 1,1 1,0 0,0</gml:coordinates
></gml:LinearRing
></gml:outerBoundaryIs
></gml:Polygon>
```

例 3

```
-- Flip coordinates and output extended EPSG (16 | 1)--
SELECT ST_AsGML(3, ST_GeomFromText('POINT(5.234234233242 6.34534534534)',4326), 5, 17);
      st_asgml
-----
<gml:Point srsName="urn:ogc:def:crs:EPSG::4326"
><gml:pos
>6.34535 5.23423</gml:pos
></gml:Point>
```

```
-- Output the envelope (32) --
SELECT ST_AsGML(3, ST_GeomFromText('LINESTRING(1 2, 3 4, 10 20)',4326), 5, 32);
      st_asgml
-----
<gml:Envelope srsName="EPSG:4326">
  <gml:lowerCorner
>1 2</gml:lowerCorner>
  <gml:upperCorner
>10 20</gml:upperCorner>
</gml:Envelope>
```

```
-- Output the envelope (32) , reverse (lat lon instead of lon lat) (16), long srs (1)= 32 | ←
16 | 1 = 49 --
SELECT ST_AsGML(3, ST_GeomFromText('LINESTRING(1 2, 3 4, 10 20)',4326), 5, 49);
      st_asgml
-----
<gml:Envelope srsName="urn:ogc:def:crs:EPSG::4326">
  <gml:lowerCorner
>2 1</gml:lowerCorner>
  <gml:upperCorner
```

```
>20 10</gml:upperCorner>
</gml:Envelope>
```

```
-- Polyhedral Example --
SELECT ST_AsGML(3, ST_GeomFromEWKT('POLYHEDRALSURFACE( ((0 0 0, 0 0 1, 0 1 1, 0 1 0, 0 0 0) ←
),
((0 0 0, 0 1 0, 1 1 0, 1 0 0, 0 0 0)), ((0 0 0, 1 0 0, 1 0 1, 0 0 1, 0 0 0)),
((1 1 0, 1 1 1, 1 0 1, 1 0 0, 1 1 0)),
((0 1 0, 0 1 1, 1 1 1, 1 1 0, 0 1 0)), ((0 0 1, 1 0 1, 1 1 1, 0 1 1, 0 0 1)) )''));
st_asgml
-----
<gml:PolyhedralSurface>
<gml:polygonPatches>
  <gml:PolygonPatch>
    <gml:exterior>
      <gml:LinearRing>
        <gml:posList srsDimension="3"
>0 0 0 0 0 1 0 1 1 0 1 0 0 0 0</gml:posList>
      </gml:LinearRing>
    </gml:exterior>
  </gml:PolygonPatch>
  <gml:PolygonPatch>
    <gml:exterior>
      <gml:LinearRing>
        <gml:posList srsDimension="3"
>0 0 0 0 1 0 1 1 0 1 0 0 0 0 0</gml:posList>
      </gml:LinearRing>
    </gml:exterior>
  </gml:PolygonPatch>
  <gml:PolygonPatch>
    <gml:exterior>
      <gml:LinearRing>
        <gml:posList srsDimension="3"
>0 0 0 1 0 0 1 0 1 0 0 1 0 0 0</gml:posList>
      </gml:LinearRing>
    </gml:exterior>
  </gml:PolygonPatch>
  <gml:PolygonPatch>
    <gml:exterior>
      <gml:LinearRing>
        <gml:posList srsDimension="3"
>1 1 0 1 1 1 1 0 1 1 0 0 1 1 0</gml:posList>
      </gml:LinearRing>
    </gml:exterior>
  </gml:PolygonPatch>
  <gml:PolygonPatch>
    <gml:exterior>
      <gml:LinearRing>
        <gml:posList srsDimension="3"
>0 1 0 0 1 1 1 1 1 1 1 0 0 1 0</gml:posList>
      </gml:LinearRing>
    </gml:exterior>
  </gml:PolygonPatch>
  <gml:PolygonPatch>
    <gml:exterior>
      <gml:LinearRing>
        <gml:posList srsDimension="3"
>0 0 1 1 0 1 1 1 1 0 1 1 0 0 1</gml:posList>
      </gml:LinearRing>
    </gml:exterior>
  </gml:PolygonPatch>
```


**Note**

ST_AskML 返回 SRID 4326 的 KML 字符串。



This function supports 3d and will not drop the z-index.

例

```
SELECT ST_AskML(ST_GeomFromText('POLYGON((0 0,0 1,1 1,1 0,0 0))',4326));
```

```

    st_askml
    -----
    <Polygon
  ><outerBoundaryIs
  ><LinearRing
  ><coordinates
  >0,0 0,1 1,1 1,0 0,0</coordinates
  ></LinearRing
  ></outerBoundaryIs
  ></Polygon>

  --3d linestring
  SELECT ST_AskML('SRID=4326;LINESTRING(1 2 3, 4 5 6)');
  <LineString
  ><coordinates
  >1,2,3 4,5,6</coordinates
  ></LineString>

```

例

ST_AsSVG, ST_AsGML

7.9.3.7 ST_AsLatLonText

ST_AsLatLonText — 返回指定几何体的经纬度文本表示。

Synopsis

text **ST_AsLatLonText**(geometry pt, text format=“”);

例

ST_AsLatLonText(geom, 'WKT').

**Note**

ST_AsLatLonText 返回的文本格式为 "X(经度) Y(纬度) 格式"。经度范围 (-180 到 180)，纬度范围 (-90 到 90)。

返回的字符串格式为 "D", "M", "S", (方向, cardinal direction) "C" 格式。D, M, S 格式为 "SSS.SSSS" ("SSS.SSSS" 为 "1.0023" 格式)。

M, S, C 格式。"C" 格式为 "S", "S" 格式为 "S", "M" 格式为 "M", "D" 格式为 "D"。

返回的字符串格式为 (方向 0 度) 格式。

2.0 格式。

SQL

SQL

```
SELECT (ST_AsLatLonText('POINT (-3.2342342 -2.32498)'));
      st_aslatlon
-----
2°19'29.928"S 3°14'3.243"W
```

(方向) 格式。

```
SELECT (ST_AsLatLonText('POINT (-3.2342342 -2.32498)', 'D°M'S.SSS"C'));
      st_aslatlon
-----
2°19'29.928"S 3°14'3.243"W
```

D, M, S, C 格式。返回的字符串格式为 "D degrees, M minutes, S seconds to the C"。

```
SELECT (ST_AsLatLonText('POINT (-3.2342342 -2.32498)', 'D degrees, M minutes, S seconds to the C'));
      st_aslatlon
-----
2 degrees, 19 minutes, 30 seconds to the S 3 degrees, 14 minutes, 3 seconds to the W
```

返回的字符串格式为 "D°M'S.SSS"。

```
SELECT (ST_AsLatLonText('POINT (-3.2342342 -2.32498)', 'D°M'S.SSS"));
      st_aslatlon
-----
-2°19'29.928" -3°14'3.243"
```

返回的字符串格式为 "D.DDDD degrees C"。

```
SELECT (ST_AsLatLonText('POINT (-3.2342342 -2.32498)', 'D.DDDD degrees C'));
      st_aslatlon
-----
2.3250 degrees S 3.2342 degrees W
```

返回的字符串格式为 "D°M'S.SSS"。

```
SELECT (ST_AsLatLonText('POINT (-302.2342342 -792.32498)'));
      st_aslatlon
-----
72°19'29.928"S 57°45'56.757"E
```

7.9.3.8 ST_AsMARC21

ST_AsMARC21 — Returns geometry as a MARC21/XML record with a geographic datafield (034).

Synopsis

text **ST_AsMARC21** (geometry geom , text format='hddmmss');



This function returns a MARC21/XML record with **Coded Cartographic Mathematical Data** representing the bounding box of a given geometry. The format parameter allows to encode the coordinates in subfields \$d,\$e,\$f and \$g in all formats supported by the MARC21/XML standard. Valid formats are:

- cardinal direction, degrees, minutes and seconds (default): hddmmss
- decimal degrees with cardinal direction: hddd.dddddd
- decimal degrees without cardinal direction: ddd.dddddd
- decimal minutes with cardinal direction: hddmm.mmmm
- decimal minutes without cardinal direction: dddmm.mmmm
- decimal seconds with cardinal direction: hddmmss.sss

The decimal sign may be also a comma, e.g. hddmm,mmm.

The precision of decimal formats can be limited by the number of characters after the decimal sign, e.g. hddmm.mm for decimal minutes with a precision of two decimals.

This function ignores the Z and M dimensions.

LOC MARC21/XML versions supported:

- **MARC21/XML 1.1**

Availability: 3.3.0



Note

This function does not support non lon/lat geometries, as they are not supported by the MARC21/XML standard (Coded Cartographic Mathematical Data).



Note

The MARC21/XML Standard does not provide any means to annotate the spatial reference system for Coded Cartographic Mathematical Data, which means that this information will be lost after conversion to MARC21/XML.



Converting a POINT to MARC21/XML formatted as hddmmss (default)

```
SELECT ST_AsMARC21( 'SRID=4326;POINT(-4.504289 54.253312) '::geometry);

          st_asmarc21
-----
<record xmlns="http://www.loc.gov/MARC21/slim">
  <datafield tag="034" ind1="1" ind2=" ">
```

```

        <subfield code="a"
>a</subfield>
        <subfield code="d"
>W0043015</subfield>
        <subfield code="e"
>W0043015</subfield>
        <subfield code="f"
>N0541512</subfield>
        <subfield code="g"
>N0541512</subfield>
    </datafield>
</record>

```

Converting a POLYGON to MARC21/XML formatted in decimal degrees

```

SELECT ST_AsMARC21('SRID=4326;POLYGON((-4.5792388916015625 54.18172660239091, -4.56756591796875
54.196993557130355, -4.546623229980469
54.18313300502024, -4.5792388916015625 54.18172660239091))'::geometry, '
hddd.dddd');

<record xmlns="http://www.loc.gov/MARC21/slim">
  <datafield tag="034" ind1="1" ind2=" ">
    <subfield code="a"
>a</subfield>
    <subfield code="d"
>W004.5792</subfield>
    <subfield code="e"
>W004.5466</subfield>
    <subfield code="f"
>N054.1970</subfield>
    <subfield code="g"
>N054.1817</subfield>
  </datafield>
</record>

```

Converting a GEOMETRYCOLLECTION to MARC21/XML formatted in decimal minutes. The geometries order in the MARC21/XML output correspond to their order in the collection.

```

SELECT ST_AsMARC21('SRID=4326;GEOMETRYCOLLECTION(POLYGON((13.1 52.65,13.516666666666667 52.65,13.516666666666667 52.38333333333333,13.1
52.38333333333333,13.1 52.65)),POINT(-4.5 54.25))'::geometry, 'hdddmm.
mmmm');

          st_asmarc21
-----
<record xmlns="http://www.loc.gov/MARC21/slim">
  <datafield tag="034" ind1="1" ind2=" ">
    <subfield code="a"
>a</subfield>
    <subfield code="d"
>E01307.0000</subfield>

```



```

                                <subfield code="e"
>E01331.0000</subfield>
                                <subfield code="f"
>N05240.0000</subfield>
                                <subfield code="g"
>N05224.0000</subfield>
                                </datafield>
                                <datafield tag="034" ind1="1" ind2=" ">
                                <subfield code="a"
>a</subfield>
                                <subfield code="d"
>W00430.0000</subfield>
                                <subfield code="e"
>W00430.0000</subfield>
                                <subfield code="f"
>N05415.0000</subfield>
                                <subfield code="g"
>N05415.0000</subfield>
                                </datafield>
</record>

```

国国

ST_GeomFromMARC21

7.9.3.9 ST_AsMVTGeom

ST_AsMVTGeom — Transforms a geometry into the coordinate space of a MVT tile.

Synopsis

geometry **ST_AsMVTGeom**(geometry geom, box2d bounds, integer extent=4096, integer buffer=256, boolean clip_geom=true);

国国

Transforms a geometry into the coordinate space of a MVT (**Mapbox Vector Tile**) tile, clipping it to the tile bounds if required. The geometry must be in the coordinate system of the target map (using **ST_Transform** if needed). Commonly this is **Web Mercator** (SRID:3857).

The function attempts to preserve geometry validity, and corrects it if needed. This may cause the result geometry to collapse to a lower dimension.

The rectangular bounds of the tile in the target map coordinate space must be provided, so the geometry can be transformed, and clipped if required. The bounds can be generated using **ST_TileEnvelope**.

This function is used to convert geometry into the tile coordinate space required by **ST_AsMVT**.

geom is the geometry to transform, in the coordinate system of the target map.

bounds is the rectangular bounds of the tile in map coordinate space, with no buffer.

extent is the tile extent size in tile coordinate space as defined by the **MVT specification**. Defaults to 4096.

buffer is the buffer size in tile coordinate space for geometry clipping. Defaults to 256.

clip_geom is a boolean to control if geometries are clipped or encoded as-is. Defaults to true.

2.2.0 国国国国国国国国国国国国.



Note

From 3.0, Wagyu can be chosen at configure time to clip and validate MVT polygons. This library is faster and produces more correct results than the GEOS default, but it might drop small polygons.

国国

```
SELECT ST_AsText(ST_AsMVTGeom(
  ST_GeomFromText('POLYGON ((0 0, 10 0, 10 5, 0 -5, 0 0))'),
  ST_MakeBox2D(ST_Point(0, 0), ST_Point(4096, 4096)),
  4096, 0, false));
               st_astext
-----
MULTIPOLYGON(((5 4096,10 4091,10 4096,5 4096)),((5 4096,0 4101,0 4096,5 4096)))
```

Canonical example for a Web Mercator tile using a computed tile bounds to query and clip geometry. This assumes the data.geom column has srid of 4326.

```
SELECT ST_AsMVTGeom(
  ST_Transform( geom, 3857 ),
  ST_TileEnvelope(12, 513, 412), extent =
> 4096, buffer =
> 64) AS geom
FROM data
WHERE geom && ST_Transform(ST_TileEnvelope(12, 513, 412, margin =
> (64.0 / 4096)),4326)
```

国国

[ST_AsMVT](#), [ST_TileEnvelope](#), [PostGIS_Wagyu_Version](#)

7.9.3.10 ST_AsMVT

ST_AsMVT — Aggregate function returning a MVT representation of a set of rows.

Synopsis

```
bytea ST_AsMVT(anyelement set row);
bytea ST_AsMVT(anyelement row, text name);
bytea ST_AsMVT(anyelement row, text name, integer extent);
bytea ST_AsMVT(anyelement row, text name, integer extent, text geom_name);
bytea ST_AsMVT(anyelement row, text name, integer extent, text geom_name, text feature_id_name);
```

国国

An aggregate function which returns a binary **Mapbox Vector Tile** representation of a set of rows corresponding to a tile layer. The rows must contain a geometry column which will be encoded as a feature geometry. The geometry must be in tile coordinate space and valid as per the **MVT specification**. **ST_AsMVTGeom** can be used to transform geometry into tile coordinate space. Other row columns are encoded as feature attributes.

The **Mapbox Vector Tile** format can store features with varying sets of attributes. To use this capability supply a JSONB column in the row data containing Json objects one level deep. The keys and values in the JSONB values will be encoded as feature attributes.

Tiles with multiple layers can be created by concatenating multiple calls to this function using || or STRING_AGG.



Important

Do not call with a GEOMETRYCOLLECTION as an element in the row. However you can use **ST_AsMVTGeom** to prepare a geometry collection for inclusion.

row row data with at least a geometry column.

name is the name of the layer. Default is the string "default".

extent is the tile extent in screen space as defined by the specification. Default is 4096.

geom_name is the name of the geometry column in the row data. Default is the first geometry column. Note that PostgreSQL by default automatically **folds unquoted identifiers to lower case**, which means that unless the geometry column is quoted, e.g. "MyMVTGeom", this parameter must be provided as lowercase.

feature_id_name is the name of the Feature ID column in the row data. If NULL or negative the Feature ID is not set. The first column matching name and valid type (smallint, integer, bigint) will be used as Feature ID, and any subsequent column will be added as a property. JSON properties are not supported.

Enhanced: 3.0 - added support for Feature ID.

Enhanced: 2.5.0 - added support parallel query.

2.2.0 国国国国国国国国国国国国.

国国

```
WITH mvtgeom AS
(
  SELECT ST_AsMVTGeom(geom, ST_TileEnvelope(12, 513, 412), extent =
> 4096, buffer =
> 64) AS geom, name, description
  FROM points_of_interest
  WHERE geom && ST_TileEnvelope(12, 513, 412, margin =
> (64.0 / 4096))
)
SELECT ST_AsMVT(mvtgeom.*)
FROM mvtgeom;
```



```
SELECT ST_AsSVG('MULTICURVE((5 5,3 5,3 3,0 3),
  CIRCULARSTRING(0 0,2 1,2 2))'::geometry, 0, 0);
st_assvg
```

```
-----
M 5 -5 L 3 -5 3 -3 0 -3 M 0 0 A 2 2 0 0 0 2 -2
```

Multi-surface

```
SELECT ST_AsSVG('MULTISURFACE(
  CURVEPOLYGON(CIRCULARSTRING(-2 0,-1 -1,0 0,1 -1,2 0,0 2,-2 0),
    (-1 0,0 0.5,1 0,0 1,-1 0)),
  ((7 8,10 10,6 14,4 11,7 8)))'::geometry, 0, 2);
```

st_assvg

```
-----
M -2 0 A 1 1 0 0 0 0 0 A 1 1 0 0 0 2 0 A 2 2 0 0 0 -2 0 Z
M -1 0 L 0 -0.5 1 0 0 -1 -1 0 Z
M 7 -8 L 10 -10 6 -14 4 -11 Z
```

7.9.3.12 ST_AsTWKB

ST_AsTWKB — 将 TWKB(Tiny Well-Known Binary) 格式化为文本。

Synopsis

bytea **ST_AsTWKB**(geometry geom, integer prec=0, integer prec_z=0, integer prec_m=0, boolean with_sizes=false, boolean with_boxes=false);
 bytea **ST_AsTWKB**(geometry[] geom, bigint[] ids, integer prec=0, integer prec_z=0, integer prec_m=0, boolean with_sizes=false, boolean with_boxes=false);

描述

将 TWKB(Tiny Well-Known Binary) 格式化为文本。TWKB 是一种紧凑的二进制格式，用于存储几何数据。它比 WKB 更小，但解析速度较慢。

该函数支持多种几何类型，包括点、线、面、多面体等。它还可以处理带有精度和度量信息的几何数据。对于带有度量信息的几何数据，可以通过设置 `prec_m` 参数来控制度量的精度。

该函数还支持将几何数据转换为文本格式，以便在数据库中存储。对于带有度量信息的几何数据，可以通过设置 `prec_m` 参数来控制度量的精度。此外，还可以通过设置 `with_boxes` 参数来控制是否包含边界框信息。

该函数还支持将几何数据转换为文本格式，以便在数据库中存储。对于带有度量信息的几何数据，可以通过设置 `prec_m` 参数来控制度量的精度。此外，还可以通过设置 `with_boxes` 参数来控制是否包含边界框信息。对于带有度量信息的几何数据，还可以通过设置 `prec_z` 参数来控制 Z 坐标的精度。



Note

<https://github.com/TWKB/Specification> 提供了 TWKB 的完整规范。此外，<https://github.com/TWKB/twkb.js> 提供了 TWKB 的 JavaScript 实现。

Enhanced: 2.4.0 memory and speed improvements.

2.2.0 国际化支持。


```
SELECT ST_AsTWKB('LINESTRING(1 1,5 5)::geometry');
          st_astwkb
-----
\x02000202020808
```

TWKB 格式，`array_agg()` 函数
 TWKB 格式。

```
SELECT ST_AsTWKB(array_agg(geom), array_agg(gid)) FROM mytable;
          st_astwkb
-----
\x040402020400000202
```



ST_GeomFromTWKB, ST_AsBinary, ST_AsEWKB, ST_AsEWKT, ST_GeomFromText

7.9.3.13 ST_AsX3D

ST AsX3D — XXX X3D XML XXXXXXX: ISO-IEC-19776-1.2-X3DEncodings-XML XXXXXXX.

Synopsis

```
text ST_AsX3D(geometry g1, integer maxdecimaldigits=15, integer options=0);
```



<http://www.web3d.org/standards/number/19776-1> X3D XML
 maxdecimaldigits () 15 .

Note



X3D 000000 PostGIS 00000000000000000000 PostGIS 000 X3D 0000000000
0000000000. 00000000000000000000 X3D 00000000000000, 00000000
000 X3D 000000000000. 000000000000000000000000. 0000000000
0000000000000000000000000000000000000000000000000 (bug ticket) 00000000.
000000 PostGIS 2D/3D 000 X3D 0000000000000000.

'XY' 数据类型。PostGIS 2.2 支持, 支持 X3D 数据类型, 支持 x/y 数据类型。支持 ST_AsX3D 函数 (long,lat or X,Y) 数据类型, X3D 数据类型/XY, y/x 数据类型。

- 0: $X/Y(\text{GeoCoordinate}/\text{GeoCoordinate} = X, Y \text{ GeoCoordinate}), \text{GeoCoordinate}, \text{GeoCoordinate}$ (非 GeoCoordinate).
- 1: $X \text{ GeoCoordinate}$. GeoCoordinate (GeoCoordinate) GeoCoordinate , GeoCoordinate GeoCoordinate "latitude first" (GeoCoordinate) GeoCoordinate .

- 2: `POINT(1000000 1000000)`. `WGS84` (SRID 4326) `POINT`, `POINT`. `POINT`. `POINT`. `POINT` X3D `POINT`. `POINT` GeoCoordinate geoSystem='GD WE longitude_first' `POINT`. X3D `POINT` GeoCoordinate geoSystem='GD WE latitude_first' `POINT`, (2 + 1) = 3 `POINT`.

PostGIS	2D X3D	3D X3D
LINESTRING	<code>PolyLine2D</code>	LineSet
MULTILINESTRING	<code>PolyLine2D</code>	IndexedLineSet
MULTIPOINT	<code>Polypoint2D</code>	PointSet
POINT		
(MULTI) POLYGON, POLYHEDRALSURFACE	<code>X3D</code> (markup)	IndexedFaceSet (faceset)
TIN	<code>TriangleSet2D</code>	IndexedTriangleSet



Note

2.      

Lots of advancements happening in 3D space particularly with **X3D Integration with HTML5**

FreeWRL is a free, open-source, cross-platform X3D viewer. It, along with, Free Wrl, is available at <http://freewrl.sourceforge.net/>. FreeWRL_Launcher is a free, open-source, cross-platform FreeWRL_Launcher.

Also check out [PostGIS minimalist X3D viewer](#) that utilizes this function and [x3dDom html/js open source toolkit](#).

2.0.0 0000 ISO-IEC-19776-1.2-X3DEncodings-XML 0000000000.

Version: 2.2.0 (x/y, z/a) Example (x/y, z/a). Example (x/y, z/a).



This function supports 3d and will not drop the z-index.



This function supports Polyhedral surfaces.



This function supports Triangles and Triangulated Irregular Network Surfaces (TIN).

FreeWrl X3D

```
SELECT '<?xml version="1.0" encoding="UTF-8"?>
<!DOCTYPE X3D PUBLIC "ISO//Web3D//DTD X3D 3.0//EN" "http://www.web3d.org/specifications/x3d
-3.0.dtd">
<X3D>
  <Scene>
    <Transform>
      <Shape>
        <Appearance>
          <Material emissiveColor=''0 0 1''/>
        </Appearance>
```

```

> ' ||
    ST_AsX3D( ST_GeomFromEWKT('POLYHEDRALSURFACE( ((0 0 0, 0 0 1, 0 1 1, 0 1 0, 0 0 0)),
((0 0 0, 0 1 0, 1 1 0, 1 0 0, 0 0 0)), ((0 0 0, 1 0 0, 1 0 1, 0 0 1, 0 0 0)),
((1 1 0, 1 1 1, 1 0 1, 1 0 0, 1 1 0)),
((0 1 0, 0 1 1, 1 1 1, 1 1 0, 0 1 0)), ((0 0 1, 1 0 1, 1 1 1, 0 1 1, 0 0 1)) )') ) ||
    '</Shape>
  </Transform>
</Scene>
</X3D>
> ' As x3ddoc;

    x3ddoc
    -----
<?xml version="1.0" encoding="UTF-8"?>
<!DOCTYPE X3D PUBLIC "ISO//Web3D//DTD X3D 3.0//EN" "http://www.web3d.org/specifications/x3d ←
-3.0.dtd">
<X3D>
  <Scene>
    <Transform>
      <Shape>
        <Appearance>
          <Material emissiveColor='0 0 1' />
        </Appearance>
        <IndexedFaceSet coordIndex='0 1 2 3 -1 4 5 6 7 -1 8 9 10 11 -1 12 13 14 15 -1 16 17 ←
18 19 -1 20 21 22 23'>
          <Coordinate point='0 0 0 0 0 1 0 1 1 0 1 0 0 0 0 0 1 0 1 1 0 1 0 0 0 0 0 1 0 0 ←
1 0 1 0 0 1 1 1 0 1 1 1 1 0 1 1 0 0 0 1 0 0 1 1 1 1 1 1 0 0 0 1 1 0 1 1 1 ←
1 0 1 1' />
        </IndexedFaceSet>
      </Shape>
    </Transform>
  </Scene>
</X3D>

```

PostGIS buildings

Copy and paste the output of this query to [x3d scene viewer](#) and click Show

```

SELECT string_agg('<Shape
>' || ST_AsX3D(ST_Extrude(geom, 0,0, i*0.5)) ||
  '<Appearance>
    <Material diffuseColor="' || (0.01*i)::text || ' 0.8 0.2" specularColor="' || ←
    (0.05*i)::text || ' 0 0.5"/>
  </Appearance>
</Shape
>', '')
FROM ST_Subdivide(ST_Letters('PostGIS'),20) WITH ORDINALITY AS f(geom,i);

```




Buildings formed by subdividing PostGIS and extrusion

实验: 实验实验 6 实验 3 实验实验实验实验

```
SELECT ST_AsX3D(
  ST_Translate(
    ST_Force_3d(
      ST_Buffer(ST_Point(10,10),5, 'quad_segs=2')), 0,0,
      3)
    ,6) As x3dfrag;

x3dfrag
-----
<IndexedFaceSet coordIndex="0 1 2 3 4 5 6 7">
  <Coordinate point="15 10 3 13.535534 6.464466 3 10 5 3 6.464466 6.464466 3 5 10 3 6.464466 13.535534 3 10 15 3 13.535534 13.535534 3 " />
</IndexedFaceSet>
```

实验: **TIN**

```
SELECT ST_AsX3D(ST_GeomFromEWKT('TIN (((
    0 0 0,
    0 0 1,
    0 1 0,
    0 0 0
  )), ((
    0 0 0,
    0 1 0,
    1 1 0,
    0 0 0
  ))
)')) As x3dfrag;

x3dfrag
-----
<IndexedTriangleSet index='0 1 2 3 4 5'
><Coordinate point='0 0 0 0 1 0 1 0 0 0 0 0 1 0 1 1 0' /></IndexedTriangleSet>
```

实验: 实验实验实验实验 (实验实验实验实验实验)

```
SELECT ST_AsX3D(
  ST_GeomFromEWKT('MULTILINESTRING((20 0 10,16 -12 10,0 -16 10,-12 -12 10,-20 0 10,-12 16 10,0 24 10,16 16 10,20 0 10),
  (12 0 10,8 8 10,0 12 10,-8 8 10,-8 0 10,-8 -4 10,0 -8 10,8 -4 10,12 0 10)))')
) As x3dfrag;
```

```

x3dfrag
-----
<IndexedLineSet coordIndex='0 1 2 3 4 5 6 7 0 -1 8 9 10 11 12 13 14 15 8'>
  <Coordinate point='20 0 10 16 -12 10 0 -16 10 -12 -12 10 -20 0 10 -12 16 10 0 24 10 16 16 10 12 0 10 8 8 10 0 12 10 -8 8 10 -8 0 10 -8 -4 10 0 -8 10 8 -4 10 ' />
</IndexedLineSet>

```

7.9.3.14 ST_GeoHash

ST_GeoHash — 将 GeoHash 编码为文本。

Synopsis

text **ST_GeoHash**(geometry geom, integer maxchars=full_precision_of_point);

描述

Computes a **GeoHash** representation of a geometry. A GeoHash encodes a geographic Point into a text form that is sortable and searchable based on prefixing. A shorter GeoHash is a less precise representation of a point. It can be thought of as a box that contains the point.

Non-point geometry values with non-zero extent can also be mapped to GeoHash codes. The precision of the code depends on the geographic extent of the geometry.

If maxchars is not specified, the returned GeoHash code is for the smallest cell containing the input geometry. Points return a GeoHash with 20 characters of precision (about enough to hold the full double precision of the input). Other geometric types may return a GeoHash with less precision, depending on the extent of the geometry. Larger geometries are represented with less precision, smaller ones with more precision. The box determined by the GeoHash code always contains the input feature.

If maxchars is specified the returned GeoHash code has at most that many characters. It maps to a (possibly) lower precision representation of the input geometry. For non-points, the starting point of the calculation is the center of the bounding box of the geometry.

1.4.0 添加。



Note

ST_GeoHash requires input geometry to be in geographic (lon/lat) coordinates.



This method supports Circular Strings and Curves.

示例

```

SELECT ST_GeoHash( ST_Point(-126,48) );

 st_geohash
-----
c0w3hf1s70w3hf1s70w3

SELECT ST_GeoHash( ST_Point(-126,48), 5);

```

```

st_geohash
-----
c0w3h

-- This line contains the point, so the GeoHash is a prefix of the point code
SELECT ST_GeoHash('LINESTRING(-126 48, -126.1 48.1)::geometry');

st_geohash
-----
c0w3

```



ST_GeomFromGeoHash, ST_PointFromGeoHash, ST_Box2dFromGeoHash

7.10 ☒☒☒ (operator)

7.10.1 Bounding Box Operators

7.10.1.1 &&

&& — A 2D array B 2D array TRUE.

Synopsis

```
boolean &&( geometry A , geometry B );
boolean &&( geography A , geography B );
```



&& $\frac{1}{2}A$ 2D $\frac{1}{2}B$ 2D $\frac{1}{2}C$ TRUE.



Note

(operand)

2.0.0 (polyhedral surface)

1.5.0 ☒☒☒☒☒☒☒☒☒☒☒☒.



This method supports Circular Strings and Curves.



This function supports Polyhedral surfaces.

例

```
SELECT tbl1.column1, tbl2.column1, tbl1.column2 && tbl2.column2 AS overlaps
FROM ( VALUES
      (1, 'LINESTRING(0 0, 3 3)::geometry),
      (2, 'LINESTRING(0 1, 0 5)::geometry)) AS tbl1,
( VALUES
      (3, 'LINESTRING(1 2, 4 6)::geometry)) AS tbl2;

 column1 | column1 | overlaps
-----+-----+-----
          1 |          3 | t
          2 |          3 | f
(2 rows)
```

例

ST_Intersects, **ST_Extent**, **|&>**, **&>**, **&<|**, **&<**, **~**, **@**

7.10.1.2 &&(geometry,box2df)

&&(geometry,box2df) — Returns TRUE if a geometry's (cached) 2D bounding box intersects a 2D float precision bounding box (BOX2DF).

Synopsis

boolean **&&**(geometry A , box2df B);

例

The **&&** operator returns TRUE if the cached 2D bounding box of geometry A intersects the 2D bounding box B, using float precision. This means that if B is a (double precision) box2d, it will be internally converted to a float precision 2D bounding box (BOX2DF)



Note

This operand is intended to be used internally by BRIN indexes, more than by users.

Availability: 2.3.0 support for Block Range INdexes (BRIN) was introduced. Requires PostgreSQL 9.5+.



This method supports Circular Strings and Curves.



This function supports Polyhedral surfaces.

例

```
SELECT ST_Point(1,1) && ST_MakeBox2D(ST_Point(0,0), ST_Point(2,2)) AS overlaps;

 overlaps
-----
t
(1 row)
```

国国

&&(box2df,geometry), &&(box2df,box2df), ~(geometry,box2df), ~(box2df,geometry), ~(box2df,box2df), @ (geometry,box2df), @ (box2df,geometry), @ (box2df,box2df)

7.10.1.3 &&(box2df,geometry)

&&(box2df,geometry) — Returns TRUE if a 2D float precision bounding box (BOX2DF) intersects a geometry's (cached) 2D bounding box.

Synopsis

boolean **&&**(box2df A , geometry B);

国国

The **&&** operator returns TRUE if the 2D bounding box A intersects the cached 2D bounding box of geometry B, using float precision. This means that if A is a (double precision) box2d, it will be internally converted to a float precision 2D bounding box (BOX2DF)



Note

This operand is intended to be used internally by BRIN indexes, more than by users.

Availability: 2.3.0 support for Block Range INdexes (BRIN) was introduced. Requires PostgreSQL 9.5+.



This method supports Circular Strings and Curves.



This function supports Polyhedral surfaces.

国国

```
SELECT ST_MakeBox2D(ST_Point(0,0), ST_Point(2,2)) && ST_Point(1,1) AS overlaps;
```

```
overlaps
-----
t
(1 row)
```

国国

&&(geometry,box2df), &&(box2df,box2df), ~(geometry,box2df), ~(box2df,geometry), ~(box2df,box2df), @ (geometry,box2df), @ (box2df,geometry), @ (box2df,box2df)

7.10.1.4 &&(box2df,box2df)

&&(box2df,box2df) — Returns TRUE if two 2D float precision bounding boxes (BOX2DF) intersect each other.

Synopsis

boolean **&&**(box2df A , box2df B);

⚠️

The **&&** operator returns TRUE if two 2D bounding boxes A and B intersect each other, using float precision. This means that if A (or B) is a (double precision) box2d, it will be internally converted to a float precision 2D bounding box (BOX2DF)



Note

This operator is intended to be used internally by BRIN indexes, more than by users.

Availability: 2.3.0 support for Block Range INdices (BRIN) was introduced. Requires PostgreSQL 9.5+.



This method supports Circular Strings and Curves.



This function supports Polyhedral surfaces.

⚠️

```
SELECT ST_MakeBox2D(ST_Point(0,0), ST_Point(2,2)) && ST_MakeBox2D(ST_Point(1,1), ST_Point(3,3)) AS overlaps;
```

```
overlaps
-----
t
(1 row)
```

⚠️

&&(geometry,box2df), **&&**(box2df,geometry), **~**(geometry,box2df), **~**(box2df,geometry), **~**(box2df,box2df),
@(geometry,box2df), **@**(box2df,geometry), **@**(box2df,box2df)

7.10.1.5 &&&

&&& — A n 维多面体 B n 维多面体 **TRUE** 当且仅当 A 与 B 相交。

Synopsis

boolean **&&&**(geometry A , geometry B);

返回

返回 A 与 B 是否重叠 TRUE 或 FALSE。



Note
操作数 (operand) 必须是 3D 几何体。

2.0.0 版本支持。

- ✓ This method supports Circular Strings and Curves.
- ✓ This function supports Polyhedral surfaces.
- ✓ This function supports Triangles and Triangulated Irregular Network Surfaces (TIN).
- ✓ This function supports 3d and will not drop the z-index.

示例: 3D 重叠

```
SELECT tbl1.column1, tbl2.column1, tbl1.column2 && tbl2.column2 AS overlaps_3d,
      tbl1.column2 && tbl2.column2 AS overlaps_2d
FROM ( VALUES
      (1, 'LINESTRING Z(0 0 1, 3 3 2)::geometry),
      (2, 'LINESTRING Z(1 2 0, 0 5 -1)::geometry)) AS tbl1,
( VALUES
      (3, 'LINESTRING Z(1 2 1, 4 6 1)::geometry)) AS tbl2;
```

column1	column1	overlaps_3d	overlaps_2d
1	3	t	t
2	3	f	t

示例: 3DM 重叠

```
SELECT tbl1.column1, tbl2.column1, tbl1.column2 && tbl2.column2 AS overlaps_3zm,
      tbl1.column2 && tbl2.column2 AS overlaps_2d
FROM ( VALUES
      (1, 'LINESTRING M(0 0 1, 3 3 2)::geometry),
      (2, 'LINESTRING M(1 2 0, 0 5 -1)::geometry)) AS tbl1,
( VALUES
      (3, 'LINESTRING M(1 2 1, 4 6 1)::geometry)) AS tbl2;
```

column1	column1	overlaps_3zm	overlaps_2d
1	3	t	t
2	3	f	t

返回

&&

7.10.1.6 &&&(geometry,gidx)

&&&(geometry,gidx) — Returns TRUE if a geometry's (cached) n-D bounding box intersects a n-D float precision bounding box (GIDX).

Synopsis

boolean **&&&**(geometry A , gidx B);

国国

The **&&&** operator returns TRUE if the cached n-D bounding box of geometry A intersects the n-D bounding box B, using float precision. This means that if B is a (double precision) box3d, it will be internally converted to a float precision 3D bounding box (GIDX)



Note

This operator is intended to be used internally by BRIN indexes, more than by users.

Availability: 2.3.0 support for Block Range INdexes (BRIN) was introduced. Requires PostgreSQL 9.5+.

-  This method supports Circular Strings and Curves.
-  This function supports Polyhedral surfaces.
-  This function supports Triangles and Triangulated Irregular Network Surfaces (TIN).
-  This function supports 3d and will not drop the z-index.

国国

```
SELECT ST_MakePoint(1,1,1) &&& ST_3DMakeBox(ST_MakePoint(0,0,0), ST_MakePoint(2,2,2)) AS overlaps;
overlaps
-----
t
(1 row)
```

国国

&&&(gidx,geometry), &&&(gidx,gidx)

7.10.1.7 &&&(gidx,geometry)

&&&(gidx,geometry) — Returns TRUE if a n-D float precision bounding box (GIDX) intersects a geometry's (cached) n-D bounding box.

Synopsis

boolean **&&&**(gidx A , geometry B);

Notes

The **&&&** operator returns TRUE if the n-D bounding box A intersects the cached n-D bounding box of geometry B, using float precision. This means that if A is a (double precision) box3d, it will be internally converted to a float precision 3D bounding box (GIDX)



Note

This operator is intended to be used internally by BRIN indexes, more than by users.

Availability: 2.3.0 support for Block Range INdexes (BRIN) was introduced. Requires PostgreSQL 9.5+.



This method supports Circular Strings and Curves.



This function supports Polyhedral surfaces.



This function supports Triangles and Triangulated Irregular Network Surfaces (TIN).



This function supports 3d and will not drop the z-index.

Notes

```
SELECT ST_3DMakeBox(ST_MakePoint(0,0,0), ST_MakePoint(2,2,2)) &&& ST_MakePoint(1,1,1) AS overlaps;
overlaps
-----
t
(1 row)
```

Notes

&&&(geometry,gidx), &&&(gidx,gidx)

7.10.1.8 &&&(gidx,gidx)

&&&(gidx,gidx) — Returns TRUE if two n-D float precision bounding boxes (GIDX) intersect each other.

Synopsis

boolean **&&&**(gidx A , gidx B);

The `&&` operator returns `TRUE` if two n-D bounding boxes A and B intersect each other, using float precision. This means that if A (or B) is a (double precision) `box3d`, it will be internally converted to a float precision 3D bounding box (GIDX)



Note

This operator is intended to be used internally by BRIN indexes, more than by users.

Availability: 2.3.0 support for Block Range INdexes (BRIN) was introduced. Requires PostgreSQL 9.5+.

- ✔ This method supports Circular Strings and Curves.
- ✔ This function supports Polyhedral surfaces.
- ✔ This function supports Triangles and Triangulated Irregular Network Surfaces (TIN).
- ✔ This function supports 3d and will not drop the z-index.


```
SELECT ST_3DMakeBox(ST_MakePoint(0,0,0), ST_MakePoint(2,2,2)) && ST_3DMakeBox(ST_MakePoint(1,1,1), ST_MakePoint(3,3,3)) AS overlaps;

overlaps
-----
t
(1 row)
```



&&&(geometry,gidx), &&&(gidx,geometry)

7.10.1.9 <

`&< - A B TRUE`

Synopsis

```
boolean &<( geometry A , geometry B );
```



&< `isA` A `isB` B `isNotA` B `isNotB` B `isTrue` TRUE.



Note

XXXXXXXX (operand) XXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXX.

例

```
SELECT tbl1.column1, tbl2.column1, tbl1.column2 &< tbl2.column2 AS overleft
FROM
  ( VALUES
    (1, 'LINESTRING(1 2, 4 6)::geometry)) AS tbl1,
  ( VALUES
    (2, 'LINESTRING(0 0, 3 3)::geometry),
    (3, 'LINESTRING(0 1, 0 5)::geometry),
    (4, 'LINESTRING(6 0, 6 1)::geometry)) AS tbl2;

column1 | column1 | overleft
-----+-----+-----
          1 |          2 | f
          1 |          3 | f
          1 |          4 | t
(3 rows)
```

例

&&, |&>, &>, &<|

7.10.1.10 &<|

&<| — A 与 B 不相交返回 TRUE。

Synopsis

boolean **&<|**(geometry A , geometry B);

例

&<| 返回 A 与 B 不相交，即 A 与 B 没有公共点，返回 TRUE。

- ✔ This method supports Circular Strings and Curves.
- ✔ This function supports Polyhedral surfaces.



Note

操作数 (operand) 必须是几何类型。

例

```
SELECT tbl1.column1, tbl2.column1, tbl1.column2 &<| tbl2.column2 AS overbelow
FROM
  ( VALUES
    (1, 'LINESTRING(6 0, 6 4)::geometry)) AS tbl1,
  ( VALUES
    (2, 'LINESTRING(0 0, 3 3)::geometry),
    (3, 'LINESTRING(0 1, 0 5)::geometry),
```

```
(4, 'LINESTRING(1 2, 4 6)::geometry)) AS tbl2;
```

column1	column1	overbelow
1	2	f
1	3	t
1	4	t

(3 rows)

例

&&, |&>, &>, &<

7.10.1.11 &>

&> — A 几何体 B 几何体 是否相交 TRUE 或 FALSE。

Synopsis

boolean **&>**(geometry A , geometry B);

例

&> 几何体 A 几何体 B 是否相交, 相交则返回 TRUE, 不相交则返回 FALSE。



Note

几何体 (operand) 必须是有效的几何体。

例

```
SELECT tbl1.column1, tbl2.column1, tbl1.column2 &
> tbl2.column2 AS overright
FROM
  ( VALUES
    (1, 'LINESTRING(1 2, 4 6)::geometry)) AS tbl1,
  ( VALUES
    (2, 'LINESTRING(0 0, 3 3)::geometry),
    (3, 'LINESTRING(0 1, 0 5)::geometry),
    (4, 'LINESTRING(6 0, 6 1)::geometry)) AS tbl2;
```

column1	column1	overright
1	2	t
1	3	t
1	4	f

(3 rows)

例

&&, |&>, &<|, &<

7.10.1.12 <<

<< — A 与 B 相交是否返回 TRUE。

Synopsis

```
boolean <<( geometry A , geometry B );
```

注意

<< 返回 TRUE 当 A 与 B 相交是否返回 TRUE。

**Note**

注意 (operand) 必须是 geometry 类型。

注意

```
SELECT tbl1.column1, tbl2.column1, tbl1.column2 << tbl2.column2 AS left
FROM
  ( VALUES
    (1, 'LINESTRING (1 2, 1 5)::geometry)) AS tbl1,
  ( VALUES
    (2, 'LINESTRING (0 0, 4 3)::geometry),
    (3, 'LINESTRING (6 0, 6 5)::geometry),
    (4, 'LINESTRING (2 2, 5 6)::geometry)) AS tbl2;
```

column1	column1	left
1	2	f
1	3	t
1	4	t

(3 rows)

注意

>>, |>>, <<|

7.10.1.13 <<|

<<| — A 与 B 相交是否返回 TRUE。

Synopsis

```
boolean <<|( geometry A , geometry B );
```

11

```
<<|  A B  TRUE
```



Note

XXXXXXXXXX (operand) XXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXX.



```
SELECT tbl1.column1, tbl2.column1, tbl1.column2 <<| tbl2.column2 AS below
FROM
  ( VALUES
    (1, 'LINESTRING (0 0, 4 3) '::geometry)) AS tbl1,
  ( VALUES
    (2, 'LINESTRING (1 4, 1 7) '::geometry),
    (3, 'LINESTRING (6 1, 6 5) '::geometry),
    (4, 'LINESTRING (2 3, 5 6) '::geometry)) AS tbl2;
```

```

column1 | column1 | below
-----+-----+-----
      1 |      2 | t
      1 |      3 | f
      1 |      4 | f
(3 rows)

```

11

<<, >>, |>>

7.10.1.14 =

— Returns TRUE if the coordinates and coordinate order geometry/geography A are the same as the coordinates and coordinate order of geometry/geography B.

Synopsis

```
boolean =( geometry A , geometry B );
boolean =( geography A , geography B );
```

11

The = operator returns TRUE if the coordinates and coordinate order geometry/geography A are the same as the coordinates and coordinate order of geometry/geography B. PostgreSQL uses the =, <, and > operators defined for geometries to perform internal orderings and comparison of geometries (ie. in a GROUP BY or ORDER BY clause).



Note

Only geometry/geography that are exactly equal in all respects, with the same coordinates, in the same order, are considered equal by this operator. For "spatial equality", that ignores things like coordinate order, and can detect features that cover the same spatial area with different representations, use **ST_OrderingEquals** or **ST_Equals**

**Caution**

This operand will NOT make use of any indexes that may be available on the geometries. For an index assisted exact equality test, combine = with &&.

Changed: 2.4.0, in prior versions this was bounding box equality not a geometric equality. If you need bounding box equality, use `~ =` instead.



This method supports Circular Strings and Curves.



This function supports Polyhedral surfaces.

例

```
SELECT 'LINESTRING(0 0, 0 1, 1 0)::geometry = 'LINESTRING(1 1, 0 0)::geometry;
?column?
```

```
-----
f
(1 row)
```

```
SELECT ST_AsText(column1)
FROM ( VALUES
      ('LINESTRING(0 0, 1 1)::geometry),
      ('LINESTRING(1 1, 0 0)::geometry)) AS foo;
      st_astext
```

```
-----
LINESTRING(0 0,1 1)
LINESTRING(1 1,0 0)
(2 rows)
```

-- Note: the GROUP BY uses the "=" to compare for geometry equivalency.

```
SELECT ST_AsText(column1)
FROM ( VALUES
      ('LINESTRING(0 0, 1 1)::geometry),
      ('LINESTRING(1 1, 0 0)::geometry)) AS foo
GROUP BY column1;
      st_astext
```

```
-----
LINESTRING(0 0,1 1)
LINESTRING(1 1,0 0)
(2 rows)
```

-- In versions prior to 2.0, this used to return true --

```
SELECT ST_GeomFromText('POINT(1707296.37 4820536.77)') =
      ST_GeomFromText('POINT(1707296.27 4820536.87)') As pt_intersect;
```

```
--pt_intersect --
f
```

例

`ST_Equals`, `ST_OrderingEquals`, `~ =`

7.10.1.15 >>

>> — A 与 B 不相交是否返回 TRUE。

Synopsis

```
boolean >>( geometry A , geometry B );
```

注意

>> 当 A 与 B 不相交时返回 TRUE。

**Note**

操作数 (operand) 必须是几何类型。

示例

```
SELECT tbl1.column1, tbl2.column1, tbl1.column2
>
> tbl2.column2 AS right
FROM
  ( VALUES
    (1, 'LINESTRING (2 3, 5 6)::geometry)) AS tbl1,
  ( VALUES
    (2, 'LINESTRING (1 4, 1 7)::geometry),
    (3, 'LINESTRING (6 1, 6 5)::geometry),
    (4, 'LINESTRING (0 0, 4 3)::geometry)) AS tbl2;
```

column1	column1	right
1	2	t
1	3	f
1	4	f

(3 rows)

注意

<<, |>>, <<|

7.10.1.16 @

@ — B 是否包含 A 是否返回 TRUE。

Synopsis

```
boolean @( geometry A , geometry B );
```


@ B A TRUE.



Note

(operand) .



```
SELECT tbl1.column1, tbl2.column1, tbl1.column2 @ tbl2.column2 AS contained
FROM
```

```
( VALUES
  (1, 'LINESTRING (1 1, 3 3)::geometry)) AS tbl1,
( VALUES
  (2, 'LINESTRING (0 0, 4 4)::geometry),
  (3, 'LINESTRING (2 2, 4 4)::geometry),
  (4, 'LINESTRING (1 1, 3 3)::geometry)) AS tbl2;
```

```

column1 | column1 | contained
-----+-----+-----
      1 |      2 | t
      1 |      3 | f
      1 |      4 | t
(3 rows)

```



~, &&

7.10.1.17 `@(geometry,box2df)`

@(geometry,box2df) — Returns TRUE if a geometry's 2D bounding box is contained into a 2D float precision bounding box (BOX2DF).

Synopsis

```
boolean @( geometry A , box2df B );
```



The @ operator returns TRUE if the A geometry's 2D bounding box is contained the 2D bounding box B, using float precision. This means that if B is a (double precision) box2d, it will be internally converted to a float precision 2D bounding box (BOX2DF)



Note

This operand is intended to be used internally by BRIN indexes, more than by users.

Availability: 2.3.0 support for Block Range INdexes (BRIN) was introduced. Requires PostgreSQL 9.5+.



This method supports Circular Strings and Curves.



This function supports Polyhedral surfaces.

国国

```
SELECT ST_Buffer(ST_GeomFromText('POINT(2 2)'), 1) @ ST_MakeBox2D(ST_Point(0,0), ST_Point(5,5)) AS is_contained;
```

```
is_contained
-----
t
(1 row)
```

国国

&&(geometry,box2df), &&(box2df,geometry), &&(box2df,box2df), ~(geometry,box2df), ~(box2df,geometry), ~(box2df,box2df), @(box2df,geometry), @(box2df,box2df)

7.10.1.18 @(box2df,geometry)

@(box2df,geometry) — Returns TRUE if a 2D float precision bounding box (BOX2DF) is contained into a geometry's 2D bounding box.

Synopsis

boolean @(box2df A , geometry B);

国国

The @ operator returns TRUE if the 2D bounding box A is contained into the B geometry's 2D bounding box, using float precision. This means that if B is a (double precision) box2d, it will be internally converted to a float precision 2D bounding box (BOX2DF)



Note

This operand is intended to be used internally by BRIN indexes, more than by users.

Availability: 2.3.0 support for Block Range INdexes (BRIN) was introduced. Requires PostgreSQL 9.5+.



This method supports Circular Strings and Curves.



This function supports Polyhedral surfaces.

❏

```
SELECT ST_MakeBox2D(ST_Point(2,2), ST_Point(3,3)) @ ST_Buffer(ST_GeomFromText('POINT(1 1)') ↵
, 10) AS is_contained;
```

```
is_contained
-----
t
(1 row)
```

❏

**`&&(geometry,box2df), &&(box2df,geometry), &&(box2df,box2df), ~(geometry,box2df), ~(box2df,geometry),
~(box2df,box2df), @(geometry,box2df), @(box2df,box2df)`**

7.10.1.19 `@(box2df,box2df)`

`@(box2df,box2df)` — Returns TRUE if a 2D float precision bounding box (BOX2DF) is contained into another 2D float precision bounding box.

Synopsis

boolean `@( box2df A , box2df B );`

❏

The `@` operator returns TRUE if the 2D bounding box A is contained into the 2D bounding box B, using float precision. This means that if A (or B) is a (double precision) box2d, it will be internally converted to a float precision 2D bounding box (BOX2DF)



Note

This operand is intended to be used internally by BRIN indexes, more than by users.

Availability: 2.3.0 support for Block Range INdexes (BRIN) was introduced. Requires PostgreSQL 9.5+.



This method supports Circular Strings and Curves.



This function supports Polyhedral surfaces.

❏

```
SELECT ST_MakeBox2D(ST_Point(2,2), ST_Point(3,3)) @ ST_MakeBox2D(ST_Point(0,0), ST_Point ↵
(5,5)) AS is_contained;
```

```
is_contained
-----
t
(1 row)
```

返回

`&&(geometry,box2df), &&(box2df,geometry), &&(box2df,box2df), ~(geometry,box2df), ~(box2df,geometry), ~(box2df,box2df), @(geometry,box2df), @(box2df,geometry)`

7.10.1.20 |&>

`|&>` — A 与 B 的交集是否非空。如果非空，返回 TRUE。

Synopsis

boolean `|&>( geometry A , geometry B );`

返回

`|&>` 返回 A 与 B 的交集是否非空。如果非空，返回 TRUE。



Note

操作数 (operand) 必须是几何类型。

返回

```
SELECT tbl1.column1, tbl2.column1, tbl1.column2 |&
> tbl2.column2 AS overabove
FROM
  ( VALUES
    (1, 'LINESTRING(6 0, 6 4)::geometry)) AS tbl1,
  ( VALUES
    (2, 'LINESTRING(0 0, 3 3)::geometry),
    (3, 'LINESTRING(0 1, 0 5)::geometry),
    (4, 'LINESTRING(1 2, 4 6)::geometry)) AS tbl2;
```

column1	column1	overabove
1	2	t
1	3	f
1	4	f

(3 rows)

返回

`&&, &>, &<|, &<`

7.10.1.21 |>>

`|>>` — A 是否完全包含 B。如果是，返回 TRUE。

Synopsis

boolean |>>(geometry A , geometry B);

描述

The |>> operator returns TRUE if the bounding box of geometry A is strictly above the bounding box of geometry B.



Note

geometry (operand) 必须是二维几何类型。

示例

```
SELECT tbl1.column1, tbl2.column1, tbl1.column2 |>> tbl2.column2 AS above
FROM
  ( VALUES
    (1, 'LINESTRING (1 4, 1 7)::geometry)) AS tbl1,
  ( VALUES
    (2, 'LINESTRING (0 0, 4 2)::geometry),
    (3, 'LINESTRING (6 1, 6 5)::geometry),
    (4, 'LINESTRING (2 3, 5 6)::geometry)) AS tbl2;
```

column1	column1	above
1	2	t
1	3	f
1	4	f

(3 rows)

描述

<<, >>, <<|

7.10.1.22 ~

~ — A 与 B 不相交返回 TRUE。

Synopsis

boolean ~(geometry A , geometry B);

描述

~ 当 A 与 B 不相交时返回 TRUE。



Note

geometry (operand) 必须是二维几何类型。

SQL

```
SELECT tbl1.column1, tbl2.column1, tbl1.column2 ~ tbl2.column2 AS contains
FROM
  ( VALUES
    (1, 'LINESTRING (0 0, 3 3)::geometry)) AS tbl1,
  ( VALUES
    (2, 'LINESTRING (0 0, 4 4)::geometry),
    (3, 'LINESTRING (1 1, 2 2)::geometry),
    (4, 'LINESTRING (0 0, 3 3)::geometry)) AS tbl2;
```

column1	column1	contains
1	2	f
1	3	t
1	4	t

(3 rows)

SQL

@, &&

7.10.1.23 ~(geometry,box2df)

~(geometry,box2df) — Returns TRUE if a geometry’s 2D bonding box contains a 2D float precision bounding box (GIDX).

Synopsis

boolean ~(geometry A , box2df B);

SQL

The ~ operator returns TRUE if the 2D bounding box of a geometry A contains the 2D bounding box B, using float precision. This means that if B is a (double precision) box2d, it will be internally converted to a float precision 2D bounding box (BOX2DF)



Note
This operand is intended to be used internally by BRIN indexes, more than by users.

Availability: 2.3.0 support for Block Range INdexes (BRIN) was introduced. Requires PostgreSQL 9.5+.

- ✔ This method supports Circular Strings and Curves.
- ✔ This function supports Polyhedral surfaces.

❏

```
SELECT ST_Buffer(ST_GeomFromText('POINT(1 1)'), 10) ~ ST_MakeBox2D(ST_Point(0,0), ST_Point(2,2)) AS contains;

contains
-----
t
(1 row)
```

❏

&&(geometry,box2df), &&(box2df,geometry), &&(box2df,box2df), ~(box2df,geometry), ~(box2df,box2df), @&(geometry,box2df), @&(box2df,geometry), @&(box2df,box2df)

7.10.1.24 ~(box2df,geometry)

~(box2df,geometry) — Returns TRUE if a 2D float precision bounding box (BOX2DF) contains a geometry's 2D bonding box.

Synopsis

boolean ~(box2df A , geometry B);

❏

The ~ operator returns TRUE if the 2D bounding box A contains the B geometry's bounding box, using float precision. This means that if A is a (double precision) box2d, it will be internally converted to a float precision 2D bounding box (BOX2DF)



Note

This operand is intended to be used internally by BRIN indexes, more than by users.

Availability: 2.3.0 support for Block Range INdexes (BRIN) was introduced. Requires PostgreSQL 9.5+.



This method supports Circular Strings and Curves.



This function supports Polyhedral surfaces.

❏

```
SELECT ST_MakeBox2D(ST_Point(0,0), ST_Point(5,5)) ~ ST_Buffer(ST_GeomFromText('POINT(2 2)'), 1) AS contains;

contains
-----
t
(1 row)
```


Synopsis

boolean `~=`(geometry A , geometry B);

描述

`~=` 返回 A 和 B 的边界框是否相等。如果相等，则返回 TRUE。



Note

该运算符 (operand) 仅支持多面体表面。

1.5.0 版本引入。



This function supports Polyhedral surfaces.



Warning

This operator has changed behavior in PostGIS 1.5 from testing for actual geometric equality to only checking for bounding box equality. To complicate things it also depends on if you have done a hard or soft upgrade which behavior your database has. To find out which behavior your database has you can run the query below. To check for true equality use [ST_OrderingEquals](#) or [ST_Equals](#).

描述

```
select 'LINESTRING(0 0, 1 1)::geometry' ~= 'LINESTRING(0 1, 1 0)::geometry' as equality;
equality    |
-----+
t          |
```

描述

[ST_Equals](#), [ST_OrderingEquals](#), [=](#)

7.10.2 距离 (operator)

7.10.2.1 <->

`<->` — A 和 B 之间的最短距离。

Synopsis

double precision `<->`(geometry A , geometry B);
double precision `<->`(geography A , geography B);

SQL

<-> 使用 2 个最近邻居。 "ORDER BY" 子句使用索引辅助 (index-assisted) 最近邻居 (nearest neighbor) 查询。 PostgreSQL 9.5 支持使用距离球 (distance sphere) 的 KNN 查询。



Note

操作符 (operand) 使用 2 个 GiST 索引。 ORDER BY 子句使用索引辅助 (index-assisted) 最近邻居 (nearest neighbor) 查询。



Note

使用 a.geom 的 SRID=3005;POINT(1011102 450541)::geometry 格式, (CTE(common table expression) 查询) 使用距离球 (distance sphere) 的 KNN 查询。

OpenGeo workshop: Nearest-Neighbour Searching 文档。

2.2.0 使用 -- PostgreSQL 9.5 支持使用距离球 (distance sphere) 的 KNN("K nearest neighbor") 查询。 KNN 查询使用索引辅助 (index-assisted) 最近邻居 (nearest neighbor) 查询。 PostgreSQL 9.4 支持使用距离球 (distance sphere) 的 KNN 查询。

2.2.0 使用 -- PostgreSQL 9.5 支持使用混合语法 (Hybrid syntax) 的 KNN 查询。 PostgreSQL 9.5 支持使用混合语法 (Hybrid syntax) 的 KNN 查询。 PostgreSQL 9.5 支持使用混合语法 (Hybrid syntax) 的 KNN 查询。

2.0.0 使用 KNN 查询。 KNN 查询使用索引辅助 (index-assisted) 最近邻居 (nearest neighbor) 查询。 PostgreSQL 9.1 支持使用距离球 (distance sphere) 的 KNN 查询。

SQL

```
SELECT ST_Distance(geom, 'SRID=3005;POINT(1011102 450541)::geometry') as d,edabbr, vaabbr
FROM va2005
ORDER BY d limit 10;
```

d	edabbr	vaabbr
0	ALQ	128
5541.57712511724	ALQ	129A
5579.67450712005	ALQ	001
6083.4207708641	ALQ	131
7691.2205404848	ALQ	003
7900.75451037313	ALQ	122
8694.20710669982	ALQ	129B
9564.24289057111	ALQ	130
12089.665931705	ALQ	127
18472.5531479404	ALQ	002

(10 rows)

KNN 查询:

```
SELECT st_distance(geom, 'SRID=3005;POINT(1011102 450541)::geometry') as d,edabbr, vaabbr
FROM va2005
ORDER BY geom <-> 'SRID=3005;POINT(1011102 450541)::geometry' limit 10;
```

d	edabbr	vaabbr
0	ALQ	128
5541.57712511724	ALQ	129A
5579.67450712005	ALQ	001
6083.4207708641	ALQ	131
7691.2205404848	ALQ	003
7900.75451037313	ALQ	122
8694.20710669982	ALQ	129B
9564.24289057111	ALQ	130
12089.665931705	ALQ	127
18472.5531479404	ALQ	002

(10 rows)

“EXPLAIN ANALYZE” 用于分析查询计划。PostgreSQL 9.5 引入了 KNN CTE(common table expression) 函数，用于返回最近的 K 个邻居。

```
WITH index_query AS (  
  SELECT ST_Distance(geom, 'SRID=3005;POINT(1011102 450541)::geometry) as d,edabbr, vaabbr  
  FROM va2005  
  ORDER BY geom <-> 'SRID=3005;POINT(1011102 450541)::geometry' LIMIT 100)  
SELECT *  
  FROM index_query  
 ORDER BY d limit 10;
```

d	edabbr	vaabbr
0	ALQ	128
5541.57712511724	ALQ	129A
5579.67450712005	ALQ	001
6083.4207708641	ALQ	131
7691.2205404848	ALQ	003
7900.75451037313	ALQ	122
8694.20710669982	ALQ	129B
9564.24289057111	ALQ	130
12089.665931705	ALQ	127
18472.5531479404	ALQ	002

(10 rows)

ST_DWithin, ST_Distance, <#>

7.10.2.2 |=|

|=| — A 与 B 的最接近点 (closest point of approach) 的轨迹 (trajectory)。

Synopsis

double precision |=|(geometry A , geometry B);

||

`|=|` 函数 (ST_IsValidTrajectory 函数) 返回 3 个最近邻的最近邻。函数 ST_DistanceCPA 返回最近邻, 函数 ST_DistanceCPA (PostgreSQL 9.5.0 引入) N 个最近邻 (nearest neighbor) 的最近邻。



Note

函数 (operand) 返回最近邻 N 个 GiST 索引。函数 ORDER BY 函数返回最近邻 N 个 GiST 索引。



Note

函数, 函数 a.geom 函数 'SRID=3005;LINESTRING(0 0 0,0 0 1)::geometry' 函数, (函数/CTE(common table expression) 函数) 函数。

2.2.0 函数。 PostgreSQL 9.5 函数 (index-supported) 函数。

||

```
-- Save a literal query trajectory in a psql variable...
\set qt 'ST_AddMeasure(ST_MakeLine(ST_MakePointM(-350,300,0),ST_MakePointM(-410,490,0)) ←
,10,20)'
-- Run the query !
SELECT track_id, dist FROM (
  SELECT track_id, ST_DistanceCPA(tr,:qt) dist
  FROM trajectories
  ORDER BY tr |=| :qt
  LIMIT 5
) foo;
track_id      dist
-----+-----
      395 | 0.576496831518066
      380 | 5.06797130410151
      390 | 7.72262293958322
      385 | 9.8004461358071
      405 | 10.9534397988433
(5 rows)
```

||

ST_DistanceCPA, ST_ClosestPointOfApproach, ST_IsValidTrajectory

7.10.2.3 <#>

<#> — A 与 B 的最近邻的最近邻。

Synopsis

double precision <#>(geometry A , geometry B);

7.10.2.4 <->

<-> — Returns the n-D distance between the A and B geometries or bounding boxes

Synopsis

double precision <->(geometry A , geometry B);

返回

<-> 返回两个几何体 A 和 B 之间的 n-D 距离。如果 A 和 B 是点，则返回两点之间的直线距离。如果 A 和 B 是线，则返回两条线之间的最短距离。如果 A 和 B 是面，则返回两个面之间的最短距离。如果 A 和 B 是体，则返回两个体之间的最短距离。



Note

如果 A 或 B 是空几何体，则返回 NULL。如果 A 和 B 都是点，则返回 GiST 索引。如果 A 和 B 都是线，则返回 ORDER BY 索引。如果 A 和 B 都是面，则返回 GiST 索引。如果 A 和 B 都是体，则返回 GiST 索引。



Note

如果 A 和 B 都是点，则返回 GiST 索引。如果 A 和 B 都是线，则返回 ORDER BY 索引。如果 A 和 B 都是面，则返回 GiST 索引。如果 A 和 B 都是体，则返回 GiST 索引。

2.2.0 版本中，PostgreSQL 9.1 版本中 KNN 索引。

返回

<->

7.11 Spatial Relationships

7.11.1 Topological Relationships

7.11.1.1 ST_3DIntersects

ST_3DIntersects — Tests if two geometries spatially intersect in 3D - only for points, linestrings, polygons, polyhedral surface (area)

Synopsis

boolean **ST_3DIntersects**(geometry geomA , geometry geomB);

国国

Overlaps, Touches, Within all imply spatial intersection. If any of the aforementioned returns true, then the geometries also spatially intersect. Disjoint implies false for spatial intersection.

**Note**

This function automatically includes a bounding box comparison that makes use of any spatial indexes that are available on the geometries.

**Note**

Because of floating robustness failures, geometries don't always intersect as you'd expect them to after geometric processing. For example the closest point on a linestring to a geometry may not lie on the linestring. For these kind of issues where a distance of a centimeter you want to just consider as intersecting, use [ST_3DDWithin](#).

Changed: 3.0.0 SFCGAL backend removed, GEOS backend supports TINs.

2.0.0 国国国国国国国国国国.



This function supports 3d and will not drop the z-index.



This function supports Polyhedral surfaces.



This function supports Triangles and Triangulated Irregular Network Surfaces (TIN).



This method implements the SQL/MM specification. SQL-MM IEC 13249-3: 5.1

国国国国

```
SELECT ST_3DIntersects(pt, line), ST_Intersects(pt, line)
FROM (SELECT 'POINT(0 0 2)::geometry As pt, 'LINESTRING (0 0 1, 0 2 3)::geometry As ↵
      line) As foo;
st_3dintersects | st_intersects
-----+-----
f               | t
(1 row)
```

TIN Examples

```
SELECT ST_3DIntersects('TIN(((0 0 0,1 0 0,0 1 0,0 0 0)))::geometry, 'POINT(.1 .1 0):: ↵
      geometry);
st_3dintersects
-----
t
```

国国

[ST_3DDWithin](#), [ST_Intersects](#)

7.11.1.2 ST_Contains

ST_Contains — Tests if every point of B lies in A, and their interiors have a point in common

Synopsis

boolean **ST_Contains**(geometry geomA, geometry geomB);

国国

Returns TRUE if geometry A contains geometry B. A contains B if and only if all points of B lie inside (i.e. in the interior or boundary of) A (or equivalently, no points of B lie in the exterior of A), and the interiors of A and B have at least one point in common.

In mathematical terms: $ST\_Contains(A, B) \Leftrightarrow (A \supset B = B) \wedge (Int(A) \supset Int(B) \neq \emptyset)$

The contains relationship is reflexive: every geometry contains itself. (In contrast, in the **ST_ContainsProperly** predicate a geometry does *not* properly contain itself.) The relationship is antisymmetric: if $ST\_Contains(A, B) = \text{true}$ and $ST\_Contains(B, A) = \text{true}$, then the two geometries must be topologically equal ($ST\_Equals(A, B) = \text{true}$).

ST_Contains is the converse of **ST_Within**. So, $ST\_Contains(A, B) = ST\_Within(B, A)$.

Note



Because the interiors must have a common point, a subtlety of the definition is that polygons and lines do *not* contain lines and points lying fully in their boundary. For further details see [Subtleties of OGC Covers, Contains, Within](#). The **ST_Covers** predicate provides a more inclusive relationship.

Note



This function automatically includes a bounding box comparison that makes use of any spatial indexes that are available on the geometries. To avoid index use, use the function `_ST_Contains`.

GEOS 国国国国国国

Enhanced: 2.3.0 Enhancement to PIP short-circuit extended to support MultiPoints with few points. Prior versions only supported point in polygon.



Important

Enhanced: 3.0.0 enabled support for GEOMETRYCOLLECTION



Important

Do not use this function with invalid geometries. You will get unexpected results.

NOTE: this is the “allowable” version that returns a boolean, not an integer.




This method implements the [OGC Simple Features Implementation Specification for SQL 1.1](#), s2.1.1.2 // s2.1.13.3 - same as `within(geometry B, geometry A)`




This method implements the SQL/MM specification. SQL-MM 3: 5.1.31

☐☐


ST_Contains returns TRUE in the following situations:



ST_Contains returns FALSE in the following situations:



Due to the interior intersection condition `ST_Contains` returns `FALSE` in the following situations (whereas `ST_Covers` returns `TRUE`):



```
-- A circle within a circle
SELECT ST_Contains(smallc, bigc) As smallcontainsbig,
       ST_Contains(bigc, smallc) As bigcontainssmall,
       ST_Contains(bigc, ST_Union(smallc, bigc)) as bigcontainsunion,
       ST_Equals(bigc, ST_Union(smallc, bigc)) as bigisunion,
       ST_Covers(bigc, ST_ExteriorRing(bigc)) As bigcoversexterior,
       ST_Contains(bigc, ST_ExteriorRing(bigc)) As bigcontainsexterior
FROM (SELECT ST_Buffer(ST_GeomFromText('POINT(1 2)'), 10) As smallc,
       ST_Buffer(ST_GeomFromText('POINT(1 2)'), 20) As bigc) As foo;

-- Result
smallcontainsbig | bigcontainssmall | bigcontainsunion | bigisunion | bigcoversexterior | bigcontainsexterior | ←
```

-----+-----+-----+-----+-----+-----

f		t		t		t		t		f

-- Example demonstrating difference between contains and contains properly

SELECT ST_GeometryType(geomA) As geomtype, ST_Contains(geomA,geomA) AS acontainsa, ↵
ST_ContainsProperly(geomA, geomA) AS acontainspropa,
ST_Contains(geomA, ST_Boundary(geomA)) As acontainsba, ST_ContainsProperly(geomA, ↵
ST_Boundary(geomA)) As acontainspropba

FROM (VALUES (ST_Buffer(ST_Point(1,1), 5,1)),
(ST_MakeLine(ST_Point(1,1), ST_Point(-1,-1))),
(ST_Point(1,1))
) As foo(geomA);

geomtype		acontainsa		acontainspropa		acontainsba		acontainspropba
-----+-----+-----+-----+-----+-----								
ST_Polygon		t		f		f		f
ST_LineString		t		f		f		f
ST_Point		t		t		f		f

☒☒

[ST_Boundary](#), [ST_ContainsProperly](#), [ST_Covers](#), [ST_CoveredBy](#), [ST_Equals](#), [ST_Within](#)

7.11.1.3 ST_ContainsProperly

ST_ContainsProperly — Tests if every point of B lies in the interior of A

Synopsis

boolean **ST_ContainsProperly**(geometry geomA, geometry geomB);

☒☒

Returns true if every point of B lies in the interior of A (or equivalently, no point of B lies in the the boundary or exterior of A).

In mathematical terms: $ST\_ContainsProperly(A, B) \Leftrightarrow Int(A) \supset B = B$

A contains B properly if the DE-9IM Intersection Matrix for the two geometries matches [T**FF*FF*]

A does not properly contain itself, but does contain itself.

A use for this predicate is computing the intersections of a set of geometries with a large polygonal geometry. Since intersection is a fairly slow operation, it can be more efficient to use containsProperly to filter out test geometries which lie fully inside the area. In these cases the intersection is known a priori to be exactly the original test geometry.



Note

This function automatically includes a bounding box comparison that makes use of any spatial indexes that are available on the geometries. To avoid index use, use the function `_ST_ContainsProperly`.



Note
The advantage of this predicate over **ST_Contains** and **ST_Intersects** is that it can be computed more efficiently, with no need to compute topology at individual points.

GEOS 1.4.0



Important
Enhanced: 3.0.0 enabled support for GEOMETRYCOLLECTION



Important
Do not use this function with invalid geometries. You will get unexpected results.

```
--a circle within a circle
SELECT ST_ContainsProperly(smallc, bigc) As smallcontainspropbig,
ST_ContainsProperly(bigc,smallc) As bigcontainspropsmall,
ST_ContainsProperly(bigc, ST_Union(smallc, bigc)) as bigcontainspropunion,
ST_Equals(bigc, ST_Union(smallc, bigc)) as bigisunion,
ST_Covers(bigc, ST_ExteriorRing(bigc)) As bigcoversexterior,
ST_ContainsProperly(bigc, ST_ExteriorRing(bigc)) As bigcontainsexterior
FROM (SELECT ST_Buffer(ST_GeomFromText('POINT(1 2)'), 10) As smallc,
ST_Buffer(ST_GeomFromText('POINT(1 2)'), 20) As bigc) As foo;
--Result
smallcontainspropbig | bigcontainspropsmall | bigcontainspropunion | bigisunion |
bigcoversexterior | bigcontainsexterior

f | t | f | t

--example demonstrating difference between contains and contains properly
SELECT ST_GeometryType(geomA) As geomtype, ST_Contains(geomA,geomA) AS acontainsa,
ST_ContainsProperly(geomA, geomA) AS acontainspropa,
ST_Contains(geomA, ST_Boundary(geomA)) As acontainsba, ST_ContainsProperly(geomA,
ST_Boundary(geomA)) As acontainspropba
FROM (VALUES ( ST_Buffer(ST_Point(1,1), 5,1) ),
( ST_MakeLine(ST_Point(1,1), ST_Point(-1,-1) ) ),
( ST_Point(1,1) )
) As foo(geomA);

geomtype | acontainsa | acontainspropa | acontainsba | acontainspropba
ST_Polygon | t | f | f | f
ST_LineString | t | f | f | f
ST_Point | t | t | f | f
```

☒☒

[ST_GeometryType](#), [ST_Boundary](#), [ST_Contains](#), [ST_Covers](#), [ST_CoveredBy](#), [ST_Equals](#), [ST_Relate](#), [ST_Within](#)

7.11.1.4 ST_CoveredBy

`ST_CoveredBy` — Tests if every point of A lies in B

Synopsis

```
boolean ST_CoveredBy(geometry geomA, geometry geomB);
boolean ST_CoveredBy(geography geogA, geography geogB);
```

☒☒

Returns `true` if every point in Geometry/Geography A lies inside (i.e. intersects the interior or boundary of) Geometry/Geography B. Equivalently, tests that no point of A lies outside (in the exterior of) B.

In mathematical terms: $ST\_CoveredBy(A, B) \Leftrightarrow A \sqsubset B = A$

`ST_CoveredBy` is the converse of [ST_Covers](#). So, $ST\_CoveredBy(A, B) = ST\_Covers(B, A)$.

Generally this function should be used instead of [ST_Within](#), since it has a simpler definition which does not have the quirk that "boundaries are not within their geometry".



Note

This function automatically includes a bounding box comparison that makes use of any spatial indexes that are available on the geometries. To avoid index use, use the function `_ST_CoveredBy`.



Important

Enhanced: 3.0.0 enabled support for GEOMETRYCOLLECTION



Important

Do not use this function with invalid geometries. You will get unexpected results.

GEOS 3.10.4

1.2.2 简体中文.

NOTE: this is the "allowable" version that returns a boolean, not an integer.

Not an OGC standard, but Oracle has it too.

例

```
--a circle coveredby a circle
SELECT ST_CoveredBy(smallc,smallc) As smallinsmall,
       ST_CoveredBy(smallc, bigc) As smallcoveredbybig,
       ST_CoveredBy(ST_ExteriorRing(bigc), bigc) As exteriorcoveredbybig,
       ST_Within(ST_ExteriorRing(bigc),bigc) As exeriorwithinbig
FROM (SELECT ST_Buffer(ST_GeomFromText('POINT(1 2)'), 10) As smallc,
       ST_Buffer(ST_GeomFromText('POINT(1 2)'), 20) As bigc) As foo;
--Result
smallinsmall | smallcoveredbybig | exteriorcoveredbybig | exeriorwithinbig
-----+-----+-----+-----
t            | t                  | t                    | f
(1 row)
```

例

[ST_Contains](#), [ST_Covers](#), [ST_ExteriorRing](#), [ST_Within](#)

7.11.1.5 ST_Covers

ST_Covers — Tests if every point of B lies in A

Synopsis

```
boolean ST_Covers(geometry geomA, geometry geomB);
boolean ST_Covers(geography geogpolyA, geography geogpointB);
```

例

Returns `true` if every point in Geometry/Geography B lies inside (i.e. intersects the interior or boundary of) Geometry/Geography A. Equivalently, tests that no point of B lies outside (in the exterior of) A.

In mathematical terms: $ST\_Covers(A, B) \Leftrightarrow A \sqcap B = B$

`ST_Covers` is the converse of [ST_CoveredBy](#). So, $ST\_Covers(A,B) = ST\_CoveredBy(B,A)$.

Generally this function should be used instead of [ST_Contains](#), since it has a simpler definition which does not have the quirk that "geometries do not contain their boundary".



Note

This function automatically includes a bounding box comparison that makes use of any spatial indexes that are available on the geometries. To avoid index use, use the function `_ST_Covers`.



Important

Enhanced: 3.0.0 enabled support for GEOMETRYCOLLECTION



Important
Do not use this function with invalid geometries. You will get unexpected results.

GEOS 重要事項

Enhanced: 2.4.0 Support for polygon in polygon and line in polygon added for geography type
Enhanced: 2.3.0 Enhancement to PIP short-circuit for geometry extended to support MultiPoints with few points. Prior versions only supported point in polygon.
1.5.0 重要事項.
1.2.2 重要事項.
NOTE: this is the "allowable" version that returns a boolean, not an integer.
Not an OGC standard, but Oracle has it too.

重要事項

Geometry example

```
--a circle covering a circle
SELECT ST_Covers(smallc,smallc) As smallinsmall,
       ST_Covers(smallc, bigc) As smallcoversbig,
       ST_Covers(bigc, ST_ExteriorRing(bigc)) As bigcoversexterior,
       ST_Contains(bigc, ST_ExteriorRing(bigc)) As bigcontainsexterior
FROM (SELECT ST_Buffer(ST_GeomFromText('POINT(1 2)'), 10) As smallc,
       ST_Buffer(ST_GeomFromText('POINT(1 2)'), 20) As bigc) As foo;
--Result
smallinsmall | smallcoversbig | bigcoversexterior | bigcontainsexterior
-----+-----+-----+-----
t             | f               | t                 | f
(1 row)
```

Geeography Example

```
-- a point with a 300 meter buffer compared to a point, a point and its 10 meter buffer
SELECT ST_Covers(geog_poly, geog_pt) As poly_covers_pt,
       ST_Covers(ST_Buffer(geog_pt,10), geog_pt) As buff_10m_covers_cent
FROM (SELECT ST_Buffer(ST_GeogFromText('SRID=4326;POINT(-99.327 31.4821)'), 300) As
       geog_poly,
       ST_GeogFromText('SRID=4326;POINT(-99.33 31.483)') As geog_pt ) As foo;

poly_covers_pt | buff_10m_covers_cent
-----+-----
f               | t
```

重要事項

ST_Contains, ST_CoveredBy, ST_Within

7.11.1.6 ST_Crosses

ST_Crosses — Tests if two geometries have some, but not all, interior points in common

Synopsis

boolean **ST_Crosses**(geometry g1, geometry g2);

国国

Compares two geometry objects and returns true if their intersection "spatially crosses"; that is, the geometries have some, but not all interior points in common. The intersection of the interiors of the geometries must be non-empty and must have dimension less than the maximum dimension of the two input geometries, and the intersection of the two geometries must not equal either geometry. Otherwise, it returns false. The crosses relation is symmetric and irreflexive.

In mathematical terms: $ST\_Crosses(A, B) \Leftrightarrow (dim(Int(A) \cap Int(B)) < \max(dim(Int(A)), dim(Int(B))) \wedge (A \cap B \neq A) \wedge (A \cap B \neq B)$

Geometries cross if their DE-9IM Intersection Matrix matches:

- T*T***** for Point/Line, Point/Area, and Line/Area situations
- T*****T** for Line/Point, Area/Point, and Area/Line situations
- 0***** for Line/Line situations
- the result is false for Point/Point and Area/Area situations



Note

The OpenGIS Simple Features Specification defines this predicate only for Point/Line, Point/Area, Line/Line, and Line/Area situations. JTS / GEOS extends the definition to apply to Line/Point, Area/Point and Area/Line situations as well. This makes the relation symmetric.



Note

This function automatically includes a bounding box comparison that makes use of any spatial indexes that are available on the geometries.



Important

Enhanced: 3.0.0 enabled support for GEOMETRYCOLLECTION




This method implements the [OGC Simple Features Implementation Specification for SQL 1.1. s2.1.13.3](#)



This method implements the SQL/MM specification. SQL-MM 3: 5.1.29

国国

The following situations all return true.



Consider a situation where a user has two tables: a table of roads and a table of highways.

<pre>CREATE TABLE roads (id serial NOT NULL, geom geometry, CONSTRAINT roads_pkey PRIMARY KEY (↵ road_id));</pre>	<pre>CREATE TABLE highways (id serial NOT NULL, the_gem geometry, CONSTRAINT roads_pkey PRIMARY KEY (↵ road_id));</pre>

To determine a list of roads that cross a highway, use a query similar to:

```
SELECT roads.id  
FROM roads, highways  
WHERE ST_Crosses(roads.geom, highways.geom);
```

国国

ST_Contains, ST_Overlaps**7.11.1.7 ST_Disjoint**

ST_Disjoint — Tests if two geometries have no points in common

Synopsisboolean **ST_Disjoint**(geometry A , geometry B);

国国

Returns true if two geometries are disjoint. Geometries are disjoint if they have no point in common. If any other spatial relationship is true for a pair of geometries, they are not disjoint. Disjoint implies that **ST_Intersects** is false.

In mathematical terms: $ST\_Disjoint(A, B) \Leftrightarrow A \cap B = \emptyset$ **Important**

Enhanced: 3.0.0 enabled support for GEOMETRYCOLLECTION

GEOS 国国国国国

**Note**

This function call does not use indexes. A negated **ST_Intersects** predicate can be used as a more performant alternative that uses indexes: `ST_Disjoint(A,B) = NOT ST_Intersects(A,B)`

**Note**

NOTE: this is the "allowable" version that returns a boolean, not an integer.



This method implements the **OGC Simple Features Implementation Specification for SQL 1.1**. s2.1.1.2 //s2.1.13.3 - a.Relate(b, 'FF*FF***')



This method implements the SQL/MM specification. SQL-MM 3: 5.1.26

国国

```
SELECT ST_Disjoint('POINT(0 0)::geometry, 'LINESTRING ( 2 0, 0 2 ) '::geometry);
st_disjoint
```

t

(1 row)

```
SELECT ST_Disjoint('POINT(0 0)::geometry, 'LINESTRING ( 0 0, 0 2 ) '::geometry);
```

```
st_disjoint
-----
f
(1 row)
```

☒☒

ST_Intersects

7.11.1.8 ST_Equals

ST_Equals — Tests if two geometries include the same set of points

Synopsis

boolean **ST_Equals**(geometry A, geometry B);

☒☒

Returns true if the given geometries are "topologically equal". Use this for a 'better' answer than '='. Topological equality means that the geometries have the same dimension, and their point-sets occupy the same space. This means that the order of vertices may be different in topologically equal geometries. To verify the order of points is consistent use **ST_OrderingEquals** (it must be noted **ST_OrderingEquals** is a little more stringent than simply verifying order of points are the same).

In mathematical terms: $ST\_Equals(A, B) \Leftrightarrow A = B$

The following relation holds: $ST\_Equals(A, B) \Leftrightarrow ST\_Within(A,B) \wedge ST\_Within(B,A)$



Important

Enhanced: 3.0.0 enabled support for GEOMETRYCOLLECTION



This method implements the **OGC Simple Features Implementation Specification for SQL 1.1. s2.1.1.2**



This method implements the SQL/MM specification. SQL-MM 3: 5.1.24

Changed: 2.2.0 Returns true even for invalid geometries if they are binary equal

☒☒

```
SELECT ST_Equals(ST_GeomFromText('LINESTRING(0 0, 10 10)'),
  ST_GeomFromText('LINESTRING(0 0, 5 5, 10 10)'));
st_equals
-----
t
(1 row)

SELECT ST_Equals(ST_Reverse(ST_GeomFromText('LINESTRING(0 0, 10 10)')),
  ST_GeomFromText('LINESTRING(0 0, 5 5, 10 10)'));
st_equals
-----
t
(1 row)
```

国国

[ST_IsValid](#), [ST_OrderingEquals](#), [ST_Reverse](#), [ST_Within](#)

7.11.1.9 ST_Intersects

ST_Intersects — Tests if two geometries intersect (they have at least one point in common)

Synopsis

```
boolean ST_Intersects( geometry geomA , geometry geomB );
boolean ST_Intersects( geography geogA , geography geogB );
```

国国

Returns `true` if two geometries intersect. Geometries intersect if they have any point in common.

For geography, a distance tolerance of 0.00001 meters is used (so points that are very close are considered to intersect).

In mathematical terms: $ST\_Intersects(A, B) \Leftrightarrow A \cap B \neq \emptyset$

Geometries intersect if their DE-9IM Intersection Matrix matches one of:

- T*****
- *T*****
- ***T*****
- ****T*****

Spatial intersection is implied by all the other spatial relationship tests, except [ST_Disjoint](#), which tests that geometries do NOT intersect.

**Note**

This function automatically includes a bounding box comparison that makes use of any spatial indexes that are available on the geometries.

Changed: 3.0.0 SFCGAL version removed and native support for 2D TINS added.

Enhanced: 2.5.0 Supports GEOMETRYCOLLECTION.

Enhanced: 2.3.0 Enhancement to PIP short-circuit extended to support MultiPoints with few points. Prior versions only supported point in polygon.

Performed by the GEOS module (for geometry), geography is native

Availability: 1.5 support for geography was introduced.

**Note**

For geography, this function has a distance tolerance of about 0.00001 meters and uses the sphere rather than spheroid calculation.

**Note**

NOTE: this is the “allowable” version that returns a boolean, not an integer.



This method implements the [OGC Simple Features Implementation Specification for SQL 1.1, s2.1.1.2 //s2.1.13.3](#) - ST_Intersects(g1, g2) --> Not (ST_Disjoint(g1, g2))



This method implements the SQL/MM specification. SQL-MM 3: 5.1.27



This method supports Circular Strings and Curves.



This function supports Triangles and Triangulated Irregular Network Surfaces (TIN).

SQL

```
SELECT ST_Intersects('POINT(0 0)::geometry, 'LINESTRING ( 2 0, 0 2 ) '::geometry);
st_intersects
-----
f
(1 row)
SELECT ST_Intersects('POINT(0 0)::geometry, 'LINESTRING ( 0 0, 0 2 ) '::geometry);
st_intersects
-----
t
(1 row)

-- Look up in table. Make sure table has a GiST index on geometry column for faster lookup.
SELECT id, name FROM cities WHERE ST_Intersects(geom, 'SRID=4326;POLYGON((28 53,27.707 52.293,27 52,26.293 52.293,26 53,26.293 53.707,27 54,27.707 53.707,28 53))');
id | name
----+-----
2  | Minsk
(1 row)
```

SQL

```
SELECT ST_Intersects(
    'SRID=4326;LINESTRING(-43.23456 72.4567,-43.23456 72.4568) '::geography,
    'SRID=4326;POINT(-43.23456 72.4567772) '::geography
);

st_intersects
-----
t
```

SQL

&&, ST_3DIntersects, ST_Disjoint

7.11.1.10 ST_LineCrossingDirection

ST_LineCrossingDirection — Returns a number indicating the crossing behavior of two LineStrings

Synopsis

integer **ST_LineCrossingDirection**(geometry linestringA, geometry linestringB);

返回

Given two linestrings returns an integer between -3 and 3 indicating what kind of crossing behavior exists between them. 0 indicates no crossing. This is only supported for LINESTRINGS.


The crossing number has the following meaning:

- 0: LINE NO CROSS
- -1: LINE CROSS LEFT
- 1: LINE CROSS RIGHT
- -2: LINE MULTICROSS END LEFT
- 2: LINE MULTICROSS END RIGHT
- -3: LINE MULTICROSS END SAME FIRST LEFT
- 3: LINE MULTICROSS END SAME FIRST RIGHT

Availability: 1.4

返回

Example: LINE CROSS LEFT and LINE CROSS RIGHT




Blue: Line A; Green: Line B

```
SELECT ST_LineCrossingDirection(lineA, lineB) As A_cross_B,
       ST_LineCrossingDirection(lineB, lineA) As B_cross_A
FROM (SELECT
  ST_GeomFromText('LINESTRING(25 169,89 114,40 70,86 43)') As lineA,
  ST_GeomFromText('LINESTRING (20 140, 71 74, 161 53)') As lineB
) As foo;
```

A_cross_B	B_cross_A
-1	1

Example: LINE_MULTICROSS END SAME FIRST LEFT and LINE_MULTICROSS END SAME FIRST RIGHT




Blue: Line A; Green: Line B

```
SELECT ST_LineCrossingDirection(lineA, lineB) As A_cross_B,
       ST_LineCrossingDirection(lineB, lineA) As B_cross_A
FROM (SELECT
      ST_GeomFromText('LINESTRING(25 169,89 114,40 70,86 43)') As lineA,
      ST_GeomFromText('LINESTRING(171 154,20 140,71 74,161 53)') As lineB
    ) As foo;
```

A_cross_B	B_cross_A
3	-3

Example: LINE_MULTICROSS END LEFT and LINE_MULTICROSS END RIGHT



Blue: Line A; Green: Line B

```
SELECT ST_LineCrossingDirection(lineA, lineB) As A_cross_B,
       ST_LineCrossingDirection(lineB, lineA) As B_cross_A
```

```
FROM (SELECT
  ST_GeomFromText('LINESTRING(25 169,89 114,40 70,86 43)') As lineA,
  ST_GeomFromText('LINESTRING(5 90, 71 74, 20 140, 171 154)') As lineB
) As foo;
```

```
A_cross_B | B_cross_A
-----+-----
      -2 |      2
```

Example: Finds all streets that cross

```
SELECT s1.gid, s2.gid, ST_LineCrossingDirection(s1.geom, s2.geom)
FROM streets s1 CROSS JOIN streets s2
      ON (s1.gid != s2.gid AND s1.geom && s2.geom )
WHERE ST_LineCrossingDirection(s1.geom, s2.geom)
> 0;
```

实验实验

ST_Crosses

7.11.1.11 ST_OrderingEquals

ST_OrderingEquals — Tests if two geometries represent the same geometry and have points in the same directional order

Synopsis

boolean **ST_OrderingEquals**(geometry A, geometry B);

实验实验

ST_OrderingEquals compares two geometries and returns t (TRUE) if the geometries are equal and the coordinates are in the same order; otherwise it returns f (FALSE).



Note

This function is implemented as per the ArcSDE SQL specification rather than SQL-MM. http://edndoc.esri.com/arcsde/9.1/sql_api/sqlapi3.htm#ST_OrderingEquals



This method implements the SQL/MM specification. SQL-MM 3: 5.1.43

实验实验

```
SELECT ST_OrderingEquals(ST_GeomFromText('LINESTRING(0 0, 10 10)'),
  ST_GeomFromText('LINESTRING(0 0, 5 5, 10 10)'));
 st_orderingequals
-----
f
(1 row)
```



```

SELECT ST_OrderingEquals(ST_GeomFromText('LINESTRING(0 0, 10 10)'),
    ST_GeomFromText('LINESTRING(0 0, 0 0, 10 10)'));
st_orderingequals
-----
t
(1 row)

SELECT ST_OrderingEquals(ST_Reverse(ST_GeomFromText('LINESTRING(0 0, 10 10)')),
    ST_GeomFromText('LINESTRING(0 0, 0 0, 10 10)'));
st_orderingequals
-----
f
(1 row)

```

☒☒

&&, ST_Equals, ST_Reverse

7.11.1.12 ST_Overlaps

ST_Overlaps — Tests if two geometries have the same dimension and intersect, but each has at least one point not in the other

Synopsis

boolean **ST_Overlaps**(geometry A, geometry B);

☒☒

Returns TRUE if geometry A and B “spatially overlap”. Two geometries overlap if they have the same dimension, their interiors intersect in that dimension. and each has at least one point inside the other (or equivalently, neither one covers the other). The overlaps relation is symmetric and irreflexive.

In mathematical terms: $ST\_Overlaps(A, B) \Leftrightarrow (dim(A) = dim(B) = dim(Int(A) \cap Int(B))) \wedge (A \cap B \neq A) \wedge (A \cap B \neq B)$



Note

This function automatically includes a bounding box comparison that makes use of any spatial indexes that are available on the geometries. To avoid index use, use the function `_ST_Overlaps`.

GEOS ☒☒☒☒☒



Important

Enhanced: 3.0.0 enabled support for GEOMETRYCOLLECTION

NOTE: this is the “allowable” version that returns a boolean, not an integer.





This method implements the **OGC Simple Features Implementation Specification for SQL 1.1**. s2.1.1.2 // s2.1.13.3



This method implements the SQL/MM specification. SQL-MM 3: 5.1.32

图例

ST_Overlaps returns TRUE in the following situations:



A Point on a LineString is contained, but since it has lower dimension it does not overlap or cross.

```
SELECT ST_Overlaps(a,b) AS overlaps,      ST_Crosses(a,b) AS crosses,
       ST_Intersects(a, b) AS intersects,  ST_Contains(b,a) AS b_contains_a
FROM (SELECT ST_GeomFromText('POINT (100 100)') As a,
       ST_GeomFromText('LINESTRING (30 50, 40 160, 160 40, 180 160)') AS b) AS t
```

overlaps	crosses	intersects	b_contains_a
f	f	t	t



A LineString that partly covers a Polygon intersects and crosses, but does not overlap since it has different dimension.

```
SELECT ST_Overlaps(a,b) AS overlaps,      ST_Crosses(a,b) AS crosses,
       ST_Intersects(a, b) AS intersects,  ST_Contains(a,b) AS contains
FROM (SELECT ST_GeomFromText('POLYGON ((40 170, 90 30, 180 100, 40 170))') AS a,
       ST_GeomFromText('LINESTRING(10 10, 190 190)') AS b) AS t;
```

overlap	crosses	intersects	contains
f	t	t	f



Two Polygons that intersect but with neither contained by the other overlap, but do not cross because their intersection has the same dimension.

```
SELECT ST_Overlaps(a,b) AS overlaps,      ST_Crosses(a,b) AS crosses,
       ST_Intersects(a, b) AS intersects,  ST_Contains(b, a) AS b_contains_a,
       ST_Dimension(a) AS dim_a, ST_Dimension(b) AS dim_b,
       ST_Dimension(ST_Intersection(a,b)) AS dim_int
FROM (SELECT ST_GeomFromText('POLYGON ((40 170, 90 30, 180 100, 40 170))') AS a,
       ST_GeomFromText('POLYGON ((110 180, 20 60, 130 90, 110 180))') AS b) AS t;
```

overlaps	crosses	intersects	b_contains_a	dim_a	dim_b	dim_int
t	f	t	f	2	2	2

[ST_Contains](#), [ST_Crosses](#), [ST_Dimension](#), [ST_Intersects](#)

7.11.1.13 ST_Relate

`ST_Relate` — Tests if two geometries have a topological relationship matching an Intersection Matrix pattern, or computes their Intersection Matrix

Synopsis

```
boolean ST_Relate(geometry geomA, geometry geomB, text intersectionMatrixPattern);
text ST_Relate(geometry geomA, geometry geomB);
text ST_Relate(geometry geomA, geometry geomB, integer boundaryNodeRule);
```

These functions allow testing and evaluating the spatial (topological) relationship between two geometries, as defined by the [Dimensionally Extended 9-Intersection Model](#) (DE-9IM).

The DE-9IM is specified as a 9-element matrix indicating the dimension of the intersections between the Interior, Boundary and Exterior of two geometries. It is represented by a 9-character text string using the symbols 'F', '0', '1', '2' (e.g. 'FF1FF0102').

A specific kind of spatial relationship can be tested by matching the intersection matrix to an *intersection matrix pattern*. Patterns can include the additional symbols 'T' (meaning "intersection is non-empty") and '*' (meaning "any value"). Common spatial relationships are provided by the named functions [ST_Contains](#), [ST_ContainsProperly](#), [ST_Covers](#), [ST_CoveredBy](#), [ST_Crosses](#), [ST_Disjoint](#), [ST_Equals](#), [ST_Intersects](#), [ST_Overlaps](#), [ST_Touches](#), and [ST_Within](#). Using an explicit pattern allows testing multiple conditions of intersects, crosses, etc in one step. It also allows testing spatial relationships which do not have a named spatial relationship function. For example, the relationship "Interior-Intersects" has the DE-9IM pattern T*****, which is not evaluated by any named predicate.

For more information refer to [Section 5.1](#).

Variant 1: Tests if two geometries are spatially related according to the given `intersectionMatrixPattern`



Note Unlike most of the named spatial relationship predicates, this does NOT automatically include an index call. The reason is that some relationships are true for geometries which do NOT intersect (e.g. Disjoint). If you are using a relationship pattern that requires intersection, then include the `&&` index call.



Note It is better to use a named relationship function if available, since they automatically use a spatial index where one exists. Also, they may implement performance optimizations which are not available with full relate evaluation.

Variant 2: Returns the DE-9IM matrix string for the spatial relationship between the two input geometries. The matrix string can be tested for matching a DE-9IM pattern using [ST_RelateMatch](#).

Variant 3: Like variant 2, but allows specifying a **Boundary Node Rule**. A boundary node rule allows finer control over whether the endpoints of MultiLineStrings are considered to lie in the DE-9IM Interior or Boundary. The boundaryNodeRule values are:

- 1: **OGC-Mod2** - line endpoints are in the Boundary if they occur an odd number of times. This is the rule defined by the OGC SFS standard, and is the default for ST_Relate.
- 2: **Endpoint** - all endpoints are in the Boundary.
- 3: **MultivalentEndpoint** - endpoints are in the Boundary if they occur more than once. In other words, the boundary is all the "attached" or "inner" endpoints (but not the "unattached/outer" ones).
- 4: **MonovalentEndpoint** - endpoints are in the Boundary if they occur only once. In other words, the boundary is all the "unattached" or "outer" endpoints.

This function is not in the OGC spec, but is implied. see s2.1.13.2

✔ This method implements the [OGC Simple Features Implementation Specification for SQL 1.1](#). s2.1.1.2 // s2.1.13.3

✔ This method implements the SQL/MM specification. SQL-MM 3: 5.1.25

GEOS 国国国国国

Enhanced: 2.0.0 - added support for specifying boundary node rule.



Important

Enhanced: 3.0.0 enabled support for GEOMETRYCOLLECTION

国国

Using the boolean-valued function to test spatial relationships.

```
SELECT ST_Relate('POINT(1 2)', ST_Buffer( 'POINT(1 2)', 2), '0FFFFF212');
st_relate
-----
t

SELECT ST_Relate(POINT(1 2)', ST_Buffer( 'POINT(1 2)', 2), '*FF*FF212');
st_relate
-----
t
```

Testing a custom spatial relationship pattern as a query condition, with && to enable using a spatial index.

```
-- Find compounds that properly intersect (not just touch) a poly (Interior Intersects)

SELECT c.* , p.name As poly_name
  FROM polys AS p
 INNER JOIN compounds As c
    ON c.geom && p.geom
    AND ST_Relate(p.geom, c.geom, 'T*****');
```

Computing the intersection matrix for spatial relationships.

```
SELECT ST_Relate( 'POINT(1 2)',
                  ST_Buffer( 'POINT(1 2)', 2));
-----
0FFFFFF212

SELECT ST_Relate( 'LINESTRING(1 2, 3 4)',
                  'LINESTRING(5 6, 7 8)' );
-----
FF1FF0102
```

Using different Boundary Node Rules to compute the spatial relationship between a LineString and a MultiLineString with a duplicate endpoint (3 3):

- Using the **OGC-Mod2** rule (1) the duplicate endpoint is in the **interior** of the MultiLineString, so the DE-9IM matrix entry [aB:bI] is 0 and [aB:bB] is F.
- Using the **Endpoint** rule (2) the duplicate endpoint is in the **boundary** of the MultiLineString, so the DE-9IM matrix entry [aB:bI] is F and [aB:bB] is 0.

```
WITH data AS (SELECT
  'LINESTRING(1 1, 3 3)::geometry AS a_line,
  'MULTILINESTRING((3 3, 3 5), (3 3, 5 3)):: geometry AS b_multiline
)
SELECT ST_Relate( a_line, b_multiline, 1) AS bnr_mod2,
       ST_Relate( a_line, b_multiline, 2) AS bnr_endpoint
FROM data;

bnr_mod2 | bnr_endpoint
-----+-----
FF10F0102 | FF1F00102
```

☒☒

Section 5.1, [ST_RelateMatch](#), [ST_Contains](#), [ST_ContainsProperly](#), [ST_Covers](#), [ST_CoveredBy](#), [ST_Crosses](#), [ST_Disjoint](#), [ST_Equals](#), [ST_Intersects](#), [ST_Overlaps](#), [ST_Touches](#), [ST_Within](#)

7.11.1.14 ST_RelateMatch

`ST_RelateMatch` — Tests if a DE-9IM Intersection Matrix matches an Intersection Matrix pattern

Synopsis

boolean **ST_RelateMatch**(text intersectionMatrix, text intersectionMatrixPattern);

☒☒

Tests if a **Dimensionally Extended 9-Intersection Model** (DE-9IM) `intersectionMatrix` value satisfies an `intersectionMatrixPattern`. Intersection matrix values can be computed by [ST_Relate](#).

For more information refer to Section 5.1.

GEOS ☒☒☒☒☒

2.0.0 ☒☒☒☒☒☒☒☒☒☒☒☒☒☒☒☒.

例

```
SELECT ST_RelateMatch('101202FFF', 'TTTTTFFF') ;
-- result --
t
```

Patterns for common spatial relationships matched against intersection matrix values, for a line in various positions relative to a polygon

```
SELECT pat.name AS relationship, pat.val AS pattern,
       mat.name AS position, mat.val AS matrix,
       ST_RelateMatch(mat.val, pat.val) AS match
FROM (VALUES ( 'Equality', 'T1FF1FFF1' ),
            ( 'Overlaps', 'T*T***T**' ),
            ( 'Within', 'T*F**F***' ),
            ( 'Disjoint', 'FF*FF****' )) AS pat(name,val)
CROSS JOIN
  (VALUES ('non-intersecting', 'FF1FF0212'),
          ('overlapping', '1010F0212'),
          ('inside', '1FF0FF212')) AS mat(name,val);
```

relationship	pattern	position	matrix	match
Equality	T1FF1FFF1	non-intersecting	FF1FF0212	f
Equality	T1FF1FFF1	overlapping	1010F0212	f
Equality	T1FF1FFF1	inside	1FF0FF212	f
Overlaps	T*T***T**	non-intersecting	FF1FF0212	f
Overlaps	T*T***T**	overlapping	1010F0212	t
Overlaps	T*T***T**	inside	1FF0FF212	f
Within	T*F**F***	non-intersecting	FF1FF0212	f
Within	T*F**F***	overlapping	1010F0212	f
Within	T*F**F***	inside	1FF0FF212	t
Disjoint	FF*FF****	non-intersecting	FF1FF0212	t
Disjoint	FF*FF****	overlapping	1010F0212	f
Disjoint	FF*FF****	inside	1FF0FF212	f

例

Section 5.1, [ST_Relate](#)

7.11.1.15 ST_Touches

ST_Touches — Tests if two geometries have at least one point in common, but their interiors do not intersect

Synopsis

boolean **ST_Touches**(geometry A, geometry B);

例

Returns TRUE if A and B intersect, but their interiors do not intersect. Equivalently, A and B have at least one point in common, and the common points lie in at least one boundary. For Point/Point inputs the relationship is always FALSE, since points do not have a boundary.

In mathematical terms: $ST\_Touches(A, B) \Leftrightarrow (Int(A) \cap Int(B) = \emptyset) \wedge (A \cap B \neq \emptyset)$

This relationship holds if the DE-9IM Intersection Matrix for the two geometries matches one of:

- FT*****
- F**T*****
- F***T****



Note This function automatically includes a bounding box comparison that makes use of any spatial indexes that are available on the geometries. To avoid using an index, use `_ST_Touches` instead.





Important
Enhanced: 3.0.0 enabled support for `GEOMETRYCOLLECTION`

- ✔ This method implements the [OGC Simple Features Implementation Specification for SQL 1.1. s2.1.1.2 // s2.1.13.3](#)
- ✔ This method implements the SQL/MM specification. SQL-MM 3: 5.1.28



The `ST_Touches` predicate returns `TRUE` in the following examples.





```
SELECT ST_Touches('LINESTRING(0 0, 1 1, 0 2)::geometry, 'POINT(1 1)::geometry');
st_touches
-----
f
(1 row)

SELECT ST_Touches('LINESTRING(0 0, 1 1, 0 2)::geometry, 'POINT(0 2)::geometry');
st_touches
-----
t
(1 row)
```

7.11.1.16 ST_Within

ST_Within — Tests if every point of A lies in B, and their interiors have a point in common

Synopsis

boolean **ST_Within**(geometry A, geometry B);



Returns TRUE if geometry A is within geometry B. A is within B if and only if all points of A lie inside (i.e. in the interior or boundary of) B (or equivalently, no points of A lie in the exterior of B), and the interiors of A and B have at least one point in common.

For this function to make sense, the source geometries must both be of the same coordinate projection, having the same SRID.

In mathematical terms: $ST\_Within(A, B) \Leftrightarrow (A \sqsubset B = A) \wedge (Int(A) \sqcap Int(B) \neq \emptyset)$

The within relation is reflexive: every geometry is within itself. The relation is antisymmetric: if $ST\_Within(A, B) = \text{true}$ and $ST\_Within(B, A) = \text{true}$, then the two geometries must be topologically equal ($ST\_Equals(A, B) = \text{true}$).

ST_Within is the converse of **ST_Contains**. So, $ST\_Within(A, B) = ST\_Contains(B, A)$.



Note

Because the interiors must have a common point, a subtlety of the definition is that lines and points lying fully in the boundary of polygons or lines are *not* within the geometry. For further details see [Subtleties of OGC Covers, Contains, Within](#). The `ST_CoveredBy` predicate provides a more inclusive relationship.



Note

This function automatically includes a bounding box comparison that makes use of any spatial indexes that are available on the geometries. To avoid index use, use the function `_ST_Within`.

GEOS 简体中文

Enhanced: 2.3.0 Enhancement to PIP short-circuit for geometry extended to support MultiPoints with few points. Prior versions only supported point in polygon.



Important

Enhanced: 3.0.0 enabled support for GEOMETRYCOLLECTION



Important

Do not use this function with invalid geometries. You will get unexpected results.

NOTE: this is the "allowable" version that returns a boolean, not an integer.



This method implements the [OGC Simple Features Implementation Specification for SQL 1.1](#). s2.1.1.2 // s2.1.13.3 - a.Relate(b, 'T**F***')



This method implements the SQL/MM specification. SQL-MM 3: 5.1.30

例

```
--a circle within a circle
SELECT ST_Within(smallc,smallc) As smallinsmall,
       ST_Within(smallc, bigc) As smallinbig,
       ST_Within(bigc,smallc) As biginsmall,
       ST_Within(ST_Union(smallc, bigc), bigc) as unioninbig,
       ST_Within(bigc, ST_Union(smallc, bigc)) as beginunion,
       ST_Equals(bigc, ST_Union(smallc, bigc)) as bigisunion
FROM
(
SELECT ST_Buffer(ST_GeomFromText('POINT(50 50)'), 20) As smallc,
       ST_Buffer(ST_GeomFromText('POINT(50 50)'), 40) As bigc) As foo;
--Result
smallinsmall | smallinbig | biginsmall | unioninbig | beginunion | bigisunion
-----+-----+-----+-----+-----+-----
t            | t          | f          | t          | t          | t
(1 row)
```



☒☒

[ST_Contains](#), [ST_CoveredBy](#), [ST_Equals](#), [ST_IsValid](#)

7.11.2 Distance Relationships

7.11.2.1 ST_3DDWithin

ST_3DDWithin — Tests if two 3D geometries are within a given 3D distance

Synopsis

boolean **ST_3DDWithin**(geometry g1, geometry g2, double precision distance_of_srid);

☒☒

Returns true if the 3D distance between two geometry values is no larger than distance `distance_of_srid`. The distance is specified in units defined by the spatial reference system of the geometries. For this function to make sense the source geometries must be in the same coordinate system (have the same SRID).



Note

This function automatically includes a bounding box comparison that makes use of any spatial indexes that are available on the geometries.



This function supports 3d and will not drop the z-index.



This function supports Polyhedral surfaces.



This method implements the SQL/MM specification. SQL-MM ?

2.0.0 简体中文

```
-- Geometry example - units in meters (SRID: 2163 US National Atlas Equal area) (3D point and line compared 2D point and line)
-- Note: currently no vertical datum support so Z is not transformed and assumed to be same units as final.
SELECT ST_3DDWithin(
    ST_Transform(ST_GeomFromEWKT('SRID=4326;POINT(-72.1235 42.3521 4)'),2163),
    ST_Transform(ST_GeomFromEWKT('SRID=4326;LINESTRING(-72.1260 42.45 15, -72.123 42.1546 20)'),2163),
    126.8
) As within_dist_3d,
ST_DWithin(
    ST_Transform(ST_GeomFromEWKT('SRID=4326;POINT(-72.1235 42.3521 4)'),2163),
    ST_Transform(ST_GeomFromEWKT('SRID=4326;LINESTRING(-72.1260 42.45 15, -72.123 42.1546 20)'),2163),
    126.8
) As within_dist_2d;

within_dist_3d | within_dist_2d
-----+-----
f              | t
```

[ST_3DDFullyWithin](#), [ST_DWithin](#), [ST_DFullyWithin](#), [ST_3DDistance](#), [ST_Distance](#), [ST_3DMaxDistance](#), [ST_Transform](#)

7.11.2.2 ST_3DDFullyWithin

ST_3DDFullyWithin — Tests if two 3D geometries are entirely within a given 3D distance

Synopsis

boolean **ST_3DDFullyWithin**(geometry g1, geometry g2, double precision distance);

Returns true if the 3D geometries are fully within the specified distance of one another. The distance is specified in units defined by the spatial reference system of the geometries. For this function to make sense, the source geometries must both be of the same coordinate projection, having the same SRID.



Note

This function automatically includes a bounding box comparison that makes use of any spatial indexes that are available on the geometries.

2.0.0

- ✔ This function supports 3d and will not drop the z-index.
- ✔ This function supports Polyhedral surfaces.

dfullywithin10		dwithin10		dfullywithin20
-----+-----+-----				
f		t		t

国国

[ST_MaxDistance](#), [ST_DWithin](#), [ST_3DDWithin](#), [ST_3DDFullyWithin](#)

7.11.2.4 ST_DWithin

ST_DWithin — Tests if two geometries are within a given distance

Synopsis

```
boolean ST_DWithin(geometry g1, geometry g2, double precision distance_of_srid);
boolean ST_DWithin(geography gg1, geography gg2, double precision distance_meters, boolean
use_spheroid = true);
```

国国

Returns true if the geometries are within a given distance

For geometry: The distance is specified in units defined by the spatial reference system of the geometries. For this function to make sense, the source geometries must be in the same coordinate system (have the same SRID).

For geography: units are in meters and distance measurement defaults to `use_spheroid = true`. For faster evaluation use `use_spheroid = false` to measure on the sphere.



Note

Use [ST_3DDWithin](#) for 3D geometries.



Note

This function call includes a bounding box comparison that makes use of any indexes that are available on the geometries.



This method implements the [OGC Simple Features Implementation Specification for SQL 1.1](#).

Availability: 1.5.0 support for geography was introduced

Enhanced: 2.1.0 improved speed for geography. See [Making Geography faster](#) for details.

Enhanced: 2.1.0 support for curved geometries was introduced.

Prior to 1.3, [ST_Expand](#) was commonly used in conjunction with `&&` and `ST_Distance` to test for distance, and in pre-1.3.4 this function used that logic. From 1.3.4, `ST_DWithin` uses a faster short-circuit distance function.

❏

```
-- Find the nearest hospital to each school
-- that is within 3000 units of the school.
-- We do an ST_DWithin search to utilize indexes to limit our search list
-- that the non-indexable ST_Distance needs to process
-- If the units of the spatial reference is meters then units would be meters
SELECT DISTINCT ON (s.gid) s.gid, s.school_name, s.geom, h.hospital_name
FROM schools s
LEFT JOIN hospitals h ON ST_DWithin(s.geom, h.geom, 3000)
ORDER BY s.gid, ST_Distance(s.geom, h.geom);

-- The schools with no close hospitals
-- Find all schools with no hospital within 3000 units
-- away from the school. Units is in units of spatial ref (e.g. meters, feet, degrees)
SELECT s.gid, s.school_name
FROM schools s
LEFT JOIN hospitals h ON ST_DWithin(s.geom, h.geom, 3000)
WHERE h.gid IS NULL;

-- Find broadcasting towers that receiver with limited range can receive.
-- Data is geometry in Spherical Mercator (SRID=3857), ranges are approximate.

-- Create geometry index that will check proximity limit of user to tower
CREATE INDEX ON broadcasting_towers using gist (geom);

-- Create geometry index that will check proximity limit of tower to user
CREATE INDEX ON broadcasting_towers using gist (ST_Expand(geom, sending_range));

-- Query towers that 4-kilometer receiver in Minsk Hackerspace can get
-- Note: two conditions, because shorter LEAST(b.sending_range, 4000) will not use index.
SELECT b.tower_id, b.geom
FROM broadcasting_towers b
WHERE ST_DWithin(b.geom, 'SRID=3857;POINT(3072163.4 7159374.1)', 4000)
AND ST_DWithin(b.geom, 'SRID=3857;POINT(3072163.4 7159374.1)', b.sending_range);
```

❏

ST_Distance, ST_3DDWithin

7.11.2.5 ST_PointInsideCircle

ST_PointInsideCircle — Tests if a point geometry is inside a circle defined by a center and radius

Synopsis

boolean **ST_PointInsideCircle**(geometry a_point, float center_x, float center_y, float radius);

❏

Returns true if the geometry is a point and is inside the circle with center center_x,center_y and radius radius.



Warning

Does not use spatial indexes. Use **ST_DWithin** instead.

Availability: 1.2

Changed: 2.2.0 In prior versions this was called ST_Point_Inside_Circle


```
SELECT ST_PointInsideCircle(ST_Point(1,2), 0.5, 2, 3);
 st_pointinsidecircle
-----
t
```



ST DWithin

7.12 Measurement Functions

7.12.1 ST_Area

ST Area — □□□□□□□□□□□□□□.

Synopsis

```
float ST_Area(geometry g1);
float ST_Area(geography geog, boolean use_spheroid = true);
```


ST_Surface(*geom*) - ST_MultiSurface(*geom*) - *geom*. *geom*, SRID *SRID* 2 *geom*. *geom*, *geom* (curved surface) *geom*. *geom*, ST_Area(*geom*,false) *geom*.

2.0.0 2 (polyhedral surface)

GeographicLib 2.2.0, Proj 4.9.0.

Changed: 3.0.0 - does not depend on SFCGAL anymore.



This method implements the [OGC Simple Features Implementation Specification for SQL 1.1](#).



This method implements the SQL/MM specification. SQL-MM 3: 8.1.2, 9.5.3




This function supports Polyhedral surfaces.



Note

$\text{atan2}(y, x)$, (2.5 $\times$ $\text{atan2}(y, x)$) 2 $\times$ $\text{atan2}(y, x)$. 2.5 $\times$ $\text{atan2}(y, x)$ 0 $\times$ $\text{atan2}(y, x)$ (non-zero) $\text{atan2}(y, x)$, XY $\text{atan2}(y, x)$.



 (plot) . EPSG:2249 .

[illegible][illegible]

```

select ST_Area(geom) sqft,
       ST_Area(ST_Transform(geom, 26986)) As sqm
from (
    select
        'SRID=2249;POLYGON((743238 2967416,743238 2967450,
        743265 2967450,743265.625 2967416,743238 2967416))' :: geometry geom
    ) subquery;

```

本图是根据国家测绘局颁布的《大地测量成果》(WGS84 4326)编制的。图中所示之
 数据仅供参考。如有变动,恕不另行通知。

```
select ST_Area(geog) / 0.3048 ^ 2 sqft_spheroid,
       ST_Area(geog, false) / 0.3048 ^ 2 sqft_sphere,
       ST_Area(geog) sqm_spheroid
from (
```

```
select ST_Transform(
    'SRID=2249;POLYGON((743238 2967416,743238 2967450,743265 ←
        2967450,743265.625 2967416,743238 2967416))'::geometry,
    4326
) :: geography geog
) as subquery;
```

```
b''|b''b''-b''b''-b''b''-b''b''-b''b''-b''b''-b''b''-b''b''-b''b''-b''b''-b''b''- ←
b''-b''b''-b''b''-b''b''-b''b''-b''b''-b''b''-b''b''-b''b''-b''b''-b''b''-b''b'' ←
'-b''b''-b''b''-b''b''-b''b''-b''b''-b''b''-b''b''-b''b''-b''b''-b''b''-b''b''-b''b'' ←
'-b''b''-b''b''-b''b''-b''b''-b''b''-b''b''-b''b''-b''b''-b''b''-b''b''-b''b''-b''b'' ←
'-b''b''-b''b''-b''b''-b''b''-b''b''-b''b''-b''b''-b''b''-b''b''-b''b''-b''b''-b''b'' ←
b''|b'' sqft_spheroid b''|b'' sqft_sphere b''|b'' sqm_spheroid b''|b''
b''|b''b''-b''b''-b''b''-b''b''-b''b''-b''b''-b''b''-b''b''-b''b''-b''b''-b''b''-b''b''- ←
b''-b''b''-b''b''-b''b''-b''b''-b''b''-b''b''-b''b''-b''b''-b''b''-b''b''-b''b''-b''b'' ←
'-b''b''-b''b''-b''b''-b''b''-b''b''-b''b''-b''b''-b''b''-b''b''-b''b''-b''b''-b''b'' ←
'-b''b''-b''b''-b''b''-b''b''-b''b''-b''b''-b''b''-b''b''-b''b''-b''b''-b''b''-b''b'' ←
'-b''b''-b''b''-b''b''-b''b''-b''b''-b''b''-b''b''-b''b''-b''b''-b''b''-b''b''-b''b'' ←
b''|b'' 928.684405784452 b''|b'' 927.049336105925 b''|b'' 86.2776044979692 b''|b''
b''|b''b''-b''b''-b''b''-b''b''-b''b''-b''b''-b''b''-b''b''-b''b''-b''b''-b''b''-b''b''- ←
b''-b''b''-b''b''-b''b''-b''b''-b''b''-b''b''-b''b''-b''b''-b''b''-b''b''-b''b''-b''b'' ←
'-b''b''-b''b''-b''b''-b''b''-b''b''-b''b''-b''b''-b''b''-b''b''-b''b''-b''b''-b''b'' ←
'-b''b''-b''b''-b''b''-b''b''-b''b''-b''b''-b''b''-b''b''-b''b''-b''b''-b''b''-b''b'' ←
'-b''b''-b''b''-b''b''-b''b''-b''b''-b''b''-b''b''-b''b''-b''b''-b''b''-b''b''-b''b''
```

If your data is in geography already:

```
select ST_Area(geog) / 0.3048 ^ 2 sqft,
       ST_Area(the_geog) sqm
from somegeogtable;
```



ST 3DArea, ST_GeomFromEWKT, ST_LengthSpheroid, ST_Perimeter, ST_Transform

7.12.2 ST Azimuth

ST Azimuth — □□□□□□ 2 □□□□□□□□□□.

Synopsis

```
float ST_Azimuth(geometry origin, geometry target);  
float ST_Azimuth(geography origin, geography target);
```


Returns the azimuth in radians of the target point from the origin point, or NULL if the two points are coincident. The azimuth angle is a positive clockwise angle referenced from the positive Y axis (geometry) or the North meridian (geography): North = 0; Northeast = $\pi/4$; East = $\pi/2$; Southeast = $3\pi/4$; South = π ; Southwest $5\pi/4$; West = $3\pi/2$; Northwest = $7\pi/4$.

For the geography type, the azimuth solution is known as the **inverse geodesic problem**.

The azimuth is a mathematical concept defined as the angle between a reference vector and a point, with angular units in radians. The result value in radians can be converted to degrees using the PostgreSQL function `degrees()`.

ST_Translate 函数用于将几何体沿指定的偏移量进行平移。有关详细信息，请参阅 [Plpgsqlfunctions PostGIS wiki section](#) 中的 upgis_lineshift 函数。

1.1.0 版本支持。
2.0.0 版本支持。
2.2.0 版本支持，依赖于 GeographicLib 库。从 Proj 4.9.0 版本开始支持。

图 1

图 1: ST_Azimuth 函数示意图

```
SELECT degrees(ST_Azimuth( ST_Point(25, 45), ST_Point(75, 100))) AS degA_B,  
       degrees(ST_Azimuth( ST_Point(75, 100), ST_Point(25, 45) )) AS degB_A;
```

degA_B	degB_A
42.2736890060937	222.273689006094




图 2

[ST_Angle](#), [ST_Translate](#), [ST_Project](#), [PostgreSQL Math Functions](#)

7.12.3 ST_Angle

ST_Angle — 返回由 3 个点 (最长) 定义的角度的度数。

Synopsis

```
float ST_Angle(geometry point1, geometry point2, geometry point4);  
float ST_Angle(geometry line1, geometry line2);
```

函数

返回由 3 点 (最长) 定义的角度的度数。

Variant 1: computes the angle enclosed by the points P1-P2-P3. If a 4th point provided computes the angle points P1-P2 and P3-P4

Variant 2: computes the angle between two vectors S1-E1 and S2-E2, defined by the start and end points of the input lines

PostgreSQL 的 `degrees()` 函数返回角度的度数。PostgreSQL 的 `degrees()` 函数返回角度的度数。

Note that `ST_Angle(P1,P2,P3) = ST_Angle(P2,P1,P2,P3)`.

Availability: 2.5.0

函数

返回由 4 点定义的角度的度数。

```
SELECT degrees( ST_Angle('POINT(0 0)', 'POINT(10 10)', 'POINT(20 0)') );
```

```
degrees
-----
270
```

Angle between vectors defined by four points

```
SELECT degrees( ST_Angle('POINT (10 10)', 'POINT (0 0)', 'POINT(90 90)', 'POINT (100 80)') );
```

```
degrees
-----
269.99999999999999
```

Angle between vectors defined by the start and end points of lines

```
SELECT degrees( ST_Angle('LINESTRING(0 0, 0.3 0.7, 1 1)', 'LINESTRING(0 0, 0.2 0.5, 1 0)') );
```

```
degrees
-----
45
```

函数

ST_Azimuth

7.12.4 ST_ClosestPoint

ST_ClosestPoint — Returns the 2D point on g1 that is closest to g2. This is the first point of the shortest line from one geometry to the other.

Synopsis

```
geometry ST_ClosestPoint(geometry geom1, geometry geom2);
geography ST_ClosestPoint(geography geom1, geography geom2, boolean use_spheroid = true);
```

返回


Returns the 2-dimensional point on `geom1` that is closest to `geom2`. This is the first point of the shortest line between the geometries (as computed by [ST_ShortestLine](#)).



Note
3 版本中 [ST_3DClosestPoint](#) 函数返回 3D 结果。

Enhanced: 3.4.0 - Support for geography.
1.5.0 版本中引入。


返回



The closest point for a Point and a LineString is the point itself. The closest point for a LineString and a Point is a point on the line.

```
SELECT ST_AsText( ST_ClosestPoint(pt,line)) AS cp_pt_line,
       ST_AsText( ST_ClosestPoint(line,pt)) AS cp_line_pt
FROM (SELECT 'POINT (160 40)::geometry AS pt,
            'LINESTRING (10 30, 50 50, 30 110, 70 90, 180 140, 130 190)::geometry AS
            line ) AS t;
```

cp_pt_line	cp_line_pt
POINT(160 40)	POINT(125.75342465753425 115.34246575342466)



The closest point on polygon A to polygon B

```
SELECT ST_AsText( ST_ClosestPoint(
                    'POLYGON ((190 150, 20 10, 160 70, 190 150))',
                    ST_Buffer('POINT(80 160)', 30)
                )) As ptwkt;
-----
POINT(131.59149149528952 101.89887534906197)
```

☐☐

[ST_3DClosestPoint](#), [ST_Distance](#), [ST_LongestLine](#), [ST_ShortestLine](#), [ST_MaxDistance](#)

7.12.5 ST_3DClosestPoint

ST_3DClosestPoint — g2 相对于 g1 的 3D 最近点。返回 3D 最近点坐标。

Synopsis

geometry **ST_3DClosestPoint**(geometry g1, geometry g2);

☐☐

g2 相对于 g1 的 3D 最近点。返回 3D 最近点坐标。3D 最近点坐标 3D 最近点坐标。



This function supports 3d and will not drop the z-index.



This function supports Polyhedral surfaces.

2.0.0 版本引入。

注意: 2.2.0 版本引入 2D 最近点函数, (最近点 Z 为 0 的最近点) 2D 最近点坐标。2D 到 3D 最近点, 最近点 Z 为 0 的最近点坐标。

图例

图例 -- 3D, 2D 最近点 (closest point)	
<pre> SELECT ST_AsEWKT(ST_3DClosestPoint(line,pt)) AS cp3d_line_pt, ST_AsEWKT(ST_ClosestPoint(line,pt)) As cp2d_line_pt FROM (SELECT 'POINT(100 100 30) '::geometry As pt, 'LINESTRING (20 80 20, 98 190 1, 110 180 3, 50 75 1000) ':: geometry As line) As foo; </pre>	
cp3d_line_pt	cp2d_line_pt
-----+	
POINT(54.6993798867619 128.935022917228 11.5475869506606) POINT(73.0769230769231 115.284615384615)	
图例 -- 3D, 2D 最近点 (closest point)	
<pre> SELECT ST_AsEWKT(ST_3DClosestPoint(line,pt)) AS cp3d_line_pt, ST_AsEWKT(ST_ClosestPoint(line,pt)) As cp2d_line_pt FROM (SELECT 'MULTIPOINT(100 100 30, 50 74 1000) '::geometry As pt, 'LINESTRING (20 80 20, 98 190 1, 110 180 3, 50 75 900) ':: geometry As line) As foo; </pre>	
cp3d_line_pt	cp2d_line_pt
-----+	
POINT(54.6993798867619 128.935022917228 11.5475869506606) POINT(50 75)	
图例 -- 3D, 2D 最近点 (closest point)	
<pre> SELECT ST_AsEWKT(ST_3DClosestPoint(poly, mline)) As cp3d, ST_AsEWKT(ST_ClosestPoint(poly, mline)) As cp2d FROM (SELECT ST_GeomFromEWKT('POLYGON((175 150 5, 20 40 5, 35 45 5, 50 60 5, 100 100 5, 175 150 5))') As poly, ST_GeomFromEWKT('MULTILINESTRING((175 155 2, 20 40 20, 50 60 -2, 125 100 1, 175 155 1), (1 10 2, 5 20 1))') As mline) As foo; </pre>	
cp3d	cp2d
-----+	
POINT(39.993580415989 54.1889925532825 5) POINT(20 40)	

图例

ST_AsEWKT, **ST_ClosestPoint**, **ST_3DDistance**, **ST_3DShortestLine**

7.12.6 ST_Distance

ST_Distance — 返回 3D 空间中的最长距离。

Synopsis

```

float ST_Distance(geometry g1, geometry g2);
float ST_Distance(geography geog1, geography geog2, boolean use_spheroid = true);

```

距离

`ST_Distance`, `ST_Distance_Sphere` 3 空间数据类型 (SRS 无关) 距离函数。

For **geography** types defaults to return the minimum geodesic distance between two geographies in meters, compute on the spheroid determined by the SRID. If `use_spheroid` is false, a faster spherical calculation is used.

- ✔ This method implements the **OGC Simple Features Implementation Specification for SQL 1.1**.
- ✔ This method implements the SQL/MM specification. SQL-MM 3: 5.1.23
- ✔ This method supports Circular Strings and Curves.

1.5.0 版本开始支持。在 PostgreSQL 11.0 之前，`ST_Distance` 使用 SFCGAL 库。从 11.0 开始，它使用 GeographicLib 库。

版本: 2.1.0 版本开始支持。在 PostgreSQL 11.0 之前，`ST_Distance` 使用 SFCGAL 库。从 11.0 开始，它使用 GeographicLib 库。从 2.1.0 版本开始，它使用 **Making Geography faster** 库。

版本: 2.1.0 版本开始支持。在 PostgreSQL 11.0 之前，`ST_Distance` 使用 SFCGAL 库。从 11.0 开始，它使用 GeographicLib 库。

版本: 2.2.0 版本开始支持。在 PostgreSQL 11.0 之前，`ST_Distance` 使用 SFCGAL 库。从 11.0 开始，它使用 GeographicLib 库。从 2.2.0 版本开始，它使用 Proj 4.9.0 库。

Changed: 3.0.0 - does not depend on SFCGAL anymore.

示例

Geometry example - units in planar degrees 4326 is WGS 84 long lat, units are degrees.

```
SELECT ST_Distance(
  'SRID=4326;POINT(-72.1235 42.3521)::geometry',
  'SRID=4326;LINESTRING(-72.1260 42.45, -72.123 42.1546)::geometry ');
-----
0.00150567726382282
```

Geometry example - units in meters (SRID: 3857, proportional to pixels on popular web maps). Although the value is off, nearby ones can be compared correctly, which makes it a good choice for algorithms like KNN or KMeans.

```
SELECT ST_Distance(
  ST_Transform('SRID=4326;POINT(-72.1235 42.3521)::geometry', 3857),
  ST_Transform('SRID=4326;LINESTRING(-72.1260 42.45, -72.123 42.1546)::geometry', 3857) ) <-
;
-----
167.441410065196
```

Geometry example - units in meters (SRID: 3857 as above, but corrected by `cos(lat)` to account for distortion)

```
SELECT ST_Distance(
  ST_Transform('SRID=4326;POINT(-72.1235 42.3521)::geometry', 3857),
  ST_Transform('SRID=4326;LINESTRING(-72.1260 42.45, -72.123 42.1546)::geometry', 3857)
) * cosd(42.3521);
-----
123.742351254151
```

Geometry example - units in meters (SRID: 26986 Massachusetts state plane meters) (most accurate for Massachusetts)


```
SELECT ST_Distance(
  ST_Transform('SRID=4326;POINT(-72.1235 42.3521)::geometry, 26986),
  ST_Transform('SRID=4326;LINESTRING(-72.1260 42.45, -72.123 42.1546)::geometry, 26986)  ←
);
-----
123.797937878454
```

Geometry example - units in meters (SRID: 2163 US National Atlas Equal area) (least accurate)

```
SELECT ST_Distance(
  ST_Transform('SRID=4326;POINT(-72.1235 42.3521)::geometry, 2163),
  ST_Transform('SRID=4326;LINESTRING(-72.1260 42.45, -72.123 42.1546)::geometry, 2163) )  ←
;
-----
126.664256056812
```

函数

Same as geometry example but note units in meters - use sphere for slightly faster and less accurate computation.

```
SELECT ST_Distance(gg1, gg2) As spheroid_dist, ST_Distance(gg1, gg2, false) As sphere_dist
FROM (SELECT
  'SRID=4326;POINT(-72.1235 42.3521)::geography as gg1,
  'SRID=4326;LINESTRING(-72.1260 42.45, -72.123 42.1546)::geography as gg2
) As foo ;

spheroid_dist | sphere_dist
-----+-----
123.802076746848 | 123.475736916397
```

函数

[ST_3DDistance](#), [ST_DWithin](#), [ST_DistanceSphere](#), [ST_DistanceSpheroid](#), [ST_MaxDistance](#), [ST_HausdorffDistance](#), [ST_FrechetDistance](#), [ST_Transform](#)

7.12.7 ST_3DDistance

ST_3DDistance — 计算两个几何体 (SRS 3D) 之间的 3D 欧几里得距离。

Synopsis

float **ST_3DDistance**(geometry g1, geometry g2);

函数

计算两个几何体 (SRS 3D) 之间的 3D 欧几里得距离。



This function supports 3d and will not drop the z-index.



This function supports Polyhedral surfaces.

✓ This method implements the SQL/MM specification. SQL-MM ISO/IEC 13249-3 2.0.0 兼容。

兼容: 2.2.0 兼容, 2D 和 3D 兼容 Z 兼容 Z 为 0 兼容。

Changed: 3.0.0 - SFCGAL version removed

兼容

```
-- Geometry example - units in meters (SRID: 2163 US National Atlas Equal area) (3D point and line compared 2D point and line)
-- Note: currently no vertical datum support so Z is not transformed and assumed to be same units as final.
SELECT ST_3DDistance(
    ST_Transform('SRID=4326;POINT(-72.1235 42.3521 4) '::geometry,2163),
    ST_Transform('SRID=4326;LINESTRING(-72.1260 42.45 15, -72.123 42.1546 20) '::geometry,2163)
) As dist_3d,
ST_Distance(
    ST_Transform('SRID=4326;POINT(-72.1235 42.3521) '::geometry,2163),
    ST_Transform('SRID=4326;LINESTRING(-72.1260 42.45, -72.123 42.1546) '::geometry,2163)
) As dist_2d;

dist_3d      |      dist_2d
-----+-----
127.295059324629 | 126.66425605671
```

```
-- Multilinestring and polygon both 3d and 2d distance
-- Same example as 3D closest point example
SELECT ST_3DDistance(poly, mline) As dist3d,
    ST_Distance(poly, mline) As dist2d
FROM (SELECT 'POLYGON((175 150 5, 20 40 5, 35 45 5, 50 60 5, 100 100 5, 175 150 5) ' :::geometry as poly,
    'MULTILINESTRING((175 155 2, 20 40 20, 50 60 -2, 125 100 1, 175 155 1), (1 10 2, 5 20 1))' :::geometry as mline) as foo;

dist3d      |      dist2d
-----+-----
0.716635696066337 | 0
```

兼容

[ST_Distance](#), [ST_3DClosestPoint](#), [ST_3DDWithin](#), [ST_3DMaxDistance](#), [ST_3DShortestLine](#), [ST_Transform](#)

7.12.8 ST_DistanceSphere

ST_DistanceSphere — 计算两个几何体在球面上的最短距离。PostGIS 1.5 兼容。

Synopsis

float **ST_DistanceSphere**(geometry geom1lonlatA, geometry geom1lonlatB, float8 radius=6371008);

图

图 2 展示了使用 `ST_DistanceSpheroid` 函数。SRID 4326 是 WGS 1984 地理坐标系。PostGIS 1.5 之前，`ST_DistanceSpheroid` 函数是不存在的。

1.5 版本之前，使用 `ST_DistanceSphere` 函数。1.5 版本之后，`ST_DistanceSpheroid` 函数被引入。

图 2.2.0 展示了 `ST_DistanceSphere` 函数的使用。

图

```
SELECT round(CAST(ST_DistanceSphere(ST_Centroid(geom), ST_GeomFromText('POINT(-118 38)', 4326)) As numeric), 2) As dist_meters,
round(CAST(ST_Distance(ST_Transform(ST_Centroid(geom), 32611),
ST_Transform(ST_GeomFromText('POINT(-118 38)', 4326), 32611)) As numeric), 2) As dist_utm11_meters,
round(CAST(ST_Distance(ST_Centroid(geom), ST_GeomFromText('POINT(-118 38)', 4326)) As numeric), 5) As dist_degrees,
round(CAST(ST_Distance(ST_Transform(geom, 32611),
ST_Transform(ST_GeomFromText('POINT(-118 38)', 4326), 32611)) As numeric), 2) As min_dist_line_point_meters
FROM
(SELECT ST_GeomFromText('LINESTRING(-118.584 38.374, -118.583 38.5)', 4326) As geom)
as foo;
dist_meters | dist_utm11_meters | dist_degrees | min_dist_line_point_meters
-----+-----+-----+-----
70424.47 | 70438.00 | 0.72900 | 65871.18
```

图

`ST_Distance`, `ST_DistanceSpheroid`

7.12.9 ST_DistanceSpheroid

`ST_DistanceSpheroid` — 计算两个几何对象之间的球面距离。PostGIS 1.5 之前，`ST_DistanceSpheroid` 函数是不存在的。

Synopsis

float **ST_DistanceSpheroid**(geometry geom1lonlatA, geometry geom1lonlatB, spheroid measurement_spheroid)

图

图 展示了使用 `ST_DistanceSpheroid` 函数。图 展示了使用 `ST_LengthSpheroid` 函数。PostGIS 1.5 之前，`ST_DistanceSpheroid` 函数是不存在的。



Note

图 展示了使用 SRID 4326 的几何对象。图 展示了使用 SRID 4326 的几何对象。

1.5 米。1.5 米。1.5 米。

2.2.0 版本 ST_Distance_Spheroid 函数。

SQL

```
SELECT round(CAST(
    ST_DistanceSpheroid(ST_Centroid(geom), ST_GeomFromText('POINT(-118 38) ←
    ',4326), 'SPHEROID["WGS 84",6378137,298.257223563]')
    As numeric),2) As dist_meters_spheroid,
    round(CAST(ST_DistanceSphere(ST_Centroid(geom), ST_GeomFromText('POINT(-118 ←
    38)',4326)) As numeric),2) As dist_meters_sphere,
    round(CAST(ST_Distance(ST_Transform(ST_Centroid(geom),32611),
    ST_Transform(ST_GeomFromText('POINT(-118 38)', 4326),32611)) As numeric),2) ←
    As dist_utm11_meters
FROM
    (SELECT ST_GeomFromText('LINESTRING(-118.584 38.374,-118.583 38.5)', 4326) As geom) ←
    as foo;
dist_meters_spheroid | dist_meters_sphere | dist_utm11_meters
-----+-----+-----
70454.92 | 70424.47 | 70438.00
```

SQL

[ST_Distance](#), [ST_DistanceSphere](#)

7.12.10 ST_FrechetDistance

ST_FrechetDistance — 计算 3 个最短距离 (shortest) 距离。

Synopsis

float **ST_FrechetDistance**(geometry g1, geometry g2, float densifyFrac = -1);

SQL

Implements algorithm for computing the Fréchet distance restricted to discrete points for both geometries, based on [Computing Discrete Fréchet Distance](#). The Fréchet distance is a measure of similarity between curves that takes into account the location and ordering of the points along the curves. Therefore it is often better than the Hausdorff distance.

When the optional densifyFrac is specified, this function performs a segment densification before computing the discrete Fréchet distance. The densifyFrac parameter sets the fraction by which to densify each segment. Each segment will be split into a number of equal-length subsegments, whose fraction of the total length is closest to the given fraction.

Units are in the units of the spatial reference system of the geometries.



Note

该函数在计算 Fréchet 距离之前，会对输入的多边形进行分段。分段的数量由 densifyFrac 参数决定。该参数设置为 -1 时，表示不进行分段。该函数返回的距离值，其单位与输入几何体的空间参考系统单位一致。

**Note**

The smaller `densifyFrac` we specify, the more accurate Fréchet distance we get. But, the computation time and the memory usage increase with the square of the number of subsegments.

GEOS 国国国国国

Availability: 2.4.0 - requires GEOS >= 3.7.0

国国

```
postgres=# SELECT st_frechetdistance('LINESTRING (0 0, 100 0)::geometry, 'LINESTRING (0 0, ↵
          50 50, 100 0)::geometry');
 st_frechetdistance
-----
          70.7106781186548
(1 row)
```

```
SELECT st_frechetdistance('LINESTRING (0 0, 100 0)::geometry, 'LINESTRING (0 0, 50 50, 100 ↵
          0)::geometry, 0.5);
 st_frechetdistance
-----
                    50
(1 row)
```

国国

ST_HausdorffDistance

7.12.11 ST_HausdorffDistance

`ST_HausdorffDistance` — 国国国国国国 3 国国国 (shortest) 国国国国国国国.

Synopsis

```
float ST_HausdorffDistance(geometry g1, geometry g2);
float ST_HausdorffDistance(geometry g1, geometry g2, float densifyFrac);
```

国国

Returns the **Hausdorff distance** between two geometries. The Hausdorff distance is a measure of how similar or dissimilar 2 geometries are.

The function actually computes the “Discrete Hausdorff Distance”. This is the Hausdorff distance computed at discrete points on the geometries. The *densifyFrac* parameter can be specified, to provide a more accurate answer by densifying segments before computing the discrete Hausdorff distance. Each segment is split into a number of equal-length subsegments whose fraction of the segment length is closest to the given fraction.

Units are in the units of the spatial reference system of the geometries.

Note

This algorithm is NOT equivalent to the standard Hausdorff distance. However, it computes an approximation that is correct for a large subset of useful cases. One important case is Linestrings that are roughly parallel to each other, and roughly equal in length. This is a useful metric for line matching.

1.5.0 简体中文.

图



Hausdorff distance (red) and distance (yellow) between two lines

```
SELECT ST_HausdorffDistance(geomA, geomB),
       ST_Distance(geomA, geomB)
FROM (SELECT 'LINESTRING (20 70, 70 60, 110 70, 170 70)>:::geometry AS geomA,
            'LINESTRING (20 90, 130 90, 60 100, 190 100)>:::geometry AS geomB) AS t;
st_hausdorffdistance | st_distance
-----+-----
37.26206567625497 | 20
```

Example: Hausdorff distance with densification.

```
SELECT ST_HausdorffDistance(
    'LINESTRING (130 0, 0 0, 0 150)>:::geometry,
    'LINESTRING (10 10, 10 150, 130 10)>:::geometry,
    0.5);
-----
70
```

Example: For each building, find the parcel that best represents it. First we require that the parcel intersect with the building geometry. `DISTINCT ON` guarantees we get each building listed only once. `ORDER BY .. ST_HausdorffDistance` selects the parcel that is most similar to the building.

```
SELECT DISTINCT ON (buildings.gid) buildings.gid, parcels.parcel_id
FROM buildings
  INNER JOIN parcels
    ON ST_Intersects(buildings.geom, parcels.geom)
ORDER BY buildings.gid, ST_HausdorffDistance(buildings.geom, parcels.geom);
```

返回

ST_FrechetDistance

7.12.12 ST_Length

ST_Length — 返回几何对象的长度。

Synopsis

```
float ST_Length(geometry a_2dlinestring);
float ST_Length(geography geog, boolean use_spheroid = true);
```

返回

几何类型: 返回几何对象的长度。对于 **ST_Curve**, **ST_MultiCurve** 返回 2 个浮点数的数组。对于 **ST_LineString**, **ST_MultiLineString** 返回 0 个浮点数的数组。对于 **ST_Perimeter** 返回浮点数的数组。对于 **ST_MultiLineString**, **ST_MultiCurve** 返回浮点数的数组。

For geography types: computation is performed using the inverse geodesic calculation. Units of length are in meters. If PostGIS is compiled with PROJ version 4.8.0 or later, the spheroid is specified by the SRID, otherwise it is exclusive to WGS84. If `use_spheroid = false`, then the calculation is based on a sphere instead of a spheroid.

对于 **ST_Length2D** 返回浮点数的数组，对于 **ST_Length** 返回浮点数的数组。



Warning

警告: 2.0.0 版本中，对于 **ST_Length** 返回浮点数的数组。2.0.0 版本中，对于 **ST_Length** 返回浮点数的数组。2.0.0 版本中，对于 **ST_Length** 返回浮点数的数组。2.0.0 版本中，对于 **ST_Length** 返回浮点数的数组。



Note

注意: 对于 **ST_Length** 返回浮点数的数组。对于 **ST_Length** 返回浮点数的数组。对于 **ST_Length** 返回浮点数的数组。对于 **ST_Length** 返回浮点数的数组。



This method implements the **OGC Simple Features Implementation Specification for SQL 1.1**. s2.1.5.1



This method implements the SQL/MM specification. SQL-MM 3: 7.1.2, 9.3.4 1.5.0 返回浮点数的数组。

返回

对于 **ST_Length** 返回浮点数的数组。对于 **ST_Length** 返回浮点数的数组。对于 **ST_Length** 返回浮点数的数组。对于 **ST_Length** 返回浮点数的数组。

```

SELECT ST_Length(ST_GeomFromText('LINESTRING(743238 2967416,743238 2967450,743265 2967450,
743265.625 2967416,743238 2967416)',2249));

st_length
-----
122.630744000095

--Transforming WGS 84 LineString to Massachusetts state plane meters
SELECT ST_Length(
    ST_Transform(
        ST_GeomFromEWKT('SRID=4326;LINESTRING(-72.1260 42.45, -72.1240 42.45666, ↔
        -72.123 42.1546)'),
        26986
    )
);

st_length
-----
34309.4563576191

```

图 7.12.12

WGS84 地理坐标转换为平面坐标。

```

-- the default calculation uses a spheroid
SELECT ST_Length(the_geog) As length_spheroid, ST_Length(the_geog,false) As length_sphere
FROM (SELECT ST_GeographyFromText(
'SRID=4326;LINESTRING(-72.1260 42.45, -72.1240 42.45666, -72.123 42.1546)') As the_geog)
As foo;

length_spheroid | length_sphere
-----+-----
34310.5703627288 | 34346.2060960742

```

图 7.12.13

ST_GeographyFromText, ST_GeomFromEWKT, ST_LengthSpheroid, ST_Perimeter, ST_Transform

7.12.13 ST_Length2D

ST_Length2D — 返回 2D 平面上的长度。与 ST_Length 类似。

Synopsis

float **ST_Length2D**(geometry a_2dlinestring);

图 7.12.14

图 7.12.14 显示了 ST_Length2D 与 ST_Length 的区别。ST_Length 返回的是 3D 长度。

ST_Length, ST_3DLength

ST_3DLength — .

```
float ST_3DLength(geometry a_3dlinestring);
```

$\text{ST\_Length} \times \text{ST\_Length2D}$ (ST_Length $\times$ ST_Length2D).

- ✔ This function supports 3d and will not drop the z-index.
 - ✔ This method implements the SQL/MM specification. SQL-MM IEC 13249-3: 7.1, 10.3
- 🔍🔍🔍: 2.0.0 🔍🔍🔍🔍 ST Length3D 🔍🔍🔍🔍🔍🔍.

[illegible]

```
SELECT ST_3DLength(ST_GeomFromText('LINESTRING(743238 2967416 1,743238 2967450 1,743265 2967450 3,743265.625 2967416 3,743238 2967416 3)',2249));
ST_3DLength
-----
122.704716741457
```

ST_Length, ST_Length2D

ST_LengthSpheroid — .

```
float ST_LengthSpheroid(geometry a geometry, spheroid a spheroid);
```


7.12.16 ST_LongestLine

ST_LongestLine — 返回 3 个最长 (longest) 的线。

Synopsis

geometry **ST_LongestLine**(geometry g1, geometry g2);

返回


Returns the 2-dimensional longest line between the points of two geometries. The line returned starts on g1 and ends on g2.

The longest line always occurs between two vertices. The function returns the first longest line if more than one is found. The length of the line is equal to the distance returned by [ST_MaxDistance](#).

If g1 and g2 are the same geometry, returns the line between the two vertices farthest apart in the geometry. The endpoints of the line lie on the circle computed by [ST_MinimumBoundingCircle](#).

1.5.0 引入。

返回



返回

```
SELECT ST_AsText( ST_LongestLine(
    'POINT (160 40)',
    'LINESTRING (10 30, 50 50, 30 110, 70 90, 180 140, 130 190)' )
    ) AS lline;
-----
LINESTRING(160 40,130 190)
```





图 10-10 最长线

```
SELECT ST_AsText( ST_LongestLine(
    'POLYGON ((190 150, 20 10, 160 70, 190 150))',
    ST_Buffer('POINT(80 160)', 30)
) ) AS llinewkt;
-----
LINESTRING(20 10,105.3073372946034 186.95518130045156)
```



Longest line across a single geometry. The length of the line is equal to the Maximum Distance. The endpoints of the line lie on the Minimum Bounding Circle.

```
SELECT ST_AsText( ST_LongestLine( geom, geom)) AS llinewkt,
       ST_MaxDistance( geom, geom) AS max_dist,
       ST_Length( ST_LongestLine(geom, geom)) AS lenll
FROM (SELECT 'POLYGON ((40 180, 110 160, 180 180, 180 120, 140 90, 160 40, 80 10, 70 40, 20 50, 40 180),
       (60 140, 99 77.5, 90 140, 60 140))'::geometry AS geom) AS t;

 llinewkt      |      max_dist      |      lenll
-----+-----+-----
LINESTRING(20 50,180 180) | 206.15528128088303 | 206.15528128088303
```



ST_MaxDistance, ST_ShortestLine, ST_3DLongestLine, ST_MinimumBoundingCircle

7.12.17 ST_3DLongestLine

ST_3DLongestLine — 3D longest line.

Synopsis

```
geometry ST_3DLongestLine(geometry g1, geometry g2);
```



3 3 (longest) . , 3
 . g1 g2 . 3
 ST_3DMaxDistance g1 g2 .

2.0.0 ☒☒☒☒☒☒☒☒☒☒☒.

Figure 2.2.0: 2D plot of Z vs X , (Z vs X with $Z = 0$ highlighted) 2D plot of Z vs Y . 2D vs 3D plot, Z vs X vs Y with $Z = 0$ highlighted.

- ✔ This function supports 3d and will not drop the z-index.
- ✔ This function supports Polyhedral surfaces.

[illegible]

```
SELECT ST_AsEWKT(ST_3DLongestLine(line,pt)) AS lol3d_line_pt,
       ST_AsEWKT(ST_LongestLine(line,pt)) As lol2d_line_pt
FROM (SELECT 'POINT(100 100 30) '::geometry As pt,
            'LINESTRING (20 80 20, 98 190 1, 110 180 3, 50 75 1000) ':: ↵
      geometry As line
      ) As foo;
```

lol3d_line_pt	lol2d_line_pt
LINESTRING(50 75 1000,100 100 30)	LINESTRING(98 190,100 100)

3D, 2D 最长线

```
SELECT ST_AsEWKT(ST_3DLongestLine(line,pt)) AS lol3d_line_pt,
       ST_AsEWKT(ST_LongestLine(line,pt)) As lol2d_line_pt
FROM (SELECT 'MULTIPOINT(100 100 30, 50 74 1000) '::geometry As pt,
            'LINESTRING (20 80 20, 98 190 1, 110 180 3, 50 75 900) '::
            geometry As line
      ) As foo;
```

lol3d_line_pt		lol2d_line_pt
-----+-----		
LINESTRING(98 190 1,50 74 1000)		LINESTRING(98 190,50 74)

3D, 2D 最长多线

```
SELECT ST_AsEWKT(ST_3DLongestLine(poly, mline)) As lol3d,
       ST_AsEWKT(ST_LongestLine(poly, mline)) As lol2d
FROM (SELECT ST_GeomFromEWKT('POLYGON((175 150 5, 20 40 5, 35 45 5, 50 60 5,
100 100 5, 175 150 5))') As poly,
       ST_GeomFromEWKT('MULTILINESTRING((175 155 2, 20 40 20, 50 60 -2, 125
100 1, 175 155 1),
       (1 10 2, 5 20 1))') As mline ) As foo;
```

lol3d		lol2d
-----+-----		
LINESTRING(175 150 5,1 10 2)		LINESTRING(175 150,1 10)

ST_3DClosestPoint, ST_3DDistance, ST_LongestLine, ST_3DShortestLine, ST_3DMaxDistance

7.12.18 ST_MaxDistance

ST_MaxDistance — 返回 2 个几何对象之间的最大距离。

Synopsis

float **ST_MaxDistance**(geometry g1, geometry g2);

3D

返回 2 个 3D 几何对象之间的最大距离。g1 与 g2 可以是点、线、面。

返回 2 个 2D 几何对象之间的最大距离。g1 与 g2 可以是点、线、面。

1.5.0 引入。

3D

3D 几何对象

```
SELECT ST_MaxDistance('POINT(0 0)::geometry', 'LINESTRING ( 2 0, 0 2 ) '::geometry);
-----
2

SELECT ST_MaxDistance('POINT(0 0)::geometry', 'LINESTRING ( 2 2, 2 2 ) '::geometry);
-----
2.82842712474619
```

Maximum distance between vertices of a single geometry.

```
SELECT ST_MaxDistance('POLYGON ((10 10, 10 0, 0 0, 10 10))'::geometry,  
                      'POLYGON ((10 10, 10 0, 0 0, 10 10))'::geometry);  
-----  
14.142135623730951
```



ST Distance, ST LongestLine, ST DFullyWithin

7.12.19 ST_3DMaxDistance

ST_3DMaxDistance — , (SRS) 3

Synopsis

```
float ST_3DMaxDistance(geometry g1, geometry g2);
```


□□□□□□□□, □□□□□□□ 3 □□□□□□□□□□□□□□□□□□□□□□□□ (SRS □□) □□□□□□□.

- ✔ This function supports 3d and will not drop the z-index.
- ✔ This function supports Polyhedral surfaces.

2.0.0 ☒☒☒☒☒☒☒☒☒☒☒.

OpenGL: 2.2.0 Mesa 21.0.3, 2D 3D GL_VERSION GL_SL GL_CORE GL_ES $\text{GL\_EXT\_ARB\_TEXTURE\_SHADER\_TEXTURE_LM}$.



```
-- Geometry example - units in meters (SRID: 2163 US National Atlas Equal area) (3D point and line compared 2D point and line)
-- Note: currently no vertical datum support so Z is not transformed and assumed to be same units as final.
SELECT ST_3DMaxDistance(
    ST_Transform(ST_GeomFromEWKT('SRID=4326;POINT(-72.1235 42.3521 10000)'),2163),
    ST_Transform(ST_GeomFromEWKT('SRID=4326;LINESTRING(-72.1260 42.45 15, -72.123 42.1546 20)'),2163)
) As dist_3d,
ST_MaxDistance(
```

```

        ST_Transform(ST_GeomFromEWKT('SRID=4326;POINT(-72.1235 42.3521 ↵
        10000)'),2163),
        ST_Transform(ST_GeomFromEWKT('SRID=4326;LINESTRING(-72.1260 42.45 ↵
        15, -72.123 42.1546 20)'),2163)
    ) As dist_2d;

    dist_3d      |      dist_2d
-----+-----
24383.7467488441 | 22247.8472107251

```

函数

[ST_Distance](#), [ST_3DDWithin](#), [ST_3DMaxDistance](#), [ST_Transform](#)

7.12.20 ST_MinimumClearance

`ST_MinimumClearance` — 返回几何体的健壮性 (robustness) 和最小 clearance (clearance) 值。

Synopsis

```
float ST_MinimumClearance(geometry g);
```

函数

(返回的) `ST_IsValid` 和 (返回的) `ST_IsSimple` 函数返回布尔值，表示几何体是否有效 (WKT, KML, GML GeoJSON 等) 和是否简单 (MapInfo TAB 等)。如果返回值为假，则表示几何体无效或不是简单几何体。

The minimum clearance is a quantitative measure of a geometry's robustness to change in coordinate precision. It is the largest distance by which vertices of the geometry can be moved without creating an invalid geometry. Larger values of minimum clearance indicate greater robustness.

函数返回两个值，分别是健壮性和最小 clearance：

- 健壮性：返回值的 2 倍。
- 最小 clearance：返回值的平方根。

为了避免精度损失导致的有效性 issues，[ST_ReducePrecision](#) 可以减少坐标精度，同时确保多边形几何体保持有效。

2.3.0 版本更新

函数

```

SELECT ST_MinimumClearance('POLYGON ((0 0, 1 0, 1 1, 0.5 3.2e-4, 0 0))');
st_minimumclearance
-----
0.00032

```


返回

[ST_MinimumClearanceLine](#), [ST_Crosses](#), [ST_Dimension](#), [ST_Intersects](#)

7.12.21 ST_MinimumClearanceLine

`ST_MinimumClearanceLine` — 返回 2 个点的 LineString，表示几何体的最小 clearance。

Synopsis

Geometry **ST_MinimumClearanceLine**(geometry g);

返回

Returns the two-point LineString spanning a geometry's minimum clearance. If the geometry does not have a minimum clearance, LINESTRING EMPTY is returned.

GEOS 版本

2.3.0 版本。GEOS 3.6.0 版本。

返回

```
SELECT ST_AsText(ST_MinimumClearanceLine('POLYGON ((0 0, 1 0, 1 1, 0.5 3.2e-4, 0 0))'));
-----
LINESTRING(0.5 0.00032,0.5 0)
```

返回

[ST_MinimumClearance](#)

7.12.22 ST_Perimeter

`ST_Perimeter` — Returns the length of the boundary of a polygonal geometry or geography.

Synopsis

float **ST_Perimeter**(geometry g1);
float **ST_Perimeter**(geography geog, boolean use_spheroid = true);

返回

对于 ST_Surface, ST_MultiSurface(几何体, 几何体) 返回 2 个点的 LineString。返回 0 个点的 LineString。返回 [ST_Length](#) 返回的 LineString。返回的 LineString 是闭合的。

For geography types, the calculations are performed using the inverse geodesic problem, where perimeter units are in meters. If PostGIS is compiled with PROJ version 4.8.0 or later, the spheroid


```
FROM ST_GeogFromText('MULTIPOLYGON((( -71.1044543107478 42.340674480411, -71.1044542869917 ↵
    42.3406744369506,
    -71.1044553562977 42.340673886454, -71.1044543107478 42.340674480411))),
    (( -71.1044543107478 42.340674480411, -71.1044860600303 42.3407237015564, -71.1045215770124 ↵
    42.3407653385914,
    -71.1045498002983 42.3407946553165, -71.1045611902745 42.3408058316308, -71.1046016507427 ↵
    42.340837442371,
    -71.104617893173 42.3408475056957, -71.1048586153981 42.3409875993595, -71.1048736143677 ↵
    42.3409959528211,
    -71.1048878050242 42.3410084812078, -71.1044020965803 42.3414730072048,
    -71.1039672113619 42.3412202916693, -71.1037740497748 42.3410666421308,
    -71.1044280218456 42.3406894151355, -71.1044543107478 42.340674480411))))') As geog;
```

per_meters	per_sphere_meters	per_ft
257.634283683311	257.412311446337	845.256836231335



ST GeogFromText, ST GeomFromText, ST Length

7.12.23 ST Perimeter2D

ST_Perimeter2D — Returns the 2D perimeter of a polygonal geometry. Alias for ST_Perimeter.

Synopsis

```
float ST_Perimeter2D(geometry geomA);
```

[illegible]

Note

```

XXXXXXXXXX ST_Perimeter XXXXXXXXXX. XXXXXXXXXX ST_Perimeter XXXXXXXXXXXXXXXXXXXX
XXXXXXXXXXXXXXXXXXXX. XXXXXXXXXXXXXXXXXXXX.

```



ST Perimeter

7.12.24 ST 3DPerimeter

ST 3DPerimeter — .

Synopsis

```
float ST_3DPerimeter(geometry geomA);
```

函数

返回几何体的 3D 周长。2D 周长使用 `ST_Perimeter2D` 函数。



This function supports 3d and will not drop the z-index.



This method implements the SQL/MM specification. SQL-MM ISO/IEC 13249-3: 8.1, 10.5

版本: 2.0.0 函数名: `ST_Perimeter3D` 返回类型: `double`。

函数

以下 SQL 查询演示了 `ST_Perimeter3D` 函数的使用。

```
SELECT ST_3DPerimeter(geom), ST_Perimeter2d(geom), ST_Perimeter(geom) FROM
      (SELECT ST_GeomFromEWKT('SRID=2249;POLYGON((743238 2967416 2,743238 2967450 1,
743265.625 2967416 1,743238 2967416 2))') As geom) As foo;
```

ST_3DPerimeter	st_perimeter2d	st_perimeter
105.465793597674	105.432997272188	105.432997272188

函数

`ST_GeomFromEWKT`, `ST_Perimeter`, `ST_Perimeter2D`

7.12.25 ST_ShortestLine

`ST_ShortestLine` — 返回两个几何体之间的最短 2D 线。

Synopsis

```
geometry ST_ShortestLine(geometry geom1, geometry geom2);
geography ST_ShortestLine(geography geom1, geography geom2, boolean use_spheroid = true);
```


函数

返回两个几何体之间的 2D 最短线。返回的线从 `geom1` 开始并在 `geom2` 结束。如果 `geom1` 和 `geom2` 相交，则结果是具有开始和结束于交点的线。线的长度与 `ST_Distance` 返回的 `g1` 和 `g2` 相同。


增强: 3.4.0 - 支持 geography。

1.5.0 函数名: `ST_ShortestLine`。

图例

*Shortest line between Point and LineString*

```
SELECT ST_AsText( ST_ShortestLine(
    'POINT (160 40)',
    'LINESTRING (10 30, 50 50, 30 110, 70 90, 180 140, 130 190)')
) As sline;
-----
LINESTRING(160 40,125.75342465753425 115.34246575342466)
```

*Shortest line between Polygons*

```
SELECT ST_AsText( ST_ShortestLine(
    'POLYGON ((190 150, 20 10, 160 70, 190 150))',
    ST_Buffer('POINT(80 160)', 30)
) ) AS llinevkt;
-----
LINESTRING(131.59149149528952 101.89887534906197,101.21320343559644 138.78679656440357)
```


3D, 2D 最短距离

```
SELECT ST_AsEWKT(ST_3DShortestLine(line,pt)) AS shl3d_line_pt,
       ST_AsEWKT(ST_ShortestLine(line,pt)) As shl2d_line_pt
FROM (SELECT 'MULTIPOINT(100 100 30, 50 74 1000) '::geometry As pt,
            'LINESTRING (20 80 20, 98 190 1, 110 180 3, 50 75 900) '::
            geometry As line
      ) As foo;
```

shl2d_line_pt	shl3d_line_pt	
		←

LINESTRING(54.6993798867619 128.935022917228 11.5475869506606,100 100 30) | LINESTRING
(50 75 50 74)

3D, 2D 最短距离

```
SELECT ST_AsEWKT(ST_3DShortestLine(poly, mline)) As shl3d,
       ST_AsEWKT(ST_ShortestLine(poly, mline)) As shl2d
FROM (SELECT ST_GeomFromEWKT('POLYGON((175 150 5, 20 40 5, 35 45 5, 50 60 5,
100 100 5, 175 150 5))') As poly,
       ST_GeomFromEWKT('MULTILINESTRING((175 155 2, 20 40 20, 50 60 -2, 125
100 1, 175 155 1),
       (1 10 2, 5 20 1))') As mline ) As foo;
```

shl3d ←

| shl2d

LINESTRING(39.993580415989 54.1889925532825 5,40.4078575708294 53.6052383805529
5.03423778139177) | LINESTRING(20 40,20 40)

3D

ST_3DClosestPoint, ST_3DDistance, ST_LongestLine, ST_ShortestLine, ST_3DMaxDistance

7.13 Overlay Functions

7.13.1 ST_ClipByBox2D

ST_ClipByBox2D — Computes the portion of a geometry falling within a rectangle.

Synopsis

geometry **ST_ClipByBox2D**(geometry geom, box2d box);

3D

Clips a geometry by a 2D box in a fast and tolerant but possibly invalid way. Topologically invalid input geometries do not result in exceptions being thrown. The output geometry is not guaranteed to be valid (in particular, self-intersections for a polygon may be introduced).

GEOS 3.10.0

2.2.0 3D 最短距离。

☒☒

```
-- Rely on implicit cast from geometry to box2d for the second parameter
SELECT ST_ClipByBox2D(geom, ST_MakeEnvelope(0,0,10,10)) FROM mytab;
```

☒☒

[ST_Intersection](#), [ST_MakeBox2D](#), [ST_MakeEnvelope](#)

7.13.2 ST_Difference

ST_Difference — Computes a geometry representing the part of geometry A that does not intersect geometry B.

Synopsis

geometry **ST_Difference**(geometry geomA, geometry geomB, float8 gridSize = -1);

☒☒

Returns a geometry representing the part of geometry A that does not intersect geometry B. This is equivalent to $A - \text{ST\_Intersection}(A,B)$. If A is completely contained in B then an empty atomic geometry of appropriate type is returned.



Note

This is the only overlay function where input order matters. **ST_Difference**(A, B) always returns a portion of A.

If the optional **gridSize** parameter is given (GEOS-3.9.0 or higher required), all result vertices are guaranteed to fall on a grid of the specified size. For the operation to give predictable results all the input vertices must fall already on the specified grid, see [ST_ReducePrecision](#).

GEOS 3.10.0

Enhanced: 3.1.0 accept a **gridSize** parameter.

Requires GEOS >= 3.9.0 to use the **gridSize** parameter.



This method implements the [OGC Simple Features Implementation Specification for SQL 1.1. s2.1.1.3](#)




This method implements the SQL/MM specification. SQL-MM 3: 5.1.20



This function supports 3d and will not drop the z-index. However, the result is computed using XY only. The result Z values are copied, averaged or interpolated.

图图



The difference of 2D linestrings.

```
SELECT ST_AsText(
  ST_Difference(
    'LINESTRING(50 100, 50 200)::geometry',
    'LINESTRING(50 50, 50 150)::geometry'
  )
);

st_astext
-----
LINESTRING(50 150,50 200)
```

The difference of 3D points.

```
SELECT ST_AsEWKT( ST_Difference(
  'MULTIPOINT(-118.58 38.38 5,-118.60 38.329 6,-118.614 38.281 7)' :: geometry,
  'POINT(-118.614 38.281 5)' :: geometry
) );

st_asewkt
-----
MULTIPOINT(-118.6 38.329 6,-118.58 38.38 5)
```

图图

[ST_SymDifference](#), [ST_Intersection](#), [ST_Union](#), [ST_ReducePrecision](#)

7.13.3 ST_Intersection

ST_Intersection — Computes a geometry representing the shared portion of geometries A and B.

Synopsis

```
geometry ST_Intersection( geometry geomA , geometry geomB , float8 gridSize = -1 );
geography ST_Intersection( geography geogA , geography geogB );
```

国国

Returns a geometry representing the point-set intersection of two geometries. In other words, that portion of geometry A and geometry B that is shared between the two geometries.

If the geometries have no points in common (i.e. are disjoint) then an empty atomic geometry of appropriate type is returned.

If the optional `gridSize` parameter is given (GEOS-3.9.0 or higher required), all result vertices are guaranteed to fall on a grid of the specified size. For the operation to give predictable results all the input vertices must fall already on the specified grid, see [ST_ReducePrecision](#).

`ST_Intersection` in conjunction with [ST_Intersects](#) is useful for clipping geometries such as in bounding box, buffer, or region queries where you only require the portion of a geometry that is inside a country or region of interest.

Note



For geography this is a thin wrapper around the geometry implementation. It first determines the best SRID that fits the bounding box of the 2 geography objects (if geography objects are within one half zone UTM but not same UTM will pick one of those) (favoring UTM or Lambert Azimuthal Equal Area (LAEA) north/south pole, and falling back on mercator in worst case scenario) and then intersection in that best fit planar spatial ref and retransforms back to WGS84 geography.



Warning

This function will drop the M coordinate values if present.



Warning

If working with 3D geometries, you may want to use SFGCAL based [ST_3DIntersection](#) which does a proper 3D intersection for 3D geometries. Although this function works with Z-coordinate, it does an averaging of Z-Coordinate.

GEOS 国国国国国国

Enhanced: 3.1.0 accept a `gridSize` parameter

Requires GEOS >= 3.9.0 to use the `gridSize` parameter

Changed: 3.0.0 does not depend on SFCGAL.

Availability: 1.5 support for geography data type was introduced.



This method implements the [OGC Simple Features Implementation Specification for SQL 1.1. s2.1.1.3](#)



This method implements the SQL/MM specification. SQL-MM 3: 5.1.18



This function supports 3d and will not drop the z-index. However, the result is computed using XY only. The result Z values are copied, averaged or interpolated.

图

```
SELECT ST_AsText(ST_Intersection('POINT(0 0)::geometry, 'LINESTRING ( 2 0, 0 2 )'::
  geometry));
  st_astext
-----
GEOMETRYCOLLECTION EMPTY

SELECT ST_AsText(ST_Intersection('POINT(0 0)::geometry, 'LINESTRING ( 0 0, 0 2 )'::
  geometry));
  st_astext
-----
POINT(0 0)
```

Clip all lines (trails) by country. Here we assume country geom are POLYGON or MULTIPOLYGONS. NOTE: we are only keeping intersections that result in a LINESTRING or MULTILINESTRING because we don't care about trails that just share a point. The dump is needed to expand a geometry collection into individual single MULT* parts. The below is fairly generic and will work for polys, etc. by just changing the where clause.

```
select clipped.gid, clipped.f_name, clipped_geom
from (
    select trails.gid, trails.f_name,
        (ST_Dump(ST_Intersection(country.geom, trails.geom))).geom clipped_geom
    from country
        inner join trails on ST_Intersects(country.geom, trails.geom)
    ) as clipped
where ST_Dimension(clipped.clipped_geom) = 1;
```

For polys e.g. polygon landmarks, you can also use the sometimes faster hack that buffering anything by 0.0 except a polygon results in an empty geometry collection. (So a geometry collection containing polys, lines and points buffered by 0.0 would only leave the polygons and dissolve the collection shell.)

```
select poly.gid,
    ST_Multi(
        ST_Buffer(
            ST_Intersection(country.geom, poly.geom),
            0.0
        )
    ) clipped_geom
from country
    inner join poly on ST_Intersects(country.geom, poly.geom)
where not ST_IsEmpty(ST_Buffer(ST_Intersection(country.geom, poly.geom), 0.0));
```

Examples: 2.5Dish

Note this is not a true intersection, compare to the same example using [ST_3DIntersection](#).

```
select ST_AsText(ST_Intersection(linestring, polygon)) As wkt
from ST_GeomFromText('LINESTRING Z (2 2 6,1.5 1.5 7,1 1 8,0.5 0.5 8,0 0 10)') AS
  linestring
CROSS JOIN ST_GeomFromText('POLYGON((0 0 8, 0 1 8, 1 1 8, 1 0 8, 0 0 8))') AS polygon;

      st_astext
-----
LINESTRING Z (1 1 8,0.5 0.5 8,0 0 10)
```

☒☒

[ST_3DIntersection](#), [ST_Difference](#), [ST_Union](#), [ST_ClipByBox2D](#), [ST_Dimension](#), [ST_Dump](#), [ST_Force2D](#), [ST_SymDifference](#), [ST_Intersects](#), [ST_Multi](#), [ST_ReducePrecision](#)

7.13.4 ST_MemUnion

`ST_MemUnion` — Aggregate function which unions geometries in a memory-efficient but slower way

Synopsis

geometry **ST_MemUnion**(geometry set geomfield);

☒☒

An aggregate function that unions the input geometries, merging them to produce a result geometry with no overlaps. The output may be a single geometry, a MultiGeometry, or a Geometry Collection.



Note

Produces the same result as [ST_Union](#), but uses less memory and more processor time. This aggregate function works by unioning the geometries incrementally, as opposed to the `ST_Union` aggregate which first accumulates an array and then unions the contents using a fast algorithm.



This function supports 3d and will not drop the z-index. However, the result is computed using XY only. The result Z values are copied, averaged or interpolated.

☒☒

```
SELECT id,
       ST_MemUnion(geom) as singlegeom
FROM sometable f
GROUP BY id;
```

☒☒

[ST_Union](#)

7.13.5 ST_Node

`ST_Node` — Nodes a collection of lines.

Synopsis

geometry **ST_Node**(geometry geom);



Returns a (Multi)LineString representing the fully noded version of a collection of linestrings. The noding preserves all of the input nodes, and introduces the least possible number of new nodes. The resulting linework is dissolved (duplicate lines are removed).

This is a good way to create fully-noded linework suitable for use as input to [ST_Polygonize](#).

[ST_UnaryUnion](#) can also be used to node and dissolve linework. It provides an option to specify a gridSize, which can provide simpler and more robust output. See also [ST_Union](#) for an aggregate variant.



This function supports 3d and will not drop the z-index.

GEOS 国国国国国

2.0.0 国国国国国国国国国国国国.

Changed: 2.4.0 this function uses GEOSNode internally instead of GEOSUnaryUnion. This may cause the resulting linestrings to have a different order and direction compared to PostGIS < 2.4.



Noding a 3D LineString which self-intersects

```
SELECT ST_AsText(
    ST_Node('LINESTRINGZ(0 0 0, 10 10 10, 0 10 5, 10 0 3)::geometry')
) As output;
-----
MULTILINESTRING Z ((0 0 0,5 5 4.5),(5 5 4.5,10 10 10,0 10 5,5 5 4.5),(5 5 4.5,10 0 3))
```

Noding two LineStrings which share common linework. Note that the result linework is dissolved.

```
SELECT ST_AsText(
    ST_Node('MULTILINESTRING ((2 5, 2 1, 7 1), (6 1, 4 1, 2 3, 2 5))::geometry')
) As output;
-----
MULTILINESTRING((2 5,2 3),(2 3,2 1,4 1),(4 1,2 3),(4 1,6 1),(6 1,7 1))
```



[ST_UnaryUnion](#), [ST_AsBinary](#)

7.13.6 ST_Split

ST_Split — Returns a collection of geometries created by splitting a geometry by another geometry.

Synopsis

geometry **ST_Split**(geometry input, geometry blade);



The function supports splitting a `LineString` by a `(Multi)Point`, `(Multi)LineString` or `(Multi)Polygon` boundary, or a `(Multi)Polygon` by a `LineString`. When a `(Multi)Polygon` is used as the blade, its linear components (the boundary) are used for splitting the input. The result geometry is always a collection.

This function is in a sense the opposite of `ST_Union`. Applying `ST_Union` to the returned collection should theoretically yield the original geometry (although due to numerical rounding this may not be exactly the case).



Note

If the the input and blade do not intersect due to numerical precision issues, the input may not be split as expected. To avoid this situation it may be necessary to snap the input to the blade first, using `ST_Snap` with a small tolerance.


Availability: 2.0.0 requires GEOS

Enhanced: 2.2.0 support for splitting a line by a multiline, a multipoint or (multi)polygon boundary was introduced.

Enhanced: 2.5.0 support for splitting a polygon by a multiline was introduced.




Split a Polygon by a Line.



```
SELECT ST_AsText( ST_Split(
    ST_Buffer(ST_GeomFromText('POINT(100 90)'), 50), -- circle
    ST_MakeLine(ST_Point(10, 10),ST_Point(190, 190)) -- line
));

-- result --
GEOMETRYCOLLECTION(
  POLYGON((150 90,149.039264020162 80.2454838991936,146.193976625564 70.8658283817455,...),
  POLYGON(...))
)
```

Split a MultiLineString by a Point, where the point lies exactly on both LineStrings elements.



```
SELECT ST_AsText(ST_Split(
  'MULTILINESTRING((10 10, 190 190), (15 15, 30 30, 100 90))',
  ST_Point(30,30))) As split;

split
-----
GEOMETRYCOLLECTION(
  LINESTRING(10 10,30 30),
  LINESTRING(30 30,190 190),
  LINESTRING(15 15,30 30),
  LINESTRING(30 30,100 90)
)
```

Split a LineString by a Point, where the point does not lie exactly on the line. Shows using **ST_Snap** to snap the line to the point to allow it to be split.

```
WITH data AS (SELECT
  'LINESTRING(0 0, 100 100)::geometry AS line,
  'POINT(51 50):: geometry AS point
)
SELECT ST_AsText( ST_Split( ST_Snap(line, point, 1), point)) AS snapped_split,
       ST_AsText( ST_Split(line, point)) AS not_snapped_not_split
FROM data;
```

snapped_split	not_snapped_not_split
GEOMETRYCOLLECTION(LINESTRING(0 0,51 50),LINESTRING(51 50,100 100))	GEOMETRYCOLLECTION(LINESTRING(0 0,100 100))



ST_Snap, ST_AsBinary

7.13.7 ST_Subdivide

ST_Subdivide — Computes a rectilinear subdivision of a geometry.

Synopsis

```
setof geometry ST_Subdivide(geometry geom, integer max_vertices=256, float8 gridSize = -1);
```

国国

Returns a set of geometries that are the result of dividing geom into parts using rectilinear lines, with each part containing no more than max_vertices.

max_vertices must be 5 or more, as 5 points are needed to represent a closed box.

If the optional gridSize parameter is given (GEOS-3.9.0 or higher required), all result vertices are guaranteed to fall on a grid of the specified size. For the operation to give predictable results all the input vertices must fall already on the specified grid, see [ST_ReducePrecision](#).

Point-in-polygon and other spatial operations are normally faster for indexed subdivided datasets. Since the bounding boxes for the parts usually cover a smaller area than the original geometry bbox, index queries produce fewer "hit" cases. The "hit" cases are faster because the spatial operations executed by the index recheck process fewer points.



Note

This is a [set-returning function](#) (SRF) that return a set of rows containing single geometry values. It can be used in a SELECT list or a FROM clause to produce a result set with one record for each result geometry.

GEOS 国国国国国

2.2.0 国国国国国国国国国国国国.


Enhanced: 2.5.0 reuses existing points on polygon split, vertex count is lowered from 8 to 5.

Enhanced: 3.1.0 accept a gridSize parameter.

Requires GEOS >= 3.9.0 to use the gridSize parameter

国国

Example: Subdivide a polygon into parts with no more than 10 vertices, and assign each part a unique id.




Subdivided to maximum 10 vertices

```
SELECT row_number() OVER() As rn, ST_AsText(geom) As wkt
FROM (SELECT ST_SubDivide(
        'POLYGON((132 10,119 23,85 35,68 29,66 28,49 42,32 56,22 64,32 110,40 119,36 150,
        57 158,75 171,92 182,114 184,132 186,146 178,176 184,179 162,184 141,190 122,
        190 100,185 79,186 56,186 52,178 34,168 18,147 13,132 10))'::geometry,10)) AS f(
        geom);
```

rn	b'' b''	wkt
1	b'' b''	POLYGON((119 23,85 35,68 29,66 28,32 56,22 64,29.8260869565217 100,119 100,119 23))
2	b'' b''	POLYGON((132 10,119 23,119 56,186 56,186 52,178 34,168 18,147 13,132 10))
3	b'' b''	POLYGON((119 56,119 100,190 100,185 79,186 56,119 56))
4	b'' b''	POLYGON((29.8260869565217 100,32 110,40 119,36 150,57 158,75 171,92 182,114 184,114 100,29.8260869565217 100))
5	b'' b''	POLYGON((114 184,132 186,146 178,176 184,179 162,184 141,190 122,190 100,114 100,114 184))

Example: Densify a long geography line using `ST_Segmentize(geography, distance)`, and use `ST_Subdivide` to split the resulting line into sublines of 8 vertices.



The densified and split lines.

```
SELECT ST_AsText( ST_Subdivide(
    ST_Segmentize('LINESTRING(0 0, 85 85)::geography,
    1200000)::geometry, 8));
```

```
LINESTRING(0 0,0.487578359029357 5.57659056746196,0.984542144675897 ↵
    11.1527721155093,1.50101059639722 16.7281035483571,1.94532113630331 21.25)
LINESTRING(1.94532113630331 21.25,2.04869538062779 22.3020741387339,2.64204641967673 ↵
    27.8740533545155,3.29994062412787 33.443216802941,4.04836719489742 ↵
    39.0084282520239,4.59890468420694 42.5)
LINESTRING(4.59890468420694 42.5,4.92498503922732 44.5680389206321,5.98737409390639 ↵
    50.1195229244701,7.3290919767674 55.6587646879025,8.79638749938413 60.1969505994924)
LINESTRING(8.79638749938413 60.1969505994924,9.11375579533779 ↵
    61.1785363177625,11.6558166691368 66.6648504160202,15.642041247655 ↵
    72.0867690601745,22.8716627200212 77.3609628116894,24.6991785131552 77.8939011989848)
LINESTRING(24.6991785131552 77.8939011989848,39.4046096622744 ↵
    82.1822848017636,44.7994523421035 82.5156766227011)
LINESTRING(44.7994523421035 82.5156766227011,85 85)
```

Example: Subdivide the complex geometries of a table in-place. The original geometry records are deleted from the source table, and new records for each subdivided result geometry are inserted.

```
WITH complex_areas_to_subdivide AS (
    DELETE from polygons_table
    WHERE ST_NPoints(geom)
> 255
    RETURNING id, column1, column2, column3, geom
)
INSERT INTO polygons_table (fid, column1, column2, column3, geom)
    SELECT fid, column1, column2, column3,
        ST_Subdivide(geom, 255) as geom
    FROM complex_areas_to_subdivide;
```

Example: Create a new table containing subdivided geometries, retaining the key of the original geometry so that the new table can be joined to the source table. Since ST_Subdivide is a set-returning (table) function that returns a set of single-value rows, this syntax automatically produces a table with one row for each result part.

```
CREATE TABLE subdivided_geoms AS
```

```
SELECT pkey, ST_Subdivide(geom) AS geom
FROM original_geoms;
```

☒☒

[ST_ClipByBox2D](#), [ST_Segmentize](#), [ST_Split](#), [ST_NPoints](#), [ST_ReducePrecision](#)

7.13.8 ST_SymDifference

ST_SymDifference — Computes a geometry representing the portions of geometries A and B that do not intersect.

Synopsis

geometry **ST_SymDifference**(geometry geomA, geometry geomB, float8 gridSize = -1);

☒☒

Returns a geometry representing the portions of geometries A and B that do not intersect. This is equivalent to $ST\_Union(A,B) - ST\_Intersection(A,B)$. It is called a symmetric difference because $ST\_SymDifference(A,B) = ST\_SymDifference(B,A)$.

If the optional `gridSize` parameter is given (GEOS-3.9.0 or higher required), all result vertices are guaranteed to fall on a grid of the specified size. For the operation to give predictable results all the input vertices must fall already on the specified grid, see [ST_ReducePrecision](#).

GEOS ☒☒☒☒☒

Enhanced: 3.1.0 accept a `gridSize` parameter.


Requires GEOS $\geq$ 3.9.0 to use the `gridSize` parameter

✔ This method implements the [OGC Simple Features Implementation Specification for SQL 1.1. s2.1.1.3](#)

✔ This method implements the SQL/MM specification. SQL-MM 3: 5.1.21

✔ This function supports 3d and will not drop the z-index. However, the result is computed using XY only. The result Z values are copied, averaged or interpolated.

☒☒



```
--Safe for 2d - symmetric difference of 2 linestrings
SELECT ST_AsText(
  ST_SymDifference(
    ST_GeomFromText('LINESTRING(50 100, 50 200)'),
    ST_GeomFromText('LINESTRING(50 50, 50 150)')
  )
);

st_astext
-----
MULTILINESTRING((50 150,50 200),(50 50,50 100))
```

```
--When used in 3d doesn't quite do the right thing
SELECT ST_AsEWKT(ST_SymDifference(ST_GeomFromEWKT('LINESTRING(1 2 1, 1 4 2)'),
  ST_GeomFromEWKT('LINESTRING(1 1 3, 1 3 4)')));

st_astext
-----
MULTILINESTRING((1 3 2.75,1 4 2),(1 1 3,1 2 2.25))
```

国国

[ST_Difference](#), [ST_Intersection](#), [ST_Union](#), [ST_ReducePrecision](#)

7.13.9 ST_UnaryUnion

ST_UnaryUnion — Computes the union of the components of a single geometry.

Synopsis

geometry **ST_UnaryUnion**(geometry geom, float8 gridSize = -1);

国国

A single-input variant of **ST_Union**. The input may be a single geometry, a MultiGeometry, or a GeometryCollection. The union is applied to the individual elements of the input.

This function can be used to fix MultiPolygons which are invalid due to overlapping components. However, the input components must each be valid. An invalid input component such as a bow-tie polygon may cause an error. For this reason it may be better to use **ST_MakeValid**.

Another use of this function is to node and dissolve a collection of linestrings which cross or overlap to make them **simple**. (**ST_Node** also does this, but it does not provide the `gridSize` option.)

It is possible to combine `ST_UnaryUnion` with **ST_Collect** to fine-tune how many geometries are be unioned at once. This allows trading off between memory usage and compute time, striking a balance between `ST_Union` and **ST_MemUnion**.

If the optional `gridSize` parameter is given (GEOS-3.9.0 or higher required), all result vertices are guaranteed to fall on a grid of the specified size. For the operation to give predictable results all the input vertices must fall already on the specified grid, see **ST_ReducePrecision**.

 This function supports 3d and will not drop the z-index. However, the result is computed using XY only. The result Z values are copied, averaged or interpolated.

Enhanced: 3.1.0 accept a `gridSize` parameter.

Requires GEOS >= 3.9.0 to use the `gridSize` parameter

2.0.0 国国国国国国国国国国国国.

国国

ST_Union, **ST_MemUnion**, **ST_MakeValid**, **ST_Collect**, **ST_Node**, **ST_ReducePrecision**

7.13.10 ST_Union

ST_Union — Computes a geometry representing the point-set union of the input geometries.

Synopsis

```
geometry ST_Union(geometry g1, geometry g2);
geometry ST_Union(geometry g1, geometry g2, float8 gridSize);
geometry ST_Union(geometry[] g1_array);
geometry ST_Union(geometry set g1field);
geometry ST_Union(geometry set g1field, float8 gridSize);
```

国国

Unions the input geometries, merging geometry to produce a result geometry with no overlaps. The output may be an atomic geometry, a MultiGeometry, or a Geometry Collection. Comes in several variants:

Two-input variant: returns a geometry that is the union of two input geometries. If either input is NULL, then NULL is returned.

Array variant: returns a geometry that is the union of an array of geometries.

Aggregate variant: returns a geometry that is the union of a rowset of geometries. The `ST_Union()` function is an "aggregate" function in the terminology of PostgreSQL. That means that it operates on

rows of data, in the same way the SUM() and AVG() functions do and like most aggregates, it also ignores NULL geometries.

See [ST_UnaryUnion](#) for a non-aggregate, single-input variant.

The ST_Union array and set variants use the fast Cascaded Union algorithm described in <http://blog.cleverelephant.ca/2009/01/must-faster-unions-in-postgis-14.html>

If the optional gridSize parameter is given (GEOS-3.9.0 or higher required), all result vertices are guaranteed to fall on a grid of the specified size. For the operation to give predictable results all the input vertices must fall already on the specified grid, see [ST_ReducePrecision](#).



Note

[ST_Collect](#) may sometimes be used in place of ST_Union, if the result is not required to be non-overlapping. ST_Collect is usually faster than ST_Union because it performs no processing on the collected geometries.

GEOS 国国国国国

ST_Union creates MultiLineString and does not sew LineStrings into a single LineString. Use [ST_LineMerge](#) to sew LineStrings.

NOTE: this function was formerly called GeomUnion(), which was renamed from "Union" because UNION is an SQL reserved word.

Enhanced: 3.1.0 accept a gridSize parameter.

Requires GEOS >= 3.9.0 to use the gridSize parameter

Changed: 3.0.0 does not depend on SFCGAL.

Availability: 1.4.0 - ST_Union was enhanced. ST_Union(geomarray) was introduced and also faster aggregate collection in PostgreSQL.



This method implements the [OGC Simple Features Implementation Specification for SQL 1.1. s2.1.1.3](#)



Note

Aggregate version is not explicitly defined in OGC SPEC.



This method implements the SQL/MM specification. SQL-MM 3: 5.1.19 the z-index (elevation) when polygons are involved.



This function supports 3d and will not drop the z-index. However, the result is computed using XY only. The result Z values are copied, averaged or interpolated.

国国

Aggregate example

```
SELECT id,
       ST_Union(geom) as singlegeom
FROM sometable f
GROUP BY id;
```

Non-Aggregate example

```
select ST_AsText(ST_Union('POINT(1 2)' :: geometry, 'POINT(-2 3)' :: geometry))

st_astext
-----
MULTIPOINT(-2 3,1 2)

select ST_AsText(ST_Union('POINT(1 2)' :: geometry, 'POINT(1 2)' :: geometry))

st_astext
-----
POINT(1 2)
```

3D example - sort of supports 3D (and with mixed dimensions!)

```
select ST_AsEWKT(ST_Union(geom))
from (
    select 'POLYGON((-7 4.2,-7.1 4.2,-7.1 4.3, -7 4.2))'::geometry geom
    union all
    select 'POINT(5 5 5)'::geometry geom
    union all
    select 'POINT(-2 3 1)'::geometry geom
    union all
    select 'LINESTRING(5 5 5, 10 10 10)'::geometry geom
) as foo;

st_asewkt
-----
GEOMETRYCOLLECTION(POINT(-2 3 1),LINESTRING(5 5 5,10 10 10),POLYGON((-7 4.2 5,-7.1 4.2 5,-7.1 4.3 5,-7 4.2 5)));
```

3d example not mixing dimensions

```
select ST_AsEWKT(ST_Union(geom))
from (
    select 'POLYGON((-7 4.2 2,-7.1 4.2 3,-7.1 4.3 2, -7 4.2 2))'::geometry geom
    union all
    select 'POINT(5 5 5)'::geometry geom
    union all
    select 'POINT(-2 3 1)'::geometry geom
    union all
    select 'LINESTRING(5 5 5, 10 10 10)'::geometry geom
) as foo;

st_asewkt
-----
GEOMETRYCOLLECTION(POINT(-2 3 1),LINESTRING(5 5 5,10 10 10),POLYGON((-7 4.2 2,-7.1 4.2 3,-7.1 4.3 2,-7 4.2 2)));

--Examples using new Array construct
SELECT ST_Union(ARRAY(SELECT geom FROM sometable));

SELECT ST_AsText(ST_Union(ARRAY[ST_GeomFromText('LINESTRING(1 2, 3 4)'),
    ST_GeomFromText('LINESTRING(3 4, 4 5)')])) As wktunion;

--wktunion---
MULTILINESTRING((3 4,4 5),(1 2,3 4))
```

函数

[ST_Collect](#), [ST_UnaryUnion](#), [ST_MemUnion](#), [ST_Intersection](#), [ST_Difference](#), [ST_SymDifference](#), [ST_Reduce](#)

7.14 几何操作

7.14.1 ST_Buffer

ST_Buffer — Computes a geometry covering all points within a given distance from a geometry.

Synopsis

```
geometry ST_Buffer(geometry g1, float radius_of_buffer, text buffer_style_parameters = "");
geometry ST_Buffer(geometry g1, float radius_of_buffer, integer num_seg_quarter_circle);
geography ST_Buffer(geography g1, float radius_of_buffer, text buffer_style_parameters);
geography ST_Buffer(geography g1, float radius_of_buffer, integer num_seg_quarter_circle);
```

描述

Computes a POLYGON or MULTIPOLYGON that represents all points whose distance from a geometry/geography is less than or equal to a given distance. A negative distance shrinks the geometry rather than expanding it. A negative distance may shrink a polygon completely, in which case POLYGON EMPTY is returned. For points and lines negative distances always return empty results.

For geometry, the distance is specified in the units of the Spatial Reference System of the geometry. For geography, the distance is specified in meters.

The optional third parameter controls the buffer accuracy and style. The accuracy of circular arcs in the buffer is specified as the number of line segments used to approximate a quarter circle (default is 8). The buffer style can be specified by providing a list of blank-separated key=value pairs as follows:

- 'quad_segs=#' : number of line segments used to approximate a quarter circle (default is 8).
- 'endcap=round|flat|square' : endcap style (defaults to "round"). 'butt' is accepted as a synonym for 'flat'.
- 'join=round|mitre|bevel' : join style (defaults to "round"). 'miter' is accepted as a synonym for 'mitre'.
- 'mitre_limit=#.#' : mitre ratio limit (only affects mitered join style). 'miter_limit' is accepted as a synonym for 'mitre_limit'.
- 'side=both|left|right' : 'left' or 'right' performs a single-sided buffer on the geometry, with the buffered side relative to the direction of the line. This is only applicable to LINESTRING geometry and does not affect POINT or POLYGON geometries. By default end caps are square.

Note



For geography this is a thin wrapper around the geometry implementation. It determines a planar spatial reference system that best fits the bounding box of the geography object (trying UTM, Lambert Azimuthal Equal Area (LAEA) North/South pole, and finally Mercator). The buffer is computed in the planar space, and then transformed back to WGS84. This may not produce the desired behavior if the input object is much larger than a UTM zone or crosses the dateline

**Note**

Buffer output is always a valid polygonal geometry. Buffer can handle invalid inputs, so buffering by distance 0 is sometimes used as a way of repairing invalid polygons. [ST_MakeValid](#) can also be used for this purpose.

**Note**

Buffering is sometimes used to perform a within-distance search. For this use case it is more efficient to use [ST_DWithin](#).

**Note**

This function ignores the Z dimension. It always gives a 2D result even when used on a 3D geometry.

Enhanced: 2.5.0 - `ST_Buffer` geometry support was enhanced to allow for side buffering specification `side=both|left|right`.

Availability: 1.5 - `ST_Buffer` was enhanced to support different endcaps and join types. These are useful for example to convert road linestrings into polygon roads with flat or square edges instead of rounded edges. Thin wrapper for geography was added.

GEOS 




This method implements the [OGC Simple Features Implementation Specification for SQL 1.1. s2.1.1.3](#)




This method implements the SQL/MM specification. SQL-MM IEC 13249-3: 5.1.30





quad_segs=8 (文档)

```
SELECT ST_Buffer(  
  ST_GeomFromText('POINT(100 90)'),  
  50, 'quad_segs=8');
```



quad_segs=2 (文档)

```
SELECT ST_Buffer(  
  ST_GeomFromText('POINT(100 90)'),  
  50, 'quad_segs=2');
```



endcap=round join=round (文档)

```
SELECT ST_Buffer(  
  ST_GeomFromText(  
    'LINESTRING(50 50,150 150,150 50)'  
  ), 10, 'endcap=round join=round');
```



endcap=square

```
SELECT ST_Buffer(  
  ST_GeomFromText(  
    'LINESTRING(50 50,150 150,150 50)'  
  ), 10, 'endcap=square join=round');
```




join=bevel

```
SELECT ST_Buffer(
  ST_GeomFromText(
    'LINESTRING(50 50,150 150,150 50)'
  ), 10, 'join=bevel');
```



join=mitre mitre_limit=5.0 (简体中文)

```
SELECT ST_Buffer(
  ST_GeomFromText(
    'LINESTRING(50 50,150 150,150 50)'
  ), 10, 'join=mitre mitre_limit=5.0');
```




side=left

```
SELECT ST_Buffer(
  ST_GeomFromText(
    'LINESTRING(50 50,150 150,150 50)'
  ), 10, 'side=left');
```




side=right

```
SELECT ST_Buffer(
  ST_GeomFromText(
    'LINESTRING(50 50,150 150,150 50)'
  ), 10, 'side=right');
```



*right-hand-winding, polygon boundary
side=left*

```
SELECT ST_Buffer(
ST_ForceRHR(
ST_Boundary(
ST_GeomFromText(
'POLYGON ((50 50, 50 150, 150 150, 150 50, 50 50))'),
), 20, 'side=left');
```



*right-hand-winding, polygon boundary
side=right*

```
SELECT ST_Buffer(
ST_ForceRHR(
ST_Boundary(
ST_GeomFromText(
'POLYGON ((50 50, 50 150, 150 150, 150 50, 50 50))'),
), 20, 'side=right');
```

```
--A buffered point approximates a circle
-- A buffered point forcing approximation of (see diagram)
-- 2 points per quarter circle is poly with 8 sides (see diagram)
SELECT ST_NPoints(ST_Buffer(ST_GeomFromText('POINT(100 90)'), 50)) As promisingcircle_pcount,
ST_NPoints(ST_Buffer(ST_GeomFromText('POINT(100 90)'), 50, 2)) As lamecircle_pcount;
```

```
promisingcircle_pcount | lamecircle_pcount
-----+-----
33 | 9
```

```
--A lighter but lamer circle
-- only 2 points per quarter circle is an octagon
--Below is a 100 meter octagon
-- Note coordinates are in NAD 83 long lat which we transform
to Mass state plane meter and then buffer to get measurements in meters;
SELECT ST_AsText(ST_Buffer(
ST_Transform(
ST_SetSRID(ST_Point(-71.063526, 42.35785), 4269), 26986)
, 100, 2)) As octagon;
```

```
-----
POLYGON((236057.59057465 900908.759918696,236028.301252769 900838.049240578,235
957.59057465 900808.759918696,235886.879896532 900838.049240578,235857.59057465
900908.759918696,235886.879896532 900979.470596815,235957.59057465 901008.759918
696,236028.301252769 900979.470596815,236057.59057465 900908.759918696))
```

☒☒

[ST_Collect](#), [ST_DWithin](#), [ST_SetSRID](#), [ST_Transform](#), [ST_Union](#), [ST_MakeValid](#)

7.14.2 ST_BuildArea

ST_BuildArea — Creates a polygonal geometry formed by the linework of a geometry.

Synopsis

geometry **ST_BuildArea**(geometry geom);

☒☒

Creates an areal geometry formed by the constituent linework of the input geometry. The input can be a LineString, MultiLineString, Polygon, MultiPolygon or a GeometryCollection. The result is a Polygon or MultiPolygon, depending on input. If the input linework does not form polygons, NULL is returned.

Unlike [ST_MakePolygon](#), this function accepts rings formed by multiple lines, and can form any number of polygons.

This function converts inner rings into holes. To turn inner rings into polygons as well, use [ST_Polygonize](#).




Note

Input linework must be correctly noded for this function to work properly. [ST_Node](#) can be used to node lines.

If the input linework crosses, this function will produce invalid polygons. [ST_MakeValid](#) can be used to ensure the output is valid.

1.1.0 简体中文版.

☒☒



```
WITH data(geom) AS (VALUES
  ('LINESTRING (180 40, 30 20, 20 90)')::geometry)
,('LINESTRING (180 40, 160 160)')::geometry)
,('LINESTRING (160 160, 80 190, 80 120, 20 90)')::geometry)
,('LINESTRING (80 60, 120 130, 150 80)')::geometry)
,('LINESTRING (80 60, 150 80)')::geometry)
)
SELECT ST_AsText( ST_BuildArea( ST_Collect( geom )))
FROM data;
```

```
-----
POLYGON((180 40,30 20,20 90,80 120,80 190,160 160,180 40),(150 80,120 130,80 60,150 80))
```



Create a donut from two circular polygons

```
SELECT ST_BuildArea(ST_Collect(inring,outring))
FROM (SELECT
  ST_Buffer('POINT(100 90)', 25) As inring,
  ST_Buffer('POINT(100 90)', 50) As outring) As t;
```

☒☒

[ST_Collect](#), [ST_MakePolygon](#), [ST_MakeValid](#), [ST_Node](#), [ST_Polygonize](#), [ST_BdPolyFromText](#), [ST_BdMPolyFromText](#) (wrappers to this function with standard OGC interface)

7.14.3 ST_Centroid

ST_Centroid — 返回几何的质心。

Synopsis

```
geometry ST_Centroid(geometry g1);
geography ST_Centroid(geography g1, boolean use_spheroid = true);
```

☒☒

Computes a point which is the geometric center of mass of a geometry. For [MULTI]POINTS, the centroid is the arithmetic mean of the input coordinates. For [MULTI]LINESTRINGS, the centroid is computed using the weighted length of each line segment. For [MULTI]POLYGONS, the centroid is computed in terms of area. If an empty geometry is supplied, an empty GEOMETRYCOLLECTION is returned. If NULL is supplied, NULL is returned. If CIRCULARSTRING or COMPOUNDCURVE are supplied, they are converted to linestring with CurveToLine first, then same than for LINESTRING

For mixed-dimension input, the result is equal to the centroid of the component Geometries of highest dimension (since the lower-dimension geometries contribute zero "weight" to the centroid).

Note that for polygonal geometries the centroid does not necessarily lie in the interior of the polygon. For example, see the diagram below of the centroid of a C-shaped polygon. To construct a point guaranteed to lie in the interior of a polygon use [ST_PointOnSurface](#).


New in 2.3.0 : supports CIRCULARSTRING and COMPOUNDCURVE (using CurveToLine)


Availability: 2.4.0 support for geography was introduced.

- ✔ This method implements the [OGC Simple Features Implementation Specification for SQL 1.1](#).
- ✔ This method implements the SQL/MM specification. SQL-MM 3: 8.1.4, 9.5.5

☒☒

In the following illustrations the red dot is the centroid of the source geometry.





```
SELECT ST_AsText(ST_Centroid('MULTIPOINT ( -1 0, -1 2, -1 3, -1 4, -1 7, 0 1, 0 3, 1 1, 2
0, 6 0, 7 8, 9 8, 10 6 )'));
```

st_astext
POINT(2.30769230769231 3.30769230769231)

(1 row)

```
SELECT ST_AsText(ST_centroid(g))
FROM ST_GeomFromText('CIRCULARSTRING(0 2, -1 1,0 0, 0.5 0, 1 0, 2 1, 1 2, 0.5 2, 0 2)')
AS g ;
```

ST_AsText(ST_centroid(g))
POINT(0.5 1)

```
SELECT ST_AsText(ST_centroid(g))
FROM ST_GeomFromText('COMPOUNDCURVE(CIRCULARSTRING(0 2, -1 1,0 0),(0 0, 0.5 0, 1 0),
CIRCULARSTRING( 1 0, 2 1, 1 2),(1 2, 0.5 2, 0 2))' ) AS g;
```

ST_AsText(ST_centroid(g))
POINT(0.5 1)



ST_PointOnSurface, ST_GeometricMedian

7.14.4 ST_ChaikinSmoothing

ST_ChaikinSmoothing — Returns a smoothed version of a geometry, using the Chaikin algorithm

Synopsis

geometry **ST_ChaikinSmoothing**(geometry geom, integer nIterations = 1, boolean preserveEndpoints = false);



Smooths a linear or polygonal geometry using **Chaikin's algorithm**. The degree of smoothing is controlled by the `nIterations` parameter. On each iteration, each interior vertex is replaced by two vertices located at 1/4 of the length of the line segments before and after the vertex. A reasonable degree of smoothing is provided by 3 iterations; the maximum is limited to 5.

If `preserveEndPoints` is true, the endpoints of Polygon rings are not smoothed. The endpoints of LineStrings are always preserved.



Note

The number of vertices doubles with each iteration, so the result geometry may have many more points than the input. To reduce the number of points use a simplification function on the result (see [ST Simplify](#), [ST SimplifyPreserveTopology](#) and [ST SimplifyVW](#)).

The result has interpolated values for the Z and M dimensions when present.



This function supports 3d and will not drop the z-index.

Availability: 2.5.0



Smoothing a triangle:

```
SELECT ST_AsText(ST_ChaikinSmoothing(geom)) smoothed
FROM (SELECT 'POLYGON((0 0, 8 8, 0 16, 0 0))'::geometry geom) AS foo;
```

smoothed

b' '-b' 'b' '-b' 'b' '-b' 'b' '-b' 'b' '-b' 'b' '-b' 'b' '-b' 'b' '-b' 'b' '-b' 'b' '-b' 'b' '-b' 'b' ' ←


b' '-b' 'b' '-b' 'b' '-b' 'b' '-b' 'b' '-b' 'b' '-b' 'b' '-b' 'b' '-b' 'b' '-b' 'b' '-b' 'b' ' ←

'-b' 'b' '-b' 'b' '-b' 'b' '-b' 'b' '-b' 'b' '-b' 'b' '-b' 'b' '-b' 'b' '-b' 'b' '-b' 'b' '-b' 'b' ' ←

'-b' 'b' '-b' 'b' '-b' 'b' '-b' 'b' '-b' 'b' '-b' 'b' '-b' 'b' '-b' 'b' '-b' 'b' '-b' 'b' ' ←


POLYGON((2 2,6 6,6 10,2 14,0 12,0 4,2 2))

Smoothing a Polygon using 1, 2 and 3 iterations:



```
SELECT ST_ChaikinSmoothing(
  'POLYGON ((20 20, 60 90, 10 150, 100 190, 190 160, 130 120, 190 50, 140 70, 120 10, 90 60, 20 20))',
  generate_series(1, 3) );
```

Smoothing a LineString using 1, 2 and 3 iterations:



```
SELECT ST_ChaikinSmoothing(
  'LINESTRING (10 140, 80 130, 100 190, 190 150, 140 20, 120 120, 50 30, 30 100)',
  generate_series(1, 3) );
```

☒☒

[ST_Simplify](#), [ST_SimplifyPreserveTopology](#), [ST_SimplifyVW](#)

7.14.5 ST_ConcaveHull

ST_ConcaveHull — Computes a possibly concave geometry that contains all input geometry vertices

Synopsis

```
geometry ST_ConcaveHull(geometry param_geom, float param_pctconvex, boolean param_allow_holes
= false);
```

国国

A concave hull is a (usually) concave geometry which contains the input, and whose vertices are a subset of the input vertices. In the general case the concave hull is a Polygon. The concave hull of two or more collinear points is a two-point LineString. The concave hull of one or more identical points is a Point. The polygon will not contain holes unless the optional `param_allow_holes` argument is specified as true.

One can think of a concave hull as "shrink-wrapping" a set of points. This is different to the **convex hull**, which is more like wrapping a rubber band around the points. A concave hull generally has a smaller area and represents a more natural boundary for the input points.

The `param_pctconvex` controls the concaveness of the computed hull. A value of 1 produces the convex hull. Values between 1 and 0 produce hulls of increasing concaveness. A value of 0 produces a hull with maximum concaveness (but still a single polygon). Choosing a suitable value depends on the nature of the input data, but often values between 0.3 and 0.1 produce reasonable results.



Note

Technically, the `param_pctconvex` determines a length as a fraction of the difference between the longest and shortest edges in the Delaunay Triangulation of the input points. Edges longer than this length are "eroded" from the triangulation. The triangles remaining form the concave hull.


For point and linear inputs, the hull will enclose all the points of the inputs. For polygonal inputs, the hull will enclose all the points of the input *and also* all the areas covered by the input. If you want a point-wise hull of a polygonal input, convert it to points first using **ST_Points**.

This is not an aggregate function. To compute the concave hull of a set of geometries use **ST_Collect** (e.g. `ST_ConcaveHull( ST_Collect( geom ), 0.80)`).

2.0.0 国国国国国国国国国国国国.

Enhanced: 3.3.0, GEOS native implementation enabled for GEOS 3.11+

图 10.10



Concave Hull of a MultiPoint

```


SELECT ST_AsText( ST_ConcaveHull(
    'MULTIPOINT ((10 72), (53 76), (56 66), (63 58), (71 51), (81 48), (91 46), (101 45), (111 46), (121 47), (131 50), (140 55), (145 64), (144 74), (135 80), (125 83), (115 85), (105 87), (95 89), (85 91), (75 93), (65 95), (55 98), (45 102), (37 107), (29 114), (22 122), (19 132), (18 142), (21 151), (27 160), (35 167), (44 172), (54 175), (64 178), (74 180), (84 181), (94 181), (104 181), (114 181), (124 181), (134 179), (144 177), (153 173), (162 168), (171 162), (177 154), (182 145), (184 135), (139 132), (136 142), (128 149), (119 153), (109 155), (99 155), (89 155), (79 153), (69 150), (61 144), (63 134), (72 128), (82 125), (92 123), (102 121), (112 119), (122 118), (132 116), (142 113), (151 110), (161 106), (170 102), (178 96), (185 88), (189 78), (190 68), (189 58), (185 49), (179 41), (171 34), (162 29), (153 25), (143 23), (133 21), (123 19), (113 19), (102 19), (92 19), (82 19), (72 21), (62 22), (52 25), (43 29), (33 34), (25 41), (19 49), (14 58), (21 73), (31 74), (42 74), (173 134), (161 134), (150 133), (97 104), (52 117), (157 156), (94 171), (112 106), (169 73), (58 165), (149 40), (70 33), (147 157), (48 153), (140 96), (47 129), (173 55), (144 86), (159 67), (150 146), (38 136), (111 170), (124 94), (26 59), (60 41), (71 162), (41 64), (88 110), (122 34), (151 97), (157 56), (39 146), (88 33), (159 45), (47 56), (138 40), (129 165), (33 48), (106 31), (169 147), (37 122), (71 109), (163 89), (37 156), (82 170), (180 72), (29 142), (46 41), (59 155), (124 106), (157 80), (175 82), (56 50), (62 116), (113 95), (144 167)))',
    0.1 ) );
---st_astext---
POLYGON ((18 142, 21 151, 27 160, 35 167, 44 172, 54 175, 64 178, 74 180, 84 181, 94 181, 104 181, 114 181, 124 181, 134 179, 144 177, 153 173, 162 168, 171 162, 177 154, 182 145, 184 135, 173 134, 161 134, 150 133, 139 132, 136 142, 128 149, 119 153, 109 155, 99 155, 89 155, 79 153, 69 150, 61 144, 63 134, 72 128, 82 125, 92 123, 102 121, 112 119, 122 118, 132 116, 142 113, 151 110, 161 106, 170 102, 178 96, 185 88, 189 78, 190 68, 189 58, 185 49, 179 41, 171 34, 162 29, 153 25, 143 23, 133 21, 123 19, 113 19, 102 19, 92 19, 82 19, 72 21, 62 22, 52 25, 43 29, 33 34, 25 41, 19 49, 14 58, 10 72, 21 73, 31 74, 42 74, 53 76, 56 66, 63 58, 71 51, 81 48, 91 46, 101 45, 111 46, 121 47, 131 50, 140 55, 145 64, 144 74, 135 80, 125 83, 115 85, 105 87, 95 89, 85 91, 75 93, 65 95, 55 98, 45 102, 37 107, 29 114, 22 122, 19 132, 18 142))

```



Concave Hull of a MultiPoint, allowing holes

```
SELECT ST_AsText( ST_ConcaveHull(
  'MULTIPOINT ((132 64), (114 64), (99 64), (81 64), (63 64), (57 49), (52 36), (46
    20), (37 20), (26 20), (32 36), (39 55), (43 69), (50 84), (57 100), (63 118),
    (68 133), (74 149), (81 164), (88 180), (101 180), (112 180), (119 164), (126
    149), (132 131), (139 113), (143 100), (150 84), (157 69), (163 51), (168 36),
    (174 20), (163 20), (150 20), (143 36), (139 49), (132 64), (99 151), (92 138),
    (88 124), (81 109), (74 93), (70 82), (83 82), (99 82), (112 82), (126 82), (121
    96), (114 109), (110 122), (103 138), (99 151), (34 27), (43 31), (48 44), (46
    58), (52 73), (63 73), (61 84), (72 71), (90 69), (101 76), (123 71), (141 62),
    (166 27), (150 33), (159 36), (146 44), (154 53), (152 62), (146 73), (134 76),
    (143 82), (141 91), (130 98), (126 104), (132 113), (128 127), (117 122), (112
    133), (119 144), (108 147), (119 153), (110 171), (103 164), (92 171), (86 160),
    (88 142), (79 140), (72 124), (83 131), (79 118), (68 113), (63 102), (68 93),
    (35 45))',
    0.15, true ) );
---st_astext---
POLYGON ((43 69, 50 84, 57 100, 63 118, 68 133, 74 149, 81 164, 88 180, 101 180, 112 180,
  119 164, 126 149, 132 131, 139 113, 143 100, 150 84, 157 69, 163 51, 168 36, 174 20, 163
  20, 150 20, 143 36, 139 49, 132 64, 114 64, 99 64, 81 64, 63 64, 57 49, 52 36, 46 20,
  37 20, 26 20, 32 36, 35 45, 39 55, 43 69), (88 124, 81 109, 74 93, 83 82, 99 82, 112 82,
  121 96, 114 109, 110 122, 103 138, 92 138, 88 124))
```



Comparing a concave hull of a Polygon to the concave hull of the constituent points. The hull respects the boundary of the polygon, whereas the points-based hull does not.

```
WITH data(geom) AS (VALUES
  ('POLYGON ((10 90, 39 85, 61 79, 50 90, 80 80, 95 55, 25 60, 90 45, 70 16, 63 38, 60 10, 50 30, 43 27, 30 10, 20 20, 10 90))'::geometry)
)
SELECT ST_ConcaveHull( geom, 0.1) AS polygon_hull,
       ST_ConcaveHull( ST_Points(geom), 0.1) AS points_hull
FROM data;
```

Using with `ST_Collect` to compute the concave hull of a geometry set.

```
-- Compute estimate of infected area based on point observations
SELECT disease_type,
       ST_ConcaveHull( ST_Collect(obs_pnt), 0.3 ) AS geom
FROM disease_obs
GROUP BY disease_type;
```

☒☒

[ST_ConvexHull](#), [ST_Collect](#), [ST_AlphaShape](#), [ST_OptimalAlphaShape](#)

7.14.6 ST_ConvexHull

`ST_ConvexHull` — Computes the convex hull of a geometry.

Synopsis

geometry **ST_ConvexHull**(geometry geomA);

ST_ConvexHull

Computes the convex hull of a geometry. The convex hull is the smallest convex geometry that encloses all geometries in the input.

One can think of the convex hull as the geometry obtained by wrapping an rubber band around a set of geometries. This is different from a **concave hull** which is analogous to "shrink-wrapping" the geometries. A convex hull is often used to determine an affected area based on a set of point observations.


In the general case the convex hull is a Polygon. The convex hull of two or more collinear points is a two-point LineString. The convex hull of one or more identical points is a Point.

This is not an aggregate function. To compute the convex hull of a set of geometries, use **ST_Collect** to aggregate them into a geometry collection (e.g. `ST_ConvexHull(ST_Collect(geom))`).

GEOS 3.10.0

- ✓ This method implements the **OGC Simple Features Implementation Specification for SQL 1.1. s2.1.1.3**
- ✓ This method implements the SQL/MM specification. SQL-MM IEC 13249-3: 5.1.16
- ✓ This function supports 3d and will not drop the z-index.

Diagram



Convex Hull of a MultiLineString and a MultiPoint

```
SELECT ST_AsText(ST_ConvexHull(
  ST_Collect(
    ST_GeomFromText('MULTILINESTRING((100 190,10 8),(150 10, 20 30))'),
    ST_GeomFromText('MULTIPOINT(50 5, 150 30, 50 10, 10 10)')
  )));
---st_astext--
POLYGON((50 5,10 8,10 10,100 190,150 30,150 10,50 5))
```

Using with `ST_Collect` to compute the convex hulls of geometry sets.

```
--Get estimate of infected area based on point observations
SELECT d.disease_type,
       ST_ConvexHull(ST_Collect(d.geom)) As geom
FROM disease_obs As d
GROUP BY d.disease_type;
```

☐☐

[ST_Collect](#), [ST_ConcaveHull](#), [ST_MinimumBoundingCircle](#)

7.14.7 ST_DelaunayTriangles

ST_DelaunayTriangles — Returns the Delaunay triangulation of the vertices of a geometry.

Synopsis

geometry **ST_DelaunayTriangles**(geometry g1, float tolerance = 0.0, int4 flags = 0);

☐☐

Computes the [Delaunay triangulation](#) of the vertices of the input geometry. The optional tolerance can be used to snap nearby input vertices together, which improves robustness in some situations. The result geometry is bounded by the convex hull of the input vertices. The result geometry representation is determined by the flags code:


- 0 - a GEOMETRYCOLLECTION of triangular POLYGONS (default)
- 1 - a MULTILINESTRING of the edges of the triangulation
- 2 - A TIN of the triangulation


GEOS ☐☐☐☐☐

2.1.0 ☐☐☐☐☐☐☐☐☐☐.

- ✔ This function supports 3d and will not drop the z-index.
- ✔ This function supports Triangles and Triangulated Irregular Network Surfaces (TIN).

☐☐






使用 `ST_DelaunayTriangles`: 对多边形进行三角剖分


geometries overlaid multilinestring triangles

```
SELECT
  ST_DelaunayTriangles(
    ST_Union(ST_GeomFromText('POLYGON((175 150, 20 40,
      50 60, 125 100, 175 150))'),
    ST_Buffer(ST_GeomFromText('POINT(110 170)'), 20)
  )
  As dtriag;
```



-- 简体中文版

```
SELECT
  ST_DelaunayTriangles(
    ST_Union(ST_GeomFromText('POLYGON((175 150, 20 40,
      50 60, 125 100, 175 150))'),
    ST_Buffer(ST_GeomFromText('POINT(110 170)'), 20)
    ),0.001,1)
  As dtriag;
```



```
-- 55 45
```

this produces a table of 42 points that form an L shape

```
SELECT (ST_DumpPoints(ST_GeomFromText(
'MULTIPOINT(14 14,34 14,54 14,74 14,94 14,114 14,134 14,
150 14,154 14,154 6,134 6,114 6,94 6,74 6,54 6,34 6,
14 6,10 6,8 6,7 7,6 8,6 10,6 30,6 50,6 70,6 90,6 110,6 130,
6 150,6 170,6 190,6 194,14 194,14 174,14 154,14 134,14 114,
14 94,14 74,14 54,14 34,14 14)'))).geom
    INTO TABLE l_shape;
```

output as individual polygon triangles

```
SELECT ST_AsText((ST_Dump(geom)).geom) As wkt
FROM ( SELECT ST_DelaunayTriangles(ST_Collect(geom)) As geom
FROM l_shape) As foo;
```

wkt

```
POLYGON((6 194,6 190,14 194,6 194))
POLYGON((14 194,6 190,14 174,14 194))
POLYGON((14 194,14 174,154 14,14 194))
POLYGON((154 14,14 174,14 154,154 14))
POLYGON((154 14,14 154,150 14,154 14))
POLYGON((154 14,150 14,154 6,154 14))
```

Example using vertices with Z values.

3D multipoint

```
SELECT ST_AsText(ST_DelaunayTriangles(ST_GeomFromText(
'MULTIPOINT Z(14 14 10, 150 14 100,34 6 25, 20 10 150)')))) As wkt;
```

wkt

```
GEOMETRYCOLLECTION Z (POLYGON Z ((14 14 10,20 10 150,34 6 25,14 14 10))
,POLYGON Z ((14 14 10,34 6 25,150 14 100,14 14 10)))
```

☒☒

[ST_VoronoiPolygons](#), [ST_TriangulatePolygon](#), [ST_ConstrainedDelaunayTriangles](#), [ST_VoronoiLines](#), [ST_Con](#)

7.14.8 ST_FilterByM

ST_FilterByM — Removes vertices based on their M value

Synopsis

geometry **ST_FilterByM**(geometry geom, double precision min, double precision max = null, boolean returnM = false);

☒☒

Filters out vertex points based on their M-value. Returns a geometry with only vertex points that have a M-value larger or equal to the min value and smaller or equal to the max value. If max-value argument is left out only min value is considered. If fourth argument is left out the m-value will not be in the resulting geometry. If resulting geometry have too few vertex points left for its geometry type an empty geometry will be returned. In a geometry collection geometries without enough points will just be left out silently.

This function is mainly intended to be used in conjunction with ST_SetEffectiveArea. ST_EffectiveArea sets the effective area of a vertex in its m-value. With ST_FilterByM it then is possible to get a simplified version of the geometry without any calculations, just by filtering



Note

There is a difference in what ST_SimplifyVW returns when not enough points meet the criteria compared to ST_FilterByM. ST_SimplifyVW returns the geometry with enough points while ST_FilterByM returns an empty geometry



Note

Note that the returned geometry might be invalid



Note

This function returns all dimensions, including the Z and M values

Availability: 2.5.0

☒☒

A linestring is filtered

```
SELECT ST_AsText(ST_FilterByM(geom,30)) simplified
FROM (SELECT ST_SetEffectiveArea('LINESTRING(5 2, 3 8, 6 20, 7 25, 10 10)::geometry) geom ←
) As foo;
```

result

```
      simplified
-----
LINESTRING(5 2,7 25,10 10)
```

☒☒

[ST_SetEffectiveArea](#), [ST_SimplifyVW](#)

7.14.9 ST_GeneratePoints

ST_GeneratePoints — Generates a multipoint of random points contained in a Polygon or MultiPolygon.

Synopsis

geometry **ST_GeneratePoints**(geometry g, integer npoints, integer seed = 0);


☒☒

ST_GeneratePoints generates a multipoint consisting of a given number of pseudo-random points which lie within the input area. The optional seed is used to regenerate a deterministic sequence of points, and must be greater than zero.

2.3.0 简体中文.

Enhanced: 3.0.0, added seed parameter

☒☒



Generated a multipoint consisting of 12 Points overlaid on top of original polygon using a random seed value 1996

```
SELECT ST_GeneratePoints(geom, 12, 1996)
FROM (
  SELECT ST_Buffer(
    ST_GeomFromText(
      'LINESTRING(50 50,150 150,150 50)'),
    10, 'endcap=round join=round') AS geom
) AS s;
```

Given a table of polygons `s`, return 12 individual points per polygon. Results will be different each time you run.

```
SELECT s.id, dp.path[1] AS pt_id, dp.geom
FROM s, ST_DumpPoints(ST_GeneratePoints(s.geom,12)) AS dp;
```

☐☐

ST_DumpPoints

7.14.10 ST_GeometricMedian

ST_GeometricMedian — 计算几何中位数 (median) 的函数。

Synopsis

geometry **ST_GeometricMedian** (geometry geom, float8 tolerance = NULL, int max_iter = 10000, boolean fail_if_not_converged = false);

☐☐

Computes the approximate geometric median of a MultiPoint geometry using the Weiszfeld algorithm. The geometric median is the point minimizing the sum of distances to the input points. It provides a centrality measure that is less sensitive to outlier points than the centroid (center of mass).

The algorithm iterates until the distance change between successive iterations is less than the supplied tolerance parameter. If this condition has not been met after `max_iterations` iterations, the function produces an error and exits, unless `fail_if_not_converged` is set to `false` (the default).

If a tolerance argument is not provided, the tolerance value is calculated based on the extent of the input geometry.

If present, the input point M values are interpreted as their relative weights.

2.3.0 支持 M 权重。

Enhanced: 2.5.0 Added support for M as weight of points.




This function supports 3d and will not drop the z-index.



This function supports M coordinates.

🔍🔍



Comparison of the geometric median (red) and centroid (turquoise) of a MultiPoint.

```
WITH test AS (  
SELECT 'MULTIPOINT((10 10), (10 40), (40 10), (190 190))'::geometry geom)  
SELECT  
  ST_AsText(ST_Centroid(geom)) centroid,  
  ST_AsText(ST_GeometricMedian(geom)) median  
FROM test;
```

centroid		median
POINT(62.5 62.5)		POINT(25.01778421249728 25.01778421249728)
(1 row)		

🔍🔍

ST_Centroid

7.14.11 ST_LineMerge

ST_LineMerge — Return the lines formed by sewing together a MultiLineString.

Synopsis

```
geometry ST_LineMerge(geometry amultilinestring);  
geometry ST_LineMerge(geometry amultilinestring, boolean directed);
```

🔍🔍

Returns a LineString or MultiLineString formed by joining together the line elements of a MultiLineString. Lines are joined at their endpoints at 2-way intersections. Lines are not joined across intersections of 3-way or greater degree.

If **directed** is TRUE, then ST_LineMerge will not change point order within LineStrings, so lines with opposite directions will not be merged

**Note**

Only use with MultiLineString/LineStrings. Other geometry types return an empty GeometryCollection

GEOS 简体中文

Enhanced: 3.3.0 accept a directed parameter.


Requires GEOS >= 3.11.0 to use the directed parameter.

1.1.0 简体中文.

**Warning**


This function strips the M dimension.

图例



Merging lines with different orientation.

```
SELECT ST_AsText(ST_LineMerge(
'MULTILINESTRING((10 160, 60 120), (120 140, 60 120), (120 140, 180 120))'
));
-----
LINESTRING(10 160,60 120,120 140,180 120)
```




Lines are not merged across intersections with degree > 2.

```
SELECT ST_AsText(ST_LineMerge(
'MULTILINESTRING((10 160, 60 120), (120 140, 60 120), (120 140, 180 120), (100 180, 120 140))'
));
-----
MULTILINESTRING((10 160,60 120,120 140),(100 180,120 140),(120 140,180 120))
```

If merging is not possible due to non-touching lines, the original MultiLineString is returned.


```
SELECT ST_AsText(ST_LineMerge(
'MULTILINESTRING((-29 -27,-30 -29.7,-36 -31,-45 -33),(-45.2 -33.2,-46 -32))'
));
-----
MULTILINESTRING((-45.2 -33.2,-46 -32),(-29 -27,-30 -29.7,-36 -31,-45 -33))
```



Lines with opposite directions are not merged if directed = TRUE.

```
SELECT ST_AsText(ST_LineMerge(
'MULTILINESTRING((60 30, 10 70), (120 50, 60 30), (120 50, 180 30))',
TRUE));
```


图




Maximum inscribed circle of a polygon. Center, nearest point, and radius are returned.

```
SELECT radius, ST_AsText(center) AS center, ST_AsText(nearest) AS nearest
FROM ST_MaximumInscribedCircle(
  'POLYGON ((40 180, 110 160, 180 180, 180 120, 140 90, 160 40, 80 10, 70 40, 20 50, 40 180), (60 140, 50 90, 90 140, 60 140))');

```

radius	center	nearest
45.165845650018	POINT(96.953125 76.328125)	POINT(140 90)



Maximum inscribed circle of a multi-linestring. Center, nearest point, and radius are returned.

图

ST_MinimumBoundingRadius, ST_LargestEmptyCircle

7.14.13 ST_LargestEmptyCircle

ST_LargestEmptyCircle — Computes the largest circle not overlapping a geometry.

Synopsis

(geometry, geometry, double precision) **ST_LargestEmptyCircle**(geometry geom, double precision tolerance=0.0, geometry boundary=POINT EMPTY);

描述

Finds the largest circle which does not overlap a set of point and line obstacles. (Polygonal geometries may be included as obstacles, but only their boundary lines are used.) The center of the circle is constrained to lie inside a polygonal boundary, which by default is the convex hull of the input geometry. The circle center is the point in the interior of the boundary which has the farthest distance from the obstacles. The circle itself is provided by the center point and a nearest point lying on an obstacle determining the circle radius.

The circle center is determined to a given accuracy specified by a distance tolerance, using an iterative algorithm. If the accuracy distance is not specified a reasonable default is used.

Returns a record with fields:

- center - center point of the circle
- nearest - a point on the geometry nearest to the center
- radius - radius of the circle


To find the largest empty circle in the interior of a polygon, see [ST_MaximumInscribedCircle](#).

Availability: 3.4.0.

Requires GEOS >= 3.9.0.


示例

```
SELECT radius,
       center,
       nearest
FROM ST_LargestEmptyCircle(
    'MULTILINESTRING (
      (10 100, 60 180, 130 150, 190 160),
      (20 50, 70 70, 90 20, 110 40),
      (160 30, 100 100, 180 100))'');
```



Largest Empty Circle within a set of lines.

```
SELECT radius,
       center,
       nearest
FROM ST_LargestEmptyCircle(
  ST_Collect(
    'MULTIPOINT ((70 50), (60 130), (130 150), (80 90))'::geometry,
    'POLYGON ((90 190, 10 100, 60 10, 190 40, 120 100, 190 180, 90 190))'::geometry) ←
    ,
    0,
    'POLYGON ((90 190, 10 100, 60 10, 190 40, 120 100, 190 180, 90 190))'::geometry
  );
```



Largest Empty Circle within a set of points, constrained to lie in a polygon. The constraint polygon boundary must be included as an obstacle, as well as specified as the constraint for the circle center.

☒☒

ST_MinimumBoundingRadius


```

SELECT ST_AsText(ST_MinimumBoundingCircle(
    ST_Collect(
        ST_GeomFromText('LINESTRING(55 75,125 150)'),
        ST_Point(20, 80)), 8
    )) As wktmbc;

wktmbc
-----
POLYGON((135.59714732062 115,134.384753327498 102.690357210921,130.79416296937 ↵
  90.8537670908995,124.963360620072 79.9451031602111,117.116420743937 ↵
  70.3835792560632,107.554896839789 62.5366393799277,96.6462329091006 ↵
  56.70583703063,84.8096427890789 53.115246672502,72.5000000000001 ↵
  51.9028526793802,60.1903572109213 53.1152466725019,48.3537670908996 ↵
  56.7058370306299,37.4451031602112 62.5366393799276,27.8835792560632 ↵
  70.383579256063,20.0366393799278 79.9451031602109,14.20583703063 ↵
  90.8537670908993,10.615246672502 102.690357210921,9.40285267938019 115,10.6152466725019 ↵
  127.309642789079,14.2058370306299 139.1462329091,20.0366393799275 ↵
  150.054896839789,27.883579256063 159.616420743937,
  37.4451031602108 167.463360620072,48.3537670908992 173.29416296937,60.190357210921 ↵
  176.884753327498,
  72.4999999999998 178.09714732062,84.8096427890786 176.884753327498,96.6462329091003 ↵
  173.29416296937,107.554896839789 167.463360620072,
  117.116420743937 159.616420743937,124.963360620072 150.054896839789,130.79416296937 ↵
  139.146232909101,134.384753327498 127.309642789079,135.59714732062 115))

```

☒☒

[ST_Collect](#), [ST_MinimumBoundingRadius](#), [ST_LargestEmptyCircle](#), [ST_LongestLine](#)

7.14.15 ST_MinimumBoundingRadius

ST_MinimumBoundingRadius — Returns the center point and radius of the smallest circle that contains a geometry.

Synopsis

(geometry, double precision) **ST_MinimumBoundingRadius**(geometry geom);

☒☒

Computes the center point and radius of the smallest circle that contains a geometry. Returns a record with fields:

- center - center point of the circle
- radius - radius of the circle

Use with [ST_Collect](#) to get the minimum bounding circle of a set of geometries.

To compute two points lying on the minimum circle (the "maximum diameter") use [ST_LongestLine](#).

2.3.0 ☒☒☒☒☒☒☒☒☒☒.


```
SELECT ST_AsText(center), radius FROM ST_MinimumBoundingRadius('POLYGON((26426 65078,26531 65242,26075 65136,26096 65427,26426 65078))');

st_astext | radius
-----+-----
POINT(26284.8418027133 65267.1145090825) | 247.436045591407
```

[ST_Collect](#), [ST_MinimumBoundingCircle](#), [ST_LongestLine](#)

7.14.16 ST_OrientedEnvelope

`ST_OrientedEnvelope` — Returns a minimum-area rectangle containing a geometry.

Synopsis

geometry **ST_OrientedEnvelope**(geometry geom);


Returns the minimum-area rotated rectangle enclosing a geometry. Note that more than one such rectangle may exist. May return a Point or LineString in the case of degenerate inputs.

Availability: 2.5.0.

Requires GEOS >= 3.6.0.

```
SELECT ST_AsText(ST_OrientedEnvelope('MULTIPOINT ((0 0), (-1 -1), (3 2))'));

st_astext
-----
POLYGON((3 2,2.88 2.16,-1.12 -0.84,-1 -1,3 2))
```



Oriented envelope of a point and linestring.

```
SELECT ST_AsText(ST_OrientedEnvelope(
    ST_Collect(
        ST_GeomFromText('LINESTRING(55 75,125 150)'),
        ST_Point(20, 80))
    )) As wktenv;

wktenv
-----
POLYGON((19.9999999999997 79.9999999999999,33.0769230769229 60.3846153846152,138.076923076924 130.384615384616,125.000000000001 150.000000000001,19.9999999999997 79.9999999999999))
```



ST_Envelope ST_MinimumBoundingCircle

7.14.17 ST_OffsetCurve

ST OffsetCurve — Returns an offset line at a given distance and side from an input line.

Synopsis

```
geometry ST_OffsetCurve(geometry line, float signed_distance, text style_parameters="");
```



Return an offset line at a given distance and side from an input line. All points of the returned geometries are not further than the given distance from the input geometry. Useful for computing parallel lines about a center line.

For positive distance the offset is on the left side of the input line and retains the same direction. For a negative distance it is on the right side and in the opposite direction.

[illegible]

Note that output may be a MULTILINESTRING or EMPTY for some jigsaw-shaped input geometries.

[illegible]

- 'quad_segs=#' : 整数 (quarter circle) 的段数 (默认为 8)
- 'join=round|mitre|bevel' : 连接类型 (默认为 "round")。'mitre' 使用 'mitre_limit' 限制 (miter) 的斜率。
- 'mitre_limit=#.#' : 限制 (mitre) 的斜率。'mitre_limit' 和 'miter_limit' 使用相同的值。

GEOS 兼容性

Behavior changed in GEOS 3.11 so offset curves now have the same direction as the input line, for both positive and negative offsets.

2.0 兼容性。

Enhanced: 2.5 - added support for GEOMETRYCOLLECTION and MULTILINESTRING




Note

This function ignores the Z dimension. It always gives a 2D result even when used on a 3D geometry.

SQL

兼容性。

```
SELECT ST_Union(
  ST_OffsetCurve(f.geom, f.width/2, 'quad_segs=4 join=round'),
  ST_OffsetCurve(f.geom, -f.width/2, 'quad_segs=4 join=round')
) as track
FROM someroadstable;
```



国 15, 国国国国国'quad_segs=4 join=round'
国国国国 15 国

```
SELECT ST_AsText(ST_OffsetCurve(↵
  ST_GeomFromText(↵
    'LINESTRING(164 16,144 16,124 16,104 ↵
      16,84 16,64 16,↵
      44 16,24 16,20 16,18 16,17 17,↵
      16 18,16 20,16 40,16 60,16 80,16 100,↵
      16 120,16 140,16 160,16 180,16 195)') ↵
    ,↵
    15, 'quad_segs=4 join=round'));
```

output

```
LINESTRING(164 1,18 1,12.2597485145237 ↵
  2.1418070123307,↵
  7.39339828220179 5.39339828220179,↵
  5.39339828220179 7.39339828220179,↵
  2.14180701233067 12.2597485145237,1 ↵
  18,1 195)
```




国 -15, 国国国国国'quad_segs=4
join=round' 国国国国 -15 国

```
SELECT ST_AsText(ST_OffsetCurve(geom,↵
  -15, 'quad_segs=4 join=round')) As ↵
  notsocurvy↵
FROM ST_GeomFromText(↵
  'LINESTRING(164 16,144 16,124 16,104 ↵
    16,84 16,64 16,↵
    44 16,24 16,20 16,18 16,17 17,↵
    16 18,16 20,16 40,16 60,16 80,16 100,↵
    16 120,16 140,16 160,16 180,16 195)') ↵
  As geom;
```


notsocurvy

```
LINESTRING(31 195,31 31,164 31)
```




偏移距离为 15 单位，拐角半径为 15 单位。 $-30 + 15 = -15$ 单位。

```
SELECT ST_AsText(ST_OffsetCurve(
  ST_OffsetCurve(geom,
    -30, 'quad_segs=4 join=round'), -15,
    'quad_segs=4 join=round')) As morecurvy
FROM ST_GeomFromText(
'LINESTRING(164 16,144 16,124 16,104
16,84 16,64 16,
44 16,24 16,20 16,18 16,17 17,
16 18,16 20,16 40,16 60,16 80,16 100,
16 120,16 140,16 160,16 180,16 195)')
As geom;
morecurvy
LINESTRING(164 31,46 31,40.2597485145236
32.1418070123307,
35.3933982822018 35.3933982822018,
32.1418070123307 40.2597485145237,31
46,31 195)
```



偏移距离为 15 单位，拐角半径为 15 单位。 $-30 + 15 = -15$ 单位。

```
SELECT ST_AsText(ST_Collect(
  ST_OffsetCurve(geom, 15, 'quad_segs=4
  join=round'),
  ST_OffsetCurve(ST_OffsetCurve(geom,
    -30, 'quad_segs=4 join=round'), -15,
    'quad_segs=4 join=round')
)
) As parallel_curves
FROM ST_GeomFromText(
'LINESTRING(164 16,144 16,124 16,104
16,84 16,64 16,
44 16,24 16,20 16,18 16,17 17,
16 18,16 20,16 40,16 60,16 80,16 100,
16 120,16 140,16 160,16 180,16 195)')
As geom;
parallel curves
MULTILINESTRING((164 1,18
1,12.2597485145237 2.1418070123307,
7.39339828220179
5.39339828220179,5.39339828220179 7.39339828220179,
2.14180701233067 12.2597485145237,1 18,1
195),
(164 31,46 31,40.2597485145236
32.1418070123307,35.3933982822018 35.3933982822018,
32.1418070123307 40.2597485145237,31
46,31 195))
```

 国国 15, 国国国国国国国国国国'quad_segs=4 join=round' <pre>SELECT ST_AsText(ST_OffsetCurve(↵ ST_GeomFromText('LINESTRING(164 16,144 16,124 16,104 ↵ 16,84 16,64 16, 44 16,24 16,20 16,18 16,17 17, 16 18,16 20,16 40,16 60,16 80,16 100, 16 120,16 140,16 160,16 180,16 195)') ↵ , 15, 'quad_segs=4 join=bevel'));</pre> output <pre>LINESTRING(164 1,18 1,7.39339828220179 ↵ 5.39339828220179, 5.39339828220179 7.39339828220179,1 ↵ 18,1 195)</pre>	 国国国 15, -15. join=mitre mitre_limit=2.1 <pre>SELECT ST_AsText(ST_Collect(ST_OffsetCurve(geom, 15, 'quad_segs=4 ↵ join=mitre mitre_limit=2.2'), ST_OffsetCurve(geom, -15, 'quad_segs ↵ =4 join=mitre mitre_limit=2.2'))) FROM ST_GeomFromText('LINESTRING(164 16,144 16,124 16,104 ↵ 16,84 16,64 16, 44 16,24 16,20 16,18 16,17 17, 16 18,16 20,16 40,16 60,16 80,16 100, 16 120,16 140,16 160,16 180,16 195)') ↵ As geom;</pre> output <pre>MULTILINESTRING((164 1,11.7867965644036 ↵ 1,1 11.7867965644036,1 195), (31 195,31 31,164 31))</pre>

国国

ST_Buffer

7.14.18 ST_PointOnSurface

ST_PointOnSurface — Computes a point guaranteed to lie in a polygon, or on a geometry.

Synopsis


geometry **ST_PointOnSurface**(geometry g1);

☒☒

Returns a POINT which is guaranteed to lie in the interior of a surface (POLYGON, MULTIPOLYGON, and CURVEPOLYGON). In PostGIS this function also works on line and point geometries.

- ✔ This method implements the [OGC Simple Features Implementation Specification for SQL 1.1](#). s3.2.14.2 // s3.2.18.2
- ✔ This method implements the SQL/MM specification. SQL-MM 3: 8.1.5, 9.5.6. The specifications define ST_PointOnSurface for surface geometries only. PostGIS extends the function to support all common geometry types. Other databases (Oracle, DB2, ArcSDE) seem to support this function only for surfaces. SQL Server 2008 supports all common geometry types.
- ✔ This function supports 3d and will not drop the z-index.

☒☒




```
SELECT ST_AsText(ST_PointOnSurface('POINT(0 5)')::geometry);
-----
POINT(0 5)

SELECT ST_AsText(ST_PointOnSurface('LINESTRING(0 5, 0 10)')::geometry);
-----
POINT(0 5)

SELECT ST_AsText(ST_PointOnSurface('POLYGON((0 0, 0 5, 5 5, 5 0, 0 0))')::geometry);
-----
POINT(2.5 2.5)

SELECT ST_AsEWKT(ST_PointOnSurface(ST_GeomFromEWKT('LINESTRING(0 5 1, 0 0 1, 0 10 2)')));
-----
POINT(0 0 1)
```

Example: The result of `ST_PointOnSurface` is guaranteed to lie within polygons, whereas the point computed by `ST_Centroid` may be outside.



Red: point on surface; Green: centroid

```
SELECT ST_AsText(ST_PointOnSurface(geom)) AS pt_on_surf,
       ST_AsText(ST_Centroid(geom)) AS centroid
FROM (SELECT 'POLYGON ((130 120, 120 190, 30 140, 50 20,
                        170 100, 90 60, 90 130, 130 120))'::geometry AS geom) AS t;
```

pt_on_surf	centroid
POINT(62.5 110)	POINT(100.18264840182648 85.11415525114155)



`ST_Centroid`, `ST_MaximumInscribedCircle`

7.14.19 ST_Polygonize

`ST_Polygonize` — Computes a collection of polygons formed from the linework of a set of geometries.

Synopsis

```
geometry ST_Polygonize(geometry set geomfield);
geometry ST_Polygonize(geometry[] geom_array);
```

☒☒

Creates a GeometryCollection containing the polygons formed by the linework of a set of geometries. If the input linework does not form any polygons, an empty GeometryCollection is returned.

This function creates polygons covering all delimited areas. If the result is intended to form a valid polygonal geometry, use **ST_BuildArea** to prevent holes being filled.




Note
The input linework must be correctly noded for this function to work properly. To ensure input is noded use **ST_Node** on the input geometry before polygonizing.




Note
GeometryCollections can be difficult to handle with external tools. Use **ST_Dump** to convert the polygonized result into separate polygons.

GEOS 3.10.0
1.0.0RC1 简体中文.

☒☒



Input lines



Polygonized result

```
WITH data(geom) AS (VALUES
  ('LINESTRING (180 40, 30 20, 20 90)')::geometry)
, ('LINESTRING (180 40, 160 160)')::geometry)
, ('LINESTRING (80 60, 120 130, 150 80)')::geometry)
```

```

,('LINESTRING (80 60, 150 80)::geometry)
,('LINESTRING (20 90, 70 70, 80 130)::geometry)
,('LINESTRING (80 130, 160 160)::geometry)
,('LINESTRING (20 90, 20 160, 70 190)::geometry)
,('LINESTRING (70 190, 80 130)::geometry)
,('LINESTRING (70 190, 160 160)::geometry)
)
SELECT ST_AsText( ST_Polygonize( geom ))
FROM data;

-----
GEOMETRYCOLLECTION (POLYGON ((180 40, 30 20, 20 90, 70 70, 80 130, 160 160, 180 40), (150 80, 120 130, 80 60, 150 80)),
POLYGON ((20 90, 20 160, 70 190, 80 130, 70 70, 20 90)),
POLYGON ((160 160, 80 130, 70 190, 160 160)),
POLYGON ((80 60, 120 130, 150 80, 80 60)))

```

Polygonizing a table of linestrings:

```

SELECT ST_AsEWKT(ST_Polygonize(geom_4269)) As geomtextrep
FROM (SELECT geom_4269 FROM ma.suffolk_edges) As foo;

-----
SRID=4269;GEOMETRYCOLLECTION(POLYGON((-71.040878 42.285678,-71.040943 42.2856,-71.04096 42.285752,-71.040878 42.285678)),
POLYGON((-71.17166 42.353675,-71.172026 42.354044,-71.17239 42.354358,-71.171794 42.354971,-71.170511 42.354855,-71.17112 42.354238,-71.17166 42.353675)))

--Use ST_Dump to dump out the polygonize geoms into individual polygons
SELECT ST_AsEWKT((ST_Dump(t.polycoll)).geom) AS geomtextrep
FROM (SELECT ST_Polygonize(geom_4269) AS polycoll
FROM (SELECT geom_4269 FROM ma.suffolk_edges)
As foo) AS t;

-----
SRID=4269;POLYGON((-71.040878 42.285678,-71.040943 42.2856,-71.04096 42.285752,-71.040878 42.285678))
SRID=4269;POLYGON((-71.17166 42.353675,-71.172026 42.354044,-71.17239 42.354358,-71.171794 42.354971,-71.170511 42.354855,-71.17112 42.354238,-71.17166 42.353675))

```

☒

ST_BuildArea, ST_Dump, ST_Node

7.14.20 ST_ReducePrecision

ST_ReducePrecision — Returns a valid geometry with points rounded to a grid tolerance.

Synopsis

geometry **ST_ReducePrecision**(geometry g, float8 gridsz);

ST_Simplify

Returns a valid geometry with all points rounded to the provided grid tolerance, and features below the tolerance removed.

Unlike **ST_SnapToGrid** the returned geometry will be valid, with no ring self-intersections or collapsed components.

Precision reduction can be used to:

- match coordinate precision to the data accuracy
- reduce the number of coordinates needed to represent a geometry
- ensure valid geometry output to formats which use lower precision (e.g. text formats such as WKT, GeoJSON or KML when the number of output decimal places is limited).
- export valid geometry to systems which use lower or limited precision (e.g. SDE, Oracle tolerance value)

Availability: 3.1.0.

Requires GEOS >= 3.9.0.

Examples

```
SELECT ST_AsText(ST_ReducePrecision('POINT(1.412 19.323)', 0.1));
      st_astext
-----
POINT(1.4 19.3)

SELECT ST_AsText(ST_ReducePrecision('POINT(1.412 19.323)', 1.0));
      st_astext
-----
POINT(1 19)

SELECT ST_AsText(ST_ReducePrecision('POINT(1.412 19.323)', 10));
      st_astext
-----
POINT(0 20)
```

Precision reduction can reduce number of vertices

```
SELECT ST_AsText(ST_ReducePrecision('LINESTRING (10 10, 19.6 30.1, 20 30, 20.3 30, 40 40)', 1));
      st_astext
-----
LINESTRING (10 10, 20 30, 40 40)
```

Precision reduction splits polygons if needed to ensure validity

```
SELECT ST_AsText(ST_ReducePrecision('POLYGON ((10 10, 60 60.1, 70 30, 40 40, 50 10, 10 10))', 10));
      st_astext
-----
MULTIPOLYGON (((60 60, 70 30, 40 40, 60 60)), ((40 40, 50 10, 10 10, 40 40)))
```

See Also

ST_SnapToGrid, **ST_Simplify**, **ST_SimplifyVW**

7.14.21 ST_SharedPaths

ST_SharedPaths — 返回两个几何体共享的路径。

Synopsis

geometry **ST_SharedPaths**(geometry lineal1, geometry lineal2);

返回

返回两个几何体共享的路径。如果两个几何体没有共享的路径，则返回空几何体。如果两个几何体是点，则返回空几何体。如果两个几何体是线，则返回共享的线段。如果两个几何体是面，则返回共享的边界。

GEOS 版本

2.0.0 及以上版本。

注意：返回的几何体是只读的。



图 7.14.21: ST_SharedPaths 函数




图 10-10. 共享路径的几何体

```
SELECT ST_AsText(
  ST_SharedPaths(
    ST_GeomFromText('MULTILINESTRING((26 125,26 200,126 200,126 125,26 125),
      (51 150,101 150,76 175,51 150))'),
    ST_GeomFromText('LINESTRING(151 100,126 156.25,126 125,90 161, 76 175)')
  )
) As wkt

-----
wkt
-----
GEOMETRYCOLLECTION(MULTILINESTRING((126 156.25,126 125),
(101 150,90 161),(90 161,76 175)),MULTILINESTRING EMPTY)
```

same example but linestring orientation flipped


```
SELECT ST_AsText(
  ST_SharedPaths(
    ST_GeomFromText('LINESTRING(76 175,90 161,126 125,126 156.25,151 100)'),
    ST_GeomFromText('MULTILINESTRING((26 125,26 200,126 200,126 125,26 125),
      (51 150,101 150,76 175,51 150))')
  )
) As wkt

-----
wkt
-----
GEOMETRYCOLLECTION(MULTILINESTRING EMPTY,
MULTILINESTRING((76 175,90 161),(90 161,101 150),(126 125,126 156.25)))
```

图 10-11


ST_Dump, ST_GeometryN, ST_NumGeometries

Simplifying a set of lines. Lines may intersect after simplification.



```
SELECT ST_Simplify(
  'MULTILINESTRING ((20 180, 20 150, 50 150, 50 100, 110 150, 150 140, 170 120), (20 10, 80 10, 80 30, 90 120), (90 120, 130 130), (130 130, 130 70, 160 40, 180 60, 180 90, 140 80), (50 40, 70 40, 80 70, 70 60, 60 60, 50 50, 50 40))',
  40);
```

Simplifying a MultiPolygon. Polygonal results may be invalid.



```
SELECT ST_Simplify(
  'MULTIPOLYGON (((90 110, 80 180, 50 160, 10 170, 10 140, 20 110, 90 110)), ((40 80, 100 100, 120 160, 170 180, 190 70, 140 10, 110 40, 60 40, 40 80), (180 70, 170 110, 142.5 128.5, 128.5 77.5, 90 60, 180 70)))',
  40);
```

☒☒

[ST_IsSimple](#), [ST_SimplifyPreserveTopology](#), [ST_SimplifyVW](#), [ST_CoverageSimplify](#), [Topology ST_Simplify](#)

7.14.23 ST_SimplifyPreserveTopology

`ST_SimplifyPreserveTopology` — Returns a simplified and valid representation of a geometry, using the Douglas-Peucker algorithm.

Synopsis

geometry **ST_SimplifyPreserveTopology**(geometry geom, float tolerance);

注意

Computes a simplified representation of a geometry using a variant of the [Douglas-Peucker algorithm](#) which limits simplification to ensure the result has the same topology as the input. The simplification tolerance is a distance value, in the units of the input SRS. Simplification removes vertices which are within the tolerance distance of the simplified linework, as long as topology is preserved. The result will be valid and simple if the input is.

The function can be called with any kind of geometry (including GeometryCollections), but only line and polygon elements are simplified. For polygonal inputs, the result will have the same number of rings (shells and holes), and the rings will not cross. Ring endpoints may be simplified. For linear inputs, the result will have the same number of lines, and lines will not intersect if they did not do so in the original geometry. Endpoints of linear geometry are preserved.



Note

This function does not preserve boundaries shared between polygons. Use [ST_CoverageSimplify](#) if this is required.

GEOS 3.10.0

1.3.3 简体中文

注意

For the same example as [ST_Simplify](#), `ST_SimplifyPreserveTopology` prevents oversimplification. The circle can at most become a square.

```
SELECT ST_Npoints(geom) AS np_before,
       ST_NPoints(ST_SimplifyPreserveTopology(geom, 0.1)) AS np01_notbadcircle,
       ST_NPoints(ST_SimplifyPreserveTopology(geom, 0.5)) AS np05_notquitecircle,
       ST_NPoints(ST_SimplifyPreserveTopology(geom, 1)) AS np1_octagon,
       ST_NPoints(ST_SimplifyPreserveTopology(geom, 10)) AS np10_square,
       ST_NPoints(ST_SimplifyPreserveTopology(geom, 100)) AS np100_stillsquare
FROM (SELECT ST_Buffer('POINT(1 3)', 10,12) AS geom) AS t;
```


np_before	np01_notbadcircle	np05_notquitecircle	np1_octagon	np10_square	
49	33	17	9	5	
	5				

Simplifying a set of lines, preserving topology of non-intersecting lines.



```
SELECT ST_SimplifyPreserveTopology(
  'MULTILINESTRING ((20 180, 20 150, 50 150, 50 100, 110 150, 150 140, 170 120), (20 10, 80 10, 80 30, 90 120), (90 120, 130 130), (130 130, 130 70, 160 40, 180 60, 180 90, 140 80), (50 40, 70 40, 80 70, 70 60, 60 60, 50 50, 50 40))',
  40);
```

Simplifying a MultiPolygon, preserving topology of shells and holes.



```
SELECT ST_SimplifyPreserveTopology(
  'MULTIPOLYGON (((90 110, 80 180, 50 160, 10 170, 10 140, 20 110, 90 110)), ((40 80, 100 100, 120 160, 170 180, 190 70, 140 10, 110 40, 60 40, 40 80), (180 70, 170 110, 142.5 128.5, 128.5 77.5, 90 60, 180 70)))',
  40);
```

☒☒

[ST_Simplify](#), [ST_SimplifyVW](#), [ST_CoverageSimplify](#)

7.14.24 ST_SimplifyPolygonHull

ST_SimplifyPolygonHull — Computes a simplified topology-preserving outer or inner hull of a polygonal geometry.

Synopsis

```
geometry ST_SimplifyPolygonHull(geometry param_geom, float vertex_fraction, boolean is_outer = true);
```

描述

Computes a simplified topology-preserving outer or inner hull of a polygonal geometry. An outer hull completely covers the input geometry. An inner hull is completely covered by the input geometry. The result is a polygonal geometry formed by a subset of the input vertices. MultiPolygons and holes are handled and produce a result with the same structure as the input.

The reduction in vertex count is controlled by the `vertex_fraction` parameter, which is a number in the range 0 to 1. Lower values produce simpler results, with smaller vertex count and less concaveness. For both outer and inner hulls a vertex fraction of 1.0 produces the original geometry. For outer hulls a value of 0.0 produces the convex hull (for a single polygon); for inner hulls it produces a triangle.

The simplification process operates by progressively removing concave corners that contain the least amount of area, until the vertex count target is reached. It prevents edges from crossing, so the result is always a valid polygonal geometry.


To get better results with geometries that contain relatively long line segments, it might be necessary to "segmentize" the input, as shown below.

GEOS 描述

Availability: 3.3.0.


Requires GEOS >= 3.11.0.

描述



Outer hull of a Polygon

```
SELECT ST_SimplifyPolygonHull(
  'POLYGON ((131 158, 136 163, 161 165, 173 156, 179 148, 169 140, 186 144, 190 137, 185 ↵
    131, 174 128, 174 124, 166 119, 158 121, 158 115, 165 107, 161 97, 166 88, 166 79, 158 ↵
    57, 145 57, 112 53, 111 47, 93 43, 90 48, 88 40, 80 39, 68 32, 51 33, 40 31, 39 34, ↵
    49 38, 34 38, 25 34, 28 39, 36 40, 44 46, 24 41, 17 41, 14 46, 19 50, 33 54, 21 55, 13 ↵
    52, 11 57, 22 60, 34 59, 41 68, 75 72, 62 77, 56 70, 46 72, 31 69, 46 76, 52 82, 47 ↵
    84, 56 90, 66 90, 64 94, 56 91, 33 97, 36 100, 23 100, 22 107, 29 106, 31 112, 46 116, ↵
    36 118, 28 131, 53 132, 59 127, 62 131, 76 130, 80 135, 89 137, 87 143, 73 145, 80 ↵
    150, 88 150, 85 157, 99 162, 116 158, 115 165, 123 165, 122 170, 134 164, 131 158))',
  0.3);
```



Inner hull of a Polygon

```
SELECT ST_SimplifyPolygonHull(
  'POLYGON ((131 158, 136 163, 161 165, 173 156, 179 148, 169 140, 186 144, 190 137, 185 ↵
    131, 174 128, 174 124, 166 119, 158 121, 158 115, 165 107, 161 97, 166 88, 166 79, 158 ↵
    57, 145 57, 112 53, 111 47, 93 43, 90 48, 88 40, 80 39, 68 32, 51 33, 40 31, 39 34, ↵
    49 38, 34 38, 25 34, 28 39, 36 40, 44 46, 24 41, 17 41, 14 46, 19 50, 33 54, 21 55, 13 ↵
    52, 11 57, 22 60, 34 59, 41 68, 75 72, 62 77, 56 70, 46 72, 31 69, 46 76, 52 82, 47 ↵
    84, 56 90, 66 90, 64 94, 56 91, 33 97, 36 100, 23 100, 22 107, 29 106, 31 112, 46 116, ↵
    36 118, 28 131, 53 132, 59 127, 62 131, 76 130, 80 135, 89 137, 87 143, 73 145, 80 ↵
    150, 88 150, 85 157, 99 162, 116 158, 115 165, 123 165, 122 170, 134 164, 131 158))',
  0.3, false);
```



Outer hull simplification of a MultiPolygon, with segmentization

```
SELECT ST_SimplifyPolygonHull(  
  ST_Segmentize(ST_Letters('xt'), 2.0),  
  0.1);
```

国国

[ST_ConvexHull](#), [ST_SimplifyVW](#), [ST_ConcaveHull](#), [ST_Segmentize](#)

7.14.25 ST_SimplifyVW

ST_SimplifyVW — Returns a simplified representation of a geometry, using the Visvalingam-Whyatt algorithm

Synopsis

geometry **ST_SimplifyVW**(geometry geom, float tolerance);

国国

Returns a simplified representation of a geometry using the [Visvalingam-Whyatt algorithm](#). The simplification tolerance is an area value, in the units of the input SRS. Simplification removes vertices which form “corners” with area less than the tolerance. The result may not be valid even if the input is.

The function can be called with any kind of geometry (including GeometryCollections), but only line and polygon elements are simplified. Endpoints of linear geometry are preserved.

Note



The returned geometry may lose its simplicity (see [ST_IsSimple](#)), topology may not be preserved, and polygonal results may be invalid (see [ST_IsValid](#)). Use [ST_SimplifyPreserveTopology](#) to preserve topology and ensure validity. [ST_CoverageSimplify](#) also preserves topology and validity.

**Note**

This function does not preserve boundaries shared between polygons. Use `ST_CoverageSimplify` if this is required.

**Note**

返回 3 个结果, 每个结果都是一个多边形。

2.2.0 简化几何体。


线

A LineString is simplified with a minimum-area tolerance of 30.

```
SELECT ST_AsText(ST_SimplifyVW(geom,30)) simplified
FROM (SELECT 'LINESTRING(5 2, 3 8, 6 20, 7 25, 10 10)'::geometry AS geom) AS t;


simplified
-----
LINESTRING(5 2,7 25,10 10)
```

Simplifying a line.



```
SELECT ST_SimplifyVW(
  'LINESTRING (10 10, 50 40, 30 70, 50 60, 70 80, 50 110, 100 100, 90 140, 100 180, 150
    170, 170 140, 190 90, 180 40, 110 40, 150 20)',
  1600);
```

Simplifying a polygon.



```
SELECT ST_SimplifyVW(
  'MULTIPOLYGON (((90 110, 80 180, 50 160, 10 170, 10 140, 20 110, 90 110)), ((40 80, 100 80, 120 160, 170 180, 190 70, 140 10, 110 40, 60 40, 40 80), (180 70, 170 110, 142.5 128.5, 128.5 77.5, 90 60, 180 70)))',
  40);
```

图例

[ST_SetEffectiveArea](#), [ST_Simplify](#), [ST_SimplifyPreserveTopology](#), [ST_CoverageSimplify](#), [Topology ST_Simplify](#)

7.14.26 ST_SetEffectiveArea

ST_SetEffectiveArea — Sets the effective area for each vertex, using the Visvalingam-Whyatt algorithm.

Synopsis

geometry **ST_SetEffectiveArea**(geometry geom, float threshold = 0, integer set_area = 1);

图例

图例展示了 ST_SetEffectiveArea 函数的使用。图中显示了一个多边形，其顶点被标记为 M。图中还显示了该多边形的简化版本，其顶点被标记为 0。图中还显示了该多边形的简化版本，其顶点被标记为 0。图中还显示了该多边形的简化版本，其顶点被标记为 0。

图例展示了 ST_SetEffectiveArea 函数的使用。图中显示了一个多边形，其顶点被标记为 M。图中还显示了该多边形的简化版本，其顶点被标记为 0。图中还显示了该多边形的简化版本，其顶点被标记为 0。图中还显示了该多边形的简化版本，其顶点被标记为 0。

图例展示了 ST_SetEffectiveArea 函数的使用。图中显示了一个多边形，其顶点被标记为 M。图中还显示了该多边形的简化版本，其顶点被标记为 0。图中还显示了该多边形的简化版本，其顶点被标记为 0。图中还显示了该多边形的简化版本，其顶点被标记为 0。



Note

图例展示了 ST_SetEffectiveArea 函数的使用。图中显示了一个多边形，其顶点被标记为 M。图中还显示了该多边形的简化版本，其顶点被标记为 0。图中还显示了该多边形的简化版本，其顶点被标记为 0。图中还显示了该多边形的简化版本，其顶点被标记为 0。

**Note**

ST_Simplify (topology) 函数在简化几何体时会保留拓扑关系。ST_SimplifyPreserveTopology 函数不会保留拓扑关系。

**Note**

ST_Simplify M 函数在简化几何体时会保留多面体关系。

**Note**

ST_Simplify 3 函数在简化几何体时，会保留几何体的拓扑关系。

2.2.0 版本中的 ST_Simplify 函数

ST_Simplify

ST_Simplify 函数在简化几何体时，会根据指定的阈值来简化几何体。ST_Simplify 0 函数在简化几何体时，会保留几何体的拓扑关系。

```
select ST_AsText(ST_SetEffectiveArea(geom)) all_pts, ST_AsText(ST_SetEffectiveArea(geom,30) ↔
) thrshld_30
FROM (SELECT 'LINESTRING(5 2, 3 8, 6 20, 7 25, 10 10)'::geometry geom) As foo;
-result
all_pts | thrshld_30
-----+-----
LINESTRING M (5 2 3.40282346638529e+38,3 8 29,6 20 1.5,7 25 49.5,10 10 3.40282346638529e ↔
+38) | LINESTRING M (5 2 3.40282346638529e+38,7 25 49.5,10 10 3.40282346638529e+38)
```

ST_Simplify

ST_SimplifyVW

7.14.27 ST_TriangulatePolygon

ST_TriangulatePolygon — Computes the constrained Delaunay triangulation of polygons

Synopsis

geometry **ST_TriangulatePolygon**(geometry geom);

ST_TriangulatePolygon

Computes the constrained Delaunay triangulation of polygons. Holes and Multipolygons are supported.

The “constrained Delaunay triangulation” of a polygon is a set of triangles formed from the vertices of the polygon, and covering it exactly, with the maximum total interior angle over all possible triangulations. It provides the “best quality” triangulation of the polygon.

Availability: 3.3.0.

Requires GEOS >= 3.11.0.

图 10.1

Triangulation of a square.

```
SELECT ST_AsText(
  ST_TriangulatePolygon('POLYGON((0 0, 0 1, 1 1, 1 0, 0 0))');

```


st_astext

GEOMETRYCOLLECTION(POLYGON((0 0,0 1,1 1,0 0)),POLYGON((1 1,1 0,0 0,1 1)))

图 10.2

Triangulation of the letter P.

```
SELECT ST_AsText(ST_TriangulatePolygon(
  'POLYGON ((26 17, 31 19, 34 21, 37 24, 38 29, 39 43, 39 161, 38 172, 36 176, 34 179, 30 181, 25 183, 10 185, 10 190, 100 190, 121 189, 139 187, 154 182, 167 177, 177 169, 184 161, 189 152, 190 141, 188 128, 186 123, 184 117, 180 113, 176 108, 170 104, 164 101, 151 96, 136 92, 119 89, 100 89, 86 89, 73 89, 73 39, 74 32, 75 27, 77 23, 79 20, 83 18, 89 17, 106 15, 106 10, 10 10, 10 15, 26 17), (152 147, 151 152, 149 157, 146 162, 142 166, 137 169, 132 172, 126 175, 118 177, 109 179, 99 180, 89 180, 80 179, 76 178, 74 176, 73 171, 73 100, 85 99, 91 99, 102 99, 112 100, 121 102, 128 104, 134 107, 139 110, 143 114, 147 118, 149 123, 151 128, 153 141, 152 147))'
));
```




Polygon Triangulation

Same example as ST_Tessellate

```
SELECT ST_TriangulatePolygon(
  'POLYGON (( 10 190, 10 70, 80 70, 80 130, 50 160, 120 160, 120 190, 10 190
  ))'::geometry
);
```

ST_AsText 图 10.3:


```
GEOMETRYCOLLECTION(POLYGON((50 160,120 190,120 160,50 160))
,POLYGON((10 70,80 130,80 70,10 70))
,POLYGON((50 160,10 70,10 190,50 160))
,POLYGON((120 190,50 160,10 190,120 190))
,POLYGON((80 130,10 70,50 160,80 130)))
```



☒☒

[ST_ConstrainedDelaunayTriangles](#), [ST_DelaunayTriangles](#), [ST_Tessellate](#)

7.14.28 ST_VoronoiLines

ST_VoronoiLines — Returns the boundaries of the Voronoi diagram of the vertices of a geometry.

Synopsis

geometry **ST_VoronoiLines**(geometry geom , float8 tolerance = 0.0 , geometry extend_to = NULL);

☒☒

Computes a two-dimensional **Voronoi diagram** from the vertices of the supplied geometry and returns the boundaries between cells in the diagram as a MultiLineString. Returns null if input geometry is null. Returns an empty geometry collection if the input geometry contains only one vertex. Returns an empty geometry collection if the extend_to envelope has zero area.


☒☒☒☒☒☒☒☒:

- **tolerance**: The distance within which vertices will be considered equivalent. Robustness of the algorithm can be improved by supplying a nonzero tolerance distance. (default = 0.0)
- **extend_to**: If present, the diagram is extended to cover the envelope of the supplied geometry, unless smaller than the default envelope (default = NULL, default envelope is the bounding box of the input expanded by about 50%).

GEOS 3.10.4

2.3.0 简体中文版.

图



Voronoi diagram lines, with tolerance of 30 units

```
SELECT ST_VoronoiLines(
    'MULTIPOINT (50 30, 60 30, 100 100,10 150, 110 120) '::geometry,
    30) AS geom;
```

ST_AsText output

```
MULTILINESTRING((135.555555555556 270,36.8181818181818 92.2727272727273),(36.8181818181818 92.2727272727273,-110 43.3333333333333),(230 -45.7142857142858,36.8181818181818 92.2727272727273))
```

图

[ST_DelaunayTriangles](#), [ST_VoronoiPolygons](#)

7.14.29 ST_VoronoiPolygons

ST_VoronoiPolygons — Returns the cells of the Voronoi diagram of the vertices of a geometry.

Synopsis

```
geometry ST_VoronoiPolygons( geometry geom , float8 tolerance = 0.0 , geometry extend_to = NULL );
```

ST_VoronoiPolygons

Computes a two-dimensional **Voronoi diagram** from the vertices of the supplied geometry. The result is a GEOMETRYCOLLECTION of POLYGONs that covers an envelope larger than the extent of the input vertices. Returns null if input geometry is null. Returns an empty geometry collection if the input geometry contains only one vertex. Returns an empty geometry collection if the extend_to envelope has zero area.


函数参数:

- **tolerance**: The distance within which vertices will be considered equivalent. Robustness of the algorithm can be improved by supplying a nonzero tolerance distance. (default = 0.0)
- **extend_to**: If present, the diagram is extended to cover the envelope of the supplied geometry, unless smaller than the default envelope (default = NULL, default envelope is the bounding box of the input expanded by about 50%).

GEOS 函数

2.3.0 函数。

示例




Points overlaid on top of Voronoi diagram

```
SELECT ST_VoronoiPolygons(
    'MULTIPOINT (50 30, 60 30, 100 100,10 150, 110 120) '::geometry
) AS geom;
```

ST_AsText output

```
GEOMETRYCOLLECTION(POLYGON((-110 43.3333333333333, -110 270, 100.5 270, 59.3478260869565 ↵
    132.826086956522, 36.8181818181818 92.2727272727273, -110 43.3333333333333)),
POLYGON((55 -90, -110 -90, -110 43.3333333333333, 36.8181818181818 92.2727272727273, 55 ↵
    79.2857142857143, 55 -90)),
POLYGON((230 47.5, 230 -20.7142857142857, 55 79.2857142857143, 36.8181818181818 ↵
    92.2727272727273, 59.3478260869565 132.826086956522, 230 47.5)), POLYGON((230 ↵
    -20.7142857142857, 230 -90, 55 -90, 55 79.2857142857143, 230 -20.7142857142857)),
POLYGON((100.5 270, 230 270, 230 47.5, 59.3478260869565 132.826086956522, 100.5 270)))
```



Voronoi diagram, with tolerance of 30 units

```
SELECT ST_VoronoiPolygons(
    'MULTIPOINT (50 30, 60 30, 100 100,10 150, 110 120) '::geometry,
    30) AS geom;
```

ST_AsText output

```
GEOMETRYCOLLECTION(POLYGON((-110 43.3333333333333, -110 270, 100.5 270, 59.3478260869565 ↔
    132.826086956522, 36.8181818181818 92.2727272727273, -110 43.3333333333333)),
POLYGON((230 47.5, 230 -45.7142857142858, 36.8181818181818 92.2727272727273, 59.3478260869565 ↔
    132.826086956522, 230 47.5)), POLYGON((230 -45.7142857142858, 230 -90, -110 -90, -110 ↔
    43.3333333333333, 36.8181818181818 92.2727272727273, 230 -45.7142857142858)),
POLYGON((100.5 270, 230 270, 230 47.5, 59.3478260869565 132.826086956522, 100.5 270)))
```

☒☒

[ST_DelaunayTriangles](#), [ST_VoronoiLines](#)

7.15 Coverages

7.15.1 ST_CoverageInvalidEdges

ST_CoverageInvalidEdges — Window function that finds locations where polygons fail to form a valid coverage.

Synopsis

```
geometry ST_CoverageInvalidEdges(geometry winset geom, float8 tolerance = 0);
```

☒☒

A window function which checks if the polygons in the window partition form a valid polygonal coverage. It returns linear indicators showing the location of invalid edges (if any) in each polygon.

A set of valid polygons is a valid coverage if the following conditions hold:

- **Non-overlapping** - polygons do not overlap (their interiors do not intersect)
- **Edge-Matched** - vertices along shared edges are identical


As a window function a value is returned for every input polygon. For polygons which violate one or more of the validity conditions the return value is a MULTILINESTRING containing the problematic edges. Coverage-valid polygons return the value NULL. Non-polygonal or empty geometries also produce NULL values.

The conditions allow a valid coverage to contain holes (gaps between polygons), as long as the surrounding polygons are edge-matched. However, very narrow gaps are often undesirable. If the *tolerance* parameter is specified with a non-zero distance, edges forming narrower gaps will also be returned as invalid.

The polygons being checked for coverage validity must also be valid geometries. This can be checked with [ST_IsValid](#).

Availability: 3.4.0

Requires GEOS >= 3.12.0



Invalid edges caused by overlap and non-matching vertices

```
WITH coverage(id, geom) AS (VALUES
  (1, 'POLYGON ((10 190, 30 160, 40 110, 100 70, 120 10, 10 10, 10 190))'::geometry),
  (2, 'POLYGON ((100 190, 10 190, 30 160, 40 110, 50 80, 74 110.5, 100 130, 140 120, 140 160, 100 190))'::geometry),
  (3, 'POLYGON ((140 190, 190 190, 190 80, 140 80, 140 190))'::geometry),
  (4, 'POLYGON ((180 40, 120 10, 100 70, 140 80, 190 80, 180 40))'::geometry)
)
SELECT id, ST_AsText(ST_CoverageInvalidEdges(geom) OVER ())
FROM coverage;
```

id	st_astext
1	LINESTRING (40 110, 100 70)
2	MULTILINESTRING ((100 130, 140 120, 140 160, 100 190), (40 110, 50 80, 74 110.5))
3	LINESTRING (140 80, 140 190)
4	null

```
-- Test entire table for coverage validity
SELECT true = ALL (
    SELECT ST_CoverageInvalidEdges(geom) OVER () IS NULL
    FROM coverage
);
```

☒☒

[ST_IsValid](#), [ST_CoverageUnion](#), [ST_CoverageSimplify](#)

7.15.2 ST_CoverageSimplify

`ST_CoverageSimplify` — Window function that simplifies the edges of a polygonal coverage.

Synopsis

geometry **ST_CoverageSimplify**(geometry winset geom, float8 tolerance, boolean simplifyBoundary = true);

☒☒

A window function which simplifies the edges of polygons in a polygonal coverage. The simplification preserves the coverage topology. This means the simplified output polygons are consistent along shared edges, and still form a valid coverage.

The simplification uses a variant of the [Visvalingam-Whyatt algorithm](#). The *tolerance* parameter has units of distance, and is roughly equal to the square root of triangular areas to be simplified.

To simplify only the “internal” edges of the coverage (those that are shared by two polygons) set the *simplifyBoundary* parameter to false.




Note

If the input is not a valid coverage there may be unexpected artifacts in the output (such as boundary intersections, or separated boundaries which appeared to be shared). Use [ST_CoverageInvalidEdges](#) to determine if a coverage is valid.

Availability: 3.4.0

Requires GEOS >= 3.12.0

☒☒



```
WITH coverage(id, geom) AS (VALUES
  (1, 'POLYGON ((160 150, 110 130, 90 100, 90 70, 60 60, 50 10, 30 30, 40 50, 25 40, 10 60, 30 100, 30 120, 20 170, 60 180, 90 190, 130 180, 130 160, 160 150), (40 160, 50 140, 66 125, 60 100, 80 140, 90 170, 60 160, 40 160))'::geometry),
  (2, 'POLYGON ((40 160, 60 160, 90 170, 80 140, 60 100, 66 125, 50 140, 40 160))'::geometry),
  (3, 'POLYGON ((110 130, 160 50, 140 50, 120 33, 90 30, 50 10, 60 60, 90 70, 90 100, 110 130))'::geometry),
  (4, 'POLYGON ((160 150, 150 120, 160 90, 160 50, 110 130, 160 150))'::geometry)
)
SELECT id, ST_AsText(ST_CoverageSimplify(geom, 30) OVER ())
FROM coverage;
```

id	st_astext
1	POLYGON ((160 150, 110 130, 50 10, 10 60, 20 170, 90 190, 160 150), (40 160, 66 125, 90 170, 40 160))
2	POLYGON ((40 160, 66 125, 90 170, 40 160))
3	POLYGON ((110 130, 160 50, 50 10, 110 130))
4	POLYGON ((160 150, 160 50, 110 130, 160 150))



ST_CoverageInvalidEdges

7.15.3 ST_CoverageUnion

ST_CoverageUnion — Computes the union of a set of polygons forming a coverage by removing shared edges.

Synopsis

geometry **ST_CoverageUnion**(geometry set geom);

ST_CoverageUnion

An aggregate function which unions a set of polygons forming a polygonal coverage. The result is a polygonal geometry covering the same area as the coverage. This function produces the same result as [ST_Union](#), but uses the coverage structure to compute the union much faster.




Note

If the input is not a valid coverage there may be unexpected artifacts in the output (such as unmerged or overlapping polygons). Use [ST_CoverageInvalidEdges](#) to determine if a coverage is valid.

Availability: 3.4.0 - requires GEOS >= 3.8.0

Examples



```
WITH coverage(id, geom) AS (VALUES
  (1, 'POLYGON ((10 10, 10 150, 80 190, 110 150, 90 110, 40 110, 50 60, 10 10))'::geometry) ←
  (2, 'POLYGON ((120 10, 10 10, 50 60, 100 70, 120 10))'::geometry),
  (3, 'POLYGON ((140 80, 120 10, 100 70, 40 110, 90 110, 110 150, 140 80))'::geometry),
  (4, 'POLYGON ((140 190, 120 170, 140 130, 160 150, 140 190))'::geometry),
  (5, 'POLYGON ((180 160, 170 140, 140 130, 160 150, 140 190, 180 160))'::geometry)
)
SELECT ST_AsText(ST_CoverageUnion(geom))
FROM coverage;

-----
MULTIPOLYGON (((10 150, 80 190, 110 150, 140 80, 120 10, 10 10, 10 150), (50 60, 100 70, 40 ←
  110, 50 60)), ((120 170, 140 190, 180 160, 170 140, 140 130, 120 170)))
```

See also

[ST_CoverageInvalidEdges](#), [ST_AsBinary](#)

7.16 Affine Transformations

7.16.1 ST_Affine

ST_Affine — Apply a 3D affine transformation to a geometry.

Synopsis

```
geometry ST_Affine(geometry geomA, float a, float b, float c, float d, float e, float f, float g, float h,
float i, float xoff, float yoff, float zoff);
geometry ST_Affine(geometry geomA, float a, float b, float d, float e, float xoff, float yoff);
```

⚠

Applies a 3D affine transformation to the geometry to do things like translate, rotate, scale in one step.

Version 1: The call

```
ST_Affine(geom, a, b, c, d, e, f, g, h, i, xoff, yoff, zoff)
```

represents the transformation matrix

```
/ a b c xoff \
| d e f yoff |
| g h i zoff |
\ 0 0 0 1 /
```

and the vertices are transformed as follows:

```
x' = a*x + b*y + c*z + xoff
y' = d*x + e*y + f*z + yoff
z' = g*x + h*y + i*z + zoff
```

All of the translate / scale functions below are expressed via such an affine transformation.

Version 2: Applies a 2d affine transformation to the geometry. The call

```
ST_Affine(geom, a, b, d, e, xoff, yoff)
```

represents the transformation matrix

```
/ a b 0 xoff \      / a b xoff \
| d e 0 yoff |  rsp. | d e yoff |
| 0 0 1 0  |      \ 0 0 1 /
\ 0 0 0 1 /
```

and the vertices are transformed as follows:

```
x' = a*x + b*y + xoff
y' = d*x + e*y + yoff
z' = z
```

This method is a subcase of the 3D method above.

⚠: 2.0.0 文档, 文档 TIN 文档.

Availability: 1.1.2. Name changed from Affine to ST_Affine in 1.2.2

**Note**

1.3.4 版本 (curve) 支持。1.3.4 版本支持。



This function supports Polyhedral surfaces.



This function supports Triangles and Triangulated Irregular Network Surfaces (TIN).



This function supports 3d and will not drop the z-index.



This method supports Circular Strings and Curves.

❏

```
--Rotate a 3d line 180 degrees about the z axis. Note this is long-hand for doing ↵
ST_Rotate();
SELECT ST_AsEWKT(ST_Affine(geom, cos(pi()), -sin(pi()), 0, sin(pi()), cos(pi()), 0, 0, ↵
    0, 1, 0, 0, 0)) As using_affine,
    ST_AsEWKT(ST_Rotate(geom, pi())) As using_rotate
FROM (SELECT ST_GeomFromEWKT('LINESTRING(1 2 3, 1 4 3)') As geom) As foo;
      using_affine      |      using_rotate
-----+-----
LINESTRING(-1 -2 3,-1 -4 3) | LINESTRING(-1 -2 3,-1 -4 3)
(1 row)

--Rotate a 3d line 180 degrees in both the x and z axis
SELECT ST_AsEWKT(ST_Affine(geom, cos(pi()), -sin(pi()), 0, sin(pi()), cos(pi()), -sin(pi()) ↵
    , 0, sin(pi()), cos(pi()), 0, 0, 0))
FROM (SELECT ST_GeomFromEWKT('LINESTRING(1 2 3, 1 4 3)') As geom) As foo;
      st_asewkt
-----
LINESTRING(-1 -2 -3,-1 -4 -3)
(1 row)
```

❏

[ST_Rotate](#), [ST_Scale](#), [ST_Translate](#), [ST_TransScale](#)

7.16.2 ST_Rotate

ST_Rotate — Rotates a geometry about an origin point.

Synopsis

```
geometry ST_Rotate(geometry geomA, float rotRadians);
geometry ST_Rotate(geometry geomA, float rotRadians, float x0, float y0);
geometry ST_Rotate(geometry geomA, float rotRadians, geometry pointOrigin);
```

ST_Rotate

Rotates geometry *rotRadians* counter-clockwise about the origin point. The rotation origin can be specified either as a POINT geometry, or as x and y coordinates. If the origin is not specified, the geometry is rotated about POINT(0 0).

历史: 2.0.0 支持 3D 几何体, 支持 TIN 几何体。

Enhanced: 2.0.0 additional parameters for specifying the origin of rotation were added.

Availability: 1.1.2. Name changed from Rotate to ST_Rotate in 1.2.2

- ✔ This function supports 3d and will not drop the z-index.
- ✔ This method supports Circular Strings and Curves.
- ✔ This function supports Polyhedral surfaces.
- ✔ This function supports Triangles and Triangulated Irregular Network Surfaces (TIN).

示例

```
--Rotate 180 degrees
SELECT ST_AsEWKT(ST_Rotate('LINESTRING (50 160, 50 50, 100 50)', pi()));
           st_asewkt
-----
LINESTRING(-50 -160,-50 -50,-100 -50)
(1 row)

--Rotate 30 degrees counter-clockwise at x=50, y=160
SELECT ST_AsEWKT(ST_Rotate('LINESTRING (50 160, 50 50, 100 50)', pi()/6, 50, 160));
           st_asewkt
-----
LINESTRING(50 160,105 64.7372055837117,148.301270189222 89.7372055837117)
(1 row)

--Rotate 60 degrees clockwise from centroid
SELECT ST_AsEWKT(ST_Rotate(geom, -pi()/3, ST_Centroid(geom)))
FROM (SELECT 'LINESTRING (50 160, 50 50, 100 50)'::geometry AS geom) AS foo;
           st_asewkt
-----
LINESTRING(116.4225 130.6721,21.1597 75.6721,46.1597 32.3708)
(1 row)
```

其他函数

[ST_Affine](#), [ST_RotateX](#), [ST_RotateY](#), [ST_RotateZ](#)

7.16.3 ST_RotateX

ST_RotateX — Rotates a geometry about the X axis.

Synopsis

geometry **ST_RotateX**(geometry geomA, float rotRadians);

☒☒

Rotates a geometry geomA - rotRadians about the X axis.



Note

ST_RotateX(geomA, rotRadians) is short-hand for ST_Affine(geomA, 1, 0, 0, 0, cos(rotRadians), -sin(rotRadians), 0, sin(rotRadians), cos(rotRadians), 0, 0, 0).

☒☒☒☒: 2.0.0 函数参考, ☒☒☒☒ TIN 函数参考.

Availability: 1.1.2. Name changed from RotateX to ST_RotateX in 1.2.2

- ✔ This function supports Polyhedral surfaces.
- ✔ This function supports 3d and will not drop the z-index.
- ✔ This function supports Triangles and Triangulated Irregular Network Surfaces (TIN).

☒☒

```
--Rotate a line 90 degrees along x-axis
SELECT ST_AsEWKT(ST_RotateX(ST_GeomFromEWKT('LINESTRING(1 2 3, 1 1 1)'), pi()/2));
           st_asewkt
-----
LINESTRING(1 -3 2,1 -1 1)
```

☒☒

ST_Affine, ST_RotateY, ST_RotateZ

7.16.4 ST_RotateY

ST_RotateY — Rotates a geometry about the Y axis.

Synopsis

geometry **ST_RotateY**(geometry geomA, float rotRadians);

☒☒

Rotates a geometry geomA - rotRadians about the y axis.



Note

ST_RotateY(geomA, rotRadians) is short-hand for ST_Affine(geomA, cos(rotRadians), 0, sin(rotRadians), 0, 1, 0, -sin(rotRadians), 0, cos(rotRadians), 0, 0, 0).

Availability: 1.1.2. Name changed from RotateY to ST_RotateY in 1.2.2

版本: 2.0.0 支持多面体, 支持 TIN 支持。



This function supports Polyhedral surfaces.



This function supports 3d and will not drop the z-index.



This function supports Triangles and Triangulated Irregular Network Surfaces (TIN).

例

```
--Rotate a line 90 degrees along y-axis
SELECT ST_AsEWKT(ST_RotateY(ST_GeomFromEWKT('LINESTRING(1 2 3, 1 1 1)'), pi()/2));
           st_asewkt
-----
LINESTRING(3 2 -1,1 1 -1)
```

例

ST_Affine, ST_RotateX, ST_RotateZ

7.16.5 ST_RotateZ

ST_RotateZ — Rotates a geometry about the Z axis.

Synopsis

geometry **ST_RotateZ**(geometry geomA, float rotRadians);

例

Rotates a geometry geomA - rotRadians about the Z axis.



Note

This is a synonym for ST_Rotate



Note

ST_RotateZ(geomA, rotRadians) is short-hand for SELECT ST_Affine(geomA, cos(rotRadians), -sin(rotRadians), 0, sin(rotRadians), cos(rotRadians), 0, 0, 0, 1, 0, 0, 0).

版本: 2.0.0 支持多面体, 支持 TIN 支持。

Availability: 1.1.2. Name changed from RotateZ to ST_RotateZ in 1.2.2

**Note**

1.3.4 版本中，`ST_Azimuth` (curve) 函数在 1.3.4 版本中进行了更新。1.3.4 版本中，`ST_Azimuth` 函数在 1.3.4 版本中进行了更新。



This function supports 3d and will not drop the z-index.



This method supports Circular Strings and Curves.



This function supports Polyhedral surfaces.



This function supports Triangles and Triangulated Irregular Network Surfaces (TIN).

SQL

```
--Rotate a line 90 degrees along z-axis
SELECT ST_AsEWKT(ST_RotateZ(ST_GeomFromEWKT('LINESTRING(1 2 3, 1 1 1)'), pi()/2));
          st_asewkt
-----
LINESTRING(-2 1 3,-1 1 1)

--Rotate a curved circle around z-axis
SELECT ST_AsEWKT(ST_RotateZ(geom, pi()/2))
FROM (SELECT ST_LineToCurve(ST_Buffer(ST_GeomFromText('POINT(234 567)'), 3)) As geom) As
foo;

-----

CURVEPOLYGON(CIRCULARSTRING(-567 237,-564.87867965644 236.12132034356,-564
234,-569.12132034356 231.87867965644,-567 237))
```

SQL

[ST_Affine](#), [ST_RotateX](#), [ST_RotateY](#)

7.16.6 ST_Scale

`ST_Scale` — Scales a geometry by given factors.

Synopsis

```
geometry ST_Scale(geometry geomA, float XFactor, float YFactor, float ZFactor);
geometry ST_Scale(geometry geomA, float XFactor, float YFactor);
geometry ST_Scale(geometry geom, geometry factor);
geometry ST_Scale(geometry geom, geometry factor, geometry origin);
```

缩放

Scales the geometry to a new size by multiplying the ordinates with the corresponding factor parameters.

The version taking a geometry as the **factor** parameter allows passing a 2d, 3dm, 3dz or 4d point to set scaling factor for all supported dimensions. Missing dimensions in the factor point are equivalent to no scaling the corresponding dimension.

The three-geometry variant allows a "false origin" for the scaling to be passed in. This allows "scaling in place", for example using the centroid of the geometry as the false origin. Without a false origin, scaling takes place relative to the actual origin, so all coordinates are just multiplied by the scale factor.

**Note**

1.3.4 支持曲线 (curve) 缩放。1.3.4 支持缩放曲线。

Availability: 1.1.0.

支持: 2.0.0 支持 TIN 缩放。

Enhanced: 2.2.0 support for scaling all dimension (**factor** parameter) was introduced.

Enhanced: 2.5.0 support for scaling relative to a local origin (**origin** parameter) was introduced.

- ✓ This function supports Polyhedral surfaces.
- ✓ This function supports 3d and will not drop the z-index.
- ✓ This method supports Circular Strings and Curves.
- ✓ This function supports Triangles and Triangulated Irregular Network Surfaces (TIN).
- ✓ This function supports M coordinates.

示例

```
--Version 1: scale X, Y, Z
SELECT ST_AsEWKT(ST_Scale(ST_GeomFromEWKT('LINESTRING(1 2 3, 1 1 1)'), 0.5, 0.75, 0.8));
          st_asewkt
-----
LINESTRING(0.5 1.5 2.4,0.5 0.75 0.8)

--Version 2: Scale X Y
SELECT ST_AsEWKT(ST_Scale(ST_GeomFromEWKT('LINESTRING(1 2 3, 1 1 1)'), 0.5, 0.75));
          st_asewkt
-----
LINESTRING(0.5 1.5 3,0.5 0.75 1)

--Version 3: Scale X Y Z M
SELECT ST_AsEWKT(ST_Scale(ST_GeomFromEWKT('LINESTRING(1 2 3 4, 1 1 1 1)'),
  ST_MakePoint(0.5, 0.75, 2, -1)));
          st_asewkt
-----
LINESTRING(0.5 1.5 6 -4,0.5 0.75 2 -1)
```

```
--Version 4: Scale X Y using false origin
SELECT ST_AsText(ST_Scale('LINESTRING(1 1, 2 2)', 'POINT(2 2)', 'POINT(1 1)::geometry'));
      st_astext
-----
LINESTRING(1 1,3 3)
```

☐☐

ST_Affine, ST_TransScale

7.16.7 ST_Translate

ST_Translate — Translates a geometry by given offsets.

Synopsis

geometry **ST_Translate**(geometry g1, float deltax, float deltax);
 geometry **ST_Translate**(geometry g1, float deltax, float deltax, float deltaz);

☐☐

Returns a new geometry whose coordinates are translated delta x,delta y,delta z units. Units are based on the units defined in spatial reference (SRID) for this geometry.



Note

1.3.4 在曲线 (curve) 上使用 ST_Translate 函数。1.3.4 在曲线上使用 ST_Translate 函数。

1.2.2 在曲线上使用 ST_Translate 函数。



This function supports 3d and will not drop the z-index.



This method supports Circular Strings and Curves.

☐☐

Move a point 1 degree longitude

```
SELECT ST_AsText(ST_Translate(ST_GeomFromText('POINT(-71.01 42.37)',4326),1,0)) As ↵
      wgs_transgeomtxt;
      wgs_transgeomtxt
-----
POINT(-70.01 42.37)
```

Move a linestring 1 degree longitude and 1/2 degree latitude


```
SELECT ST_AsText(ST_Translate(ST_GeomFromText('LINESTRING(-71.01 42.37,-71.11 42.38)',4326) ↵
,1,0.5)) As wgs_transgeomtxt;
           wgs_transgeomtxt
-----
LINESTRING(-70.01 42.87,-70.11 42.88)
```

Move a 3d point

```
SELECT ST_AsEWKT(ST_Translate(CAST('POINT(0 0 0)' As geometry), 5, 12,3));
           st_asewkt
-----
POINT(5 12 3)
```

Move a curve and a point

```
SELECT ST_AsText(ST_Translate(ST_Collect('CURVEPOLYGON(CIRCULARSTRING(4 3,3.12 0.878,1 ↵
0,-1.121 5.1213,6 7, 8 9,4 3))','POINT(1 3)'),1,2));

-----

GEOMETRYCOLLECTION(CURVEPOLYGON(CIRCULARSTRING(5 5,4.12 2.878,2 2,-0.121 7.1213,7 9,9 11,5 ↵
5)),POINT(2 5))
```

☒☒

[ST_Affine](#), [ST_AsText](#), [ST_GeomFromText](#)

7.16.8 ST_TransScale

ST_TransScale — Translates and scales a geometry by given offsets and factors.

Synopsis

geometry **ST_TransScale**(geometry geomA, float deltaX, float deltaY, float XFactor, float YFactor);

☒☒

Translates the geometry using the deltaX and deltaY args, then scales it using the XFactor, YFactor args, working in 2D only.



Note

`ST_TransScale(geomA, deltaX, deltaY, XFactor, YFactor)` is short-hand for `ST_Affine(geomA, XFactor, 0, 0, 0, YFactor, 0, 0, 0, 1, deltaX*XFactor, deltaY*YFactor, 0)`.



Note

1.3.4 简体中文 (curve) 简体中文. 1.3.4 简体中文.

Availability: 1.1.0.



This function supports 3d and will not drop the z-index.



This method supports Circular Strings and Curves.

☒☒

```
SELECT ST_AsEWKT(ST_TransScale(ST_GeomFromEWKT('LINESTRING(1 2 3, 1 1 1)'), 0.5, 1, 1, 2));
           st_asewkt
```

```
-----
LINESTRING(1.5 6 3,1.5 4 1)
```

```
--Buffer a point to get an approximation of a circle, convert to curve and then translate ↩
1,2 and scale it 3,4
```

```
SELECT ST_AsText(ST_Transscale(ST_LineToCurve(ST_Buffer('POINT(234 567)', 3)),1,2,3,4));
```

```
-----
CURVEPOLYGON(CIRCULARSTRING(714 2276,711.363961030679 2267.51471862576,705 ↩
2264,698.636038969321 2284.48528137424,714 2276))
```

☒☒

[ST_Affine](#), [ST_Translate](#)

7.17 Clustering Functions

7.17.1 ST_ClusterDBSCAN

`ST_ClusterDBSCAN` — Window function that returns a cluster id for each input geometry using the DBSCAN algorithm.

Synopsis

integer **ST_ClusterDBSCAN**(geometry winset geom, float8 eps, integer minpoints);

☒☒

A window function that returns a cluster number for each input geometry, using the 2D [Density-based spatial clustering of applications with noise \(DBSCAN\)](#) algorithm. Unlike [ST_ClusterKMeans](#), it does not require the number of clusters to be specified, but instead uses the desired [distance](#) (eps) and density (minpoints) parameters to determine each cluster.

An input geometry is added to a cluster if it is either:

- A “core” geometry, that is within eps [distance](#) of at least minpoints input geometries (including itself); or

- A "border" geometry, that is within eps **distance** of a core geometry.

Note that border geometries may be within eps distance of core geometries in more than one cluster. Either assignment would be correct, so the border geometry will be arbitrarily assigned to one of the available clusters. In this situation it is possible for a correct cluster to be generated with fewer than minpoints geometries. To ensure deterministic assignment of border geometries (so that repeated calls to ST_ClusterDBSCAN will produce identical results) use an ORDER BY clause in the window definition. Ambiguous cluster assignments may differ from other DBSCAN implementations.


Note

Geometries that do not meet the criteria to join any cluster are assigned a cluster number of NULL.


2.3.0 国国国国国国国国国国国国.



This method supports Circular Strings and Curves.

国国

Clustering polygon within 50 meters of each other, and requiring at least 2 polygons per cluster.



Clusters within 50 meters with at least 2 items per cluster. Singletons have NULL for cid

```
SELECT name, ST_ClusterDBSCAN(geom, eps = 50, minpoints = 2) over () AS cid
FROM boston_polys
WHERE name > '' AND building > ''
      AND ST_DWithin(geom,
      ST_Transform(
      ST_GeomFromText('POINT (-71.04054 42.35141)', 4326), 26986),
      500);
```

bucket	name	
0	Manulife Tower	
0	Park Lane Seaport I	
0	Park Lane Seaport II	
0	Renaissance Boston Waterfront Hotel	
0	Seaport Boston Hotel	
0	Seaport Hotel & World Trade Center	
0	Waterside Place	
0	World Trade Center East	
1	100 Northern Avenue	
1	100 Pier 4	
1	The Institute of Contemporary Art	
2	101 Seaport	
2	District Hall	
2	One Marina Park Drive	
2	Twenty Two Liberty	
2	Vertex	
2	Vertex	
2	Watermark Seaport	
2	Blue Hills Bank Pavilion	
NULL	World Trade Center West	
NULL		

(20 rows)

A example showing combining parcels with the same cluster number into geometry collections.

```
SELECT cid, ST_Collect(geom) AS cluster_geom, array_agg(parcel_id) AS ids_in_cluster FROM (
  SELECT parcel_id, ST_ClusterDBSCAN(geom, eps => 0.5, minpoints => 5) over () AS cid, geom
  FROM parcels) sq
GROUP BY cid;
```

ST_DWithin, ST_ClusterKMeans, ST_ClusterIntersecting, ST_ClusterIntersectingWin, ST_ClusterWithin, ST_ClusterWithinWin

7.17.2 ST_ClusterIntersecting

ST_ClusterIntersecting — Aggregate function that clusters input geometries into connected sets.

Synopsis

```
geometry[] ST_ClusterIntersecting(geometry set g);
```

ⓘ

An aggregate function that returns an array of GeometryCollections partitioning the input geometries into connected clusters that are disjoint. Each geometry in a cluster intersects at least one other geometry in the cluster, and does not intersect any geometry in other clusters.

2.2.0 简体中文.

ⓘ

```
WITH testdata AS
  (SELECT unnest(ARRAY['LINESTRING (0 0, 1 1)::geometry',
    'LINESTRING (5 5, 4 4)::geometry',
    'LINESTRING (6 6, 7 7)::geometry',
    'LINESTRING (0 0, -1 -1)::geometry',
    'POLYGON ((0 0, 4 0, 4 4, 0 4, 0 0))::geometry']) AS geom)

SELECT ST_AsText(unnest(ST_ClusterIntersecting(geom))) FROM testdata;

-- result

st_astext
-----
GEOMETRYCOLLECTION(LINESTRING(0 0,1 1),LINESTRING(5 5,4 4),LINESTRING(0 0,-1 -1),POLYGON((0 0,4 0,4 4,0 4,0 0)))
GEOMETRYCOLLECTION(LINESTRING(6 6,7 7))
```

ⓘ

[ST_ClusterIntersectingWin](#), [ST_ClusterWithin](#), [ST_ClusterWithinWin](#)

7.17.3 ST_ClusterIntersectingWin

ST_ClusterIntersectingWin — Window function that returns a cluster id for each input geometry, clustering input geometries into connected sets.

Synopsis

```
integer ST_ClusterIntersectingWin(geometry winset geom);
```

A window function that builds connected clusters of geometries that intersect. It is possible to traverse all geometries in a cluster without leaving the cluster. The return value is the cluster number that the geometry argument participates in, or null for null inputs.

Availability: 3.4.0

```
WITH testdata AS (
  SELECT id, geom::geometry FROM (
    VALUES (1, 'LINESTRING (0 0, 1 1)'),
            (2, 'LINESTRING (5 5, 4 4)'),
            (3, 'LINESTRING (6 6, 7 7)'),
            (4, 'LINESTRING (0 0, -1 -1)'),
            (5, 'POLYGON ((0 0, 4 0, 4 4, 0 4, 0 0))')) AS t(id, geom)
)
SELECT id,
       ST_AsText(geom),
       ST_ClusterIntersectingWin(geom) OVER () AS cluster
FROM testdata;
```

id	st_astext	cluster
1	LINESTRING(0 0,1 1)	0
2	LINESTRING(5 5,4 4)	0
3	LINESTRING(6 6,7 7)	1
4	LINESTRING(0 0,-1 -1)	0
5	POLYGON((0 0,4 0,4 4,0 4,0 0))	0

[ST_ClusterIntersecting](#), [ST_ClusterWithin](#), [ST_ClusterWithinWin](#)

7.17.4 ST_ClusterKMeans

ST_ClusterKMeans — Window function that returns a cluster id for each input geometry using the K-means algorithm.

Synopsis

integer **ST_ClusterKMeans**(geometry winset geom, integer number_of_clusters, float max_radius);

Returns **K-means** cluster number for each input geometry. The distance used for clustering is the distance between the centroids for 2D geometries, and distance between bounding box centers for 3D geometries. For POINT inputs, M coordinate will be treated as weight of input and has to be larger than 0.

max_radius, if set, will cause ST_ClusterKMeans to generate more clusters than k ensuring that no cluster in output has radius larger than max_radius. This is useful in reachability analysis.

Enhanced: 3.2.0 Support for max_radius


Enhanced: 3.1.0 Support for 3D geometries and weights

2.3.0 新新新新新新新新新新新.

新新

Generate dummy set of parcels for examples:

```
CREATE TABLE parcels AS
SELECT lpad((row_number() over())::text,3,'0') As parcel_id, geom,
('{residential, commercial}'::text[])[1 + mod(row_number()OVER(),2)] As type
FROM
  ST_Subdivide(ST_Buffer('SRID=3857;LINESTRING(40 100, 98 100, 100 150, 60 90)'::geometry ←
    40, 'endcap=square'),12) As geom;
```



Parcels color-coded by cluster number (cid)

```
SELECT ST_ClusterKMeans(geom, 3) OVER() AS cid, parcel_id, geom
FROM parcels;
```

cid	parcel_id	geom
0	001	0103000000...
0	002	0103000000...
1	003	0103000000...
0	004	0103000000...
1	005	0103000000...
2	006	0103000000...
2	007	0103000000...

Partitioning parcel clusters by type:

```
SELECT ST_ClusterKMeans(geom, 3) over (PARTITION BY type) AS cid, parcel_id, type
FROM parcels;
```

cid	parcel_id	type
1	005	commercial
1	003	commercial
2	007	commercial
0	001	commercial
1	004	residential
0	002	residential
2	006	residential

Example: Clustering a preaggregated planetary-scale data population dataset using 3D clusering and weighting. Identify at least 20 regions based on **Kontur Population Data** that do not span more than 3000 km from their center:

```
create table kontur_population_3000km_clusters as
select
  geom,
  ST_ClusterKMeans(
    ST_Force4D(
      ST_Transform(ST_Force3D(geom), 4978), -- cluster in 3D XYZ CRS
      mvalue => population -- set clustering to be weighed by population
    ),
    20, -- aim to generate at least 20 clusters
    max_radius => 3000000 -- but generate more to make each under 3000 km radius
  ) over () as cid
from
  kontur_population;
```



World population clustered to above specs produces 46 clusters. Clusters are centered at well-populated regions (New York, Moscow). Greenland is one cluster. There are island clusters that span across the antimeridian. Cluster edges follow Earth’s curvature.

ST_ClusterDBSCAN, **ST_ClusterIntersectingWin**, **ST_ClusterWithinWin**, **ST_ClusterIntersecting**, **ST_ClusterST_Subdivide**, **ST_Force3D**, **ST_Force4D**,

7.17.5 ST_ClusterWithin

ST_ClusterWithin — Aggregate function that clusters geometries by separation distance.

Synopsis

geometry[] **ST_ClusterWithin**(geometry set g, float8 distance);



An aggregate function that returns an array of GeometryCollections, where each collection is a cluster containing some input geometries. Clustering partitions the input geometries into sets in which each geometry is within the specified *distance* of at least one other geometry in the same cluster. Distances are Cartesian distances in the units of the SRID.

ST_ClusterWithin is equivalent to running **ST_ClusterDBSCAN** with `minpoints => 0`.

2.2.0 简体中文.



This method supports Circular Strings and Curves.



```
WITH testdata AS
  (SELECT unnest(ARRAY['LINESTRING (0 0, 1 1)::geometry',
                      'LINESTRING (5 5, 4 4)::geometry',
                      'LINESTRING (6 6, 7 7)::geometry',
                      'LINESTRING (0 0, -1 -1)::geometry',
                      'POLYGON ((0 0, 4 0, 4 4, 0 4, 0 0))::geometry']) AS geom)

SELECT ST_AsText(unnest(ST_ClusterWithin(geom, 1.4))) FROM testdata;

--result

st_astext
-----
GEOMETRYCOLLECTION(LINESTRING(0 0,1 1),LINESTRING(5 5,4 4),LINESTRING(0 0,-1 -1),POLYGON((0 0,4 0,4 4,0 4,0 0)))
GEOMETRYCOLLECTION(LINESTRING(6 6,7 7))
```



ST_ClusterWithinWin, **ST_ClusterDBSCAN**, **ST_ClusterIntersecting**, **ST_ClusterIntersectingWin**

7.17.6 ST_ClusterWithinWin

ST_ClusterWithinWin — Window function that returns a cluster id for each input geometry, clustering using separation distance.

Synopsis

integer **ST_ClusterWithinWin**(geometry winset geom, float8 distance);



A window function that returns a cluster number for each input geometry. Clustering partitions the geometries into sets in which each geometry is within the specified distance of at least one other geometry in the same cluster. Distances are Cartesian distances in the units of the SRID.

ST_ClusterWithinWin is equivalent to running **ST_ClusterDBSCAN** with `minpoints => 0`.

Availability: 3.4.0



This method supports Circular Strings and Curves.

```
WITH testdata AS (  
  SELECT id, geom::geometry FROM (  
    VALUES (1, 'LINESTRING (0 0, 1 1)'),  
            (2, 'LINESTRING (5 5, 4 4)'),  
            (3, 'LINESTRING (6 6, 7 7)'),  
            (4, 'LINESTRING (0 0, -1 -1)'),  
            (5, 'POLYGON ((0 0, 4 0, 4 4, 0 4, 0 0))') AS t(id, geom)  
  )  
SELECT id,  
       ST_AsText(geom),  
       ST_ClusterWithin(geom, 1.4) OVER () AS cluster  
FROM testdata;
```

id	st_astext	cluster
1	LINESTRING(0 0,1 1)	0
2	LINESTRING(5 5,4 4)	0
3	LINESTRING(6 6,7 7)	1
4	LINESTRING(0 0,-1 -1)	0
5	POLYGON((0 0,4 0,4 4,0 4,0 0))	0

[ST_ClusterWithin](#), [ST_ClusterDBSCAN](#), [ST_ClusterIntersecting](#), [ST_ClusterIntersectingWin](#),

7.18 Bounding Box Functions

7.18.1 Box2D

Box2D — Returns a BOX2D representing the 2D extent of a geometry.

Synopsis

box2d **Box2D**(geometry geom);

Returns a **box2d** representing the 2D extent of the geometry.

Compatibility: 2.0.0 **Geometry Types:** **POINT**, **LINESTRING**, **POLYGON**, **TIN**, **MULTIPOINT**, **MULTILINESTRING**, **MULTIPOLYGON**.

-  This method supports Circular Strings and Curves.
-  This function supports Polyhedral surfaces.
-  This function supports Triangles and Triangulated Irregular Network Surfaces (TIN).

例

```
SELECT Box2D(ST_GeomFromText('LINESTRING(1 2, 3 4, 5 6)'));
```

```
box2d
```

```
-----
```

```
BOX(1 2,5 6)
```

```
SELECT Box2D(ST_GeomFromText('CIRCULARSTRING(220268 150415,220227 150505,220227 150406)'));
```

```
box2d
```

```
-----
```

```
BOX(220186.984375 150406,220288.25 150506.140625)
```

例

Box3D, ST_GeomFromText

7.18.2 Box3D

Box3D — Returns a BOX3D representing the 3D extent of a geometry.

Synopsis

box3d **Box3D**(geometry geom);

例

Returns a **box3d** representing the 3D extent of the geometry.

例: 2.0.0 版本, 支持 TIN 几何体。

- ✓ This method supports Circular Strings and Curves.
- ✓ This function supports Polyhedral surfaces.
- ✓ This function supports Triangles and Triangulated Irregular Network Surfaces (TIN).
- ✓ This function supports 3d and will not drop the z-index.

例

```
SELECT Box3D(ST_GeomFromEWKT('LINESTRING(1 2 3, 3 4 5, 5 6 5)'));
```

```
Box3d
```

```
-----
```

```
BOX3D(1 2 3,5 6 5)
```

```
SELECT Box3D(ST_GeomFromEWKT('CIRCULARSTRING(220268 150415 1,220227 150505 1,220227 150406 1)'));
```

```
Box3d
```

```
-----
```

```
BOX3D(220227 150406 1,220268 150415 1)
```

国国

Box2D, ST_GeomFromEWKT

7.18.3 ST_EstimatedExtent

ST_EstimatedExtent — Returns the estimated extent of a spatial table.

Synopsis

```
box2d ST_EstimatedExtent(text schema_name, text table_name, text geocolumn_name, boolean parent_only);
box2d ST_EstimatedExtent(text schema_name, text table_name, text geocolumn_name);
box2d ST_EstimatedExtent(text table_name, text geocolumn_name);
```

国国

Returns the estimated extent of a spatial table as a **box2d**. The current schema is used if not specified. The estimated extent is taken from the geometry column's statistics. This is usually much faster than computing the exact extent of the table using **ST_Extent** or **ST_3DExtent**.

The default behavior is to also use statistics collected from child tables (tables with INHERITS) if available. If `parent_only` is set to TRUE, only statistics for the given table are used and child tables are ignored.

For PostgreSQL >= 8.0.0 statistics are gathered by VACUUM ANALYZE and the result extent will be about 95% of the actual one. For PostgreSQL < 8.0.0 statistics are gathered by running `update_geometry_stats` and the result extent is exact.



Note

In the absence of statistics (empty table or no ANALYZE called) this function returns NULL. Prior to version 1.5.4 an exception was thrown instead.



Note

Escaping names for tables and/or namespaces that include special characters and quotes may require special handling. A user notes: "For schemas and tables, use identifier escaping rules to produce a double-quoted string, and afterwards remove the first and last double-quote character. For geometry column pass as is."

1.0.0 国国国国国国国国国国国国.

Changed: 2.1.0. Up to 2.0.x this was called ST_Estimated_Extent.



This method supports Circular Strings and Curves.

国国

```
SELECT ST_EstimatedExtent('ny', 'edges', 'geom');
--result--
BOX(-8877653 4912316,-8010225.5 5589284)

SELECT ST_EstimatedExtent('feature_poly', 'geom');
--result--
BOX(-124.659652709961 24.6830825805664,-67.7798080444336 49.0012092590332)
```

新新

ST_Extent, ST_3DExtent

7.18.4 ST_Expand

ST_Expand — Returns a bounding box expanded from another bounding box or a geometry.

Synopsis

```
geometry ST_Expand(geometry geom, float units_to_expand);
geometry ST_Expand(geometry geom, float dx, float dy, float dz=0, float dm=0);
box2d ST_Expand(box2d box, float units_to_expand);
box2d ST_Expand(box2d box, float dx, float dy);
box3d ST_Expand(box3d box, float units_to_expand);
box3d ST_Expand(box3d box, float dx, float dy, float dz=0);
```

新新

Returns a bounding box expanded from the bounding box of the input, either by specifying a single distance with which the box should be expanded on both axes, or by specifying an expansion distance for each axis. Uses double-precision. Can be used for distance queries, or to add a bounding box filter to a query to take advantage of a spatial index.

In addition to the version of **ST_Expand** accepting and returning a geometry, variants are provided that accept and return **box2d** and **box3d** data types.

Distances are in the units of the spatial reference system of the input.

ST_Expand is similar to **ST_Buffer**, except while buffering expands a geometry in all directions, **ST_Expand** expands the bounding box along each axis.



Note

Pre version 1.3, **ST_Expand** was used in conjunction with **ST_Distance** to do indexable distance queries. For example, `geom && ST_Expand('POINT(10 20)', 10) AND ST_Distance(geom, 'POINT(10 20)') < 10`. This has been replaced by the simpler and more efficient **ST_DWithin** function.

Availability: 1.5.0 behavior changed to output double precision instead of float4 coordinates.

新新新: 2.0.0 新新新新新新新, 新新新 TIN 新新新新新新新新新.

Enhanced: 2.3.0 support was added to expand a box by different amounts in different dimensions.



This function supports Polyhedral surfaces.



This function supports Triangles and Triangulated Irregular Network Surfaces (TIN).

☒☒



Note

Examples below use US National Atlas Equal Area (SRID=2163) which is a meter projection

```
--10 meter expanded box around bbox of a linestring
SELECT CAST(ST_Expand(ST_GeomFromText('LINESTRING(2312980 110676,2312923 110701,2312892 110714)', 2163),10) As box2d);
                                st_expand
-----
BOX(2312882 110666,2312990 110724)

--10 meter expanded 3D box of a 3D box
SELECT ST_Expand(CAST('BOX3D(778783 2951741 1,794875 2970042.61545891 10)' As box3d),10)
                                st_expand
-----
BOX3D(778773 2951731 -9,794885 2970052.61545891 20)

--10 meter geometry astext rep of a expand box around a point geometry
SELECT ST_AsEWKT(ST_Expand(ST_GeomFromEWKT('SRID=2163;POINT(2312980 110676)'),10));
                                st_asewkt
-----
SRID=2163;POLYGON((2312970 110666,2312970 110686,2312990 110686,2312990 110666,2312970 110666))
```

☒☒

[ST_Buffer](#), [ST_DWithin](#), [ST_SRID](#)

7.18.5 ST_Extent

ST_Extent — Aggregate function that returns the bounding box of geometries.

Synopsis

box2d **ST_Extent**(geometry set geomfield);

☒☒

An aggregate function that returns a **box2d** bounding box that bounds a set of geometries. The bounding box coordinates are in the spatial reference system of the input geometries. **ST_Extent** is similar in concept to Oracle Spatial/Locator's **SDO_AGGR_MBR**.



Note

ST_Extent returns boxes with only X and Y ordinates even with 3D geometries. To return XYZ ordinates use **ST_3DExtent**.



Note
The returned box3d value does not include a SRID. Use `ST_SetSRID` to convert it into a geometry with SRID metadata. The SRID is the same as the input geometries.

注意: 2.0.0 版本开始, 支持 TIN 数据类型。

- ✔ This function supports Polyhedral surfaces.
- ✔ This function supports Triangles and Triangulated Irregular Network Surfaces (TIN).

注意



Note
Examples below use Massachusetts State Plane ft (SRID=2249)

```
SELECT ST_Extent(geom) as bextent FROM sometable;
                                st_bextent
-----
BOX(739651.875 2908247.25,794875.8125 2970042.75)

--Return extent of each category of geometries
SELECT ST_Extent(geom) as bextent
FROM sometable
GROUP BY category ORDER BY category;

                                bextent                                |      name
-----+-----
BOX(778783.5625 2951741.25,794875.8125 2970042.75) | A
BOX(751315.8125 2919164.75,765202.6875 2935417.25) | B
BOX(739651.875 2917394.75,756688.375 2935866)      | C

--Force back into a geometry
-- and render the extended text representation of that geometry
SELECT ST_SetSRID(ST_Extent(geom),2249) as bextent FROM sometable;

                                bextent
-----
SRID=2249;POLYGON((739651.875 2908247.25,739651.875 2970042.75,794875.8125 2970042.75,
794875.8125 2908247.25,739651.875 2908247.25))
```

注意

`ST_EstimatedExtent`, `ST_3DExtent`, `ST_SetSRID`

7.18.6 ST_3DExtent

`ST_3DExtent` — Aggregate function that returns the 3D bounding box of geometries.

Synopsis

box3d **ST_3DExtent**(geometry set geomfield);

⚠

An aggregate function that returns a **box3d** (includes Z ordinate) bounding box that bounds a set of geometries.

The bounding box coordinates are in the spatial reference system of the input geometries.



Note

The returned box3d value does not include a SRID. Use **ST_SetSRID** to convert it into a geometry with SRID metadata. The SRID is the same as the input geometries.

⚠: 2.0.0 弃用, 使用 **TIN** 代替。

Changed: 2.0.0 In prior versions this used to be called ST_Extent3D

- ✔ This function supports 3d and will not drop the z-index.
- ✔ This method supports Circular Strings and Curves.
- ✔ This function supports Polyhedral surfaces.
- ✔ This function supports Triangles and Triangulated Irregular Network Surfaces (TIN).

⚠

```
SELECT ST_3DExtent(foo.geom) As b3extent
FROM (SELECT ST_MakePoint(x,y,z) As geom
      FROM generate_series(1,3) As x
      CROSS JOIN generate_series(1,2) As y
      CROSS JOIN generate_series(0,2) As Z) As foo;
      b3extent
-----
BOX3D(1 1 0,3 2 2)

--Get the extent of various elevated circular strings
SELECT ST_3DExtent(foo.geom) As b3extent
FROM (SELECT ST_Translate(ST_Force_3DZ(ST_LineToCurve(ST_Buffer(ST_Point(x,y),1))),0,0,z)
      As geom
      FROM generate_series(1,3) As x
      CROSS JOIN generate_series(1,2) As y
      CROSS JOIN generate_series(0,2) As Z) As foo;
      b3extent
-----
BOX3D(1 0 0,4 2 2)
```

⚠

ST_Extent, **ST_Force3DZ**, **ST_SetSRID**

7.18.7 ST_MakeBox2D

ST_MakeBox2D — Creates a BOX2D defined by two 2D point geometries.

Synopsis

box2d **ST_MakeBox2D**(geometry pointLowLeft, geometry pointUpRight);

返回

Creates a **box2d** defined by two Point geometries. This is useful for doing range queries.

返回

```
--Return all features that fall reside or partly reside in a US national atlas coordinate ↵
    bounding box
--It is assumed here that the geometries are stored with SRID = 2163 (US National atlas ↵
    equal area)
SELECT feature_id, feature_name, geom
FROM features
WHERE geom && ST_SetSRID(ST_MakeBox2D(ST_Point(-989502.1875, 528439.5625),
    ST_Point(-987121.375 ,529933.1875)),2163)
```

返回

ST_Point, **ST_SetSRID**, **ST_SRID**

7.18.8 ST_3DMakeBox

ST_3DMakeBox — Creates a BOX3D defined by two 3D point geometries.

Synopsis

box3d **ST_3DMakeBox**(geometry point3DLowLeftBottom, geometry point3DUpRightTop);

返回

Creates a **box3d** defined by two 3D Point geometries.



This function supports 3D and will not drop the z-index.

Changed: 2.0.0 In prior versions this used to be called ST_MakeBox3D

返回

```
SELECT ST_3DMakeBox(ST_MakePoint(-989502.1875, 528439.5625, 10),
    ST_MakePoint(-987121.375 ,529933.1875, 10)) As abb3d
--bb3d--
-----
BOX3D(-989502.1875 528439.5625 10,-987121.375 529933.1875 10)
```

☒☒

[ST_MakePoint](#), [ST_SetSRID](#), [ST_SRID](#)

7.18.9 ST_XMax

ST_XMax — Returns the X maxima of a 2D or 3D bounding box or a geometry.

Synopsis

float **ST_XMax**(box3d aGeomorBox2DorBox3D);

☒☒

Returns the X maxima of a 2D or 3D bounding box or a geometry.



Note

Although this function is only defined for box3d, it also works for box2d and geometry values due to automatic casting. However, it will not accept a geometry or box2d text representation, since those do not auto-cast.



This function supports 3d and will not drop the z-index.



This method supports Circular Strings and Curves.

☒☒

```
SELECT ST_XMax('BOX3D(1 2 3, 4 5 6)');
st_xmax
-----
4

SELECT ST_XMax(ST_GeomFromText('LINESTRING(1 3 4, 5 6 7)'));
st_xmax
-----
5

SELECT ST_XMax(CAST('BOX(-3 2, 3 4)' As box2d));
st_xmax
-----
3
--Observe THIS DOES NOT WORK because it will try to auto-cast the string representation to
a BOX3D
SELECT ST_XMax('LINESTRING(1 3, 5 6)');
--ERROR:  BOX3D parser - doesn't start with BOX3D(

SELECT ST_XMax(ST_GeomFromEWKT('CIRCULARSTRING(220268 150415 1,220227 150505 2,220227
150406 3)'));
st_xmax
-----
220288.248780547
```

☒☒

`ST_XMin`, `ST_YMax`, `ST_YMin`, `ST_ZMax`, `ST_ZMin`

7.18.10 ST_XMin

`ST_XMin` — Returns the X minima of a 2D or 3D bounding box or a geometry.

Synopsis

float **ST_XMin**(box3d aGeomorBox2DorBox3D);

☒☒

Returns the X minima of a 2D or 3D bounding box or a geometry.



Note

Although this function is only defined for box3d, it also works for box2d and geometry values due to automatic casting. However it will not accept a geometry or box2d text representation, since those do not auto-cast.



This function supports 3d and will not drop the z-index.



This method supports Circular Strings and Curves.

☒☒

```
SELECT ST_XMin('BOX3D(1 2 3, 4 5 6)');
st_xmin
-----
1

SELECT ST_XMin(ST_GeomFromText('LINESTRING(1 3 4, 5 6 7)'));
st_xmin
-----
1

SELECT ST_XMin(CAST('BOX(-3 2, 3 4)' As box2d));
st_xmin
-----
-3
--Observe THIS DOES NOT WORK because it will try to auto-cast the string representation to
a BOX3D
SELECT ST_XMin('LINESTRING(1 3, 5 6)');
--ERROR:  BOX3D parser - doesn't start with BOX3D(

SELECT ST_XMin(ST_GeomFromEWKT('CIRCULARSTRING(220268 150415 1,220227 150505 2,220227
150406 3)'));
st_xmin
-----
220186.995121892
```

☒☒

`ST_XMax`, `ST_YMax`, `ST_YMin`, `ST_ZMax`, `ST_ZMin`

7.18.11 ST_YMax

`ST_YMax` — Returns the Y maxima of a 2D or 3D bounding box or a geometry.

Synopsis

`float ST_YMax(box3d aGeomorBox2DorBox3D);`

☒☒

Returns the Y maxima of a 2D or 3D bounding box or a geometry.



Note

Although this function is only defined for `box3d`, it also works for `box2d` and geometry values due to automatic casting. However it will not accept a geometry or `box2d` text representation, since those do not auto-cast.



This function supports 3d and will not drop the z-index.



This method supports Circular Strings and Curves.

☒☒

```
SELECT ST_YMax('BOX3D(1 2 3, 4 5 6)');
st_ymax
-----
5

SELECT ST_YMax(ST_GeomFromText('LINESTRING(1 3 4, 5 6 7)'));
st_ymax
-----
6

SELECT ST_YMax(CAST('BOX(-3 2, 3 4)' As box2d));
st_ymax
-----
4
--Observe THIS DOES NOT WORK because it will try to auto-cast the string representation to
a BOX3D
SELECT ST_YMax('LINESTRING(1 3, 5 6)');
--ERROR:  BOX3D parser - doesn't start with BOX3D(

SELECT ST_YMax(ST_GeomFromEWKT('CIRCULARSTRING(220268 150415 1,220227 150505 2,220227
150406 3)'));
st_ymax
-----
150506.126829327
```

☒☒

`ST_XMin`, `ST_XMax`, `ST_YMin`, `ST_ZMax`, `ST_ZMin`

7.18.12 ST_YMin

`ST_YMin` — Returns the Y minima of a 2D or 3D bounding box or a geometry.

Synopsis

float **ST_YMin**(box3d aGeomorBox2DorBox3D);

☒☒

Returns the Y minima of a 2D or 3D bounding box or a geometry.



Note

Although this function is only defined for box3d, it also works for box2d and geometry values due to automatic casting. However it will not accept a geometry or box2d text representation, since those do not auto-cast.



This function supports 3d and will not drop the z-index.



This method supports Circular Strings and Curves.

☒☒

```
SELECT ST_YMin('BOX3D(1 2 3, 4 5 6)');
st_ymin
-----
2

SELECT ST_YMin(ST_GeomFromText('LINESTRING(1 3 4, 5 6 7)'));
st_ymin
-----
3

SELECT ST_YMin(CAST('BOX(-3 2, 3 4)' As box2d));
st_ymin
-----
2
--Observe THIS DOES NOT WORK because it will try to auto-cast the string representation to
a BOX3D
SELECT ST_YMin('LINESTRING(1 3, 5 6)');
--ERROR:  BOX3D parser - doesn't start with BOX3D(

SELECT ST_YMin(ST_GeomFromEWKT('CIRCULARSTRING(220268 150415 1,220227 150505 2,220227
150406 3)'));
st_ymin
-----
150406
```

☒☒

`ST_GeomFromEWKT`, `ST_XMin`, `ST_XMax`, `ST_YMax`, `ST_ZMax`, `ST_ZMin`

7.18.13 ST_ZMax

`ST_ZMax` — Returns the Z maxima of a 2D or 3D bounding box or a geometry.

Synopsis

`float ST_ZMax(box3d aGeomorBox2DorBox3D);`

☒☒

Returns the Z maxima of a 2D or 3D bounding box or a geometry.



Note

Although this function is only defined for box3d, it also works for box2d and geometry values due to automatic casting. However it will not accept a geometry or box2d text representation, since those do not auto-cast.



This function supports 3d and will not drop the z-index.



This method supports Circular Strings and Curves.

☒☒

```
SELECT ST_ZMax('BOX3D(1 2 3, 4 5 6)');
```

```
st_zmax
```

```
-----
```

```
6
```

```
SELECT ST_ZMax(ST_GeomFromEWKT('LINESTRING(1 3 4, 5 6 7)'));
```

```
st_zmax
```

```
-----
```

```
7
```

```
SELECT ST_ZMax('BOX3D(-3 2 1, 3 4 1)');
```

```
st_zmax
```

```
-----
```

```
1
```

--Observe THIS DOES NOT WORK because it will try to auto-cast the string representation to a BOX3D ↩

```
SELECT ST_ZMax('LINESTRING(1 3 4, 5 6 7)');
```

```
--ERROR: BOX3D parser - doesn't start with BOX3D(
```

```
SELECT ST_ZMax(ST_GeomFromEWKT('CIRCULARSTRING(220268 150415 1,220227 150505 2,220227 150406 3)'));
```

```
st_zmax
```

```
-----
```

```
3
```

☒☒

`ST_GeomFromEWKT`, `ST_XMin`, `ST_XMax`, `ST_YMax`, `ST_YMin`, `ST_ZMax`

7.18.14 ST_ZMin

`ST_ZMin` — Returns the Z minima of a 2D or 3D bounding box or a geometry.

Synopsis

float **ST_ZMin**(box3d aGeomorBox2DorBox3D);

☒☒

Returns the Z minima of a 2D or 3D bounding box or a geometry.



Note

Although this function is only defined for box3d, it also works for box2d and geometry values due to automatic casting. However it will not accept a geometry or box2d text representation, since those do not auto-cast.



This function supports 3d and will not drop the z-index.



This method supports Circular Strings and Curves.

☒☒

```
SELECT ST_ZMin('BOX3D(1 2 3, 4 5 6)');
st_zmin
-----
3

SELECT ST_ZMin(ST_GeomFromEWKT('LINESTRING(1 3 4, 5 6 7)'));
st_zmin
-----
4

SELECT ST_ZMin('BOX3D(-3 2 1, 3 4 1) ');
st_zmin
-----
1
--Observe THIS DOES NOT WORK because it will try to auto-cast the string representation to
a BOX3D
SELECT ST_ZMin('LINESTRING(1 3 4, 5 6 7)');
--ERROR:  BOX3D parser - doesn't start with BOX3D(

SELECT ST_ZMin(ST_GeomFromEWKT('CIRCULARSTRING(220268 150415 1,220227 150505 2,220227
150406 3)')));
st_zmin
-----
1
```

返回

`ST_GeomFromEWKT`, `ST_GeomFromText`, `ST_XMin`, `ST_XMax`, `ST_YMax`, `ST_YMin`, `ST_ZMax`

7.19 线性引用 (Linear Referencing)

7.19.1 `ST_LineInterpolatePoint`

`ST_LineInterpolatePoint` — Returns a point interpolated along a line at a fractional location.

Synopsis

geometry **`ST_LineInterpolatePoint`**(geometry a_linestring, float8 a_fraction);
 geography **`ST_LineInterpolatePoint`**(geography a_linestring, float8 a_fraction, boolean use_spheroid = true);

返回

返回一个点，该点位于沿给定线段的指定比例位置。比例必须在 0 到 1 之间。Float8 类型。

该函数与 `ST_LineLocatePoint` 函数一起使用。



Note

This function computes points in 2D and then interpolates values for Z and M, while `ST_3DLineInterpolatePoint` computes points in 3D and only interpolates the M value.



Note

1.1.1 版本中，M 和 Z 值（如果有）将被插值。比例必须在 0.0 到 1.0 之间。

0.8.2 版本中，1.1.1 版本中 Z 和 M 值将被插值。

版本：2.1.0 版本，在 2.0.x 版本中，`ST_Line_Interpolate_Point` 函数。



This function supports 3d and will not drop the z-index.

Figure 7.19.3




Figure 7.19.3: A `LineString` with points interpolated every 20%

```
--Return points each 20% along a 2D line
SELECT ST_AsText(ST_LineInterpolatePoints('LINESTRING(25 50, 100 125, 150 190)', 0.20))
-----
MULTIPOINT((51.5974135047432 76.5974135047432),(78.1948270094864 103.194827009486) ↔
, (104.132163186446 130.37181214238),(127.066081593223 160.18590607119),(150 190))
```

Figure 7.19.4

`ST_LineInterpolatePoint`, `ST_LineLocatePoint`

7.19.4 ST_LineLocatePoint

`ST_LineLocatePoint` — Returns the fractional location of the closest point on a line to a point.

Synopsis

```
float8 ST_LineLocatePoint(geometry a_linestring, geometry a_point);
float8 ST_LineLocatePoint(geography a_linestring, geography a_point, boolean use_spheroid = true);
```

Figure 7.19.4

Figure 7.19.4: The `ST_LineLocatePoint` function returns the fractional location of the closest point on a line to a point. The result is a float8 value between 0 and 1.

The `ST_LineLocatePoint` function is implemented using the `ST_LineInterpolatePoint` and `ST_LineSubstring` functions.

The `ST_LineLocatePoint` function is implemented using the `ST_LineInterpolatePoint` and `ST_LineSubstring` functions.

1.1.0 `ST_LineLocatePoint` function.

Changes: 2.1.0 `ST_LineLocatePoint`, 2.0.x `ST_LineLocatePoint` function.

❏

```
--Rough approximation of finding the street number of a point along the street
--Note the whole foo thing is just to generate dummy data that looks
--like house centroids and street
--We use ST_DWithin to exclude
--houses too far away from the street to be considered on the street
SELECT ST_AsText(house_loc) As as_text_house_loc,
       startstreet_num +
       CAST( (endstreet_num - startstreet_num)
            * ST_LineLocatePoint(street_line, house_loc) As integer) As
       street_num
FROM
  (SELECT ST_GeomFromText('LINESTRING(1 2, 3 4)') As street_line,
        ST_Point(x*1.01,y*1.03) As house_loc, 10 As startstreet_num,
        20 As endstreet_num
  FROM generate_series(1,3) x CROSS JOIN generate_series(2,4) As y)
As foo
WHERE ST_DWithin(street_line, house_loc, 0.2);

as_text_house_loc | street_num
-----+-----
POINT(1.01 2.06) |          10
POINT(2.02 3.09) |          15
POINT(3.03 4.12) |          20

--find closest point on a line to a point or other geometry
SELECT ST_AsText(ST_LineInterpolatePoint(foo.the_line, ST_LineLocatePoint(foo.the_line,
  ST_GeomFromText('POINT(4 3)'))))
FROM (SELECT ST_GeomFromText('LINESTRING(1 2, 4 5, 6 7)') As the_line) As foo;
st_astext
-----
POINT(3 4)
```

❏

ST_DWithin, ST_Length2D, ST_LineInterpolatePoint, ST_LineSubstring

7.19.5 ST_LineSubstring

ST_LineSubstring — Returns the part of a line between two fractional locations.

Synopsis

geometry **ST_LineSubstring**(geometry a_linestring, float8 startfraction, float8 endfraction);
 geography **ST_LineSubstring**(geography a_linestring, float8 startfraction, float8 endfraction);

❏

Computes the line which is the section of the input line starting and ending at the given fractional locations. The first argument must be a LINESTRING. The second and third arguments are values in the range [0, 1] representing the start and end locations as fractions of line length. The Z and M values are interpolated for added endpoints if present.

'❏' ❏' ❏' ❏❏❏❏❏❏❏❏❏❏❏❏❏ **ST_LineInterpolatePoint** ❏❏❏❏❏❏❏❏.

**Note**

This only works with LINESTRINGs. To use on contiguous MULTILINESTRINGs first join them with **ST_LineMerge**.

**Note**

1.1.1 函数支持 M 和 Z 索引 (3D 和 4D 几何). 1.1.0 版本不支持 M 和 Z 索引.

Enhanced: 3.4.0 - Support for geography was introduced.


更新: 2.1.0 版本, 在 2.0.x 版本中引入 **ST_Line_Substring** 函数.

1.1.0 版本. 1.1.1 版本支持 Z 和 M 索引.



This function supports 3d and will not drop the z-index.

图例



图例 1/3 点 (0.333, 0.666) 表示切割点

```
SELECT ST_AsText(ST_LineSubstring( 'LINESTRING (20 180, 50 20, 90 80, 120 40, 180 150)',  
0.333, 0.666));
```

```
LINESTRING (45.17311810399485 45.74337011202746, 50 20, 90 80, 112.97593050157862  
49.36542599789519)
```

If start and end locations are the same, the result is a POINT.

```
SELECT ST_AsText(ST_LineSubstring( 'LINESTRING(25 50, 100 125, 150 190)', 0.333, 0.333));
```

```
POINT(69.2846934853974 94.2846934853974)
```

A query to cut a LineString into sections of length 100 or shorter. It uses **generate_series()** with a **CROSS JOIN LATERAL** to produce the equivalent of a FOR loop.

```
WITH data(id, geom) AS (VALUES
    ( 'A', 'LINESTRING( 0 0, 200 0)::geometry ),
    ( 'B', 'LINESTRING( 0 100, 350 100)::geometry ),
    ( 'C', 'LINESTRING( 0 200, 50 200)::geometry )
)
SELECT id, i,
    ST_AsText( ST_LineSubstring( geom, startfrac, LEAST( endfrac, 1 )) ) AS geom
FROM (
    SELECT id, geom, ST_Length(geom) len, 100 sublen FROM data
) AS d
CROSS JOIN LATERAL (
    SELECT i, (sublen * i) / len AS startfrac,
        (sublen * (i+1)) / len AS endfrac
    FROM generate_series(0, floor( len / sublen )::integer ) AS t(i)
    -- skip last i if line length is exact multiple of sublen
    WHERE (sublen * i) / len <
> 1.0
) AS d2;
```

id	i	geom
A	0	LINESTRING(0 0,100 0)
A	1	LINESTRING(100 0,200 0)
B	0	LINESTRING(0 100,100 100)
B	1	LINESTRING(100 100,200 100)
B	2	LINESTRING(200 100,300 100)
B	3	LINESTRING(300 100,350 100)
C	0	LINESTRING(0 200,50 200)

Geography implementation measures along a spheroid, geometry along a line

```
SELECT ST_AsText(ST_LineSubstring( 'LINESTRING(-118.2436 34.0522, -71.0570 42.3611)::' ↵
    geography, 0.333, 0.666),6) AS geog_sub
, ST_AsText(ST_LineSubstring('LINESTRING(-118.2436 34.0522, -71.0570 42.3611)::' ↵
    geometry, 0.333, 0.666),6) AS geom_sub;
```

geog_sub	geom_sub
LINESTRING(-104.167064 38.854691,-87.674646 41.849854)	LINESTRING(-102.530462 36.819064,-86.817324 39.585927)



ST_Length, **ST_LineExtend**, **ST_LineInterpolatePoint**, **ST_LineMerge**

7.19.6 ST_LocateAlong

ST_LocateAlong — Returns the point(s) on a geometry that match a measure value.

Synopsis

geometry **ST_LocateAlong**(geometry geom_with_measure, float8 measure, float8 offset = 0);

函数

Returns the location(s) along a measured geometry that have the given measure values. The result is a Point or MultiPoint. Polygonal inputs are not supported.

If `offset` is provided, the result is offset to the left or right of the input line by the specified distance. A positive offset will be to the left, and a negative one to the right.



Note

Use this function only for linear geometries with an M component

The semantic is specified by the *ISO/IEC 13249-3 SQL/MM Spatial* standard.

1.1.0 函数 `ST_Locate_Along_Measure` 函数。

2.0.0 函数 `ST_Locate_Along_Measure` 函数。 函数 `ST_Locate_Along_Measure` 函数， 函数 `ST_Locate_Along_Measure` 函数。



This function supports M coordinates.



This method implements the SQL/MM specification. SQL-MM IEC 13249-3: 5.1.13

函数

```
SELECT ST_AsText(
  ST_LocateAlong(
    'MULTILINESTRING((1 2 3, 3 4 2, 9 4 3),(1 2 3, 5 4 5))'::geometry,
    3 ));

-----
MULTIPOINT M ((1 2 3),(9 4 3),(1 2 3))
```

函数

[ST_LocateBetween](#), [ST_LocateBetweenElevations](#), [ST_InterpolatePoint](#)

7.19.7 ST_LocateBetween

`ST_LocateBetween` — Returns the portions of a geometry that match a measure range.

Synopsis

geometry **ST_LocateBetween**(geometry geom, float8 measure_start, float8 measure_end, float8 offset = 0);

函数

该函数返回一个与输入几何体相交的几何体。如果输入几何体是一个多边形，那么返回的几何体也是一个多边形。如果输入几何体是一个点，那么返回的几何体也是一个点。如果输入几何体是一个线串，那么返回的几何体也是一个线串。如果输入几何体是一个多面体壳，那么返回的几何体也是一个多面体壳。如果输入几何体是一个几何集合，那么返回的几何体也是一个几何集合。

Clipping a non-convex POLYGON may produce invalid geometry.

The semantic is specified by the *ISO/IEC 13249-3 SQL/MM Spatial* standard.

1.1.0 函数 `ST_Locate_Between_Measures` 函数。

函数: 2.0.0 函数 `ST_Locate_Along_Measure` 函数。该函数返回一个与输入几何体相交的几何体。如果输入几何体是一个多边形，那么返回的几何体也是一个多边形。如果输入几何体是一个点，那么返回的几何体也是一个点。如果输入几何体是一个线串，那么返回的几何体也是一个线串。如果输入几何体是一个多面体壳，那么返回的几何体也是一个多面体壳。如果输入几何体是一个几何集合，那么返回的几何体也是一个几何集合。


Enhanced: 3.0.0 - added support for POLYGON, TIN, TRIANGLE.

✓ This function supports M coordinates.

✓ This method implements the SQL/MM specification. SQL-MM IEC 13249-3: 5.1

函数

```
SELECT ST_AsText(
  ST_LocateBetween(
    'MULTILINESTRING M ((1 2 3, 3 4 2, 9 4 3),(1 2 3, 5 4 5))':: geometry,
    1.5, 3 ));
-----
GEOMETRYCOLLECTION M (LINESTRING M (1 2 3,3 4 2,9 4 3),POINT M (1 2 3))
```



A LineString with the section between measures 2 and 8, offset to the left

```
SELECT ST_AsText( ST_LocateBetween(
  ST_AddMeasure('LINESTRING (20 180, 50 20, 100 120, 180 20)', 0, 10),
  2, 8,
  20
));
-----
```



```
MULTILINESTRING((54.49835019899045 104.53426957938231,58.70056060327303 ↵
82.12248075654186,69.16695286779743 103.05526528559065,82.11145618000168 ↵
128.94427190999915,84.24893681714357 132.32493442618113,87.01636951231555 ↵
135.21267035596549,90.30307285299679 137.49198684843182,93.97759758337769 ↵
139.07172433557758,97.89298381958797 139.8887023914453,101.89263860095893 ↵
139.9102465862721,105.81659870902816 139.13549527600819,109.50792827749828 ↵
137.5954340631298,112.81899532549731 135.351656550512,115.6173761888606 ↵
132.49390095108848,145.31017306064817 95.37790486135405))
```

☒☒

ST_LocateAlong, ST_LocateAlong, ST_LocateBetween

7.19.8 ST_LocateBetweenElevations

ST_LocateBetweenElevations — Returns the portions of a geometry that lie in an elevation (Z) range.

Synopsis

geometry **ST_LocateBetweenElevations**(geometry geom, float8 elevation_start, float8 elevation_end);

☒☒

Returns a geometry (collection) with the portions of a geometry that lie in an elevation (Z) range.

Clipping a non-convex POLYGON may produce invalid geometry.

1.4.0 ☒☒☒☒☒☒☒☒☒☒☒☒☒☒☒☒.

Enhanced: 3.0.0 - added support for POLYGON, TIN, TRIANGLE.



This function supports 3d and will not drop the z-index.

☒☒

```
SELECT ST_AsText(
  ST_LocateBetweenElevations(
    'LINESTRING(1 2 3, 4 5 6)::geometry,
    2, 4 ));
```

st_astext

MULTILINESTRING Z ((1 2 3,2 3 4))

```
SELECT ST_AsText(
  ST_LocateBetweenElevations(
    'LINESTRING(1 2 6, 4 5 -1, 7 8 9)',
    6, 9)) As ewelev;
```

ewelev

GEOMETRYCOLLECTION Z (POINT Z (1 2 6),LINESTRING Z (6.1 7.1 6,7 8 9))

函数

[ST_Dump](#), [ST_LocateAlong](#), [ST_LocateBetween](#)

7.19.9 ST_InterpolatePoint

`ST_InterpolatePoint` — 返回线性几何体在给定位置 (M 分量) 的插值点。

Synopsis

```
float8 ST_InterpolatePoint(geometry linear_geom_with_measure, geometry point);
```

函数

Returns an interpolated measure value of a linear measured geometry at the location closest to the given point.



Note

Use this function only for linear geometries with an M component

2.0.0 版本引入。



This function supports 3d and will not drop the z-index.

函数

```
SELECT ST_InterpolatePoint('LINESTRING M (0 0 0, 10 0 20)', 'POINT(5 5)');
-----
10
```

函数

[ST_AddMeasure](#), [ST_LocateAlong](#), [ST_LocateBetween](#)

7.19.10 ST_AddMeasure

`ST_AddMeasure` — 在线性几何体上添加测量值。

Synopsis

```
geometry ST_AddMeasure(geometry geom_mline, float8 measure_start, float8 measure_end);
```

注意

此函数在 1.5.0 版本之前不支持 3D 几何。在 1.5.0 版本中，它支持 3D 几何，并且不会丢弃 z 索引。

1.5.0 版本支持 3D 几何。



This function supports 3d and will not drop the z-index.

示例

```
SELECT ST_AsText(ST_AddMeasure(
ST_GeomFromEWKT('LINESTRING(1 0, 2 0, 4 0)'),1,4)) As ewelev;
           ewelev
-----
LINESTRINGM(1 0 1,2 0 2,4 0 4)

SELECT ST_AsText(ST_AddMeasure(
ST_GeomFromEWKT('LINESTRING(1 0 4, 2 0 4, 4 0 4)'),10,40)) As ewelev;
           ewelev
-----
LINESTRING(1 0 4 10,2 0 4 20,4 0 4 40)

SELECT ST_AsText(ST_AddMeasure(
ST_GeomFromEWKT('LINESTRINGM(1 0 4, 2 0 4, 4 0 4)'),10,40)) As ewelev;
           ewelev
-----
LINESTRINGM(1 0 10,2 0 20,4 0 40)

SELECT ST_AsText(ST_AddMeasure(
ST_GeomFromEWKT('MULTILINESTRINGM((1 0 4, 2 0 4, 4 0 4),(1 0 4, 2 0 4, 4 0 4)'),10,70)) As ←
           ewelev;
           ewelev
-----
MULTILINESTRINGM((1 0 10,2 0 20,4 0 40),(1 0 40,2 0 50,4 0 70))
```

7.20 Trajectory Functions

7.20.1 ST_IsValidTrajectory

ST_IsValidTrajectory — Tests if the geometry is a valid trajectory.

Synopsis

boolean **ST_IsValidTrajectory**(geometry line);

注意

Tests if a geometry encodes a valid trajectory. A valid trajectory is represented as a **LINESTRING** with measures (M values). The measure values must increase from each vertex to the next.

Valid trajectories are expected as input to spatio-temporal functions like [ST_ClosestPointOfApproach](#)

2.2.0 简体中文.



This function supports 3d and will not drop the z-index.

例

```
-- A valid trajectory
SELECT ST_IsValidTrajectory(ST_MakeLine(
  ST_MakePointM(0,0,1),
  ST_MakePointM(0,1,2))
);
t

-- An invalid trajectory
SELECT ST_IsValidTrajectory(ST_MakeLine(ST_MakePointM(0,0,1), ST_MakePointM(0,1,0)));
NOTICE:  Measure of vertex 1 (0) not bigger than measure of vertex 0 (1)
st_isvalidtrajectory
-----
f
```

例

ST_ClosestPointOfApproach

7.20.2 ST_ClosestPointOfApproach

ST_ClosestPointOfApproach — Returns a measure at the closest point of approach of two trajectories.

Synopsis

float8 **ST_ClosestPointOfApproach**(geometry track1, geometry track2);

例

Returns the smallest measure at which points interpolated along the given trajectories are the least distance apart.

Inputs must be valid trajectories as checked by **ST_IsValidTrajectory**. Null is returned if the trajectories do not overlap in their M ranges.

To obtain the actual points at the computed measure use **ST_LocateAlong**.

2.2.0 简体中文.



This function supports 3d and will not drop the z-index.

例

```
-- Return the time in which two objects moving between 10:00 and 11:00
-- are closest to each other and their distance at that point
WITH inp AS ( SELECT
  ST_AddMeasure('LINESTRING Z (0 0 0, 10 0 5)')::geometry,
  extract(epoch from '2015-05-26 10:00')::timestampz,
  extract(epoch from '2015-05-26 11:00')::timestampz
) a,
  ST_AddMeasure('LINESTRING Z (0 2 10, 12 1 2)')::geometry,
  extract(epoch from '2015-05-26 10:00')::timestampz,
  extract(epoch from '2015-05-26 11:00')::timestampz
) b
), cpa AS (
  SELECT ST_ClosestPointOfApproach(a,b) m FROM inp
), points AS (
  SELECT ST_GeometryN(ST_LocateAlong(a,m),1) pa,
         ST_GeometryN(ST_LocateAlong(b,m),1) pb
  FROM inp, cpa
)
SELECT to_timestamp(m) t,
       ST_3DDistance(pa,pb) distance,
       ST_AsText(pa, 2) AS pa, ST_AsText(pb, 2) AS pb
FROM points, cpa;
```

t	distance	pa	
	pb		
2015-05-26 10:45:31.034483-07	1.9652147377620688	POINT ZM (7.59 0 3.79 1432662331.03)	
		POINT ZM (9.1 1.24 3.93 1432662331.03)	

☒☒

[ST_IsValidTrajectory](#), [ST_DistanceCPA](#), [ST_LocateAlong](#), [ST_AddMeasure](#)

7.20.3 ST_DistanceCPA

ST_DistanceCPA — Returns the distance between the closest point of approach of two trajectories.

Synopsis

float8 **ST_DistanceCPA**(geometry track1, geometry track2);

☒☒

Returns the distance (in 2D) between two trajectories at their closest point of approach. Inputs must be valid trajectories as checked by [ST_IsValidTrajectory](#). Null is returned if the trajectories do not overlap in their M ranges.

2.2.0 ☒☒☒☒☒☒☒☒☒☒.

✔ This function supports 3d and will not drop the z-index.

例

```
-- Return the minimum distance of two objects moving between 10:00 and 11:00
WITH inp AS ( SELECT
  ST_AddMeasure('LINESTRING Z (0 0 0, 10 0 5)::geometry',
    extract(epoch from '2015-05-26 10:00'::timestampz),
    extract(epoch from '2015-05-26 11:00'::timestampz)
  ) a,
  ST_AddMeasure('LINESTRING Z (0 2 10, 12 1 2)::geometry',
    extract(epoch from '2015-05-26 10:00'::timestampz),
    extract(epoch from '2015-05-26 11:00'::timestampz)
  ) b
)
SELECT ST_DistanceCPA(a,b) distance FROM inp;

      distance
-----
1.965214737762069
```

例

[ST_IsValidTrajectory](#), [ST_ClosestPointOfApproach](#), [ST_AddMeasure](#), [ST_DistanceCPA](#)

7.20.4 ST_CPAWithin

ST_CPAWithin — Tests if the closest point of approach of two trajectories is within the specified distance.

Synopsis

boolean **ST_CPAWithin**(geometry track1, geometry track2, float8 dist);

例

Tests whether two moving objects have ever been closer than the specified distance.

Inputs must be valid trajectories as checked by [ST_IsValidTrajectory](#). False is returned if the trajectories do not overlap in their M ranges.

2.2.0 简体中文。



This function supports 3d and will not drop the z-index.

例

```
WITH inp AS ( SELECT
  ST_AddMeasure('LINESTRING Z (0 0 0, 10 0 5)::geometry',
    extract(epoch from '2015-05-26 10:00'::timestampz),
    extract(epoch from '2015-05-26 11:00'::timestampz)
  ) a,
  ST_AddMeasure('LINESTRING Z (0 2 10, 12 1 2)::geometry',
    extract(epoch from '2015-05-26 10:00'::timestampz),
    extract(epoch from '2015-05-26 11:00'::timestampz)
  ) b
)
```

```
)
SELECT ST_CPAWithin(a,b,2), ST_DistanceCPA(a,b) distance FROM inp;

 st_cpawithin |      distance
-----+-----
 t            | 1.96521473776207
```



`ST_IsValidTrajectory`, `ST_ClosestPointOfApproach`, `ST_DistanceCPA`, `|=|`

7.21 Version Functions

7.21.1 PostGIS_Extensions_Upgrade

`PostGIS_Extensions_Upgrade` — Packages and upgrades PostGIS extensions (e.g. `postgis_raster`, `postgis_topology`, `postgis_sfcgal`) to given or latest version.

Synopsis

text **PostGIS_Extensions_Upgrade**(text target_version=null);



Packages and upgrades PostGIS extensions to given or latest version. Only extensions you have installed in the database will be packaged and upgraded if needed. Reports full PostGIS version and build configuration infos after. This is short-hand for doing multiple `CREATE EXTENSION .. FROM unpackaged` and `ALTER EXTENSION .. UPDATE` for each PostGIS extension. Currently only tries to upgrade extensions `postgis`, `postgis_raster`, `postgis_sfcgal`, `postgis_topology`, and `postgis_tiger_geocoder`. Availability: 2.5.0



Note

Changed: 3.4.0 to add `target_version` argument.
Changed: 3.3.0 support for upgrades from any PostGIS version. Does not work on all systems.
Changed: 3.0.0 to repackage loose extensions and support `postgis_raster`.



```
SELECT PostGIS_Extensions_Upgrade();
```

```
NOTICE: Packaging extension postgis
NOTICE: Packaging extension postgis_raster
NOTICE: Packaging extension postgis_sfcgal
NOTICE: Extension postgis_topology is not available or not packagable for some reason
NOTICE: Extension postgis_tiger_geocoder is not available or not packagable for some reason
      postgis_extensions_upgrade
-----
Upgrade completed, run SELECT postgis_full_version(); for details
(1 row)
```

❏

Section [3.4](#), [PostGIS_GEOS_Version](#), [PostGIS_Lib_Version](#), [PostGIS_LibXML_Version](#), [PostGIS_PROJ_Version](#), [PostGIS_Version](#)

7.21.2 PostGIS_Full_Version

`PostGIS_Full_Version` — Reports full PostGIS version and build configuration infos.

Synopsis

text `PostGIS_Full_Version()`;

❏

Reports full PostGIS version and build configuration infos. Also informs about synchronization between libraries and scripts suggesting upgrades as needed.

Enhanced: 3.4.0 now includes extra PROJ configurations `NETWORK_ENABLED`, `URL_ENDPOINT` and `DATABASE_PATH` of `proj.db` location

❏

```
SELECT PostGIS_Full_Version();
```

postgis_full_version
POSTGIS="3.4.0dev 3.3.0rc2-993-g61bdf43a7" [EXTENSION] PGSQL="160" GEOS="3.12.0dev-CAPI ↔ -1.18.0" SFCGAL="1.3.8" PROJ="7.2.1 NETWORK_ENABLED=OFF URL_ENDPOINT=https://cdn.proj. ↔ org USER_WRITABLE_DIRECTORY=/tmp/proj DATABASE_PATH=/usr/share/proj/proj.db" GDAL="GDAL ↔ 3.2.2, released 2021/03/05" LIBXML="2.9.10" LIBJSON="0.15" LIBPROTOBUF="1.3.3" WAGYU ↔ ="0.5.0 (Internal)" TOPOLOGY RASTER (1 row)

❏

Section [3.4](#), [PostGIS_GEOS_Version](#), [PostGIS_Lib_Version](#), [PostGIS_LibXML_Version](#), [PostGIS_PROJ_Version](#), [PostGIS_Wagyu_Version](#), [PostGIS_Version](#)

7.21.3 PostGIS_GEOS_Version

`PostGIS_GEOS_Version` — Returns the version number of the GEOS library.

Synopsis

text `PostGIS_GEOS_Version()`;

❏

Returns the version number of the GEOS library, or NULL if GEOS support is not enabled.

❏

```
SELECT PostGIS_GEOS_Version();
       postgis_geos_version
-----
3.12.0dev-CAPI-1.18.0
(1 row)
```

❏

[PostGIS_Full_Version](#), [PostGIS_Lib_Version](#), [PostGIS_LibXML_Version](#), [PostGIS_PROJ_Version](#), [PostGIS_Version](#)

7.21.4 PostGIS_GEOS_Compiled_Version

`PostGIS_GEOS_Compiled_Version` — Returns the version number of the GEOS library against which PostGIS was built.

Synopsis

text **`PostGIS_GEOS_Compiled_Version()`**;

❏

Returns the version number of the GEOS library, or against which PostGIS was built.

Availability: 3.4.0

❏

```
SELECT PostGIS_GEOS_Compiled_Version();
       postgis_geos_compiled_version
-----
3.12.0
(1 row)
```

❏

[PostGIS_GEOS_Version](#), [PostGIS_Full_Version](#)

7.21.5 PostGIS_Liblwgeom_Version

`PostGIS_Liblwgeom_Version` — Returns the version number of the liblwgeom library. This should match the version of PostGIS.

Synopsis

text **`PostGIS_Liblwgeom_Version()`**;

☐☐

Returns the version number of the liblwgeom library/

☐☐

```
SELECT PostGIS_Liblwgeom_Version();
postgis_liblwgeom_version
-----
3.4.0dev 3.3.0rc2-993-g61bdf43a7
(1 row)
```

☐☐

[PostGIS_Full_Version](#), [PostGIS_Lib_Version](#), [PostGIS_LibXML_Version](#), [PostGIS_PROJ_Version](#), [PostGIS_Version](#)

7.21.6 PostGIS_LibXML_Version

`PostGIS_LibXML_Version` — Returns the version number of the libxml2 library.

Synopsis

text **`PostGIS_LibXML_Version()`**;

☐☐

Returns the version number of the LibXML2 library.

1.5 国际化.

☐☐

```
SELECT PostGIS_LibXML_Version();
postgis_libxml_version
-----
2.9.10
(1 row)
```

☐☐

[PostGIS_Full_Version](#), [PostGIS_Lib_Version](#), [PostGIS_PROJ_Version](#), [PostGIS_GEOS_Version](#), [PostGIS_Version](#)

7.21.7 PostGIS_LibJSON_Version

`PostGIS_LibJSON_Version` — Returns the version number of the libjson-c library.

Synopsis

text **PostGIS_LibJSON_Version()**;

PostGIS_LibJSON_Version()

Returns the version number of the LibJSON-C library.

PostGIS_LibJSON_Version()

```
SELECT PostGIS_LibJSON_Version();
       postgis_libjson_version
-----
0.17
```

PostGIS_LibJSON_Version()

PostGIS_Full_Version, **PostGIS_Lib_Version**, **PostGIS_PROJ_Version**, **PostGIS_GEOS_Version**, **PostGIS_Versions**

7.21.8 PostGIS_Lib_Build_Date

PostGIS_Lib_Build_Date — Returns build date of the PostGIS library.

Synopsis

text **PostGIS_Lib_Build_Date()**;

PostGIS_Lib_Build_Date()

Returns build date of the PostGIS library.

PostGIS_Lib_Build_Date()

```
SELECT PostGIS_Lib_Build_Date();
       postgis_lib_build_date
-----
2023-06-22 03:56:11
(1 row)
```

7.21.9 PostGIS_Lib_Version

PostGIS_Lib_Version — Returns the version number of the PostGIS library.

Synopsis

text **PostGIS_Lib_Version()**;

☒☒

Returns the version number of the PostGIS library.

☒☒

```
SELECT PostGIS_Lib_Version();
 postgis_lib_version
-----
 3.4.0dev
(1 row)
```

☒☒

[PostGIS_Full_Version](#), [PostGIS_GEOS_Version](#), [PostGIS_LibXML_Version](#), [PostGIS_PROJ_Version](#), [PostGIS_Version](#)

7.21.10 PostGIS_PROJ_Version

`PostGIS_PROJ_Version` — Returns the version number of the PROJ4 library.

Synopsis

text **`PostGIS_PROJ_Version()`**;

☒☒

Returns the version number of the PROJ library and some configuration options of proj.

Enhanced: 3.4.0 now includes `NETWORK_ENABLED`, `URL_ENDPOINT` and `DATABASE_PATH` of `proj.db` location

☒☒

```
SELECT PostGIS_PROJ_Version();
 postgis_proj_version
-----
7.2.1 NETWORK_ENABLED=OFF URL_ENDPOINT=https://cdn.proj.org USER_WRITABLE_DIRECTORY=/tmp/ ↵
proj DATABASE_PATH=/usr/share/proj/proj.db
(1 row)
```

☒☒

[PostGIS_PROJ_Compiled_Version](#), [PostGIS_Full_Version](#), [PostGIS_GEOS_Version](#), [PostGIS_Lib_Version](#), [PostGIS_LibXML_Version](#), [PostGIS_Version](#)

7.21.11 PostGIS_PROJ_Compiled_Version

`PostGIS_PROJ_Compiled_Version` — Returns the version number of the PROJ library against which PostGIS was built.

Synopsis

text **PostGIS_PROJ_Compiled_Version()**;



Returns the version number of the PROJ library, or against which PostGIS was built.

Availability: 3.5.0



```
SELECT PostGIS_PROJ_Compiled_Version();
 postgis_proj_compiled_version
-----
 9.1.1
(1 row)
```



[PostGIS_PROJ_Version](#), [PostGIS_Full_Version](#)

7.21.12 PostGIS_Wagyu_Version

PostGIS_Wagyu_Version — Returns the version number of the internal Wagyu library.

Synopsis

text **PostGIS_Wagyu_Version()**;



Returns the version number of the internal Wagyu library, or NULL if Wagyu support is not enabled.



```
SELECT PostGIS_Wagyu_Version();
 postgis_wagyu_version
-----
 0.5.0 (Internal)
(1 row)
```



[PostGIS_Full_Version](#), [PostGIS_GEOS_Version](#), [PostGIS_PROJ_Version](#), [PostGIS_Lib_Version](#), [PostGIS_LibXML2_Version](#), [PostGIS_Version](#)

7.21.13 PostGIS_Scripts_Build_Date

PostGIS_Scripts_Build_Date — Returns build date of the PostGIS scripts.

Synopsis

text **PostGIS_Scripts_Build_Date()**;



Returns build date of the PostGIS scripts.

1.0.0RC1 .



```
SELECT PostGIS_Scripts_Build_Date();
       postgis_scripts_build_date
-----
2023-06-22 03:56:11
(1 row)
```



[PostGIS_Full_Version](#), [PostGIS_GEOS_Version](#), [PostGIS_Lib_Version](#), [PostGIS_LibXML_Version](#), [PostGIS_Version](#)

7.21.14 PostGIS_Scripts_Installed

PostGIS_Scripts_Installed — Returns version of the PostGIS scripts installed in this database.

Synopsis

text **PostGIS_Scripts_Installed()**;



Returns version of the PostGIS scripts installed in this database.



Note

If the output of this function doesn't match the output of [PostGIS_Scripts_Released](#) you probably missed to properly upgrade an existing database. See the [Upgrading](#) section for more info.

Availability: 0.9.0

❏

```
SELECT PostGIS_Scripts_Installed();
 postgis_scripts_installed
-----
3.4.0dev 3.3.0rc2-993-g61bdf43a7
(1 row)
```

❏

[PostGIS_Full_Version](#), [PostGIS_Scripts_Released](#), [PostGIS_Version](#)

7.21.15 PostGIS_Scripts_Released

`PostGIS_Scripts_Released` — Returns the version number of the `postgis.sql` script released with the installed PostGIS lib.

Synopsis

text **`PostGIS_Scripts_Released()`**;

❏

Returns the version number of the `postgis.sql` script released with the installed PostGIS lib.



Note

Starting with version 1.1.0 this function returns the same value of [PostGIS_Lib_Version](#). Kept for backward compatibility.

Availability: 0.9.0

❏

```
SELECT PostGIS_Scripts_Released();
 postgis_scripts_released
-----
3.4.0dev 3.3.0rc2-993-g61bdf43a7
(1 row)
```

❏

[PostGIS_Full_Version](#), [PostGIS_Scripts_Installed](#), [PostGIS_Lib_Version](#)

7.21.16 PostGIS_Version

`PostGIS_Version` — Returns PostGIS version number and compile-time options.

Synopsis

text **PostGIS_Version()**;

返回

Returns PostGIS version number and compile-time options.

返回

```
SELECT PostGIS_Version();
               postgis_version
-----
3.4 USE_GEOS=1 USE_PROJ=1 USE_STATS=1
(1 row)
```

返回

PostGIS_Full_Version, **PostGIS_GEOS_Version**, **PostGIS_Lib_Version**, **PostGIS_LibXML_Version**, **PostGIS_PROJ_Version**

7.22 PostGIS GUC(Grand Unified Custom Variable)

7.22.1 postgis.gdal_datapath

postgis.gdal_datapath — GDAL 的 GDAL_DATA 目录的路径。如果未设置，则默认为 GDAL_DATA 目录。

返回

GDAL 的 GDAL_DATA 目录的路径 PostgreSQL GUC 变量。 **postgis.gdal_datapath** 是 GDAL 的 GDAL_DATA 目录的路径。

GDAL 的 GDAL_DATA 目录的路径 (hard-coded) 的 GDAL_DATA 目录的路径。 GDAL 的 GDAL_DATA 目录的路径。



Note

PostgreSQL 的 postgresql.conf 文件中的 GDAL_DATA 目录的路径。如果未设置，则默认为 GDAL_DATA 目录。

2.2.0 版本的 GDAL 的 GDAL_DATA 目录的路径。



Note

GDAL 的 GDAL_DATA 目录的路径 GDAL_DATA 目录的路径。

❌❌

postgis.gdal_datapath 配置为默认值。

```
SET postgis.gdal_datapath TO '/usr/local/share/gdal.hidden';
SET postgis.gdal_datapath TO default;
```

配置为 Windows 默认值。

```
ALTER DATABASE gisdb
SET postgis.gdal_datapath = 'C:/Program Files/PostgreSQL/9.3/gdal-data';
```

❌❌

PostGIS_GDAL_Version, ST_Transform

7.22.2 postgis.gdal_enabled_drivers

postgis.gdal_enabled_drivers — PostGIS 启用的 GDAL 驱动程序。GDAL 驱动程序 GDAL_SKIP 禁用。

❌❌

PostGIS 启用的 GDAL 驱动程序。GDAL 驱动程序 GDAL_SKIP 禁用。PostgreSQL 配置文件 postgresql.conf 配置。配置为默认值。

PostgreSQL 配置文件 postgresql.conf 配置 POSTGIS_GDAL_ENABLED_DRIVERS 为 (pass) 为 postgis.gdal_enabled_drivers 配置。

配置为默认值。GDAL 驱动程序 GDAL_SKIP 禁用。配置为默认值。配置为默认值。

Note

postgis.gdal_enabled_drivers 配置为默认值。配置为默认值。



- DISABLE_ALL 禁用 GDAL 驱动程序。DISABLE_ALL 禁用, postgis.gdal_enabled_drivers 配置为默认值。
- ENABLE_ALL 启用 GDAL 驱动程序。
- VSICURL 启用 GDAL 驱动程序 /vsicurl/ 配置。

postgis.gdal_enabled_drivers 为 DISABLE_ALL 禁用, DB 配置, ST_FromGDALRaster(), ST_AsGDALRaster(), ST_AsTIFF(), ST_AsJPEG() 和 ST_AsPNG() 配置。



Note

PostGIS 配置, postgis.gdal_enabled_drivers 为 DISABLE_ALL 禁用。

**Note**

GDAL_SKIP 选项 GDAL 的 [Configuration Options](#) 文档。

2.2.0 版本。

❗

To set and reset `postgis.gdal_enabled_drivers` for current session

```
SET postgis.gdal_enabled_drivers = 'ENABLE_ALL';
SET postgis.gdal_enabled_drivers = default;
```

Set for all new connections to a specific database to specific drivers

```
ALTER DATABASE mygisdb SET postgis.gdal_enabled_drivers TO 'GTiff PNG JPEG';
```

Setting for whole database cluster to enable all drivers. Requires super user access. Also note that database, session, and user settings override this.

```
--writes to postgres.auto.conf
ALTER SYSTEM SET postgis.gdal_enabled_drivers TO 'ENABLE_ALL';
--Reloads postgres conf
SELECT pg_reload_conf();
```

❗

[ST_FromGDALRaster](#), [ST_AsGDALRaster](#), [ST_AsTIFF](#), [ST_AsPNG](#), [ST_AsJPEG](#), [postgis.enable_outdb_raster](#)

7.22.3 postgis.enable_outdb_rasters

`postgis.enable_outdb_rasters` — DB 选项。

❗

DB 选项。PostgreSQL 的 `postgresql.conf` 文件。

PostgreSQL 的 `0` 选项 `POSTGIS_ENABLE_OUTDB_RASTERS` (pass) `postgis.enable_outdb_rasters` 选项。

**Note**

`postgis.enable_outdb_rasters` 选项, GUC `postgis.enable_outdb_rasters` 选项。

**Note**

❗ PostGIS 选项, `postgis.enable_outdb_rasters` 选项。

2.2.0 版本。

❏

`postgis.enable_outdb_rasters` 配置选项。

```
SET postgis.enable_outdb_rasters TO True;
SET postgis.enable_outdb_rasters = default;
SET postgis.enable_outdb_rasters = True;
SET postgis.enable_outdb_rasters = False;
```

Set for all new connections to a specific database

```
ALTER DATABASE gisdb SET postgis.enable_outdb_rasters = true;
```

Setting for whole database cluster. Requires super user access. Also note that database, session, and user settings override this.

```
--writes to postgres.auto.conf
ALTER SYSTEM SET postgis.enable_outdb_rasters = true;
--Reloads postgres conf
SELECT pg_reload_conf();
```

❏

`postgis.gdal_enabled_drivers` `postgis.gdal_vsi_options`

7.22.4 postgis.gdal_vsi_options

`postgis.gdal_vsi_options` — DB 配置选项。

❏

A string configuration to set options used when working with an out-db raster. **Configuration options** control things like how much space GDAL allocates to local data cache, whether to read overviews, and what access keys to use for remote out-db data sources.

Availability: 3.2.0

❏

`postgis.enable_outdb_rasters` 配置选项。

```
SET postgis.gdal_vsi_options = 'AWS_ACCESS_KEY_ID=xxxxxxxxxxxxx AWS_SECRET_ACCESS_KEY=
yyyyyyyyyyyyyyyyyyyyyyyyyyyy';
```

Set `postgis.gdal_vsi_options` just for the *current transaction* using the `LOCAL` keyword:

```
SET LOCAL postgis.gdal_vsi_options = 'AWS_ACCESS_KEY_ID=xxxxxxxxxxxxx
AWS_SECRET_ACCESS_KEY=yyyyyyyyyyyyyyyyyyyyyyyy';
```

❏

`postgis.enable_outdb_rasters` `postgis.gdal_enabled_drivers`

7.23 Troubleshooting Functions

7.23.1 PostGIS_AddBBox

PostGIS_AddBBox — 添加边界框。

Synopsis

geometry **PostGIS_AddBBox**(geometry geomA);

返回

返回类型是 geometry。返回的几何体是 geomA 的副本，其边界框已扩展以包含 geomA 的边界框。



Note

PostGIS_AddBBox 仅适用于二维几何体。对于三维几何体，使用 PostGIS_Add3DBBox。PostGIS_AddBBox 不适用于多面体（polyhedra），因为它会返回一个无效的几何体。PostGIS_AddBBox 不适用于空几何体（null geometry）。



This method supports Circular Strings and Curves.

返回

```
UPDATE sometable
SET geom = PostGIS_AddBBox(geom)
WHERE PostGIS_HasBBox(geom) = false;
```

返回

[PostGIS_DropBBox](#), [PostGIS_HasBBox](#)

7.23.2 PostGIS_DropBBox

PostGIS_DropBBox — 移除边界框。

Synopsis

geometry **PostGIS_DropBBox**(geometry geomA);

XXXXXXXXXXXXXXXXXXXX. XXXXXXXXXXXXXXXXXXXX, XXXXXXXXXXXXXXXXXXXX. XX
XXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXX. XXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXX, X
XXX ST Intersects XXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXX.

Note

[illegible]

✔ This method supports Circular Strings and Curves.


```
--This example drops bounding boxes where the cached box is not correct
--The force to ST_AsBinary before applying Box2D forces a ↵
    recalculation of the box, and Box2D applied to the table ↵
    geometry always
-- returns the cached bounding box.
UPDATE sometable

SET geom = PostGIS_DropBBox(geom)
WHERE Not (Box2D(ST_AsBinary(geom)) = Box2D(geom));

UPDATE sometable
SET geom = PostGIS_AddBBox(geom)
WHERE Not PostGIS_HasBBOX(geom);
```



PostGIS AddBBox, PostGIS HasBBox, Box2D

7.23.3 PostGIS_HasBBox

PostGIS HasBBox — `boolean`, `boolean`.

Synopsis

```
boolean PostGIS_HasBBox(geometry geomA);
```



PostGIS AddBBox | PostGIS DropBBox

✔ This method supports Circular Strings and Curves.

❏

```
SELECT geom
FROM sometable WHERE PostGIS_HasBBox(geom) = false;
```

❏

PostGIS_AddBBox, PostGIS_DropBBox

Chapter 8

SFCGAL Functions Reference

SFCGAL 是一个 2D 和 3D 几何处理库，它封装了 CGAL 库的 C++ 接口 (wrapper)。它提供了许多函数，用于处理几何数据，包括点、线、面、体等。

SFCGAL 的官方网站是 <http://www.sfcgal.org>。您可以在该网站上找到 SFCGAL 的文档和下载链接。SFCGAL 是 PostGIS 3.5.0 版本引入的。

8.1 SFCGAL Management Functions

8.1.1 postgis_sfcgal_version

`postgis_sfcgal_version` — 返回 SFCGAL 的版本号。

Synopsis

```
text postgis_sfcgal_version(void);
```

返回

返回 SFCGAL 的版本号。

2.1.0 版本引入。



This method needs SFCGAL backend.

返回

`postgis_sfcgal_full_version`

8.1.2 postgis_sfcgal_full_version

`postgis_sfcgal_full_version` — Returns the full version of SFCGAL in use including CGAL and Boost versions

Synopsis

text **postgis_sfcgal_version**(void);

返回

Returns the full version of SFCGAL in use including CGAL and Boost versions

Availability: 3.3.0

 This method needs SFCGAL backend.

返回

postgis_sfcgal_version

8.2 SFCGAL Accessors and Setters

8.2.1 CG_ForceLHR

CG_ForceLHR — LHR(Left Hand Reverse; 返回) 返回。

Synopsis

geometry **CG_ForceLHR**(geometry geom);

返回

Availability: 3.5.0

 This method needs SFCGAL backend.

 This function supports 3d and will not drop the z-index.

 This function supports Polyhedral surfaces.

 This function supports Triangles and Triangulated Irregular Network Surfaces (TIN).

8.2.2 CG_IsPlanar

CG_IsPlanar — 返回。

Synopsis

boolean **CG_IsPlanar**(geometry geom);

函数

Availability: 3.5.0

- ✔ This method needs SFCGAL backend.
- ✔ This function supports 3d and will not drop the z-index.
- ✔ This function supports Polyhedral surfaces.
- ✔ This function supports Triangles and Triangulated Irregular Network Surfaces (TIN).

8.2.3 CG_IsSolid

`CG_IsSolid` — 检查几何体是否是实心体。返回布尔值。

Synopsis

boolean **CG_IsSolid**(geometry geom1);

函数

Availability: 3.5.0

- ✔ This method needs SFCGAL backend.
- ✔ This function supports 3d and will not drop the z-index.
- ✔ This function supports Polyhedral surfaces.
- ✔ This function supports Triangles and Triangulated Irregular Network Surfaces (TIN).

8.2.4 CG_MakeSolid

`CG_MakeSolid` — 将几何体转换为实心体。如果几何体已经是实心体，则返回原几何体。否则，将几何体转换为实心体。返回的几何体是 Polyhedral 表面、Triangles 或 Triangulated Irregular Network Surfaces (TIN)。

Synopsis

geometry **CG_MakeSolid**(geometry geom1);

函数

Availability: 3.5.0

- ✔ This method needs SFCGAL backend.
- ✔ This function supports 3d and will not drop the z-index.
- ✔ This function supports Polyhedral surfaces.
- ✔ This function supports Triangles and Triangulated Irregular Network Surfaces (TIN).

8.2.5 CG_Orientation

CG_Orientation — 返回几何体的朝向 (orientation)。

Synopsis

```
integer CG_Orientation(geometry geom);
```

返回

如果几何体是逆时针方向，则返回 1；如果是顺时针方向，则返回 -1。

Availability: 3.5.0



This method needs SFCGAL backend.



This function supports 3d and will not drop the z-index.

8.2.6 CG_Area

CG_Area — 计算几何体的面积

Synopsis

```
double precision CG_Area( geometry geom );
```

返回

计算几何体的面积。

Performed by the SFCGAL module



Note

NOTE: this function returns a double precision value representing the area.

Availability: 3.5.0



This method needs SFCGAL backend.

示例

```
SELECT CG_Area('Polygon ((0 0, 0 5, 5 5, 5 0, 0 0), (1 1, 2 1, 2 2, 1 2, 1 1), (3 3, 4 3, 4 4, 3 4, 3 3))');
      cg_area
      -
      25
(1 row)
```

返回

ST_3DArea, ST_Area

8.2.7 CG_3DArea

CG_3DArea — 3 维多面体表面的面积。返回 0 或正浮点数值。

Synopsis

```
float CG_3DArea(geometry geom1);
```

返回

Availability: 3.5.0

- ✓ This method needs SFCGAL backend.
- ✓ This method implements the SQL/MM specification. SQL-MM IEC 13249-3: 8.1, 10.5
- ✓ This function supports 3d and will not drop the z-index.
- ✓ This function supports Polyhedral surfaces.
- ✓ This function supports Triangles and Triangulated Irregular Network Surfaces (TIN).

返回

注意: 此函数使用 KWT 多面体表面表示法。返回 0 或正浮点数值。返回 0 表示空几何体，返回正浮点数值表示非空几何体。

```
SELECT CG_3DArea(geom) As cube_surface_area,
       CG_3DArea(CG_MakeSolid(geom)) As solid_surface_area
FROM (SELECT 'POLYHEDRALSURFACE( ((0 0 0, 0 0 1, 0 1 1, 0 1 0, 0 0 0)),
  ((0 0 0, 0 1 0, 1 1 0, 1 0 0, 0 0 0)),
  ((0 0 0, 1 0 0, 1 0 1, 0 0 1, 0 0 0)),
  ((1 1 0, 1 1 1, 1 0 1, 1 0 0, 1 1 0)),
  ((0 1 0, 0 1 1, 1 1 1, 1 1 0, 0 1 0)),
  ((0 0 1, 1 0 1, 1 1 1, 0 1 1, 0 0 1)) )::geometry' As f(geom);

cube_surface_area | solid_surface_area
-----+-----
6 | 0
```

返回

CG_Area, CG_MakeSolid, CG_IsSolid, CG_Area

8.2.8 CG_Volume

CG_Volume — 3 维多面体的体积。返回 0 或正浮点数值。

Synopsis

```
float CG_Volume(geometry geom1);
```

国国

Availability: 3.5.0

- ✔ This method needs SFCGAL backend.
- ✔ This function supports 3d and will not drop the z-index.
- ✔ This function supports Polyhedral surfaces.
- ✔ This function supports Triangles and Triangulated Irregular Network Surfaces (TIN).
- ✔ This method implements the SQL/MM specification. SQL-MM IEC 13249-3: 9.1 (same as CG_3DVolume)

国国

When closed surfaces are created with WKT, they are treated as areal rather than solid. To make them solid, you need to use **CG_MakeSolid**. Areal geometries have no volume. Here is an example to demonstrate.

```
SELECT CG_Volume(geom) As cube_surface_vol,
       CG_Volume(CG_MakeSolid(geom)) As solid_surface_vol
FROM (SELECT 'POLYHEDRALSURFACE( ((0 0 0, 0 0 1, 0 1 1, 0 1 0, 0 0 0)),
      ((0 0 0, 0 1 0, 1 1 0, 1 0 0, 0 0 0)),
      ((0 0 0, 1 0 0, 1 0 1, 0 0 1, 0 0 0)),
      ((1 1 0, 1 1 1, 1 0 1, 1 0 0, 1 1 0)),
      ((0 1 0, 0 1 1, 1 1 1, 1 1 0, 0 1 0)),
      ((0 0 1, 1 0 1, 1 1 1, 0 1 1, 0 0 1)) )':geometry) As f(geom);

cube_surface_vol | solid_surface_vol
-----+-----
0 | 1
```

国国

CG_3DArea, **CG_MakeSolid**, **CG_IsSolid**

8.2.9 ST_ForceLHR

ST_ForceLHR — LHR(Left Hand Reverse; 国国国国) 国国国国国国国国.

Synopsis

```
geometry ST_ForceLHR(geometry geom);
```

¶¶



Warning
`ST_ForceLHR` is deprecated as of 3.5.0. Use `CG_ForceLHR` instead.

2.1.0 新增功能。

- ✓ This method needs SFCGAL backend.
- ✓ This function supports 3d and will not drop the z-index.
- ✓ This function supports Polyhedral surfaces.
- ✓ This function supports Triangles and Triangulated Irregular Network Surfaces (TIN).

8.2.10 ST_IsPlanar

`ST_IsPlanar` — 判断几何体是否是平面。

Synopsis

boolean **ST_IsPlanar**(geometry geom);

¶¶



Warning
`ST_IsPlanar` is deprecated as of 3.5.0. Use `CG_IsPlanar` instead.

2.2.0 新增功能。从 2.1.0 版本开始，2.1 版本的功能。

- ✓ This method needs SFCGAL backend.
- ✓ This function supports 3d and will not drop the z-index.
- ✓ This function supports Polyhedral surfaces.
- ✓ This function supports Triangles and Triangulated Irregular Network Surfaces (TIN).

8.2.11 ST_IsSolid

`ST_IsSolid` — 判断几何体是否是实心体。

Synopsis

boolean **ST_IsSolid**(geometry geom1);

¶



Warning
`ST_IsSolid` is deprecated as of 3.5.0. Use `CG_IsSolid` instead.

2.2.0 新增功能。

- ✓ This method needs SFCGAL backend.
- ✓ This function supports 3d and will not drop the z-index.
- ✓ This function supports Polyhedral surfaces.
- ✓ This function supports Triangles and Triangulated Irregular Network Surfaces (TIN).

8.2.12 ST_MakeSolid

`ST_MakeSolid` — 将几何体转换为多面体。如果输入是 TIN，则将其转换为多面体。

Synopsis

geometry **ST_MakeSolid**(geometry geom1);

¶



Warning
`ST_MakeSolid` is deprecated as of 3.5.0. Use `CG_MakeSolid` instead.

2.2.0 新增功能。

- ✓ This method needs SFCGAL backend.
- ✓ This function supports 3d and will not drop the z-index.
- ✓ This function supports Polyhedral surfaces.
- ✓ This function supports Triangles and Triangulated Irregular Network Surfaces (TIN).

8.2.13 ST_Orientation

`ST_Orientation` — 返回几何体的朝向 (orientation)。

Synopsis

integer **ST_Orientation**(geometry geom);



Warning

ST_Orientation is deprecated as of 3.5.0. Use **CG_Orientation** instead.

□□□□□□□□□□□□□□. □□□□□□□□□□□□□□ -1 □, □□□□□□□□ 1 □□□□□□□□.

2.1.0 ☒☒☒☒☒☒☒☒☒☒☒.



This method needs SFCGAL backend.



This function supports 3d and will not drop the z-index.

8.2.14 ST_3DArea

ST_3DArea — 3 字节的浮点值。 0 表示空值。

Synopsis

```
floatST_3DArea(geometry geom1);
```



Warning

ST_3DArea is deprecated as of 3.5.0. Use **CG_3DArea** instead.

2.1.0 ☒☒☒☒☒☒☒☒☒☒☒.



This method needs SFCGAL backend.



This method implements the SQL/MM specification. SQL-MM IEC 13249-3: 8.1, 10.5



This function supports 3d and will not drop the z-index.



This function supports Polyhedral surfaces.



This function supports Triangles and Triangulated Irregular Network Surfaces (TIN).

[illegible]

```
SELECT ST_3DArea(geom) As cube_surface_area,
       ST_3DArea(ST_MakeSolid(geom)) As solid_surface_area
FROM (SELECT 'POLYHEDRALSURFACE( ((0 0 0, 0 0 1, 0 1 1, 0 1 0, 0 0 0)),
  ((0 0 0, 0 1 0, 1 1 0, 1 0 0, 0 0 0)),
  ((0 0 0, 1 0 0, 1 0 1, 0 0 1, 0 0 0)),
  ((1 1 0, 1 1 1, 1 0 1, 1 0 0, 1 1 0)),
  ((0 1 0, 0 1 1, 1 1 1, 1 1 0, 0 1 0)),
  ((0 0 1, 1 0 1, 1 1 1, 0 1 1, 0 0 1)) )'::geometry) As f(geom);

cube_surface_area | solid_surface_area
-----+-----
6 | 0
```

☒☒

[ST_Area](#), [ST_MakeSolid](#), [ST_IsSolid](#), [ST_Area](#)

8.2.15 ST_Volume

ST_Volume — 3 维几何体的体积。返回几何体 (多面体) 的体积。

Synopsis

float **ST_Volume**(geometry geom1);

☒☒



Warning

ST_Volume is deprecated as of 3.5.0. Use **CG_Volume** instead.

2.2.0 版本引入。

- ✓ This method needs SFCGAL backend.
- ✓ This function supports 3d and will not drop the z-index.
- ✓ This function supports Polyhedral surfaces.
- ✓ This function supports Triangles and Triangulated Irregular Network Surfaces (TIN).
- ✓ This method implements the SQL/MM specification. SQL-MM IEC 13249-3: 9.1 (same as ST_3DVolume)

☒☒

WKT 多面体, 多面体。使用 [ST_MakeSolid](#) 创建多面体。返回几何体的体积。


```
SELECT ST_Volume(geom) As cube_surface_vol,
       ST_Volume(ST_MakeSolid(geom)) As solid_surface_vol
FROM (SELECT 'POLYHEDRALSURFACE( ((0 0 0, 0 0 1, 0 1 1, 0 1 0, 0 0 0)),
  ((0 0 0, 0 1 0, 1 1 0, 1 0 0, 0 0 0)),
  ((0 0 0, 1 0 0, 1 0 1, 0 0 1, 0 0 0)),
  ((1 1 0, 1 1 1, 1 0 1, 1 0 0, 1 1 0)),
  ((0 1 0, 0 1 1, 1 1 1, 1 1 0, 0 1 0)),
  ((0 0 1, 1 0 1, 1 1 1, 0 1 1, 0 0 1)) )'::geometry) As f(geom);

cube_surface_vol | solid_surface_vol
-----+-----
0 | 1
```

[ST_3DArea](#), [ST_MakeSolid](#), [ST_IsSolid](#)

8.3 SFCGAL Processing and Relationship Functions

8.3.1 CG_Intersection

CG_Intersection — Computes the intersection of two geometries

Synopsis

geometry **CG_Intersection**(geometry geomA , geometry geomB);

Computes the intersection of two geometries.
Performed by the SFCGAL module



Note

NOTE: this function returns a geometry representing the intersection.

Availability: 3.5.0



This method needs SFCGAL backend.

```
SELECT ST_AsText(CG_Intersection('LINESTRING(0 0, 5 5)', 'LINESTRING(5 0, 0 5)'));
           cg_intersection
           -----
           POINT(2.5 2.5)
           (1 row)
```

☒☒

[ST_3DIntersection](#), [ST_Intersection](#)

8.3.2 CG_Intersects

CG_Intersects — Tests if two geometries intersect (they have at least one point in common)

Synopsis

boolean **CG_Intersects**(geometry geomA , geometry geomB);

☒☒

Returns true if two geometries intersect. Geometries intersect if they have any point in common.

Performed by the SFCGAL module



Note

NOTE: this is the "allowable" version that returns a boolean, not an integer.

Availability: 3.5.0



This method needs SFCGAL backend.



This function supports Triangles and Triangulated Irregular Network Surfaces (TIN).

☒☒☒☒

```
SELECT CG_Intersects('POINT(0 0)::geometry, 'LINESTRING ( 2 0, 0 2 ) '::geometry);
   cg_intersects
-----
f
(1 row)
SELECT CG_Intersects('POINT(0 0)::geometry, 'LINESTRING ( 0 0, 0 2 ) '::geometry);
   cg_intersects
-----
t
(1 row)
```

☒☒

[CG_3DIntersects](#), [ST_3DIntersects](#), [ST_Intersection](#), [ST_Disjoint](#)

8.3.3 CG_3DIntersects

CG_3DIntersects — Tests if two 3D geometries intersect

Synopsis

boolean **CG_3DIntersects**(geometry geomA , geometry geomB);

国国

Tests if two 3D geometries intersect. 3D geometries intersect if they have any point in common in the three-dimensional space.

Performed by the SFCGAL module



Note

NOTE: this is the "allowable" version that returns a boolean, not an integer.

Availability: 3.5.0



This method needs SFCGAL backend.



This function supports Triangles and Triangulated Irregular Network Surfaces (TIN).

国国国国

```
SELECT CG_3DIntersects('POINT(1.2 0.1 0)', 'POLYHEDRALSURFACE(((0 0 0,0.5 0.5 0,1 0 0,1 1 0,0 1 0,0 0 0)),((1 0 0,2 0 0,2 1 0,1 1 0,1 0 0),(1.2 0.2 0,1.2 0.8 0,1.8 0.8 0,1.8 0.2 0,1.2 0.2 0)))');
      cg_3dintersects
-----
t
(1 row)
```

国国

CG_Intersects, **ST_3DIntersects**, **ST_Intersects**, **ST_Disjoint**

8.3.4 CG_Difference

CG_Difference — Computes the geometric difference between two geometries

Synopsis

geometry **CG_Difference**(geometry geomA , geometry geomB);

関数

Computes the geometric difference between two geometries. The resulting geometry is a set of points that are present in geomA but not in geomB.

Performed by the SFCGAL module



Note

NOTE: this function returns a geometry.

Availability: 3.5.0



This method needs SFCGAL backend.



This function supports Triangles and Triangulated Irregular Network Surfaces (TIN).

例

```
SELECT ST_AsText(CG_Difference('POLYGON((0 0, 0 1, 1 1, 1 0, 0 0))'::geometry, 'LINESTRING ↵
(0 0, 2 2)'::geometry));
cg_difference
-----
POLYGON((0 0,1 0,1 1,0 1,0 0))
(1 row)
```

関数

ST_3DDifference, ST_Difference

8.3.5 ST_3DDifference

ST_3DDifference — 3次元幾何体間の差を返す関数。

Synopsis

geometry **ST_3DDifference**(geometry geom1, geometry geom2);

関数



Warning

ST_3DDifference is deprecated as of 3.5.0. Use **CG_3DDifference** instead.

geom2 返回 geom1 的副本。

2.2.0 版本。

- ✔ This method needs SFCGAL backend.
- ✔ This method implements the SQL/MM specification. SQL-MM IEC 13249-3: 5.1
- ✔ This function supports 3d and will not drop the z-index.
- ✔ This function supports Polyhedral surfaces.
- ✔ This function supports Triangles and Triangulated Irregular Network Surfaces (TIN).

8.3.6 CG_3DDifference

CG_3DDifference — 3 维几何体差。

Synopsis

geometry **CG_3DDifference**(geometry geom1, geometry geom2);

返回

geom2 返回 geom1 的副本。


Availability: 3.5.0

- ✔ This method needs SFCGAL backend.
- ✔ This method implements the SQL/MM specification. SQL-MM IEC 13249-3: 5.1
- ✔ This function supports 3d and will not drop the z-index.
- ✔ This function supports Polyhedral surfaces.
- ✔ This function supports Triangles and Triangulated Irregular Network Surfaces (TIN).

返回


PostGIS **ST_AsX3D** 返回 3 维几何体的 X3Dom HTML 格式。HTML 格式。

```
SELECT CG_Extrude(ST_Buffer(
  ST_GeomFromText('POINT(100 90)'),
  CG_Extrude(ST_Buffer(ST_GeomFromText('POINT(80 80)'),
    50, 'quad_segs=1'),0,0,30) AS geom2;
```



3 个 3D 模型。geom2 是 3D 模型。

```
SELECT CG_3DDifference(geom1,geom2)
  quad_segs=2'),0,0,30) AS geom1,
  quad_segs=2'),0,0,30) AS geom1,
  CG_Extrude(
    ST_Buffer(ST_GeomFromText('POINT(80 80)'),
      50, 'quad_segs=1'),0,0,30) AS geom2 ) As t;
```



geom2 是 3D 模型。

图例

CG_Extrude, ST_AsX3D, CG_3DIntersection CG_3DUnion

8.3.7 CG_Distance

CG_Distance — Computes the minimum distance between two geometries

Synopsis

double precision **CG_Distance**(geometry geomA , geometry geomB);

图例

Computes the minimum distance between two geometries.
Performed by the SFCGAL module



Note
NOTE: this function returns a double precision value representing the distance.

Availability: 3.5.0

- ✓ This method needs SFCGAL backend.
- ✓ This function supports Triangles and Triangulated Irregular Network Surfaces (TIN).

例

```
SELECT CG_Distance('LINESTRING(0.0 0.0,-1.0 -1.0)', 'LINESTRING(3.0 4.0,4.0 5.0)');
      cg_distance
      -----
      2.0
(1 row)
```

见

[CG_3DDistance](#), [CG_Distance](#)

8.3.8 CG_3DDistance

CG_3DDistance — Computes the minimum 3D distance between two geometries

Synopsis

double precision **CG_3DDistance**(geometry geomA , geometry geomB);

见

Computes the minimum 3D distance between two geometries.

Performed by the SFCGAL module



Note

NOTE: this function returns a double precision value representing the 3D distance.

Availability: 3.5.0



This method needs SFCGAL backend.



This function supports Triangles and Triangulated Irregular Network Surfaces (TIN).

例

```
SELECT CG_3DDistance('LINESTRING(-1.0 0.0 2.0,1.0 0.0 3.0)', 'TRIANGLE((-4.0 0.0 1.0,4.0 0.0 1.0,0.0 4.0 1.0,-4.0 0.0 1.0))');
      cg_3ddistance
      -----
      1
(1 row)
```

见

[CG_Distance](#), [ST_3DDistance](#)

8.3.9 ST_3DConvexHull

ST_3DConvexHull — 计算 3D 几何体的凸包。

Synopsis

```
geometry ST_3DConvexHull(geometry geom1);
```

几何体



Warning

ST_3DConvexHull is deprecated as of 3.5.0. Use **CG_3DConvexHull** instead.

Availability: 3.3.0

- ✓ This method needs SFCGAL backend.
- ✓ This function supports 3d and will not drop the z-index.
- ✓ This function supports Polyhedral surfaces.
- ✓ This function supports Triangles and Triangulated Irregular Network Surfaces (TIN).

8.3.10 CG_3DConvexHull

CG_3DConvexHull — 计算 3D 几何体的凸包。

Synopsis

```
geometry CG_3DConvexHull(geometry geom1);
```

几何体

Availability: 3.5.0


- ✓ This method needs SFCGAL backend.
 - ✓ This function supports 3d and will not drop the z-index.
 - ✓ This function supports Polyhedral surfaces.
 - ✓ This function supports Triangles and Triangulated Irregular Network Surfaces (TIN).
-

图 8.3.10

```
SELECT ST_AsText(CG_3DConvexHull('LINESTRING Z(0 0 5, 1 5 3, 5 7 6, 9 5 3 , 5 7 5, 6 3 5) ↵
  '::geometry));

POLYHEDRALSURFACE Z (((1 5 3,9 5 3,0 0 5,1 5 3)),((1 5 3,0 0 5,5 7 6,1 5 3)),((5 7 6,5 7 ↵
  5,1 5 3,5 7 6)),((0 0 5,6 3 5,5 7 6,0 0 5)),((6 3 5,9 5 3,5 7 6,6 3 5)),((0 0 5,9 5 3,6 ↵
  3 5,0 0 5)),((9 5 3,5 7 5,5 7 6,9 5 3)),((1 5 3,5 7 5,9 5 3,1 5 3)))

WITH f AS (SELECT i, CG_Extrude(geom, 0,0, i ) AS geom
  FROM ST_Subdivide(ST_Letters('CH'),5) WITH ORDINALITY AS sd(geom,i)
 )
SELECT CG_3DConvexHull(ST_Collect(f.geom) )
FROM f;
```



Original geometry overlaid with 3D convex hull

图 8.3.11

ST_Letters, ST_AsX3D

8.3.11 ST_3DIntersection

ST_3DIntersection — 3 个 3D 几何体的交集。

Synopsis

geometry **ST_3DIntersection**(geometry geom1, geometry geom2);

⚠



Warning

ST_3DIntersection is deprecated as of 3.5.0. Use **CG_3DIntersection** instead.

geom1 ⚠ geom2 返回包含交集的几何体。

2.1.0 返回空集。

- ✔ This method needs SFCGAL backend.
- ✔ This method implements the SQL/MM specification. SQL-MM IEC 13249-3: 5.1
- ✔ This function supports 3d and will not drop the z-index.
- ✔ This function supports Polyhedral surfaces.
- ✔ This function supports Triangles and Triangulated Irregular Network Surfaces (TIN).

8.3.12 CG_3DIntersection

CG_3DIntersection — 3 返回交集的几何体。

Synopsis

geometry **CG_3DIntersection**(geometry geom1, geometry geom2);

⚠

geom1 ⚠ geom2 返回包含交集的几何体。

Availability: 3.5.0

- ✔ This method needs SFCGAL backend.
- ✔ This method implements the SQL/MM specification. SQL-MM IEC 13249-3: 5.1
- ✔ This function supports 3d and will not drop the z-index.
- ✔ This function supports Polyhedral surfaces.
- ✔ This function supports Triangles and Triangulated Irregular Network Surfaces (TIN).

3D 几何体

PostGIS **ST_AsX3D** 函数 3D 几何体转换为 X3Dom HTML 格式或 SVG 格式。HTML 格式可以嵌入到网页中。

```
SELECT CG_Extrude(ST_Buffer(
  ST_GeomFromText('POINT(100 90)'),
  50, 'quads=1'),0,0,30) AS geom2;
```




图 3-1 3D 几何体。geom2 是 geom1 的缓冲区。

```
SELECT CG_3DIntersection(geom1,geom2)
  50, 'quads=2'),0,0,30) AS geom1,
  quad_segs=2'),0,0,30) AS geom1,
  CG_Extrude(ST_Buffer(ST_GeomFromText('POINT(80 80)'),
    50, 'quads=1'),0,0,30) AS geom2 ) As t;
```




图 3-2 geom1 与 geom2 的 3D 交集。

3D 几何体与文本

```
SELECT ST_AsText(CG_3DIntersection(linestring, polygon)) As wkt
FROM ST_GeomFromText('LINESTRING Z (2 2 6,1.5 1.5 7,1 1 8,0.5 0.5 8,0 0 10)') AS linestring
CROSS JOIN ST_GeomFromText('POLYGON((0 0 8, 0 1 8, 1 1 8, 1 0 8, 0 0 8))') AS polygon;

wkt
-----
LINESTRING Z (1 1 8,0.5 0.5 8)
```

3D 几何体与文本 (3D 几何体与文本)

```
SELECT ST_AsText(CG_3DIntersection(
  ST_GeomFromText('POLYHEDRALSURFACE Z( ((0 0 0, 0 0 1, 0 1 1, 0 1 0, 0 0 0)),
  ((0 0 0, 0 1 0, 1 1 0, 1 0 0, 0 0 0)), ((0 0 0, 1 0 0, 1 0 1, 0 0 1, 0 0 0)),
  ((1 1 0, 1 1 1, 1 0 1, 1 0 0, 1 1 0)),
  ((0 1 0, 0 1 1, 1 1 1, 1 1 0, 0 1 0)), ((0 0 1, 1 0 1, 1 1 1, 0 1 1, 0 0 1)) )'),
  'POLYGON Z ((0 0 0, 0 0 0.5, 0 0.5 0.5, 0 0.5 0, 0 0 0))'::geometry))
```

```
TIN Z (((0 0 0,0 0 0.5,0 0.5 0.5,0 0 0)),((0 0.5 0,0 0 0,0 0.5 0.5,0 0.5 0)))
```

3D 几何体与文本 (3D 几何体与文本)

```
SELECT ST_AsText(CG_3DIntersection( CG_Extrude(ST_Buffer('POINT(10 20)'::geometry,10,1),
  0,0,30),
  CG_Extrude(ST_Buffer('POINT(10 20)'::geometry,10,1),2,0,10) ));
```

```
POLYHEDRALSURFACE Z (((13.333333333333 13.333333333333 10,20 20 0,20 20 ↵
10,13.333333333333 13.333333333333 10)),
((20 20 10,16.666666666667 23.333333333333 10,13.333333333333 13.333333333333 ↵
10,20 20 10)),
((20 20 0,16.666666666667 23.333333333333 10,20 20 10,20 20 0)),
((13.333333333333 13.333333333333 10,10 10 0,20 20 0,13.333333333333 ↵
13.333333333333 10)),
((16.666666666667 23.333333333333 10,12 28 10,13.333333333333 13.333333333333 ↵
10,16.666666666667 23.333333333333 10)),
((20 20 0,9.999999999995 30 0,16.666666666667 23.333333333333 10,20 20 0)),
((10 10 0,9.999999999995 30 0,20 20 0,10 10 0)),((13.333333333333 ↵
13.333333333333 10,12 12 10,10 10 0,13.333333333333 13.333333333333 10)),
((12 28 10,12 12 10,13.333333333333 13.333333333333 10,12 28 10)),
((16.666666666667 23.333333333333 10,9.999999999995 30 0,12 28 ↵
10,16.666666666667 23.333333333333 10)),
((10 10 0,0 20 0,9.999999999995 30 0,10 10 0)),
((12 12 10,11 11 10,10 10 0,12 12 10)),((12 28 10,11 11 10,12 12 10,12 28 10)),
((9.999999999995 30 0,11 29 10,12 28 10,9.999999999995 30 0)),((0 20 0,2 20 ↵
10,9.999999999995 30 0,0 20 0)),
((10 10 0,2 20 10,0 20 0,10 10 0)),((11 11 10,2 20 10,10 10 0,11 11 10)),((12 28 ↵
10,11 29 10,11 11 10,12 28 10)),
((9.999999999995 30 0,2 20 10,11 29 10,9.999999999995 30 0)),((11 11 10,11 29 ↵
10,2 20 10,11 11 10)))
```

8.3.13 CG_Union

CG_Union — Computes the union of two geometries

Synopsis

geometry **CG_Union**(geometry geomA , geometry geomB);



Computes the union of two geometries.

Performed by the SFCGAL module



Note

NOTE: this function returns a geometry representing the union.

Availability: 3.5.0



This method needs SFCGAL backend.



```
SELECT CG_Union('POINT(.5 0)', 'LINESTRING(-1 0,1 0)');
      cg_union
-----
LINESTRING(-1 0,0.5 0,1 0)
(1 row)
```

国国

[ST_3DUnion](#), [ST_AsBinary](#)

8.3.14 ST_3DUnion

ST_3DUnion — Perform 3D union.

Synopsis

geometry **ST_3DUnion**(geometry geom1, geometry geom2);
geometry **ST_3DUnion**(geometry set g1field);

国国

**Warning**

[ST_3DUnion](#) is deprecated as of 3.5.0. Use [CG_3DUnion](#) instead.

2.2.0 国国国国国国国国国国.

Availability: 3.3.0 aggregate variant was added



This method needs SFCGAL backend.



This method implements the SQL/MM specification. SQL-MM IEC 13249-3: 5.1



This function supports 3d and will not drop the z-index.



This function supports Polyhedral surfaces.



This function supports Triangles and Triangulated Irregular Network Surfaces (TIN).

Aggregate variant: returns a geometry that is the 3D union of a rowset of geometries. The ST_3DUnion() function is an “aggregate” function in the terminology of PostgreSQL. That means that it operates on rows of data, in the same way the SUM() and AVG() functions do and like most aggregates, it also ignores NULL geometries.

8.3.15 CG_3DUnion

CG_3DUnion — Perform 3D union using postgis_sfcgal.

Synopsis

geometry **CG_3DUnion**(geometry geom1, geometry geom2);
geometry **CG_3DUnion**(geometry set g1field);

函数

Availability: 3.5.0


- ✔ This method needs SFCGAL backend.
- ✔ This method implements the SQL/MM specification. SQL-MM IEC 13249-3: 5.1
- ✔ This function supports 3d and will not drop the z-index.
- ✔ This function supports Polyhedral surfaces.
- ✔ This function supports Triangles and Triangulated Irregular Network Surfaces (TIN).

Aggregate variant: returns a geometry that is the 3D union of a rowset of geometries. The `CG_3DUnion()` function is an “aggregate” function in the terminology of PostgreSQL. That means that it operates on rows of data, in the same way the `SUM()` and `AVG()` functions do and like most aggregates, it also ignores NULL geometries.

函数


PostGIS **ST_AsX3D** 函数 3 维几何体转换为 X3Dom HTML 或 VRML 格式。HTML 或 VRML 格式。

```
SELECT CG_Extrude(ST_Buffer(
    ST_GeomFromText('POINT(100 90)'),
    50, 'quad_segs=1'),0,0,30) AS geom2;
```



3 维几何体转换为 X3Dom HTML 或 VRML 格式。

```
SELECT CG_3DUnion(geom1,geom2)
    50, 'quad_segs=2'),0,0,30) AS geom1,
    50, 'quad_segs=2'),0,0,30) AS geom1,
    CG_Extrude(ST_Buffer(ST_GeomFrom
    50, 'quad_segs=1'),0,0,30) AS geom2 )
```



geom1 与 geom2 的 3D 并集。

函数

CG_Extrude, ST_AsX3D, CG_3DIntersection CG_3DDifference

8.3.16 ST_AlphaShape

`ST_AlphaShape` — Computes an Alpha-shape enclosing a geometry

Synopsis

geometry **ST_AlphaShape**(geometry geom, float alpha, boolean allow_holes = false);

国国



Warning

ST_AlphaShape is deprecated as of 3.5.0. Use **CG_AlphaShape** instead.

Computes the **Alpha-Shape** of the points in a geometry. An alpha-shape is a (usually) concave polygonal geometry which contains all the vertices of the input, and whose vertices are a subset of the input vertices. An alpha-shape provides a closer fit to the shape of the input than the shape produced by the **convex hull**.

8.3.17 CG_AlphaShape

CG_AlphaShape — Computes an Alpha-shape enclosing a geometry

Synopsis

geometry **CG_AlphaShape**(geometry geom, float alpha, boolean allow_holes = false);

国国

Computes the **Alpha-Shape** of the points in a geometry. An alpha-shape is a (usually) concave polygonal geometry which contains all the vertices of the input, and whose vertices are a subset of the input vertices. An alpha-shape provides a closer fit to the shape of the input than the shape produced by the **convex hull**.

The “closeness of fit” is controlled by the alpha parameter, which can have values from 0 to infinity. Smaller alpha values produce more concave results. Alpha values greater than some data-dependent value produce the convex hull of the input.

Note



Following the CGAL implementation, the alpha value is the *square* of the radius of the disc used in the Alpha-Shape algorithm to “erode” the Delaunay Triangulation of the input points. See **CGAL Alpha-Shapes** for more information. This is different from the original definition of alpha-shapes, which defines alpha as the radius of the eroding disc.

The computed shape does not contain holes unless the optional `allow_holes` argument is specified as true.


This function effectively computes a concave hull of a geometry in a similar way to **ST_ConcaveHull**, but uses CGAL and a different algorithm.

Availability: 3.5.0 - requires SFCGAL >= 1.4.1.



This method needs SFCGAL backend.


图 10.10



Alpha-shape of a MultiPoint (same example As [CG_OptimalAlphaShape](#))

```
SELECT ST_AsText(CG_AlphaShape('MULTIPOINT((63 84),(76 88),(68 73),(53 18),(91 50),(81 70),
(88 29),(24 82),(32 51),(37 23),(27 54),(84 19),(75 87),(44 42),(77 67),(90 30) ←
,(36 61),(32 65),
(81 47),(88 58),(68 73),(49 95),(81 60),(87 50),
(78 16),(79 21),(30 22),(78 43),(26 85),(48 34),(35 35),(36 40),(31 79),(83 29) ←
,(27 84),(52 98),(72 95),(85 71),
(75 84),(75 77),(81 29),(77 73),(41 42),(83 72),(23 36),(89 53),(27 57),(57 97) ←
,(27 77),(39 88),(60 81),
(80 72),(54 32),(55 26),(62 22),(70 20),(76 27),(84 35),(87 42),(82 54),(83 64) ←
,(69 86),(60 90),(50 86),(43 80),(36 73),
(36 68),(40 75),(24 67),(23 60),(26 44),(28 33),(40 32),(43 19),(65 16),(73 16) ←
,(38 46),(31 59),(34 86),(45 90),(64 97))'::geometry,80.2));
```


```
POLYGON((89 53,91 50,87 42,90 30,88 29,84 19,78 16,73 16,65 16,53 18,43 19,
37 23,30 22,28 33,23 36,26 44,27 54,23 60,24 67,27 77,
24 82,26 85,34 86,39 88,45 90,49 95,52 98,57 97,
64 97,72 95,76 88,75 84,83 72,85 71,88 58,89 53))
```



Alpha-shape of a MultiPoint, allowing holes (same example as [CG_OptimalAlphaShape](#))


```
SELECT ST_AsText(CG_AlphaShape('MULTIPOINT((63 84),(76 88),(68 73),(53 18),(91 50),(81 70) ←
, (88 29),(24 82),(32 51),(37 23),(27 54),(84 19),(75 87),(44 42),(77 67),(90 30),(36 61) ←
, (32 65),(81 47),(88 58),(68 73),(49 95),(81 60),(87 50),
(78 16),(79 21),(30 22),(78 43),(26 85),(48 34),(35 35),(36 40),(31 79),(83 29),(27 84) ←
, (52 98),(72 95),(85 71),
(75 84),(75 77),(81 29),(77 73),(41 42),(83 72),(23 36),(89 53),(27 57),(57 97),(27 77) ←
, (39 88),(60 81),
(80 72),(54 32),(55 26),(62 22),(70 20),(76 27),(84 35),(87 42),(82 54),(83 64),(69 86) ←
, (60 90),(50 86),(43 80),(36 73),
(36 68),(40 75),(24 67),(23 60),(26 44),(28 33),(40 32),(43 19),(65 16),(73 16),(38 46) ←
, (31 59),(34 86),(45 90),(64 97))'::geometry, 100.1,true))
```

```
POLYGON((89 53,91 50,87 42,90 30,84 19,78 16,73 16,65 16,53 18,43 19,30 22,28 33,23 36,
26 44,27 54,23 60,24 67,27 77,24 82,26 85,34 86,39 88,45 90,49 95,52 98,57 97,64 97,72 95,
76 88,75 84,83 72,85 71,88 58,89 53),(36 61,36 68,40 75,43 80,60 81,68 73,77 67,
81 60,82 54,81 47,78 43,76 27,62 22,54 32,44 42,38 46,36 61))
```



Alpha-shape of a MultiPoint, allowing holes (same example as [ST_ConcaveHull](#))

```
SELECT ST_AsText(CG_AlphaShape(
'MULTIPOINT ((132 64), (114 64), (99 64), (81 64), (63 64), (57 49), (52 ←
36), (46 20), (37 20), (26 20), (32 36), (39 55), (43 69), (50 84), (57 ←
100), (63 118), (68 133), (74 149), (81 164), (88 180), (101 180), (112 ←
180), (119 164), (126 149), (132 131), (139 113), (143 100), (150 84), ←
(157 69), (163 51), (168 36), (174 20), (163 20), (150 20), (143 36), ←
(139 49), (132 64), (99 151), (92 138), (88 124), (81 109), (74 93), (70 ←
82), (83 82), (99 82), (112 82), (126 82), (121 96), (114 109), (110 ←
122), (103 138), (99 151), (34 27), (43 31), (48 44), (46 58), (52 73), ←
(63 73), (61 84), (72 71), (90 69), (101 76), (123 71), (141 62), (166 ←
27), (150 33), (159 36), (146 44), (154 53), (152 62), (146 73), (134 ←
76), (143 82), (141 91), (130 98), (126 104), (132 113), (128 127), (117 ←
122), (112 133), (119 144), (108 147), (119 153), (110 171), (103 164), ←
(92 171), (86 160), (88 142), (79 140), (72 124), (83 131), (79 118), ←
(68 113), (63 102), (68 93), (35 45))'::geometry,102.2, true));
```

```
POLYGON((26 20,32 36,35 45,39 55,43 69,50 84,57 100,63 118,68 133,74 149,81 164,88 180,
101 180,112 180,119 164,126 149,132 131,139 113,143 100,150 84,157 69,163 ←
51,168 36,
174 20,163 20,150 20,143 36,139 49,132 64,114 64,99 64,90 69,81 64,63 64,57 ←
49,52 36,46 20,37 20,26 20),
```

```
(74 93,81 109,88 124,92 138,103 138,110 122,114 109,121 96,112 82,99 82,83 82,74 93))
```

☒☒

[ST_ConcaveHull](#), [CG_OptimalAlphaShape](#)

8.3.18 CG_ApproxConvexPartition

`CG_ApproxConvexPartition` — Computes approximal convex partition of the polygon geometry

Synopsis

geometry **CG_ApproxConvexPartition**(geometry geom);

☒☒

Computes approximal convex partition of the polygon geometry (using a triangulation).

Note



A partition of a polygon P is a set of polygons such that the interiors of the polygons do not intersect and the union of the polygons is equal to the interior of the original polygon P. `CG_ApproxConvexPartition` and `CG_GreeneApproxConvexPartition` functions produce approximately optimal convex partitions. Both these functions produce convex decompositions by first decomposing the polygon into simpler polygons; `CG_ApproxConvexPartition` uses a triangulation and `CG_GreeneApproxConvexPartition` a monotone partition. These two functions both guarantee that they will produce no more than four times the optimal number of convex pieces but they differ in their runtime complexities. Though the triangulation-based approximation algorithm often results in fewer convex pieces, this is not always the case.


Availability: 3.5.0 - requires SFCGAL >= 1.5.0.

Requires SFCGAL >= 1.5.0



This method needs SFCGAL backend.

图 8.3.18



Approximal Convex Partition (same example As [CG_YMonotonePartition](#), [CG_GreeneApproxConvexPartition](#) and [CG_OptimalConvexPartition](#))

```
SELECT ST_AsText(CG_ApproxConvexPartition('POLYGON((156 150,83 181,89 131,148 120,107 61,32 159,0 45,41 86,45 1,177 2,67 24,109 31,170 60,180 110,156 150))'::geometry));

GEOMETRYCOLLECTION(POLYGON((156 150,83 181,89 131,148 120,156 150)),POLYGON((32 159,0 45,41 86,32 159)),POLYGON((107 61,32 159,41 86,107 61)),POLYGON((45 1,177 2,67 24,45 1)),POLYGON((41 86,45 1,67 24,41 86)),POLYGON((107 61,41 86,67 24,109 31,107 61)),POLYGON((148 120,107 61,109 31,170 60,148 120)),POLYGON((156 150,148 120,170 60,180 110,156 150)))
```

图 8.3.19

[CG_YMonotonePartition](#), [CG_GreeneApproxConvexPartition](#), [CG_OptimalConvexPartition](#)

8.3.19 ST_ApproximateMedialAxis

ST_ApproximateMedialAxis — 返回几何体的近似中轴。

Synopsis

geometry **ST_ApproximateMedialAxis**(geometry geom);

图 8.3.20



Warning

ST_ApproximateMedialAxis is deprecated as of 3.5.0. Use [CG_ApproximateMedialAxis](#) instead.

Return an approximate medial axis for the areal input based on its straight skeleton. Uses an SFCGAL specific API when built against a capable version (1.2.0+). Otherwise the function is just a wrapper around `CG_StraightSkeleton` (slower case).

2.2.0 简体中文.

- ✔ This method needs SFCGAL backend.
- ✔ This function supports 3d and will not drop the z-index.
- ✔ This function supports Polyhedral surfaces.
- ✔ This function supports Triangles and Triangulated Irregular Network Surfaces (TIN).

8.3.20 CG_ApproximateMedialAxis

`CG_ApproximateMedialAxis` — 简体中文.

Synopsis

geometry **CG_ApproximateMedialAxis**(geometry geom);

☐☐


Return an approximate medial axis for the areal input based on its straight skeleton. Uses an SFCGAL specific API when built against a capable version (1.2.0+). Otherwise the function is just a wrapper around `CG_StraightSkeleton` (slower case).

Availability: 3.5.0

- ✔ This method needs SFCGAL backend.
- ✔ This function supports 3d and will not drop the z-index.
- ✔ This function supports Polyhedral surfaces.
- ✔ This function supports Triangles and Triangulated Irregular Network Surfaces (TIN).

☐☐

```
SELECT CG_ApproximateMedialAxis(ST_GeomFromText('POLYGON (( 190 190, 10 190, 10 10, 190 10, ↵
190 20, 160 30, 60 30, 60 130, 190 140, 190 190 ))'));
```



☒☒

CG_StraightSkeleton

8.3.21 ST_ConstrainedDelaunayTriangles

ST_ConstrainedDelaunayTriangles — Return a constrained Delaunay triangulation around the given input geometry.

Synopsis

geometry **ST_ConstrainedDelaunayTriangles**(geometry g1);

☒☒



Warning
ST_ConstrainedDelaunayTriangles is deprecated as of 3.5.0. Use **CG_ConstrainedDelaunayTriangles** instead.

Return a **Constrained Delaunay triangulation** around the vertices of the input geometry. Output is a TIN.



This method needs SFCGAL backend.

2.1.0 ☒☒☒☒☒☒☒☒☒☒.



This function supports 3d and will not drop the z-index.

8.3.22 CG_ConstrainedDelaunayTriangles

CG_ConstrainedDelaunayTriangles — Return a constrained Delaunay triangulation around the given input geometry.

Synopsis



geometry **CG_ConstrainedDelaunayTriangles**(geometry g1);

Return a **Constrained Delaunay triangulation** around the vertices of the input geometry. Output is a TIN.

✔ This method needs SFCGAL backend.

2.1.0

✔ This function supports 3d and will not drop the z-index.

	
<i>CG_ConstrainedDelaunayTriangles of 2 polygons</i>	<i>ST_DelaunayTriangles of 2 polygons. Triangle edges cross polygon boundaries.</i>
<pre>select CG_ConstrainedDelaunayTriangles(ST_Union(POLYGON((175 150, 20 40, 50 60, 125 100, 175 150)), ST_Buffer('POINT(110 170)::geometry', 20)));</pre>	<pre>select ST_DelaunayTriangles(ST_Union(POLYGON((175 150, 20 40, 50 60, 125 100, 175 150)), ST_Buffer('POINT(110 170)::geometry', 20)));</pre>

函数

[ST_DelaunayTriangles](#), [ST_TriangulatePolygon](#), [CG_Tessellate](#), [ST_ConcaveHull](#), [ST_Dump](#)

8.3.23 ST_Extrude

ST_Extrude — 将几何体沿 z 轴挤出。

Synopsis

geometry **ST_Extrude**(geometry geom, float x, float y, float z);

函数



Warning

ST_Extrude is deprecated as of 3.5.0. Use **CG_Extrude** instead.

2.1.0 函数参考。

- ✔ This method needs SFCGAL backend.
- ✔ This function supports 3d and will not drop the z-index.
- ✔ This function supports Polyhedral surfaces.
- ✔ This function supports Triangles and Triangulated Irregular Network Surfaces (TIN).

8.3.24 CG_Extrude

CG_Extrude — 将几何体沿 z 轴挤出。

Synopsis

geometry **CG_Extrude**(geometry geom, float x, float y, float z);


函数

Availability: 3.5.0

- ✔ This method needs SFCGAL backend.
- ✔ This function supports 3d and will not drop the z-index.
- ✔ This function supports Polyhedral surfaces.
- ✔ This function supports Triangles and Triangulated Irregular Network Surfaces (TIN).

图

PostGIS **ST_AsX3D** 返回 3 维几何体的 X3Dom HTML 描述。X3Dom HTML 描述是 HTML 描述。

<pre>SELECT ST_Buffer(ST_GeomFromText('POINT (100 90)'), 50, 'quad_segs=2',0,0,30);</pre> 	<pre>CG_Extrude(ST_Buffer(ST_GeomFromText(' POINT(100 90)'), 50, 'quad_segs=2',0,0,30);</pre>  Z 值 30 表示垂直高度。 <i>Z(PolyhedralSurfaceZ)</i> 描述。
图 <pre>SELECT ST_GeomFromText('LINESTRING(50 50, 100 90, 95 150)')</pre> 	<pre>SELECT CG_Extrude(ST_GeomFromText('LINESTRING(50 50, 100 90, 95 150)')</pre>  Z 值 30 表示垂直高度。 <i>Z(PolyhedralSurfaceZ)</i> 描述。

图

图

ST_AsX3D, CG_ExtrudeStraightSkeleton

8.3.25 CG_ExtrudeStraightSkeleton

CG_ExtrudeStraightSkeleton — Straight Skeleton Extrusion

Synopsis

geometry **CG_ExtrudeStraightSkeleton**(geometry geom, float roof_height, float body_height = 0);

国国

Computes an extrusion with a maximal height of the polygon geometry.

Note



Perhaps the first (historically) use-case of straight skeletons: given a polygonal roof, the straight skeleton directly gives the layout of each tent. If each skeleton edge is lifted from the plane a height equal to its offset distance, the resulting roof is "correct" in that water will always fall down to the contour edges (the roof's border), regardless of where it falls on the roof. The function computes this extrusion aka "roof" on a polygon. If the argument `body_height > 0`, so the polygon is extruded like with `CG_Extrude(polygon, 0, 0, body_height)`. The result is an union of these polyhedralsurfaces.

Availability: 3.5.0 - requires SFCGAL >= 1.5.0.

Requires SFCGAL >= 1.5.0



This method needs SFCGAL backend.

国国

```
SELECT ST_AsText(CG_ExtrudeStraightSkeleton('POLYGON (( 0 0, 5 0, 5 5, 4 5, 4 4, 0 4, 0 0 ) ←
, (1 1, 1 2, 2 2, 2 1, 1 1))', 3.0, 2.0));
```

```
POLYHEDRALSURFACE Z (((0 0 0,0 4 0,4 4 0,4 5 0,5 5 0,5 0 0,0 0 0),(1 1 0,2 1 0,2 2 0,1 2 ←
0,1 1 0)),((0 0 0,0 0 2,0 4 2,0 4 0,0 0 0)),((0 4 0,0 4 2,4 4 2,4 4 0,0 4 0)),((4 4 0,4 ←
4 2,4 5 2,4 5 0,4 4 0)),((4 5 0,4 5 2,5 5 2,5 5 0,4 5 0)),((5 5 0,5 5 2,5 0 2,5 0 0,5 5 ←
0)),((5 0 0,5 0 2,0 0 2,0 0 0,5 0 0)),((1 1 0,1 1 2,2 1 2,2 1 0,1 1 0)),((2 1 0,2 1 2,2 ←
2 2,2 2 0,2 1 0)),((2 2 0,2 2 2,1 2 2,1 2 0,2 2 0)),((1 2 0,1 2 2,1 1 2,1 1 0,1 2 0)) ←
,((4 5 2,5 5 2,4 4 2,4 5 2)),((2 1 2,5 0 2,0 0 2,2 1 2)),((5 5 2,5 0 2,4 4 2,5 5 2)),((2 ←
1 2,0 0 2,1 1 2,2 1 2)),((1 2 2,1 1 2,0 0 2,1 2 2)),((0 4 2,2 2 2,1 2 2,0 4 2)),((0 4 ←
2,1 2 2,0 0 2,0 4 2)),((4 4 2,5 0 2,2 2 2,4 4 2)),((4 4 2,2 2 2,0 4 2,4 4 2)),((2 2 2,5 ←
0 2,2 1 2,2 2 2)),((0.5 2.5 2.5,0 0 2,0.5 0.5 2.5,0.5 2.5 2.5)),((1 3 3,0 4 2,0.5 2.5 ←
2.5,1 3 3)),((0.5 2.5 2.5,0 4 2,0 0 2,0.5 2.5 2.5)),((2.5 0.5 2.5,5 0 2,3.5 1.5 3.5,2.5 ←
0.5 2.5)),((0 0 2,5 0 2,2.5 0.5 2.5,0 0 2)),((0.5 0.5 2.5,0 2,2.5 0.5 2.5,0.5 0.5 2.5) ←
),((4.5 3.5 2.5,5 2,4.5 4.5 2.5,4.5 3.5 2.5)),((3.5 2.5 3.5,3.5 1.5 3.5,4.5 3.5 ←
2.5,3.5 2.5 3.5)),((4.5 3.5 2.5,5 0 2,5 2,4.5 3.5 2.5)),((3.5 1.5 3.5,5 0 2,4.5 3.5 ←
2.5,3.5 1.5 3.5)),((5 5 2,4 5 2,4.5 4.5 2.5,5 5 2)),((4.5 4.5 2.5,4 4 2,4.5 3.5 2.5,4.5 ←
4.5 2.5)),((4.5 4.5 2.5,4 5 2,4 4 2,4.5 4.5 2.5)),((3 3 3,0 4 2,1 3 3,3 3 3)),((3.5 2.5 ←
3.5,4.5 3.5 2.5,3 3 3,3.5 2.5 3.5)),((3 3 3,4 4 2,0 4 2,3 3 3)),((4.5 3.5 2.5,4 4 2,3 3 ←
3,4.5 3.5 2.5)),((2 1 2,1 1 2,0.5 0.5 2.5,2 1 2)),((2.5 0.5 2.5,2 1 2,0.5 0.5 2.5,2.5 ←
0.5 2.5)),((1 1 2,1 2 2,0.5 2.5 2.5,1 1 2)),((0.5 0.5 2.5,1 1 2,0.5 2.5 2.5,0.5 0.5 2.5) ←
),((1 3 3,2 2 2,3 3 3,1 3 3)),((0.5 2.5 2.5,1 2 2,1 3 3,0.5 2.5 2.5)),((1 3 3,1 2 2,2 2 ←
2,1 3 3)),((2 2 2,2 1 2,2.5 0.5 2.5,2 2 2)),((3.5 2.5 3.5,3 3 3,3.5 1.5 3.5,3.5 2.5 3.5) ←
),((3.5 1.5 3.5,2 2 2,2.5 0.5 2.5,3.5 1.5 3.5)),((3 3 3,2 2 2,3.5 1.5 3.5,3 3 3)))
```

国国

[ST_Extrude](#), [CG_StraightSkeleton](#)

8.3.26 CG_GreeneApproxConvexPartition

CG_GreeneApproxConvexPartition — Computes approximal convex partition of the polygon geometry

Synopsis

geometry **CG_GreeneApproxConvexPartition**(geometry geom);

国国

Computes approximal monotone convex partition of the polygon geometry.

Note



A partition of a polygon P is a set of polygons such that the interiors of the polygons do not intersect and the union of the polygons is equal to the interior of the original polygon P. CG_ApproxConvexPartition and CG_GreeneApproxConvexPartition functions produce approximately optimal convex partitions. Both these functions produce convex decompositions by first decomposing the polygon into simpler polygons; CG_ApproxConvexPartition uses a triangulation and CG_GreeneApproxConvexPartition a monotone partition. These two functions both guarantee that they will produce no more than four times the optimal number of convex pieces but they differ in their runtime complexities. Though the triangulation-based approximation algorithm often results in fewer convex pieces, this is not always the case.


Availability: 3.5.0 - requires SFCGAL >= 1.5.0.

Requires SFCGAL >= 1.5.0



This method needs SFCGAL backend.

图



Greene Approximal Convex Partition (same example As [CG_YMonotonePartition](#), [CG_ApproxConvexPartition](#) and [CG_OptimalConvexPartition](#))

```
SELECT ST_AsText(CG_GreeneApproxConvexPartition('POLYGON((156 150,83 181,89 131,148 120,107 61,32 159,0 45,41 86,45 1,177 2,67 24,109 31,170 60,180 110,156 150))'::geometry));

GEOMETRYCOLLECTION(POLYGON((32 159,0 45,41 86,32 159)),POLYGON((45 1,177 2,67 24,45 1)),
POLYGON((67 24,109 31,170 60,107 61,67 24)),POLYGON((41 86,45 1,67 24,41 86)),POLYGON
((107 61,32 159,41 86,67 24,107 61)),POLYGON((148 120,107 61,170 60,148 120)),POLYGON
((148 120,170 60,180 110,156 150,148 120)),POLYGON((156 150,83 181,89 131,148 120,156 150)))
```

图

[CG_YMonotonePartition](#), [CG_ApproxConvexPartition](#), [CG_OptimalConvexPartition](#)

8.3.27 ST_MinkowskiSum

ST_MinkowskiSum — 计算两个几何体的闵可夫斯基和。

Synopsis

geometry **ST_MinkowskiSum**(geometry geom1, geometry geom2);

图



Warning

ST_MinkowskiSum is deprecated as of 3.5.0. Use [CG_MinkowskiSum](#) instead.

返回两个几何体的并集，即包含两个几何体的最小几何体。

该函数使用 A 和 B 的 Minkowski 和来计算两个几何体的并集。Minkowski 和是运动规划 (motion planning) 和 CAD (computer-aided design) 中的一个重要概念。有关 Minkowski 和的更多信息，请参阅 [Wikipedia Minkowski addition](#)。

该函数返回两个几何体的并集。如果两个几何体不相交，则返回空集。如果两个几何体相交，则返回它们的并集。如果两个几何体重合，则返回它们的重叠部分。如果两个几何体是点，则返回包含这两个点的线段。如果两个几何体是线，则返回包含这两条线的多边形。如果两个几何体是面，则返回包含这两个面的体。

该函数使用 [CGAL 2D Minkowski sum](#) 来计算两个几何体的并集。

2.1.0 版本引入。



This method needs SFCGAL backend.

8.3.28 CG_MinkowskiSum

CG_MinkowskiSum — 计算两个几何体的 Minkowski 和。

Synopsis

```
geometry CG_MinkowskiSum(geometry geom1, geometry geom2);
```

返回

返回两个几何体的并集，即包含两个几何体的最小几何体。

该函数使用 A 和 B 的 Minkowski 和来计算两个几何体的并集。Minkowski 和是运动规划 (motion planning) 和 CAD (computer-aided design) 中的一个重要概念。有关 Minkowski 和的更多信息，请参阅 [Wikipedia Minkowski addition](#)。

该函数返回两个几何体的并集。如果两个几何体不相交，则返回空集。如果两个几何体相交，则返回它们的并集。如果两个几何体重合，则返回它们的重叠部分。如果两个几何体是点，则返回包含这两个点的线段。如果两个几何体是线，则返回包含这两条线的多边形。如果两个几何体是面，则返回包含这两个面的体。

该函数使用 [CGAL 2D Minkowski sum](#) 来计算两个几何体的并集。


Availability: 3.5.0



This method needs SFCGAL backend.

返回

返回两个几何体的并集，即包含两个几何体的最小几何体。




```

SELECT CG_MinkowskiSum(line, circle))
FROM (SELECT
  ST_MakeLine(ST_Point(10, 10),ST_Point(100, 100)) As line,
  ST_Buffer(ST_GeomFromText('POINT(50 50)'), 30) As circle) As foo;

-- wkt --
MULTIPOLYGON(((30 59.9999999999999,30.5764415879031 ↵
  54.1472903395161,32.2836140246614 48.5194970290472,35.0559116309237 ↵
  43.3328930094119,38.7867965644036 38.7867965644035,43.332893009412 ↵
  35.0559116309236,48.5194970290474 32.2836140246614,54.1472903395162 ↵
  30.5764415879031,60.0000000000001 30,65.8527096604839 ↵
  30.5764415879031,71.4805029709527 32.2836140246614,76.6671069905881 ↵
  35.0559116309237,81.2132034355964 38.7867965644036,171.213203435596 ↵
  128.786796564404,174.944088369076 133.332893009412,177.716385975339 ↵
  138.519497029047,179.423558412097 144.147290339516,180 150,179.423558412097 ↵
  155.852709660484,177.716385975339 161.480502970953,174.944088369076 ↵
  166.667106990588,171.213203435596 171.213203435596,166.667106990588 ↵
  174.944088369076,
  161.480502970953 177.716385975339,155.852709660484 179.423558412097,150 ↵
  180,144.147290339516 179.423558412097,138.519497029047 ↵
  177.716385975339,133.332893009412 174.944088369076,128.786796564403 ↵
  171.213203435596,38.7867965644035 81.2132034355963,35.0559116309236 ↵
  76.667106990588,32.2836140246614 71.4805029709526,30.5764415879031 ↵
  65.8527096604838,30 59.9999999999999)))

```

XXXXXXXXXXXXXXXXXXXXXXXXXXXX



```
SELECT CG_MinkowskiSum(mp, poly)
  FROM (SELECT 'MULTIPOINT(25 50,70 25)::geometry As mp,
 'POLYGON((130 150, 20 40, 50 60, 125 100, 130 150))::geometry As poly
 ) As foo

-- wkt --
MULTIPOLYGON(
  ((70 115,100 135,175 175,225 225,70 115)),
  ((120 65,150 85,225 125,275 175,120 65))
)
```

8.3.29 ST_OptimalAlphaShape

ST_OptimalAlphaShape — Computes an Alpha-shape enclosing a geometry using an "optimal" alpha value.

Synopsis

```
geometry ST_OptimalAlphaShape(geometry geom, boolean allow_holes = false, integer nb_components  
= 1);
```



Warning

Warning
ST_OptimalAlphaShape is deprecated as of 3.5.0. Use CG_OptimalAlphaShape instead.

Computes the "optimal" alpha-shape of the points in a geometry. The alpha-shape is computed using a value of α chosen so that:

1. the number of polygon elements is equal to or smaller than `nb_components` (which defaults to 1)
2. all input points are contained in the shape

The result will not contain holes unless the optional `allow_holes` argument is specified as true.

Availability: 3.3.0 - requires SFCGAL $\geq$ 1.4.1.



This method needs SFCGAL backend.

8.3.30 CG_OptimalAlphaShape

CG_OptimalAlphaShape — Computes an Alpha-shape enclosing a geometry using an "optimal" alpha value.

Synopsis

geometry **CG_OptimalAlphaShape**(geometry geom, boolean allow_holes = false, integer nb_components = 1);



Computes the "optimal" alpha-shape of the points in a geometry. The alpha-shape is computed using a value of α chosen so that:


1. the number of polygon elements is equal to or smaller than `nb_components` (which defaults to 1)
2. all input points are contained in the shape

The result will not contain holes unless the optional `allow_holes` argument is specified as true.

Availability: 3.5.0 - requires SFCGAL $\geq$ 1.4.1.



This method needs SFCGAL backend.




Optimal alpha-shape of a MultiPoint (same example as [CG_AlphaShape](#))

```

SELECT ST_AsText(CG_OptimalAlphaShape('MULTIPOINT((63 84),(76 88),(68 73),(53 18),(91 50) ←
, (81 70),
    (88 29),(24 82),(32 51),(37 23),(27 54),(84 19),(75 87),(44 42),(77 67),(90 ←
    30),(36 61),(32 65),
    (81 47),(88 58),(68 73),(49 95),(81 60),(87 50),
    (78 16),(79 21),(30 22),(78 43),(26 85),(48 34),(35 35),(36 40),(31 79),(83 ←
    29),(27 84),(52 98),(72 95),(85 71),
    (75 84),(75 77),(81 29),(77 73),(41 42),(83 72),(23 36),(89 53),(27 57),(57 ←
    97),(27 77),(39 88),(60 81),
    (80 72),(54 32),(55 26),(62 22),(70 20),(76 27),(84 35),(87 42),(82 54),(83 ←
    64),(69 86),(60 90),(50 86),(43 80),(36 73),
    (36 68),(40 75),(24 67),(23 60),(26 44),(28 33),(40 32),(43 19),(65 16),(73 ←
    16),(38 46),(31 59),(34 86),(45 90),(64 97))'::geometry));

POLYGON((89 53,91 50,87 42,90 30,88 29,84 19,78 16,73 16,65 16,53 18,43 19,37 23,30 22,28 ←
33,23 36,
    26 44,27 54,23 60,24 67,27 77,24 82,26 85,34 86,39 88,45 90,49 95,52 98,57 ←
    97,64 97,72 95,76 88,75 84,75 77,83 72,85 71,83 64,88 58,89 53))

```



Optimal alpha-shape of a MultiPoint, allowing holes (same example as [CG_AlphaShape](#))

```

SELECT ST_AsText(CG_OptimalAlphaShape('MULTIPOINT((63 84),(76 88),(68 73),(53 18),(91 50) ←
, (81 70),(88 29),(24 82),(32 51),(37 23),(27 54),(84 19),(75 87),(44 42),(77 67),(90 30) ←
, (36 61),(32 65),(81 47),(88 58),(68 73),(49 95),(81 60),(87 50),
    (78 16),(79 21),(30 22),(78 43),(26 85),(48 34),(35 35),(36 40),(31 79),(83 29),(27 ←
    84),(52 98),(72 95),(85 71),
    (75 84),(75 77),(81 29),(77 73),(41 42),(83 72),(23 36),(89 53),(27 57),(57 97),(27 ←
    77),(39 88),(60 81),
    (80 72),(54 32),(55 26),(62 22),(70 20),(76 27),(84 35),(87 42),(82 54),(83 64),(69 ←
    86),(60 90),(50 86),(43 80),(36 73),
    (36 68),(40 75),(24 67),(23 60),(26 44),(28 33),(40 32),(43 19),(65 16),(73 16),(38 ←
    46),(31 59),(34 86),(45 90),(64 97))'::geometry, allow_holes => true));

POLYGON((89 53,91 50,87 42,90 30,88 29,84 19,78 16,73 16,65 16,53 18,43 19,37 23,30 22,28 ←
33,23 36,26 44,27 54,23 60,24 67,27 77,24 82,26 85,34 86,39 88,45 90,49 95,52 98,57 ←
97,64 97,72 95,76 88,75 84,75 77,83 72,85 71,83 64,88 58,89 53),(36 61,36 68,40 75,43 ←
80,50 86,60 81,68 73,77 67,81 60,82 54,81 47,78 43,81 29,76 27,70 20,62 22,55 26,54 ←
32,48 34,44 42,38 46,36 61))

```


☒☒

[ST_ConcaveHull](#), [CG_AlphaShape](#)

8.3.31 CG_OptimalConvexPartition

CG_OptimalConvexPartition — Computes an optimal convex partition of the polygon geometry

Synopsis

geometry **CG_OptimalConvexPartition**(geometry geom);

☒☒

Computes an optimal convex partition of the polygon geometry.



Note

A partition of a polygon P is a set of polygons such that the interiors of the polygons do not intersect and the union of the polygons is equal to the interior of the original polygon P. CG_OptimalConvexPartition produces a partition that is optimal in the number of pieces.


Availability: 3.5.0 - requires SFCGAL >= 1.5.0.

Requires SFCGAL >= 1.5.0



This method needs SFCGAL backend.

☒☒



Optimal Convex Partition (same example As [CG_YMonotonePartition](#), [CG_ApproxConvexPartition](#) and [CG_GreeneApproxConvexPartition](#))

```
SELECT ST_AsText(CG_OptimalConvexPartition('POLYGON((156 150,83 181,89 131,148 120,107 61,32 159,0 45,41 86,45 1,177 2,67 24,109 31,170 60,180 110,156 150))'::geometry));
```

```
GEOMETRYCOLLECTION(POLYGON((156 150,83 181,89 131,148 120,156 150)),POLYGON((32 159,0 45,41 ↵
86,32 159)),POLYGON((45 1,177 2,67 24,45 1)),POLYGON((41 86,45 1,67 24,41 86)),POLYGON ↵
((107 61,32 159,41 86,67 24,109 31,107 61)),POLYGON((148 120,107 61,109 31,170 60,180 ↵
110,148 120)),POLYGON((156 150,148 120,180 110,156 150)))
```

☒☒

[CG_YMonotonePartition](#), [CG_ApproxConvexPartition](#), [CG_GreeneApproxConvexPartition](#)

8.3.32 CG_StraightSkeleton

CG_StraightSkeleton — ☒☒☒☒☒☒☒☒☒ (straight skeleton) ☒☒☒☒☒☒.

Synopsis

geometry **CG_StraightSkeleton**(geometry geom, boolean use_distance_as_m = false);

☒☒

Availability: 3.5.0

Requires SFCGAL >= 1.3.8 for option use_distance_as_m


- ✔ This method needs SFCGAL backend.
- ✔ This function supports 3d and will not drop the z-index.
- ✔ This function supports Polyhedral surfaces.
- ✔ This function supports Triangles and Triangulated Irregular Network Surfaces (TIN).

☒☒

```
SELECT CG_StraightSkeleton(ST_GeomFromText('POLYGON (( 190 190, 10 190, 10 10, 190 10, 190 ↵
20, 160 30, 60 30, 60 130, 190 140, 190 190 ))'));
```

```
ST_AsText(CG_StraightSkeleton('POLYGON((0 0,1 0,1 1,0 1,0 0))', true);
```

```
MULTILINESTRING M ((0 0 0,0.5 0.5 0.5),(1 0 0,0.5 0.5 0.5),(1 1 0,0.5 0.5 0.5),(0 1 0,0.5 ↵
0.5 0.5))
```



☒

[CG_ExtrudeStraightSkeleton](#)

8.3.33 ST_StraightSkeleton

ST_StraightSkeleton — 计算 (straight skeleton) 骨架。

Synopsis

geometry **ST_StraightSkeleton**(geometry geom);

☒




Warning
[ST_StraightSkeleton](#) is deprecated as of 3.5.0. Use [CG_StraightSkeleton](#) instead.

2.1.0 添加。

- ✔ This method needs SFCGAL backend.
- ✔ This function supports 3d and will not drop the z-index.
- ✔ This function supports Polyhedral surfaces.
- ✔ This function supports Triangles and Triangulated Irregular Network Surfaces (TIN).

图例

```
SELECT ST_StraightSkeleton(ST_GeomFromText('POLYGON (( 190 190, 10 190, 10 10, 190 10, 190 20, 160 30, 60 30, 60 130, 190 140, 190 190 ))'));
```



图例

CG_ExtrudeStraightSkeleton

8.3.34 ST_Tessellate

ST_Tessellate — 将多边形分解为三角形 (tessellation) 返回 TIN 格式 TIN 格式 多边形。

Synopsis

geometry **ST_Tessellate**(geometry geom);

图例



Warning
ST_Tessellate is deprecated as of 3.5.0. Use **CG_Tessellate** instead.

[图例] 将多边形分解为三角形 (tessellation) 返回 TIN 格式 TIN 格式 多边形。



Note
ST_TriangulatePolygon does similar to this function except that it returns a geometry collection of polygons instead of a TIN and also only works with 2D geometries.

2.1.0 新增。

- ✔ This method needs SFCGAL backend.
- ✔ This function supports 3d and will not drop the z-index.
- ✔ This function supports Polyhedral surfaces.
- ✔ This function supports Triangles and Triangulated Irregular Network Surfaces (TIN).

8.3.35 CG_Tessellate

`CG_Tessellate` — 对几何体进行三角剖分 (tessellation) 生成 TIN 或 TIN 集合。

Synopsis

geometry **CG_Tessellate**(geometry geom);

返回

[geometry] 对几何体进行三角剖分 (tessellation) 生成 TIN 或 TIN 集合。



Note

ST_TriangulatePolygon does similar to this function except that it returns a geometry collection of polygons instead of a TIN and also only works with 2D geometries.

Availability: 3.5.0

- ✔ This method needs SFCGAL backend.
- ✔ This function supports 3d and will not drop the z-index.
- ✔ This function supports Polyhedral surfaces.
- ✔ This function supports Triangles and Triangulated Irregular Network Surfaces (TIN).

返回

```
SELECT ST_GeomFromText('POLYHEDRALSURFACE ↵
  Z( ((0 0 0, 0 0 1, 0 1 1, 0 1 0, 0 0 0)), ↵
      ((0 0 ↵
0, 0 1 0, 1 1 0, 1 0 0, 0 0 0)), ((0 0 0, 1 0 0, 1 ↵
      ((1 1 ↵
0, 1 1 1, 1 0 1, 1 0 0, 1 1 0)), ↵
      ((0 1 ↵
0, 0 1 1, 1 1 1, 1 1 0, 0 1 0)), ((0 0 1, 1 0 1, 1
```




图 10-10

```
SELECT CG_Tessellate(ST_GeomFromText(' ↵
  POLYHEDRALSURFACE Z( ((0 0 0, 0 0 1, 0 1 1, 0 1 ↵
      ((0 0 0, ↵
0 1 0, 1 1 0, 1 0 0, 0 0 0)), ((0 0 0, 1 0 0, 1 ↵
      ((1 1 0, ↵
1 1 1, 1 0 1, 1 0 0, 1 1 0)), ↵
      ((0 1 0, ↵
0 1 1, 1 1 1, 1 1 0, 0 1 0)), ((0 0 1, 1 0 1, 1
```

ST_AsText 图 10-11:

```
TIN Z( ((0 0 0,0 0 1,0 1 1,0 0 0)),((0 1 ↵
1 0 0,0 1 0,0 1 1,0 1 0)), ↵
      ((0 0 0,0 1 0,1 1 ↵
0,0 0 0)), ↵
      ((1 0 0,0 0 0,1 1 ↵
1 0 1,1 1 1),0 1 1,0 1 0,1 0 1 0 1)), ↵
      ((0 0 1,0 0 0,1 0 ↵
0,0 0 1)), ↵
      ((1 1 0,1 1 1,1 0 ↵
1,1 1 0)),((1 0 0,1 1 0,1 0 1,1 0 0)), ↵
      ((0 1 0,0 1 1,1 1 ↵
1,0 1 0)),((1 1 0,0 1 0,1 1 1,1 1 0)), ↵
      ((0 1 1,1 0 1,1 1 ↵
1,0 1 1)),((0 1 1,0 0 1,1 0 1,0 1 1)))
```



图 10-11

SELECT 'POLYGON ((10 190, 10 70, 80 70, 80 130, 50 160, 120 160, 120 190, 10 190))';

⊠⊠⊠⊠⊠

```

SELECT
    CG_Tessellate('
        POLYGON (( 10 190, 10 70, 80 70, 80 130, 50 160,
                    ;

    ST_AsText ⊠⊠⊠:
    geometry:
    TIN(((80 130,50 160,80 70,80 130)),((50 160,10 190,10 70,50 160)),
        ((80 70,50 160,10 70,80 70)),((120 160,120 190,50 160,120 160)),
        ((120 190,10 190,50 160,120 190)))
    
```

⊠⊠⊠⊠⊠⊠⊠⊠⊠⊠



CG ConstrainedDelaunayTriangles, ST DelaunayTriangles, ST TriangulatePolygon

8.3.36 CG_Triangulate

CG Triangulate — Triangulates a polygonal geometry

Synopsis

```
geometry CG_Triangulate( geometry geom );
```



Triangulates a polygonal geometry.

Performed by the SFCGAL module



Note!

Note

NOTE: this function returns a geometry representing the triangulated result.

Availability: 3.5.0



This method needs SFCGAL backend.

实验实验

```
SELECT CG_Triangulate('POLYGON((0.0 0.0,1.0 0.0,1.0 1.0,0.0 1.0,0.0 0.0),(0.2 0.2,0.2 0.8,0.8 0.8,0.8 0.2,0.2 0.2))');
      cg_triangulate
      -----
      TIN(((0.8 0.2,0.2 0.2,1 0,0.8 0.2)),((0.2 0.2,0 0,1 0,0.2 0.2)),((1 1,0.8 0.8,0.8 0.2,1 1)),((0 1,0 0,0.2 0.2,0 1)),((0 1,0.2 0.8,1 1,0 1)),((0 1,0.2 0.2,0.2 0.8,0 1)),((0.2 0.8,0.8 0.8,1 1,0.2 0.8)),((0.2 0.8,0.2 0.2,0.8 0.8)),((1 1,0.8 0.2,1 0,1 1)),((0.8 0.8,0.2 0.8,0.8 0.2,0.8 0.8)))
(1 row)
```

实验

CG_ConstrainedDelaunayTriangles, **ST_DelaunayTriangles**, **ST_TriangulatePolygon**

8.3.37 CG_Visibility

CG_Visibility — Compute a visibility polygon from a point or a segment in a polygon geometry

Synopsis

```
geometry CG_Visibility(geometry polygon, geometry point);
geometry CG_Visibility(geometry polygon, geometry pointA, geometry pointB);
```

实验

Availability: 3.5.0 - requires SFCGAL >= 1.5.0.

Requires SFCGAL >= 1.5.0



This method needs SFCGAL backend.



This function supports 3d and will not drop the z-index.



This function supports Polyhedral surfaces.




This function supports Triangles and Triangulated Irregular Network Surfaces (TIN).

实验

```
SELECT CG_Visibility('POLYGON((23.5 23.5,23.5 173.5,173.5 173.5,173.5 23.5,23.5 23.5),(108 98,108 36,156 37,155 99,108 98),(107 157.5,107 106.5,135 107.5,133 127.5,143.5 127.5,143.5 108.5,153.5 109.5,151.5 166,107 157.5),(41 95.5,41 35,100.5 36,98.5 68,78.5 68,77.5 96.5,41 95.5),(39 150,40 104,97.5 106.5,95.5 152,39 150))::geometry, 'POINT(91 87)::geometry');
```



```
SELECT CG_Visibility('POLYGON((23.5 23.5,23.5 173.5,173.5 173.5,173.5 23.5,23.5 23.5),(108 98,108 36,156 37,155 99,108 98),(107 157.5,107 106.5,135 107.5,133 127.5,143.5 127.5,143.5 108.5,153.5 109.5,151.5 166,107 157.5),(41 95.5,41 35,100.5 36,98.5 68,78.5 68,77.5 96.5,41 95.5),(39 150,40 104,97.5 106.5,95.5 152,39 150))'::geometry,'POINT(78.5 68)'::geometry, 'POINT(98.5 68)'::geometry);
```



8.3.38 CG_YMonotonePartition

CG_YMonotonePartition — Computes y-monotone partition of the polygon geometry

Synopsis

```
geometry CG_YMonotonePartition(geometry geom);
```



Computes y-monotone partition of the polygon geometry.


**Note**

A partition of a polygon P is a set of polygons such that the interiors of the polygons do not intersect and the union of the polygons is equal to the interior of the original polygon P. A y-monotone polygon is a polygon whose vertices $v_1, \dots, v_n$ can be divided into two chains $v_1, \dots, v_k$ and $v_k, \dots, v_n, v_1$, such that any horizontal line intersects either chain at most once. This algorithm does not guarantee a bound on the number of polygons produced with respect to the optimal number.

Availability: 3.5.0 - requires SFCGAL >= 1.5.0.
Requires SFCGAL >= 1.5.0

 This method needs SFCGAL backend.

图



```
SELECT ST_AsText(CG_YMonotonePartition('POLYGON((156 150,83 181,89 131,148 120,107 61,32 159,0 45,41 86,45 1,177 2,67 24,109 31,170 60,180 110,156 150))'::geometry));

GEOMETRYCOLLECTION(POLYGON((32 159,0 45,41 86,32 159)),POLYGON((107 61,32 159,41 86,45 1,177 2,67 24,109 31,170 60,107 61)),POLYGON((156 150,83 181,89 131,148 120,107 61,170 60,180 110,156 150)))
```

图

CG_ApproxConvexPartition, CG_GreeneApproxConvexPartition, CG_OptimalConvexPartition

Chapter 9

 (topology)

[illegible]

Sandro Santilli's presentation at PostGIS Day Paris 2011 conference gives a good synopsis of PostGIS Topology and where it is headed [Topology with PostGIS 2.0 slide deck](#).

Vincent Picavet provides a good synopsis and overview of what is Topology, how is it used, and various FOSS4G tools that support it in [PostGIS Topology PGConf EU 2012](#).

GIS US Census Topologically Integrated Geographic Encoding and Referencing System (TIGER) PostGIS Topology Load Tiger.

PostGIS 2.0.0 支持 PostGIS 2.0.0 版本, 支持 PostGIS 2.0.0 版本. PostGIS 2.0.0 支持, 支持 PostGIS 2.0.0 版本, 支持 PostGIS 2.0.0 版本. SQL-MM 支持 PostGIS 2.0.0 版本.

PostGIS Topology Wiki.

□□□□□□□□□□□□□□ topology □□□□□□□□□□□□□□.

SQL/MM ☐☒ ST_ ☐☒, PostGIS ☐☒

Topology support is build by default starting with PostGIS 2.0, and can be disabled specifying `--without-topology` configure option at build time as described in [Chapter 2](#)

9.1 ☐ ☐ ☐ ☐

9.1.1 getfaceedges_returntype

`getfaceedges` `returntype` — A composite type that consists of a sequence number and an edge number.

A composite type that consists of a sequence number and an edge number. This is the return type for `ST_GetFaceEdges` and `GetNodeEdges` functions.

1. **sequence** `sequence`: `SRID topology.topology`
2. **edge** `edge`:

9.1.2 TopoGeometry

TopoGeometry — A composite type representing a topologically defined geometry.

简介

TopoGeometry 是 PostGIS 3.5 引入的一个新数据类型，用于表示拓扑定义的几何。TopoGeometry 由 topology_id, layer_id, id, type 四个属性组成。

1. **topology_id** integer: 表示 SRID 所属的 topology.topology 名称。
2. **layer_id** integer: TopoGeometry 所属的 layer_id。topology_id 和 layer_id 在 topology.layers 表中 (unique reference) 唯一。
3. **id** integer: 表示几何体的 ID，在 topology.layers 表中唯一。
4. **type** integer: 表示几何体的类型。1: [点] 点, 2: [线] 线, 3: [面] 面, 4: [体] 体。

结构

TopoGeometry 的存储结构如下所示。

topology_id	integer
layer_id	integer

函数

CreateTopoGeom

9.1.3 validate_topology_returntype

validate_topology_returntype — A composite type that consists of an error message and id1 and id2 to denote location of error. This is the return type for ValidateTopology.

简介

validate_topology_returntype 是 PostGIS 3.5 引入的一个新数据类型，用于表示拓扑验证的错误信息。ValidateTopology 函数返回 validate_topology_returntype 类型的结果，包含 ID id1 和 id2。

1. **error** varchar: 错误描述。
 可能的值 (descriptor) 包括: coincident nodes(重合节点), edge crosses node(边穿过节点), edge not simple(边不简单), edge end node geometry mismatch(边端节点几何不匹配), edge start node geometry mismatch(边起始节点几何不匹配), face overlaps face(面重叠面), face within face(面在面内)。
2. **id1** integer: 表示错误的几何体 ID (edge)/面 (face)/点 (node)。
3. **id2** integer: 表示错误的几何体 ID (edge)/面 (face)/点 (node)。

函数

[ValidateTopology](#)

9.2 拓扑

9.2.1 TopoElement

TopoElement — 拓扑几何的 2 个元素之一。

函数

拓扑几何 [TopoGeometry](#) 由 1 个或多个 2 个元素组成。

每个 TopoGeometry 由一个或多个 (topological primitive) 元素组成 (1: node, 2: edge, 3: face) 组成。每个 TopoGeometry 由一个或多个 TopoGeometry 元素组成。



Note

每个 TopoGeometry 由一个或多个 TopoGeometry 元素组成，每个 TopoGeometry 由一个或多个 topology.layer 元素组成。

函数

```
SELECT te[1] AS id, te[2] AS type FROM
( SELECT ARRAY[1,2]::topology.topoelement AS te ) f;
id | type
----+-----
1  | 2
```

```
SELECT ARRAY[1,2]::topology.topoelement;
te
-----
{1,2}
```

```
--Example of what happens when you try to case a 3 element array to topoelement
-- NOTE: topoement has to be a 2 element array so fails dimension check
SELECT ARRAY[1,2,3]::topology.topoelement;
ERROR:  value for domain topology.topoelement violates check constraint "dimensions"
```

函数

[GetTopoGeomElements](#), [TopoElementArray](#), [TopoGeometry](#), [TopoGeom_addElement](#), [TopoGeom_remElement](#)

9.2.2 TopoElementArray

TopoElementArray — An array of TopoElement objects.



1 TopoElement TopoElement.



```
SELECT '{{1,2},{4,3}}'::topology.topoelementarray As tea;
      tea
-----
{{1,2},{4,3}}

-- more verbose equivalent --
SELECT ARRAY[ARRAY[1,2], ARRAY[4,3]]::topology.topoelementarray As tea;
      tea
-----
{{1,2},{4,3}}

--using the array agg function packaged with topology --
SELECT topology.TopoElementArray_Agg(ARRAY[e,t]) As tea
  FROM generate_series(1,4) As e CROSS JOIN generate_series(1,3) As t;
      tea
-----
{{1,1},{1,2},{1,3},{2,1},{2,2},{2,3},{3,1},{3,2},{3,3},{4,1},{4,2},{4,3}}
```



TopoElement, GetTopoGeomElementArray, TopoElementArray Agg

9.3 TopoGeometry

9.3.1 AddTopoGeometryColumn

AddTopoGeometryColumn — `TopoGeometry` `topology.layer` `layer id`.

Synopsis

```
integer AddTopoGeometryColumn(varchar topology_name, varchar schema_name, varchar table_name,
varchar column_name, varchar feature_type);
integer AddTopoGeometryColumn(varchar topology_name, varchar schema_name, varchar table_name,
varchar column_name, varchar feature_type, integer child_layer);
```



`TopoGeometry` 数据类型。 `TopoGeometry` 数据类型用于存储拓扑几何数据。
`AddTopoGeometryColumn()` 函数用于添加拓扑几何列。

topology.layer 函数返回 topology.layer 的 TopoGeometry 列。

[child_layer] 如果为 NULL，则返回 topology.layer 的 TopoGeometry 列。如果 child_layer 不为 NULL，则返回 child_layer 的 TopoGeometry 列。

（AddTopoGeometryColumn 函数 ID 列）返回 TopoGeometry 列。

Valid feature_types are: POINT, MULTIPOINT, LINE, MULTILINE, POLYGON, MULTIPOLYGON, COLLECTION

Availability: 1.1

例

```
-- Note for this example we created our new table in the ma_topo schema
-- though we could have created it in a different schema -- in which case topology_name and ←
-- schema_name would be different
CREATE SCHEMA ma;
CREATE TABLE ma.parcels(gid serial, parcel_id varchar(20) PRIMARY KEY, address text);
SELECT topology.AddTopoGeometryColumn('ma_topo', 'ma', 'parcels', 'topo', 'POLYGON');
```

```
CREATE SCHEMA ri;
CREATE TABLE ri.roads(gid serial PRIMARY KEY, road_name text);
SELECT topology.AddTopoGeometryColumn('ri_topo', 'ri', 'roads', 'topo', 'LINE');
```

例

DropTopoGeometryColumn, toTopoGeom, CreateTopology, CreateTopoGeom

9.3.2 RenameTopoGeometryColumn

RenameTopoGeometryColumn — Renames a topogeometry column

Synopsis

topology.layer **RenameTopoGeometryColumn**(regclass layer_table, name feature_column, name new_name)

例

This function changes the name of an existing TopoGeometry column ensuring metadata information about it is updated accordingly.

Availability: 3.4.0

例

```
SELECT topology.RenameTopoGeometryColumn('public.parcels', 'topogeom', 'tgeom');
```

函数

[AddTopoGeometryColumn](#), [RenameTopology](#)

9.3.3 DropTopology

DropTopology — 删除 topology: 删除 topology.topology 表, 并删除 geometry_columns 表。

Synopsis

```
integer DropTopology(varchar topology_schema_name);
```

函数

删除 topology.topology 表, 并删除 geometry_columns 表。删除 topology.topology 表时, 会删除 topology.topology 表中的所有记录。删除 geometry_columns 表时, 会删除 geometry_columns 表中的所有记录。

Availability: 1.1

函数

ma_topo 删除 topology.topology 表 geometry_columns 表。

```
SELECT topology.DropTopology('ma_topo');
```

函数

[DropTopoGeometryColumn](#)

9.3.4 RenameTopology

RenameTopology — 重命名 topology

Synopsis

```
varchar RenameTopology(varchar old_name, varchar new_name);
```

函数

重命名 topology schema, 更新其在 topology.topology 表中的元数据记录。

Availability: 3.4.0

图

Rename a topology from topo_stage to topo_prod.

```
SELECT topology.RenameTopology('topo_stage', 'topo_prod');
```

图

CopyTopology, RenameTopoGeometryColumn

9.3.5 DropTopoGeometryColumn

DropTopoGeometryColumn — schema_name 图 table_name 图 Topogeometry 图 topology.layer 图.

Synopsis

text **DropTopoGeometryColumn**(varchar schema_name, varchar table_name, varchar column_name);

图

schema_name 图 table_name 图 Topogeometry 图 topology.layer 图 图. 图. 图: 图 NULL 图.

Availability: 1.1

图

```
SELECT topology.DropTopoGeometryColumn('ma_topo', 'parcel_topo', 'topo');
```

图

AddTopoGeometryColumn

9.3.6 Populate_Topology_Layer

Populate_Topology_Layer — Adds missing entries to topology.layer table by reading metadata from topo tables.

Synopsis

setof record **Populate_Topology_Layer**();

国国

Adds missing entries to the `topology.layer` table by inspecting topology constraints on tables. This function is useful for fixing up entries in topology catalog after restores of schemas with topo data.

It returns the list of entries created. Returned columns are `schema_name`, `table_name`, `feature_column`.

2.3.0 国国国国国国国国国国国国.

国国

```
SELECT CreateTopology('strk_topo');
CREATE SCHEMA strk;
CREATE TABLE strk.parcels(gid serial, parcel_id varchar(20) PRIMARY KEY, address text);
SELECT topology.AddTopoGeometryColumn('strk_topo', 'strk', 'parcels', 'topo', 'POLYGON');
-- this will return no records because this feature is already registered
SELECT *
  FROM topology.Populate_Topology_Layer();

-- let's rebuild
TRUNCATE TABLE topology.layer;

SELECT *
  FROM topology.Populate_Topology_Layer();

SELECT topology_id,layer_id, schema_name As sn, table_name As tn, feature_column As fc
FROM topology.layer;
```

schema_name	table_name	feature_column
-----+-----+-----		
strk	parcels	topo
(1 row)		

topology_id	layer_id	sn	tn	fc
-----+-----+-----+-----+-----				
2	2	strk	parcels	topo
(1 row)				

国国

AddTopoGeometryColumn

9.3.7 TopologySummary

TopologySummary — Takes a topology name and provides summary totals of types of objects in topology.

Synopsis

text **TopologySummary**(varchar topology_schema_name);

❏❏

Takes a topology name and provides summary totals of types of objects in topology.

2.0.0 简体中文.

❏❏

```
SELECT topology.topologysummary('city_data');
           topologysummary
-----
Topology city_data (329), SRID 4326, precision: 0
22 nodes, 24 edges, 10 faces, 29 topogeoms in 5 layers
Layer 1, type Polygonal (3), 9 topogeoms
  Deploy: features.land_parcels.feature
Layer 2, type Puntal (1), 8 topogeoms
  Deploy: features.traffic_signs.feature
Layer 3, type Lineal (2), 8 topogeoms
  Deploy: features.city_streets.feature
Layer 4, type Polygonal (3), 3 topogeoms
  Hierarchy level 1, child layer 1
  Deploy: features.big_parcels.feature
Layer 5, type Puntal (1), 1 topogeoms
  Hierarchy level 1, child layer 2
  Deploy: features.big_signs.feature
```

❏❏

Topology_Load_Tiger

9.3.8 ValidateTopology

ValidateTopology — Returns a set of validate_topology_returntype objects detailing issues with topology.

Synopsis

setof validate_topology_returntype **ValidateTopology**(varchar toponame, geometry bbox);

❏❏

Returns a set of **validate_topology_returntype** objects detailing issues with topology, optionally limiting the check to the area specified by the **bbox** parameter.

List of possible errors, what they mean and what the returned ids represent are displayed below:

❏❏	id1	id2	Meaning
coincident nodes	Identifier of first node.	Identifier of second node.	Two nodes have the same geometry.
edge crosses node(❏❏❏❏❏❏❏❏❏)	Identifier of the edge.	Identifier of the node.	An edge has a node in its interior. See ST_Relate .

国国	id1	id2	Meaning
invalid edge(国国国国国国国国国国)	Identifier of the edge.		An edge geometry is invalid. See ST_IsValid .
edge not simple(国国国国国国国国国国)	Identifier of the edge.		An edge geometry has self-intersections. See ST_IsSimple .
edge crosses edge(国国国国国国国国国国国国)	Identifier of first edge.	Identifier of second edge.	Two edges have an interior intersection. See ST_Relate .
edge start node geometry mismatch(国国国国国国国国国国国国国国)	Identifier of the edge.	Identifier of the indicated start node.	The geometry of the node indicated as the starting node for an edge does not match the first point of the edge geometry. See ST_StartPoint .
edge end node geometry mismatch(国国国国国国国国国国国国国国)	Identifier of the edge.	Identifier of the indicated end node.	The geometry of the node indicated as the ending node for an edge does not match the last point of the edge geometry. See ST_EndPoint .
face without edges(国国国国国国国国国国)	Identifier of the orphaned face.		No edge reports an existing face on either of its sides (left_face, right_face).
face has no rings(国国国国国国国国国国)	Identifier of the partially-defined face.		Edges reporting a face on their sides do not form a ring.
face has wrong mbr	Identifier of the face with wrong mbr cache.		Minimum bounding rectangle of a face does not match minimum bounding box of the collection of edges reporting the face on their sides.
hole not in advertised face	Signed identifier of an edge, identifying the ring. See GetRingEdges .		A ring of edges reporting a face on its exterior is contained in different face.
not-isolated node has not- containing_face	Identifier of the ill-defined node.		A node which is reported as being on the boundary of one or more edges is indicating a containing face.
isolated node has containing_face	Identifier of the ill-defined node.		A node which is not reported as being on the boundary of any edges is lacking the indication of a containing face.

☒☒	id1	id2	Meaning
isolated node has wrong containing_face	Identifier of the misrepresented node.		A node which is not reported as being on the boundary of any edges indicates a containing face which is not the actual face containing it. See GetFaceContaining-Point .
invalid next_right_edge	Identifier of the misrepresented edge.	Signed id of the edge which should be indicated as the next right edge.	The edge indicated as the next edge encountered walking on the right side of an edge is wrong.
invalid next_left_edge	Identifier of the misrepresented edge.	Signed id of the edge which should be indicated as the next left edge.	The edge indicated as the next edge encountered walking on the left side of an edge is wrong.
mixed face labeling in ring	Signed identifier of an edge, identifying the ring. See GetRingEdges .		Edges in a ring indicate conflicting faces on the walking side. This is also known as a "Side Location Conflict".
non-closed ring	Signed identifier of an edge, identifying the ring. See GetRingEdges .		A ring of edges formed by following next_left_edge/next_right_edge attributes starts and ends on different nodes.
face has multiple shells	Identifier of the contended face.	Signed identifier of an edge, identifying the ring. See GetRingEdges .	More than a one ring of edges indicate the same face on its interior.

1.0.0 ☒☒☒☒☒☒☒☒☒☒☒.

2.0.0 2020-08-10 12:00:00, 2020-08-10 12:00:00 (false positive) 2020-08-10 12:00:00.

2.2.0 'edge crosses node' id1 id2

Changed: 3.2.0 added optional bbox parameter, perform face labeling and edge linking checks.



```
SELECT * FROM topology.ValidateTopology('ma_topo');
      error      | id1 | id2
-----+-----+-----
face without edges |    1 |
```



validatetopology returntype, Topology Load Tiger

9.3.9 ValidateTopologyRelation

ValidateTopologyRelation — Returns info about invalid topology relation records

Synopsis

setof record **ValidateTopologyRelation**(varchar toponame);

返回

Returns a set records giving information about invalidities in the relation table of the topology.

Availability: 3.2.0

返回

ValidateTopology

9.3.10 FindTopology

FindTopology — Returns a topology record by different means.

Synopsis

topology **FindTopology**(TopoGeometry topogeom);
 topology **FindTopology**(regclass layerTable, name layerColumn);
 topology **FindTopology**(name layerSchema, name layerTable, name layerColumn);
 topology **FindTopology**(text topoName);
 topology **FindTopology**(int id);

返回

Takes a topology identifier or the identifier of a topology-related object and returns a topology.topology record.

Availability: 3.2.0

返回

```
SELECT name(findTopology('features.land_parcels', 'feature'));
      name
-----
city_data
(1 row)
```

返回

FindLayer

9.3.11 FindLayer

FindLayer — Returns a topology.layer record by different means.

Synopsis

```
topology.layer FindLayer(TopoGeometry tg);  
topology.layer FindLayer(regclass layer_table, name feature_column);  
topology.layer FindLayer(name schema_name, name table_name, name feature_column);  
topology.layer FindLayer(integer topology_id, integer layer_id);
```



Takes a layer identifier or the identifier of a topology-related object and returns a topology.layer record.

Availability: 3.2.0



```
SELECT layer_id(findLayer('features.land_parcel', 'feature'));  
 layer_id  
-----  
         1  
(1 row)
```



FindTopology

9.4 Topology Statistics Management

Adding elements to a topology triggers many database queries for finding existing edges that will be split, adding nodes and updating edges that will node with the new linework. For this reason it is useful that statistics about the data in the topology tables are up-to-date.

PostGIS Topology population and editing functions do not automatically update the statistics because a updating stats after each and every change in a topology would be overkill, so it is the caller's duty to take care of that.



Note

That the statistics updated by autovacuum will NOT be visible to transactions which started before autovacuum process completed, so long-running transactions will need to run ANALYZE themselves, to use updated statistics.

9.5

9.5.1 CreateTopology

CreateTopology — Creates a new topology schema and registers it in the topology.topology table.

Synopsis

```
integer CreateTopology(varchar topology_schema_name);
integer CreateTopology(varchar topology_schema_name, integer srid);
integer CreateTopology(varchar topology_schema_name, integer srid, double precision prec);
integer CreateTopology(varchar topology_schema_name, integer srid, double precision prec, boolean hasz);
```

国国

Creates a new topology schema with name `topology_name` and registers it in the `topology.topology` table. Topologies must be uniquely named. The topology tables (`edge_data`, `face`, `node`, and `relation`) are created in the schema. It returns the id of the topology.

The `srid` is the [spatial reference system](#) SRID for the topology.

The tolerance `prec` is measured in the units of the spatial reference system. The tolerance defaults to 0.

`hasz` defaults to false if not specified.

This is similar to the SQL/MM [ST_InitTopoGeo](#) but has more functionality.

Availability: 1.1

Enhanced: 2.0 added the signature accepting `hasZ`

国国

Create a topology schema called `ma_topo` that stores edges and nodes in Massachusetts State Plane-meters (SRID = 26986). The tolerance represents 0.5 meters since the spatial reference system is meter-based.

```
SELECT topology.CreateTopology('ma_topo', 26986, 0.5);
```

Create a topology for Rhode Island called `ri_topo` in spatial reference system State Plane-feet (SRID = 3438)

```
SELECT topology.CreateTopology('ri_topo', 3438) AS topoid;
topoid
-----
2
```

国国

Section [4.5](#), [ST_InitTopoGeo](#), [Topology_Load_Tiger](#)

9.5.2 CopyTopology

CopyTopology — Makes a copy of a topology (nodes, edges, faces, layers and TopoGeometries) into a new schema

Synopsis

```
integer CopyTopology(varchar existing_topology_name, varchar new_name);
```


函数

Creates a new topology with name `new_name`, with SRID and precision copied from `existing_topology_name`. The nodes, edges and faces in `existing_topology_name` are copied into the new topology, as well as Layers and their associated TopoGeometries.



Note

The new rows in the `topology.layer` table contain synthetic values for `schema_name`, `table_name` and `feature_column`. This is because the TopoGeometry objects exist only as a definition and are not yet available in a user-defined table.

2.0.0 函数参考.

函数

Make a backup of a topology called `ma_topo`.

```
SELECT topology.CopyTopology('ma_topo', 'ma_topo_backup');
```

函数

Section [4.5, CreateTopology, RenameTopology](#)

9.5.3 ST_InitTopoGeo

`ST_InitTopoGeo` — Creates a new topology schema and registers it in the `topology.topology` table.

Synopsis

text **ST_InitTopoGeo**(varchar topology_schema_name);

函数

This is the SQL-MM equivalent of [CreateTopology](#). It lacks options for spatial reference system and tolerance. it returns a text description of the topology creation, instead of the topology id.

Availability: 1.1



This method implements the SQL/MM specification. SQL-MM 3 Topo-Geo and Topo-Net 3: Routine Details: X.3.17

函数

```
SELECT topology.ST_InitTopoGeo('topo_schema_to_create') AS topocreation;
               astopocreation
-----
Topology-Geometry 'topo_schema_to_create' (id:7) created.
```


9.5.5 TopoGeo_AddPoint

TopoGeo_AddPoint — 向拓扑中添加点 (split) 并返回其标识符。

Synopsis

integer **TopoGeo_AddPoint**(varchar atopology, geometry apoint, float8 tolerance);

返回

Adds a point to an existing topology and returns its identifier. The given point will snap to existing nodes or edges within given tolerance. An existing edge may be split by the snapped point.

2.0.0 版本引入。

注意

[TopoGeo_AddLineString](#), [TopoGeo_AddPolygon](#), [TopoGeo_LoadGeometry](#), [AddNode](#), [CreateTopology](#)

9.5.6 TopoGeo_AddLineString

TopoGeo_AddLineString — Adds a linestring to an existing topology using a tolerance and possibly splitting existing edges/faces.

Synopsis

SETOF integer **TopoGeo_AddLineString**(varchar atopology, geometry aline, float8 tolerance);

返回

Adds a linestring to an existing topology and returns a set of signed edge identifiers forming it up (negative identifies mean the edge goes in the opposite direction of the input linestring). The given line will snap to existing nodes or edges within given tolerance. Existing edges and faces may be split by the line. New nodes and faces may be added.



Note

Updating statistics about topologies being loaded via this function is up to caller, see [maintaining statistics during topology editing and population](#).

2.0.0 版本引入。

Enhanced: 3.2.0 added support for returning signed identifier.

注意

[TopoGeo_AddPoint](#), [TopoGeo_AddPolygon](#), [TopoGeo_LoadGeometry](#), [AddEdge](#), [CreateTopology](#)

9.5.7 TopoGeo_AddPolygon

TopoGeo_AddPolygon — Adds a polygon to an existing topology using a tolerance and possibly splitting existing edges/faces. Returns face identifiers.

Synopsis

SETOF integer **TopoGeo_AddPolygon**(varchar atopology, geometry apoly, float8 tolerance);

ⓘ

Adds a polygon to an existing topology and returns a set of face identifiers forming it up. The boundary of the given polygon will snap to existing nodes or edges within given tolerance. Existing edges and faces may be split by the boundary of the new polygon.



Note

Updating statistics about topologies being loaded via this function is up to caller, see [maintaining statistics during topology editing and population](#).

2.0.0 简体中文.

ⓘ

[TopoGeo_AddPoint](#), [TopoGeo_AddLineString](#), [TopoGeo_LoadGeometry](#), [AddFace](#), [CreateTopology](#)

9.5.8 TopoGeo_LoadGeometry

TopoGeo_LoadGeometry — Load a geometry into an existing topology, snapping and splitting as needed.

Synopsis

void **TopoGeo_LoadGeometry**(varchar atopology, geometry ageom, float8 tolerance);

ⓘ

Loads a geometry into an existing topology. The given geometry will snap to existing nodes or edges within given tolerance. Existing edges and faces may be split as a consequence of the load.



Note

Updating statistics about topologies being loaded via this function is up to caller, see [maintaining statistics during topology editing and population](#).

Availability: 3.5.0

函数

[TopoGeo_AddPoint](#), [TopoGeo_AddLineString](#), [TopoGeo_AddPolygon](#), [CreateTopology](#)

9.6 拓扑函数

9.6.1 ST_AddIsoNode

`ST_AddIsoNode` — 添加孤立的 (isolated) 节点 ID 到拓扑。如果 NULL 则返回 NULL, 否则返回拓扑 ID。

Synopsis

```
integer ST_AddIsoNode(varchar atopology, integer aface, geometry apoint);
```

函数

`atopology` 拓扑 ID(`faceid`) 的字符串, `apoint` 要添加的点的几何体, 如果 NULL 则返回 NULL, 否则返回拓扑 ID。

如果 `apoint` 的 SRID 与 `atopology` 的 SRID 不同, 则返回 NULL。如果 `apoint` 的 SRID 与 `atopology` 的 SRID 相同, 则返回拓扑 ID。

`aface` 如果 NULL 则返回 `apoint` 的 SRID, 否则返回拓扑 ID。

Availability: 1.1



This method implements the SQL/MM specification. SQL-MM: Topo-Net Routines: X+1.3.1

函数

函数

[AddNode](#), [CreateTopology](#), [DropTopology](#), [ST_Intersects](#)

9.6.2 ST_AddIsoEdge

`ST_AddIsoEdge` — 添加孤立的 (isolated) 边 ID 到拓扑。如果 NULL 则返回 NULL, 否则返回拓扑 ID。

Synopsis

```
integer ST_AddIsoEdge(varchar atopology, integer anode, integer anothernode, geometry alinestring);
```

几何。

`ST_AddEdgeNewFace` 在 `anode` 和 `anothernode` 之间添加新的边 `alinesring`。如果 `alinesring` 是 `NULL`，则返回 `NULL`。如果 `alinesring` 不是 `NULL`，则返回 `alinesring` 的 ID。
 如果 `alinesring` 是 `NULL`，则返回 `alinesring` 的 ID。
 如果 `alinesring` 不是 `NULL`，则返回 `alinesring` 的 ID。

`alinesring` 是 `alinesring` (SRID) 的别名，如果 `alinesring` 是 `NULL`，则返回 `NULL`。如果 `alinesring` 不是 `NULL`，则返回 `alinesring` 的 ID。

`alinesring` 是 `anode` 和 `anothernode` 之间的边，如果 `alinesring` 不是 `NULL`，则返回 `alinesring` 的 ID。

`anode` 和 `anothernode` 是 `alinesring` 的端点，如果 `alinesring` 不是 `NULL`，则返回 `alinesring` 的 ID。

Availability: 1.1

 This method implements the SQL/MM specification. SQL-MM: Topo-Geo and Topo-Net 3: Routine Details: X.3.4

几何。

几何。

[ST_AddIsoNode](#), [ST_IsSimple](#), [ST_Within](#)

9.6.3 ST_AddEdgeNewFaces

`ST_AddEdgeNewFaces` — 在 `atopology` 中添加新的边，如果 `atopology` 是 `NULL`，则返回 `NULL`。如果 `atopology` 不是 `NULL`，则返回 `atopology` 的 ID。

Synopsis

integer **ST_AddEdgeNewFaces**(varchar atopology, integer anode, integer anothernode, geometry acurve);

几何。

`ST_AddEdgeNewFaces` 在 `atopology` 中添加新的边，如果 `atopology` 是 `NULL`，则返回 `NULL`。如果 `atopology` 不是 `NULL`，则返回 `atopology` 的 ID。

`ST_AddEdgeNewFaces` 在 `atopology` 中添加新的边，如果 `atopology` 是 `NULL`，则返回 `NULL`。如果 `atopology` 不是 `NULL`，则返回 `atopology` 的 ID。

`ST_AddEdgeNewFaces` 在 `atopology` 中添加新的边，如果 `atopology` 是 `NULL`，则返回 `NULL`。如果 `atopology` 不是 `NULL`，则返回 `atopology` 的 ID。

`acurve` 是 `acurve` (SRID) 的别名，如果 `acurve` 是 `NULL`，则返回 `NULL`。如果 `acurve` 不是 `NULL`，则返回 `acurve` 的 ID。

2.0 版本。

 This method implements the SQL/MM specification. SQL-MM: Topo-Geo and Topo-Net 3: Routine Details: X.3.12

几何。

几何。

[ST_RemEdgeNewFace](#)

[ST_AddEdgeModFace](#)

函数

返回一个拓扑，该拓扑是输入拓扑的副本，其中指定的边被移除。

如果指定的 ID 不存在，则返回 NULL。如果指定的 ID 不存在，则返回 NULL。如果指定的 ID 不存在，则返回 NULL。

如果指定的 ID 不存在，则返回 NULL。

Refuses to remove an edge participating in the definition of an existing TopoGeometry. Refuses to heal two faces if any TopoGeometry is defined by only one of them (and not the other).

如果指定的 ID 不存在，则返回 NULL。如果指定的 ID 不存在，则返回 NULL。如果指定的 ID 不存在，则返回 NULL。

2.0 版本。



This method implements the SQL/MM specification. SQL-MM: Topo-Geo and Topo-Net 3: Routine Details: X.3.14

函数

函数

ST_RemEdgeModFace

ST_AddEdgeNewFaces

9.6.6 ST_RemEdgeModFace

ST_RemEdgeModFace — Removes an edge, and if the edge separates two faces deletes one face and modifies the other face to cover the space of both.

Synopsis

integer **ST_RemEdgeModFace**(varchar atopoology, integer anedge);

函数

Removes an edge, and if the removed edge separates two faces deletes one face and modifies the other face to cover the space of both. Preferentially keeps the face on the right, to be consistent with **ST_AddEdgeModFace**. Returns the id of the face which is preserved.

如果指定的 ID 不存在，则返回 NULL。

Refuses to remove an edge participating in the definition of an existing TopoGeometry. Refuses to heal two faces if any TopoGeometry is defined by only one of them (and not the other).

如果指定的 ID 不存在，则返回 NULL。如果指定的 ID 不存在，则返回 NULL。如果指定的 ID 不存在，则返回 NULL。

2.0 版本。



This method implements the SQL/MM specification. SQL-MM: Topo-Geo and Topo-Net 3: Routine Details: X.3.15

函数

函数

[ST_AddEdgeModFace](#)

[ST_RemEdgeNewFace](#)

9.6.7 ST_ChangeEdgeGeom

ST_ChangeEdgeGeom — 修改拓扑中的边几何。

Synopsis

text **ST_ChangeEdgeGeom**(varchar atopology, integer anedge, geometry acurve);

函数

如果任何参数为 null，则给定的边在拓扑模式中的边表中不存在，acurve 不是 LINESTRING，或修改将更改底层拓扑，则抛出错误。

If any arguments are null, the given edge does not exist in the edge table of the topology schema, the acurve is not a LINESTRING, or the modification would change the underlying topology then an error is thrown.

acurve 具有 SRID 的几何体。

acurve 必须是 LINESTRING，且必须是有效的。

此函数返回修改后的拓扑。

1.1.0 版本引入。

更新: 2.0.0 版本引入。

 This method implements the SQL/MM specification. SQL-MM: Topo-Geo and Topo-Net 3: Routine Details X.3.6

函数

```
SELECT topology.ST_ChangeEdgeGeom('ma_topo', 1,
    ST_GeomFromText('LINESTRING(227591.9 893900.4,227622.6 893844.3,227641.6
    893816.6, 227704.5 893778.5)', 26986) );
----
Edge 1 changed
```

函数

[ST_AddEdgeModFace](#)

[ST_RemEdgeModFace](#)

[ST_ModEdgeSplit](#)

9.6.8 ST_ModEdgeSplit

ST_ModEdgeSplit — 将拓扑中的边在指定点处分割，并返回新边的 ID。该函数返回一个整数，表示新边的 ID。

Synopsis

integer **ST_ModEdgeSplit**(varchar atopology, integer anedge, geometry apoint);

返回

该函数返回一个整数，表示新边的 ID。该函数返回一个整数，表示新边的 ID。该函数返回一个整数，表示新边的 ID。

Availability: 1.1

从 2.0 版本开始，ST_ModEdgesSplit 函数已弃用。

 This method implements the SQL/MM specification. SQL-MM: Topo-Geo and Topo-Net 3: Routine Details: X.3.9

示例

```
-- Add an edge --
SELECT topology.AddEdge('ma_topo', ST_GeomFromText('LINESTRING(227592 893910, 227600 893910)', 26986) ) As edgeid;

-- edgeid-
3

-- Split the edge --
SELECT topology.ST_ModEdgeSplit('ma_topo', 3, ST_SetSRID(ST_Point(227594,893910),26986) ) As node_id;
       node_id
-----
7
```

示例

[ST_NewEdgesSplit](#), [ST_ModEdgeHeal](#), [ST_NewEdgeHeal](#), [AddEdge](#)

9.6.9 ST_ModEdgeHeal

ST_ModEdgeHeal — 通过删除连接它们的节点并修改第一条边和删除第二条边来愈合两条边。返回删除的节点 ID。

Synopsis

int **ST_ModEdgeHeal**(varchar atopology, integer anedge, integer anotheredge);

国国

Heals two edges by deleting the node connecting them, modifying the first edge and deleting the second edge. Returns the id of the deleted node. Updates all existing joined edges and relationships accordingly.

2.0 国国国国国国国国国国国国.

 This method implements the SQL/MM specification. SQL-MM: Topo-Geo and Topo-Net 3: Routine Details: X.3.9

国国

[ST_ModEdgeSplit](#) [ST_NewEdgesSplit](#)

9.6.10 ST_NewEdgeHeal

ST_NewEdgeHeal — Heals two edges by deleting the node connecting them, deleting both edges, and replacing them with an edge whose direction is the same as the first edge provided.

Synopsis

int **ST_NewEdgeHeal**(varchar atopology, integer anedge, integer anotheredge);

国国

Heals two edges by deleting the node connecting them, deleting both edges, and replacing them with an edge whose direction is the same as the first edge provided. Returns the id of the new edge replacing the healed ones. Updates all existing joined edges and relationships accordingly.

2.0 国国国国国国国国国国国国.

 This method implements the SQL/MM specification. SQL-MM: Topo-Geo and Topo-Net 3: Routine Details: X.3.9

国国

[ST_ModEdgeHeal](#) [ST_ModEdgeSplit](#) [ST_NewEdgesSplit](#)

9.6.11 ST_MoveIsoNode

ST_MoveIsoNode — Moves an isolated node in a topology from one point to another. If new apoint geometry exists as a node an error is thrown. Returns description of move.

Synopsis

text **ST_MoveIsoNode**(varchar atopology, integer anode, geometry apoint);

函数

`ST_AddIsoNode` 添加一个孤立节点。 `apoint` 指定新节点的位置。如果 `apoint` 为 NULL，则新节点位于现有边的端点处。如果新节点位于现有边的端点处，则新节点位于现有边的端点处。如果新节点位于现有边的端点处，则新节点位于现有边的端点处。

If any arguments are null, the `apoint` is not a point, the existing node is not isolated (is a start or end point of an existing edge), new node location intersects an existing edge (even at the end points) or the new location is in a different face (since 3.2.0) then an exception is thrown.

`SRID` (SRID) 指定新节点的 SRID。

2.0.0 版本引入。

Enhanced: 3.2.0 ensures the node cannot be moved in a different face

 This method implements the SQL/MM specification. SQL-MM: Topo-Net Routines: X.3.2

函数

```
-- Add an isolated node with no face --
SELECT topology.ST_AddIsoNode('ma_topo', NULL, ST_GeomFromText('POINT(227579 893916)', 26986) ) As nodeid;
nodeid
-----
7
-- Move the new node --
SELECT topology.ST_MoveIsoNode('ma_topo', 7, ST_GeomFromText('POINT(227579.5 893916.5)', 26986) ) As descrip;
descrip
-----
Isolated Node 7 moved to location 227579.5,893916.5
```

函数

ST_AddIsoNode

9.6.12 ST_NewEdgesSplit

`ST_NewEdgesSplit` 将现有边分割成两条边。现有边由 `anedge` 指定。新边由 `apoint` 指定。新边由 `apoint` 指定。新边由 `apoint` 指定。

Synopsis

integer **ST_NewEdgesSplit**(varchar atopology, integer anedge, geometry apoint);

函数

`apoint` 指定新节点的位置。如果 `apoint` 为 NULL，则新节点位于现有边的端点处。如果新节点位于现有边的端点处，则新节点位于现有边的端点处。如果新节点位于现有边的端点处，则新节点位于现有边的端点处。

`SRID` (SRID) 指定新节点的 SRID。如果 `apoint` 为 NULL，则新节点位于现有边的端点处。如果新节点位于现有边的端点处，则新节点位于现有边的端点处。如果新节点位于现有边的端点处，则新节点位于现有边的端点处。

Availability: 1.1

 This method implements the SQL/MM specification. SQL-MM: Topo-Net Routines: X.3.8

例

```
-- Add an edge --
SELECT topology.AddEdge('ma_topo', ST_GeomFromText('LINESTRING(227575 893917,227592 893900) ', 26986) ) As edgeid;
-- result-
edgeid
-----
      2
-- Split the new edge --
SELECT topology.ST_NewEdgesSplit('ma_topo', 2, ST_GeomFromText('POINT(227578.5 893913.5)', 26986) ) As newnodeid;
newnodeid
-----
      6
```

例

[ST_ModEdgeSplit](#) [ST_ModEdgeHeal](#) [ST_NewEdgeHeal](#) [AddEdge](#)

9.6.13 ST_RemoveIsoNode

ST_RemoveIsoNode — 删除拓扑中的孤立节点。 删除孤立节点 (没有面的节点) 后, 返回结果。

Synopsis

text **ST_RemoveIsoNode**(varchar atopology, integer anode);

例

删除拓扑中的孤立节点。 删除孤立节点 (没有面的节点) 后, 返回结果。

Availability: 1.1

 This method implements the SQL/MM specification. SQL-MM: Topo-Geo and Topo-Net 3: Routine Details: X+1.3.3

例

```
-- Remove an isolated node with no face --
SELECT topology.ST_RemoveIsoNode('ma_topo', 7 ) As result;
result
-----
Isolated node 7 removed
```

例

[ST_AddIsoNode](#)

9.6.14 ST_RemoveIsoEdge

ST_RemoveIsoEdge — Removes an isolated edge and returns description of action. If the edge is not isolated, then an exception is thrown.

Synopsis

text **ST_RemoveIsoEdge**(varchar atopology, integer anedge);

返回

Removes an isolated edge and returns description of action. If the edge is not isolated, then an exception is thrown.

Availability: 1.1

 This method implements the SQL/MM specification. SQL-MM: Topo-Geo and Topo-Net 3: Routine Details: X+1.3.3

示例

```
-- Remove an isolated node with no face --
SELECT topology.ST_RemoveIsoNode('ma_topo', 7 ) As result;
           result
-----
Isolated node 7 removed
```

参见

[ST_AddIsoNode](#)

9.7 拓扑函数

9.7.1 GetEdgeByPoint

GetEdgeByPoint — Finds the edge-id of an edge that intersects a given point.

Synopsis

integer **GetEdgeByPoint**(varchar atopology, geometry apoint, float8 tol1);

返回

Retrieves the id of an edge that intersects a Point.

geometry, point, geometry (edgeid) geometry. tolerance = 0 geometry.

If apoint doesn't intersect an edge, returns 0 (zero).

If use tolerance > 0 and there is more than one edge near the point then an exception is thrown.

**Note**

当 tolerance = 0 时，ST_Intersects 与 ST_DWithin 等价。

GEOS 版本

2.0.0 版本。

图

图 **AddEdge** 图。

```
SELECT topology.GetEdgeByPoint('ma_topo',geom, 1) As with1mtol, topology.GetEdgeByPoint(' ←
      ma_topo',geom,0) As withnotol
FROM ST_GeomFromEWKT('SRID=26986;POINT(227622.6 893843)') As geom;
with1mtol | withnotol
-----+-----
          2 |          0
```

```
SELECT topology.GetEdgeByPoint('ma_topo',geom, 1) As nearnode
FROM ST_GeomFromEWKT('SRID=26986;POINT(227591.9 893900.4)') As geom;

-- get error --
ERROR:  Two or more edges found
```

图

AddEdge, GetNodeByPoint, GetFaceByPoint

9.7.2 GetFaceByPoint

GetFaceByPoint — Finds face intersecting a given point.

Synopsis

integer **GetFaceByPoint**(varchar atopology, geometry apoint, float8 tol1);

图

Finds a face referenced by a Point, with given tolerance.

The function will effectively look for a face intersecting a circle having the point as center and the tolerance as radius.

If no face intersects the given query location, 0 is returned (universal face).

If more than one face intersect the query location an exception is thrown.

2.0.0 版本。

Enhanced: 3.2.0 more efficient implementation and clearer contract, stops working with invalid topologies.

国国

```
SELECT topology.GetFaceByPoint('ma_topo',geom, 10) As with1mtol, topology.GetFaceByPoint(' ←
ma_topo',geom,0) As withnotol
FROM ST_GeomFromEWKT('POINT(234604.6 899382.0)') As geom;
```

```
with1mtol | withnotol
-----+-----
1 | 0
```

```
SELECT topology.GetFaceByPoint('ma_topo',geom, 1) As nearnode
FROM ST_GeomFromEWKT('POINT(227591.9 893900.4)') As geom;
```

```
-- get error --
ERROR: Two or more faces found
```

国国

[GetFaceContainingPoint](#), [AddFace](#), [GetNodeByPoint](#), [GetEdgeByPoint](#)

9.7.3 GetFaceContainingPoint

GetFaceContainingPoint — Finds the face containing a point.

Synopsis

integer **GetFaceContainingPoint**(text atopology, geometry apoint);

国国

Returns the id of the face containing a point.

An exception is thrown if the point falls on a face boundary.



Note

The function relies on a valid topology, using edge linking and face labeling.

Availability: 3.2.0

国国

[ST_GetFaceGeometry](#)

9.7.4 GetNodeByPoint

GetNodeByPoint — Finds the node-id of a node at a point location.

Synopsis

integer **GetNodeByPoint**(varchar atopology, geometry apoint, float8 tol1);

¶¶

Retrieves the id of a node at a point location.

The function returns an integer (id-node) given a topology, a POINT and a tolerance. If tolerance = 0 means exact intersection, otherwise retrieves the node from an interval.

If apoint doesn't intersect a node, returns 0 (zero).

If use tolerance > 0 and there is more than one node near the point then an exception is thrown.



Note

¶¶¶ tolerance = 0 ¶¶ ST_Intersects ¶, ¶¶¶¶¶ ST_DWithin ¶¶¶¶.

GEOS ¶¶¶¶

2.0.0 ¶¶¶¶¶¶¶¶.

¶¶

¶¶¶¶¶ **AddEdge** ¶¶¶¶¶¶¶¶¶¶¶.

```
SELECT topology.GetNodeByPoint('ma_topo',geom, 1) As nearnode
FROM ST_GeomFromEWKT('SRID=26986;POINT(227591.9 893900.4)') As geom;
      nearnode
-----
          2
```

```
SELECT topology.GetNodeByPoint('ma_topo',geom, 1000) As too_much_tolerance
FROM ST_GeomFromEWKT('SRID=26986;POINT(227591.9 893900.4)') As geom;

---get error--
ERROR:  Two or more nodes found
```

¶¶

AddEdge, **GetEdgeByPoint**, **GetFaceByPoint**

9.7.5 GetTopologyID

GetTopologyID — ¶¶¶¶¶¶¶¶ topology.topology ¶¶¶¶¶¶¶ ID ¶¶¶¶¶.

Synopsis

integer **GetTopologyID**(varchar toponame);

例

topology.topology ID .

Availability: 1.1

例

```
SELECT topology.GetTopologyID('ma_topo') As topo_id;
topo_id
-----
1
```

例

[CreateTopology](#), [DropTopology](#), [GetTopologyName](#), [GetTopologySRID](#)

9.7.6 GetTopologySRID

GetTopologySRID — topology.topology SRID .

Synopsis

integer **GetTopologyID**(varchar toponame);

例

topology .
2.0.0 .

例

```
SELECT topology.GetTopologySRID('ma_topo') As SRID;
SRID
-----
4326
```

例

[CreateTopology](#), [DropTopology](#), [GetTopologyName](#), [GetTopologyID](#)

9.7.7 GetTopologyName

GetTopologyName — ID () .

Synopsis

varchar **GetTopologyName**(integer topology_id);

返回

返回 topology ID topology.topology 名称 (名称) 名称。

Availability: 1.1

示例

```
SELECT topology.GetTopologyName(1) As topo_name;
      topo_name
-----
      ma_topo
```

参见

[CreateTopology](#), [DropTopology](#), [GetTopologyID](#), [GetTopologySRID](#)

9.7.8 ST_GetFaceEdges

ST_GetFaceEdges — aface 返回面边界边。

Synopsis

getfaceedges_returntype **ST_GetFaceEdges**(varchar atopology, integer aface);

返回

aface 返回面边界边。返回 (sequence) ID(edgeid) 返回。返回 1 返回。

返回。返回 (返回) 返回。

2.0 返回。

 This method implements the SQL/MM specification. SQL-MM 3 Topo-Geo and Topo-Net 3: Routine Details: X.3.5

示例

```
-- Returns the edges bounding face 1
SELECT (topology.ST_GetFaceEdges('tt', 1)).*;
-- result --
sequence | edge
-----+-----
1 | -4
2 | 5
```

3		7
4		-6
5		1
6		2
7		3

(7 rows)

```
-- Returns the sequence, edge id
-- and geometry of the edges that bound face 1
-- If you just need geom and seq, can use ST_GetFaceGeometry
SELECT t.seq, t.edge, geom
FROM topology.ST_GetFaceEdges('tt',1) As t(seq,edge)
      INNER JOIN tt.edge AS e ON abs(t.edge) = e.edge_id;
```



GetRingEdges, AddFace, ST GetFaceGeometry

9.7.9 ST_GetFaceGeometry

ST GetFaceGeometry — 16x16x16x16x16x16 ID 16x16x16x16x16x16.

Synopsis

```
geometry ST_GetFaceGeometry(varchar atopology, integer aface);
```



XXXXXXXXXXXXXXXX ID XXXXXXXXXXXXXXXX. XXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXX.

Availability: 1.1

✔ This method implements the SQL/MM specification. SQL-MM 3 Topo-Geo and Topo-Net 3: Routine Details: X.3.16



```
-- Returns the wkt of the polygon added with AddFace
SELECT ST_AsText(topology.ST_GetFaceGeometry('ma_topo', 1)) As facegeomwkt;
-- result --
        facegeomwkt
-----
POLYGON((234776.9 899563.7,234896.5 899456.7,234914 899436.4,234946.6 899356.9,
234872.5 899328.7,234891 899285.4,234992.5 899145,234890.6 899069,
234755.2 899255.4,234612.7 899379.4,234776.9 899563.7))
```



AddFace

9.7.10 GetRingEdges

GetRingEdges — .

Synopsis

```
getfaceedges_returntype GetRingEdges(varchar atopology, integer aring, integer max_edges=null);
```

[illegible]

XXXXXXXXXX ID XXXXXX, XXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXX. XX
XXXXXXXXXX ID XXXXXX, XXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXX.

```
max_edges = NULL; // The maximum number of edges per node. If set to zero, it will be determined by the number of nodes.
// If set to a non-zero value, it will be used to limit the number of edges per node.
```



Note

[illegible]

2.0.0 □□□□□□□□□□.

ST_GetFaceEdges, GetNodeEdges

9.7.11 GetNodeEdges

GetNodeEdges — .

Synopsis

```
getfaceedges returntype GetNodeEdges(varchar atopology, integer anode);
```

[illegible]

Note

[illegible]

2.0 □□□□□□□□□□.

图。

图。 **AddEdge** 图，图，图。

图，allowEdgeSplitting 图。

computeContainingFace 图。



Note

apoint 图，图 ID(nodeid) 图。

2.0.0 图。

图。

```
SELECT topology.AddNode('ma_topo', ST_GeomFromText('POINT(227641.6 893816.5)', 26986) ) As ↵
       nodeid;
-- result --
nodeid
-----
4
```

图。

AddEdge, CreateTopology

9.8.3 AddEdge

AddEdge — 图，图，图 (图) 图 ID(edgeid) 图。

Synopsis

integer **AddEdge**(varchar toponame, geometry aline);

图。

图 toponame 图，图 (图) 图 ID(edgeid) 图。图 “(universe)” 图。



Note

图 aline 图，图，图。

**Note**

aline 的 srid 与 ST_GeomFromText 的 srid 必须相同。否则将导致不可预料的结果。

GEOS 版本

**Warning**

AddEdge is deprecated as of 3.5.0. Use **TopoGeo_AddLineString** instead.

2.0.0 版本。

SQL

```
SELECT topology.AddEdge('ma_topo', ST_GeomFromText('LINESTRING(227575.8 893917.2,227591.9
893900.4)', 26986) ) As edgeid;
-- result-
edgeid
-----
1

SELECT topology.AddEdge('ma_topo', ST_GeomFromText('LINESTRING(227591.9 893900.4,227622.6
893844.2,227641.6 893816.5,
227704.5 893778.5)', 26986) ) As edgeid;
-- result --
edgeid
-----
2

SELECT topology.AddEdge('ma_topo', ST_GeomFromText('LINESTRING(227591.2 893900, 227591.9
893900.4,
227704.5 893778.5)', 26986) ) As edgeid;
-- gives error --
ERROR:  Edge intersects (not on endpoints) with existing edge 1
```

SQL

TopoGeo_AddLineString, **CreateTopology**, Section 4.5

9.8.4 AddFace

AddFace — 添加面 (face primitive) 到拓扑。

Synopsis

integer **AddFace**(varchar toponame, geometry apolygon, boolean force_new=false);

 (face primitive) .

left_face right_face containing_face



Note!

Note

```

edge next_left_edge next_right_edge

```

[illegible]

apolygon 0000000000000000, force_new 0 (0000) 0000000000 ID 0000
0, force_new 00000000000000 ID 00000000.



Note!

Note

XXXXXXXXXXXXXXXX (force_new = true) XXX, XX, XXXXXXXXXXXXXXXXXXXXXXXXXXXX
XXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXX. XXXXXXXXXXX MBR XXXXXXXXXXXXXXXXXXXX
XXXX. XXXXXXXXXXXXXXXXXXXX.



Note!

Note

apolygon [hex] srid [hex] srid [hex]. [hex]
[hex].

2.0.0 ☒☒☒☒☒☒☒☒☒☒☒.


```
-- first add the edges we use generate_series as an iterator (the below
-- will only work for polygons with < 10000 points because of our max in gs)
SELECT topology.AddEdge('ma_topo', ST_MakeLine(ST_PointN(geom,i), ST_PointN(geom, i + 1) )) ↵
    As edgeid
FROM (SELECT ST_NPoints(geom) AS npt, geom
      FROM
        (SELECT ST_Boundary(ST_GeomFromText('POLYGON((234896.5 899456.7,234914 ↵
          899436.4,234946.6 899356.9,234872.5 899328.7,
          234891 899285.4,234992.5 899145, 234890.6 899069,234755.2 899255.4,
          234612.7 899379.4,234776.9 899563.7,234896.5 899456.7)))', 26986) ) As geom
      ) As geoms) As facen CROSS JOIN generate_series(1,10000) As i
WHERE i < npt;

-- result --
edgeid
-----
3
4
5
6
7
8
```

```

9
10
11
12
(10 rows)
-- then add the face -

SELECT topology.AddFace('ma_topo',
    ST_GeomFromText('POLYGON((234896.5 899456.7,234914 899436.4,234946.6 899356.9,234872.5
    899328.7,
    234891 899285.4,234992.5 899145, 234890.6 899069,234755.2 899255.4,
    234612.7 899379.4,234776.9 899563.7,234896.5 899456.7)))', 26986) ) As faceid;
-- result --
faceid
-----
1
```



AddEdge, CreateTopology, Section 4.5

9.8.5 ST_Simplify

ST Simplify — ST_Simplify - ST_Simplify (Douglas-Peucker) ST_Simplify TopoGeometry ST_Simplify ST_Simplify ST_Simplify .

Synopsis

```
geometry ST_Simplify(TopoGeometry tg, float8 tolerance);
```



ϵ -Douglas-Peucker TopoGeometry " " "
".



Note

XXXXXXXXXXXXXXXXXXXX, XXXXXXXXXXXXXXXXXXXX.
 XXXX/XXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXX.

GEOS ☒ ☒ ☒ ☒ ☒

2.1.0 ☒☒☒☒☒☒☒☒☒☒☒.



☒☒ ST Simplify, ST IsSimple, ST IsValid, ST ModEdgeSplit

9.8.6 RemoveUnusedPrimitives

RemoveUnusedPrimitives — Removes topology primitives which not needed to define existing Topo-Geometry objects.

Synopsis

```
int RemoveUnusedPrimitives(text topology_name, geometry bbox);
```


Finds all primitives (nodes, edges, faces) that are not strictly needed to represent existing TopoGeometry objects and removes them, maintaining topology validity (edge linking, face labeling) and TopoGeometry space occupation.

No new primitive identifiers are created, but rather existing primitives are expanded to include merged faces (upon removing edges) or healed edges (upon removing nodes).


Availability: 3.3.0



ST ModEdgeHeal, ST RemEdgeModFace

9.9 TopoGeometry ☒☒☒

9.9.1 CreateTopoGeom

```
CreateTopoGeom — . tg_type  1: [], 2: [], 3: [], 4: .
```

Synopsis

```
topogeometry CreateTopoGeom(varchar toponame, integer tg_type, integer layer_id, topoelemen-
tarray tg_objs);
```

```
topogeometry CreateTopoGeom(varchar toponame, integer tg_type, integer layer id);
```



Creates a topogeometry object for layer denoted by `layer_id` and registers it in the relations table in the `toponame` schema.

`tg_type` is an integer: 1:[multi]point (punctal), 2:[multi]line (lineal), 3:[multi]poly (areal), 4:collection.
`layer_id` is the layer id in the topology.layer table.

□□□□□□□□□□□□□□□□, □□□□□□□□□□□□□□□□, □□□□□□□□□□□□□□
□□□, □□, □□□, □□□□□□□□□□□□□□□□□□□□□□.

TopoGeometry

Availability: 1.1

例: 创建拓扑几何

Create a topogeom in ri_topo schema for layer 2 (our ri_roads), of type (2) LINE, for the first edge (we loaded in ST_CreateTopoGeo).

```
INSERT INTO ri.ri_roads(road_name, topo) VALUES('Unknown', topology.CreateTopoGeom('ri_topo' ↵
',2,2,'{{1,2}}'::topology.topoelementarray);
```

例: 创建拓扑几何 **TopoGeometry** 列

创建拓扑几何列。将 blockgroups 表中的多边形转换为 TopoGeometry 列。将多边形与 faces 表中的 faces 表关联:

```
-- create our topo geometry column --
SELECT topology.AddTopoGeometryColumn(
    'topo_boston',
    'boston', 'blockgroups', 'topo', 'POLYGON');

-- addtopogeometrycolumn --
1

-- update our column assuming
-- everything is perfectly aligned with our edges
UPDATE boston.blockgroups AS bg
    SET topo = topology.CreateTopoGeom('topo_boston'
    ,3,1
    , foo.bfaces)
FROM (SELECT b.gid, topology.TopoElementArray_Agg(ARRAY[f.face_id,3]) As bfaces
    FROM boston.blockgroups As b
    INNER JOIN topo_boston.face As f ON b.geom && f.mbr
    WHERE ST_Covers(b.geom, topology.ST_GetFaceGeometry('topo_boston', f.face_id))
    GROUP BY b.gid) As foo
WHERE foo.gid = bg.gid;
```

```
--the world is rarely perfect allow for some error
--count the face if 50% of it falls
-- within what we think is our blockgroup boundary
UPDATE boston.blockgroups AS bg
    SET topo = topology.CreateTopoGeom('topo_boston'
    ,3,1
    , foo.bfaces)
FROM (SELECT b.gid, topology.TopoElementArray_Agg(ARRAY[f.face_id,3]) As bfaces
    FROM boston.blockgroups As b
    INNER JOIN topo_boston.face As f ON b.geom && f.mbr
    WHERE ST_Covers(b.geom, topology.ST_GetFaceGeometry('topo_boston', f.face_id))
    OR
    ( ST_Intersects(b.geom, topology.ST_GetFaceGeometry('topo_boston', f.face_id))
    AND ST_Area(ST_Intersection(b.geom, topology.ST_GetFaceGeometry('topo_boston', ↵
    f.face_id) ) ) >
    ST_Area(topology.ST_GetFaceGeometry('topo_boston', f.face_id))*0.5
    )
    GROUP BY b.gid) As foo
WHERE foo.gid = bg.gid;

-- and if we wanted to convert our topogeometry back
-- to a denormalized geometry aligned with our faces and edges
-- cast the topo to a geometry
-- The really cool thing is my new geometries
-- are now aligned with my tiger street centerlines
UPDATE boston.blockgroups SET new_geom = topo::geometry;
```

函数

`AddTopoGeometryColumn`, `toTopoGeom` `ST_CreateTopoGeo`, `ST_GetFaceGeometry`, `TopoElementArray`, `TopoElementArray_Agg`

9.9.2 toTopoGeom

`toTopoGeom` — Converts a simple Geometry into a topo geometry.

Synopsis

topogeometry **toTopoGeom**(geometry geom, varchar toponame, integer layer_id, float8 tolerance);
topogeometry **toTopoGeom**(geometry geom, topogeometry topogeom, float8 tolerance);

函数

函数返回 **TopoGeometry** 类型。

函数接受两个参数。第一个参数是 geometry 类型。第二个参数是 relation 类型的 TopoGeometry 类型。

函数 `TopoGeometry` (topogeom 类型) 返回 TopoGeometry 类型。

tolerance 参数指定了 TopoGeometry 的 tolerance 值。

参数 1 (toponame) 指定了 TopoGeometry 的 toponame。

参数 2 (layer_id) 指定了 TopoGeometry 的 layer_id。如果 layer_id 为 0，则使用 `clearTopoGeom` 函数清除 TopoGeometry。

2.0 版本支持。

版本: 2.1.0 版本支持 TopoGeometry 类型。

函数

函数 (workflow) 函数。

```
-- do this if you don't have a topology setup already
-- creates topology not allowing any tolerance
SELECT topology.CreateTopology('topo_boston_test', 2249);
-- create a new table
CREATE TABLE nei_topo(gid serial primary key, nei varchar(30));
--add a topogeometry column to it
SELECT topology.AddTopoGeometryColumn('topo_boston_test', 'public', 'nei_topo', 'topo', 'MULTIPOLYGON') As new_layer_id;
new_layer_id
-----
1

--use new layer id in populating the new topogeometry column
-- we add the topogeoms to the new layer with 0 tolerance
INSERT INTO nei_topo(nei, topo)
SELECT nei, topology.toTopoGeom(geom, 'topo_boston_test', 1)
FROM neighborhoods
WHERE gid BETWEEN 1 and 15;
```

```
--use to verify what has happened --
SELECT * FROM
    topology.TopologySummary('topo_boston_test');

-- summary--
Topology topo_boston_test (5), SRID 2249, precision 0
61 nodes, 87 edges, 35 faces, 15 topogeoms in 1 layers
Layer 1, type Polygonal (3), 15 topogeoms
Deploy: public.nei_topo.topo

-- Shrink all TopoGeometry polygons by 10 meters
UPDATE nei_topo SET topo = ST_Buffer(clearTopoGeom(topo), -10);

-- Get the no-one-lands left by the above operation
-- I think GRASS calls this "polygon0 layer"
SELECT ST_GetFaceGeometry('topo_boston_test', f.face_id)
FROM topo_boston_test.face f
WHERE f.face_id
> 0 -- don't consider the universe face
AND NOT EXISTS ( -- check that no TopoGeometry references the face
    SELECT * FROM topo_boston_test.relation
    WHERE layer_id = 1 AND element_id = f.face_id
);
```

☐☐

[CreateTopology](#), [AddTopoGeometryColumn](#), [CreateTopoGeom](#), [TopologySummary](#), [clearTopoGeom](#)

9.9.3 TopoElementArray_Agg

TopoElementArray_Agg — Returns a `topoelementarray` for a set of `element_id`, type arrays (`topoelements`).

Synopsis

`topoelementarray` **TopoElementArray_Agg**(`topoelement set tefield`);

☐☐

TopoElement ☐☐☐☐☐☐ **TopoElementArray** ☐☐☐☐☐☐☐☐☐☐.

2.0.0 ☐☐☐☐☐☐☐☐☐☐☐☐.

☐☐

```
SELECT topology.TopoElementArray_Agg(ARRAY[e,t]) As tea
FROM generate_series(1,3) As e CROSS JOIN generate_series(1,4) As t;
tea
-----
{{1,1},{1,2},{1,3},{1,4},{2,1},{2,2},{2,3},{2,4},{3,1},{3,2},{3,3},{3,4}}
```


TopoElement, TopoElementArray

9.9.4 TopoElement

TopoElement — Converts a topogeometry to a topoelement.

Synopsis

```
topoelement TopoElement(topogeometry topo);
```



Converts a **TopoGeometry** to a **TopoElement**.

Availability: 3.4.0



XXXXXXXXXXXXXXXXXXXXXXXX (workflow) XXXX.

```
-- do this if you don't have a topology setup already
```

```
-- Creates topology not allowing any tolerance
```

```
SELECT TopoElement(topo)
```

FROM neighborhoods;

```
-- using as cast
```

```
SELECT topology.TopoElementArray Agg(topo::topoelement)
```

FROM neighborhoods

GROUP BY city;

11

TopoElementArray Agg, TopoGeometry, TopoElement

9.10 TopoGeometry ☒☒☒

9.10.1 clearTopoGeom

`clearTopoGeom` — Clears the content of a topo geometry.

Synopsis

```
topogeometry clearTopoGeom(topogeometry topogeom);
```

图

TopoGeometry 是 **TopoGeometry** 的子类。 **toTopoGeom** 是 **TopoGeometry** 的函数。

2.1 图。

图

```
-- Shrink all TopoGeometry polygons by 10 meters
UPDATE nei_topo SET topo = ST_Buffer(clearTopoGeom(topo), -10);
```

图

toTopoGeom

9.10.2 TopoGeom_addElement

TopoGeom_addElement — Adds an element to the definition of a TopoGeometry.

Synopsis

topogeometry **TopoGeom_addElement**(topogeometry tg, topoelement el);

图

TopoGeometry 是 **TopoElement** 的子类。 是 **TopoGeometry** 的函数。

2.3 图。

图

```
-- Add edge 5 to TopoGeometry tg
UPDATE mylayer SET tg = TopoGeom_addElement(tg, '{5,2}');
```

图

TopoGeom_remElement, CreateTopoGeom

9.10.3 TopoGeom_remElement

TopoGeom_remElement — Removes an element from the definition of a TopoGeometry.

Synopsis

topogeometry **TopoGeom_remElement**(topogeometry tg, topoelement el);

函数

TopoGeometry 函数 **TopoElement** 函数。

2.3 函数。

函数

```
-- Remove face 43 from TopoGeometry tg
UPDATE mylayer SET tg = TopoGeom_remElement(tg, '{43,3}');
```

函数

TopoGeom_addElement, CreateTopoGeom

9.10.4 TopoGeom_addTopoGeom

TopoGeom_addTopoGeom — Adds element of a TopoGeometry to the definition of another TopoGeometry.

Synopsis

topogeometry **TopoGeom_addTopoGeom**(topogeometry tgt, topogeometry src);

函数

Adds the elements of a **TopoGeometry** to the definition of another TopoGeometry, possibly changing its cached type (type attribute) to a collection, if needed to hold all elements in the source object.

The two TopoGeometry objects need be defined against the *same* topology and, if hierarchically defined, need be composed by elements of the same child layer.

Availability: 3.2

函数

```
-- Set an "overall" TopoGeometry value to be composed by all
-- elements of specific TopoGeometry values
UPDATE mylayer SET tg_overall = TopoGeom_addTopogeom(
    TopoGeom_addTopoGeom(
        clearTopoGeom(tg_overall),
        tg_specific1
    ),
    tg_specific2
);
```

函数

TopoGeom_addElement, clearTopoGeom, CreateTopoGeom

9.10.5 toTopoGeom

`toTopoGeom` — Adds a geometry shape to an existing topo geometry.

Refer to `toTopoGeom`.

9.11 TopoGeometry ☒☒☒

9.11.1 GetTopoGeomElementArray

GetTopoGeomElementArray — Returns a `topoelementarray` (an array of `topoelements`) containing the topological elements and type of the given `TopoGeometry` (primitive elements).

Synopsis

```

topoelementarray GetTopoGeomElementArray(varchar toponame, integer layer_id, integer tg_id);
topoelementarray GetTopoGeomElementArray(topogeometry tg);

```



```

TopoGeometry (TopoElementArray).
GetTopoGeomElements

```

tg_id topology.layer layer_id TopoGeometry
 TopoGeometry ID.

Availability: 1.1



GetTopoGeomElements, TopoElementArray

9.11.2 GetTopoGeomElements

GetTopoGeomElements — Returns a set of `topoelement` objects containing the topological `element_id`, `element_type` and `element_data` of the given `TopoGeometry` (primitive elements).

Synopsis

```
setof topoelement GetTopoGeomElements(varchar toponame, integer layer_id, integer tg_id);
setof topoelement GetTopoGeomElements(topogeometry tg);
```

返回

Returns a set of `element_id,element_type` (topoelements) corresponding to primitive topology elements **TopoElement** (1: nodes, 2: edges, 3: faces) that a given topogeometry object in `toponame` schema is composed of.

`tg_id` 拓扑层 `layer_id` 拓扑层 ID `TopoGeometry` ID.

2.0.0 版本。

返回

返回

[GetTopoGeomElementArray](#), [TopoElement](#), [TopoGeom_addElement](#), [TopoGeom_remElement](#)

9.11.3 ST_SRID

ST_SRID — Returns the spatial reference identifier for a topogeometry.

Synopsis

integer **ST_SRID**(topogeometry tg);

返回

Returns the spatial reference identifier for the ST_Geometry as defined in `spatial_ref_sys` table. Section [4.5](#)



Note

`spatial_ref_sys` table is a table that catalogs all spatial reference systems known to PostGIS and is used for transformations from one spatial reference system to another. So verifying you have the right spatial reference system identifier is important if you plan to ever transform your geometries.

Availability: 3.2.0



This method implements the SQL/MM specification. SQL-MM 3: 14.1.5

返回

```
SELECT ST_SRID(ST_GeomFromText('POINT(-71.1043 42.315)',4326));
-- result
4326
```

返回

Section [4.5](#), [ST_SetSRID](#), [ST_Transform](#), [ST_SRID](#)

9.12 TopoGeometry ☒☒☒

9.12.1 AsGML

AsGML — TopoGeometry ☒ GML ☒☒☒☒☒☒☒☒☒.

Synopsis

```

text AsGML(topogeometry tg);
text AsGML(topogeometry tg, text nsprefix_in);
text AsGML(topogeometry tg, regclass visitedTable);
text AsGML(topogeometry tg, regclass visitedTable, text nsprefix);
text AsGML(topogeometry tg, text nsprefix_in, integer precision, integer options);
text AsGML(topogeometry tg, text nsprefix_in, integer precision, integer options, regclass visitedTable);
text AsGML(topogeometry tg, text nsprefix_in, integer precision, integer options, regclass visitedTable,
text idprefix);
text AsGML(topogeometry tg, text nsprefix_in, integer precision, integer options, regclass visitedTable,
text idprefix, int gmlversion);

```



TopoGeometry ☒ GML ☒ GML3 ☒ . nsprefix_in ☒ gml
☒ . nsprefix ☒ (non-qualified) ☒
☒ (15) ☒ (1) ☒ ST_AsGML ☒

```
visitedTable , , 
 (xlink:xref) . 'element type' 'element id' () 2 
. . ,
element type  element_id , , . 
  . :
```

```
CREATE TABLE visited (
    element_type integer, element_id integer,
    unique(element_type, element_id)
);
```

```
idprefix 00000000, 000000000000000000000000.
```

gm1ver 1.0.0, ST_AsGML 1.0.0. 3 2.0.0.




 CreateTopoGeom
 

```
SELECT topology.AsGML(topo) As rdgml
FROM ri.roads
WHERE road_name = 'Unknown';

-- rdgml--
<gml:TopoCurve>
  <gml:directedEdge>
    <gml:Edge gml:id="E1">
      <gml:directedNode orientation="-">
```

```

        <gml:Node gml:id="N1"/>
      </gml:directedNode>
    </gml:directedNode>
  </gml:directedNode>
  <gml:curveProperty>
    <gml:Curve srsName="urn:ogc:def:crs:EPSG::3438">
      <gml:segments>
        <gml:LineStringSegment>
          <gml:posList srsDimension="2"
>384744 236928 384750 236923 384769 236911 384799 236895 384811 236890
          384833 236884 384844 236882 384866 236881 384879 236883 384954 ↵
          236898 385087 236932 385117 236938
          385167 236938 385203 236941 385224 236946 385233 236950 385241 ↵
          236956 385254 236971
          385260 236979 385268 236999 385273 237018 385273 237037 385271 ↵
          237047 385267 237057 385225 237125
          385210 237144 385192 237161 385167 237192 385162 237202 385159 ↵
          237214 385159 237227 385162 237241
          385166 237256 385196 237324 385209 237345 385234 237375 385237 ↵
          237383 385238 237399 385236 237407
          385227 237419 385213 237430 385193 237439 385174 237451 385170 ↵
          237455 385169 237460 385171 237475
          385181 237503 385190 237521 385200 237533 385206 237538 385213 ↵
          237541 385221 237542 385235 237540 385242 237541
          385249 237544 385260 237555 385270 237570 385289 237584 385292 ↵
          237589 385291 237596 385284 237630</gml:posList>
        </gml:LineStringSegment>
      </gml:segments>
    </gml:Curve>
  </gml:curveProperty>
</gml:Edge>
</gml:directedEdge>
</gml:TopoCurve>

```

创建拓扑并生成 GML 数据。

```

SELECT topology.AsGML(topo,'') As rdgml
FROM ri.roads
WHERE road_name = 'Unknown';

-- rdgml--
<TopoCurve>
  <directedEdge>
    <Edge id="E1">
      <directedNode orientation="-">
        <Node id="N1"/>
      </directedNode>
      <directedNode
>384744 236928 384750 236923 384769 236911 384799 236895 384811 236890
      384833 236884 384844 236882 384866 236881 384879 236883 384954 ↵
      236898 385087 236932 385117 236938
      385167 236938 385203 236941 385224 236946 385233 236950 385241 ↵
      236956 385254 236971
      385260 236979 385268 236999 385273 237018 385273 237037 385271 ↵
      237047 385267 237057 385225 237125
      385210 237144 385192 237161 385167 237192 385162 237202 385159 ↵

```

```

                237214 385159 237227 385162 237241
385166 237256 385196 237324 385209 237345 385234 237375 385237 ←
                237383 385238 237399 385236 237407
385227 237419 385213 237430 385193 237439 385174 237451 385170 ←
                237455 385169 237460 385171 237475
385181 237503 385190 237521 385200 237533 385206 237538 385213 ←
                237541 385221 237542 385235 237540 385242 237541
385249 237544 385260 237555 385270 237570 385289 237584 385292 ←
                237589 385291 237596 385284 237630</posList>
        </LineStringSegment>
    </segments>
</Curve>
</curveProperty>
</Edge>
</directedEdge>
</TopoCurve>

```

☐☐

CreateTopoGeom, ST_CreateTopoGeo

9.12.2 AsTopoJSON

AsTopoJSON — TopoGeometry 转换为 TopoJSON 格式。

Synopsis

text **AsTopoJSON**(topogeometry tg, regclass edgeMapTable);

☐☐

TopoGeometry 转换为 TopoJSON 格式。edgeMapTable 为 NULL 时，将 TopoGeometry (arc) 转换为 TopoJSON (lookup/storage) 格式。compact 为 "true" 时，将 TopoGeometry 转换为 TopoJSON 格式。

当 compact 为 "true" 时，"serial" 为 "arc id" 或 "edge id" 时，将 TopoGeometry 转换为 TopoJSON 格式。当 "edge_id" 为 "edge id" 时，将 TopoGeometry 转换为 TopoJSON 格式。



Note

TopoJSON 格式为 0-1 格式，"edgeMapTable" 为 1-1 格式。

TopoJSON 格式，TopoJSON (snippet) 格式，TopoJSON (lookup/storage) 格式。TopoJSON 格式。

2.1.0 格式。

格式: 2.2.1 格式 (puntal) 格式。

☐☐

ST_AsGeoJSON

❏❏

```
CREATE TEMP TABLE edgemap(arc_id serial, edge_id int unique);

-- header
SELECT '{ "type": "Topology", "transform": { "scale": [1,1], "translate": [0,0] }, "objects" ←
      ": {'

-- objects
UNION ALL SELECT '' || feature_name || ': ' || AsTopoJSON(feature, 'edgemap')
FROM features.big_parcel WHERE feature_name = 'P3P4';

-- arcs
WITH edges AS (
  SELECT m.arc_id, e.geom FROM edgemap m, city_data.edge e
  WHERE e.edge_id = m.edge_id
), points AS (
  SELECT arc_id, (st_dumppoints(geom)).* FROM edges
), compare AS (
  SELECT p2.arc_id,
         CASE WHEN p1.path IS NULL THEN p2.geom
              ELSE ST_Translate(p2.geom, -ST_X(p1.geom), -ST_Y(p1.geom))
         END AS geom
  FROM points p2 LEFT OUTER JOIN points p1
  ON ( p1.arc_id = p2.arc_id AND p2.path[1] = p1.path[1]+1 )
  ORDER BY arc_id, p2.path
), arcsdump AS (
  SELECT arc_id, (regexp_matches( ST_AsGeoJSON(geom), '\[.*\]'))[1] as t
  FROM compare
), arcs AS (
  SELECT arc_id, '[' || array_to_string(array_agg(t), ',') || ']' as a FROM arcsdump
  GROUP BY arc_id
  ORDER BY arc_id
)
SELECT '}', "arcs": [' UNION ALL
SELECT array_to_string(array_agg(a), E',\n') from arcs

-- footer
UNION ALL SELECT '}]':::text as t;

-- Result:
{ "type": "Topology", "transform": { "scale": [1,1], "translate": [0,0] }, "objects": {
"P3P4": { "type": "MultiPolygon", "arcs": [[[ -1]], [[6,5,-5,-4,-3,1]]] }
}, "arcs": [
[[25,30],[6,0],[0,10],[-14,0],[0,-10],[8,0]],
[[35,6],[0,8]],
[[35,6],[12,0]],
[[47,6],[0,8]],
[[47,14],[0,8]],
[[35,22],[12,0]],
[[35,14],[0,8]]
]]}
```

9.13 创建拓扑

9.13.1 Equals

Equals — 检查 TopoGeometry 是否相等。

Synopsis

boolean **Equals**(topogeometry tg1, topogeometry tg2);

几何类型

几何 TopoGeometry 函数 (几何, 几何, 几何) 返回布尔值。

**Note**

几何 TopoGeometry 函数。几何 TopoGeometry 函数。

1.1.0 版本。

 This function supports 3d and will not drop the z-index.

几何

几何

[GetTopoGeomElements](#), [ST_Equals](#)

9.13.2 Intersects

Intersects — 几何 TopoGeometry 函数。

Synopsis

boolean **Intersects**(topogeometry tg1, topogeometry tg2);

几何

几何 TopoGeometry 函数。

**Note**

This function not supported for topogeometries that are geometry collections. It also can not compare topogeometries from different topologies. Also not currently supported for hierarchical topogeometries (topogeometries composed of other topogeometries).

1.1.0 版本。

 This function supports 3d and will not drop the z-index.

☒☒

☒☒

ST_Intersects

9.14 Importing and exporting Topologies

Once you have created topologies, and maybe associated topological layers, you might want to export them into a file-based format for backup or transfer into another database.

Using the standard dump/restore tools of PostgreSQL is problematic because topologies are composed by a set of tables (4 for primitives, an arbitrary number for layers) and records in metadata tables (topology.topology and topology.layer). Additionally, topology identifiers are not univoque across databases so that parameter of your topology will need to be changes upon restoring it.

In order to simplify export/restore of topologies a pair of executables are provided: `pgtopo_export` and `pgtopo_import`. Example usage:

```
pgtopo_export dev_db topo1 | pgtopo_import topo1 | psql staging_db
```

9.14.1 Using the Topology exporter

The `pgtopo_export` script takes the name of a database and a topology and outputs a dump file which can be used to import the topology (and associated layers) into a new database.

By default `pgtopo_export` writes the dump file to the standard output so that it can be piped to `pgtopo_import` or redirected to a file (refusing to write to terminal). You can optionally specify an output filename with the `-f` commandline switch.

By default `pgtopo_export` includes a dump of all layers defined against the given topology. This may be more data than you need, or may be non-working (in case your layer tables have complex dependencies) in which case you can request skipping the layers with the `--skip-layers` switch and deal with those separately.

Invoking `pgtopo_export` with the `--help` (or `-h` for short) switch will always print short usage string.

The dump file format is a compressed tar archive of a `pgtopo_export` directory containing at least a `pgtopo_dump_version` file with format version info. As of version 1 the directory contains tab-delimited CSV files with data of the topology primitive tables (node, edge_data, face, relation), the topology and layer records associated with it and (unless `--skip-layers` is given) a custom-format PostgreSQL dump of tables reported as being layers of the given topology.

9.14.2 Using the Topology importer

The `pgtopo_import` script takes a `pgtopo_export` format topology dump and a name to give to the topology to be created and outputs an SQL script reconstructing the topology and associated layers.

The generated SQL file will contain statements that create a topology with the given name, load primitive data in it, restores and registers all topology layers by properly linking all TopoGeometry values to their correct topology.

By default `pgtopo_import` reads the dump from the standard input so that it can be used in conjunction with `pgtopo_export` in a pipeline. You can optionally specify an input filename with the `-f` commandline switch.

By default `pgtopo_import` includes in the output SQL file the code to restore all layers found in the dump.

This may be unwanted or non-working in case your target database already have tables with the same name as the ones in the dump. In that case you can request skipping the layers with the `--skip-layers` switch and deal with those separately (or later).

SQL to only load and link layers to a named topology can be generated using the `--only-layers` switch. This can be useful to load layers AFTER resolving the naming conflicts or to link layers to a different topology (say a spatially-simplified version of the starting topology).

Chapter 10

栅格数据, 栅格索引

10.1 栅格数据

栅格数据, 栅格索引 raster2pgsql 是 PostGIS 的一个扩展, 用于加载栅格数据。

10.1.1 raster2pgsql 使用

The raster2pgsql is a raster loader executable that loads GDAL supported raster formats into SQL suitable for loading into a PostGIS raster table. It is capable of loading folders of raster files as well as creating overviews of rasters.

Since the raster2pgsql is compiled as part of PostGIS most often (unless you compile your own GDAL library), the raster types supported by the executable will be the same as those compiled in the GDAL dependency library. To get a list of raster types your particular raster2pgsql supports use the -G switch.



Note

栅格数据 (factor) 栅格数据, 栅格索引。 <http://trac.osgeo.org/postgis/ticket/1764> 栅格数据。

10.1.1.1 Example Usage

栅格数据 100x100 栅格数据:

```
# -s use srid 4326
# -I create spatial index
# -C use standard raster constraints
# -M vacuum analyze after load
# *.tif load all these files
# -F include a filename column in the raster table
# -t tile the output 100x100
# public.demelevation load into this table
raster2pgsql -s 4326 -I -C -M -F -t 100x100 *.tif public.demelevation
> elev.sql

# -d connect to this database
# -f read this file after connecting
psql -d gisdb -f elev.sql
```

**Note**

If you do not specify the schema as part of the target table name, the table will be created in the default schema of the database or user you are connecting with.

UNIX 安装与使用指南:

```
raster2pgsql -s 4326 -I -C -M *.tif -F -t 100x100 public.demelevation | psql -d gisdb
```

安装与使用指南: `aerial` 安装与使用指南, 安装 2 到 4 个
安装与使用指南, 安装与使用指南 (安装与使用指南 DB 安装) 安装, 安装与使用指南
安装与使用指南 -e 安装与使用指南 (安装与使用指南安装与使用指南安装与使用指南
安装与使用指南). 安装 128x128 安装与使用指南安装与使用指南安装与使用指南. 安装与使用指南
安装与使用指南. 安装与使用指南安装与使用指南安装与使用指南 -F 安装与使用指南 "filename" 安装与使用指南
安装与使用指南.

```
raster2pgsql -I -C -e -Y -F -s 26986 -t 128x128 -l 2,4 bostonaerials2008/*.jpg aerals. ↵  
boston | psql -U postgres -d gisdb -h localhost -p 5432
```

--get a list of raster types supported:

```
raster2pgsql -G
```

-G 安装与使用指南:

Available GDAL raster formats:

```
Virtual Raster
GeoTIFF
National Imagery Transmission Format
Raster Product Format TOC format
ECRG TOC format
Erdas Imagine Images (.img)
CEOS SAR Image
CEOS Image
...
Arc/Info Export E00 GRID
ZMap Plus Grid
NOAA NGS Geoid Height Grids
```

10.1.1.2 raster2pgsql options

-? 安装与使用指南. 安装与使用指南.

-G 安装与使用指南.

c|a|d|p -- 安装与使用指南:

-c 安装与使用指南 (安装与使用指南) 安装与使用指南. 安装与使用指南.

-a 安装与使用指南 (安装与使用指南) 安装与使用指南.

-d 安装与使用指南, 安装与使用指南 (安装与使用指南) 安装与使用指南.

-p 安装与使用指南, 安装与使用指南.

安装与使用指南: 安装与使用指南

-C raster_columns 安装与使用指南 SRID, 安装与使用指南
安装与使用指南.

- x **extent** (extent) 指定栅格数据的范围。-C 指定栅格数据的坐标系。
- r **regular blocking** (regular blocking) 指定栅格数据的分块方式 (正则分块)。-C 指定栅格数据的坐标系。

选项说明: 指定栅格数据的范围、坐标系、分块方式、坐标系、分块方式。

- s **<SRID>** 指定栅格数据的 SRID 值。如果为 0，则使用 SRID 值。指定栅格数据的坐标系。
- b **BAND** 指定栅格数据的波段 (1-255)。指定栅格数据的波段。指定栅格数据的波段。
- t **TILE_SIZE** 指定栅格数据的分块大小。TILE_SIZE 指定栅格数据的分块大小。指定栅格数据的分块大小。
- P 指定栅格数据的分块大小 (padding) 指定栅格数据的分块大小。
- R, --register 指定栅格数据的注册 (DB 注册) 指定栅格数据的注册。
- l **OVERVIEW_FACTOR** 指定栅格数据的概览因子。指定栅格数据的概览因子。指定栅格数据的概览因子。
- N **NODATA** "NODATA" 指定栅格数据的 NODATA 值。

选项说明: 指定栅格数据的注册、概览因子、NODATA 值。

- f **COLUMN** 指定栅格数据的列名。指定栅格数据的列名。
- F 指定栅格数据的列名。
- n **COLUMN** 指定栅格数据的列名。-F 指定栅格数据的列名。
- q PostgreSQL 指定栅格数据的列名。
- I 指定栅格数据的 GiST 索引。
- M 指定栅格数据的 (vacuum analyze) 操作。
- k Keeps empty tiles and skips NODATA value checks for each raster band. Note you save time in checking, but could end up with far more junk rows in your database and those junk rows are not marked as empty tiles.
- T **tablespace** 指定栅格数据的表空间。-X 指定栅格数据的表空间 (指定栅格数据的表空间)。
- X **tablespace** 指定栅格数据的表空间。-I 指定栅格数据的表空间 (指定栅格数据的表空间)。
- Y **max_rows_per_copy=50** Use copy statements instead of insert statements. Optionally specify max_rows_per_copy; default 50 when not specified.
- e 指定栅格数据的表空间, 指定栅格数据的表空间 (transaction) 指定栅格数据的表空间。
- E **ENDIAN** 指定栅格数据的端序 (endianness) 指定栅格数据的端序。XDR 为 0, 指定栅格数据的端序。NDR 为 1 指定栅格数据的端序。指定栅格数据的端序。
- V **version** 指定栅格数据的版本。指定栅格数据的版本。指定栅格数据的版本。

10.1.2 PostGIS 安装与使用

指定栅格数据的表空间、端序、版本。指定栅格数据的表空间、端序、版本。指定栅格数据的表空间、端序、版本。

1. 创建表 myrasters:

```
CREATE TABLE myrasters(rid serial primary key, rast raster);
```

2. 创建表 myrasters 的索引。使用 `ST_MakeEmptyRaster` 和 `ST_AddBand` 函数。

使用 `ST_AsRaster` 函数，使用 `ST_Union` 和 `ST_MapAlgebra` 函数 (algebra) 函数。

使用 `ST_Transform` 函数。

3. 创建索引 myrasters_rast_st_convexhull_idx:

```
CREATE INDEX myrasters_rast_st_convexhull_idx ON myrasters USING gist( ST_ConvexHull( ← rast) );
```

使用 `ST_ConvexHull` 函数 (convex hull) 函数。



Note

PostGIS 2.0 使用 `ST_Envelope` 函数 (envelop) 函数。

4. `AddRasterConstraints` 函数。

10.1.3 Using "out db" cloud rasters

The `raster2pgsql` tool uses GDAL to access raster data, and can take advantage of a key GDAL feature: the ability to read from rasters that are **stored remotely** in cloud "object stores" (e.g. AWS S3, Google Cloud Storage).

Efficient use of cloud stored rasters requires the use of a "cloud optimized" format. The most well-known and widely used is the **"cloud optimized GeoTIFF"** format. Using a non-cloud format, like a JPEG, or an un-tiled TIFF will result in very poor performance, as the system will have to download the entire raster each time it needs to access a subset.

First, load your raster into the cloud storage of your choice. Once it is loaded, you will have a URI to access it with, either an "http" URI, or sometimes a URI specific to the service. (e.g., "s3://bucket/object"). To access non-public buckets, you will need to supply GDAL config options to authenticate your connection. Note that this command is *reading* from the cloud raster and *writing* to the database.

```
AWS_ACCESS_KEY_ID=xxxxxxxxxxxxxxxxxxxxx \
AWS_SECRET_ACCESS_KEY=xxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxx \
raster2pgsql \
-s 990000 \
-t 256x256 \
-I \
-R \
/vsis3/your.bucket.com/your_file.tif \
your_table \
| psql your_db
```

Once the table is loaded, you need to give the database permission to read from remote rasters, by setting two permissions, `postgis.enable_outdb_rasters` and `postgis.gdal_enabled_drivers`.

```
SET postgis.enable_outdb_rasters = true;
SET postgis.gdal_enabled_drivers TO 'ENABLE_ALL';
```

To make the changes sticky, set them directly on your database. You will need to re-connect to experience the new settings.

```
ALTER DATABASE your_db SET postgis.enable_outdb_rasters = true;
ALTER DATABASE your_db SET postgis.gdal_enabled_drivers TO 'ENABLE_ALL';
```

For non-public rasters, you may have to provide access keys to read from the cloud rasters. The same keys you used to write the `raster2pgsql` call can be set for use inside the database, with the `postgis.gdal_vsi_options` configuration. Note that multiple options can be set by space-separating the key=value pairs.

```
SET postgis.gdal_vsi_options = 'AWS_ACCESS_KEY_ID=xxxxxxxxxxxxxxxxxxxxx
AWS_SECRET_ACCESS_KEY=xxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxx';
```

Once you have the data loaded and permissions set you can interact with the raster table like any other raster table, using the same functions. The database will handle all the mechanics of connecting to the cloud data when it needs to read pixel data.

10.2 使用云数据

PostGIS 支持使用云数据。使用云数据时，您需要提供访问密钥。这些密钥用于写入 `raster2pgsql` 调用，也可以设置在数据库内部，使用 `postgis.gdal_vsi_options` 配置。注意，多个选项可以通过空格分隔的 key=value 对来设置。

1. `raster_columns` 表用于存储云数据的元数据。
2. `raster_overviews` 表用于存储云数据的概图。使用 `-l` 选项可以生成概图。

10.2.1 使用云数据

`raster_columns` 表用于存储云数据的元数据。该表包含以下列：
`raster_id`：云数据的唯一标识符。
`table_name`：存储数据的表名。
`column_name`：存储数据的列名。
`srid`：空间参考标识符。
`scale_x`：X轴的比例尺。
`scale_y`：Y轴的比例尺。

使用 `-c` 选项可以生成概图。使用 `raster_columns` 表时，需要添加 `AddRasterConstraints` 约束。

- `r_table_catalog`：存储数据的目录名。
- `r_table_schema`：存储数据的模式名。
- `r_table_name`：存储数据的表名。
- `r_raster_column`：存储数据的列名。PostGIS 使用 `raster_columns` 表来管理云数据。
- `srid`：空间参考标识符。Section 4.5 介绍了如何设置。
- `scale_x`：X轴的比例尺。使用 `scale_x` 和 `scale_y` 来设置。使用 `ST_ScaleX` 函数。

- `scale_y` 縦方向のスケール (倍率) を指定。デフォルトは `scale_y` が `scale_y` の場合、`scale_y` が `ST_ScaleY` の場合。
- `blocksize_x` 横方向のブロックサイズ (単位: 画素) を指定。デフォルトは `ST_Width` の値。
- `blocksize_y` 縦方向のブロックサイズ (単位: 画素) を指定。デフォルトは `ST_Height` の値。
- `same_alignment` 入力データと出力データのアライメントが同じかどうかを指定。デフォルトは `ST_SameAlignment` の値。
- `regular_blocking` 規則的なブロック処理を行うかどうかを指定。デフォルトは `regular_blocking` の値。
- `num_bands` 出力データのバンド数を指定。デフォルトは `ST_NumBands` の値。
- `pixel_types` 出力データのピクセルタイプを指定。デフォルトは `ST_BandPixelType` の値。
- `nodata_values` `nodata_value` (double precision) の値 (数) を指定。デフォルトは `ST_BandNoDataValue` の値。
- `out_db` 出力データのデータベース名を指定。デフォルトは `out_db` の値。
- `extent` 出力データの範囲 (extent) を指定。デフォルトは `DropRasterConstraints` の値。
- `spatial index` 空間インデックスを指定。

10.2.2 ☐ ☐ ☐ ☐ ☐ ☐

```
raster_overviews --raster_columns raster_overviews --l -l AddOverviewConstraints
```

☐.



Note

```
raster_overviews || raster_columns || '. raster_columns  
|| raster_overviews || raster_columns ||  
(join) ||
```

[illegible]

- XXXXXXXXXXXXXXXXXXXXX.
- XXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXX.
XXXXXXXXXXXXXXXXXXXXX.
(rule-of-thumb) XXXXXXXXXXXXXXXXXXXX.

raster overviews .

- `o_table_catalog` 表所在数据库名称。
- `o_table_schema` 表所在模式名称。
- `o_table_name` 表名称。
- `o_raster_column` 栅格列名称。
- `r_table_catalog` 表所在数据库名称。
- `r_table_schema` 表所在模式名称。
- `r_table_name` 表名称。
- `r_raster_column` 栅格列名称。
- `overview_factor` 概览因子。该因子决定了在生成概览图时，原始栅格的分辨率被放大的倍数。例如，如果原始栅格的分辨率为 1 米，那么因子为 2 的概览图的分辨率就是 2 米。因子为 4 的概览图的分辨率就是 4 米。因子为 125 的概览图的分辨率就是 125 米。因子为 5000 的概览图的分辨率就是 5000 米。因子为 1600 的概览图的分辨率就是 1600 米。因子为 400 的概览图的分辨率就是 400 米。因子为 200 的概览图的分辨率就是 200 米。因子为 100 的概览图的分辨率就是 100 米。因子为 50 的概览图的分辨率就是 50 米。因子为 25 的概览图的分辨率就是 25 米。因子为 12.5 的概览图的分辨率就是 12.5 米。因子为 6.25 的概览图的分辨率就是 6.25 米。因子为 3.125 的概览图的分辨率就是 3.125 米。因子为 1.5625 的概览图的分辨率就是 1.5625 米。因子为 0.78125 的概览图的分辨率就是 0.78125 米。因子为 0.390625 的概览图的分辨率就是 0.390625 米。因子为 0.1953125 的概览图的分辨率就是 0.1953125 米。因子为 0.09765625 的概览图的分辨率就是 0.09765625 米。因子为 0.048828125 的概览图的分辨率就是 0.048828125 米。因子为 0.0244140625 的概览图的分辨率就是 0.0244140625 米。因子为 0.01220703125 的概览图的分辨率就是 0.01220703125 米。因子为 0.006103515625 的概览图的分辨率就是 0.006103515625 米。因子为 0.0030517578125 的概览图的分辨率就是 0.0030517578125 米。因子为 0.00152587890625 的概览图的分辨率就是 0.00152587890625 米。因子为 0.000762939453125 的概览图的分辨率就是 0.000762939453125 米。因子为 0.0003814697265625 的概览图的分辨率就是 0.0003814697265625 米。因子为 0.00019073486328125 的概览图的分辨率就是 0.00019073486328125 米。因子为 9.5367431640625e-05 的概览图的分辨率就是 9.5367431640625e-05 米。因子为 4.76837158203125e-05 的概览图的分辨率就是 4.76837158203125e-05 米。因子为 2.384185791015625e-05 的概览图的分辨率就是 2.384185791015625e-05 米。因子为 1.1920928955078125e-05 的概览图的分辨率就是 1.1920928955078125e-05 米。因子为 5.9604644775390625e-06 的概览图的分辨率就是 5.9604644775390625e-06 米。因子为 2.98023223876953125e-06 的概览图的分辨率就是 2.98023223876953125e-06 米。因子为 1.490116119384765625e-06 的概览图的分辨率就是 1.490116119384765625e-06 米。因子为 7.450580596923828125e-07 的概览图的分辨率就是 7.450580596923828125e-07 米。因子为 3.7252902984619140625e-07 的概览图的分辨率就是 3.7252902984619140625e-07 米。因子为 1.86264514923095703125e-07 的概览图的分辨率就是 1.86264514923095703125e-07 米。因子为 9.31322574615478515625e-08 的概览图的分辨率就是 9.31322574615478515625e-08 米。因子为 4.656612873077392578125e-08 的概览图的分辨率就是 4.656612873077392578125e-08 米。因子为 2.3283064365386962890625e-08 的概览图的分辨率就是 2.3283064365386962890625e-08 米。因子为 1.16415321826934814453125e-08 的概览图的分辨率就是 1.16415321826934814453125e-08 米。因子为 5.82076609134674072265625e-09 的概览图的分辨率就是 5.82076609134674072265625e-09 米。因子为 2.910383045673370361328125e-09 的概览图的分辨率就是 2.910383045673370361328125e-09 米。因子为 1.4551915228366851806640625e-09 的概览图的分辨率就是 1.4551915228366851806640625e-09 米。因子为 7.2759576141834259033203125e-10 的概览图的分辨率就是 7.2759576141834259033203125e-10 米。因子为 3.63797880709171295166015625e-10 的概览图的分辨率就是 3.63797880709171295166015625e-10 米。因子为 1.818989403545856475830078125e-10 的概览图的分辨率就是 1.818989403545856475830078125e-10 米。因子为 9.094947017729282379150390625e-11 的概览图的分辨率就是 9.094947017729282379150390625e-11 米。因子为 4.5474735088646411895751953125e-11 的概览图的分辨率就是 4.5474735088646411895751953125e-11 米。因子为 2.27373675443232059478759765625e-11 的概览图的分辨率就是 2.27373675443232059478759765625e-11 米。因子为 1.136868377216160297393798828125e-11 的概览图的分辨率就是 1.136868377216160297393798828125e-11 米。因子为 5.684341886080801486968994140625e-12 的概览图的分辨率就是 5.684341886080801486968994140625e-12 米。因子为 2.8421709430404007434844970703125e-12 的概览图的分辨率就是 2.8421709430404007434844970703125e-12 米。因子为 1.42108547152020037174224853515625e-12 的概览图的分辨率就是 1.42108547152020037174224853515625e-12 米。因子为 7.10542735760100185871124267578125e-13 的概览图的分辨率就是 7.10542735760100185871124267578125e-13 米。因子为 3.552713678800500929355621337890625e-13 的概览图的分辨率就是 3.552713678800500929355621337890625e-13 米。因子为 1.7763568394002504646778106689453125e-13 的概览图的分辨率就是 1.7763568394002504646778106689453125e-13 米。因子为 8.8817841970012523233890533447265625e-14 的概览图的分辨率就是 8.8817841970012523233890533447265625e-14 米。因子为 4.44089209850062616169452667236328125e-14 的概览图的分辨率就是 4.44089209850062616169452667236328125e-14 米。因子为 2.220446049250313080847263336181640625e-14 的概览图的分辨率就是 2.220446049250313080847263336181640625e-14 米。因子为 1.1102230246251565404236316680908203125e-14 的概览图的分辨率就是 1.1102230246251565404236316680908203125e-14 米。因子为 5.5511151231257827021181583340541015625e-15 的概览图的分辨率就是 5.5511151231257827021181583340541015625e-15 米。因子为 2.77555756156289135105907916702705078125e-15 的概览图的分辨率就是 2.77555756156289135105907916702705078125e-15 米。因子为 1.387778780781445675529539583513525390625e-15 的概览图的分辨率就是 1.387778780781445675529539583513525390625e-15 米。因子为 6.938893903907228377647697917567626953125e-16 的概览图的分辨率就是 6.938893903907228377647697917567626953125e-16 米。因子为 3.4694469519536141888238489587838134765625e-16 的概览图的分辨率就是 3.4694469519536141888238489587838134765625e-16 米。因子为 1.73472347597680709441192447939190673828125e-16 的概览图的分辨率就是 1.73472347597680709441192447939190673828125e-16 米。因子为 8.67361737988403547205962239695953369140625e-17 的概览图的分辨率就是 8.67361737988403547205962239695953369140625e-17 米。因子为 4.336808689942017736029811198479766845703125e-17 的概览图的分辨率就是 4.336808689942017736029811198479766845703125e-17 米。因子为 2.1684043449710088680149055992398834228515625e-17 的概览图的分辨率就是 2.1684043449710088680149055992398834228515625e-17 米。因子为 1.08420217248550443400745279961994171142578125e-17 的概览图的分辨率就是 1.08420217248550443400745279961994171142578125e-17 米。因子为 5.42101086242752217003726399809970855712890625e-18 的概览图的分辨率就是 5.42101086242752217003726399809970855712890625e-18 米。因子为 2.710505431213761085018631999049854278564453125e-18 的概览图的分辨率就是 2.710505431213761085018631999049854278564453125e-18 米。因子为 1.3552527156068805425093159995249271392822265625e-18 的概览图的分辨率就是 1.3552527156068805425093159995249271392822265625e-18 米。因子为 6.7762635780344027125465799976246356964111328125e-19 的概览图的分辨率就是 6.7762635780344027125465799976246356964111328125e-19 米。因子为 3.38813178901720135627328999881231784820556640625e-19 的概览图的分辨率就是 3.38813178901720135627328999881231784820556640625e-19 米。因子为 1.694065894508600678136644999406158924102783203125e-19 的概览图的分辨率就是 1.694065894508600678136644999406158924102783203125e-19 米。因子为 8.470329472543003390683224997030794620513916015625e-20 的概览图的分辨率就是 8.470329472543003390683224997030794620513916015625e-20 米。因子为 4.2351647362715016953416124985153973102569580078125e-20 的概览图的分辨率就是 4.2351647362715016953416124985153973102569580078125e-20 米。因子为 2.11758236813575084767080624925769865512847900390625e-20 的概览图的分辨率就是 2.11758236813575084767080624925769865512847900390625e-20 米。因子为 1.058791184067875423835403124628849327564239501953125e-20 的概览图的分辨率就是 1.058791184067875423835403124628849327564239501953125e-20 米。因子为 5.293955920339377119177015623144246637821197509765625e-21 的概览图的分辨率就是 5.293955920339377119177015623144246637821197509765625e-21 米。因子为 2.6469779601696885595885078115721233189105987548828125e-21 的概览图的分辨率就是 2.6469779601696885595885078115721233189105987548828125e-21 米。因子为 1.32348898008484427979425390578606165945529937744140625e-21 的概览图的分辨率就是 1.32348898008484427979425390578606165945529937744140625e-21 米。因子为 6.61744490042422139897126952893030829727649688720703125e-22 的概览图的分辨率就是 6.61744490042422139897126952893030829727649688720703125e-22 米。因子为 3.308722450212110699485634764465154148638248443603515625e-22 的概览图的分辨率就是 3.308722450212110699485634764465154148638248443603515625e-22 米。因子为 1.6543612251060553497428173822325770743191242218017578125e-22 的概览图的分辨率就是 1.6543612251060553497428173822325770743191242218017578125e-22 米。因子为 8.2718061255302767487140869111628853715956211090087890625e-23 的概览图的分辨率就是 8.2718061255302767487140869111628853715956211090087890625e-23 米。因子为 4.13590306276513837435704345558144268579781055450439453125e-23 的概览图的分辨率就是 4.13590306276513837435704345558144268579781055450439453125e-23 米。因子为 2.067951531382569187178521727790721342898905277252197265625e-23 的概览图的分辨率就是 2.067951531382569187178521727790721342898905277252197265625e-23 米。因子为 1.0339757656912845935892608638953606714494526386260986328125e-23 的概览图的分辨率就是 1.0339757656912845935892608638953606714494526386260986328125e-23 米。因子为 5.1698788284564229679463043169768033572247631931304931640625e-24 的概览图的分辨率就是 5.1698788284564229679463043169768033572247631931304931640625e-24 米。因子为 2.58493941422821148397315215848840167861238159656524658203125e-24 的概览图的分辨率就是 2.58493941422821148397315215848840167861238159656524658203125e-24 米。因子为 1.292469707114105741986576079244200839306190798282623291015625e-24 的概览图的分辨率就是 1.292469707114105741986576079244200839306190798282623291015625e-24 米。因子为 6.462348535570528709932880396221004196530953991413116455078125e-25 的概览图的分辨率就是 6.462348535570528709932880396221004196530953991413116455078125e-25 米。因子为 3.2311742677852643549664401981105020982654769957065582275390625e-25 的概览图的分辨率就是 3.2311742677852643549664401981105020982654769957065582275390625e-25 米。因子为 1.61558713389263217748322009905525104913273849785327911376953125e-25 的概览图的分辨率就是 1.61558713389263217748322009905525104913273849785327911376953125e-25 米。因子为 8.07793566946316088741610049527625524566369248926639556884765625e-26 的概览图的分辨率就是 8.07793566946316088741610049527625524566369248926639556884765625e-26 米。因子为 4.038967834731580443708050247638127622831846244633197784423828125e-26 的概览图的分辨率就是 4.038967834731580443708050247638127622831846244633197784423828125e-26 米。因子为 2.0194839173657902218540251238190638114159231223165988922119140625e-26 的概览图的分辨率就是 2.0194839173657902218540251238190638114159231223165988922119140625e-26 米。因子为 1.00974195868289511092701256190953190570796156115829944610595703125e-26 的概览图的分辨率就是 1.00974195868289511092701256190953190570796156115829944610595703125e-26 米。因子为 5.0487097934144755546350628095476595285398078057914972305297875e-27 的概览图的分辨率就是 5.0487097934144755546350628095476595285398078057914972305297875e-27 米。因子为 2.52435489670723777731753140477382976426990390289574861526489375e-27 的概览图的分辨率就是 2.52435489670723777731753140477382976426990390289574861526489375e-27 米。因子为 1.262177448353618888658765702386914882134951951447874307632446875e-27 的概览图的分辨率就是 1.262177448353618888658765702386914882134951951447874307632446875e-27 米。因子为 6.310887241768094443293828511934574410674759757239371538162234375e-28 的概览图的分辨率就是 6.310887241768094443293828511934574410674759757239371538162234375e-28 米。因子为 3.1554436208840472216469142559672872053373798786196857690811171875e-28 的概览图的分辨率就是 3.1554436208840472216469142559672872053373798786196857690811171875e-28 米。因子为 1.57772181044202361082345712798364360266868993930984288454055859375e-28 的概览图的分辨率就是 1.57772181044202361082345712798364360266868993930984288454055859375e-28 米。因子为 7.88860905221011805411728563991821801334344969654921442270279296875e-29 的概览图的分辨率就是 7.88860905221011805411728563991821801334344969654921442270279296875e-29 米。因子为 3.944304526105059027058642819959109006671724848274607211351396484375e-29 的概览图的分辨率就是 3.944304526105059027058642819959109006671724848274607211351396484375e-29 米。因子为 1.9721522630525295135293214099795545033358624241373036056756982421875e-29 的概览图的分辨率就是 1.9721522630525295135293214099795545033358624241373036056756982421875e-29 米。因子为 9.8607613152626475676466070498977725166793121206865180283784912109375e-30 的概览图的分辨率就是 9.8607613152626475676466070498977725166793121206865180283784912109375e-30 米。因子为 4.93038065763132378382330352494888625833965606034325901418924560546875e-30 的概览图的分辨率就是 4.93038065763132378382330352494888625833965606034325901418924560546875e-30 米。因子为 2.465190328815661891911651762474443129169828030171629507094622802734375e-30 的概览图的分辨率就是 2.465190328815661891911651762474443129169828030171629507094622802734375e-30 米。因子为 1.2325951644078309459558258812372215645849140150858147535473114013671875e-30 的概览图的分辨率就是 1.2325951644078309459558258812372215645849140150858147535473114013671875e-30 米。因子为 6.1629758220391547297791279061861078229245700754290737677365570068359375e-31 的概览图的分辨率就是 6.1629758220391547297791279061861078229245700754290737677365570068359375e-31 米。因子为 3.08148791101957736488956395309305391146228503771453688386827850341796875e-31 的概览图的分辨率就是 3.08148791101957736488956395309305391146228503771453688386827850341796875e-31 米。因子为 1.540743955509788682444781976546526955731142518857268441934139251708984375e-31 的概览图的分辨率就是 1.540743955509788682444781976546526955731142518857268441934139251708984375e-31 米。因子为 7.703719777548943412223909882732634778655712594286342209670696258544921875e-32 的概览图的分辨率就是 7.703719777548943412223909882732634778655712594286342209670696258544921875e-32 米。因子为 3.8518598887744717061119549413663173893278562971431711048353481292724609375e-32 的概览图的分辨率就是 3.8518598887744717061119549413663173893278562971431711048353481292724609375e-32 米。因子为 1.92592994438723585305597747068315869466392814857158555241767406463623046875e-32 的概览图的分辨率就是 1.92592994438723585305597747068315869466392814857158555241767406463623046875e-32 米。因子为 9.62964972193617926527988735341579347331964074285792776208837032318115234375e-33 的概览图的分辨率就是 9.62964972193617926527988735341579347331964074285792776208837032318115234375e-33 米。因子为 4.814824860968089632639943676707896736659820371428963881044185161590576171875e-33 的概览图的分辨率就是 4.814824860968089632639943676707896736659820371428963881044185161590576171875e-33 米。因子为 2.4074124304840448163199718383539483683299101857144819405220925807952880859375e-33 的概览图的分辨率就是 2.40741243048404481631997183835394836832991018571448194052209

```

        $input_srid = intval($_REQUEST['srid']);
    }
    else { $input_srid = 26986; }
    /** The set bytea_output may be needed for PostgreSQL 9.0+, but not for 8.4 */
    $sql = "set bytea_output='escape';
    SELECT ST_AsPNG(ST_Transform(
        ST_AddBand(ST_Union(rast,1), ARRAY[ST_Union(rast,2),ST_Union(rast,3)]),
        ,3)))
    FROM aerials.boston
    WHERE
        ST_Intersects(rast, ST_Transform(ST_MakeEnvelope(-71.1217, 42.227, -71.1210, 42.218,4326),26986) )";
    $result = pg_query($sql);
    $row = pg_fetch_row($result);
    pg_free_result($result);
    if ($row === false) return;
    echo pg_unescape_bytea($row[0]);
    ?>

```

10.3.2 国际化 ST_AsPNG 国际化 ASP.NET C# 国际化

国际化, npgsql PostgreSQL .NET 国际化 **ST_AsGDALRaster** 国际化 1, 2, 3 国际化 PHP 国际化 (request stream) 国际化. 国际化 PHP 国际化 "img src" HTML 国际化.

国际化 npgsql PostgreSQL .NET 国际化. <http://npgsql.projects.postgresql.org/> 国际化. 国际化 ASP.NET bin 国际化.

国际化 (combine) 国际化 WGS84 国际化, **ST_Union** 国际化 (union) 国际化, **ST_Transform** 国际化, **ST_AsPNG** 国际化 PNG 国际化.

国际化 C# 国际化 Section 10.3.1 国际化.

http://mywebserver/test_raster.php?srid=2249

国际化, 国际化.

```

-- web.config connection string section --
<connectionStrings>
  <add name="DSN"
    connectionString="server=localhost;database=mydb;Port=5432;User Id=myuser;password=
    mypwd"/>
</connectionStrings>

```

```

// Code for TestRaster.ashx
<%@ WebHandler Language="C#" Class="TestRaster" %>
using System;
using System.Data;
using System.Web;
using Npgsql;

public class TestRaster : IHttpHandler
{
    public void ProcessRequest(HttpContext context)
    {
        context.Response.ContentType = "image/png";
    }
}

```

```

        context.Response.BinaryWrite(GetResults(context));
    }

    public bool IsReusable {
        get { return false; }
    }

    public byte[] GetResults(HttpContext context)
    {
        byte[] result = null;
        NpgsqlCommand command;
        string sql = null;
        int input_srid = 26986;
    try {
        using (NpgsqlConnection conn = new NpgsqlConnection(System.↵
            Configuration.ConfigurationManager.ConnectionStrings["DSN"].↵
            ConnectionString)) {
            conn.Open();

            if (context.Request["srid"] != null)
            {
                input_srid = Convert.ToInt32(context.Request["srid"]);
            }
            sql = @"SELECT ST_AsPNG(
                    ST_Transform(
                        ST_AddBand(
                            ST_Union(rast,1), ARRAY[ST_Union(rast,2),ST_Union(rast,3)]
                                ,:input_srid) ) As new_rast
                    FROM aerials.boston
                    WHERE
                        ST_Intersects(rast,
                            ST_Transform(ST_MakeEnvelope(-71.1217, 42.227, ↵
                                -71.1210, 42.218,4326),26986) )";
            command = new NpgsqlCommand(sql, conn);
            command.Parameters.Add(new NpgsqlParameter("input_srid", input_srid));

            result = (byte[]) command.ExecuteScalar();
            conn.Close();
        }
    }
    catch (Exception ex)
    {
        result = null;
        context.Response.Write(ex.Message.Trim());
    }
    return result;
}

```

10.3.3 使用 Npgsql 在 Java 中访问 PostGIS

本节将介绍如何在 Java 中使用 Npgsql 访问 PostGIS。

<http://jdbc.postgresql.org/download.html> 提供了 PostgreSQL JDBC 驱动程序的下载链接。

安装驱动程序后，可以在 Java 代码中使用：

```
set env CLASSPATH ....\postgresql-9.0-801.jdbc4.jar
javac SaveQueryImage.java
jar cfm SaveQueryImage.jar Manifest.txt *.class
```

编译并打包后的文件如下：

```
java -jar SaveQueryImage.jar "SELECT ST_AsPNG(ST_AsRaster(ST_Buffer(ST_Point(1,5),10, ' ↵
quad_segs=2'),150, 150, '8BUI',100));" "test.png"
```

```
-- Manifest.txt --
Class-Path: postgresql-9.0-801.jdbc4.jar
Main-Class: SaveQueryImage
```

```
// Code for SaveQueryImage.java
import java.sql.Connection;
import java.sql.SQLException;
import java.sql.PreparedStatement;
import java.sql.ResultSet;
import java.io.*;

public class SaveQueryImage {
    public static void main(String[] argv) {
        System.out.println("Checking if Driver is registered with DriverManager.");

        try {
            //java.sql.DriverManager.registerDriver (new org.postgresql.Driver());
            Class.forName("org.postgresql.Driver");
        }
        catch (ClassNotFoundException cnfe) {
            System.out.println("Couldn't find the driver!");
            cnfe.printStackTrace();
            System.exit(1);
        }

        Connection conn = null;

        try {
            conn = DriverManager.getConnection("jdbc:postgresql://localhost:5432/mydb","myuser ↵
            ", "mypwd");
            conn.setAutoCommit(false);

            PreparedStatement sGetImg = conn.prepareStatement(argv[0]);

            ResultSet rs = sGetImg.executeQuery();

            FileOutputStream fout;
            try
            {
                rs.next();
                /** Output to file name requested by user */
                fout = new FileOutputStream(new File(argv[1]) );
                fout.write(rs.getBytes(1));
                fout.close();
            }
            catch(Exception e)
            {
                System.out.println("Can't create file");
                e.printStackTrace();
            }

            rs.close();
```

```

        sGetImg.close();
        conn.close();
    }
    catch (SQLException se) {
        System.out.println("Couldn't connect: print out a stack trace and exit.");
        se.printStackTrace();
        System.exit(1);
    }
}
}

```

10.3.4 PLPython 调用 SQL 函数

PLPython 是 PostgreSQL 的一个扩展。PLPython 函数使用 Python 语言编写。PLPython 函数使用 `PLPythonu` 或 `PLPythonu3u` 扩展。

```

CREATE OR REPLACE FUNCTION write_file (param_bytes bytea, param_filepath text)
RETURNS text
AS $$
f = open(param_filepath, 'wb+')
f.write(param_bytes)
return param_filepath
$$ LANGUAGE plpythonu;

```

```

--write out 5 images to the PostgreSQL server in varying sizes
-- note the postgresql daemon account needs to have write access to folder
-- this echos back the file names created;
SELECT write_file(ST_AsPNG(
    ST_AsRaster(ST_Buffer(ST_Point(1,5),j*5, 'quad_segs=2'),150*j, 150*j, '8BUI',100)),
    'C:/temp/slices'|| j || '.png')
FROM generate_series(1,5) As j;

write_file
-----
C:/temp/slices1.png
C:/temp/slices2.png
C:/temp/slices3.png
C:/temp/slices4.png
C:/temp/slices5.png

```

10.3.5 PSQL 调用 PLPython 函数

PSQL 是 PostgreSQL 的交互式 SQL 客户端。PostgreSQL 的 PSQL 客户端可以调用 PLPython 函数。PSQL 客户端使用 `psql` 命令。PSQL 客户端使用 `psql` 命令。

PSQL 客户端使用 `psql` 命令。PSQL 客户端使用 `psql` 命令。

```

SELECT oid, lowrite(lo_open(oid, 131072), png) As num_bytes
FROM
( VALUES (lo_create(0),
    ST_AsPNG( (SELECT rast FROM aerials.boston WHERE rid=1) )
) ) As v(oid,png);
-- you'll get an output something like --
oid | num_bytes
-----+-----
2630819 | 74860

```

```
-- next note the oid and do this replacing the c:/test.png to file path location
-- on your local computer
\lo_export 2630819 'C:/temp/aerial_samp.png'

-- this deletes the file from large object storage on db
SELECT lo_unlink(2630819);
```


11.1 几何函数

11.1.1 geomval

geomval — (geometry) geom 的 (geometry) val, 返回 geometry 值。

例

geomval 返回 geometry, .geom 返回 geometry。ST_DumpAsPolygon 返回 geometry。

例

Section 13.6

11.1.2 addbandarg

addbandarg — 返回 ST_AddBand 返回的 geometry。

例

返回 ST_AddBand 返回的 geometry。

index integer 返回 1-geometry。NULL 返回, 返回 geometry。

pixeltype text ST_BandPixelType 返回 geometry。

initialvalue double precision 返回 geometry。

nodataval double precision 返回 NODATA 返回。NULL 返回, 返回 NODATA 返回。

例

ST_AddBand

11.1.3 rastbandarg

rastbandarg — 返回 geometry。

例

返回 geometry。

rast raster 返回 geometry。

nband integer 返回 1-geometry。

'(表达式 (a-b) 与 a-b 表达式。

pixeltype text ST_BandPixelType 表达式。

nodataval double precision NODATA 表达式。 表达式, 表达式。

例: 值 2 与 255 与 NODATA 与 8BUI 表达式。

```
SELECT ROW(2, '0-100:1-10, 101-500:11-150,501 - 10000: 151-254', '8BUI', 255)::reclassarg;
```

例: 值 1 与 NODATA 与 1BB 表达式。

```
SELECT ROW(1, '0-100]:0, (100-255:1', '1BB', NULL)::reclassarg;
```

例

ST_Reclass

11.1.6 summarystats

summarystats — ST_SummaryStats 与 ST_SummaryStatsAgg 表达式。

例

ST_SummaryStats 与 **ST_SummaryStatsAgg** 表达式。

count integer 表达式。

sum double precision 表达式。

mean double precision 表达式。

stddev double precision 表达式。

min double precision 表达式。

max double precision 表达式。

例

ST_SummaryStats, ST_SummaryStatsAgg

11.1.7 unionarg

unionarg — 表达式 UNION 表达式 ST_Union 表达式。

例：

创建表并加载数据：UNION 操作符使用 `ST_Union` 函数将两个栅格表合并。

nband integer 指定栅格表的波段数，默认为 1-波段。

uniontype text UNION 操作符使用 `ST_Union` 函数将两个栅格表合并。

例：

`ST_Union`

11.2 栅格函数

11.2.1 AddRasterConstraints

AddRasterConstraints — Adds raster constraints to a loaded raster table for a specific column that constrains spatial ref, scaling, blocksize, alignment, bands, band type and a flag to denote if raster column is regularly blocked. The table must be loaded with data for the constraints to be inferred. Returns true if the constraint setting was accomplished and issues a notice otherwise.

Synopsis

```
boolean AddRasterConstraints(name rasttable, name rastcolumn, boolean srid=true, boolean scale_x=true,
boolean scale_y=true, boolean blocksize_x=true, boolean blocksize_y=true, boolean same_alignment=true,
boolean regular_blocking=false, boolean num_bands=true, boolean pixel_types=true, boolean no-
data_values=true, boolean out_db=true, boolean extent=true );
boolean AddRasterConstraints(name rasttable, name rastcolumn, text[] VARIADIC constraints);
boolean AddRasterConstraints(name rastschema, name rasttable, name rastcolumn, text[] VARI-
ADIC constraints);
boolean AddRasterConstraints(name rastschema, name rasttable, name rastcolumn, boolean srid=true,
boolean scale_x=true, boolean scale_y=true, boolean blocksize_x=true, boolean blocksize_y=true,
boolean same_alignment=true, boolean regular_blocking=false, boolean num_bands=true, boolean
pixel_types=true, boolean nodata_values=true, boolean out_db=true, boolean extent=true );
```

例：

`raster_columns` 表包含栅格表的信息，`rastschema` 表包含栅格表的 schema 信息。srid 为 SPATIAL_REF_SYS 表中的 srid。

`raster2pgsql` 函数用于将栅格数据加载到数据库中。

有关该函数的详细信息，请参见 Section 10.2.1 中的描述。

- `blocksize` X Y 指定栅格表的块大小。
- `blocksize_x` X 指定 (X 轴方向) 的块大小。
- `blocksize_y` Y 指定 (Y 轴方向) 的块大小。
- `extent` 指定栅格表的范围。默认为栅格表的边界框。
- `num_bands` 指定栅格表的波段数。

- `pixel_types` 指定栅格像素的数据类型。默认是 `N` (无符号整数)。
- `regular_blocking` 指定栅格是否规则 (即所有栅格的块大小和像素大小是否相同)。
- `same_alignment` 确保它们都具有相同的对齐方式，意味着任何两个你比较的栅格都会返回 `true`。请参考 [ST_SameAlignment](#)。
- `srid` 指定栅格的 SRID。
- `--` 指定其他选项。



Note

在创建栅格表时，必须指定 `pixel_types` 和 `regular_blocking`。



Note

在创建栅格表时，必须指定 `DropRasterConstraints`。

2.0.0 安装与配置

创建表:

```
CREATE TABLE myrasters(rid SERIAL primary key, rast raster);
INSERT INTO myrasters(rast)
SELECT ST_AddBand(ST_MakeEmptyRaster(1000, 1000, 0.3, -0.3, 2, 2, 0, 0,4326), 1, '8BSI'::text, -129, NULL);

SELECT AddRasterConstraints('myrasters'::name, 'rast'::name);

-- verify if registered correctly in the raster_columns view --
SELECT srid, scale_x, scale_y, blocksize_x, blocksize_y, num_bands, pixel_types, nodata_values
FROM raster_columns
WHERE r_table_name = 'myrasters';

srid | scale_x | scale_y | blocksize_x | blocksize_y | num_bands | pixel_types | nodata_values |
-----+-----+-----+-----+-----+-----+-----+-----+
4326 | 2 | 2 | 1000 | 1000 | 1 | {8BSI} | {0}
```

创建表:

```
CREATE TABLE public.myrasters2(rid SERIAL primary key, rast raster);
INSERT INTO myrasters2(rast)
SELECT ST_AddBand(ST_MakeEmptyRaster(1000, 1000, 0.3, -0.3, 2, 2, 0, 0,4326), 1, '8BSI'::text, -129, NULL);
```

```
SELECT AddRasterConstraints('public'::name, 'myrasters2'::name, 'rast'::name, ' ←
    regular_blocking', 'blocksize');
-- get notice--
NOTICE: Adding regular blocking constraint
NOTICE: Adding blocksize-X constraint
NOTICE: Adding blocksize-Y constraint
```

☐☐

Section [10.2.1, ST_AddBand, ST_MakeEmptyRaster, DropRasterConstraints, ST_BandPixelType, ST_SRID](#)

11.2.2 DropRasterConstraints

DropRasterConstraints — 删除 PostGIS 栅格表上的约束。该函数将指定的栅格表上的所有约束（包括 regular_blocking、blocksize-X、blocksize-Y、same_alignment、regular_blocking、num_bands、pixel_types、nodata_values、out_db、extent）删除。

Synopsis

boolean **DropRasterConstraints**(name rasttable, name rastcolumn, boolean srid, boolean scale_x, boolean scale_y, boolean blocksize_x, boolean blocksize_y, boolean same_alignment, boolean regular_blocking, boolean num_bands=true, boolean pixel_types=true, boolean nodata_values=true, boolean out_db=true, boolean extent=true);

boolean **DropRasterConstraints**(name rastschema, name rasttable, name rastcolumn, boolean srid=true, boolean scale_x=true, boolean scale_y=true, boolean blocksize_x=true, boolean blocksize_y=true, boolean same_alignment=true, boolean regular_blocking=false, boolean num_bands=true, boolean pixel_types=true, boolean nodata_values=true, boolean out_db=true, boolean extent=true);

boolean **DropRasterConstraints**(name rastschema, name rasttable, name rastcolumn, text[] constraints);

☐☐

AddRasterConstraints 函数，用于在 PostGIS 栅格表上添加约束。该函数将指定的栅格表上的所有约束（包括 regular_blocking、blocksize-X、blocksize-Y、same_alignment、regular_blocking、num_bands、pixel_types、nodata_values、out_db、extent）添加到指定的栅格表上。

该函数将指定的栅格表上的所有约束（包括 regular_blocking、blocksize-X、blocksize-Y、same_alignment、regular_blocking、num_bands、pixel_types、nodata_values、out_db、extent）添加到指定的栅格表上。

```
DROP TABLE mytable
```

该函数将指定的栅格表上的所有约束（包括 regular_blocking、blocksize-X、blocksize-Y、same_alignment、regular_blocking、num_bands、pixel_types、nodata_values、out_db、extent）添加到指定的栅格表上，并返回 SQL 语句。

```
ALTER TABLE mytable DROP COLUMN rast
```

该函数将指定的栅格表上的所有约束（包括 regular_blocking、blocksize-X、blocksize-Y、same_alignment、regular_blocking、num_bands、pixel_types、nodata_values、out_db、extent）添加到指定的栅格表上，并返回 SQL 语句。

2.0.0 版本。


```

    ST_MakeEmptyRaster(500, 500, 0, 0, 4),
    1, '8BSI'::text, -129, NULL
) r2;

SELECT AddOverviewConstraints('res2', 'r2', 'res1', 'r1', 2);

-- verify if registered correctly in the raster_overviews view --
SELECT o_table_name ot, o_raster_column oc,
       r_table_name rt, r_raster_column rc,
       overview_factor f
FROM raster_overviews WHERE o_table_name = 'res2';
  ot | oc | rt | rc | f
-----+-----+-----+-----+---
 res2 | r2 | res1 | r1 | 2
(1 row)

```

☐☐

Section [10.2.2, DropOverviewConstraints, ST_CreateOverview, AddRasterConstraints](#)

11.2.4 DropOverviewConstraints

DropOverviewConstraints — 删除 (overview) 元数据。

Synopsis

boolean **DropOverviewConstraints**(name ovschema, name ovtable, name ovcolumn);
 boolean **DropOverviewConstraints**(name ovtable, name ovcolumn);

☐☐

raster_overviews 元数据表。该表包含有关栅格元数据的元数据。

ovschema 元数据模式名, search_path 元数据搜索路径。

2.0.0 版本引入。

☐☐

Section [10.2.2, AddOverviewConstraints, DropRasterConstraints](#)

11.2.5 PostGIS_GDAL_Version

PostGIS_GDAL_Version — 返回 PostGIS 使用的 GDAL 版本。

Synopsis

text **PostGIS_GDAL_Version**();

安装

PostGIS 安装 GDAL 依赖库。GDAL 安装依赖库。

安装

```
SELECT PostGIS_GDAL_Version();
       postgis_gdal_version
-----
GDAL 1.11dev, released 2013/04/13
```

安装

`postgis.gdal_datapath`

11.2.6 PostGIS_Raster_Lib_Build_Date

PostGIS_Raster_Lib_Build_Date — 返回 PostGIS 的构建日期。

Synopsis

text **PostGIS_Raster_Lib_Build_Date();**

安装

安装依赖库。

安装

```
SELECT PostGIS_Raster_Lib_Build_Date();
       postgis_raster_lib_build_date
-----
2010-04-28 21:15:10
```

安装

`PostGIS_Raster_Lib_Version`

11.2.7 PostGIS_Raster_Lib_Version

PostGIS_Raster_Lib_Version — 返回 PostGIS 的构建版本。

Synopsis

text **PostGIS_Raster_Lib_Version();**

例

PostGIS_Raster_Lib_Version().

例

```
SELECT PostGIS_Raster_Lib_Version();
postgis_raster_lib_version
-----
2.0.0
```

例

PostGIS_Lib_Version

11.2.8 ST_GDALDrivers

ST_GDALDrivers — Returns a list of raster formats supported by PostGIS through GDAL. Only those formats with can_write=True can be used by ST_AsGDALRaster

Synopsis

setof record **ST_GDALDrivers**(integer OUT idx, text OUT short_name, text OUT long_name, text OUT can_read, text OUT can_write, text OUT create_options);

例

Returns a list of raster formats short_name,long_name and creator options of each format supported by GDAL. Use the short_name as input in the format parameter of **ST_AsGDALRaster**. Options vary depending on what drivers your libgdal was compiled with. create_options returns an xml formatted set of CreationOptionList/Option consisting of name and optional type, description and set of VALUE for each creator option for the specific driver.

Changed: 2.5.0 - add can_read and can_write columns.

例: 2.0.6, 2.1.3 例 - GUC 例 gdal_enabled_drivers 例, 例

2.0.0 例. GDAL 1.6.0 例.

例: 例

```
SET postgis.gdal_enabled_drivers = 'ENABLE_ALL';
SELECT short_name, long_name, can_write
FROM st_gdaldrivers()
ORDER BY short_name;
```

short_name	long_name	can_write
AAIGrid	Arc/Info ASCII Grid	t
ACE2	ACE2	f
ADRG	ARC Digitized Raster Graphics	f

AIG	Arc/Info Binary Grid	f
AirSAR	AirSAR Polarimetric Image	f
ARG	Azavea Raster Grid format	t
BAG	Bathymetry Attributed Grid	f
BIGGIF	Graphics Interchange Format (.gif)	f
BLX	Magellan topo (.blx)	t
BMP	MS Windows Device Independent Bitmap	f
BSB	Maptech BSB Nautical Charts	f
PAux	PCI .aux Labelled	f
PCIDSK	PCIDSK Database File	f
PCRaster	PCRaster Raster File	f
PDF	Geospatial PDF	f
PDS	NASA Planetary Data System	f
PDS4	NASA Planetary Data System 4	t
PLMOSAIC	Planet Labs Mosaics API	f
PLSCENES	Planet Labs Scenes API	f
PNG	Portable Network Graphics	t
PNM	Portable Pixmap Format (netpbm)	f
PRF	Racurs PHOTOMOD PRF	f
R	R Object Data Store	t
Rasterlite	Rasterlite	t
RDA	DigitalGlobe Raster Data Access driver	f
RIK	Swedish Grid RIK (.rik)	f
RMF	Raster Matrix Format	f
ROI_PAC	ROI_PAC raster	f
RPFTOC	Raster Product Format TOC format	f
RRASTER	R Raster	f
RS2	RadarSat 2 XML Product	f
RST	Idrisi Raster A.1	t
SAFE	Sentinel-1 SAR SAFE Product	f
SAGA	SAGA GIS Binary Grid (.sdat, .sg-grd-z)	t
SAR_CEOS	CEOS SAR Image	f
SDTS	SDTS Raster	f
SENTINEL2	Sentinel 2	f
SGI	SGI Image File Format 1.0	f
SNODAS	Snow Data Assimilation System	f
SRP	Standard Raster Product (ASRP/USRP)	f
SRTMHGT	SRTMHGT File Format	t
Terragen	Terragen heightfield	f
TIL	EarthWatch .TIL	f
TSX	TerraSAR-X Product	f
USGSDEM	USGS Optional ASCII DEM (and CDED)	t
VICAR	MIPL VICAR file	f
VRT	Virtual Raster	t
WCS	OGC Web Coverage Service	f
WMS	OGC Web Map Service	t
WMTS	OGC Web Map Tile Service	t
XPM	X11 PixMap Format	t
XYZ	ASCII Gridded XYZ	t
ZMap	ZMap Plus Grid	t

国际化: 国际化国际化国际化国际化

```
-- Output the create options XML column of JPEG as a table --
-- Note you can use these creator options in ST_AsGDALRaster options argument
SELECT (xpath('@name', g.opt))[1]::text As oname,
       (xpath('@type', g.opt))[1]::text As otype,
       (xpath('@description', g.opt))[1]::text As descrip
FROM (SELECT unnest(xpath('/CreationOptionList/Option', create_options::xml)) As opt
FROM st_gdaldrivers())
```

```
WHERE short_name = 'JPEG') As g;
```

oname	otype	descrip
PROGRESSIVE	boolean	whether to generate a progressive JPEG
QUALITY	int	good=100, bad=0, default=75
WORLDFILE	boolean	whether to generate a worldfile
INTERNAL_MASK	boolean	whether to generate a validity mask
COMMENT	string	Comment
SOURCE_ICC_PROFILE	string	ICC profile encoded in Base64
EXIF_THUMBNAIL	boolean	whether to generate an EXIF thumbnail(overview). By default its max dimension will be 128
THUMBNAIL_WIDTH	int	Forced thumbnail width
THUMBNAIL_HEIGHT	int	Forced thumbnail height

(9 rows)

```
-- raw xml output for creator options for GeoTiff --
```

```
SELECT create_options
```

```
FROM st_gdaldrivers()
```

```
WHERE short_name = 'GTiff';
```

```
<CreationOptionList>
```

```
  <Option name="COMPRESS" type="string-select">
```

```
    <Value
```

```
>NONE</Value>
```

```
    <Value
```

```
>LZW</Value>
```

```
    <Value
```

```
>PACKBITS</Value>
```

```
    <Value
```

```
>JPEG</Value>
```

```
    <Value
```

```
>CCITTRLE</Value>
```

```
    <Value
```

```
>CCITTFAX3</Value>
```

```
    <Value
```

```
>CCITTFAX4</Value>
```

```
    <Value
```

```
>DEFLATE</Value>
```

```
  </Option>
```

```
  <Option name="PREDICTOR" type="int" description="Predictor Type"/>
```

```
  <Option name="JPEG_QUALITY" type="int" description="JPEG quality 1-100" default="75"/>
```

```
  <Option name="ZLEVEL" type="int" description="DEFLATE compression level 1-9" default ←  
    ="6"/>
```

```
  <Option name="NBITS" type="int" description="BITS for sub-byte files (1-7), sub-uint16 ←  
    (9-15), sub-uint32 (17-31)"/>
```

```
  <Option name="INTERLEAVE" type="string-select" default="PIXEL">
```

```
    <Value
```

```
>BAND</Value>
```

```
    <Value
```

```
>PIXEL</Value>
```

```
  </Option>
```

```
  <Option name="TILED" type="boolean" description="Switch to tiled format"/>
```

```
  <Option name="TFW" type="boolean" description="Write out world file"/>
```

```
  <Option name="RPB" type="boolean" description="Write out .RPB (RPC) file"/>
```

```
  <Option name="BLOCKXSIZE" type="int" description="Tile Width"/>
```

```
  <Option name="BLOCKYSIZE" type="int" description="Tile/Strip Height"/>
```

```
  <Option name="PHOTOMETRIC" type="string-select">
```

```
    <Value
```

```
>MINISBLACK</Value>
```

```
    <Value
```

```

>MINISWHITE</Value>
  <Value
>PALETTE</Value>
  <Value
>RGB</Value>
  <Value
>CMYK</Value>
  <Value
>YCBCR</Value>
  <Value
>CIELAB</Value>
  <Value
>ICCLAB</Value>
  <Value
>ITULAB</Value>
  </Option>
  <Option name="SPARSE_OK" type="boolean" description="Can newly created files have ↵
    missing blocks?" default="FALSE"/>
  <Option name="ALPHA" type="boolean" description="Mark first extrasample as being alpha ↵
    "/>
  <Option name="PROFILE" type="string-select" default="GDALGeoTIFF">
    <Value
>GDALGeoTIFF</Value>
    <Value
>GeoTIFF</Value>
    <Value
>BASELINE</Value>
  </Option>
  <Option name="PIXELTYPE" type="string-select">
    <Value
>DEFAULT</Value>
    <Value
>SIGNEDBYTE</Value>
  </Option>
  <Option name="BIGTIFF" type="string-select" description="Force creation of BigTIFF file ↵
    ">
    <Value
>YES</Value>
    <Value
>NO</Value>
    <Value
>IF_NEEDED</Value>
    <Value
>IF_SAFER</Value>
  </Option>
  <Option name="ENDIANNESS" type="string-select" default="NATIVE" description="Force ↵
    endianness of created file. For DEBUG purpose mostly">
    <Value
>NATIVE</Value>
    <Value
>INVERTED</Value>
    <Value
>LITTLE</Value>
    <Value
>BIG</Value>
  </Option>
  <Option name="COPY_SRC_OVERVIEWS" type="boolean" default="NO" description="Force copy ↵
    of overviews of source dataset (CreateCopy())"/>
</CreationOptionList>

-- Output the create options XML column for GTiff as a table --
SELECT (xpath('@name', g.opt))[1]::text As oname,

```

```

        (xpath('@type', g.opt))[1]::text As otype,
        (xpath('@description', g.opt))[1]::text As descrip,
        array_to_string(xpath('Value/text()', g.opt),', ') As vals
FROM (SELECT unnest(xpath('/CreationOptionList/Option', create_options::xml)) As opt
FROM st_gdaldrivers()
WHERE short_name = 'GTiff') As g;

```

oname	otype	descrip	vals
COMPRESS	string-select		NONE, LZW, ←
PACKBITS, JPEG, CCITTRLE, CCITTFAX3, CCITTFAX4, DEFLATE			
PREDICTOR	int	Predictor Type	←
JPEG_QUALITY	int	JPEG quality 1-100	←
ZLEVEL	int	DEFLATE compression level 1-9	←
NBITS	int	BITS for sub-byte files (1-7), sub-uint16 (9-15), sub-uint32 (17-31)	←
INTERLEAVE	string-select		BAND, PIXEL
TILED	boolean	Switch to tiled format	←
TFW	boolean	Write out world file	←
RPB	boolean	Write out .RPB (RPC) file	←
BLOCKXSIZE	int	Tile Width	←
BLOCKYSIZE	int	Tile/Strip Height	←
PHOTOMETRIC	string-select		MINISBLACK, ←
MINISWHITE, PALETTE, RGB, CMYK, YCBCR, CIELAB, ICCLAB, ITULAB			
SPARSE_OK	boolean	Can newly created files have missing blocks?	←
ALPHA	boolean	Mark first extrasample as being alpha	←
PROFILE	string-select		GDALGeoTIFF, ←
GeoTIFF, BASELINE			
PIXELTYPE	string-select		DEFAULT, ←
SIGNEDBYTE			
BIGTIFF	string-select	Force creation of BigTIFF file	←
ENDIANNESS	string-select	Force endianness of created file. For DEBUG purpose	←
mostly			NATIVE, INVERTED, LITTLE, BIG
COPY_SRC_OVERVIEWS	boolean	Force copy of overviews of source dataset (CreateCopy	←
(()))			

(19 rows)



[ST_AsGDALRaster](#), [ST_SRID](#), [postgis.gdal_enabled_drivers](#)

11.2.9 ST_Contour

ST_Contour — Generates a set of vector contours from the provided raster band, using the [GDAL contouring algorithm](#).

Synopsis

setof record **ST_Contour**(raster rast, integer bandnumber=1, double precision level_interval=100.0, double precision level_base=0.0, double precision[] fixed_levels=ARRAY[], boolean polygonize=false);

国国

Generates a set of vector contours from the provided raster band, using the [GDAL contouring algorithm](#).

When the `fixed_levels` parameter is a non-empty array, the `level_interval` and `level_base` parameters are ignored.

Input parameters are:

rast The raster to generate the contour of

bandnumber The band to generate the contour of

level_interval The elevation interval between contours generated

level_base The "base" relative to which contour intervals are applied, this is normally zero, but could be different. To generate 10m contours at 5, 15, 25, ... the `LEVEL_BASE` would be 5.

fixed_levels The elevation interval between contours generated

polygonize If true, contour polygons will be created, rather than polygon lines.

Return values are a set of records with the following attributes:

geom The geometry of the contour line.

id A unique identifier given to the contour line by GDAL.

value The raster value the line represents. For an elevation DEM input, this would be the elevation of the output contour.

Availability: 3.2.0

国国

```
WITH c AS (
SELECT (ST_Contour(rast, 1, fixed_levels => ARRAY[100.0, 200.0, 300.0])).*
FROM dem_grid WHERE rid = 1
)
SELECT st_astext(geom), id, value
FROM c;
```

国国

[ST_InterpolateRaster](#)

Synopsis

raster **UpdateRasterSRID**(name schema_name, name table_name, name column_name, integer new_srid);
 raster **UpdateRasterSRID**(name table_name, name column_name, integer new_srid);

更新

将指定栅格列的 SRID 更新为指定的 SRID。如果指定了 schema_name，则更新 schema_name 中的 table_name 表中的 column_name 列。如果未指定 schema_name，则更新当前数据库中的 table_name 表中的 column_name 列。



Note

更新后的 SRID 必须与原始 SRID 兼容。否则，将引发错误。

2.1.0 更新日志

更新

UpdateGeometrySRID

11.2.12 ST_CreateOverview

ST_CreateOverview — 创建栅格的概述图。

Synopsis

regclass **ST_CreateOverview**(regclass tab, name col, int factor, text algo='NearestNeighbor');

更新

创建指定栅格列的概述图。概述图是原始栅格的缩小版本，其分辨率由 factor 参数指定。factor 必须是 2 的幂。如果未指定 algo，则使用 'NearestNeighbor'。

raster_overviews 表将包含概述图。概述图将存储在 raster_overviews 表中。

支持的算法包括 'NearestNeighbor', 'Bilinear', 'Cubic', 'CubicSpline', 以及 'Lanczos'。有关更多选项，请参阅 [GDAL Warp resampling methods](#)。

2.2.0 更新日志

更新

Output to generally better quality but slower to product format

```
SELECT ST_CreateOverview('mydata.mytable'::regclass, 'rast', 2, 'Lanczos');
```

Output to faster to process default nearest neighbor

```
SELECT ST_CreateOverview('mydata.mytable'::regclass, 'rast', 2);
```


例

[ST_Retile](#), [AddOverviewConstraints](#), [AddRasterConstraints](#), [Section 10.2.2](#)

11.3 関数 (constructor)

11.3.1 ST_AddBand

ST_AddBand — 指定した位置 (index) に指定したタイプと初期値の新しいバンドを追加する。ノodata値も指定可能。

Synopsis

- (1) raster **ST_AddBand**(raster rast, addbandarg[] addbandargset);
- (2) raster **ST_AddBand**(raster rast, integer index, text pixeltype, double precision initialvalue=0, double precision nodataval=NULL);
- (3) raster **ST_AddBand**(raster rast, text pixeltype, double precision initialvalue=0, double precision nodataval=NULL);
- (4) raster **ST_AddBand**(raster torast, raster fromrast, integer fromband=1, integer torastindex=at_end);
- (5) raster **ST_AddBand**(raster torast, raster[] fromrasts, integer fromband=1, integer torastindex=at_end);
- (6) raster **ST_AddBand**(raster rast, integer index, text outdbfile, integer[] outdbindex, double precision nodataval=NULL);
- (7) raster **ST_AddBand**(raster rast, text outdbfile, integer[] outdbindex, integer index=at_end, double precision nodataval=NULL);

例

Returns a raster with a new band added in given position (index), of given type, of given initial value, and of given nodata value. If no index is specified, the band is added to the end. If no fromband is specified, band 1 is assumed. Pixel type is a string representation of one of the pixel types specified in [ST_BandPixelType](#). If an existing index is specified all subsequent bands $\geq$ that index are incremented by 1. If an initial value greater than the max of the pixel type is specified, then the initial value is set to the highest value allowed by the pixel type.

addbandarg 1 例, **addbandarg** 例

5 例, **torast** NULL 例 **fromband** 例 (累計) 例。

outdbfile 6 7 例, **outdbfile** 例。 PostgreSQL 例。

例: 2.1.0 例 **addbandarg** 例。

例: 2.1.0 例 DB 例。

例: 例

```
-- Add another band of type 8 bit unsigned integer with pixels initialized to 200
UPDATE dummy_rast
SET rast = ST_AddBand(rast, '8BUI'::text, 200)
WHERE rid = 1;
```

```
-- Create an empty raster 100x100 units, with upper left right at 0, add 2 bands (band 1 is 0/1 boolean bit switch, band2 allows values 0-15)
-- uses addbandargs
INSERT INTO dummy_rast(rid,rast)
VALUES(10, ST_AddBand(ST_MakeEmptyRaster(100, 100, 0, 0, 1, -1, 0, 0, 0),
ARRAY[
    ROW(1, '1BB'::text, 0, NULL),
    ROW(2, '4BUI'::text, 0, NULL)
]::addbandarg[]
)
);

-- output meta data of raster bands to verify all is right --
SELECT (bmd).*
FROM (SELECT ST_BandMetaData(rast,generate_series(1,2)) As bmd
FROM dummy_rast WHERE rid = 10) AS foo;
--result --
pixeltype | nodatavalue | isoutdb | path
-----+-----+-----+-----
1BB       |             | f       |
4BUI      |             | f       |

-- output meta data of raster -
SELECT (rmd).width, (rmd).height, (rmd).numbands
FROM (SELECT ST_MetaData(rast) As rmd
FROM dummy_rast WHERE rid = 10) AS foo;
-- result --
upperleftx | upperlefty | width | height | scalex | scaley | skewx | skewy | srid |
numbands
-----+-----+-----+-----+-----+-----+-----+-----+-----+-----
0 | 0 | 100 | 100 | 1 | -1 | 0 | 0 | 0 |
2
```

例: 创建带元数据的栅格

```
SELECT
*
FROM ST_BandMetadata(
    ST_AddBand(
        ST_MakeEmptyRaster(10, 10, 0, 0, 1, -1, 0, 0, 0),
        ARRAY[
            ROW(NULL, '8BUI', 255, 0),
            ROW(NULL, '16BUI', 1, 2),
            ROW(2, '32BUI', 100, 12),
            ROW(2, '32BF', 3.14, -1)
        ]::addbandarg[]
    ),
    ARRAY[]::integer[]
);

bandnum | pixeltype | nodatavalue | isoutdb | path
-----+-----+-----+-----+-----
1 | 8BUI      | 0           | f       |
2 | 32BF      | -1          | f       |
3 | 32BUI     | 12          | f       |
4 | 16BUI     | 2           | f       |
```

```
-- Aggregate the 1st band of a table of like rasters into a single raster
-- with as many bands as there are test_types and as many rows (new rasters) as there are ←
-- mice
-- NOTE: The ORDER BY test_type is only supported in PostgreSQL 9.0+
-- for 8.4 and below it usually works to order your data in a subselect (but not guaranteed ←
-- )
-- The resulting raster will have a band for each test_type alphabetical by test_type
-- For mouse lovers: No mice were harmed in this exercise
SELECT
  mouse,
  ST_AddBand(NULL, array_agg(rast ORDER BY test_type), 1) As rast
FROM mice_studies
GROUP BY mouse;
```

DB

```
SELECT
  *
FROM ST_BandMetadata(
  ST_AddBand(
    ST_MakeEmptyRaster(10, 10, 0, 0, 1, -1, 0, 0, 0),
    '/home/raster/mytestraster.tif'::text, NULL::int[]
  ),
  ARRAY[]::integer[]
);
```

bandnum	pixeltype	nodatavalue	isoutdb	path
1	8BUI		t	/home/raster/mytestraster.tif
2	8BUI		t	/home/raster/mytestraster.tif
3	8BUI		t	/home/raster/mytestraster.tif

[ST_BandMetaData](#), [ST_BandPixelType](#), [ST_MakeEmptyRaster](#), [ST_MetaData](#), [ST_NumBands](#), [ST_Reclass](#)

11.3.2 ST_AsRaster

ST_AsRaster — PostGIS PostGIS

Synopsis


raster **ST_AsRaster**(geometry geom, raster ref, text pixeltype, double precision value=1, double precision nodataval=0, boolean touched=false);
raster **ST_AsRaster**(geometry geom, raster ref, text[] pixeltype=ARRAY['8BUI'], double precision[] value=ARRAY[1], double precision[] nodataval=ARRAY[0], boolean touched=false);
raster **ST_AsRaster**(geometry geom, double precision scalex, double precision scaley, double precision gridx, double precision gridy, text pixeltype, double precision value=1, double precision nodataval=0, double precision skewx=0, double precision skewy=0, boolean touched=false);
raster **ST_AsRaster**(geometry geom, double precision scalex, double precision scaley, double precision gridx=NULL, double precision gridy=NULL, text[] pixeltype=ARRAY['8BUI'], double precision[] value=ARRAY[1], double precision[] nodataval=ARRAY[0], double precision skewx=0, double precision skewy=0, boolean touched=false);



Note

XXXXXXXXXX, TIN, XXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXX, GDAL XXXXXXXXXXXXXXXXXXXX
XXXXXXXXXXXXXXXXXX.

☒☒: **PNG** ☒☒☒☒☒☒☒☒



```
-- this will output a black circle taking up 150 x 150 pixels --
SELECT ST_AsPNG(ST_AsRaster(ST_Buffer(ST_Point(1,5),10),150, 150));
```



PostGIS ☒☒☒☒☒☒☒☒☒☒☒☒☒☒☒☒

```
-- the bands map to RGB bands - the value (118,154,118) - teal --
SELECT ST_AsPNG(
  ST_AsRaster(
    ST_Buffer(
      ST_GeomFromText('LINESTRING(50 50,150 150,150 50)'), 10,'join=bevel'),
      200,200,ARRAY['8BUI', '8BUI', '8BUI'], ARRAY[118,154,118], ARRAY[0,0,0]));
```



ST BandPixelType, ST Buffer, ST GDALDrivers, ST AsGDALRaster, ST AsPNG, ST AsJPEG, ST SRID

11.3.3 ST_Band

[illegible]

Synopsis

```
raster ST_Band(raster rast, integer[] nbands = ARRAY[1]);
raster ST_Band(raster rast, integer nband);
raster ST_Band(raster rast, text nbands, character delimiter=,);
```

返回

Returns one or more bands of an existing raster as a new raster. Useful for building new rasters from existing rasters or export of only selected bands of a raster or rearranging the order of bands in a raster. If no band is specified or any of specified bands does not exist in the raster, then all bands are returned. Used as a helper function in various functions such as for deleting a band.



Warning

如果 nbands 指定为文本，则使用逗号分隔的带数字列表，如 '1,2,3'。如果指定为数组，则使用大括号分隔的带数字列表，如 {1,2,3}。如果指定为数组，则使用大括号分隔的带数字列表，如 {1,2,3}。PostGIS 3.5.0 之前，文本格式仅支持逗号分隔的带数字列表。PostGIS 3.5.0 及以后版本支持两种格式。PostGIS 3.5.0 及以后版本支持两种格式。

2.0.0 版本中，ST_Band 函数返回一个 raster。

示例


```
-- Make 2 new rasters: 1 containing band 1 of dummy, second containing band 2 of dummy and then reclassified as a 2BUI
SELECT ST_NumBands(rast1) As numb1, ST_BandPixelType(rast1) As pix1,
       ST_NumBands(rast2) As numb2, ST_BandPixelType(rast2) As pix2
FROM (
  SELECT ST_Band(rast) As rast1, ST_Reclass(ST_Band(rast,3), '100-200):1, [200-254:2', '2 BUI') As rast2
  FROM dummy_rast
  WHERE rid = 2) As foo;
```

numb1	pix1	numb2	pix2
1	8BUI	1	2BUI

```
-- Return bands 2 and 3. Using array cast syntax
SELECT ST_NumBands(ST_Band(rast, '{2,3}'::int[])) As num_bands
FROM dummy_rast WHERE rid=2;
```

```
num_bands
-----
2
```

```
-- Return bands 2 and 3. Use array to define bands
SELECT ST_NumBands(ST_Band(rast, ARRAY[2,3])) As num_bands
FROM dummy_rast
WHERE rid=2;
```



```
--Make a new raster with 2nd band of original and 1st band repeated twice,  
and another with just the third band  
SELECT rast, ST_Band(rast, ARRAY[2,1,1]) As dupe_band,  
       ST_Band(rast, 3) As sing_band  
FROM samples.than_chunked  
WHERE rid=35;
```

图例

[ST_AddBand](#), [ST_NumBands](#), [ST_Reclass](#), Chapter 11

11.3.4 ST_MakeEmptyCoverage

ST_MakeEmptyCoverage — Cover georeferenced area with a grid of empty raster tiles.

Synopsis

raster **ST_MakeEmptyCoverage**(integer tilewidth, integer tileheight, integer width, integer height, double precision upperleftx, double precision upperlefty, double precision scalex, double precision scaley, double precision skewx, double precision skewy, integer srid=unknown);

图例

Create a set of raster tiles with [ST_MakeEmptyRaster](#). Grid dimension is width & height. Tile dimension is tilewidth & tileheight. The covered georeferenced area is from upper left corner (upperleftx, upperlefty) to lower right corner (upperleftx + width * scalex, upperlefty + height * scaley).



Note

Note that scaley is generally negative for rasters and scalex is generally positive. So lower right corner will have a lower y value and higher x value than the upper left corner.

示例

Create 16 tiles in a 4x4 grid to cover the WGS84 area from upper left corner (22, 77) to lower right corner (55, 33).

```
SELECT (ST_MetaData(tile)).* FROM ST_MakeEmptyCoverage(1, 1, 4, 4, 22, 33, (55 - 22)/(4)::float, (33 - 77)/(4)::float, 0., 0., 4326) tile;
```

upperleftx numbands	upperlefty	width	height	scalex	scaley	skewx	skewy	srid	
22	33	1	1	8.25	-11	0	0	4326	
30.25	0	33	1	8.25	-11	0	0	4326	
38.5	0	33	1	8.25	-11	0	0	4326	
46.75	0	33	1	8.25	-11	0	0	4326	
22	22	1	1	8.25	-11	0	0	4326	
30.25	0	22	1	8.25	-11	0	0	4326	
38.5	0	22	1	8.25	-11	0	0	4326	
46.75	0	22	1	8.25	-11	0	0	4326	
22	11	1	1	8.25	-11	0	0	4326	
30.25	0	11	1	8.25	-11	0	0	4326	
38.5	0	11	1	8.25	-11	0	0	4326	
46.75	0	11	1	8.25	-11	0	0	4326	
22	0	0	1	8.25	-11	0	0	4326	
30.25	0	0	1	8.25	-11	0	0	4326	
38.5	0	0	1	8.25	-11	0	0	4326	
46.75	0	0	1	8.25	-11	0	0	4326	

函数

ST_MakeEmptyRaster

11.3.5 ST_MakeEmptyRaster

ST_MakeEmptyRaster — 创建空栅格 (列 & 行), 列 X 行, 列宽, 行高 (scalex, scaley, skewx & skewy) 指定坐标系 (SRID) 指定 (列宽) 指定 (行高). 指定列宽, 行高, 指定 SRID 指定 (列宽) 指定 (行高). SRID 指定, 指定 0(unknown) 指定.

Synopsis

setof raster **ST_Tile**(raster rast, int[] nband, integer width, integer height, boolean padwithnodata=FALSE, double precision nodataval=NULL);
 setof raster **ST_Tile**(raster rast, integer nband, integer width, integer height, boolean padwithnodata=FALSE, double precision nodataval=NULL);
 setof raster **ST_Tile**(raster rast, integer width, integer height, boolean padwithnodata=FALSE, double precision nodataval=NULL);

参数

返回类型: 栅格集合 (set of raster)。

padwithnodata = FALSE 时, 如果输入栅格的 nband 参数指定的波段数少于实际栅格的波段数, 则使用 NODATA 值 (padding) 填充缺失的波段。如果 padwithnodata = TRUE, 则使用 nodataval 指定的 NODATA 值填充缺失的波段。



Note

如果输入栅格来自 PostgreSQL 数据库, 则返回的栅格集合来自 PostgreSQL 数据库。

2.1.0 版本更新

参数

```
WITH foo AS (
  SELECT ST_AddBand(ST_AddBand(ST_MakeEmptyRaster(3, 3, 0, 0, 1, -1, 0, 0, 0), 1, '8BUI', 1, 0), 2, '8BUI', 10, 0) AS rast UNION ALL
  SELECT ST_AddBand(ST_AddBand(ST_MakeEmptyRaster(3, 3, 3, 0, 1, -1, 0, 0, 0), 1, '8BUI', 2, 0), 2, '8BUI', 20, 0) AS rast UNION ALL
  SELECT ST_AddBand(ST_AddBand(ST_MakeEmptyRaster(3, 3, 6, 0, 1, -1, 0, 0, 0), 1, '8BUI', 3, 0), 2, '8BUI', 30, 0) AS rast UNION ALL

  SELECT ST_AddBand(ST_AddBand(ST_MakeEmptyRaster(3, 3, 0, -3, 1, -1, 0, 0, 0), 1, '8BUI', 4, 0), 2, '8BUI', 40, 0) AS rast UNION ALL
  SELECT ST_AddBand(ST_AddBand(ST_MakeEmptyRaster(3, 3, 3, -3, 1, -1, 0, 0, 0), 1, '8BUI', 5, 0), 2, '8BUI', 50, 0) AS rast UNION ALL
  SELECT ST_AddBand(ST_AddBand(ST_MakeEmptyRaster(3, 3, 6, -3, 1, -1, 0, 0, 0), 1, '8BUI', 6, 0), 2, '8BUI', 60, 0) AS rast UNION ALL

  SELECT ST_AddBand(ST_AddBand(ST_MakeEmptyRaster(3, 3, 0, -6, 1, -1, 0, 0, 0), 1, '8BUI', 7, 0), 2, '8BUI', 70, 0) AS rast UNION ALL
  SELECT ST_AddBand(ST_AddBand(ST_MakeEmptyRaster(3, 3, 3, -6, 1, -1, 0, 0, 0), 1, '8BUI', 8, 0), 2, '8BUI', 80, 0) AS rast UNION ALL
  SELECT ST_AddBand(ST_AddBand(ST_MakeEmptyRaster(3, 3, 6, -6, 1, -1, 0, 0, 0), 1, '8BUI', 9, 0), 2, '8BUI', 90, 0) AS rast
), bar AS (
  SELECT ST_Union(rast) AS rast FROM foo
), baz AS (
  SELECT ST_Tile(rast, 3, 3, TRUE) AS rast FROM bar
)
SELECT
  ST_DumpValues(rast)
FROM baz;
```

st_dumpvalues

```

-----
(1,"{{1,1,1},{1,1,1},{1,1,1}}")
(2,"{{10,10,10},{10,10,10},{10,10,10}}")
(1,"{{2,2,2},{2,2,2},{2,2,2}}")
(2,"{{20,20,20},{20,20,20},{20,20,20}}")
(1,"{{3,3,3},{3,3,3},{3,3,3}}")
(2,"{{30,30,30},{30,30,30},{30,30,30}}")
(1,"{{4,4,4},{4,4,4},{4,4,4}}")
(2,"{{40,40,40},{40,40,40},{40,40,40}}")
(1,"{{5,5,5},{5,5,5},{5,5,5}}")
(2,"{{50,50,50},{50,50,50},{50,50,50}}")
(1,"{{6,6,6},{6,6,6},{6,6,6}}")
(2,"{{60,60,60},{60,60,60},{60,60,60}}")
(1,"{{7,7,7},{7,7,7},{7,7,7}}")
(2,"{{70,70,70},{70,70,70},{70,70,70}}")
(1,"{{8,8,8},{8,8,8},{8,8,8}}")
(2,"{{80,80,80},{80,80,80},{80,80,80}}")
(1,"{{9,9,9},{9,9,9},{9,9,9}}")
(2,"{{90,90,90},{90,90,90},{90,90,90}}")
(18 rows)

```

```

WITH foo AS (
  SELECT ST_AddBand(ST_AddBand(ST_MakeEmptyRaster(3, 3, 0, 0, 1, -1, 0, 0, 0), 1, '8BUI', ←
    1, 0), 2, '8BUI', 10, 0) AS rast UNION ALL
  SELECT ST_AddBand(ST_AddBand(ST_MakeEmptyRaster(3, 3, 3, 0, 1, -1, 0, 0, 0), 1, '8BUI', ←
    2, 0), 2, '8BUI', 20, 0) AS rast UNION ALL
  SELECT ST_AddBand(ST_AddBand(ST_MakeEmptyRaster(3, 3, 6, 0, 1, -1, 0, 0, 0), 1, '8BUI', ←
    3, 0), 2, '8BUI', 30, 0) AS rast UNION ALL

  SELECT ST_AddBand(ST_AddBand(ST_MakeEmptyRaster(3, 3, 0, -3, 1, -1, 0, 0, 0), 1, '8BUI' ←
    ', 4, 0), 2, '8BUI', 40, 0) AS rast UNION ALL
  SELECT ST_AddBand(ST_AddBand(ST_MakeEmptyRaster(3, 3, 3, -3, 1, -1, 0, 0, 0), 1, '8BUI' ←
    ', 5, 0), 2, '8BUI', 50, 0) AS rast UNION ALL
  SELECT ST_AddBand(ST_AddBand(ST_MakeEmptyRaster(3, 3, 6, -3, 1, -1, 0, 0, 0), 1, '8BUI' ←
    ', 6, 0), 2, '8BUI', 60, 0) AS rast UNION ALL

  SELECT ST_AddBand(ST_AddBand(ST_MakeEmptyRaster(3, 3, 0, -6, 1, -1, 0, 0, 0), 1, '8BUI' ←
    ', 7, 0), 2, '8BUI', 70, 0) AS rast UNION ALL
  SELECT ST_AddBand(ST_AddBand(ST_MakeEmptyRaster(3, 3, 3, -6, 1, -1, 0, 0, 0), 1, '8BUI' ←
    ', 8, 0), 2, '8BUI', 80, 0) AS rast UNION ALL
  SELECT ST_AddBand(ST_AddBand(ST_MakeEmptyRaster(3, 3, 6, -6, 1, -1, 0, 0, 0), 1, '8BUI' ←
    ', 9, 0), 2, '8BUI', 90, 0) AS rast
), bar AS (
  SELECT ST_Union(rast) AS rast FROM foo
), baz AS (
  SELECT ST_Tile(rast, 3, 3, 2) AS rast FROM bar
)
SELECT
  ST_DumpValues(rast)
FROM baz;

```

st_dumpvalues

```

-----
(1,"{{10,10,10},{10,10,10},{10,10,10}}")
(1,"{{20,20,20},{20,20,20},{20,20,20}}")
(1,"{{30,30,30},{30,30,30},{30,30,30}}")
(1,"{{40,40,40},{40,40,40},{40,40,40}}")
(1,"{{50,50,50},{50,50,50},{50,50,50}}")
(1,"{{60,60,60},{60,60,60},{60,60,60}}")
(1,"{{70,70,70},{70,70,70},{70,70,70}}")
(1,"{{80,80,80},{80,80,80},{80,80,80}}")

```

```
(1, "{90,90,90},{90,90,90},{90,90,90}")
(9 rows)
```

☐☐

[ST_Union](#), [ST_Retile](#)

11.3.7 ST_Retile

`ST_Retile` — 将栅格重采样为指定的宽度和高度。

Synopsis

SETOF raster **ST_Retile**(regclass tab, name col, geometry ext, float8 sfx, float8 sfy, int tw, int th, text algo='NearestNeighbor');

☐☐

`sfx` (`sfx`) 和 `sfy` (`sfy`) 指定栅格在 x 和 y 方向上的缩放因子。 `tw` (`tw`) 和 `th` (`th`) 指定栅格在 x 和 y 方向上的宽度。 `tab` (`tab`) 和 `col` (`col`) 指定栅格的表名和列名。 `ext` (`ext`) 指定栅格的几何类型。

`algo` 指定重采样方法。支持的选项有：'NearestNeighbor', 'Bilinear', 'Cubic', 'CubicSpline', 和 'Lanczos'。默认值为 'NearestNeighbor'。有关更多选项，请参阅 [GDAL Warp resampling methods](#)。

2.2.0 版本引入。

☐☐

[ST_CreateOverview](#)

11.3.8 ST_FromGDALRaster

`ST_FromGDALRaster` — 从 GDAL 数据集创建栅格。

Synopsis

raster **ST_FromGDALRaster**(bytea gdaldata, integer srid=NULL);

☐☐

`gdaldata` 是 GDAL 数据集的字节数据。 `gdaldata` 是 bytea 类型的 GDAL 数据集的字节数据。

`srid` 是 SRID 的整数。如果 `srid` 为 NULL，则使用 GDAL 数据集的 SRID。如果 `srid` 不为 NULL，则使用指定的 SRID。

2.1.0 版本引入。

例

```
WITH foo AS (
  SELECT ST_AsPNG(ST_AddBand(ST_AddBand(ST_AddBand(ST_MakeEmptyRaster(2, 2, 0, 0, 0.1, ←
    -0.1, 0, 0, 4326), 1, '8BUI', 1, 0), 2, '8BUI', 2, 0), 3, '8BUI', 3, 0)) AS png
),
bar AS (
  SELECT 1 AS rid, ST_FromGDALRaster(png) AS rast FROM foo
  UNION ALL
  SELECT 2 AS rid, ST_FromGDALRaster(png, 3310) AS rast FROM foo
)
SELECT
  rid,
  ST_Metadata(rast) AS metadata,
  ST_SummaryStats(rast, 1) AS stats1,
  ST_SummaryStats(rast, 2) AS stats2,
  ST_SummaryStats(rast, 3) AS stats3
FROM bar
ORDER BY rid;
```

rid	metadata	stats1	stats2	stats3
1	(0,0,2,2,1,-1,0,0,0,3)	(4,4,1,0,1,1)	(4,8,2,0,2,2)	(4,12,3,0,3,3)
2	(0,0,2,2,1,-1,0,0,3310,3)	(4,4,1,0,1,1)	(4,8,2,0,2,2)	(4,12,3,0,3,3)

(2 rows)

例

ST_AsGDALRaster

11.4 栅格函数 (accessor)

11.4.1 ST_GeoReference

ST_GeoReference — 返回 (world) 坐标参考系统信息。GDAL 或 ESRI 格式。返回 GDAL 格式。

Synopsis

text **ST_GeoReference**(raster rast, text format=GDAL);

例

ST_GeoReference 返回, 返回 (carriage) 坐标参考系统信息。GDAL 或 ESRI 格式。返回 GDAL 格式。返回 'GDAL' 或 'ESRI' 格式。

返回格式:

GDAL:

```
scalex
skewy
skewx
scaley
```

```
upperleftx
upperlefty
```

ESRI:

```
scalex
skewy
skewx
scaley
upperleftx + scalex*0.5
upperlefty + scaley*0.5
```

例

```
SELECT ST_GeoReference(rast, 'ESRI') As esri_ref, ST_GeoReference(rast, 'GDAL') As gdal_ref
FROM dummy_rast WHERE rid=1;
```

esri_ref	gdal_ref
2.0000000000	2.0000000000
0.0000000000	0.0000000000
0.0000000000	0.0000000000
3.0000000000	3.0000000000
1.5000000000	0.5000000000
2.0000000000	0.5000000000

例

ST_SetGeoReference, ST_ScaleX, ST_ScaleY

11.4.2 ST_Height

ST_Height — 返回栅格的垂直高度。

Synopsis

integer **ST_Height**(raster rast);

例

返回栅格的高度。

例

```
SELECT rid, ST_Height(rast) As rastheight
FROM dummy_rast;
```

rid	rastheight
1	20
2	5

返回

ST_Width

11.4.3 ST_IsEmpty

ST_IsEmpty — 返回一个空栅格 (width = 0, height = 0) 的布尔值。返回 true 表示空栅格。

Synopsis

boolean **ST_IsEmpty**(raster rast);

返回

返回一个空栅格 (width = 0, height = 0) 的布尔值。返回 true 表示空栅格。
2.0.0 版本引入。

返回

```
SELECT ST_IsEmpty(ST_MakeEmptyRaster(100, 100, 0, 0, 0, 0, 0, 0, 0))
st_isempty |
-----+
f          |

SELECT ST_IsEmpty(ST_MakeEmptyRaster(0, 0, 0, 0, 0, 0, 0, 0, 0))
st_isempty |
-----+
t          |
```

返回

ST_HasNoBand

11.4.4 ST_MemSize

ST_MemSize — 返回一个栅格占用的内存大小 (以字节为单位)。

Synopsis

integer **ST_MemSize**(raster rast);

1		0.5		0.5		10		20		2		3		0		0		0		↵
2		3427927.75		5793244		5		5		0.05		-0.05		0		0		0		↵
		0																		
		3																		

[ST_BandMetaData](#), [ST_NumBands](#)

11.4.6 ST_NumBands

ST_NumBands — 返回栅格的波段数。

Synopsis

integer **ST_NumBands**(raster rast);

返回栅格的波段数。

```
SELECT rid, ST_NumBands(rast) As numbands
FROM dummy_rast;
```

rid	numbands
1	0
2	3

[ST_Value](#)

11.4.7 ST_PixelHeight

ST_PixelHeight — 返回栅格的像素高度。

Synopsis

double precision **ST_PixelHeight**(raster rast);

返回栅格的像素高度。如果栅格是 3D 的，则返回高度值。如果栅格是 2D 的，则返回像素高度。

返回栅格的像素高度。如果栅格是 3D 的，则返回高度值。如果栅格是 2D 的，则返回像素高度。 [ST_PixelWidth](#) 返回像素宽度。

例: 获取栅格属性

```
SELECT ST_Height(rast) As rastheight, ST_PixelHeight(rast) As pixheight,
       ST_ScaleX(rast) As scalex, ST_ScaleY(rast) As scaley, ST_SkewX(rast) As skewx,
       ST_SkewY(rast) As skewy
FROM dummy_rast;
```

rastheight	pixheight	scalex	scaley	skewx	skewy
20	3	2	3	0	0
5	0.05	0.05	-0.05	0	0

例: 0 度旋转栅格

```
SELECT ST_Height(rast) As rastheight, ST_PixelHeight(rast) As pixheight,
       ST_ScaleX(rast) As scalex, ST_ScaleY(rast) As scaley, ST_SkewX(rast) As skewx,
       ST_SkewY(rast) As skewy
FROM (SELECT ST_SetSKew(rast,0.5,0.5) As rast
      FROM dummy_rast) As skewed;
```

rastheight	pixheight	scalex	scaley	skewx	skewy
20	3.04138126514911	2	3	0.5	0.5
5	0.502493781056044	0.05	-0.05	0.5	0.5

例

[ST_PixelWidth](#), [ST_ScaleX](#), [ST_ScaleY](#), [ST_SkewX](#), [ST_SkewY](#)

11.4.8 ST_PixelWidth

`ST_PixelWidth` — 返回栅格的像素宽度。


Synopsis

double precision **ST_PixelWidth**(raster rast);

例

返回栅格的像素宽度。对于非正方形栅格，返回的像素宽度与像素高度不同。

对于正方形栅格，返回的像素宽度与像素高度相同。



i : 单位向量
 j : 单位向量

例: 设置偏斜

```
SELECT ST_Width(rast) As rastwidth, ST_PixelWidth(rast) As pixwidth,
       ST_ScaleX(rast) As scalex, ST_ScaleY(rast) As scaley, ST_SkewX(rast) As skewx,
       ST_SkewY(rast) As skewy
FROM dummy_rast;
```

rastwidth	pixwidth	scalex	scaley	skewx	skewy
10	2	2	3	0	0
5	0.05	0.05	-0.05	0	0

例: 0 偏斜

```
SELECT ST_Width(rast) As rastwidth, ST_PixelWidth(rast) As pixwidth,
       ST_ScaleX(rast) As scalex, ST_ScaleY(rast) As scaley, ST_SkewX(rast) As skewx,
       ST_SkewY(rast) As skewy
FROM (SELECT ST_SetSkew(rast,0.5,0.5) As rast
      FROM dummy_rast) As skewed;
```

rastwidth	pixwidth	scalex	scaley	skewx	skewy
10	2.06155281280883	2	3	0.5	0.5
5	0.502493781056044	0.05	-0.05	0.5	0.5

函数

[ST_PixelHeight](#), [ST_ScaleX](#), [ST_ScaleY](#), [ST_SkewX](#), [ST_SkewY](#)

11.4.9 ST_ScaleX

ST_ScaleX — 将栅格的 X 轴像素大小缩放为指定的值。

Synopsis

float8 **ST_ScaleX**(raster rast);

返回

返回栅格的 X 轴像素大小。如果指定的值不为 1，则返回的像素大小将乘以指定的缩放因子。
版本: 2.0.0 在 WKTRaster 中通过 ST_PixelSizeX 函数实现。

示例

```
SELECT rid, ST_ScaleX(rast) As rastpixwidth
FROM dummy_rast;
```

rid	rastpixwidth
1	2
2	0.05

注意

ST_Width

11.4.10 ST_ScaleY

ST_ScaleY — 将栅格的 Y 轴像素大小缩放为指定的值。

Synopsis

float8 **ST_ScaleY**(raster rast);

返回

返回栅格的 Y 轴像素大小。如果指定的值不为 1，则返回的像素大小将乘以指定的缩放因子。
版本: 2.0.0 在 WKTRaster 中通过 ST_PixelSizeY 函数实现。

示例

```
SELECT rid, ST_ScaleY(rast) As rastpixheight
FROM dummy_rast;
```

rid	rastpixheight
1	3
2	-0.05

函数

ST_Height

11.4.11 ST_RasterToWorldCoord

ST_RasterToWorldCoord — 给定栅格像素的 X, Y(列, 行) 返回地理坐标。
返回类型: geometry。 1 个参数。

Synopsis

record **ST_RasterToWorldCoord**(raster rast, integer xcolumn, integer yrow);

函数

给定栅格像素的 X, Y(列, 行) 返回地理坐标。 参数 X, Y 是栅格像素的列和行。 默认值 1 表示第一列，0 表示第一行。 返回类型是 geometry。 2.1.0 版本引入。

2.1.0 版本引入。

函数

```
-- non-skewed raster
SELECT
  rid,
  (ST_RasterToWorldCoord(rast,1, 1)).*,
  (ST_RasterToWorldCoord(rast,2, 2)).*
FROM dummy_rast
```

rid	longitude	latitude	longitude	latitude
1	0.5	0.5	2.5	3.5
2	3427927.75	5793244	3427927.8	5793243.95

```
-- skewed raster
SELECT
  rid,
  (ST_RasterToWorldCoord(rast, 1, 1)).*,
  (ST_RasterToWorldCoord(rast, 2, 3)).*
FROM (
  SELECT
    rid,
    ST_SetSkew(rast, 100.5, 0) As rast
  FROM dummy_rast
) As foo
```

rid	longitude	latitude	longitude	latitude
1	0.5	0.5	203.5	6.5
2	3427927.75	5793244	3428128.8	5793243.9

函数

[ST_RasterToWorldCoordX](#), [ST_RasterToWorldCoordY](#), [ST_SetSkew](#)

11.4.12 ST_RasterToWorldCoordX

`ST_RasterToWorldCoordX` — 给定栅格和列索引，返回该列的 X 世界坐标。返回类型是 `float8`。

Synopsis

```
float8 ST_RasterToWorldCoordX(raster rast, integer xcolumn);
float8 ST_RasterToWorldCoordX(raster rast, integer xcolumn, integer yrow);
```

函数

给定栅格和列索引，返回该列的 X 世界坐标。返回类型是 `float8`。如果提供了行索引，则返回该像素的世界坐标。否则，返回该列的 X 世界坐标。



Note

如果提供了行索引，则返回该像素的世界坐标。否则，返回该列的 X 世界坐标。使用 `ST_ScaleX`, `ST_SkewX`, 和 `ST_SetSkew` 函数可以设置栅格的 X 世界坐标。

注意: 2.1.0 版本之前，`ST_Raster2WorldCoordX` 函数已经弃用。

函数

```
-- non-skewed raster providing column is sufficient
SELECT rid, ST_RasterToWorldCoordX(rast,1) As xlcoord,
       ST_RasterToWorldCoordX(rast,2) As x2coord,
       ST_ScaleX(rast) As pixelx
FROM dummy_rast;
```

rid	xlcoord	x2coord	pixelx
1	0.5	2.5	2
2	3427927.75	3427927.8	0.05

```
-- for fun lets skew it
SELECT rid, ST_RasterToWorldCoordX(rast, 1, 1) As xlcoord,
       ST_RasterToWorldCoordX(rast, 2, 3) As x2coord,
       ST_ScaleX(rast) As pixelx
FROM (SELECT rid, ST_SetSkew(rast, 100.5, 0) As rast FROM dummy_rast) As foo;
```

rid	xlcoord	x2coord	pixelx
1	0.5	203.5	2
2	3427927.75	3428128.8	0.05

函数

[ST_ScaleX](#), [ST_RasterToWorldCoordY](#), [ST_SetSkew](#), [ST_SkewX](#)

11.4.13 ST_RasterToWorldCoordY

`ST_RasterToWorldCoordY` — 给定栅格和行号 Y 的坐标。返回 1 个浮点值。

Synopsis

```
float8 ST_RasterToWorldCoordY(raster rast, integer yrow);
float8 ST_RasterToWorldCoordY(raster rast, integer xcolumn, integer yrow);
```

函数

给定栅格和行号 Y 的坐标。返回 1 个浮点值。如果提供了 xcolumn，则返回 xcolumn 和 yrow 的坐标。否则，返回 yrow 的坐标。



Note

如果提供了 xcolumn，Y 坐标将返回 xcolumn 和 yrow 的坐标。否则，返回 yrow 的坐标。ST_ScaleY, ST_SkewY, 函数返回 Y 坐标。

注意: 2.1.0 版本中 ST_Raster2WorldCoordY 函数已弃用。

函数

```
-- non-skewed raster providing row is sufficient
SELECT rid, ST_RasterToWorldCoordY(rast,1) As ylcoord,
       ST_RasterToWorldCoordY(rast,3) As y2coord,
       ST_ScaleY(rast) As pixely
FROM dummy_rast;
```

rid	ylcoord	y2coord	pixely
1	0.5	6.5	3
2	5793244	5793243.9	-0.05

```
-- for fun lets skew it
SELECT rid, ST_RasterToWorldCoordY(rast,1,1) As ylcoord,
       ST_RasterToWorldCoordY(rast,2,3) As y2coord,
       ST_ScaleY(rast) As pixely
FROM (SELECT rid, ST_SetSkew(rast,0,100.5) As rast FROM dummy_rast) As foo;
```

rid	ylcoord	y2coord	pixely
1	0.5	107	3
2	5793244	5793344.4	-0.05

[ST_ScaleY](#), [ST_RasterToWorldCoordX](#), [ST_SetSkew](#), [ST_SkewY](#)

11.4.14 ST_Rotation

`ST_Rotation` — 返回栅格的旋转角度。

Synopsis

`float8 ST_Rotation(raster rast);`

返回栅格的旋转角度。如果栅格是正交的，则返回 0。如果栅格是 45 度旋转的，则返回 0.785398163397448。NaN 表示未知。如果栅格是 45 度旋转的，则返回 0.785398163397448。

```
SELECT rid, ST_Rotation(ST_SetScale(ST_SetSkew(rast, sqrt(2)), sqrt(2))) as rot FROM dummy_rast;
```

rid	rot
1	0.785398163397448
2	0.785398163397448

[ST_SetRotation](#), [ST_SetScale](#), [ST_SetSkew](#)

11.4.15 ST_SkewX

`ST_SkewX` — 返回栅格的 X 轴偏斜 (skew) 角度。

Synopsis

`float8 ST_SkewX(raster rast);`

返回栅格的 X 轴偏斜 (skew) 角度。如果栅格是正交的，则返回 0。如果栅格是 45 度偏斜的，则返回 0.785398163397448。

例

```
SELECT rid, ST_SkewX(rast) As skewx, ST_SkewY(rast) As skewy,
       ST_GeoReference(rast) as georef
FROM dummy_rast;
```

rid	skewx	skewy	georef
1	0	0	2.0000000000
			: 0.0000000000
			: 0.0000000000
			: 3.0000000000
			: 0.5000000000
			: 0.5000000000
2	0	0	: 0.0500000000
			: 0.0000000000
			: 0.0000000000
			: -0.0500000000
			: 3427927.7500000000
			: 5793244.0000000000

例

[ST_GeoReference](#), [ST_SkewY](#), [ST_SetSkew](#)

11.4.16 ST_SkewY

ST_SkewY — 返回栅格 Y 轴偏斜 (以度为单位) 的浮点值。

Synopsis

float8 **ST_SkewY**(raster rast);

例

返回栅格 Y 轴偏斜 (以度为单位) 的浮点值。返回值为 0.0000000000。

例

```
SELECT rid, ST_SkewX(rast) As skewx, ST_SkewY(rast) As skewy,
       ST_GeoReference(rast) as georef
FROM dummy_rast;
```

rid	skewx	skewy	georef
1	0	0	2.0000000000
			: 0.0000000000
			: 0.0000000000
			: 3.0000000000
			: 0.5000000000
			: 0.5000000000
			: 0.0500000000
			: 0.0000000000
			: 0.0000000000
			: -0.0500000000
			: 3427927.7500000000
			: 5793244.0000000000

```
2 |      0 |      0 | 0.050000000000
  |      |      |      | : 0.000000000000
  |      |      |      | : 0.000000000000
  |      |      |      | : -0.050000000000
  |      |      |      | : 3427927.750000000000
  |      |      |      | : 5793244.000000000000
```



ST GeoReference, ST SkewX, ST SetSkew

11.4.17 ST_SRID

ST SRID — spatial ref sys , .

Synopsis

```
integer ST_SRID(raster rast);
```



spatial ref sys , .



Note

Note: PostGIS 2.0 uses SRID -1 as the default SRID.



```
SELECT ST_SRID(rast) As srid
FROM dummy rast WHERE rid=1;
```

```
srid
-----
0
```



Section 4.5, ST_SRID

11.4.18 ST_Summary

ST Summary — □□□□□□□□□□□□□□□□.

Synopsis

```
text ST_Summary(raster rast);
```


图例

[ST_UpperLeftY](#), [ST_GeoReference](#), [Box3D](#)

11.4.20 ST_UpperLeftY

`ST_UpperLeftY` — 返回栅格的 Y 坐标。

Synopsis

`float8 ST_UpperLeftY(raster rast);`

图例

返回栅格的 Y 坐标。

图例

```
SELECT rid, ST_UpperLeftY(rast) As uly
FROM dummy_rast;
```

rid	uly
1	0.5
2	5793244

图例

[ST_UpperLeftX](#), [ST_GeoReference](#), [Box3D](#)

11.4.21 ST_Width

`ST_Width` — 返回栅格的宽度。

Synopsis

`integer ST_Width(raster rast);`

图例

返回栅格的宽度。

例

```
SELECT ST_Width(rast) As rastwidth
FROM dummy_rast WHERE rid=1;

rastwidth
-----
10
```

例

ST_Height

11.4.22 ST_WorldToRasterCoord

ST_WorldToRasterCoord — 给定 X, Y(经度, 纬度) 返回栅格中的列和行索引。

Synopsis

record **ST_WorldToRasterCoord**(raster rast, geometry pt);
record **ST_WorldToRasterCoord**(raster rast, double precision longitude, double precision latitude);

例

给定 X, Y(经度, 纬度) 返回栅格中的列和行索引。给定 X, Y 返回栅格中的列和行索引。给定 X, Y 返回栅格中的列和行索引。

2.1.0 版本引入。

例

```
SELECT
    rid,
    (ST_WorldToRasterCoord(rast,3427927.8,20.5)).*,
    (ST_WorldToRasterCoord(rast,ST_GeomFromText('POINT(3427927.8 20.5)',ST_SRID(rast)))).*
FROM dummy_rast;

rid | columnx | rowy | columnx | rowy
-----+-----+-----+-----+-----
1 | 1713964 | 7 | 1713964 | 7
2 | 2 | 115864471 | 2 | 115864471
```

例

ST_WorldToRasterCoordX, ST_WorldToRasterCoordY, ST_RasterToWorldCoordX, ST_RasterToWorldCoordY, ST_SRID

11.4.23 ST_WorldToRasterCoordX

`ST_WorldToRasterCoordX` — 给定 (pt) 的 X, Y 坐标 (xw, yw)。

Synopsis

```
integer ST_WorldToRasterCoordX(raster rast, geometry pt);
integer ST_WorldToRasterCoordX(raster rast, double precision xw);
integer ST_WorldToRasterCoordX(raster rast, double precision xw, double precision yw);
```

给定 (pt) 的 X, Y 坐标 (xw, yw)。 给定 (xw, yw) 坐标 (xw, yw) 的 X 坐标。 给定 (xw, yw) 坐标 (xw, yw) 的 Y 坐标。 给定 (xw, yw) 坐标 (xw, yw) 的 X 坐标。 给定 (xw, yw) 坐标 (xw, yw) 的 Y 坐标。

版本: 2.1.0 添加 `ST_World2RasterCoordX`。

```
SELECT rid, ST_WorldToRasterCoordX(rast,3427927.8) As xcoord,
       ST_WorldToRasterCoordX(rast,3427927.8,20.5) As xcoord_xwyw,
       ST_WorldToRasterCoordX(rast,ST_GeomFromText(' POINT(3427927.8 20.5)',ST_SRID(rast))) As ptxcoord
FROM dummy_rast;
```

rid	xcoord	xcoord_xwyw	ptxcoord
1	1713964	1713964	1713964
2	1	1	1

[ST_RasterToWorldCoordX](#), [ST_RasterToWorldCoordY](#), [ST_SRID](#)

11.4.24 ST_WorldToRasterCoordY

`ST_WorldToRasterCoordY` — 给定 (pt) 的 X, Y 坐标 (xw, yw)。

Synopsis

```
integer ST_WorldToRasterCoordY(raster rast, geometry pt);
integer ST_WorldToRasterCoordY(raster rast, double precision xw);
integer ST_WorldToRasterCoordY(raster rast, double precision xw, double precision yw);
```




Note
If `isoutdb` is `False`, `path`, `outdbbandnum`, `filesize` and `filetimestamp` are `NULL`. If `outdb` access is disabled, `filesize` and `filetimestamp` will also be `NULL`.

Enhanced: 2.5.0 to include *outdbbandnum*, *filesize* and *filetimestamp* for `outdb` rasters.

例: 例 1

```
SELECT
  rid,
  (foo.md).*
FROM (
  SELECT
    rid,
    ST_BandMetaData(rast, 1) AS md
  FROM dummy_rast
  WHERE rid=2
) As foo;
```

rid	pixeltype	nodatavalue	isoutdb	path	outdbbandnum
2	8BUI		0	f	

例: 例 2

```
WITH foo AS (
  SELECT
    ST_AddBand(NULL::raster, '/home/pele/devel/geo/postgis-git/raster/test/regress/ ↵
    loader/Projected.tif', NULL::int[]) AS rast
)
SELECT
  *
FROM ST_BandMetadata(
  (SELECT rast FROM foo),
  ARRAY[1,3,2]::int[]
);
```

bandnum	pixeltype	nodatavalue	isoutdb	outdbbandnum	filesize	filetimestamp	path ↵
1	8BUI		t				/home/pele/devel/geo/postgis-git/raster/test ↵ /regress/loader/Projected.tif
3	8BUI		t				/home/pele/devel/geo/postgis-git/raster/test ↵ /regress/loader/Projected.tif
2	8BUI		t				/home/pele/devel/geo/postgis-git/raster/test ↵ /regress/loader/Projected.tif



ST_MetaData, ST_BandPixelType

11.5.2 ST_BandNoDataValue

`ST_BandNoDataValue` — 返回指定 NODATA 值的栅格带的值。返回值的范围是 1 到 255。

Synopsis

double precision **ST_BandNoDataValue**(raster rast, integer bandnum=1);

返回

返回 NODATA 值的栅格带的值。

返回

```
SELECT ST_BandNoDataValue(rast,1) As bnval1,
       ST_BandNoDataValue(rast,2) As bnval2, ST_BandNoDataValue(rast,3) As bnval3
FROM dummy_rast
WHERE rid = 2;
```

bnval1	bnval2	bnval3
0	0	0

返回

ST_NumBands

11.5.3 ST_BandIsNoData

`ST_BandIsNoData` — 返回指定 NODATA 值的栅格带的值。

Synopsis

boolean **ST_BandIsNoData**(raster rast, integer band, boolean forceChecking=true);
boolean **ST_BandIsNoData**(raster rast, boolean forceChecking=true);

返回

返回 NODATA 值的栅格带的值。返回值的范围是 1 到 255。如果返回 TRUE，则表示该值在 NODATA 范围内。如果返回 FALSE，则表示该值不在 NODATA 范围内。

2.0.0 版本引入。

Note



在 2.0.0 版本中，`ST_BandIsNoData` 函数在默认情况下返回 TRUE。如果希望返回 FALSE，可以使用 `ST_SetBandIsNoData` 函数。例如，`ST_SetBandIsNoData(rast, 1, TRUE)` 将第一个带的 NODATA 值设置为 TRUE。使用 `ST_SetBandIsNoData` 函数时，需要指定要设置的带的编号。例如，`ST_SetBandIsNoData(rast, 1, TRUE)` 将第一个带的 NODATA 值设置为 TRUE。

❏❏

```
-- Create dummy table with one raster column
create table dummy_rast (rid integer, rast raster);

-- Add raster with two bands, one pixel/band. In the first band, nodatavalue = pixel value ←
  = 3.
-- In the second band, nodatavalue = 13, pixel value = 4
insert into dummy_rast values(1,
(
'01' -- little endian (uint8 ndr)
||
'0000' -- version (uint16 0)
||
'0200' -- nBands (uint16 0)
||
'17263529ED684A3F' -- scaleX (float64 0.000805965234044584)
||
'F9253529ED684ABF' -- scaleY (float64 -0.00080596523404458)
||
'1C9F33CE69E352C0' -- ipX (float64 -75.5533328537098)
||
'718F0E9A27A44840' -- ipY (float64 49.2824585505576)
||
'ED50EB853EC32B3F' -- skewX (float64 0.000211812383858707)
||
'7550EB853EC32B3F' -- skewY (float64 0.000211812383858704)
||
'E6100000' -- SRID (int32 4326)
||
'0100' -- width (uint16 1)
||
'0100' -- height (uint16 1)
||
'6' -- hasnodatavalue and isnodata value set to true.
||
'2' -- first band type (4BUI)
||
'03' -- novalue==3
||
'03' -- pixel(0,0)==3 (same that nodata)
||
'0' -- hasnodatavalue set to false
||
'5' -- second band type (16BSI)
||
'0D00' -- novalue==13
||
'0400' -- pixel(0,0)==4
)::raster
);

select st_bandisnodata(rast, 1) from dummy_rast where rid = 1; -- Expected true
select st_bandisnodata(rast, 2) from dummy_rast where rid = 1; -- Expected false
```

❏❏

ST_BandNoDataValue, ST_NumBands, ST_SetBandNoDataValue, ST_SetBandIsNoData

11.5.4 ST_BandPath

`ST_BandPath` — 返回指定栅格带的文件路径。 `bandnum` 指定要返回的带的编号，默认为 1。

Synopsis

text **ST_BandPath**(raster rast, integer bandnum=1);

返回

指定栅格带的文件路径。 DB 指定要返回的带的编号，默认为 1。

返回

返回

11.5.5 ST_BandFileSize

`ST_BandFileSize` — 返回存储在文件系统中的带的文件大小。如果未指定 `bandnum`，则默认为 1。

Synopsis

bigint **ST_BandFileSize**(raster rast, integer bandnum=1);

返回

返回存储在文件系统中的带的文件大小。如果调用时在数据库带中，或如果 outdb 访问未启用，则抛出错误。

此函数通常与 `ST_BandPath()` 和 `ST_BandFileTimestamp()` 一起使用，以便客户端可以确定在 outdb 栅格中看到的文件名是否与服务器看到的相同。

Availability: 2.5.0

返回

```
SELECT ST_BandFileSize(rast,1) FROM dummy_rast WHERE rid = 1;
```

```
st_bandfilesize
-----
240574
```

11.5.6 ST_BandFileTimestamp

ST_BandFileTimestamp — Returns the file timestamp of a band stored in file system. If no bandnum specified, 1 is assumed.

Synopsis

bigint **ST_BandFileTimestamp**(raster rast, integer bandnum=1);

返回

Returns the file timestamp (number of seconds since Jan 1st 1970 00:00:00 UTC) of a band stored in file system. Throws an error if called with an in db band, or if outdb access is not enabled.

This function is typically used in conjunction with ST_BandPath() and ST_BandFileSize() so a client can determine if the filename of a outdb raster as seen by it is the same as the one seen by the server.

Availability: 2.5.0

返回

```
SELECT ST_BandFileTimestamp(rast,1) FROM dummy_rast WHERE rid = 1;
```

```
st_bandfiletimestamp
-----
1521807257
```

11.5.7 ST_BandPixelType

ST_BandPixelType — 返回指定栅格的像素数据类型。bandnum 指定要查询的波段，默认为 1。

Synopsis

text **ST_BandPixelType**(raster rast, integer bandnum=1);

返回

Returns name describing data type and size of values stored in each cell of given band.

11 返回的字符串格式为：`bandnum 数据类型 大小`。

- 1BB - 1 字节
- 2BUI - 2 字节的无符号整数
- 4BUI - 4 字节的无符号整数
- 8BSI - 8 字节的有符号整数
- 8BUI - 8 字节的无符号整数
- 16BSI - 16 字节的有符号整数
- 16BUI - 16 字节的无符号整数

- 32BSI - 32 有符号整数
- 32BUI - 32 无符号整数
- 32BF - 32 浮点
- 64BF - 64 浮点

例

```
SELECT ST_BandPixelType(rast,1) As btype1,
       ST_BandPixelType(rast,2) As btype2, ST_BandPixelType(rast,3) As btype3
FROM dummy_rast
WHERE rid = 2;
```

btype1	btype2	btype3
8BUI	8BUI	8BUI

例

ST_NumBands

11.5.8 ST_MinPossibleValue

ST_MinPossibleValue — 返回像素类型的可能的最小值。

Synopsis

```
integer ST_MinPossibleValue(text pixeltype);
```

例

返回 16 位有符号整数的可能的最小值。

例

```
SELECT ST_MinPossibleValue('16BSI');

 st_minpossiblevalue
-----
                -32768

SELECT ST_MinPossibleValue('8BUI');

 st_minpossiblevalue
-----
                   0
```

ST_BandPixelType

11.5.9 ST_HasNoBand

ST_HasNoBand — 检查栅格是否具有指定的波段。如果具有指定的波段，则返回 1，否则返回 0。

Synopsis

boolean **ST_HasNoBand**(raster rast, integer bandnum=1);

检查栅格是否具有指定的波段。如果具有指定的波段，则返回 1，否则返回 0。
2.0.0 版本引入。

```
SELECT rid, ST_HasNoBand(rast) As hb1, ST_HasNoBand(rast,2) as hb2,
ST_HasNoBand(rast,4) as hb4, ST_NumBands(rast) As numbands
FROM dummy_rast;
```

rid	hb1	hb2	hb4	numbands
1	t	t	t	0
2	f	f	t	3

ST_NumBands

11.6 栅格操作函数 (setter)

11.6.1 ST_PixelAsPolygon

ST_PixelAsPolygon — 将栅格像素转换为多边形。

Synopsis

geometry **ST_PixelAsPolygon**(raster rast, integer columnx, integer rowy);

将栅格像素转换为多边形。
2.0.0 版本引入。

例

```
-- get raster pixel polygon
SELECT i,j, ST_AsText(ST_PixelAsPolygon(foo.rast, i,j)) As b1pgeom
FROM dummy_rast As foo
      CROSS JOIN generate_series(1,2) As i
      CROSS JOIN generate_series(1,1) As j
WHERE rid=2;
```

i	j	b1pgeom
1	1	POLYGON((3427927.75 5793244,3427927.8 5793244,3427927.8 5793243.95,...
2	1	POLYGON((3427927.8 5793244,3427927.85 5793244,3427927.85 5793243.95, ..

例

[ST_DumpAsPolygons](#), [ST_PixelAsPolygons](#), [ST_PixelAsPoint](#), [ST_PixelAsPoints](#), [ST_PixelAsCentroid](#), [ST_PixelAsCentroids](#), [ST_Intersection](#), [ST_AsText](#)

11.6.2 ST_PixelAsPolygons

`ST_PixelAsPolygons` — 将栅格中的指定像素转换为多边形。X, Y 坐标为浮点型。

Synopsis

setof record **ST_PixelAsPolygons**(raster rast, integer band=1, boolean exclude_nodata_value=TRUE);

例

返回记录格式: *geom geometry*, *val* double precision, *x* integer, *y* integers.



Note

When `exclude_nodata_value = TRUE`, only those pixels whose values are not NODATA are returned as points.



Note

`ST_PixelAsPolygons` 返回的记录格式与 `ST_DumpAsPolygons` 返回的记录格式相同。

2.0.0 版本引入。

版本: 2.1.0 版本引入 `exclude_nodata_value` 参数。

版本: 2.1.1 版本引入 `exclude_nodata_value` 参数。

例

```
-- get raster pixel polygon
SELECT (gv).x, (gv).y, (gv).val, ST_AsText((gv).geom) geom
FROM (SELECT ST_PixelAsPolygons(
          ST_SetValue(ST_SetValue(ST_AddBand(ST_MakeEmptyRaster(2, 2, 0, 0, 0.001, ←
          -0.001, 0.001, 0.001, 4269),
          '8BUI'::text, 1, 0),
          2, 2, 10),
          1, 1, NULL)
) gv
) foo;
```

x	y	val	geom
1	1		POLYGON((0 0,0.001 0.001,0.002 0,0.001 -0.001,0 0))
1	2	1	POLYGON((0.001 -0.001,0.002 0,0.003 -0.001,0.002 -0.002,0.001 -0.001))
2	1	1	POLYGON((0.001 0.001,0.002 0.002,0.003 0.001,0.002 0,0.001 0.001))
2	2	10	POLYGON((0.002 0,0.003 0.001,0.004 0,0.003 -0.001,0.002 0))

例

[ST_DumpAsPolygons](#), [ST_PixelAsPolygon](#), [ST_PixelAsPoint](#), [ST_PixelAsPoints](#), [ST_PixelAsCentroid](#), [ST_PixelAsCentroids](#), [ST_AsText](#)

11.6.3 ST_PixelAsPoint

`ST_PixelAsPoint` — 从栅格中提取点几何。

Synopsis

geometry **ST_PixelAsPoint**(raster rast, integer columnx, integer rowy);

例

从栅格中提取点几何。

2.1.0 从栅格中提取点几何。

例

```
SELECT ST_AsText(ST_PixelAsPoint(rast, 1, 1)) FROM dummy_rast WHERE rid = 1;
```

st_astext
POINT(0.5 0.5)

例

[ST_DumpAsPolygons](#), [ST_PixelAsPolygon](#), [ST_PixelAsPolygons](#), [ST_PixelAsPoints](#), [ST_PixelAsCentroid](#), [ST_PixelAsCentroids](#)

11.6.4 ST_PixelAsPoints

`ST_PixelAsPoints` — 将栅格中的指定波段转换为点。返回包含 X, Y 坐标和像素值的表。

Synopsis

setof record **ST_PixelAsPoints**(raster rast, integer band=1, boolean exclude_nodata_value=TRUE);

返回

表包含以下列：x, y 坐标和像素值。返回格式为：geom geometry, val double precision, x integer, y integers。

Return record format: *geom* geometry, *val* double precision, *x* integer, *y* integers.



Note

When `exclude_nodata_value = TRUE`, only those pixels whose values are not NODATA are returned as points.

2.1.0 版本引入。

2.1.1 版本引入 `exclude_nodata_value` 参数。

返回

```
SELECT x, y, val, ST_AsText(geom) FROM (SELECT (ST_PixelAsPoints(rast, 1)).* FROM dummy_rast WHERE rid = 2) foo;
```

x	y	val	st_astext
1	1	253	POINT(3427927.75 5793244)
2	1	254	POINT(3427927.8 5793244)
3	1	253	POINT(3427927.85 5793244)
4	1	254	POINT(3427927.9 5793244)
5	1	254	POINT(3427927.95 5793244)
1	2	253	POINT(3427927.75 5793243.95)
2	2	254	POINT(3427927.8 5793243.95)
3	2	254	POINT(3427927.85 5793243.95)
4	2	253	POINT(3427927.9 5793243.95)
5	2	249	POINT(3427927.95 5793243.95)
1	3	250	POINT(3427927.75 5793243.9)
2	3	254	POINT(3427927.8 5793243.9)
3	3	254	POINT(3427927.85 5793243.9)
4	3	252	POINT(3427927.9 5793243.9)
5	3	249	POINT(3427927.95 5793243.9)
1	4	251	POINT(3427927.75 5793243.85)
2	4	253	POINT(3427927.8 5793243.85)
3	4	254	POINT(3427927.85 5793243.85)
4	4	254	POINT(3427927.9 5793243.85)
5	4	253	POINT(3427927.95 5793243.85)
1	5	252	POINT(3427927.75 5793243.8)
2	5	250	POINT(3427927.8 5793243.8)
3	5	254	POINT(3427927.85 5793243.8)
4	5	254	POINT(3427927.9 5793243.8)
5	5	254	POINT(3427927.95 5793243.8)

返回

[ST_DumpAsPolygons](#), [ST_PixelAsPolygon](#), [ST_PixelAsPolygons](#), [ST_PixelAsPoint](#), [ST_PixelAsCentroid](#), [ST_PixelAsCentroids](#)

11.6.5 ST_PixelAsCentroid

`ST_PixelAsCentroid` — 返回栅格像素 (x, y) 的几何体。

Synopsis

geometry **ST_PixelAsCentroid**(raster rast, integer x, integer y);

返回

返回栅格像素 (x, y) 的几何体。

版本: 2.1.0 引入 C 语言实现。

2.1.0 版本引入。

返回

```
SELECT ST_AsText(ST_PixelAsCentroid(rast, 1, 1)) FROM dummy_rast WHERE rid = 1;
```

```
st_astext
-----
POINT(1.5 2)
```

返回

[ST_DumpAsPolygons](#), [ST_PixelAsPolygon](#), [ST_PixelAsPolygons](#), [ST_PixelAsPoint](#), [ST_PixelAsPoints](#), [ST_PixelAsCentroids](#)

11.6.6 ST_PixelAsCentroids

`ST_PixelAsCentroids` — 返回栅格像素 (x, y) 的几何体 X, Y 坐标。

Synopsis

setof record **ST_PixelAsCentroids**(raster rast, integer band=1, boolean exclude_nodata_value=TRUE);

返回

返回记录格式: `geom geometry`, `val` double precision, `x` integer, `y` integers.



Note

When `exclude_nodata_value` = TRUE, only those pixels whose values are not NODATA are returned as points.

- 2.1.0 添加 C 语言支持。
- 2.1.1 添加 `exclude_nodata_value` 参数。
- 2.1.0 添加 `geom` 参数。

返回

```
--LATERAL syntax requires PostgreSQL 9.3+
SELECT x, y, val, ST_AsText(geom)
  FROM (SELECT dp.* FROM dummy_rast, LATERAL ST_PixelAsCentroids(rast, 1) AS dp WHERE rid <=
        = 2) foo;
```

x	y	val	st_astext
1	1	253	POINT(3427927.775 5793243.975)
2	1	254	POINT(3427927.825 5793243.975)
3	1	253	POINT(3427927.875 5793243.975)
4	1	254	POINT(3427927.925 5793243.975)
5	1	254	POINT(3427927.975 5793243.975)
1	2	253	POINT(3427927.775 5793243.925)
2	2	254	POINT(3427927.825 5793243.925)
3	2	254	POINT(3427927.875 5793243.925)
4	2	253	POINT(3427927.925 5793243.925)
5	2	249	POINT(3427927.975 5793243.925)
1	3	250	POINT(3427927.775 5793243.875)
2	3	254	POINT(3427927.825 5793243.875)
3	3	254	POINT(3427927.875 5793243.875)
4	3	252	POINT(3427927.925 5793243.875)
5	3	249	POINT(3427927.975 5793243.875)
1	4	251	POINT(3427927.775 5793243.825)
2	4	253	POINT(3427927.825 5793243.825)
3	4	254	POINT(3427927.875 5793243.825)
4	4	254	POINT(3427927.925 5793243.825)
5	4	253	POINT(3427927.975 5793243.825)
1	5	252	POINT(3427927.775 5793243.775)
2	5	250	POINT(3427927.825 5793243.775)
3	5	254	POINT(3427927.875 5793243.775)
4	5	254	POINT(3427927.925 5793243.775)
5	5	254	POINT(3427927.975 5793243.775)

返回

`ST_DumpAsPolygons`, `ST_PixelAsPolygon`, `ST_PixelAsPolygons`, `ST_PixelAsPoint`, `ST_PixelAsPoints`, `ST_Pixel`

11.6.7 ST_Value

ST_Value — 返回 columnx, rowy 栅格中的值, 如果指定了 geometry pt, 则返回该点处的值。如果指定了 band 1, 则返回该带的值。exclude_nodata_value 如果为 true, 则当遇到 nodata 值时返回 null。exclude_nodata_value 如果为 false, 则当遇到 nodata 值时返回 0。

Synopsis

```
double precision ST_Value(raster rast, geometry pt, boolean exclude_nodata_value=true);
double precision ST_Value(raster rast, integer band, geometry pt, boolean exclude_nodata_value=true,
text resample='nearest');
double precision ST_Value(raster rast, integer x, integer y, boolean exclude_nodata_value=true);
double precision ST_Value(raster rast, integer band, integer x, integer y, boolean exclude_nodata_value=true);
```

参数

columnx, rowy 栅格中的列和行索引。如果指定了 geometry pt, 则返回该点处的值。如果指定了 band 1, 则返回该带的值。exclude_nodata_value 如果为 true, 则当遇到 nodata 值时返回 null。exclude_nodata_value 如果为 false, 则当遇到 nodata 值时返回 0。

The allowed values of the resample parameter are "nearest" which performs the default nearest-neighbor resampling, and "bilinear" which performs a **bilinear interpolation** to estimate the value between pixel centers.

2.1.0 版本: exclude_nodata_value 参数是可选的。

2.0.0 版本: exclude_nodata_value 参数是可选的。

示例

```
-- get raster values at particular postgis geometry points
-- the srid of your geometry should be same as for your raster
SELECT rid, ST_Value(rast, foo.pt_geom) As b1pval, ST_Value(rast, 2, foo.pt_geom) As b2pval
FROM dummy_rast CROSS JOIN (SELECT ST_SetSRID(ST_Point(3427927.77, 5793243.76), 0) As
pt_geom) As foo
WHERE rid=2;
```

```
rid | b1pval | b2pval
-----+-----+-----
  2 |    252 |    79
```

```
-- general fictitious example using a real table
SELECT rid, ST_Value(rast, 3, sometable.geom) As b3pval
FROM sometable
WHERE ST_Intersects(rast,sometable.geom);
```

```
SELECT rid, ST_Value(rast, 1, 1, 1) As b1pval,
ST_Value(rast, 2, 1, 1) As b2pval, ST_Value(rast, 3, 1, 1) As b3pval
FROM dummy_rast
WHERE rid=2;
```

```
rid | b1pval | b2pval | b3pval
-----+-----+-----+-----
  2 |    253 |    78 |    70
```

```

--- Get all values in bands 1,2,3 of each pixel --
SELECT x, y, ST_Value(rast, 1, x, y) As b1val,
       ST_Value(rast, 2, x, y) As b2val, ST_Value(rast, 3, x, y) As b3val
FROM dummy_rast CROSS JOIN
generate_series(1, 1000) As x CROSS JOIN generate_series(1, 1000) As y
WHERE rid = 2 AND x <= ST_Width(rast) AND y <= ST_Height(rast);

```

x	y	b1val	b2val	b3val
1	1	253	78	70
1	2	253	96	80
1	3	250	99	90
1	4	251	89	77
1	5	252	79	62
2	1	254	98	86
2	2	254	118	108
:				
:				

```

--- Get all values in bands 1,2,3 of each pixel same as above but returning the upper left ←
point point of each pixel --
SELECT ST_AsText(ST_SetSRID(
  ST_Point(ST_UpperLeftX(rast) + ST_ScaleX(rast)*x,
    ST_UpperLeftY(rast) + ST_ScaleY(rast)*y),
    ST_SRID(rast))) As uplpt
, ST_Value(rast, 1, x, y) As b1val,
  ST_Value(rast, 2, x, y) As b2val, ST_Value(rast, 3, x, y) As b3val
FROM dummy_rast CROSS JOIN
generate_series(1,1000) As x CROSS JOIN generate_series(1,1000) As y
WHERE rid = 2 AND x <= ST_Width(rast) AND y <= ST_Height(rast);

```

uplpt	b1val	b2val	b3val
POINT(3427929.25 5793245.5)	253	78	70
POINT(3427929.25 5793247)	253	96	80
POINT(3427929.25 5793248.5)	250	99	90
:			

```

--- Get a polygon formed by union of all pixels
that fall in a particular value range and intersect particular polygon --
SELECT ST_AsText(ST_Union(pixpolyg)) As shadow
FROM (SELECT ST_Translate(ST_MakeEnvelope(
  ST_UpperLeftX(rast), ST_UpperLeftY(rast),
  ST_UpperLeftX(rast) + ST_ScaleX(rast),
  ST_UpperLeftY(rast) + ST_ScaleY(rast), 0
), ST_ScaleX(rast)*x, ST_ScaleY(rast)*y
) As pixpolyg, ST_Value(rast, 2, x, y) As b2val
FROM dummy_rast CROSS JOIN
generate_series(1,1000) As x CROSS JOIN generate_series(1,1000) As y
WHERE rid = 2
AND x <= ST_Width(rast) AND y <= ST_Height(rast)) As foo
WHERE
  ST_Intersects(
    pixpolyg,
    ST_GeomFromText('POLYGON((3427928 5793244,3427927.75 5793243.75,3427928 ←
5793243.75,3427928 5793244))',0)

```

```
) AND b2val != 254;
```

```
shadow
```

```
-----
MULTIPOLYGON(((3427928 5793243.9,3427928 5793243.85,3427927.95 5793243.85,3427927.95  ←
5793243.9,
3427927.95 5793243.95,3427928 5793243.95,3427928.05 5793243.95,3427928.05  ←
5793243.9,3427928 5793243.9)),((3427927.95 5793243.9,3427927.95 579324
3.85,3427927.9 5793243.85,3427927.85 5793243.85,3427927.85 5793243.9,3427927.9  ←
5793243.9,3427927.9 5793243.95,
3427927.95 5793243.95,3427927.95 5793243.9)),((3427927.85 5793243.75,3427927.85  ←
5793243.7,3427927.8 5793243.7,3427927.8 5793243.75
,3427927.8 5793243.8,3427927.8 5793243.85,3427927.85 5793243.85,3427927.85  ←
5793243.8,3427927.85 5793243.75)),
((3427928.05 5793243.75,3427928.05 5793243.7,3427928 5793243.7,3427927.95  ←
5793243.7,3427927.95 5793243.75,3427927.95 5793243.8,3427
927.95 5793243.85,3427928 5793243.85,3427928 5793243.8,3427928.05 5793243.8,
3427928.05 5793243.75)),((3427927.95 5793243.75,3427927.95 5793243.7,3427927.9  ←
5793243.7,3427927.85 5793243.7,
3427927.85 5793243.75,3427927.85 5793243.8,3427927.85 5793243.85,3427927.9 5793243.85,
3427927.95 5793243.85,3427927.95 5793243.8,3427927.95 5793243.75)))
```

```
--- Checking all the pixels of a large raster tile can take a long time.
--- You can dramatically improve speed at some lose of precision by orders of magnitude
-- by sampling pixels using the step optional parameter of generate_series.
-- This next example does the same as previous but by checking 1 for every 4 (2x2) pixels  ←
and putting in the last checked
-- putting in the checked pixel as the value for subsequent 4
```

```
SELECT ST_AsText(ST_Union(pixpolyg)) As shadow
FROM (SELECT ST_Translate(ST_MakeEnvelope(
    ST_UpperLeftX(rast), ST_UpperLeftY(rast),
    ST_UpperLeftX(rast) + ST_ScaleX(rast)*2,
    ST_UpperLeftY(rast) + ST_ScaleY(rast)*2, 0
    ), ST_ScaleX(rast)*x, ST_ScaleY(rast)*y
    ) As pixpolyg, ST_Value(rast, 2, x, y) As b2val
FROM dummy_rast CROSS JOIN
generate_series(1,1000,2) As x CROSS JOIN generate_series(1,1000,2) As y
WHERE rid = 2
AND x <= ST_Width(rast) AND y <= ST_Height(rast) ) As foo
WHERE
    ST_Intersects(
        pixpolyg,
        ST_GeomFromText('POLYGON((3427928 5793244,3427927.75 5793243.75,3427928  ←
5793243.75,3427928 5793244))',0)
    ) AND b2val != 254;
```

```
shadow
```

```
-----
MULTIPOLYGON(((3427927.9 5793243.85,3427927.8 5793243.85,3427927.8 5793243.95,
3427927.9 5793243.95,3427928 5793243.95,3427928.1 5793243.95,3427928.1 5793243.85,3427928  ←
5793243.85,3427927.9 5793243.85)),
((3427927.9 5793243.65,3427927.8 5793243.65,3427927.8 5793243.75,3427927.8  ←
5793243.85,3427927.9 5793243.85,
3427928 5793243.85,3427928 5793243.75,3427928.1 5793243.75,3427928.1 5793243.65,3427928  ←
5793243.65,3427927.9 5793243.65)))
```

返回

[ST_SetValue](#), [ST_DumpAsPolygons](#), [ST_NumBands](#), [ST_PixelAsPolygon](#), [ST_ScaleX](#), [ST_ScaleY](#), [ST_UpperLeftX](#), [ST_UpperLeftY](#), [ST_SRID](#), [ST_AsText](#), [ST_Point](#), [ST_MakeEnvelope](#), [ST_Intersects](#), [ST_Intersection](#)

11.6.8 ST_NearestValue

ST_NearestValue — columnx 行号, 返回指定栅格中最近的非空值。如果指定了 columnx 和 rowy, 则返回指定像素的值。如果指定了 columnx 和 rowy, 则返回指定像素的值。如果指定了 columnx 和 rowy, 则返回指定像素的值。

Synopsis

```
double precision ST_NearestValue(raster rast, integer bandnum, geometry pt, boolean exclude_nodata_value=
double precision ST_NearestValue(raster rast, geometry pt, boolean exclude_nodata_value=true);
double precision ST_NearestValue(raster rast, integer bandnum, integer columnx, integer rowy,
boolean exclude_nodata_value=true);
double precision ST_NearestValue(raster rast, integer columnx, integer rowy, boolean exclude_nodata_valu
```

返回

返回 columnx, rowy 指定的像素值。如果指定了 columnx 和 rowy, 则返回指定像素的值。如果指定了 columnx 和 rowy, 则返回指定像素的值。如果指定了 columnx 和 rowy, 则返回指定像素的值。

如果指定了 1 个像素, 则返回指定像素的 bandnum 值。如果指定了 1 个像素, 则返回指定像素的 bandnum 值。如果指定了 1 个像素, 则返回指定像素的 bandnum 值。如果指定了 1 个像素, 则返回指定像素的 bandnum 值。

2.1.0 版本引入。



Note

ST_NearestValue 返回指定像素的 **ST_Value** 值。

返回

```
-- pixel 2x2 has value
SELECT
  ST_Value(rast, 2, 2) AS value,
  ST_NearestValue(rast, 2, 2) AS nearestvalue
FROM (
  SELECT
    ST_SetValue(
      ST_SetValue(
        ST_SetValue(
          ST_SetValue(
            ST_SetValue(
              ST_AddBand(
                ST_MakeEmptyRaster(5, 5, -2, 2, 1, -1, 0, 0, 0),
                '8BUI'::text, 1, 0
              ),
              1, 1, 0.
            ),
          ),
        ),
      ),
    )
```

```
        2, 3, 0.
      ),
      3, 5, 0.
    ),
    4, 2, 0.
  ),
  5, 4, 0.
) AS rast
) AS foo

value | nearestvalue
-----+-----
1 | 1

-- pixel 2x3 is NODATA
SELECT
  ST_Value(rast, 2, 3) AS value,
  ST_NearestValue(rast, 2, 3) AS nearestvalue
FROM (
  SELECT
    ST_SetValue(
      ST_SetValue(
        ST_SetValue(
          ST_SetValue(
            ST_SetValue(
              ST_AddBand(
                ST_MakeEmptyRaster(5, 5, -2, 2, 1, -1, 0, 0, 0),
                '8BUI'::text, 1, 0
              ),
              1, 1, 0.
            ),
            2, 3, 0.
          ),
          3, 5, 0.
        ),
        4, 2, 0.
      ),
      5, 4, 0.
    ) AS rast
  ) AS foo

value | nearestvalue
-----+-----
| 1
```



ST_Neighborhood, ST_Value

11.6.9 ST_SetZ

ST_SetZ — Returns a geometry with the same X/Y coordinates as the input geometry, and values from the raster copied into the Z dimension using the requested resample algorithm.

Synopsis

geometry **ST_SetZ**(raster rast, geometry geom, text resample=nearest, integer band=1);

☒☒

Returns a geometry with the same X/Y coordinates as the input geometry, and values from the raster copied into the Z dimensions using the requested resample algorithm.

The `resample` parameter can be set to “nearest” to copy the values from the cell each vertex falls within, or “bilinear” to use **bilinear interpolation** to calculate a value that takes neighboring cells into account also.

Availability: 3.2.0

☒☒

```
--
-- 2x2 test raster with values
--
-- 10 50
-- 40 20
--
WITH test_raster AS (
SELECT
ST_SetValues(
  ST_AddBand(
    ST_MakeEmptyRaster(width => 2, height => 2,
      upperleftx => 0, upperlefty => 2,
      scalex => 1.0, scaley => -1.0,
      skewx => 0, skewy => 0, srid => 4326),
    index => 1, pixeltype => '16BSI',
    initialvalue => 0,
    nodataval => -999),
    1,1,1,
    newvalueset =>ARRAY[ARRAY[10.0::float8, 50.0::float8], ARRAY[40.0::float8, 20.0::float8] ←
      ]) AS rast
)
SELECT
ST_AsText(
  ST_SetZ(
    rast,
    band => 1,
    geom => 'SRID=4326;LINESTRING(1.0 1.9, 1.0 0.2)::geometry',
    resample => 'bilinear'
  ))
FROM test_raster

          st_astext
-----
LINESTRING Z (1 1.9 38,1 0.2 27)
```

☒☒

ST_Value, ST_SetSRID

11.6.10 ST_SetM

ST_SetM — Returns a geometry with the same X/Y coordinates as the input geometry, and values from the raster copied into the M dimension using the requested resample algorithm.

Synopsis

geometry **ST_SetM**(raster rast, geometry geom, text resample=nearest, integer band=1);

☐☐

Returns a geometry with the same X/Y coordinates as the input geometry, and values from the raster copied into the M dimensions using the requested resample algorithm.

The `resample` parameter can be set to “nearest” to copy the values from the cell each vertex falls within, or “bilinear” to use [bilinear interpolation](#) to calculate a value that takes neighboring cells into account also.

Availability: 3.2.0

☐☐

```
--
-- 2x2 test raster with values
--
-- 10 50
-- 40 20
--
WITH test_raster AS (
SELECT
ST_SetValues(
  ST_AddBand(
    ST_MakeEmptyRaster(width => 2, height => 2,
      upperleftx => 0, upperlefty => 2,
      scalex => 1.0, scaley => -1.0,
      skewx => 0, skewy => 0, srid => 4326),
    index => 1, pixeltype => 'l6BSI',
    initialvalue => 0,
    nodataval => -999),
  1,1,1,
  newvalueset => ARRAY[ARRAY[10.0::float8, 50.0::float8], ARRAY[40.0::float8, 20.0::float8] ←
    ]) AS rast
)
SELECT
ST_AsText(
  ST_SetM(
    rast,
    band => 1,
    geom => 'SRID=4326;LINESTRING(1.0 1.9, 1.0 0.2)::geometry',
    resample => 'bilinear'
  ))
FROM test_raster

          st_astext
-----
LINESTRING M (1 1.9 38,1 0.2 27)
```

☐☐

ST_Value, ST_SetSRID

11.6.11 ST_Neighborhood

ST_Neighborhood — columnx × rowy, 返回指定栅格中指定列和行周围的像素值。NODATA 值将返回 NULL。2 个参数版本。

Synopsis

```
double precision[][] ST_Neighborhood(raster rast, integer bandnum, integer columnX, integer rowY,
integer distanceX, integer distanceY, boolean exclude_nodata_value=true);
double precision[][] ST_Neighborhood(raster rast, integer columnX, integer rowY, integer distanceX,
integer distanceY, boolean exclude_nodata_value=true);
double precision[][] ST_Neighborhood(raster rast, integer bandnum, geometry pt, integer distanceX,
integer distanceY, boolean exclude_nodata_value=true);
double precision[][] ST_Neighborhood(raster rast, geometry pt, integer distanceX, integer distanceY,
boolean exclude_nodata_value=true);
```

参数

columnx × rowy, 指定栅格中的列和行。NODATA 值将返回 NULL。2 个参数版本。distanceX 和 distanceY 指定了从指定列和行开始的距离。默认情况下，距离为 3 个像素。Y 指定了 2 个像素。2 个参数版本。columnx × rowy 指定了栅格中的列和行。

bandnum 1 指定了栅格中的波段。bandnum 1 指定了栅格中的波段。exclude_nodata_value 指定了是否排除 NODATA 值。nodata 指定了是否排除 NODATA 值。exclude_nodata_value 指定了是否排除 NODATA 值。



Note

距离为 2 个像素的邻域大小为 $2 * (distanceX + distanceY) + 1$ 。距离为 distanceX 和 distanceY 指定了 1 个像素，邻域大小为 3x3 个像素。



Note

ST_Min4ma, ST_Sum4ma, ST_Mean4ma 返回指定栅格中指定列和行周围的 2 个像素值的平均值。

2.1.0 版本更新

参数

```
-- pixel 2x2 has value
SELECT
  ST_Neighborhood(rast, 2, 2, 1, 1)
FROM (
  SELECT
    ST_SetValues(
      ST_AddBand(
        ST_MakeEmptyRaster(5, 5, -2, 2, 1, -1, 0, 0, 0),
        '8BUI'::text, 1, 0
      ),
```

```

        1, 1, 1, ARRAY[
            [0, 1, 1, 1, 1],
            [1, 1, 1, 0, 1],
            [1, 0, 1, 1, 1],
            [1, 1, 1, 1, 0],
            [1, 1, 0, 1, 1]
        ]::double precision[],
        1
    ) AS rast
) AS foo

    st_neighborhood
-----
{{NULL,1,1},{1,1,1},{1,NULL,1}}

```

```

-- pixel 2x3 is NODATA
SELECT
    ST_Neighborhood(rast, 2, 3, 1, 1)
FROM (
    SELECT
        ST_SetValues(
            ST_AddBand(
                ST_MakeEmptyRaster(5, 5, -2, 2, 1, -1, 0, 0, 0),
                '8BUI'::text, 1, 0
            ),
            1, 1, 1, ARRAY[
                [0, 1, 1, 1, 1],
                [1, 1, 1, 0, 1],
                [1, 0, 1, 1, 1],
                [1, 1, 1, 1, 0],
                [1, 1, 0, 1, 1]
            ]::double precision[],
            1
        ) AS rast
    ) AS foo

    st_neighborhood
-----
{{1,1,1},{1,NULL,1},{1,1,1}}

```

```

-- pixel 3x3 has value
-- exclude_nodata_value = FALSE
SELECT
    ST_Neighborhood(rast, 3, 3, 1, 1, false)
FROM ST_SetValues(
    ST_AddBand(
        ST_MakeEmptyRaster(5, 5, -2, 2, 1, -1, 0, 0, 0),
        '8BUI'::text, 1, 0
    ),
    1, 1, 1, ARRAY[
        [0, 1, 1, 1, 1],
        [1, 1, 1, 0, 1],
        [1, 0, 1, 1, 1],
        [1, 1, 1, 1, 0],
        [1, 1, 0, 1, 1]
    ]::double precision[],
    1
) AS rast

    st_neighborhood
-----

```



```
-- Store the changed raster --
UPDATE dummy_rast SET rast = ST_SetValue(rast,1, ST_Point(3427927.75, 5793243.95),100)
WHERE rid = 2 ;
```



ST_Value, ST_DumpAsPolygons

11.6.13 ST_SetValues

ST SetValues —

Synopsis

```

raster ST_SetValues(raster rast, integer nband, integer columnx, integer rowy, double precision[] newvalueset, boolean[][] noset=NULL, boolean keepnodata=FALSE);
raster ST_SetValues(raster rast, integer nband, integer columnx, integer rowy, double precision[] newvalueset, double precision nosetvalue, boolean keepnodata=FALSE);
raster ST_SetValues(raster rast, integer nband, integer columnx, integer rowy, integer width, integer height, double precision newvalue, boolean keepnodata=FALSE);
raster ST_SetValues(raster rast, integer columnx, integer rowy, integer width, integer height, double precision newvalue, boolean keepnodata=FALSE);
raster ST_SetValues(raster rast, integer nband, geomval[] geomvalset, boolean keepnodata=FALSE);

```



XXXXXXXXXX, XXXXXXXXXXXXXXXX (X) XXXXXXXXXXXXXXXXXXXX.

```
keepnodata TRUE ###, NODATA ##### newvalueset #####  
##.
```

1 column, columnx, row newvalueset newvalueset newvalueset noset (PostgreSQL 1.0.0).

```

2 1 1, noset nosetvalue
.newvalueset nosetvalue 2

```

3 columns, columnx, rowy columns, width height columns. 3 columns

4 rast 3

5 个, 每个值都是 **geomval** 类型。每个 POINT 或 MULTIPOINT 值, 每个值都是 **geomval** 类型。每个值都是 **geomval** 类型。 5 个。

2.1.0 ☒☒☒☒☒☒☒☒☒☒☒.

图例: 图 1

```
/*
The ST_SetValues() does the following...

+ - + - + - +      + - + - + - +
| 1 | 1 | 1 |      | 1 | 1 | 1 |
+ - + - + - +      + - + - + - +
| 1 | 1 | 1 |      =
> | 1 | 9 | 9 |
+ - + - + - +      + - + - + - +
| 1 | 1 | 1 |      | 1 | 9 | 9 |
+ - + - + - +      + - + - + - +

*/
SELECT
    (poly).x,
    (poly).y,
    (poly).val
FROM (
    SELECT
        ST_PixelAsPolygons(
            ST_SetValues(
                ST_AddBand(
                    ST_MakeEmptyRaster(3, 3, 0, 0, 1, -1, 0, 0, 0),
                    1, '8BUI', 1, 0
                ),
                1, 2, 2, ARRAY[[9, 9], [9, 9]]::double precision[][]
            )
        ) AS poly
    ) foo
ORDER BY 1, 2;

x | y | val
---+---+---
1 | 1 | 1
1 | 2 | 1
1 | 3 | 1
2 | 1 | 1
2 | 2 | 9
2 | 3 | 9
3 | 1 | 1
3 | 2 | 9
3 | 3 | 9
```

```
/*
The ST_SetValues() does the following...

+ - + - + - +      + - + - + - +
| 1 | 1 | 1 |      | 9 | 9 | 9 |
+ - + - + - +      + - + - + - +
| 1 | 1 | 1 |      =
> | 9 | 9 | 9 |
+ - + - + - +      + - + - + - +
| 1 | 1 | 1 |      | 9 | 9 | 9 |
+ - + - + - +      + - + - + - +

*/
SELECT
    (poly).x,
```

```
(poly).y,  
(poly).val  
FROM (  
SELECT  
    ST_PixelAsPolygons(  
        ST_SetValues(  
            ST_AddBand(  
                ST_MakeEmptyRaster(3, 3, 0, 0, 1, -1, 0, 0, 0),  
                1, '8BUI', 1, 0  
            ),  
            1, 1, 1, ARRAY[[9, 9, 9], [9, NULL, 9], [9, 9, 9]]::double precision[][])  
        ) AS poly  
    ) foo  
ORDER BY 1, 2;
```

x	y	val
1	1	9
1	2	9
1	3	9
2	1	9
2	2	
2	3	9
3	1	9
3	2	9
3	3	9

```
/*  
The ST_SetValues() does the following...  
  
+ - + - + - +      + - + - + - +  
| 1 | 1 | 1 |      | 9 | 9 | 9 |  
+ - + - + - +      + - + - + - +  
| 1 | 1 | 1 |      => | 1 |   | 9 |  
+ - + - + - +      + - + - + - +  
| 1 | 1 | 1 |      | 9 | 9 | 9 |  
+ - + - + - +      + - + - + - +  
*/  
SELECT  
    (poly).x,  
    (poly).y,  
    (poly).val  
FROM (  
SELECT  
    ST_PixelAsPolygons(  
        ST_SetValues(  
            ST_AddBand(  
                ST_MakeEmptyRaster(3, 3, 0, 0, 1, -1, 0, 0, 0),  
                1, '8BUI', 1, 0  
            ),  
            1, 1, 1,  
            ARRAY[[9, 9, 9], [9, NULL, 9], [9, 9, 9]]::double precision[][],  
            ARRAY[[false], [true]]::boolean[][])  
        ) AS poly  
    ) foo  
ORDER BY 1, 2;  
  
x | y | val  
---+---+---
```


1	1	9
1	2	1
1	3	9
2	1	9
2	2	
2	3	9
3	1	9
3	2	9
3	3	9

```
/*
The ST_SetValues() does the following...

+ - + - + - +      + - + - + - +
|   | 1 | 1 |      |   | 9 | 9 |
+ - + - + - +      + - + - + - +
| 1 | 1 | 1 |      => | 1 |   | 9 |
+ - + - + - +      + - + - + - +
| 1 | 1 | 1 |      | 9 | 9 | 9 |
+ - + - + - +      + - + - + - +
*/
SELECT
    (poly).x,
    (poly).y,
    (poly).val
FROM (
SELECT
    ST_PixelAsPolygons(
        ST_SetValues(
            ST_SetValue(
                ST_AddBand(
                    ST_MakeEmptyRaster(3, 3, 0, 0, 1, -1, 0, 0, 0),
                    1, '8BUI', 1, 0
                ),
                1, 1, 1, NULL
            ),
            1, 1, 1,
            ARRAY[[9, 9, 9], [9, NULL, 9], [9, 9, 9]]::double precision[][],
            ARRAY[[false], [true]]::boolean[][],
            TRUE
        )
    ) AS poly
) foo
ORDER BY 1, 2;
```

x	y	val
1	1	
1	2	1
1	3	9
2	1	9
2	2	
2	3	9
3	1	9
3	2	9
3	3	9

```

/*
The ST_SetValues() does the following...

+ - + - + - +      + - + - + - +
| 1 | 1 | 1 |      | 1 | 1 | 1 |
+ - + - + - +      + - + - + - +
| 1 | 1 | 1 |      => | 1 | 9 | 9 |
+ - + - + - +      + - + - + - +
| 1 | 1 | 1 |      | 1 | 9 | 9 |
+ - + - + - +      + - + - + - +
*/
SELECT
    (poly).x,
    (poly).y,
    (poly).val
FROM (
    SELECT
        ST_PixelAsPolygons(
            ST_SetValues(
                ST_AddBand(
                    ST_MakeEmptyRaster(3, 3, 0, 0, 1, -1, 0, 0, 0),
                    1, '8BUI', 1, 0
                ),
                1, 1, 1, ARRAY[[-1, -1, -1], [-1, 9, 9], [-1, 9, 9]]::double precision[3][3], -1
            )
        ) AS poly
    ) foo
ORDER BY 1, 2;

x | y | val
---+---+---
1 | 1 | 1
1 | 2 | 1
1 | 3 | 1
2 | 1 | 1
2 | 2 | 9
2 | 3 | 9
3 | 1 | 1
3 | 2 | 9
3 | 3 | 9

```

```

/*
This example is like the previous one. Instead of nosetvalue = -1, nosetvalue = NULL

The ST_SetValues() does the following...

+ - + - + - +      + - + - + - +
| 1 | 1 | 1 |      | 1 | 1 | 1 |
+ - + - + - +      + - + - + - +
| 1 | 1 | 1 |      => | 1 | 9 | 9 |
+ - + - + - +      + - + - + - +
| 1 | 1 | 1 |      | 1 | 9 | 9 |
+ - + - + - +      + - + - + - +
*/
SELECT
    (poly).x,
    (poly).y,
    (poly).val
FROM (
    SELECT
        ST_PixelAsPolygons(

```

```
        ST_SetValues(
            ST_AddBand(
                ST_MakeEmptyRaster(3, 3, 0, 0, 1, -1, 0, 0, 0),
                1, '8BUI', 1, 0
            ),
            1, 1, 1, ARRAY[[NULL, NULL, NULL], [NULL, 9, 9], [NULL, 9, 9]]::double precision --
            precision[][] , NULL::double precision
        )
    ) AS poly
) foo
ORDER BY 1, 2;
```

x	y	val
1	1	1
1	2	1
1	3	1
2	1	1
2	2	9
2	3	9
3	1	1
3	2	9
3	3	9

图 3

```
/*
The ST_SetValues() does the following...

+ - + - + - +      + - + - + - +
| 1 | 1 | 1 |      | 1 | 1 | 1 |
+ - + - + - +      + - + - + - +
| 1 | 1 | 1 |      => | 1 | 9 | 9 |
+ - + - + - +      + - + - + - +
| 1 | 1 | 1 |      | 1 | 9 | 9 |
+ - + - + - +      + - + - + - +
*/
SELECT
    (poly).x,
    (poly).y,
    (poly).val
FROM (
    SELECT
        ST_PixelAsPolygons(
            ST_SetValues(
                ST_AddBand(
                    ST_MakeEmptyRaster(3, 3, 0, 0, 1, -1, 0, 0, 0),
                    1, '8BUI', 1, 0
                ),
                1, 2, 2, 2, 2, 9
            )
        ) AS poly
    ) foo
ORDER BY 1, 2;
```

x	y	val
1	1	1
1	2	1
1	3	1

2	1	1
2	2	9
2	3	9
3	1	1
3	2	9
3	3	9

/*
The ST_SetValues() does the following...

+ - + - + - +		+ - + - + - +
1 1 1		1 1 1
+ - + - + - +		+ - + - + - +
1 1	=>	1 9
+ - + - + - +		+ - + - + - +
1 1 1		1 9 9
+ - + - + - +		+ - + - + - +

```
*/
SELECT
  (poly).x,
  (poly).y,
  (poly).val
FROM (
  SELECT
    ST_PixelAsPolygons(
      ST_SetValues(
        ST_SetValue(
          ST_AddBand(
            ST_MakeEmptyRaster(3, 3, 0, 0, 1, -1, 0, 0, 0),
            1, '8BUI', 1, 0
          ),
          1, 2, 2, NULL
        ),
        1, 2, 2, 2, 2, 9, TRUE
      )
    ) AS poly
) foo
ORDER BY 1, 2;
```

x	y	val
1	1	1
1	2	1
1	3	1
2	1	1
2	2	
2	3	9
3	1	1
3	2	9
3	3	9

练习5

```
WITH foo AS (
  SELECT 1 AS rid, ST_AddBand(ST_MakeEmptyRaster(5, 5, 0, 0, 1, -1, 0, 0, 0), 1, '8BUI',
    0, 0) AS rast
), bar AS (
  SELECT 1 AS gid, 'SRID=0;POINT(2.5 -2.5)::geometry geom UNION ALL
  SELECT 2 AS gid, 'SRID=0;POLYGON((1 -1, 4 -1, 4 -4, 1 -4, 1 -1))::geometry geom UNION
    ALL
```

```
SELECT 3 AS gid, 'SRID=0;POLYGON((0 0, 5 0, 5 -1, 1 -1, 1 -4, 0 -4, 0 0))'::geometry ↵
      geom UNION ALL
SELECT 4 AS gid, 'SRID=0;MULTIPOINT(0 0, 4 4, 4 -4)'::geometry
)
SELECT
  rid, gid, ST_DumpValues(ST_SetValue(rast, 1, geom, gid))
FROM foo t1
CROSS JOIN bar t2
ORDER BY rid, gid;
```

rid	gid	st_dumpvalues
1	1	(1,"{{NULL,NULL,NULL,NULL,NULL},{NULL,NULL,NULL,NULL,NULL},{NULL,NULL,1,NULL, ↵ NULL},{NULL,NULL,NULL,NULL,NULL},{NULL,NULL,NULL,NULL,NULL}}")
1	2	(1,"{{NULL,NULL,NULL,NULL,NULL},{NULL,2,2,2,NULL},{NULL,2,2,2,NULL},{NULL ↵ ,2,2,2,NULL},{NULL,NULL,NULL,NULL,NULL}}")
1	3	(1,"{{3,3,3,3,3},{3,NULL,NULL,NULL,NULL},{3,NULL,NULL,NULL,NULL},{3,NULL,NULL, ↵ NULL,NULL},{NULL,NULL,NULL,NULL,NULL}}")
1	4	(1,"{{4,NULL,NULL,NULL,NULL},{NULL,NULL,NULL,NULL,NULL},{NULL,NULL,NULL,NULL, ↵ NULL},{NULL,NULL,NULL,NULL,NULL},{NULL,NULL,NULL,NULL,4}}")

(4 rows)

geomvals geomvals geomvals.

```
WITH foo AS (
  SELECT 1 AS rid, ST_AddBand(ST_MakeEmptyRaster(5, 5, 0, 0, 1, -1, 0, 0, 0), 1, '8BUI', ↵
    0, 0) AS rast
), bar AS (
  SELECT 1 AS gid, 'SRID=0;POINT(2.5 -2.5)'::geometry geom UNION ALL
  SELECT 2 AS gid, 'SRID=0;POLYGON((1 -1, 4 -1, 4 -4, 1 -4, 1 -1))'::geometry geom UNION ↵
    ALL
  SELECT 3 AS gid, 'SRID=0;POLYGON((0 0, 5 0, 5 -1, 1 -1, 1 -4, 0 -4, 0 0))'::geometry ↵
    geom UNION ALL
  SELECT 4 AS gid, 'SRID=0;MULTIPOINT(0 0, 4 4, 4 -4)'::geometry
)
SELECT
  t1.rid, t2.gid, t3.gid, ST_DumpValues(ST_SetValues(rast, 1, ARRAY[ROW(t2.geom, t2.gid), ↵
    ROW(t3.geom, t3.gid)]::geomval[]))
FROM foo t1
CROSS JOIN bar t2
CROSS JOIN bar t3
WHERE t2.gid = 1
      AND t3.gid = 2
ORDER BY t1.rid, t2.gid, t3.gid;
```

rid	gid	gid	st_dumpvalues
1	1	2	(1,"{{NULL,NULL,NULL,NULL,NULL},{NULL,2,2,2,NULL},{NULL,2,2,2,NULL},{ ↵ NULL,2,2,2,NULL},{NULL,NULL,NULL,NULL,NULL}}")

(1 row)

.

```
WITH foo AS (
  SELECT 1 AS rid, ST_AddBand(ST_MakeEmptyRaster(5, 5, 0, 0, 1, -1, 0, 0, 0), 1, '8BUI', ↵
    0, 0) AS rast
), bar AS (
  SELECT 1 AS gid, 'SRID=0;POINT(2.5 -2.5)'::geometry geom UNION ALL
  SELECT 2 AS gid, 'SRID=0;POLYGON((1 -1, 4 -1, 4 -4, 1 -4, 1 -1))'::geometry geom UNION ↵
    ALL
```

```
SELECT 3 AS gid, 'SRID=0;POLYGON((0 0, 5 0, 5 -1, 1 -1, 1 -4, 0 -4, 0 0))'::geometry ↵
      geom UNION ALL
SELECT 4 AS gid, 'SRID=0;MULTIPOINT(0 0, 4 4, 4 -4)'::geometry
)
SELECT
  t1.rid, t2.gid, t3.gid, ST_DumpValues(ST_SetValues(rast, 1, ARRAY[ROW(t2.geom, t2.gid), ↵
    ROW(t3.geom, t3.gid)]::geomval[]))
FROM foo t1
CROSS JOIN bar t2
CROSS JOIN bar t3
WHERE t2.gid = 2
      AND t3.gid = 1
ORDER BY t1.rid, t2.gid, t3.gid;
```

rid	gid	gid	st_dumpvalues
1	2	1	(1,"{{NULL,NULL,NULL,NULL,NULL},{NULL,2,2,2,NULL},{NULL,2,1,2,NULL},{ ↵ NULL,2,2,2,NULL},{NULL,NULL,NULL,NULL,NULL}}")

(1 row)

☐☐

ST_Value, ST_SetValue, ST_PixelAsPolygons

11.6.14 ST_DumpValues

ST_DumpValues — ☐☐☐☐☐☐☐☐ 2 ☐☐☐☐☐☐☐☐☐☐.

Synopsis

setof record **ST_DumpValues**(raster rast , integer[] nband=NULL , boolean exclude_nodata_value=true);
double precision[][] **ST_DumpValues**(raster rast , integer nband , boolean exclude_nodata_value=true);

☐☐

☐☐☐☐☐☐☐☐ 2 ☐☐☐☐☐☐☐☐☐ (☐☐☐☐☐☐☐☐, ☐☐☐☐☐☐☐☐☐☐). nband ☐ NULL ☐ ☐☐☐☐☐☐☐☐☐, ☐☐☐☐☐☐☐☐☐☐☐☐☐☐☐☐.

2.1.0 ☐☐☐☐☐☐☐☐☐☐☐☐.

☐☐

```
WITH foo AS (
  SELECT ST_AddBand(ST_AddBand(ST_AddBand(ST_MakeEmptyRaster(3, 3, 0, 0, 1, -1, 0, 0, 0), ↵
    1, '8BUI'::text, 1, 0), 2, '32BF'::text, 3, -9999), 3, '16BSI', 0, 0) AS rast
)
SELECT
  (ST_DumpValues(rast)).*
FROM foo;
```

nband	valarray
1	{{1,1,1},{1,1,1},{1,1,1}}
2	{{3,3,3},{3,3,3},{3,3,3}}
3	{{NULL,NULL,NULL},{NULL,NULL,NULL},{NULL,NULL,NULL}}

(3 rows)

```
WITH foo AS (  
  SELECT ST_AddBand(ST_AddBand(ST_AddBand(ST_MakeEmptyRaster(3, 3, 0, 0, 1, -1, 0, 0, 0), ←  
    1, '8BUI'::text, 1, 0), 2, '32BF'::text, 3, -9999), 3, '16BSI', 0, 0) AS rast  
)  
SELECT  
  (ST_DumpValues(rast, ARRAY[3, 1])).*  
FROM foo;
```

nband	valarray
3	{{NULL,NULL,NULL},{NULL,NULL,NULL},{NULL,NULL,NULL}}
1	{{1,1,1},{1,1,1},{1,1,1}}

(2 rows)

```
WITH foo AS (  
  SELECT ST_SetValue(ST_AddBand(ST_MakeEmptyRaster(3, 3, 0, 0, 1, -1, 0, 0, 0), 1, '8BUI' ←  
    , 1, 0), 1, 2, 5) AS rast  
)  
SELECT  
  (ST_DumpValues(rast, 1))[2][1]  
FROM foo;
```

st_dumpvalues
5

(1 row)



[ST_Value](#), [ST_SetValue](#), [ST_SetValues](#)

11.6.15 ST_PixelOfValue

ST_PixelOfValue — 返回具有指定值的像素的列索引和行索引。

Synopsis

```
setof record ST_PixelOfValue( raster rast , integer nband , double precision[] search , boolean ex-  
clude_nodata_value=true );  
setof record ST_PixelOfValue( raster rast , double precision[] search , boolean exclude_nodata_value=true  
);  
setof record ST_PixelOfValue( raster rast , integer nband , double precision search , boolean ex-  
clude_nodata_value=true );  
setof record ST_PixelOfValue( raster rast , double precision search , boolean exclude_nodata_value=true  
);
```


11.7 地理参考

11.7.1 ST_SetGeoReference

`ST_SetGeoReference` — 将地理参考信息设置到 6 个参数。支持 GDAL 和 ESRI 两种格式。GDAL 格式为：

Synopsis

`raster` **ST_SetGeoReference**(`raster rast`, `text georefcoords`, `text format=GDAL`);
`raster` **ST_SetGeoReference**(`raster rast`, `double precision upperleftx`, `double precision upperlefty`,
`double precision scalex`, `double precision scaley`, `double precision skewx`, `double precision skewy`);

格式：

支持 GDAL 和 ESRI 两种格式。'GDAL' 和 'ESRI' 格式分别对应 GDAL 和 ESRI 格式。6 个参数分别对应 NULL 值。

支持的格式：

GDAL:

```
scalex skewy skewx scaley upperleftx upperlefty
```

ESRI:

```
scalex skewy skewx scaley upperleftx + scalex*0.5 upperlefty + scaley*0.5
```



Note

在 PostgreSQL 12 之前，使用 `ST_SetGeoReference` 设置地理参考信息时，需要先将数据插入到数据库，然后再使用 `ST_SetGeoReference` 设置地理参考信息。

从 2.1.0 版本开始，`ST_SetGeoReference` 支持在创建表时直接设置地理参考信息。

示例：

```
WITH foo AS (
  SELECT ST_MakeEmptyRaster(5, 5, 0, 0, 1, -1, 0, 0, 0) AS rast
)
SELECT
  0 AS rid, (ST_Metadatas(rast)).*
FROM foo
UNION ALL
SELECT
  1, (ST_Metadatas(ST_SetGeoReference(rast, '10 0 0 -10 0.1 0.1', 'GDAL'))).*
FROM foo
UNION ALL
SELECT
  2, (ST_Metadatas(ST_SetGeoReference(rast, '10 0 0 -10 5.1 -4.9', 'ESRI'))).*
FROM foo
UNION ALL
SELECT
```

3, (ST_Metadata(ST_SetGeoReference(rast, 1, 1, 10, -10, 0.001, 0.001))).*

FROM foo

rid	upperleftx skewy	srid	numbands	upperlefty	width	height	scalex	scaley	skewx	
0	0	0	0	0	5	5	1	-1	0	↔
1	0	0	0.1	0.1	5	5	10	-10	0	↔
2	0.09999999999999996	0.09999999999999996			5	5	10	-10	0	↔
3	0.001	0	1	1	5	5	10	-10	0.001	↔

[ST_GeoReference](#), [ST_ScaleX](#), [ST_ScaleY](#), [ST_UpperLeftX](#), [ST_UpperLeftY](#)

11.7.2 ST_SetRotation

ST_SetRotation — 设置栅格的旋转。

Synopsis

raster **ST_SetRotation**(raster rast, float8 rotation);

设置栅格的旋转。旋转角度以度为单位。如果旋转角度为0，则返回原始栅格。

SELECT

ST_ScaleX(rast1), ST_ScaleY(rast1), ST_SkewX(rast1), ST_SkewY(rast1),

ST_ScaleX(rast2), ST_ScaleY(rast2), ST_SkewX(rast2), ST_SkewY(rast2)

FROM (

SELECT ST_SetRotation(rast, 15) AS rast1, rast as rast2 FROM dummy_rast

) AS foo;

st_scalex	st_scaley	st_skewx	st_skewy	
st_scalex	st_scaley	st_skewx	st_skewy	
-1.51937582571764	-2.27906373857646	1.95086352047135	1.30057568031423	↔
2	3	0	0	
-0.0379843956429411	-0.0379843956429411	0.0325143920078558	0.0325143920078558	↔
0.05	-0.05	0	0	

[ST_Rotation](#), [ST_ScaleX](#), [ST_ScaleY](#), [ST_SkewX](#), [ST_SkewY](#)

11.7.3 ST_SetScale

ST_SetScale — X 和 Y 缩放因子。返回缩放后的栅格。 格式: `ST_SetScale(raster rast, float8 xy)`。 格式: `ST_SetScale(raster rast, float8 x, float8 y)`。

Synopsis

```
raster ST_SetScale(raster rast, float8 xy);
raster ST_SetScale(raster rast, float8 x, float8 y);
```

返回

X 和 Y 缩放因子。返回缩放后的栅格。 格式: `ST_SetScale(raster rast, float8 xy)`。 格式: `ST_SetScale(raster rast, float8 x, float8 y)`。



Note

ST_SetScale 与 `ST_Rescale` 类似。 `ST_Rescale` 返回缩放后的栅格。 `ST_SetScale` 返回缩放后的栅格。 `ST_SetScale` 与 `ST_Rescale` 类似。 `ST_SetScale` 返回缩放后的栅格。 `ST_SetScale` 与 `ST_Rescale` 类似。 `ST_SetScale` 返回缩放后的栅格。

版本: 2.0.0 在 WKTRaster 中。 `ST_SetPixelSize` 与 `ST_SetScale` 类似。 2.0.0 版本。 `ST_SetPixelSize` 与 `ST_SetScale` 类似。

返回

```
UPDATE dummy_rast
  SET rast = ST_SetScale(rast, 1.5)
WHERE rid = 2;

SELECT ST_ScaleX(rast) As pixx, ST_ScaleY(rast) As pixy, Box3D(rast) As newbox
FROM dummy_rast
WHERE rid = 2;
```

pixx	pixy	newbox
1.5	1.5	BOX(3427927.75 5793244 0, 3427935.25 5793251.5 0)

```
UPDATE dummy_rast
  SET rast = ST_SetScale(rast, 1.5, 0.55)
WHERE rid = 2;

SELECT ST_ScaleX(rast) As pixx, ST_ScaleY(rast) As pixy, Box3D(rast) As newbox
FROM dummy_rast
WHERE rid = 2;
```

pixx	pixy	newbox
1.5	0.55	BOX(3427927.75 5793244 0, 3427935.25 5793247 0)

返回

`ST_ScaleX`, `ST_ScaleY`, `Box3D`

11.7.4 ST_SetSkew

`ST_SetSkew` — 设置 X 和 Y 的偏斜 (skew) 值。 设置 X 和 Y 的偏斜值。

Synopsis

raster **ST_SetSkew**(raster rast, float8 skewxy);
raster **ST_SetSkew**(raster rast, float8 skewx, float8 skewy);

返回

设置 X 和 Y 的偏斜值 (skew) 值。 设置 X 和 Y 的偏斜值。 设置 X 和 Y 的偏斜值。

返回

```
-- Example 1
UPDATE dummy_rast SET rast = ST_SetSkew(rast,1,2) WHERE rid = 1;
SELECT rid, ST_SkewX(rast) As skewx, ST_SkewY(rast) As skewy,
       ST_GeoReference(rast) as georef
FROM dummy_rast WHERE rid = 1;
```

rid	skewx	skewy	georef
1	1	2	2.0000000000 : 2.0000000000 : 1.0000000000 : 3.0000000000 : 0.5000000000 : 0.5000000000

```
-- Example 2 set both to same number:
UPDATE dummy_rast SET rast = ST_SetSkew(rast,0) WHERE rid = 1;
SELECT rid, ST_SkewX(rast) As skewx, ST_SkewY(rast) As skewy,
       ST_GeoReference(rast) as georef
FROM dummy_rast WHERE rid = 1;
```

rid	skewx	skewy	georef
1	0	0	2.0000000000 : 0.0000000000 : 0.0000000000 : 3.0000000000 : 0.5000000000 : 0.5000000000

返回

[ST_GeoReference](#), [ST_SetGeoReference](#), [ST_SkewX](#), [ST_SkewY](#)

11.7.5 ST_SetSRID

ST_SetSRID — 将 SRID 与 spatial_ref_sys 表中的 SRID 名称关联。

Synopsis

raster **ST_SetSRID**(raster rast, integer srid);

返回

具有 SRID 的栅格。



Note

如果栅格具有 SRID，则 ST_SetSRID 将 SRID 设置为指定的值。如果栅格没有 SRID，则 ST_SetSRID 将 SRID 设置为指定的值。如果栅格具有 SRID，则 ST_SetSRID 将 SRID 设置为指定的值。

返回

Section 4.5, [ST_SRID](#)

11.7.6 ST_SetUpperLeft

ST_SetUpperLeft — 设置栅格的上左角像素的投影 X 和 Y 坐标。

Synopsis

raster **ST_SetUpperLeft**(raster rast, double precision x, double precision y);

返回

设置栅格的上左角像素的投影 X 和 Y 坐标

返回

```
SELECT ST_SetUpperLeft(rast, -71.01, 42.37)
FROM dummy_rast
WHERE rid = 2;
```

返回

[ST_UpperLeftX](#), [ST_UpperLeftY](#)

11.7.7 ST_Resample

ST_Resample — 对栅格进行重采样，指定新的宽度和高度，以及可选的网格大小、网格大小、偏斜度和偏斜度。返回具有指定宽度和高度的栅格。

Synopsis

```
raster ST_Resample(raster rast, integer width, integer height, double precision gridx=NULL, double
precision gridy=NULL, double precision skewx=0, double precision skewy=0, text algorithm=NearestNeighbor,
double precision maxerr=0.125);
raster ST_Resample(raster rast, double precision scalex=0, double precision scaley=0, double preci-
sion gridx=NULL, double precision gridy=NULL, double precision skewx=0, double precision skewy=0,
text algorithm=NearestNeighbor, double precision maxerr=0.125);
raster ST_Resample(raster rast, raster ref, text algorithm=NearestNeighbor, double precision max-
err=0.125, boolean usescale=true);
raster ST_Resample(raster rast, raster ref, boolean usescale, text algorithm=NearestNeighbor, dou-
ble precision maxerr=0.125);
```

参数

`width` 和 `height` (width & height), `gridx` 和 `gridy` (gridx & gridy), `scalex`, `scaley`, `skewx` & `skewy` (scalex, scaley, skewx & skewy) 是可选的。如果提供了 `SRID`，则返回的栅格将具有该 `SRID`。

New pixel values are computed using one of the following resampling algorithms:

- NearestNeighbor (english or american spelling)
- Bilinear
- Cubic
- CubicSpline
- Lanczos
- Max
- Min

The default is NearestNeighbor which is the fastest but results in the worst interpolation.

`maxerr` 是可选的，默认为 0.125。



Note

有关 **GDAL Warp resampling methods** 的更多信息，请参阅 [GDAL Warp resampling methods](#)。

2.0.0 版本引入。GDAL 1.6.1 版本引入。

Enhanced: 3.4.0 max and min resampling options added

实验

```
SELECT
  ST_Width(orig) AS orig_width,
  ST_Width(reduce_100) AS new_width
FROM (
  SELECT
    rast AS orig,
    ST_Resample(rast,100,100) AS reduce_100
  FROM aerials.boston
  WHERE ST_Intersects(rast,
    ST_Transform(
      ST_MakeEnvelope(-71.128, 42.2392, -71.1277, 42.2397, 4326),26986)
    )
  LIMIT 1
) AS foo;
```

orig_width	new_width
200	100

实验

ST_Rescale, ST_Resize, ST_Transform

11.7.8 ST_Rescale

ST_Rescale — Resample a raster by adjusting only its scale (or pixel size). New pixel values are computed using the NearestNeighbor (english or american spelling), Bilinear, Cubic, CubicSpline, Lanczos, Max or Min resampling algorithm. Default is NearestNeighbor.

Synopsis

```
raster ST_Rescale(raster rast, double precision scalex, text algorithm=NearestNeighbor, double
precision maxerr=0.125);
raster ST_Rescale(raster rast, double precision scalex, double precision scaley, text algorithm=NearestNeighbor,
double precision maxerr=0.125);
```

实验

Resample a raster by adjusting only its scale (or pixel size). New pixel values are computed using one of the following resampling algorithms:

- NearestNeighbor (english or american spelling)
- Bilinear
- Cubic
- CubicSpline
- Lanczos
- Max

- Min

The default is NearestNeighbor which is the fastest but results in the worst interpolation.

scalex and scaley define the new pixel size. scaley must often be negative to get well oriented raster.

scalex 和 scaley 指定新的像素大小，scaley 经常为负数以获得正确的方向。ST_Resize 使用最近邻插值。

maxerr 是变换近似的阈值（以像素为单位）。如果未指定 maxerr，则使用默认值 0.125，这是 GDAL gdalwarp 工具使用的值。如果设置为零，则不进行近似。



Note

GDAL Warp resampling methods 参考。



Note

ST_Rescale 使用 ST_SetScale 设置新的像素大小。ST_SetScale 设置新的像素大小（以像素为单位）。ST_Rescale 使用 ST_SetScale 设置新的像素大小。ST_SetScale 设置新的像素大小。

2.0.0 版本。GDAL 1.6.1 版本。

Enhanced: 3.4.0 max and min resampling options added

更新: 2.1.0 版本 SRID 参考。

返回

返回 0.001 和 0.0015 的像素大小。

```
-- the original raster pixel size
SELECT ST_PixelWidth(ST_AddBand(ST_MakeEmptyRaster(100, 100, 0, 0, 0.001, -0.001, 0, 0, 4269), '8BUI'::text, 1, 0)) width

width
-----
0.001

-- the rescaled raster raster pixel size
SELECT ST_PixelWidth(ST_Rescale(ST_AddBand(ST_MakeEmptyRaster(100, 100, 0, 0, 0.001, -0.001, 0, 0, 4269), '8BUI'::text, 1, 0), 0.0015)) width

width
-----
0.0015
```

返回

ST_Resize, ST_Resample, ST_SetScale, ST_ScaleX, ST_ScaleY, ST_Transform

11.7.9 ST_Reskew

ST_Reskew — 旋转 (旋转/倾斜) 栅格数据。 NearestNeighbor(最近邻), Bilinear, Cubic, CubicSpline 和 Lanczos 是最近邻的别名。最近邻 NearestNeighbor 是默认值。

Synopsis

```
raster ST_Reskew(raster rast, double precision skewxy, text algorithm=NearestNeighbor, double
precision maxerr=0.125);
raster ST_Reskew(raster rast, double precision skewx, double precision skewy, text algorithm=NearestNeighbor,
double precision maxerr=0.125);
```

参数

skewx 和 **skewy** 是旋转/倾斜的度数。 NearestNeighbor(最近邻), Bilinear, Cubic, CubicSpline 和 Lanczos 是最近邻的别名。最近邻 NearestNeighbor 是默认值。

skewx 和 **skewy** 是旋转/倾斜的度数。

最近邻 NearestNeighbor 是默认值。

maxerr 是最近邻 NearestNeighbor 的默认值 0.125。



Note

最近邻 NearestNeighbor 是默认值。



Note

ST_Reskew 函数与 **ST_SetSkew** 函数类似。 **ST_SetSkew** 函数 (最近邻) 是默认值。 **ST_Reskew** 函数是最近邻的别名。最近邻 NearestNeighbor 是默认值。 **ST_SetSkew** 函数是最近邻的别名。

2.0.0 版本中，GDAL 1.6.1 版本中。

最近邻: 2.1.0 版本中 SRID 最近邻。

参数

最近邻 0.0 最近邻 0.0015 最近邻。

```
-- the original raster non-rotated
SELECT ST_Rotation(ST_AddBand(ST_MakeEmptyRaster(100, 100, 0, 0, 0.001, -0.001, 0, 0, 4269) ←
, '8BUI'::text, 1, 0));

-- result
0

-- the reskewed raster raster rotation
SELECT ST_Rotation(ST_Reskew(ST_AddBand(ST_MakeEmptyRaster(100, 100, 0, 0, 0.001, -0.001, ←
0, 0, 4269), '8BUI'::text, 1, 0), 0.0015));

-- result
-0.982793723247329
```



ST Resample, ST Rescale, ST SetSkew, ST SetRotation, ST SkewX, ST SkewY, ST Transform

11.7.10 ST_SnapToGrid

ST_SnapToGrid — `geometry` `geometry`. NearestNeighbor(`geometry` `geometry`), Bilinear, Cubic, CubicSpline `int` Lanczos `geometry` `geometry`. `geometry` NearestNeighbor `geometry`.

Synopsis

```
raster ST_SnapToGrid(raster rast, double precision gridx, double precision gridy, text algorithm=NearestN
double precision maxerr=0.125, double precision scalex=DEFAULT 0, double precision scaley=DEFAULT
0);
```

```
raster ST_SnapToGrid(raster rast, double precision gridx, double precision gridy, double precision  
scalex, double precision scaley, text algorithm=NearestNeighbor, double precision maxerr=0.125);
```

ST_SnapToGrid(raster rast, double precision gridx, double precision gridy, double precision
 scalexy, text algorithm=NearestNeighbor, double precision maxerr=0.125);



00000000 (gridx & gridy) 00000000 (scalex & scaley) 0000000000000000
 0000000000000000. NearestNeighbor(00000000), Bilinear, Cubic, CubicSpline 0
 0 Lanczos 00000000000000000000000000000000. 00000000000000000000
 NearestNeighbor 000.

`gridx` `gridy` `int`, `int`. `int`, `int`.

You can optionally define the pixel size of the new grid with `scalex` and `scaley`.

[illegible]

```
maxerr 0.125
```



Note

GDAL Warp resampling methods.



Note

ST Resample

2.0.0 20200818. GDAL 1.6.1 20200818.

Figure 2.1.0: SRID 2146

例

以下 SQL 语句返回栅格的上左角 X 坐标。

```
-- the original raster upper left X
SELECT ST_UpperLeftX(ST_AddBand(ST_MakeEmptyRaster(10, 10, 0, 0, 0.001, -0.001, 0, 0, 4269) ←
, '8BUI'::text, 1, 0));
-- result
0

-- the upper left of raster after snapping
SELECT ST_UpperLeftX(ST_SnapToGrid(ST_AddBand(ST_MakeEmptyRaster(10, 10, 0, 0, 0.001, ←
-0.001, 0, 0, 4269), '8BUI'::text, 1, 0), 0.0002, 0.0002));

--result
-0.0008
```

例

[ST_Resample](#), [ST_Rescale](#), [ST_UpperLeftX](#), [ST_UpperLeftY](#)

11.7.11 ST_Resize

ST_Resize — 将栅格重新调整到指定的宽度和高度。

Synopsis

raster **ST_Resize**(raster rast, integer width, integer height, text algorithm=NearestNeighbor, double precision maxerr=0.125);
raster **ST_Resize**(raster rast, double precision percentwidth, double precision percentheight, text algorithm=NearestNeighbor, double precision maxerr=0.125);
raster **ST_Resize**(raster rast, text width, text height, text algorithm=NearestNeighbor, double precision maxerr=0.125);

例

以下 SQL 语句将栅格重新调整到指定的宽度和高度。使用最近邻插值算法。

NearestNeighbor(最近邻), Bilinear, Cubic, CubicSpline 和 Lanczos 是支持的插值算法。最近邻插值算法是默认值。

1 将栅格重新调整到指定的宽度和高度。

2 将栅格重新调整到指定的宽度和高度，并指定最大误差。

3 将栅格重新调整到指定的宽度和高度，并指定最大误差和插值算法。

2.1.0 版本开始支持。GDAL 1.6.1 版本开始支持。

例

```
WITH foo AS(
SELECT
  1 AS rid,
  ST_Resize(
    ST_AddBand(
      ST_MakeEmptyRaster(1000, 1000, 0, 0, 1, -1, 0, 0, 0)
      , 1, '8BUI', 255, 0
    )
    , '50%', '500') AS rast
UNION ALL
SELECT
  2 AS rid,
  ST_Resize(
    ST_AddBand(
      ST_MakeEmptyRaster(1000, 1000, 0, 0, 1, -1, 0, 0, 0)
      , 1, '8BUI', 255, 0
    )
    , 500, 100) AS rast
UNION ALL
SELECT
  3 AS rid,
  ST_Resize(
    ST_AddBand(
      ST_MakeEmptyRaster(1000, 1000, 0, 0, 1, -1, 0, 0, 0)
      , 1, '8BUI', 255, 0
    )
    , 0.25, 0.9) AS rast
), bar AS (
  SELECT rid, ST_Metadata(rast) AS meta, rast FROM foo
)
SELECT rid, (meta).* FROM bar
```

rid	upperleftx	upperlefty	width	height	scalex	scaley	skewx	skewy	srid	
numbands										
1	0	0	500	500	1	-1	0	0	0	
2	0	0	500	100	1	-1	0	0	0	
3	0	0	250	900	1	-1	0	0	0	

(3 rows)

例

ST_Resample, ST_Rescale, ST_Reskew, ST_SnapToGrid

11.7.12 ST_Transform

ST Transform — 将地理要素从一种空间参考系统转换为另一种空间参考系统。最近邻、双线性、三次、三次样条、Lanczos 插值方法。最近邻插值。

Synopsis

```
raster ST_Transform(raster rast, integer srid, text algorithm=NearestNeighbor, double precision
maxerr=0.125, double precision scalex, double precision scaley);
raster ST_Transform(raster rast, integer srid, double precision scalex, double precision scaley, text
algorithm=NearestNeighbor, double precision maxerr=0.125);
raster ST_Transform(raster rast, raster alignto, text algorithm=NearestNeighbor, double precision
maxerr=0.125);
```



 (pixel warp) 

 NearestNeighbor
 0.125 .

GDAL's 'NearestNeighbor', 'Bilinear', 'Cubic', 'CubicSpline', 'Lanczos' resampling methods.

[illegible]

XXXXXXXX, 3 alignto XXXXXXXXXXXXXXXX. XXXXXXXXXXXXXXXXXXXX
XX (SRID) XXXXXXXX, (ST SameAlignment = TRUE XXX) XXXXXXXXXXXXXXXXXXXX.

Note



If you find your transformation support is not working right, you may need to set the environment variable PROJSO to the .so or .dll projection library your PostGIS is using. This just needs to have the name of the file. So for example on windows, you would in Control Panel -> System -> Environment Variables add a system variable called PROJSO and set it to libproj.dll (if you are using proj 4.6.1). You'll have to restart your PostgreSQL service/daemon after this change.



Warning

When transforming a coverage of tiles, you almost always want to use a reference raster to insure same alignment and no gaps in your tiles as demonstrated in example: Variant 3.

2.0.0 11111111111111111111. GDAL 1.6.1 11111111111111111111.

2.1.0 ST Transform(rast, alignto) [ST Transform\(rast, alignto\)](#).



```
SELECT ST_Width(mass_stm) As w_before, ST_Width(wgs_84) As w_after,
       ST_Height(mass_stm) As h_before, ST_Height(wgs_84) As h_after
FROM
  ( SELECT rast As mass_stm, ST_Transform(rast,4326) As wgs_84
    , ST_Transform(rast,4326, 'Bilinear') AS wgs_84_bilin
    FROM aerials.o_2_boston
      WHERE ST_Intersects(rast,
        ST_Transform(ST_MakeEnvelope(-71.128, 42.2392, -71.1277, 42.2397, 4326) ↵
          ,26986) )
    LIMIT 1) As foo;
```

w_before	w_after	h_before	h_after
200	228	200	170

 栅格数据 (mass_stm)	 WGS84 栅格 (wgs_84) 栅格	 栅格 NN 栅格 Bilinear 栅格 栅格 WGS84 栅格 (wgs_84_bilin) 栅格

图 3

使用 ST_Transform(raster, srid) 或 ST_Transform(raster, alignto) 对栅格数据进行坐标变换。


```
WITH foo AS (
  SELECT 0 AS rid, ST_AddBand(ST_MakeEmptyRaster(2, 2, -500000, 600000, 100, -100, 0, 0, 2163), 1, '16BUI', 1, 0) AS rast UNION ALL
  SELECT 1, ST_AddBand(ST_MakeEmptyRaster(2, 2, -499800, 600000, 100, -100, 0, 0, 2163), 1, '16BUI', 2, 0) AS rast UNION ALL
  SELECT 2, ST_AddBand(ST_MakeEmptyRaster(2, 2, -499600, 600000, 100, -100, 0, 0, 2163), 1, '16BUI', 3, 0) AS rast UNION ALL

  SELECT 3, ST_AddBand(ST_MakeEmptyRaster(2, 2, -500000, 599800, 100, -100, 0, 0, 2163), 1, '16BUI', 10, 0) AS rast UNION ALL
  SELECT 4, ST_AddBand(ST_MakeEmptyRaster(2, 2, -499800, 599800, 100, -100, 0, 0, 2163), 1, '16BUI', 20, 0) AS rast UNION ALL
  SELECT 5, ST_AddBand(ST_MakeEmptyRaster(2, 2, -499600, 599800, 100, -100, 0, 0, 2163), 1, '16BUI', 30, 0) AS rast UNION ALL

  SELECT 6, ST_AddBand(ST_MakeEmptyRaster(2, 2, -500000, 599600, 100, -100, 0, 0, 2163), 1, '16BUI', 100, 0) AS rast UNION ALL
  SELECT 7, ST_AddBand(ST_MakeEmptyRaster(2, 2, -499800, 599600, 100, -100, 0, 0, 2163), 1, '16BUI', 200, 0) AS rast UNION ALL
  SELECT 8, ST_AddBand(ST_MakeEmptyRaster(2, 2, -499600, 599600, 100, -100, 0, 0, 2163), 1, '16BUI', 300, 0) AS rast
), bar AS (
  SELECT
    ST_Transform(rast, 4269) AS alignto
  FROM foo
  LIMIT 1
), baz AS (
  SELECT
    rid,
    rast,
    ST_Transform(rast, 4269) AS not_aligned,
    ST_Transform(rast, alignto) AS aligned
```

```
FROM foo
CROSS JOIN bar
)
SELECT
  ST_SameAlignment(rast) AS rast,
  ST_SameAlignment(not_aligned) AS not_aligned,
  ST_SameAlignment(aligned) AS aligned
FROM baz

rast | not_aligned | aligned
-----+-----+-----
t    | f             | t
```



☒☒

ST_Transform, ST_SetSRID

11.8 地理函数

11.8.1 ST_SetBandNoDataValue

ST_SetBandNoDataValue — NODATA 值。 1 个 NODATA 值。 1 个 NODATA 值, nodata value = NULL 值。

Synopsis

raster **ST_SetBandNoDataValue**(raster rast, double precision nodatavalue);
raster **ST_SetBandNoDataValue**(raster rast, integer band, double precision nodatavalue, boolean forcechecking=false);

☒☒

☒☒☒ NODATA 值。 1 个 NODATA 值。 1 个 NODATA 值, nodata value = NULL 值。 ST_Polygon, ST_DumpAsPolygons, ST_PixelAs...()



```
-- change just first band no data value
UPDATE dummy_rast
  SET rast = ST_SetBandNoDataValue(rast,1, 254)
WHERE rid = 2;

-- change no data band value of bands 1,2,3
UPDATE dummy_rast
  SET rast =
    ST_SetBandNoDataValue(
      ST_SetBandNoDataValue(
        ST_SetBandNoDataValue(
          rast,1, 254)
        ,2,99),
      3,108)
  WHERE rid = 2;

-- wipe out the nodata value this will ensure all pixels are considered for all processing ←
functions
UPDATE dummy_rast
  SET rast = ST_SetBandNoDataValue(rast,1, NULL)
WHERE rid = 2;
```



ST_BandNoDataValue, ST_NumBands

11.8.2 ST_SetBandIsNoData

ST_SetBandIsNoData — `isnodata` `XXXXXXXXXXXX`.

Synopsis

```
raster ST_SetBandIsNoData(raster rast, integer band=1);
```



`isnodata` 0 or 1. If 1, no data was received from the sensor.
ST BandIsNoData 0 or 1. If 1, no data was received from the sensor.

2.0.0 ☒☒☒☒☒☒☒☒☒☒☒.



```
-- Create dummy table with one raster column
create table dummy_rast (rid integer, rast raster);

-- Add raster with two bands, one pixel/band. In the first band, nodatavalue = pixel value
= 3.
-- In the second band, nodatavalue = 13, pixel value = 4
insert into dummy_rast values(1,
```



```
(
'01' -- little endian (uint8 ndr)
||
'0000' -- version (uint16 0)
||
'0200' -- nBands (uint16 0)
||
'17263529ED684A3F' -- scaleX (float64 0.000805965234044584)
||
'F9253529ED684ABF' -- scaleY (float64 -0.00080596523404458)
||
'1C9F33CE69E352C0' -- ipX (float64 -75.5533328537098)
||
'718F0E9A27A44840' -- ipY (float64 49.2824585505576)
||
'ED50EB853EC32B3F' -- skewX (float64 0.000211812383858707)
||
'7550EB853EC32B3F' -- skewY (float64 0.000211812383858704)
||
'E6100000' -- SRID (int32 4326)
||
'0100' -- width (uint16 1)
||
'0100' -- height (uint16 1)
||
'4' -- hasnodatavalue set to true, isnodata value set to false (when it should be true)
||
'2' -- first band type (4BUI)
||
'03' -- novalue==3
||
'03' -- pixel(0,0)==3 (same that nodata)
||
'0' -- hasnodatavalue set to false
||
'5' -- second band type (16BSI)
||
'0D00' -- novalue==13
||
'0400' -- pixel(0,0)==4
)::raster
);

select st_bandisnodata(rast, 1) from dummy_rast where rid = 1; -- Expected false
select st_bandisnodata(rast, 1, TRUE) from dummy_rast where rid = 1; -- Expected true

-- The isnodata flag is dirty. We are going to set it to true
update dummy_rast set rast = st_setbandisnodata(rast, 1) where rid = 1;

select st_bandisnodata(rast, 1) from dummy_rast where rid = 1; -- Expected true
```

☒☒

ST_BandNoDataValue, ST_NumBands, ST_SetBandNoDataValue, ST_BandIsNoData

11.8.3 ST_SetBandPath

ST_SetBandPath — Update the external path and band number of an out-db band

Synopsis

raster **ST_SetBandPath**(raster rast, integer band, text outdbpath, integer outdbindex, boolean force=false)

⚠⚠

Updates an out-db band's external raster file path and external band number.



Note

If force is set to true, no tests are done to ensure compatibility (e.g. alignment, pixel support) between the external raster file and the PostGIS raster. This mode is intended for file system changes where the external raster resides.

Availability: 2.5.0

⚠⚠

```
WITH foo AS (
  SELECT
    ST_AddBand(NULL::raster, '/home/pele/devel/geo/postgis-git/raster/test/regress/ ↵
      loader/Projected.tif', NULL::int[]) AS rast
)
SELECT
  1 AS query,
  *
FROM ST_BandMetadata(
  (SELECT rast FROM foo),
  ARRAY[1,3,2]::int[]
)
UNION ALL
SELECT
  2,
  *
FROM ST_BandMetadata(
  (
    SELECT
      ST_SetBandPath(
        rast,
        2,
        '/home/pele/devel/geo/postgis-git/raster/test/regress/loader/Projected2.tif ↵
        ',
        1
      ) AS rast
    FROM foo
  ),
  ARRAY[1,3,2]::int[]
)
ORDER BY 1, 2;
```

query	bandnum	pixeltype	nodatavalue	isoutdb	↔
				path	↔
outdbbandnum					
-----+-----+-----+-----+-----+-----					
1	1	8BUI		t	/home/pele/devel/geo/postgis-git/ ↔
		raster/test/regress/loader/Projected.tif			1
1	2	8BUI		t	/home/pele/devel/geo/postgis-git/ ↔
		raster/test/regress/loader/Projected.tif			2
1	3	8BUI		t	/home/pele/devel/geo/postgis-git/ ↔
		raster/test/regress/loader/Projected.tif			3
2	1	8BUI		t	/home/pele/devel/geo/postgis-git/ ↔
		raster/test/regress/loader/Projected.tif			1
2	2	8BUI		t	/home/pele/devel/geo/postgis-git/ ↔
		raster/test/regress/loader/Projected2.tif			1
2	3	8BUI		t	/home/pele/devel/geo/postgis-git/ ↔
		raster/test/regress/loader/Projected.tif			3

☒☒

ST_BandMetaData, ST_SetBandIndex

11.8.4 ST_SetBandIndex

ST_SetBandIndex — Update the external band number of an out-db band

Synopsis

raster **ST_SetBandIndex**(raster rast, integer band, integer outdbindex, boolean force=false);

☒☒

Updates an out-db band’s external band number. This does not touch the external raster file associated with the out-db band



Note
If force is set to true, no tests are done to ensure compatibility (e.g. alignment, pixel support) between the external raster file and the PostGIS raster. This mode is intended for where bands are moved around in the external raster file.



Note
Internally, this method replaces the PostGIS raster’s band at index band with a new band instead of updating the existing path information.

Availability: 2.5.0

❏

```
WITH foo AS (
  SELECT
    ST_AddBand(NULL::raster, '/home/pele/devel/geo/postgis-git/raster/test/regress/ ↵
      loader/Projected.tif', NULL::int[]) AS rast
)
SELECT
  1 AS query,
  *
FROM ST_BandMetadata(
  (SELECT rast FROM foo),
  ARRAY[1,3,2]::int[]
)
UNION ALL
SELECT
  2,
  *
FROM ST_BandMetadata(
  (
    SELECT
      ST_SetBandIndex(
        rast,
        2,
        1
      ) AS rast
    FROM foo
  ),
  ARRAY[1,3,2]::int[]
)
ORDER BY 1, 2;
```

query	bandnum	pixeltype	nodatavalue	isoutdb	path	outdbbandnum
1	1	8BUI		t	/home/pele/devel/geo/postgis-git/ ↵ raster/test/regress/loader/Projected.tif	1
1	2	8BUI		t	/home/pele/devel/geo/postgis-git/ ↵ raster/test/regress/loader/Projected.tif	2
1	3	8BUI		t	/home/pele/devel/geo/postgis-git/ ↵ raster/test/regress/loader/Projected.tif	3
2	1	8BUI		t	/home/pele/devel/geo/postgis-git/ ↵ raster/test/regress/loader/Projected.tif	1
2	2	8BUI		t	/home/pele/devel/geo/postgis-git/ ↵ raster/test/regress/loader/Projected.tif	1
2	3	8BUI		t	/home/pele/devel/geo/postgis-git/ ↵ raster/test/regress/loader/Projected.tif	3

❏

ST_BandMetaData, ST_SetBandPath

11.9 统计函数

11.9.1 ST_Count

ST_Count — 返回栅格中指定波段内非空像素的数量。如果指定了 `exclude_nodata_value` 参数，则排除该值对应的像素。默认值为 1。如果指定了 `NODATA` 参数，则排除 NODATA 值对应的像素。

Synopsis

```
bigint ST_Count(raster rast, integer nband=1, boolean exclude_nodata_value=true);
bigint ST_Count(raster rast, boolean exclude_nodata_value);
```

参数

`nband` 指定要统计的波段。默认为 1。如果指定了 `NODATA` 参数，则排除 NODATA 值对应的像素。



Note

`exclude_nodata_value` 参数，如果为 `true`，则排除 `NODATA` 值对应的像素。如果指定了 `NODATA` 参数，则排除 NODATA 值对应的像素。

2.2.0 版本中，`ST_Count(rastertable, rastercolumn, ...)` 函数返回一个聚合函数。使用 `ST_CountAgg` 函数。

2.0.0 版本中，`ST_Count` 函数返回一个聚合函数。

示例

```
--example will count all pixels not 249 and one will count all pixels. --
SELECT rid, ST_Count(ST_SetBandNoDataValue(rast,249)) As exclude_nodata,
       ST_Count(ST_SetBandNoDataValue(rast,249),false) As include_nodata
FROM dummy_rast WHERE rid=2;
```

rid	exclude_nodata	include_nodata
2	23	25

相关链接

[ST_CountAgg](#), [ST_SummaryStats](#), [ST_SetBandNoDataValue](#)

11.9.2 ST_CountAgg

ST_CountAgg — 返回栅格中指定波段内非空像素的数量。如果指定了 `exclude_nodata_value` 参数，则排除该值对应的像素。默认值为 1。如果指定了 `NODATA` 参数，则排除 NODATA 值对应的像素。

Synopsis

bigint **ST_CountAgg**(raster rast, integer nband, boolean exclude_nodata_value, double precision sample_percent);
 bigint **ST_CountAgg**(raster rast, integer nband, boolean exclude_nodata_value);
 bigint **ST_CountAgg**(raster rast, boolean exclude_nodata_value);

返回

返回一个 64 位整数。nband 默认为 1。exclude_nodata_value 默认为 true，表示在统计时忽略 nodata 值。sample_percent 默认为 0，表示统计所有像素。sample_percent 为 1 表示统计所有像素。

2.2.0 版本引入。

示例

```
WITH foo AS (
  SELECT
    rast.rast
  FROM (
    SELECT ST_SetValue(
      ST_SetValue(
        ST_SetValue(
          ST_AddBand(
            ST_MakeEmptyRaster(10, 10, 10, 10, 2, 2, 0, 0,0)
            , 1, '64BF', 0, 0
          )
          , 1, 1, 1, -10
        )
        , 1, 5, 4, 0
      )
      , 1, 5, 5, 3.14159
    ) AS rast
  ) AS rast
  FULL JOIN (
    SELECT generate_series(1, 10) AS id
  ) AS id
  ON 1 = 1
)
SELECT
  ST_CountAgg(rast, 1, TRUE)
FROM foo;

 st_countagg
-----
          20
(1 row)
```

参见

[ST_Count](#), [ST_SummaryStats](#), [ST_SetBandNoDataValue](#)

11.9.3 ST_Histogram

ST_Histogram — (bin; 栅格, 带, 排除空值, 精度, 宽度, 右偏) 返回包含统计信息的表。 统计信息包括最小值, 最大值, 计数, 百分比。 返回的表包含 nband 列。

Synopsis

SETOF record **ST_Histogram**(raster rast, integer nband=1, boolean exclude_nodata_value=true, integer bins=autocomputed, double precision[] width=NULL, boolean right=false);
SETOF record **ST_Histogram**(raster rast, integer nband, integer bins, double precision[] width=NULL, boolean right=false);
SETOF record **ST_Histogram**(raster rast, integer nband, boolean exclude_nodata_value, integer bins, boolean right);
SETOF record **ST_Histogram**(raster rast, integer nband, integer bins, boolean right);

返回

返回的表包含 min, max, count, percent 列。 返回的表包含 nband 列。



Note

如果 exclude_nodata_value 为 true, 则返回的表包含 exclude_nodata_value 列。

width width: 精度/宽度。 精度 width 列, width 列。

例如: 9, width [a, b, c] [a, b, c, a, b, c, a, b, c] 列。

bins (breakout) 列: 精度/宽度。 精度 bins 列。

right 精度/宽度 (精度) 列。 X 精度/宽度 [a, b] 列 (a, b) 列。

Changed: 3.1.0 Removed ST_Histogram(table_name, column_name) variant.

2.0.0 精度/宽度。

例如: 精度 - 1, 2, 3 精度/宽度。

```
SELECT band, (stats).*
FROM (SELECT rid, band, ST_Histogram(rast, band) As stats
      FROM dummy_rast CROSS JOIN generate_series(1,3) As band
      WHERE rid=2) As foo;
```

band	min	max	count	percent
1	249	250	2	0.08
1	250	251	2	0.08
1	251	252	1	0.04
1	252	253	2	0.08
1	253	254	18	0.72

2	78	113.2	11	0.44
2	113.2	148.4	4	0.16
2	148.4	183.6	4	0.16
2	183.6	218.8	1	0.04
2	218.8	254	5	0.2
3	62	100.4	11	0.44
3	100.4	138.8	5	0.2
3	138.8	177.2	4	0.16
3	177.2	215.6	1	0.04
3	215.6	254	4	0.16

图 11.9.3: 图 2 的直方图，显示了 6 个 bin 的统计信息。

```
SELECT (stats).*
FROM (SELECT rid, ST_Histogram(rast, 2,6) As stats
      FROM dummy_rast
      WHERE rid=2) As foo;
```

min	max	count	percent
78	107.333333	9	0.36
107.333333	136.666667	6	0.24
136.666667	166	0	0
166	195.333333	4	0.16
195.333333	224.666667	1	0.04
224.666667	254	5	0.2

(6 rows)

-- Same as previous but we explicitly control the pixel value range of each bin.

```
SELECT (stats).*
FROM (SELECT rid, ST_Histogram(rast, 2,6,ARRAY[0.5,1,4,100,5]) As stats
      FROM dummy_rast
      WHERE rid=2) As foo;
```

min	max	count	percent
78	78.5	1	0.08
78.5	79.5	1	0.04
79.5	83.5	0	0
83.5	183.5	17	0.0068
183.5	188.5	0	0
188.5	254	6	0.003664

(6 rows)

图 11.9.4

[ST_Count](#), [ST_SummaryStats](#), [ST_SummaryStatsAgg](#)

11.9.4 ST_Quantile

`ST_Quantile` — 返回指定 (population) 的指定 (quantile) 值。例如，`ST_Quantile(rast, 0.25)` 返回 25% (percentile) 的值。

Synopsis

SETOF record **ST_Quantile**(raster rast, integer nband=1, boolean exclude_nodata_value=true, double precision[] quantiles=NULL);
SETOF record **ST_Quantile**(raster rast, double precision[] quantiles);
SETOF record **ST_Quantile**(raster rast, integer nband, double precision[] quantiles);
double precision **ST_Quantile**(raster rast, double precision quantile);
double precision **ST_Quantile**(raster rast, boolean exclude_nodata_value, double precision quantile=NULL);
double precision **ST_Quantile**(raster rast, integer nband, double precision quantile);
double precision **ST_Quantile**(raster rast, integer nband, boolean exclude_nodata_value, double precision quantile);
double precision **ST_Quantile**(raster rast, integer nband, double precision quantile);

注意

ST_Quantile (population) ST_Quantile (quantile) 0. 0.25, 0.5, 0.75 (percentile) ST_Quantile.



Note

exclude_nodata_value 默认为 true, NODATA 默认为 false.

Changed: 3.1.0 Removed ST_Quantile(table_name, column_name) variant.

2.0.0 支持 25%, 50%, 75% (percentile) 计算.

注意

```
UPDATE dummy_rast SET rast = ST_SetBandNoDataValue(rast,249) WHERE rid=2;
--Example will consider only pixels of band 1 that are not 249 and in named quantiles --
```

```
SELECT (pvq).*
FROM (SELECT ST_Quantile(rast, ARRAY[0.25,0.75]) As pvq
      FROM dummy_rast WHERE rid=2) As foo
ORDER BY (pvq).quantile;
```

quantile	value
0.25	253
0.75	254

```
SELECT ST_Quantile(rast, 0.75) As value
FROM dummy_rast WHERE rid=2;
```

```
value
-----
254
```

```
--real live example. Quantile of all pixels in band 2 intersecting a geometry
SELECT rid, (ST_Quantile(rast,2)).* As pvc
FROM o_4_boston
WHERE ST_Intersects(rast,
  ST_GeomFromText('POLYGON((224486 892151,224486 892200,224706 892200,224706
    892151,224486 892151))',26986)
```

```
    )
ORDER BY value, quantile,rid
;
```

rid	quantile	value
1	0	0
2	0	0
14	0	1
15	0	2
14	0.25	37
1	0.25	42
15	0.25	47
2	0.25	50
14	0.5	56
1	0.5	64
15	0.5	66
2	0.5	77
14	0.75	81
15	0.75	87
1	0.75	94
2	0.75	106
14	1	199
1	1	244
2	1	255
15	1	255

☐☐

[ST_Count](#), [ST_SummaryStats](#), [ST_SummaryStatsAgg](#), [ST_SetBandNoDataValue](#)

11.9.5 ST_SummaryStats

`ST_SummaryStats` — 返回栅格的统计信息，包括 count, sum, mean, stddev, min, max 等。返回类型是 `text`。如果 nband 为 1，则返回一个值。

Synopsis

```
summarystats ST_SummaryStats(raster rast, boolean exclude_nodata_value);
summarystats ST_SummaryStats(raster rast, integer nband, boolean exclude_nodata_value);
```

☐☐

返回的统计信息包括 count, sum, mean, stddev, min, max 等。返回类型是 `text`。如果 nband 为 1，则返回一个值。



Note

如果 nband 为 1，则返回一个值。如果 exclude_nodata_value 为 true，则排除 nodata 值。



Note

在调用 `ST_SummaryStats` 时，`sample_percent` 为 1 表示使用所有像素。

2.2.0 版本中 `ST_SummaryStats(rastertable, rastercolumn, ...)` 函数已弃用。请使用 `ST_SummaryStatsAgg` 函数。
2.0.0 版本中 `ST_SummaryStats` 函数已弃用。

例：统计栅格数据

```
SELECT rid, band, (stats).*
FROM (SELECT rid, band, ST_SummaryStats(rast, band) As stats
      FROM dummy_rast CROSS JOIN generate_series(1,3) As band
      WHERE rid=2) As foo;
```

rid	band	count	sum	mean	stddev	min	max
2	1	23	5821	253.086957	1.248061	250	254
2	2	25	3682	147.28	59.862188	78	254
2	3	25	3290	131.6	61.647384	62	254

例：统计栅格数据的像素值

PostGIS 版本 64 位的栅格数据（例如 102,000 个，150x150 个像素，134,000 个）需要 574 兆字节。

```
WITH
-- our features of interest
feat AS (SELECT gid As building_id, geom_26986 As geom FROM buildings AS b
        WHERE gid IN(100, 103,150)
        ),
-- clip band 2 of raster tiles to boundaries of builds
-- then get stats for these clipped regions
b_stats AS
(SELECT building_id, (stats).*
FROM (SELECT building_id, ST_SummaryStats(ST_Clip(rast,2,geom)) As stats
      FROM aerials.boston
      INNER JOIN feat
      ON ST_Intersects(feats.geom,rast)
      ) As foo
      )
-- finally summarize stats
SELECT building_id, SUM(count) As num_pixels
      , MIN(min) As min_pval
      , MAX(max) As max_pval
      , SUM(mean*count)/SUM(count) As avg_pval
      FROM b_stats
      WHERE count
      > 0
```

building_id	num_pixels	min_pval	max_pval	avg_pval
100	1090	1	255	61.0697247706422
103	655	7	182	70.5038167938931
150	895	2	252	185.642458100559

例: 统计每个波段

```
-- stats for each band --
SELECT band, (stats).*
FROM (SELECT band, ST_SummaryStats('o_4_boston','rast', band) As stats
      FROM generate_series(1,3) As band) As foo;
```

band	count	sum	mean	stddev	min	max
1	8450000	725799	82.7064349112426	45.6800222638537	0	255
2	8450000	700487	81.4197705325444	44.2161184161765	0	255
3	8450000	575943	74.682739408284	44.2143885481407	0	255

```
-- For a table -- will get better speed if set sampling to less than 100%
-- Here we set to 25% and get a much faster answer
SELECT band, (stats).*
FROM (SELECT band, ST_SummaryStats('o_4_boston','rast', band,true,0.25) As stats
      FROM generate_series(1,3) As band) As foo;
```

band	count	sum	mean	stddev	min	max
1	2112500	180686	82.6890480473373	45.6961043857248	0	255
2	2112500	174571	81.448503668639	44.2252623171821	0	255
3	2112500	144364	74.6765884023669	44.2014869384578	0	255

例

summarystats, ST_SummaryStatsAgg, ST_Count, ST_Clip

11.9.6 ST_SummaryStatsAgg

ST_SummaryStatsAgg — 聚合统计。返回 count, sum, mean, stddev, min, max 统计结果。聚合统计 1 个波段。

Synopsis

```
summarystats ST_SummaryStatsAgg(raster rast, integer nband, boolean exclude_nodata_value, double precision sample_percent);
summarystats ST_SummaryStatsAgg(raster rast, boolean exclude_nodata_value, double precision sample_percent);
summarystats ST_SummaryStatsAgg(raster rast, integer nband, boolean exclude_nodata_value);
```

例

聚合统计 count, sum, mean, stddev, min, max 统计结果 **summarystats** 聚合统计 nband 个波段。



Note

如果 nodata 值被包含在内，则 exclude_nodata_value 必须为 true。



Note

ST_SummaryStatsAgg 函数支持 sample_percent 参数，其值在 0 到 1 之间，表示对输入数据进行随机采样。默认值为 1.0，即使用全部数据。

2.2.0 新增功能。

SQL

```
WITH foo AS (
  SELECT
    rast.rast
  FROM (
    SELECT ST_SetValue(
      ST_SetValue(
        ST_SetValue(
          ST_AddBand(
            ST_MakeEmptyRaster(10, 10, 10, 10, 2, 2, 0, 0,0)
            , 1, '64BF', 0, 0
          )
          , 1, 1, 1, -10
        )
        , 1, 5, 4, 0
      )
      , 1, 5, 5, 3.14159
    ) AS rast
  ) AS rast
  FULL JOIN (
    SELECT generate_series(1, 10) AS id
  ) AS id
  ON 1 = 1
)
SELECT
  (stats).count,
  round((stats).sum::numeric, 3),
  round((stats).mean::numeric, 3),
  round((stats).stddev::numeric, 3),
  round((stats).min::numeric, 3),
  round((stats).max::numeric, 3)
FROM (
  SELECT
    ST_SummaryStatsAgg(rast, 1, TRUE, 1) AS stats
  FROM foo
) bar;
```

count	round	round	round	round	round
20	-68.584	-3.429	6.571	-10.000	3.142

(1 row)

SQL

[summarystats](#), [ST_SummaryStats](#), [ST_Count](#), [ST_Clip](#)

11.9.7 ST_ValueCount

ST_ValueCount — 返回指定栅格（或栅格表）中指定值的统计信息。返回一个包含两个元素的数组：第一个元素是值，第二个元素是该值在指定栅格中的计数。如果指定了 `exclude_nodata_value` 参数，则统计信息将排除 NODATA 值。如果指定了 `searchvalues` 参数，则统计信息将仅针对指定的搜索值进行计算。

Synopsis

```
SETOF record ST_ValueCount(raster rast, integer nband=1, boolean exclude_nodata_value=true,
double precision[] searchvalues=NULL, double precision roundto=0, double precision OUT value, in-
teger OUT count);
SETOF record ST_ValueCount(raster rast, integer nband, double precision[] searchvalues, double
precision roundto=0, double precision OUT value, integer OUT count);
SETOF record ST_ValueCount(raster rast, double precision[] searchvalues, double precision roundto=0,
double precision OUT value, integer OUT count);
bigint ST_ValueCount(raster rast, double precision searchvalue, double precision roundto=0);
bigint ST_ValueCount(raster rast, integer nband, boolean exclude_nodata_value, double precision
searchvalue, double precision roundto=0);
bigint ST_ValueCount(raster rast, integer nband, double precision searchvalue, double precision
roundto=0);
SETOF record ST_ValueCount(text rastertable, text rastercolumn, integer nband=1, boolean ex-
clude_nodata_value=true, double precision[] searchvalues=NULL, double precision roundto=0, dou-
ble precision OUT value, integer OUT count);
SETOF record ST_ValueCount(text rastertable, text rastercolumn, double precision[] searchvalues,
double precision roundto=0, double precision OUT value, integer OUT count);
SETOF record ST_ValueCount(text rastertable, text rastercolumn, integer nband, double precision[]
searchvalues, double precision roundto=0, double precision OUT value, integer OUT count);
bigint ST_ValueCount(text rastertable, text rastercolumn, integer nband, boolean exclude_nodata_value,
double precision searchvalue, double precision roundto=0);
bigint ST_ValueCount(text rastertable, text rastercolumn, double precision searchvalue, double pre-
cision roundto=0);
bigint ST_ValueCount(text rastertable, text rastercolumn, integer nband, double precision search-
value, double precision roundto=0);
```

返回

返回一个包含两个元素的数组：第一个元素是值，第二个元素是该值在指定栅格中的计数。

如果指定了 `nband` 参数，则统计信息将仅针对指定的波段进行计算。如果指定了 `searchvalues` 参数，则统计信息将仅针对指定的搜索值进行计算。



Note

`exclude_nodata_value` 参数默认为 `true`，NODATA 值将被排除在统计信息之外。

2.0.0 版本引入。

返回

```
UPDATE dummy_rast SET rast = ST_SetBandNoDataValue(rast,249) WHERE rid=2;
--Example will count only pixels of band 1 that are not 249. --
```

```
SELECT (pvc).*
FROM (SELECT ST_ValueCount(rast) As pvc
      FROM dummy_rast WHERE rid=2) As foo
      ORDER BY (pvc).value;
```

value	count
250	2
251	1
252	2
253	6
254	12

```
-- Example will count all pixels of band 1 including 249 --
```

```
SELECT (pvc).*
FROM (SELECT ST_ValueCount(rast,1,false) As pvc
      FROM dummy_rast WHERE rid=2) As foo
      ORDER BY (pvc).value;
```

value	count
249	2
250	2
251	1
252	2
253	6
254	12

```
-- Example will count only non-nodata value pixels of band 2
```

```
SELECT (pvc).*
FROM (SELECT ST_ValueCount(rast,2) As pvc
      FROM dummy_rast WHERE rid=2) As foo
      ORDER BY (pvc).value;
```

value	count
78	1
79	1
88	1
89	1
96	1
97	1
98	1
99	2
112	2

```
:
```

```
--real live example. Count all the pixels in an aerial raster tile band 2 intersecting a geometry ↩
```

```
-- and return only the pixel band values that have a count > 500
```

```
SELECT (pvc).value, SUM((pvc).count) As total
FROM (SELECT ST_ValueCount(rast,2) As pvc
      FROM o_4_boston
      WHERE ST_Intersects(rast,
        ST_GeomFromText('POLYGON((224486 892151,224486 892200,224706 892200,224706 ↩
        892151,224486 892151))',26986)
      )
      ) As foo
```


11.11 ☐ ☐ ☐ ☐ ☐

11.11.1 ST_AsBinary/ST_AsWKB

ST_AsBinary/ST_AsWKB — Return the Well-Known Binary (WKB) representation of the raster.

Synopsis

```
bytea ST_AsBinary(raster rast, boolean outasin=FALSE);
```

```
bytea ST_AsWKB(raster rast, boolean outasin=FALSE);
```


Returns the Binary representation of the raster. If `outasin` is `TRUE`, out-db bands are treated as in-db. Refer to `raster/doc/RFC2-WellKnownBinaryFormat` located in the PostGIS source folder for details of the representation.

[illegible]

Note

XXXXXXXXXX, WKB XXXXXX DB XXXXXXXXXXXXXXXXXXXXXXXX. XXXXXXXX DB XXXXXXXXXXXXXXXXXXXXXXXX, outasin XXXXXXXXXXXXXXXX.

2.1.0 outasim 2.1.0.

Enhanced: 2.5.0 Addition of ST AsWKB



```
SELECT ST_AsBinary(rast) As rastbin FROM dummy_rast WHERE rid=1;
```

rastbin

```
\001\000\000\000\000\000\000\000\000\000\000@ \000\000\000\000\000\010@ ←  
 \000\000\000\000\000\000\340? \000\000\000\000\000\340? \000\000\000\000\000\000\000\000\000\000\000\000\0
```



ST RastFromWKB, ST AsHexWKB

11.11.2 ST AsHexWKB

ST AsHexWKB — Return the Well-Known Binary (WKB) in Hex representation of the raster.

Synopsis

```
bytea ST_AsHexWKB(raster rast, boolean outasin=FALSE);
```


JPEG Output Example, multiple tiles as single raster

```
SELECT ST_AsGDALRaster(ST_Union(rast), 'JPEG', ARRAY['QUALITY=50']) As rastjpg
FROM dummy_rast
WHERE rast && ST_MakeEnvelope(10, 10, 11, 11);
```

Using PostgreSQL Large Object Support to export raster

One way to export raster into another format is using [PostgreSQL large object export functions](#). We'll repeat the prior example but also exporting. Note for this you'll need to have super user access to db since it uses server side lo functions. It will also export to path on server network. If you need export locally, use the psql equivalent lo_ functions which export to the local file system instead of the server file system.

```
DROP TABLE IF EXISTS tmp_out ;

CREATE TABLE tmp_out AS
SELECT lo_from_bytea(0,
    ST_AsGDALRaster(ST_Union(rast), 'JPEG', ARRAY['QUALITY=50'])
) AS loid
FROM dummy_rast
WHERE rast && ST_MakeEnvelope(10, 10, 11, 11);

SELECT lo_export(loid, '/tmp/dummy.jpg')
FROM tmp_out;

SELECT lo_unlink(loid)
FROM tmp_out;
```

GeoTiff 国际化

```
SELECT ST_AsGDALRaster(rast, 'GTiff') As rastjpg
FROM dummy_rast WHERE rid=2;

-- Out GeoTiff with jpeg compression, 90% quality
SELECT ST_AsGDALRaster(rast, 'GTiff',
    ARRAY['COMPRESS=JPEG', 'JPEG_QUALITY=90'],
    4269) As rasttiff
FROM dummy_rast WHERE rid=2;
```

国际化

Section [10.3, ST_GDALDrivers, ST_SRID](#)

11.11.4 ST_AsJPEG

ST_AsJPEG — 国际化 JPEG (Joint Photographic Exports Group) 国际化 (国际化 国际化) 国际化。国际化, 国际化 1 国际化 3 国际化。国际化。国际化 3 国际化 3 国际化 RGB 国际化。

Synopsis

```
bytea ST_AsJPEG(raster rast, text[] options=NULL);
bytea ST_AsJPEG(raster rast, integer nband, integer quality);
bytea ST_AsJPEG(raster rast, integer nband, text[] options=NULL);
bytea ST_AsJPEG(raster rast, integer[] nbands, text[] options=NULL);
bytea ST_AsJPEG(raster rast, integer[] nbands, integer quality);
```

描述

ST_AsJPEG(raster rast, text[] options=NULL) 使用 JPEG (Joint Photographic Experts Group) 格式将栅格数据导出为字节数组。ST_AsJPEG(raster rast, integer nband, integer quality) 使用 ST_AsGDALRaster 将栅格数据导出为字节数组。ST_AsJPEG(raster rast, integer nband, text[] options=NULL) 使用 ST_AsGDALRaster 将栅格数据导出为字节数组。ST_AsJPEG(raster rast, integer[] nbands, text[] options=NULL) 使用 ST_AsGDALRaster 将栅格数据导出为字节数组。ST_AsJPEG(raster rast, integer[] nbands, integer quality) 使用 ST_AsGDALRaster 将栅格数据导出为字节数组。

- **nband** - 指定要导出的波段数量。
- **nbands** - 指定要导出的波段列表 (JPEG 支持 3 个波段)。指定 RGB 波段。指定 ARRAY[3,2,1] 指定 3 个波段, 第 2 个波段, 第 1 个波段。
- **quality** - 1 到 100 之间的值。指定 JPEG 的质量。
- **options** - JPEG 选项。GDAL 选项 (ST_GDALDrivers 中的 JPEG 选项 create_options)。JPEG 选项, 指定 PROGRESSIVE ON/OFF 指定 75 到 0 到 100 指定 QUALITY 选项。指定 GDAL 选项。

2.0.0 版本。GDAL 1.6.0 版本。

用法:

```
-- output first 3 bands 75% quality
SELECT ST_AsJPEG(rast) As rastjpg
FROM dummy_rast WHERE rid=2;

-- output only first band as 90% quality
SELECT ST_AsJPEG(rast,1,90) As rastjpg
FROM dummy_rast WHERE rid=2;

-- output first 3 bands (but make band 2 Red, band 1 green, and band 3 blue, progressive and 90% quality
SELECT ST_AsJPEG(rast,ARRAY[2,1,3],ARRAY['QUALITY=90','PROGRESSIVE=ON']) As rastjpg
FROM dummy_rast WHERE rid=2;
```

描述

Section 10.3, ST_GDALDrivers, ST_AsGDALRaster, ST_AsPNG, ST_AsTIFF

11.11.5 ST_AsPNG

ST_AsPNG — 使用 PNG (Portable Network Graphics) 格式将栅格数据导出为字节数组 (PNG 格式) 将栅格数据导出为字节数组。ST_AsPNG(raster rast, integer nband, integer quality) 使用 ST_AsGDALRaster 将栅格数据导出为字节数组。ST_AsPNG(raster rast, integer nband, text[] options=NULL) 使用 ST_AsGDALRaster 将栅格数据导出为字节数组。ST_AsPNG(raster rast, integer[] nbands, text[] options=NULL) 使用 ST_AsGDALRaster 将栅格数据导出为字节数组。ST_AsPNG(raster rast, integer[] nbands, integer quality) 使用 ST_AsGDALRaster 将栅格数据导出为字节数组。

Synopsis

```

bytea ST_AsPNG(raster rast, text[] options=NULL);
bytea ST_AsPNG(raster rast, integer nband, integer compression);
bytea ST_AsPNG(raster rast, integer nband, text[] options=NULL);
bytea ST_AsPNG(raster rast, integer[] nbands, integer compression);
bytea ST_AsPNG(raster rast, integer[] nbands, text[] options=NULL);

```


PNG(Portable Network Graphics) 格式。 使用 `ST_AsGDALRaster` 函数。 使用 3 个参数。
 srid 指定 SRID 值。 使用 3 个参数。
 使用 3 个参数。

- `nband` - 1 (PNG 1 band). `gdalinfo` shows 1 band.
- `nbands` - 4 (PNG 4 bands). `gdalinfo` shows 4 bands. `gdalinfo` shows `ARRAY[3,2,1]` 3 bands, 2 bands, 1 band.
- `compression` - 1 (PNG 1 band). `gdalinfo` shows 1 band.
- `options` - PNG `gdalinfo` shows `GDAL` (ST `GDALDrivers` PNG `create_options` `gdalinfo`). PNG `gdalinfo`, `gdalinfo` `ZLEVEL` (1 - 6) `gdalinfo`, `gdalinfo` `ARRAY['ZLEVEL=9']` `gdalinfo`. `gdalinfo` 2 `gdalinfo` `gdalinfo`. `gdalinfo` `GDAL` `gdalinfo`.

2.0.0 20200818. GDAL 1.6.0 20100522.



```
SELECT ST_AsPNG(rast) As rastpng
FROM dummy_rast WHERE rid=2;

-- export the first 3 bands and map band 3 to Red, band 1 to Green, band 2 to blue
SELECT ST_AsPNG(rast, ARRAY[3,1,2]) As rastpng
FROM dummy_rast WHERE rid=2;
```



ST AsGDALRaster, ST ColorMap, ST GDALDrivers, Section 10.3

11.11.6 ST_AsTIFF

ST_AsTIFF — Return the raster selected bands as a single TIFF image (byte array). If no band is specified or any of specified bands does not exist in the raster, then will try to use all bands.

Synopsis

```
bytea ST_AsTIFF(raster rast, text[] options=",", integer srid=sameasource);
bytea ST_AsTIFF(raster rast, text compression=",", integer srid=sameasource);
bytea ST_AsTIFF(raster rast, integer[] nbands, text compression=",", integer srid=sameasource);
bytea ST_AsTIFF(raster rast, integer[] nbands, text[] options, integer srid=sameasource);
```

选项

ST_AsTIFF 使用 TIFF (Tagged Image File Format) 格式。ST_AsTIFF 使用 GDAL 库。ST_AsTIFF 使用 ST_AsGDALRaster 函数。ST_AsTIFF 使用 ST_AsGDALRaster 函数。ST_AsTIFF 使用 SRS 系统，ST_AsTIFF 使用 SRS 系统。ST_AsTIFF 使用 SRS 系统。

- **nbands** - 指定带数 (PNG 支持 3 个带)。指定 RGB 带。指定 ARRAY[3,2,1] 指定 3 个带，指定 2 个带，指定 1 个带。
- **compression** - 指定压缩: JPEG90(指定)，LZW, JPEG, DEFLATE9
- **options** - GTiff 使用 GDAL 选项 (ST_GDALDrivers 指定 GTiff 选项 create_options 指定)。指定 GDAL 选项。
- **srid** - 指定 spatial_ref_sys 的 SRID 值。指定 SRID 值。

2.0.0 版本。GDAL 1.6.0 版本。

选项: JPEG 90%

```
SELECT ST_AsTIFF(rast, 'JPEG90') As rasttiff
FROM dummy_rast WHERE rid=2;
```

选项

ST_GDALDrivers, ST_AsGDALRaster, ST_SRID

11.12 几何操作

11.12.1 ST_Clip

ST_Clip — Returns the raster clipped by the input geometry. If band number is not specified, all bands are processed. If **crop** is not specified or **TRUE**, the output raster is cropped. If **touched** is set to **TRUE**, then touched pixels are included, otherwise only if the center of the pixel is in the geometry it is included.

Synopsis

```
raster ST_Clip(raster rast, integer[] nband, geometry geom, double precision[] nodataval=NULL,
boolean crop=TRUE, boolean touched=FALSE);
raster ST_Clip(raster rast, integer nband, geometry geom, double precision nodataval, boolean crop=TRUE,
boolean touched=FALSE);
raster ST_Clip(raster rast, integer nband, geometry geom, boolean crop, boolean touched=FALSE);
raster ST_Clip(raster rast, geometry geom, double precision[] nodataval=NULL, boolean crop=TRUE,
boolean touched=FALSE);
raster ST_Clip(raster rast, geometry geom, double precision nodataval, boolean crop=TRUE, boolean
touched=FALSE);
raster ST_Clip(raster rast, geometry geom, boolean crop, boolean touched=FALSE);
```



geom . , .

```
ST_Clip [REDACTED] NODATA [REDACTED]. NODATA [REDACTED]
[REDACTED] NODATA [REDACTED], [REDACTED] NODATA [REDACTED] ST_MinPossibleValue(ST_Band
band)) [REDACTED]. [REDACTED] NODATA [REDACTED], [REDACTED] NODATA [REDACTED]
[REDACTED] NODATA [REDACTED]. NODATA [REDACTED], [REDACTED] NODATA [REDACTED].
NODATA [REDACTED].
```

If `crop` is not specified, `true` is assumed meaning the output raster is cropped to the intersection of the `geomand` raster extents. If `crop` is set to `false`, the new raster gets the same extent as `rast`. If `touched` is set to `true`, then all pixels in the `rast` that intersect the geometry are selected.



Note

The default behavior is `touched=false`, which will only select pixels where the center of the pixel is covered by the geometry.

Enhanced: 3.5.0 - touched argument added.

2.0.0 ☒☒☒☒☒☒☒☒☒☒☒.

☐☐☐☐: 2.1.0 ☐☐☐☐ C ☐☐☐☐☐☐☐☐☐☐.

Examples here use Massachusetts aerial data available on MassGIS site [MassGIS Aerial Orthos](#).

Examples: Comparing selecting all touched vs. not all touched

```
SELECT ST_Count(rast) AS count_pixels_in_orig, ST_Count(rast_touched) AS all_touched_pixels ←
      , ST_Count(rast_not_touched) AS default_clip
FROM ST_AsRaster(ST_Letters('R'), scalex =
> 1.0, scaley =
> -1.0) AS r(rast)
      INNER JOIN ST_GeomFromText('LINESTRING(0 1, 5 6, 10 10)') AS g(geom)
ON ST_Intersects(r.rast,g.geom)
      , ST_Clip(r.rast, g.geom, touched =
> true) AS rast_touched
      , ST_Clip(r.rast, g.geom, touched =
> false) AS rast_not_touched;
```

```
count_pixels_in_orig | all_touched_pixels | default_clip
-----+-----+-----
                2605 |                16 |                10
(1 row)
```

Examples: 1 band clipping (not touched)

```
-- Clip the first band of an aerial tile by a 20 meter buffer.
SELECT ST_Clip(rast, 1,
              ST_Buffer(ST_Centroid(ST_Envelope(rast)),20)
              ) from aerials.boston
WHERE rid = 4;
```



```
-- Demonstrate effect of crop on final dimensions of raster
-- Note how final extent is clipped to that of the geometry
-- if crop = true
SELECT ST_XMax(ST_Envelope(ST_Clip(rast, 1, clipper, true))) As xmax_w_trim,
       ST_XMax(clipper) As xmax_clipper,
       ST_XMax(ST_Envelope(ST_Clip(rast, 1, clipper, false))) As xmax_wo_trim,
       ST_XMax(ST_Envelope(rast)) As xmax_rast_orig
FROM (SELECT rast, ST_Buffer(ST_Centroid(ST_Envelope(rast)),6) As clipper
      FROM aerials.boston
      WHERE rid = 6) As foo;
```

xmax_w_trim	xmax_clipper	xmax_wo_trim	xmax_rast_orig
230657.436173996	230657.436173996	230666.436173996	230666.436173996



crop 1 如果 clipper 的几何形状与栅格的原始范围不同，则使用 clipper 的几何形状裁剪栅格。

```
-- Same example as before, but we need to set crop to false to be able to use ST_AddBand
-- because ST_AddBand requires all bands be the same Width and height
SELECT ST_AddBand(ST_Clip(rast, 1,
      ST_Buffer(ST_Centroid(ST_Envelope(rast)),20),false
      ), ARRAY[ST_Band(rast,2),ST_Band(rast,3)] ) from aerials.boston
WHERE rid = 6;
```



原始图像



缓冲 - 裁剪

SQL: 缓冲裁剪

```
-- Clip all bands of an aerial tile by a 20 meter buffer.
-- Only difference is we don't specify a specific band to clip
-- so all bands are clipped
SELECT ST_Clipping(rast,
    ST_Buffer(ST_Centroid(ST_Envelope(rast)), 20),
    false
) from aerials.boston
WHERE rid = 4;
```



原始图像



缓冲

SQL

[ST_AddBand](#), [ST_Count](#), [ST_MapAlgebra \(callback function version\)](#), [ST_Intersection](#)

11.12.2 ST_ColorMap

ST_ColorMap — 将 8BUI 栅格 (grayscale, RGB, RGBA) 映射到 4 个颜色带。返回 1 个栅格。

Synopsis

raster **ST_ColorMap**(raster rast, integer nband=1, text colormap=grayscale, text method=INTERPOLATE)

raster **ST_ColorMap**(raster rast, text colormap, text method=INTERPOLATE);

返回

`rast` 的 `nband` 个波段使用 `colormap` 指定的 8BUI 的 4 个颜色值进行映射。
`colormap` 指定了 8BUI 的 4 个颜色值。

`nband` 指定了波段数，默认为 1 个波段。

指定的 `colormap` 指定了 8BUI 的 4 个颜色值。

指定的 `colormap` 指定了：

- grayscale 或 greyscale - 8BUI 的 4 个颜色值 (shades of gray)
- pseudocolor - 8BUI(RGBA) 的 4 个颜色值，指定的 4 个颜色值 (RGBA) 的 4 个颜色值 (0 到 255 的整数)。
- fire - 8BUI(RGBA) 的 4 个颜色值，指定的 4 个颜色值 (RGBA) 的 4 个颜色值 (0 到 255 的整数)。
- bluered - 8BUI(RGBA) 的 4 个颜色值，指定的 4 个颜色值 (RGBA) 的 4 个颜色值 (0 到 255 的整数)。

指定的 `colormap` 指定了 (指定的 4 个颜色值) 指定的 4 个颜色值 (RGBA) 的 4 个颜色值 (0 到 255 的整数)。

```
5 0 0 0 255
4 100:50 55 255
1 150,100 150 255
0% 255 255 255 255
nv 0 0 0 0
```

`colormap` 指定了 GDAL 的 (color-relief) 指定的 `gdaldem` 指定的 4 个颜色值。

指定的 `method` 指定了：

- INTERPOLATE - 指定的 4 个颜色值 (RGBA) 的 4 个颜色值 (0 到 255 的整数)。
- EXACT - 指定的 4 个颜色值 (RGBA) 的 4 个颜色值 (0 到 255 的整数)。
- NEAREST - 指定的 4 个颜色值 (RGBA) 的 4 个颜色值 (0 到 255 的整数)。



Note

指定的 `ColorBrewer` 指定的 4 个颜色值。



Warning

指定的 `NODATA` 指定的 4 个颜色值 (RGBA) 的 4 个颜色值 (0 到 255 的整数)。

2.1.0 指定的 4 个颜色值 (RGBA) 的 4 个颜色值 (0 到 255 的整数)。

[illegible]

```
-- setup test raster table --
DROP TABLE IF EXISTS funky_shapes;
CREATE TABLE funky_shapes(rast raster);

INSERT INTO funky_shapes(rast)
WITH ref AS (
    SELECT ST_MakeEmptyRaster( 200, 200, 0, 200, 1, -1, 0, 0) AS rast
)
SELECT
    ST_Union(rast)
FROM (
    SELECT
        ST_AsRaster(
            ST_Rotate(
                ST_Buffer(
                    ST_GeomFromText('LINESTRING(0 2,50 50,150 150,125 50)'),
                    i*2
                ),
                pi() * i * 0.125, ST_Point(50,50)
            ),
            ref.rast, '8BUI'::text, i * 5
        ) AS rast
    FROM ref
    CROSS JOIN generate_series(1, 10, 3) AS i
) AS shapes;
```


```
SELECT
    ST_NumBands(rast) As n_orig,
    ST_NumBands(ST_ColorMap(rast,1, 'greyscale')) As ngrey,
    ST_NumBands(ST_ColorMap(rast,1, 'pseudocolor')) As npseudo,
    ST_NumBands(ST_ColorMap(rast,1, 'fire')) As nfire,
    ST_NumBands(ST_ColorMap(rast,1, 'bluered')) As nbluered,
    ST_NumBands(ST_ColorMap(rast,1, '
100% 255    0    0
80%  160    0    0
50%  130    0    0
30%   30    0    0
20%   60    0    0
0%    0     0    0
    nv 255 255 255
    ')) As nred
FROM funky_shapes;
```

```
n_orig | ngrey | npseudo | nfire | nbluered | nred
-----+-----+-----+-----+-----+-----
      1 |      1 |      4 |      4 |      4 |      3
```

ST AsPNG

```
SELECT
    ST_AsPNG(rast) As orig_png,
    ST_AsPNG(ST_ColorMap(rast,1,'greyscale')) As grey_png,
    ST_AsPNG(ST_ColorMap(rast,1, 'pseudocolor')) As pseudo_png,
    ST_AsPNG(ST_ColorMap(rast,1, 'nfire')) As fire_png,
    ST_AsPNG(ST_ColorMap(rast,1, 'bluered')) As bluered_png,
```

```
ST_AsPNG(ST_ColorMap(rast,1, '
100% 255 0 0
80% 160 0 0
50% 130 0 0
30% 30 0 0
20% 60 0 0
0% 0 0 0
nv 255 255 255
')) As red_png
FROM funky_shapes;
```



ST_AsPNG, ST_AsRaster ST_MapAlgebra (callback function version), ST_Grayscale ST_NumBands, ST_Reclass, ST_SetBandNoDataValue, ST_Union

11.12.3 ST_Grayscale

ST_Grayscale — Creates a new one-8BUI band raster from the source raster and specified bands representing Red, Green and Blue

Synopsis

(1) raster **ST_Grayscale**(raster rast, integer redband=1, integer greenband=2, integer blueband=3, text extenttype=INTERSECTION);

(2) raster **ST_Grayscale**(rastbandarg[] rastbandargset, text extenttype=INTERSECTION);

注意

Create a raster with one 8BUI band given three input bands (from one or more rasters). Any input band whose pixel type is not 8BUI will be reclassified using **ST_Reclass**.



Note


This function is not like **ST_ColorMap** with the grayscale keyword as **ST_ColorMap** operates on only one band while this function expects three bands for RGB. This function applies the following equation for converting RGB to Grayscale: $0.2989 * RED + 0.5870 * GREEN + 0.1140 * BLUE$

Availability: 2.5.0

例: 例 1

```
SET postgis.gdal_enabled_drivers = 'ENABLE_ALL';
SET postgis.enable_outdb_rasters = True;

WITH apple AS (
  SELECT ST_AddBand(
    ST_MakeEmptyRaster(350, 246, 0, 0, 1, -1, 0, 0, 0),
    '/tmp/apple.png'::text,
    NULL::int[]
  ) AS rast
)
SELECT
  ST_AsPNG(rast) AS original_png,
  ST_AsPNG(ST_Grayscale(rast)) AS grayscale_png
FROM apple;
```



例 2

```
SET postgis.gdal_enabled_drivers = 'ENABLE_ALL';
SET postgis.enable_outdb_rasters = True;

WITH apple AS (
  SELECT ST_AddBand(
    ST_MakeEmptyRaster(350, 246, 0, 0, 1, -1, 0, 0, 0),
    '/tmp/apple.png'::text,
    NULL::int[]
  ) AS rast
)
SELECT
  ST_AsPNG(rast) AS original_png,
  ST_AsPNG(ST_Grayscale(
    ARRAY[
      ROW(rast, 1)::rastbandarg, -- red
      ROW(rast, 2)::rastbandarg, -- green
      ROW(rast, 3)::rastbandarg, -- blue
    ]::rastbandarg[]
  )) AS grayscale_png
FROM apple;
```

例

ST_AsPNG, ST_Reclass, ST_ColorMap

11.12.4 ST_Intersection

ST_Intersection — 返回几何与栅格相交的栅格。如果几何与栅格不相交，则返回空栅格。

Synopsis

```
setof geomval ST_Intersection(geometry geom, raster rast, integer band_num=1);
setof geomval ST_Intersection(raster rast, geometry geom);
```


例: 点, 线 -- 点-面相交

```
SELECT
  foo.rid,
  foo.gid,
  ST_AsText((foo.geomval).geom) As geomwkt,
  (foo.geomval).val
FROM (
  SELECT
    A.rid,
    g.gid,
    ST_Intersection(A.rast, g.geom) As geomval
  FROM dummy_rast AS A
  CROSS JOIN (
    VALUES
      (1, ST_Point(3427928, 5793243.85) ),
      (2, ST_GeomFromText('LINESTRING(3427927.85 5793243.75,3427927.8  ←
        5793243.75,3427927.8 5793243.8)')),
      (3, ST_GeomFromText('LINESTRING(1 2, 3 4)'))
    ) As g(gid,geom)
  WHERE A.rid = 2
) As foo;
```

rid	gid	geomwkt	val
2	1	POINT(3427928 5793243.85)	249
2	1	POINT(3427928 5793243.85)	253
2	2	POINT(3427927.85 5793243.75)	254
2	2	POINT(3427927.8 5793243.8)	251
2	2	POINT(3427927.8 5793243.8)	253
2	2	LINESTRING(3427927.8 5793243.75,3427927.8 5793243.8)	252
2	2	MULTILINESTRING((3427927.8 5793243.8,3427927.8 5793243.75),...)	250
2	3	GEOMETRYCOLLECTION EMPTY	

例

geomval, ST_Intersects, ST_MapAlgebraExpr, ST_Clip, ST_AsText

11.12.5 ST_MapAlgebra (callback function version)

ST_MapAlgebra (callback function version) — 栅格 - 栅格 1 栅格, 栅格, 栅格
栅格 1 栅格 1 栅格。

Synopsis

raster **ST_MapAlgebra**(rastbandarg[] rastbandargset, regprocedure callbackfunc, text pixeltype=NULL, text extenttype=INTERSECTION, raster customextent=NULL, integer distancex=0, integer distancey=0, text[] VARIADIC userargs=NULL);
raster **ST_MapAlgebra**(raster rast, integer[] nband, regprocedure callbackfunc, text pixeltype=NULL, text extenttype=FIRST, raster customextent=NULL, integer distancex=0, integer distancey=0, text[] VARIADIC userargs=NULL);
raster **ST_MapAlgebra**(raster rast, integer nband, regprocedure callbackfunc, text pixeltype=NULL, text extenttype=FIRST, raster customextent=NULL, integer distancex=0, integer distancey=0, text[] VARIADIC userargs=NULL);

```
raster ST_MapAlgebra(raster rast1, integer nband1, raster rast2, integer nband2, regprocedure call-  
backfunc, text pixelftype=NULL, text extenttype=INTERSECTION, raster customextent=NULL, inte-  
ger distancex=0, integer distancey=0, text[] VARIADIC userargs=NULL);
```

```
raster ST_MapAlgebra(raster rast, integer nband, regprocedure callbackfunc, float8[] mask, boolean
weighted, text pixelttype=NULL, text extenttype=INTERSECTION, raster customextent=NULL, text[]
VARIADIC userargs=NULL);
```


□□□ 1 □□□, □□□□□, □□□□□□□□□□ 1 □□□□□□□□ 1 □□□□□□□□□□□□□.

rast,rast1,rast2, rastbandargset □□□ (代數) □□□□□□□□□□□□□□□□

[illegible]

```
nband, nband1, nband2 [0-9]. nband [0-9]. nband1 [0-9] rast1 [0-9] nband2 [0-9] 2 [0-9]/[0-9] 2 [0-9] rast2 [0-9]
```

callbackfunc The callbackfunc parameter must be the name and signature of an SQL or PL/pgSQL function, cast to a regprocedure. An example PL/pgSQL function example is:

```
CREATE OR REPLACE FUNCTION sample_callbackfunc(value double precision[][][], position integer[][], VARIADIC userargs text[]) RETURNS double precision AS $$ BEGIN RETURN 0; END; $$ LANGUAGE 'plpgsql' IMMUTABLE;
```

The callbackfunc must have three arguments: a 3-dimension double precision array, a 2-dimension integer array and a variadic 1-dimension text array. The first argument value is the set of values (as double precision) from all input rasters. The three dimensions (where indexes are 1-based) are: raster #, row y, column x. The second argument position is the set of pixel positions from the output raster and input rasters. The outer dimension (where indexes are 0-based) is the raster #. The position at outer dimension index 0 is the output raster's pixel position. For each outer dimension, there are two elements in the inner dimension for X and Y. The third argument `userargs` is for passing through any user-specified arguments.

Passing a regprocedure argument to a SQL function requires the full function signature to be passed, then cast to a regprocedure type. To pass the above example PL/pgSQL function as an argument, the SQL for the argument is:

```
'sample callbackfunc(double precision[], integer[], text[])':regprocedure
```

Note that the argument contains the name of the function, the types of the function arguments, quotes around the name and argument types, and a cast to a `regprocedure`.

mask An n-dimensional array (matrix) of numbers used to filter what cells get passed to map algebra call-back function. 0 means a neighbor cell value should be treated as no-data and 1 means value should be treated as data. If weight is set to true, then the values, are used as multipliers to multiple the pixel value of that value in the neighborhood position.

weighted mask $\begin{matrix} \square & \square & \square & \square & \square & \square & \square & \square & \square & \square \\ \square & \square & \square & \square & \square & \square & \square & \square & \square & \square \end{matrix}$ ($\begin{matrix} \square & \square & \square & \square & \square & \square & \square & \square \\ \square & \square & \square & \square & \square & \square & \square & \square \end{matrix}$) $\begin{matrix} \square & \square \\ \square & \square \end{matrix}$ (mask $\begin{matrix} \square & \square & \square & \square & \square & \square & \square & \square & \square & \square \\ \square & \square & \square & \square & \square & \square & \square & \square & \square & \square \end{matrix}$)
 $\begin{matrix} \square & \square \\ \square & \square \end{matrix}$) $\begin{matrix} \square & \square & \square & \square & \square & \square & \square & \square \\ \square & \square & \square & \square & \square & \square & \square & \square \end{matrix}$ ($\begin{matrix} \square & \square \\ \square & \square \end{matrix}$) $\begin{matrix} \square & \square & \square \\ \square & \square & \square \end{matrix}$.

pixeltype pixeltype 数据类型, 数据类型名称。pixeltype 为 NULL 数据类型, 数据类型名称 (数据类型: INTERSECTION, UNION, FIRST, CUSTOM), 数据类型名称 (数据类型: SECOND, LAST) 数据类型名称。数据类型名称, 数据类型 pixeltype 数据类型。

数据类型名称 **ST_BandPixelType** 数据类型名称, 数据类型, NULL 数据类型。

extenttype 数据类型名称 INTERSECTION(数据类型), UNION, FIRST(数据类型 1 数据类型名称), SECOND, LAST, CUSTOM 数据类型。

customextent extenttype 为 CUSTOM 数据类型, 数据类型 customextent 数据类型名称。数据类型 1 为 4 数据类型名称。

distancex The distance in pixels from the reference cell in x direction. So width of resulting matrix would be $2*distancex + 1$. If not specified only the reference cell is considered (neighborhood of 0).

distancey 数据类型名称 Y 数据类型名称。数据类型名称 $2*distancey + 1$ 数据类型。数据类型名称 (数据类型 0) 数据类型。

userargs callbackfunc 数据类型名称 variadic text 数据类型。数据类型名称 callbackfunc 数据类型, userargs 数据类型。



Note

(数据类型名称) VARIADIC 数据类型名称, PostgreSQL 数据类型 **Query Language (SQL) Functions** "SQL Functions with Variable Numbers of Arguments" 数据类型名称。



Note

数据类型名称, callbackfunc 数据类型 text[] 数据类型。

数据类型 1 数据类型名称/raster数据类型名称 rastbandarg 数据类型名称。数据类型 1 数据类型名称。

数据类型 2 为 3 数据类型名称 1 数据类型名称。数据类型 2 为 3 数据类型名称。

数据类型 4 数据类型名称 1 数据类型名称 2 数据类型名称。数据类型 4 数据类型名称。

2.2.0 数据类型 mask 数据类型名称。

2.1.0 数据类型名称。

数据类型: 数据类型 1

数据类型 1 为, 数据类型 1 为

```
WITH foo AS (
  SELECT 1 AS rid, ST_AddBand(ST_MakeEmptyRaster(2, 2, 0, 0, 1, -1, 0, 0, 0), 1, '16BUI', ↵
    1, 0) AS rast
)
SELECT
  ST_MapAlgebra(
    ARRAY[ROW(rast, 1)]::rastbandarg[],
    'sample_callbackfunc(double precision[], int[], text[])::regprocedure
  ) AS rast
FROM foo
```

图 1 图, 图

```
WITH foo AS (
    SELECT 1 AS rid, ST_AddBand(ST_AddBand(ST_AddBand(ST_MakeEmptyRaster(2, 2, 0, 0, 1, -1, 0, 0, 0), 1, '16BUI', 1, 0), 2, '8BUI', 10, 0), 3, '32BUI', 100, 0) AS rast
)
SELECT
    ST_MapAlgebra(
        ARRAY[ROW(rast, 3), ROW(rast, 1), ROW(rast, 3), ROW(rast, 2)]::rastbandarg[],
        'sample_callbackfunc(double precision[], int[], text[])::regprocedure'
    ) AS rast
FROM foo
```

图, 图

```
WITH foo AS (
    SELECT 1 AS rid, ST_AddBand(ST_AddBand(ST_AddBand(ST_MakeEmptyRaster(2, 2, 0, 0, 1, -1, 0, 0, 0), 1, '16BUI', 1, 0), 2, '8BUI', 10, 0), 3, '32BUI', 100, 0) AS rast UNION ALL
    SELECT 2 AS rid, ST_AddBand(ST_AddBand(ST_AddBand(ST_MakeEmptyRaster(2, 2, 0, 0, 1, -1, 0, 0, 0), 1, '16BUI', 2, 0), 2, '8BUI', 20, 0), 3, '32BUI', 300, 0) AS rast
)
SELECT
    ST_MapAlgebra(
        ARRAY[ROW(t1.rast, 3), ROW(t2.rast, 1), ROW(t2.rast, 3), ROW(t1.rast, 2)]::rastbandarg[],
        'sample_callbackfunc(double precision[], int[], text[])::regprocedure'
    ) AS rast
FROM foo t1
CROSS JOIN foo t2
WHERE t1.rid = 1
    AND t2.rid = 2
```

图. PostgreSQL 9.1 图.

```
WITH foo AS (
    SELECT 0 AS rid, ST_AddBand(ST_MakeEmptyRaster(2, 2, 0, 0, 1, -1, 0, 0, 0), 1, '16BUI', 1, 0) AS rast UNION ALL
    SELECT 1, ST_AddBand(ST_MakeEmptyRaster(2, 2, 2, 0, 1, -1, 0, 0, 0), 1, '16BUI', 2, 0) AS rast UNION ALL
    SELECT 2, ST_AddBand(ST_MakeEmptyRaster(2, 2, 4, 0, 1, -1, 0, 0, 0), 1, '16BUI', 3, 0) AS rast UNION ALL

    SELECT 3, ST_AddBand(ST_MakeEmptyRaster(2, 2, 0, -2, 1, -1, 0, 0, 0), 1, '16BUI', 10, 0) AS rast UNION ALL
    SELECT 4, ST_AddBand(ST_MakeEmptyRaster(2, 2, 2, -2, 1, -1, 0, 0, 0), 1, '16BUI', 20, 0) AS rast UNION ALL
    SELECT 5, ST_AddBand(ST_MakeEmptyRaster(2, 2, 4, -2, 1, -1, 0, 0, 0), 1, '16BUI', 30, 0) AS rast UNION ALL

    SELECT 6, ST_AddBand(ST_MakeEmptyRaster(2, 2, 0, -4, 1, -1, 0, 0, 0), 1, '16BUI', 100, 0) AS rast UNION ALL
    SELECT 7, ST_AddBand(ST_MakeEmptyRaster(2, 2, 2, -4, 1, -1, 0, 0, 0), 1, '16BUI', 200, 0) AS rast UNION ALL
    SELECT 8, ST_AddBand(ST_MakeEmptyRaster(2, 2, 4, -4, 1, -1, 0, 0, 0), 1, '16BUI', 300, 0) AS rast
)
SELECT
    t1.rid,
    ST_MapAlgebra(
        ARRAY[ROW(ST_Union(t2.rast), 1)]::rastbandarg[],
        'sample_callbackfunc(double precision[], int[], text[])::regprocedure',
```

```

        '32BUI',
        'CUSTOM', t1.rast,
        1, 1
    ) AS rast
FROM foo t1
CROSS JOIN foo t2
WHERE t1.rid = 4
      AND t2.rid BETWEEN 0 AND 8
      AND ST_Intersects(t1.rast, t2.rast)
GROUP BY t1.rid, t1.rast

```

以下示例使用 PostgreSQL 9.0 的 `ST_AddBand` 函数。

```

WITH src AS (
    SELECT 0 AS rid, ST_AddBand(ST_MakeEmptyRaster(2, 2, 0, 0, 1, -1, 0, 0, 0), 1, '16BUI', 1, 0) AS rast UNION ALL
    SELECT 1, ST_AddBand(ST_MakeEmptyRaster(2, 2, 2, 0, 1, -1, 0, 0, 0), 1, '16BUI', 2, 0) AS rast UNION ALL
    SELECT 2, ST_AddBand(ST_MakeEmptyRaster(2, 2, 4, 0, 1, -1, 0, 0, 0), 1, '16BUI', 3, 0) AS rast UNION ALL

    SELECT 3, ST_AddBand(ST_MakeEmptyRaster(2, 2, 0, -2, 1, -1, 0, 0, 0), 1, '16BUI', 10, 0) AS rast UNION ALL
    SELECT 4, ST_AddBand(ST_MakeEmptyRaster(2, 2, 2, -2, 1, -1, 0, 0, 0), 1, '16BUI', 20, 0) AS rast UNION ALL
    SELECT 5, ST_AddBand(ST_MakeEmptyRaster(2, 2, 4, -2, 1, -1, 0, 0, 0), 1, '16BUI', 30, 0) AS rast UNION ALL

    SELECT 6, ST_AddBand(ST_MakeEmptyRaster(2, 2, 0, -4, 1, -1, 0, 0, 0), 1, '16BUI', 100, 0) AS rast UNION ALL
    SELECT 7, ST_AddBand(ST_MakeEmptyRaster(2, 2, 2, -4, 1, -1, 0, 0, 0), 1, '16BUI', 200, 0) AS rast UNION ALL
    SELECT 8, ST_AddBand(ST_MakeEmptyRaster(2, 2, 4, -4, 1, -1, 0, 0, 0), 1, '16BUI', 300, 0) AS rast
)
WITH foo AS (
    SELECT
        t1.rid,
        ST_Union(t2.rast) AS rast
    FROM src t1
    JOIN src t2
        ON ST_Intersects(t1.rast, t2.rast)
        AND t2.rid BETWEEN 0 AND 8
    WHERE t1.rid = 4
    GROUP BY t1.rid
), bar AS (
    SELECT
        t1.rid,
        ST_MapAlgebra(
            ARRAY[ROW(t2.rast, 1)::rastbandarg[],
                'raster_nmapalgebra_test(double precision[], int[], text[])::regprocedure,
                '32BUI',
                'CUSTOM', t1.rast,
                1, 1
            ] AS rast
        FROM src t1
        JOIN foo t2
            ON t1.rid = t2.rid
    )
SELECT
    rid,
    (ST_Metadata(rast)),

```

```
(ST_BandMetadata(rast, 1)),
  ST_Value(rast, 1, 1, 1)
FROM bar;
```

实验: 实验 2 实验 3

实验实验 1 实验, 实验实验

```
WITH foo AS (
  SELECT 1 AS rid, ST_AddBand(ST_AddBand(ST_AddBand(ST_MakeEmptyRaster(2, 2, 0, 0, 1, -1, ←
    0, 0, 0), 1, '16BUI', 1, 0), 2, '8BUI', 10, 0), 3, '32BUI', 100, 0) AS rast
)
SELECT
  ST_MapAlgebra(
    rast, ARRAY[3, 1, 3, 2]::integer[],
    'sample_callbackfunc(double precision[], int[], text[])'::regprocedure
  ) AS rast
FROM foo
```

实验实验 1 实验, 实验 1 实验

```
WITH foo AS (
  SELECT 1 AS rid, ST_AddBand(ST_AddBand(ST_AddBand(ST_MakeEmptyRaster(2, 2, 0, 0, 1, -1, ←
    0, 0, 0), 1, '16BUI', 1, 0), 2, '8BUI', 10, 0), 3, '32BUI', 100, 0) AS rast
)
SELECT
  ST_MapAlgebra(
    rast, 2,
    'sample_callbackfunc(double precision[], int[], text[])'::regprocedure
  ) AS rast
FROM foo
```

实验: 实验 4

实验实验 2 实验, 实验 2 实验


```
WITH foo AS (
  SELECT 1 AS rid, ST_AddBand(ST_AddBand(ST_AddBand(ST_MakeEmptyRaster(2, 2, 0, 0, 1, -1, ←
    0, 0, 0), 1, '16BUI', 1, 0), 2, '8BUI', 10, 0), 3, '32BUI', 100, 0) AS rast UNION ←
    ALL
  SELECT 2 AS rid, ST_AddBand(ST_AddBand(ST_AddBand(ST_MakeEmptyRaster(2, 2, 0, 1, 1, -1, ←
    0, 0, 0), 1, '16BUI', 2, 0), 2, '8BUI', 20, 0), 3, '32BUI', 300, 0) AS rast
)
SELECT
  ST_MapAlgebra(
    t1.rast, 2,
    t2.rast, 1,
    'sample_callbackfunc(double precision[], int[], text[])'::regprocedure
  ) AS rast
FROM foo t1
CROSS JOIN foo t2
WHERE t1.rid = 1
  AND t2.rid = 2
```


mask 掩模

```

WITH foo AS (SELECT
  ST_SetBandNoDataValue(
  ST_SetValue(ST_SetValue(ST_AsRaster(
    ST_Buffer(
      ST_GeomFromText('LINESTRING(50 50,100 90,100 50)'), 5,'join=bevel'),
      200,200,ARRAY['8BUI'], ARRAY[100], ARRAY[0]), ST_Buffer('POINT(70 70)')::
        geometry,10,'quad_segs=1') ,50),
    'LINESTRING(20 20, 100 100, 150 98)')::geometry,1),0) AS rast )
SELECT 'original' AS title, rast
FROM foo
UNION ALL
SELECT 'no mask mean value' AS title, ST_MapAlgebra(rast,1,'ST_mean4ma(double precision[],
  int[], text[])'::regprocedure) AS rast
FROM foo
UNION ALL
SELECT 'mask only consider neighbors, exclude center' AS title, ST_MapAlgebra(rast,1,'
  ST_mean4ma(double precision[], int[], text[])'::regprocedure,
  '{{1,1,1}, {1,0,1}, {1,1,1}}'::double precision[], false) As rast
FROM foo
UNION ALL
SELECT 'mask weighted only consider neighbors, exclude center multi other pixel values by
  2' AS title, ST_MapAlgebra(rast,1,'ST_mean4ma(double precision[], int[], text[])'::
  regprocedure,
  '{{2,2,2}, {2,0,2}, {2,2,2}}'::double precision[], true) As rast
FROM foo;

```





图例

[rastbandarg](#), [ST_Union](#), [ST_MapAlgebra \(expression version\)](#)

11.12.6 ST_MapAlgebra (expression version)

ST_MapAlgebra (expression version) — 对栅格 - 栅格 1 应用表达式 2，并返回结果，数据类型与输入栅格 1 相同。SQL 函数 1 对栅格 1 应用表达式 1。

Synopsis

raster **ST_MapAlgebra**(raster rast, integer nband, text pixeltype, text expression, double precision nodataval=NULL);
raster **ST_MapAlgebra**(raster rast, text pixeltype, text expression, double precision nodataval=NULL);
raster **ST_MapAlgebra**(raster rast1, integer nband1, raster rast2, integer nband2, text expression, text pixeltype=NULL, text extenttype=INTERSECTION, text nodata1expr=NULL, text nodata2expr=NULL, double precision nodatanodataval=NULL);
raster **ST_MapAlgebra**(raster rast1, raster rast2, text expression, text pixeltype=NULL, text extenttype=INTERSECTION, text nodata1expr=NULL, text nodata2expr=NULL, double precision nodatanodataval=NULL);

图例

对栅格 1 应用表达式 2，并返回结果，数据类型与输入栅格 1 相同。SQL 函数 1 对栅格 1 应用表达式 1。

2.1.0 版本引入。

名称: 函数 1, 2 (返回 1 个)

函数 (rast) **返回** expression **返回** PostgreSQL **返回** 类型, 返回 1 个 **返回** 类型. nband **返回** 类型, 返回 1 个 **返回** 类型. **返回** 类型, **返回** 类型, **返回** 1 个 **返回** 类型.

pixeltype **返回** 类型, **返回** 类型. **pixeltype** **返回** NULL **返回** 类型, **返回** 类型 rast **返回** 类型.

- expression **返回** 类型.
 1. [rast] - **返回** 类型
 2. [rast.val] - **返回** 类型
 3. [rast.x] - **返回** 1-**返回** 类型
 4. [rast.y] - **返回** 1-**返回** 类型

名称: 函数 3, 4 (返回 2 个)

函数 rast1, (rast2) **返回** expression **返回** 2 个 **返回** 类型, **返回** PostgreSQL **返回** 类型, 返回 1 个 **返回** 类型. band1, band2 **返回** 类型, 返回 1 个 **返回** 类型. **返回** 类型 (返回, **返回** 类型) **返回** 类型. extenttype **返回** 类型.

expression **返回** 2 个 **返回** 类型 PostgreSQL **返回** 类型 PostgreSQL **返回** 类型/返回类型. 返回: (([rast1] + [rast2])/2.0)::integer

pixeltype **返回** 类型. **返回** **ST_BandPixelType** **返回** 类型, **返回** 类型, NULL **返回** 类型. **返回** 类型 NULL **返回** 类型, **返回** 类型 **返回** 类型.

extenttype **返回** 类型

1. INTERSECTION - **返回** 类型. **返回** 类型.
2. UNION - **返回** 类型.
3. FIRST - **返回** 类型.
4. SECOND - **返回** 类型.

nodataexpr rast1 **返回** 类型 NODATA **返回** 类型 rast2 **返回** 类型 **返回** 类型, 返回 rast2 **返回** 类型.

nodata2expr rast2 **返回** 类型 NODATA **返回** 类型 rast1 **返回** 类型 **返回** 类型, 返回 rast1 **返回** 类型.

nodatanodataval **返回** 类型 rast1 **返回** rast2 **返回** 类型 NODATA **返回** 类型 **返回** 类型.

- expression, nodataexpr **返回** nodata2expr **返回** 类型.
 1. [rast1] - rast1 **返回** 类型
 2. [rast1.val] - rast1 **返回** 类型
 3. [rast1.x] - rast1 **返回** 1-**返回** 类型
 4. [rast1.y] - rast1 **返回** 1-**返回** 类型
 5. [rast2] - rast2 **返回** 类型
 6. [rast2.val] - rast2 **返回** 类型
 7. [rast2.x] - rast2 **返回** 1-**返回** 类型
 8. [rast2.y] - rast2 **返回** 1-**返回** 类型

例 1

```
WITH foo AS (
  SELECT ST_AddBand(ST_MakeEmptyRaster(10, 10, 0, 0, 1, 1, 0, 0, 0), '32BF'::text, 1, -1) ←
    AS rast
)
SELECT
  ST_MapAlgebra(rast, 1, NULL, 'ceil([rast]*[rast.x]/[rast.y]+[rast.val])')
FROM foo;
```

例 3

```
WITH foo AS (
  SELECT 1 AS rid, ST_AddBand(ST_AddBand(ST_AddBand(ST_MakeEmptyRaster(2, 2, 0, 0, 1, -1, ←
    0, 0, 0), 1, '16BUI', 1, 0), 2, '8BUI', 10, 0), 3, '32BUI'::text, 100, 0) AS rast ←
    UNION ALL
  SELECT 2 AS rid, ST_AddBand(ST_AddBand(ST_AddBand(ST_MakeEmptyRaster(2, 2, 0, 0, 1, 1, -1, ←
    0, 0, 0), 1, '16BUI', 2, 0), 2, '8BUI', 20, 0), 3, '32BUI'::text, 300, 0) AS rast
)
SELECT
  ST_MapAlgebra(
    t1.rast, 2,
    t2.rast, 1,
    '([rast2] + [rast1.val]) / 2'
  ) AS rast
FROM foo t1
CROSS JOIN foo t2
WHERE t1.rid = 1
AND t2.rid = 2;
```

例

rastbandarg, **ST_Union**, **ST_MapAlgebra** (callback function version)

11.12.7 ST_MapAlgebraExpr

ST_MapAlgebraExpr — 例 1 例: PostgreSQL 例
例, 例, 例 1 例. 例, 例 1 例.

Synopsis

raster **ST_MapAlgebraExpr**(raster rast, integer band, text pixeltype, text expression, double precision nodataval=NULL);
raster **ST_MapAlgebraExpr**(raster rast, text pixeltype, text expression, double precision nodataval=NULL);

例



Warning

ST_MapAlgebraExpr 2.1.0 例. 例 **ST_MapAlgebra** (expression version) 例.

`ST_MapAlgebra(rast, expression)` 是 PostgreSQL 的 `ST_MapAlgebra` 函数，它接受 1 个 `rast` 参数和 1 个 `expression` 参数。nband 是栅格的带数，它接受 1 个 `rast` 参数。如果 `rast` 是 3 带的，那么 `expression` 应该是一个三元表达式。如果 `rast` 是 1 带的，那么 `expression` 应该是一个一元表达式。

`pixeltype` 是栅格的像素类型，它接受 1 个 `rast` 参数。如果 `pixeltype` 是 NULL，那么 `ST_MapAlgebra` 将使用 `rast` 的像素类型。

`ST_MapAlgebra(rast, 1-栅格的带数, 1-栅格的带数, 1-栅格的带数)` 是 `ST_MapAlgebra` 的另一种形式，它接受 4 个参数：栅格、栅格的带数、栅格的带数、栅格的带数。

2.0.0 版本支持 `ST_MapAlgebra`。

图 1

图 2 是 `ST_MapAlgebra` 的另一种形式，它接受 1 个 `rast` 参数和 1 个 `expression` 参数。

```
ALTER TABLE dummy_rast ADD COLUMN map_rast raster;
UPDATE dummy_rast SET map_rast = ST_MapAlgebraExpr(rast, NULL, 'mod([rast]::numeric,2)')
WHERE rid = 2;
```

```
SELECT
  ST_Value(rast,1,i,j) As origval,
  ST_Value(map_rast, 1, i, j) As mapval
FROM dummy_rast
CROSS JOIN generate_series(1, 3) AS i
CROSS JOIN generate_series(1,3) AS j
WHERE rid = 2;
```

origval	mapval
253	1
254	0
253	1
253	1
254	0
254	0
250	0
254	0
254	0

`ST_MapAlgebra` 的 `NODATA` 选项用于处理 `NODATA` 值。如果 `NODATA` 是 0，那么 `ST_MapAlgebra` 将返回 2BUI。如果 `NODATA` 是 1，那么 `ST_MapAlgebra` 将返回 1BUI。

```
ALTER TABLE dummy_rast ADD COLUMN map_rast2 raster;
UPDATE dummy_rast SET
  map_rast2 = ST_MapAlgebraExpr(rast, '2BUI'::text, 'CASE WHEN [rast] BETWEEN 100 and 250
    THEN 1 WHEN [rast] = 252 THEN 2 WHEN [rast] BETWEEN 253 and 254 THEN 3 ELSE 0 END'::
    text, '0')
WHERE rid = 2;
```



```
SELECT DISTINCT
  ST_Value(rast,1,i,j) As origval,
  ST_Value(map_rast2, 1, i, j) As mapval
FROM dummy_rast
CROSS JOIN generate_series(1, 5) AS i
CROSS JOIN generate_series(1,5) AS j
WHERE rid = 2;
```

origval	mapval
249	1

250		1
251		
252		2
253		3
254		3

```
SELECT
    ST_BandPixelType(map_rast2) As b1pixtyp
FROM dummy_rast
WHERE rid = 2;
```

```
blpixtyp
-----
2BUI
```

~~original (column rast view)~~~~rast view ma~~[illegible]

```
SELECT
    ST_AddBand(
        ST_AddBand(
            ST_AddBand(
                ST_MakeEmptyRaster(rast_view),
                ST_MapAlgebraExpr(rast_view,1,NULL,'tan([rast])*[rast]')
            ),
            ST_Band(rast_view,2)
        ),
        ST_Band(rast_view, 3)
    ) As rast_view_ma
FROM wind
WHERE rid=167;
```


ST MapAlgebraExpr, ST MapAlgebraFct, ST BandPixelType, ST GeoReference, ST Value

11.12.8 ST_MapAlgebraExpr

ST_MapAlgebraExpr — 对栅格 2 进行代数运算: 对栅格 2 进行代数运算 PostgreSQL 表达式, 栅格, 栅格数据类型, 栅格 1 的波段. 栅格数据类型, 栅格 1 的波段. 栅格数据类型 (栅格, 栅格数据类型) 栅格数据类型. extenttype 栅格数据类型. extenttype 栅格 INTERSECTION, UNION, FIRST, SECOND 栅格数据类型.

Synopsis

```
raster ST_MapAlgebraExpr(raster rast1, raster rast2, text expression, text pixeltype=same_as_rast1_band
text extenttype=INTERSECTION, text nodata1expr=NULL, text nodata2expr=NULL, double preci-
sion nodatanodataval=NULL);
raster ST_MapAlgebraExpr(raster rast1, integer band1, raster rast2, integer band2, text expression,
text pixeltype=same_as_rast1_band, text extenttype=INTERSECTION, text nodata1expr=NULL, text
nodata2expr=NULL, double precision nodatanodataval=NULL);
```

栅格



Warning

ST_MapAlgebraExpr 2.1.0 栅格数据类型. 栅格 **ST_MapAlgebra (expression version)** 栅格数据类型.

栅格 rast1, (rast2) 栅格 expression 栅格 2 栅格, 栅格 PostgreSQL 栅格数据类型, 栅格 1 栅格数据类型. band1, band2 栅格数据类型, 栅格 1 栅格数据类型. 栅格数据类型 (栅格, 栅格数据类型) 栅格数据类型. extenttype 栅格数据类型.

expression 栅格 2 栅格 PostgreSQL 栅格数据类型 PostgreSQL 栅格数据类型. 栅格: $(([rast1] + [rast2])/2.0)::integer$

pixeltype 栅格数据类型. 栅格 **ST_BandPixelType** 栅格数据类型, 栅格数据类型, NULL 栅格数据类型. 栅格数据类型 NULL 栅格数据类型, 栅格数据类型 栅格数据类型.

extenttype 栅格数据类型

1. INTERSECTION - 栅格数据类型. 栅格数据类型.
2. UNION - 栅格数据类型.
3. FIRST - 栅格数据类型.
4. SECOND - 栅格数据类型.

nodata1expr rast1 栅格数据类型 NODATA 栅格数据类型 rast2 栅格数据类型 栅格数据类型, 栅格 rast2 栅格数据类型.

nodata2expr rast2 栅格数据类型 NODATA 栅格数据类型 rast1 栅格数据类型 栅格数据类型, 栅格 rast1 栅格数据类型.

nodatanodataval 栅格数据类型 rast1 栅格 rast2 栅格数据类型 NODATA 栅格数据类型 栅格数据类型.

pixeltype 数据类型, 数据类型必须与 rast1 数据类型相同。 pixeltype 为 NULL 数据类型
数据类型, 数据类型必须与 rast1 数据类型相同。

数据类型数据类型 [rast1.val], [rast2.val], 数据类型数据类型 [rast1.x],
[rast1.y] 数据类型数据类型。

2.0.0 数据类型数据类型。

图: 图 2 数据类型数据类型

数据类型 2 数据类型数据类型 (modulo) 数据类型数据类型 1 数据类型数据类型数据类型。

```
--Create a cool set of rasters --
DROP TABLE IF EXISTS fun_shapes;
CREATE TABLE fun_shapes(rid serial PRIMARY KEY, fun_name text, rast raster);

-- Insert some cool shapes around Boston in Massachusetts state plane meters --
INSERT INTO fun_shapes(fun_name, rast)
VALUES ('ref', ST_AsRaster(ST_MakeEnvelope(235229, 899970, 237229, 901930,26986),200,200,'8BUI',0,0));

INSERT INTO fun_shapes(fun_name,rast)
WITH ref(rast) AS (SELECT rast FROM fun_shapes WHERE fun_name = 'ref' )
SELECT 'area' AS fun_name, ST_AsRaster(ST_Buffer(ST_SetSRID(ST_Point(236229, 900930),26986)
, 1000),
    ref.rast,'8BUI', 10, 0) As rast
FROM ref
UNION ALL
SELECT 'rand bubbles',
    ST_AsRaster(
        (SELECT ST_Collect(geom)
        FROM (SELECT ST_Buffer(ST_SetSRID(ST_Point(236229 + i*random()*100, 900930 + j*random()
*100),26986), random()*20) As geom
        FROM generate_series(1,10) As i, generate_series(1,10) As j
        ) As foo ), ref.rast,'8BUI', 200, 0)
FROM ref;

--map them -
SELECT ST_MapAlgebraExpr(
    area.rast, bub.rast, '[rast2.val]', '8BUI', 'INTERSECTION', '[rast2.val]', '[rast1.
val]') As interrast,
    ST_MapAlgebraExpr(
        area.rast, bub.rast, '[rast2.val]', '8BUI', 'UNION', '[rast2.val]', '[rast1.val
]') As unionrast
FROM
    (SELECT rast FROM fun_shapes WHERE
    fun_name = 'area') As area
CROSS JOIN (SELECT rast
FROM fun_shapes WHERE
    fun_name = 'rand bubbles') As bub
```




图 10-10: 两个缓冲区的交集和并集

```
-- we use ST_AsPNG to render the image so all single band ones look grey --
WITH mygeoms
  AS ( SELECT 2 As bnum, ST_Buffer(ST_Point(1,5),10) As geom
        UNION ALL
        SELECT 3 AS bnum,
              ST_Buffer(ST_GeomFromText('LINESTRING(50 50,150 150,150 50)'), 10,'join= ↵
              bevel') As geom
        UNION ALL
        SELECT 1 As bnum,
              ST_Buffer(ST_GeomFromText('LINESTRING(60 50,150 150,150 50)'), 5,'join= ↵
              bevel') As geom
      ),
  -- define our canvas to be 1 to 1 pixel to geometry
  canvas
  AS (SELECT ST_AddBand(ST_MakeEmptyRaster(200,
      200,
      ST_XMin(e)::integer, ST_YMax(e)::integer, 1, -1, 0, 0) , '8BUI'::text,0) As rast
      FROM (SELECT ST_Extent(geom) As e,
                  Max(ST_SRID(geom)) As srid
            from mygeoms
            ) As foo
      ),
  rbands AS (SELECT ARRAY(SELECT ST_MapAlgebraExpr(canvas.rast, ST_AsRaster(m.geom, canvas ↵
      .rast, '8BUI', 100),
              '[[rast2.val]]', '8BUI', 'FIRST', '[[rast2.val]]', '[[rast1.val]]') As rast
            FROM mygeoms AS m CROSS JOIN canvas
            ORDER BY m.bnum) As rasts
      )
  SELECT rasts[1] As rast1 , rasts[2] As rast2, rasts[3] As rast3, ST_AddBand(
      ST_AddBand(rasts[1],rasts[2]), rasts[3]) As final_rast
  FROM rbands;
```




图: 教程 2 教程

```
-- Create new 3 band raster composed of first 2 clipped bands, and overlay of 3rd band with ←
  our geometry
-- This query took 3.6 seconds on PostGIS windows 64-bit install
WITH pr AS
-- Note the order of operation: we clip all the rasters to dimensions of our region
(SELECT ST_Clip(rast,ST_Expand(geom,50) ) As rast, g.geom
  FROM aerals.o_2_boston AS r INNER JOIN
-- union our parcels of interest so they form a single geometry we can later intersect with
  (SELECT ST_Union(ST_Transform(geom,26986)) AS geom
    FROM landparcels WHERE pid IN('0303890000', '0303900000')) As g
   ON ST_Intersects(rast::geometry, ST_Expand(g.geom,50))
),
-- we then union the raster shards together
-- ST_Union on raster is kinda of slow but much faster the smaller you can get the rasters
-- therefore we want to clip first and then union
prunion AS
```



```

(SELECT ST_AddBand(NULL, ARRAY[ST_Union(rast,1),ST_Union(rast,2),ST_Union(rast,3)] ) As ←
  clipped,geom
FROM pr
GROUP BY geom)
-- return our final raster which is the unioned shard with
-- with the overlay of our parcel boundaries
-- add first 2 bands, then mapalgebra of 3rd band + geometry
SELECT ST_AddBand(ST_Band(clipped,ARRAY[1,2])
  , ST_MapAlgebraExpr(ST_Band(clipped,3), ST_AsRaster(ST_Buffer(ST_Boundary(geom),2), ←
    clipped, '8BUI',250),
    '[rast2.val]', '8BUI', 'FIRST', '[rast2.val]', '[rast1.val]')) ) As rast
FROM prunion;

```



XXXXXXXXXXXXXXXXXXXXXXXXXXXX.

☐☐

[ST_MapAlgebraExpr](#), [ST_AddBand](#), [ST_AsPNG](#), [ST_AsRaster](#), [ST_MapAlgebraFct](#), [ST_BandPixelType](#), [ST_GeoReference](#), [ST_Value](#), [ST_Union](#), [ST_Union](#)

11.12.9 ST_MapAlgebraFct

ST_MapAlgebraFct — 对栅格数据应用 1 个函数: 对 PostgreSQL 栅格函数进行栅格化, 对栅格函数进行栅格化, 对 1 个栅格函数进行栅格化. 对栅格函数进行栅格化, 对 1 个栅格函数进行栅格化.

Synopsis

```

raster ST_MapAlgebraFct(raster rast, regprocedure onerasteruserfunc);
raster ST_MapAlgebraFct(raster rast, regprocedure onerasteruserfunc, text[] VARIADIC args);
raster ST_MapAlgebraFct(raster rast, text pixeltype, regprocedure onerasteruserfunc);

```

raster **ST_MapAlgebraFct**(raster rast, text pixeltyp, regprocedure onerasteruserfunc, text[] VARIADIC args);
 raster **ST_MapAlgebraFct**(raster rast, integer band, regprocedure onerasteruserfunc);
 raster **ST_MapAlgebraFct**(raster rast, integer band, regprocedure onerasteruserfunc, text[] VARIADIC args);
 raster **ST_MapAlgebraFct**(raster rast, integer band, text pixeltyp, regprocedure onerasteruserfunc);
 raster **ST_MapAlgebraFct**(raster rast, integer band, text pixeltyp, regprocedure onerasteruserfunc, text[] VARIADIC args);

警告



Warning

ST_MapAlgebraFct 2.1.0 函数在 PostgreSQL 11.0 之前版本中不可用。使用 **ST_MapAlgebra (callback function version)** 函数。

rast (rast) 是 onerasteruserfunc 函数在 PostgreSQL 中定义的函数，它接受 1 个或多个参数。band 是整数，默认为 1。pixeltyp 是文本，默认为 NULL。args 是文本数组，默认为 1 个参数。

pixeltyp 是文本，默认为 NULL。args 是文本数组，默认为 1 个参数。

The onerasteruserfunc parameter must be the name and signature of a SQL or PL/pgSQL function, cast to a regprocedure. A very simple and quite useless PL/pgSQL function example is:

```
CREATE OR REPLACE FUNCTION simple_function(pixel FLOAT, pos INTEGER[], VARIADIC args TEXT [])
RETURNS FLOAT
AS $$ BEGIN
    RETURN 0.0;
END; $$
LANGUAGE 'plpgsql' IMMUTABLE;
```

The userfunction may accept two or three arguments: a float value, an optional integer array, and a variadic text array. The first argument is the value of an individual raster cell (regardless of the raster datatype). The second argument is the position of the current processing cell in the form '{x,y}'. The third argument indicates that all remaining parameters to **ST_MapAlgebraFct** shall be passed through to the userfunction.

Passing a regprocedure argument to a SQL function requires the full function signature to be passed, then cast to a regprocedure type. To pass the above example PL/pgSQL function as an argument, the SQL for the argument is:

```
'simple_function(float,integer[],text[])::regprocedure
```

Note that the argument contains the name of the function, the types of the function arguments, quotes around the name and argument types, and a cast to a regprocedure.

userfunction 是变长文本数组。使用 **ST_MapAlgebraFct** 函数，args 是变长文本数组。



Note

(**ST_MapAlgebraFct**) VARIADIC 函数在 PostgreSQL 11.0 之前版本中不可用。使用 **Query Language (SQL) Functions** 中的“SQL Functions with Variable Numbers of Arguments”函数。

**Note**

在调用 `mod_fct` 函数时，`userfunction` 参数必须指定为 `text[]` 类型的数组。

2.0.0 版本开始支持。

##

在表 `dummy_rast` 中添加列 `map_rast` (modulo) 函数，并更新该列。

```
ALTER TABLE dummy_rast ADD COLUMN map_rast raster;
CREATE FUNCTION mod_fct(pixel float, pos integer[], variadic args text[])
RETURNS float
AS $$
BEGIN
    RETURN pixel::integer % 2;
END;
$$
LANGUAGE 'plpgsql' IMMUTABLE;

UPDATE dummy_rast SET map_rast = ST_MapAlgebraFct(rast,NULL,'mod_fct(float,integer[],text
[])::regprocedure) WHERE rid = 2;

SELECT ST_Value(rast,1,i,j) As origval, ST_Value(map_rast, 1, i, j) As mapval
FROM dummy_rast CROSS JOIN generate_series(1, 3) AS i CROSS JOIN generate_series(1,3) AS j
WHERE rid = 2;
```

origval	mapval
253	1
254	0
253	1
253	1
254	0
254	0
250	0
254	0
254	0

在表 `dummy_rast` 中添加列 `map_rast2` (0) 函数，并更新该列。

```
ALTER TABLE dummy_rast ADD COLUMN map_rast2 raster;
CREATE FUNCTION classify_fct(pixel float, pos integer[], variadic args text[])
RETURNS float
AS
$$
DECLARE
    nodata float := 0;
BEGIN
    IF NOT args[1] IS NULL THEN
        nodata := args[1];
    END IF;
    IF pixel < 251 THEN
        RETURN 1;
    ELSIF pixel = 252 THEN
        RETURN 2;
    ELSIF pixel
```

```
> 252 THEN
      RETURN 3;
    ELSE
      RETURN nodata;
    END IF;
END;
$$
LANGUAGE 'plpgsql';
UPDATE dummy_rast SET map_rast2 = ST_MapAlgebraFct(rast,'2BUI','classify_fct(float,integer ↵
    [],text[])':::regprocedure, '0') WHERE rid = 2;
```



```
SELECT DISTINCT ST_Value(rast,1,i,j) As origval, ST_Value(map_rast2, 1, i, j) As mapval
FROM dummy_rast CROSS JOIN generate_series(1, 5) AS i CROSS JOIN generate_series(1,5) AS j
WHERE rid = 2;
```

original	mapval
249	1
250	1
251	
252	2
253	3
254	3

```
SELECT ST_BandPixelType(map_rast2) As blpixtyp
FROM dummy_rast WHERE rid = 2;
```

b1pixtyp

2BUI

~~⊠⊠ (rast-view ⊠)~~~~rast view ma~~[illegible]

```
CREATE FUNCTION rast_plus_tan(pixel float, pos integer[], variadic args text[])
RETURNS float
AS
$$
```

```
BEGIN
    RETURN tan(pixel) * pixel;
END;
$$
LANGUAGE 'plpgsql';

SELECT ST_AddBand(
    ST_AddBand(
        ST_AddBand(
            ST_MakeEmptyRaster(rast_view),
            ST_MapAlgebraFct(rast_view,1,NULL,'rast_plus_tan(float,integer[],text[])':: regprocedure)
        ),
        ST_Band(rast_view,2)
    ),
    ST_Band(rast_view, 3) As rast_view_ma
)
FROM wind
WHERE rid=167;
```


ST_MapAlgebraExpr, ST_BandPixelType, ST_GeoReference, ST_SetValue

11.12.10 ST MapAlgebraFct

ST_MapAlgebraFct — 2 2: 2 PostgreSQL 2, 2, 1 1. 1 INTERSECTION.

Synopsis

```

raster ST_MapAlgebraFct(raster rast1, raster rast2, regprocedure tworastuserfunc, text pixeltype=same_as_rast1, text extenttype=INTERSECTION, text[] VARIADIC userargs);
raster ST_MapAlgebraFct(raster rast1, integer band1, raster rast2, integer band2, regprocedure tworastuserfunc, text pixeltype=same_as_rast1, text extenttype=INTERSECTION, text[] VARIADIC userargs);

```



Warning

ST_MapAlgebraFct 2.1.0                                

```
CREATE FUNCTION rast1, rast2 TEXT tworastuserfunc RETURNS PostgreSQL TEXT AS $$
    SELECT band1 || band2 FROM rast1, rast2 WHERE band1 = band2 AND rast1 = rast2;
END;
```

```
pixeltype 0x000000, 0x000000000000000000000000. pixeltype 0x NULL 0x00000000
0x000000. 0x0000000000000000 rast1 0x000000000000000000000000.
```

The `tworastuserfunc` parameter must be the name and signature of an SQL or PL/pgSQL function, cast to a `regprocedure`. An example PL/pgSQL function example is:

```
CREATE OR REPLACE FUNCTION simple_function_for_two_rasters(pixel1 FLOAT, pixel2 FLOAT, pos ←
  INTEGER[], VARIADIC args TEXT[])
  RETURNS FLOAT
  AS $$ BEGIN
    RETURN 0.0;
  END; $$
LANGUAGE 'plpgsql' IMMUTABLE;
```

The `tworastuserfunc` may accept three or four arguments: a double precision value, a double precision value, an optional integer array, and a variadic text array. The first argument is the value of an individual raster cell in `rast1` (regardless of the raster datatype). The second argument is an individual raster cell value in `rast2`. The third argument is the position of the current processing cell in the form `'{x,y}'`. The fourth argument indicates that all remaining parameters to `ST_MapAlgebraFct` shall be passed through to the `tworastuserfunc`.

Passing a regprocedure argument to a SQL function requires the full function signature to be passed, then cast to a regprocedure type. To pass the above example PL/pgSQL function as an argument, the SQL for the argument is:

```
'simple_function(double precision, double precision, integer[], text[])':regprocedure
```

Note that the argument contains the name of the function, the types of the function arguments, quotes around the name and argument types, and a cast to a regprocedure.

The fourth argument to the `tworastuserfunc` is a variadic text array. All trailing text arguments to any `ST_MapAlgebraFct` call are passed through to the specified `tworastuserfunc`, and are contained in the `userargs` argument.



Note

(`ST_MapAlgebraFct`) VARIADIC `TEXT[]`, PostgreSQL `Query Language (SQL) Functions` “SQL Functions with Variable Numbers of Arguments”.



Note

`tworastuserfunc` `TEXT[]`.

2.0.0 国际化。

国际化: 国际化

```
-- define our user defined function --
CREATE OR REPLACE FUNCTION raster_mapalgebra_union(
  rast1 double precision,
  rast2 double precision,
  pos integer[],
  VARIADIC userargs text[]
)
  RETURNS double precision
  AS $$
  DECLARE
  BEGIN
  CASE
```

```


        WHEN rast1 IS NOT NULL AND rast2 IS NOT NULL THEN
            RETURN ((rast1 + rast2)/2.);
        WHEN rast1 IS NULL AND rast2 IS NULL THEN
            RETURN NULL;
        WHEN rast1 IS NULL THEN
            RETURN rast2;
        ELSE
            RETURN rast1;
    END CASE;

    RETURN NULL;
END;
$$ LANGUAGE 'plpgsql' IMMUTABLE COST 1000;

-- prep our test table of rasters
DROP TABLE IF EXISTS map_shapes;
CREATE TABLE map_shapes(rid serial PRIMARY KEY, rast raster, bnum integer, descrip text);
INSERT INTO map_shapes(rast,bnum, descrip)
WITH mygeoms
  AS ( SELECT 2 As bnum, ST_Buffer(ST_Point(90,90),30) As geom, 'circle' As descrip
      UNION ALL
      SELECT 3 AS bnum,
            ST_Buffer(ST_GeomFromText('LINESTRING(50 50,150 150,150 50)'), 15) As geom, ←
            'big road' As descrip
      UNION ALL
      SELECT 1 As bnum,
            ST_Translate(ST_Buffer(ST_GeomFromText('LINESTRING(60 50,150 150,150 50)'), ←
            8,'join=bevel'), 10,-6) As geom, 'small road' As descrip
      ),
  -- define our canvas to be 1 to 1 pixel to geometry
  canvas
  AS ( SELECT ST_AddBand(ST_MakeEmptyRaster(250,
      250,
      ST_XMin(e)::integer, ST_YMax(e)::integer, 1, -1, 0, 0 ) , '8BUI'::text,0) As rast
      FROM (SELECT ST_Extent(geom) As e,
            Max(ST_SRID(geom)) As srid
            from mygeoms
            ) As foo
      )
  -- return our rasters aligned with our canvas
SELECT ST_AsRaster(m.geom, canvas.rast, '8BUI', 240) As rast, bnum, descrip
  FROM mygeoms AS m CROSS JOIN canvas
UNION ALL
SELECT canvas.rast, 4, 'canvas'
FROM canvas;

-- Map algebra on single band rasters and then collect with ST_AddBand
INSERT INTO map_shapes(rast,bnum,descrip)
SELECT ST_AddBand(ST_AddBand(rasts[1], rasts[2]),rasts[3]), 4, 'map bands overlay fct union ←
  (canvas)'
  FROM (SELECT ARRAY(SELECT ST_MapAlgebraFct(m1.rast, m2.rast,
    'raster_mapalgebra_union(double precision, double precision, integer[], text[]) ←
    '::regprocedure, '8BUI', 'FIRST')
    FROM map_shapes As m1 CROSS JOIN map_shapes As m2
    WHERE m1.descrip = 'canvas' AND m2.descrip <
    > 'canvas' ORDER BY m2.bnum) As rasts) As foo;

```





 (R: small road, G: circle, B: big road)

```
CREATE OR REPLACE FUNCTION raster_mapalgebra_userargs(
    rast1 double precision,
    rast2 double precision,
    pos integer[],
    VARIADIC userargs text[]
)
RETURNS double precision
AS $$
DECLARE
BEGIN
    CASE
        WHEN rast1 IS NOT NULL AND rast2 IS NOT NULL THEN
            RETURN least(userargs[1]::integer,(rast1 + rast2)/2.);
        WHEN rast1 IS NULL AND rast2 IS NULL THEN
            RETURN userargs[2]::integer;
        WHEN rast1 IS NULL THEN
            RETURN greatest(rast2,random()*userargs[3]::integer)::integer;
        ELSE
            RETURN greatest(rast1, random()*userargs[4]::integer)::integer;
    END CASE;

    RETURN NULL;
END;
$$ LANGUAGE 'plpgsql' VOLATILE COST 1000;

SELECT ST_MapAlgebraFct(m1.rast, 1, m1.rast, 3,
    'raster_mapalgebra_userargs(double precision, double precision, integer[], text ↵
        [])::regprocedure,
        '8BUI', 'INTERSECT', '100','200','200','0')
    FROM map_shapes As m1
WHERE m1.descrip = 'map bands overlay fct union (canvas)';
```




图 11.12.11: ST_MapAlgebraFctNgb 的 3D 渲染结果

图 11.12.11

[ST_MapAlgebraExpr](#), [ST_BandPixelType](#), [ST_GeoReference](#), [ST_SetValue](#)

11.12.11 ST_MapAlgebraFctNgb

ST_MapAlgebraFctNgb — 图 11.12.11: 图 11.12.11 PostgreSQL 图 11.12.11 (Map Algebra Nearest Neighbor) 图 11.12.11. 图 11.12.11 (neighborhood) 图 11.12.11 PostgreSQL 图 11.12.11.

Synopsis

raster **ST_MapAlgebraFctNgb**(raster rast, integer band, text pixeltype, integer ngbwidth, integer ngbheight, regprocedure onerastngbuserfunc, text nodatamode, text[] VARIADIC args);

图 11.12.11



Warning

ST_MapAlgebraFctNgb 2.1.0 图 11.12.11. 图 11.12.11 **ST_MapAlgebra (callback function version)** 图 11.12.11.

图 11.12.11: 图 11.12.11 (neighborhood) 图 11.12.11 PostgreSQL 图 11.12.11. 图 11.12.11, 图 11.12.11.

rast 图 11.12.11

band 整数 (范围 1)

pixeltype 文本。格式 `ST_BandPixelType` 返回像素类型, 格式, NULL 格式。格式 NULL 格式, `rast` 格式 格式。格式。格式。

ngbwidth 整数 (neighborhood) 格式

ngbheight 整数 (neighborhood) 格式

onerastngbuserfunc 格式 PL/pgSQL 格式 `psql` 格式。格式 格式 2 格式。

nodatamode NODATA 格式 NULL 格式。

'ignore': 格式 NODATA 格式。格式, 格式 NODATA 格式。

'NULL': 格式 NODATA 格式 NULL 格式。格式。

'value': 格式 NODATA 格式 (格式) 格式。格式 NODATA 格式, (格式) 'NULL' 格式。

args 格式

2.0.0 格式。

格式

格式 http://trac.osgeo.org/gdal/wiki/frmts_wtkraster.html 格式 `ST_Rescale` 格式。

```
--
-- A simple 'callback' user function that averages up all the values in a neighborhood.
--
CREATE OR REPLACE FUNCTION rast_avg(matrix float[][] , nodatamode text, variadic args text ←
[])
RETURNS float AS
$$
DECLARE
    _matrix float[][];
    x1 integer;
    x2 integer;
    y1 integer;
    y2 integer;
    sum float;
BEGIN
    _matrix := matrix;
    sum := 0;
    FOR x in array_lower(matrix, 1)..array_upper(matrix, 1) LOOP
        FOR y in array_lower(matrix, 2)..array_upper(matrix, 2) LOOP
            sum := sum + _matrix[x][y];
        END LOOP;
    END LOOP;
    RETURN (sum*1.0/(array_upper(matrix,1)*array_upper(matrix,2) ))::integer ;
END;
$$
LANGUAGE 'plpgsql' IMMUTABLE COST 1000;

-- now we apply to our raster averaging pixels within 2 pixels of each other in X and Y ←
direction --
SELECT ST_MapAlgebraFctNgb(rast, 1, '8BUI', 4,4,
```

```
'rast_avg(float[][], text, text[])'::regprocedure, 'NULL', NULL) As nn_with_border
FROM katrinas_rescaled
limit 1;
```




图 11.12.12

[ST_MapAlgebraFct](#), [ST_MapAlgebraExpr](#), [ST_Rescale](#)

11.12.12 ST_Reclass

ST_Reclass — 重新分类栅格。 `band` 指定要重新分类的波段。 `reclassarg` 指定重新分类的表达式。 `pixeltype` 指定输出栅格的像素类型。 `nodataval` 指定输出栅格的空值。

Synopsis

```
raster ST_Reclass(raster rast, integer nband, text reclassexpr, text pixeltype, double precision no-
dataval=NULL);
raster ST_Reclass(raster rast, reclassarg[] VARIADIC reclassargset);
raster ST_Reclass(raster rast, text reclassexpr, text pixeltype);
```

图 11.12.12

`reclassarg` (rast) 指定重新分类的表达式。 PostgreSQL 表达式语言。 `band` 指定要重新分类的波段，从 1 开始。 `pixeltype` 指定输出栅格的像素类型。 `nodataval` 指定输出栅格的空值。 `reclassarg` 指定重新分类的表达式。

`pixeltype` 指定输出栅格的像素类型。 `reclassargset` 指定重新分类的表达式， `reclassarg`(`reclassarg`) 指定重新分类的表达式。

2.0.0 版本引入。

数据表

表 2 包含 8BUI 和 4BUI 类型的 101 个 254 字节的 NODATA 值。

```
ALTER TABLE dummy_rast ADD COLUMN reclass_rast raster;
UPDATE dummy_rast SET reclass_rast = ST_Reclass(rast,2,'0-87:1-10, 88-100:11-15, 101-254:0-0', '4BUI',0) WHERE rid = 2;

SELECT i as col, j as row, ST_Value(rast,2,i,j) As origval,
       ST_Value(reclass_rast, 2, i, j) As reclassval,
       ST_Value(reclass_rast, 2, i, j, false) As reclassval_include_nodata
FROM dummy_rast CROSS JOIN generate_series(1, 3) AS i CROSS JOIN generate_series(1,3) AS j
WHERE rid = 2;
```

col	row	origval	reclassval	reclassval_include_nodata
1	1	78	9	9
2	1	98	14	14
3	1	122		0
1	2	96	14	14
2	2	118		0
3	2	180		0
1	3	99	15	15
2	3	112		0
3	3	169		0

重新分类结果

表 1, 2, 3 包含 1BB, 4BUI, 4BUI 类型的 101 个 254 字节的 NODATA 值。表 1 (包含 1BB 类型) 包含 101 个 254 字节的 NODATA 值, 表 2 包含 8BUI 和 4BUI 类型的 101 个 254 字节的 NODATA 值。

```
UPDATE dummy_rast SET reclass_rast =
  ST_Reclass(rast,
    ROW(2,'0-87]:1-10, (87-100]:11-15, (101-254]:0-0', '4BUI',NULL)::reclassarg,
    ROW(1,'0-253]:1, 254:0', '1BB', NULL)::reclassarg,
    ROW(3,'0-70]:1, (70-86]:2, [86-150]:3, [150-255]:4', '4BUI', NULL)::reclassarg
  ) WHERE rid = 2;

SELECT i as col, j as row,ST_Value(rast,1,i,j) As ov1, ST_Value(reclass_rast, 1, i, j) As rv1,
       ST_Value(rast,2,i,j) As ov2, ST_Value(reclass_rast, 2, i, j) As rv2,
       ST_Value(rast,3,i,j) As ov3, ST_Value(reclass_rast, 3, i, j) As rv3
FROM dummy_rast CROSS JOIN generate_series(1, 3) AS i CROSS JOIN generate_series(1,3) AS j
WHERE rid = 2;
```

col	row	ov1	rv1	ov2	rv2	ov3	rv3
1	1	253	1	78	9	70	1
2	1	254	0	98	14	86	3
3	1	253	1	122	0	100	3
1	2	253	1	96	14	80	2
2	2	254	0	118	0	108	3
3	2	254	0	180	0	162	4
1	3	250	1	99	15	90	3
2	3	254	0	112	0	108	3
3	3	254	0	169	0	175	4

32BF 数据类型用于存储 32 位浮点值。

32BF 数据类型用于存储 32 位浮点值 ((8BUI,8BUI,8BUI) 数据类型用于存储 8 位无符号整数)。

```
ALTER TABLE wind ADD COLUMN rast_view raster;
UPDATE wind
  set rast_view = ST_AddBand( NULL,
    ARRAY[
      ST_Reclass(rast, 1, '0-1-10]:1-10,9-10]:11,(11-33:0':::text, '8BUI':::text,0),
      ST_Reclass(rast,1, '11-33):0-255,[0-32:0,(34-1000:0':::text, '8BUI':::text,0),
      ST_Reclass(rast,1,'0-32]:0,(32-100:100-255':::text, '8BUI':::text,0)
    ]
  );
```

ST

[ST_AddBand](#), [ST_Band](#), [ST_BandPixelType](#), [ST_MakeEmptyRaster](#), [reclassarg](#), [ST_Value](#)

11.12.13 ST_Union

ST_Union — 将 1 个或多个栅格合并为一个栅格。

Synopsis

```
raster ST_Union(setof raster rast);
raster ST_Union(setof raster rast, unionarg[] unionargset);
raster ST_Union(setof raster rast, integer nband);
raster ST_Union(setof raster rast, text uniontype);
raster ST_Union(setof raster rast, integer nband, text uniontype);
```

ST

将 1 个或多个栅格合并为一个栅格。unionarg 可以是栅格名称、栅格变量或栅格函数。uniontype 可以是栅格名称、栅格变量或栅格函数。uniontype 可以是 LAST(栅格), FIRST, MIN, MAX, COUNT, SUM, MEAN, RANGE 等。



Note

In order for rasters to be unioned, they must all have the same alignment. Use [ST_SameAlignment](#) and [ST_NotSameAlignmentReason](#) for more details and help. One way to fix alignment issues is to use [ST_Resample](#) and use the same reference raster for alignment.

2.0.0 版本引入。

更新: 2.1.0 版本引入 (在 C 语言中)。

2.1.0 版本引入 **ST_Union(rast, unionarg)** 函数。

更新: 2.1.0 版本引入 **ST_Union(rast)** 函数 1 个参数。PostGIS 3.5.7 版本引入。

更新: 2.1.0 版本引入 **ST_Union(rast, uniontype)** 函数 4 个参数。

例: 从栅格瓦片创建单波段栅格

```
-- this creates a single band from first band of raster tiles
-- that form the original file system tile
SELECT filename, ST_Union(rast,1) As file_rast
FROM sometable WHERE filename IN('dem01','dem02') GROUP BY filename;
```

例: 从栅格瓦片创建多波段栅格

```
-- this creates a multi band raster collecting all the tiles that intersect a line
-- Note: In 2.0, this would have just returned a single band raster
-- , new union works on all bands by default
-- this is equivalent to unionarg: ARRAY[ROW(1, 'LAST'), ROW(2, 'LAST'), ROW(3, 'LAST')]:: ←
  unionarg[]
SELECT ST_Union(rast)
FROM aeriāls.boston
WHERE ST_Intersects(rast, ST_GeomFromText('LINESTRING(230486 887771, 230500 88772)',26986) ←
);
```

例: 从栅格瓦片创建多波段栅格

从栅格瓦片创建多波段栅格, 从栅格瓦片创建多波段栅格。

```
-- this creates a multi band raster collecting all the tiles that intersect a line
SELECT ST_Union(rast,ARRAY[ROW(2, 'LAST'), ROW(1, 'LAST'), ROW(3, 'LAST')]::unionarg[])
FROM aeriāls.boston
WHERE ST_Intersects(rast, ST_GeomFromText('LINESTRING(230486 887771, 230500 88772)',26986) ←
);
```

例

unionarg, ST_Envelope, ST_ConvexHull, ST_Clip, ST_Union

11.13 空间函数

11.13.1 ST_Distinct4ma

ST_Distinct4ma — 从栅格瓦片创建多波段栅格。

Synopsis

float8 **ST_Distinct4ma**(float8[][] matrix, text nodatamode, text[] VARIADIC args);
double precision **ST_Distinct4ma**(double precision[][][] value, integer[][] pos, text[] VARIADIC user-args);

函数

ST_DistanceWeighted (Inverse Distance Weighted method) 返回两个点之间的距离。

userargs 指定要使用的距离权重函数。默认为 2。距离权重函数可以是 0 到 1 之间的任意值 (力率) 乘以 (距离的 k 次方)。距离权重函数, 默认为 1。距离权重函数可以是 0 到 1 之间的任意值 (力率) 乘以 (距离的 k 次方)。距离权重函数, 默认为 1。距离权重函数可以是 0 到 1 之间的任意值 (力率) 乘以 (距离的 k 次方)。

距离权重函数可以是 0 到 1 之间的任意值 (力率) 乘以 (距离的 k 次方)。

$$\hat{z}(x_o) = \frac{\sum_{j=1}^m z(x_j) d_{ij}^{-k}}{\sum_{j=1}^m d_{ij}^{-k}}$$

$k =$ 距离权重函数 (power factor), 0 到 1 之间的任意值



Note

距离权重函数 **ST_MapAlgebra (callback function version)** 返回两个点之间的距离。

2.1.0 版本引入。

函数

-- NEEDS EXAMPLE

函数

ST_MapAlgebra (callback function version), ST_MinDist4ma

11.13.3 ST_Max4ma

ST_Max4ma — 返回两个点之间的最大距离。

Synopsis

float8 **ST_Max4ma**(float8[][] matrix, text nodatamode, text[] VARIADIC args);
double precision **ST_Max4ma**(double precision[][] value, integer[][] pos, text[] VARIADIC userargs);

函数

距离权重函数可以是 0 到 1 之间的任意值 (力率) 乘以 (距离的 k 次方)。

默认为 2。距离权重函数可以是 0 到 1 之间的任意值 (力率) 乘以 (距离的 k 次方)。



Note

从 1 开始 `ST_MapAlgebraFctNgb` 函数支持空值。



Note

从 2 开始 `ST_MapAlgebra (callback function version)` 函数支持空值。



Warning

2.1.0 版本 `ST_MapAlgebraFctNgb` 函数不支持空值。

2.0.0 版本 `ST_MapAlgebraFctNgb` 函数不支持空值。
从 2.1.0 版本开始 `ST_MapAlgebraFctNgb` 函数支持空值。

SQL

```
SELECT
  rid,
  st_value(
    st_mapalgebrafctngb(rast, 1, NULL, 1, 1, 'st_max4ma(float[][],text,text[])'::
      regprocedure, 'ignore', NULL), 2, 2
  )
FROM dummy_rast
WHERE rid = 2;
rid | st_value
-----+-----
  2 |      254
(1 row)
```

函数

`ST_MapAlgebraFctNgb`, `ST_MapAlgebra (callback function version)`, `ST_Min4ma`, `ST_Sum4ma`, `ST_Mean4ma`, `ST_Range4ma`, `ST_Distinct4ma`, `ST_StdDev4ma`

11.13.4 ST_Mean4ma

`ST_Mean4ma` — 计算 4 个相邻像素的平均值。

Synopsis

`float8 ST_Mean4ma(float8[][] matrix, text nodatamode, text[] VARIADIC args);`
`double precision ST_Mean4ma(double precision[][] value, integer[][] pos, text[] VARIADIC user-args);`

[illegible]

```

    2 0000, 0000 userargs 0000 NODATA 0000000000000000.

```



Note

```
0x1 ST_MapAlgebraFctNgb [XXXXXXXXXXXXXXXXXXXXXXXXXXXX].
```



Note

2 **ST_MapAlgebra (callback function version)**



Warning

2.1.0  **ST_MapAlgebraFctNgb**  1 .

2.0.0 ☒☒☒☒☒☒☒☒☒☒☒.

☒☒☒☒: 2.1.0 ☒☒☒☒☒☒ 2 ☒☒☒☒☒☒☒.

☒☒: ☒☒ 1

```
SELECT
  rid,
  st_value(
    st_mapalgebrafctngb(rast, 1, '32BF', 1, 1, 'st_mean4ma(float[][],text,text[])':: ↵
    regprocedure, 'ignore', NULL), 2, 2
  )
FROM dummy_rast
WHERE rid = 2;
 rid |      st_value
-----+-----
   2 | 253.222229003906
(1 row)
```

☒☒: ☒☒ 2

```
SELECT
  rid,
  st_value(
    ST_MapAlgebra(rast, 1, 'st_mean4ma(double precision[][][], integer[][], text ↵
      [])'::regprocedure, '32BF', 'FIRST', NULL, 1, 1)
    , 2, 2)
FROM dummy_rast
WHERE rid = 2;
rid |      st_value
-----+-----
  2 | 253.222229003906
(1 row)
```

函数

[ST_MapAlgebraFctNgb](#), [ST_MapAlgebra](#) (callback function version), [ST_Min4ma](#), [ST_Max4ma](#), [ST_Sum4ma](#), [ST_Range4ma](#), [ST_StdDev4ma](#)

11.13.5 ST_Min4ma

`ST_Min4ma` — 返回栅格中每个像素的最小值。

Synopsis

`float8` **ST_Min4ma**(`float8[][]` matrix, `text` nodatamode, `text[]` VARIADIC args);
`double precision` **ST_Min4ma**(`double precision[][][]` value, `integer[][]` pos, `text[]` VARIADIC userargs);

函数

返回栅格中每个像素的最小值。

需要 2 个参数, 变长参数 `userargs` 可以指定 NODATA 值。



Note

需要 1 个 [ST_MapAlgebraFctNgb](#) 函数。



Note

需要 2 个 [ST_MapAlgebra](#) (callback function version) 函数。



Warning

2.1.0 版本 [ST_MapAlgebraFctNgb](#) 函数需要 1 个参数。

2.0.0 版本 [ST_Min4ma](#) 函数。

兼容性: 2.1.0 版本需要 2 个参数。

函数

```
SELECT
  rid,
  st_value(
    st_mapalgebrafctngb(rast, 1, NULL, 1, 1, 'st_min4ma(float[][],text,text[])':: ↵
      regprocedure, 'ignore', NULL), 2, 2
  )
FROM dummy_rast
WHERE rid = 2;
 rid | st_value
-----+-----
   2 |    250
(1 row)
```

函数

[ST_MapAlgebraFctNgb](#), [ST_MapAlgebra](#) (callback function version), [ST_Max4ma](#), [ST_Sum4ma](#), [ST_Mean4ma](#), [ST_Range4ma](#), [ST_Distinct4ma](#), [ST_StdDev4ma](#)

11.13.6 ST_MinDist4ma

`ST_MinDist4ma` — 返回指定栅格中指定位置的最小距离 (以米为单位) 的栅格。

Synopsis

double precision **ST_MinDist4ma**(double precision[][][] value, integer[][] pos, text[] VARIADIC user-args);

函数

返回指定栅格中指定位置的最小距离 (以米为单位) 的栅格。



Note

此函数与 [ST_InvDistWeight4ma](#) 类似，但返回的是最小距离而不是权重。权重是距离的倒数。



Note

此函数与 [ST_MapAlgebra](#) (callback function version) 类似，但返回的是最小距离而不是权重。

2.1.0 版本引入。

函数

-- NEEDS EXAMPLE

函数

[ST_MapAlgebra](#) (callback function version), [ST_InvDistWeight4ma](#)

11.13.7 ST_Range4ma

`ST_Range4ma` — 返回指定栅格中指定位置的值的范围 (以米为单位) 的栅格。

Synopsis

float8 **ST_Range4ma**(float8[][] matrix, text nodatamode, text[] VARIADIC args);
double precision **ST_Range4ma**(double precision[][][] value, integer[][] pos, text[] VARIADIC user-args);

函数

函数返回一个浮点数组。

函数 2 参数, 函数 userargs 函数 NODATA 函数返回一个浮点数组。



Note

函数 1 函数 **ST_MapAlgebraFctNgb** 函数返回一个浮点数组。



Note

函数 2 函数 **ST_MapAlgebra (callback function version)** 函数返回一个浮点数组。



Warning

2.1.0 函数 **ST_MapAlgebraFctNgb** 函数返回一个浮点数组 1 函数返回一个浮点数组。

2.0.0 函数返回一个浮点数组。

函数: 2.1.0 函数 2 函数返回一个浮点数组。

函数

```
SELECT
  rid,
  st_value(
    st_mapalgebrafctngb(rast, 1, NULL, 1, 1, 'st_range4ma(float[][],text,text[])':: ↵
    regprocedure, 'ignore', NULL), 2, 2
  )
FROM dummy_rast
WHERE rid = 2;
rid | st_value
-----+-----
  2 |         4
(1 row)
```

函数

ST_MapAlgebraFctNgb, **ST_MapAlgebra (callback function version)**, **ST_Min4ma**, **ST_Max4ma**, **ST_Sum4ma**, **ST_Mean4ma**, **ST_Distinct4ma**, **ST_StdDev4ma**

11.13.8 ST_StdDev4ma

ST_StdDev4ma — 函数返回一个浮点数组。

Synopsis

float8 **ST_StdDev4ma**(float8[][] matrix, text nodatamode, text[] VARIADIC args);
double precision **ST_StdDev4ma**(double precision[][][] value, integer[][] pos, text[] VARIADIC user-args);

注意

此函数在 2.0.0 版本中引入。



Note

注意 1 **ST_MapAlgebraFctNgb** 函数在 2.0.0 版本中引入。



Note

注意 2 **ST_MapAlgebra (callback function version)** 函数在 2.0.0 版本中引入。



Warning

2.1.0 版本中 **ST_MapAlgebraFctNgb** 函数在 1 个参数下使用。

2.0.0 版本中引入。

注意: 2.1.0 版本中 2 个参数使用。

注意

```
SELECT
  rid,
  st_value(
    st_mapalgebrafctngb(rast, 1, '32BF', 1, 1, 'st_stddev4ma(float[][],text,text[])':: ↵
    regprocedure, 'ignore', NULL), 2, 2
  )
FROM dummy_rast
WHERE rid = 2;
 rid |      st_value
-----+-----
   2 | 1.30170822143555
(1 row)
```

注意

ST_MapAlgebraFctNgb, **ST_MapAlgebra (callback function version)**, **ST_Min4ma**, **ST_Max4ma**, **ST_Sum4ma**, **ST_Mean4ma**, **ST_Distinct4ma**, **ST_StdDev4ma**

11.13.9 ST_Sum4ma

ST_Sum4ma — 在 4 个移动平均窗口中求和。

Synopsis

float8 **ST_Sum4ma**(float8[][] matrix, text nodatamode, text[] VARIADIC args);
double precision **ST_Sum4ma**(double precision[][][] value, integer[][] pos, text[] VARIADIC user-args);

注意

ST_Sum4ma 返回一个浮点8精度值。

参数 2 是用户参数，可以是 NODATA 或任何文本。



Note

参数 1 是 **ST_MapAlgebraFctNgb** 的回调函数名称。



Note

参数 2 是 **ST_MapAlgebra (callback function version)** 的回调函数名称。



Warning

2.1.0 版本中 **ST_MapAlgebraFctNgb** 的回调函数名称 1 是必需的。

2.0.0 版本中 **ST_MapAlgebraFctNgb** 的回调函数名称 1 是必需的。

注意：2.1.0 版本中 2 个参数是必需的。

注意

```
SELECT
  rid,
  st_value(
    st_mapalgebrafctngb(rast, 1, '32BF', 1, 1, 'st_sum4ma(float[][][],text,text[])':: ↵
    regprocedure, 'ignore', NULL), 2, 2
  )
FROM dummy_rast
WHERE rid = 2;
rid | st_value
-----+-----
  2 |      2279
(1 row)
```

注意

ST_MapAlgebraFctNgb, **ST_MapAlgebra (callback function version)**, **ST_Min4ma**, **ST_Max4ma**, **ST_Mean4ma**, **ST_Range4ma**, **ST_Distinct4ma**, **ST_StdDev4ma**

11.14 地形函数

11.14.1 ST_Aspect

`ST_Aspect` — 计算给定栅格 (栅格) 的方位角。返回方位角值。

Synopsis

```
raster ST_Aspect(raster rast, integer band=1, text pixeltype=32BF, text units=DEGREES, boolean
interpolate_nodata=FALSE);
raster ST_Aspect(raster rast, integer band, raster customextent, text pixeltype=32BF, text units=DEGREES,
boolean interpolate_nodata=FALSE);
```

参数

`rast` 是输入栅格 (栅格) 的方位角。返回方位角值。

`units` 是方位角的单位。RADIANS, DEGREES(默认) 是可能的值。

`units = RADIANS` 时, 方位角值在 0 到 2π 之间。

`units = DEGREES` 时, 方位角值在 0 到 360 之间。

如果 `band` 为 0, 则返回 -1。



Note

方位角 (slope), 方位角 (aspect), 阴影 (hillshade) 函数在 [ESRI - How hillshade works](#) 和 [ERDAS Field Guide - Aspect Images](#) 中有详细解释。

2.0.0 版本引入。

更新: 2.1.0 版本引入 `ST_MapAlgebra()` 函数, 使用 `interpolate_nodata` 参数。

更新: 2.1.0 版本引入 `ST_MapAlgebra()` 函数。2.1.0 版本引入 `ST_MapAlgebra()` 函数。

示例: 1

```
WITH foo AS (
  SELECT ST_SetValues(
    ST_AddBand(ST_MakeEmptyRaster(5, 5, 0, 0, 1, -1, 0, 0, 0), 1, '32BF', 0, -9999),
    1, 1, 1, ARRAY[
      [1, 1, 1, 1, 1],
      [1, 2, 2, 2, 1],
      [1, 2, 3, 2, 1],
      [1, 2, 2, 2, 1],
      [1, 1, 1, 1, 1]
    ]::double precision[5][5]
  ) AS rast
)
SELECT
  ST_DumpValues(ST_Aspect(rast, 1, '32BF'))
FROM foo
```



```
(1, "{315,341.565063476562,0,18.4349479675293,45},{288.434936523438,315,0,45,71.5650482177734},{270
2227,180,161.565048217773,135}}")
(1 row)
```

☒☒: ☒☒ 2

XXXXXXXXXXXXXXXXXXXX. XXXX PostgreSQL 9.1 XXXXXXXXXXXXXXXX.


```

WITH foo AS (
    SELECT ST_Tile(
        ST_SetValues(
            ST_AddBand(
                ST_MakeEmptyRaster(6, 6, 0, 0, 1, -1, 0, 0, 0),
                1, '32BF', 0, -9999
            ),
            1, 1, 1, ARRAY[
                [1, 1, 1, 1, 1, 1],
                [1, 1, 1, 1, 2, 1],
                [1, 2, 2, 3, 3, 1],
                [1, 1, 3, 2, 1, 1],
                [1, 2, 2, 1, 2, 1],
                [1, 1, 1, 1, 1, 1]
            ]::double precision[]
        ),
        2, 2
    ) AS rast
)
SELECT
    t1.rast,
    ST_Aspect(ST_Union(t2.rast), 1, t1.rast)
FROM foo t1
CROSS JOIN foo t2
WHERE ST_Intersects(t1.rast, t2.rast)
GROUP BY t1.rast;

```


ST MapAlgebra (callback function version), ST TRI, ST TPI, ST Roughness, ST HillShade, ST Slope

11.14.2 ST HillShade

ST HillShade — 

Synopsis

```
raster ST_HillShade(raster rast, integer band=1, text pixeltype=32BF, double precision azimuth=315,  
double precision altitude=45, double precision max_bright=255, double precision scale=1.0, boolean
```

interpolate_nodata=FALSE);

raster **ST_HillShade**(raster rast, integer band, raster customextent, text pixeltype=32BF, double precision azimuth=315, double precision altitude=45, double precision max_bright=255, double precision scale=1.0, boolean interpolate_nodata=FALSE);

説明

azimuth 方位角, 0 から 360 度の範囲で指定します。0 は北 (真北) を指し、90 は東 (天頂) を指します。単位は度です。0 から 255 の範囲で指定します。

altitude 傾斜角, 0 から 90 度の範囲で指定します。0 は水平面を指し、90 は天頂を指します。単位は度です。

max_bright 最大明るさ, 0 から 255 の範囲で指定します。0 は黒を指し、255 は白を指します。

scale スケール, 1.0 を指定します。0 から 255 の範囲で指定します。

scale 111120 を指定します。単位: 111120 scale=370400, 単位: 111120 scale=111120 を指定します。

interpolate_nodata 0 または 1 を指定します。0 は NODATA を挿入し、1 は ST_InvDistWeight4ma を使用して NODATA を処理します。



Note

傾斜角の計算方法については、[How hillshade works](#) を参照してください。

2.0.0 以降のバージョンで利用可能です。

例: 2.1.0 以降のバージョンで ST_MapAlgebra() を使用して、azimuth を interpolate_nodata を指定して実行します。

例: 2.1.0 以降のバージョンで ST_MapAlgebra() を使用して、altitude を interpolate_nodata を指定して実行します。

例: 例 1

```
WITH foo AS (
  SELECT ST_SetValues(
    ST_AddBand(ST_MakeEmptyRaster(5, 5, 0, 0, 1, -1, 0, 0, 0), 1, '32BF', 0, -9999),
    1, 1, 1, ARRAY[
      [1, 1, 1, 1, 1],
      [1, 2, 2, 2, 1],
      [1, 2, 3, 2, 1],
      [1, 2, 2, 2, 1],
      [1, 1, 1, 1, 1]
    ]::double precision[]
  ) AS rast
)
SELECT
  ST_DumpValues(ST_Hillshade(rast, 1, '32BF'))
FROM foo
```

```
(1, "{NULL,NULL,NULL,NULL,NULL},{NULL,251.32763671875,220.749786376953,147.224319458008, ←
NULL},{NULL,220.749786376953,180.312225341797,67.7497863769531,NULL},{NULL ←
,147.224319458008
,67.7497863769531,43.1210060119629,NULL},{NULL,NULL,NULL,NULL,NULL}}")
(1 row)
```

图例: 图 2

图例: 图 2. 图例 PostgreSQL 9.1 图例.

```
WITH foo AS (
  SELECT ST_Tile(
    ST_SetValues(
      ST_AddBand(
        ST_MakeEmptyRaster(6, 6, 0, 0, 1, -1, 0, 0, 0),
        1, '32BF', 0, -9999
      ),
      1, 1, 1, ARRAY[
        [1, 1, 1, 1, 1, 1],
        [1, 1, 1, 1, 2, 1],
        [1, 2, 2, 3, 3, 1],
        [1, 1, 3, 2, 1, 1],
        [1, 2, 2, 1, 2, 1],
        [1, 1, 1, 1, 1, 1]
      ]::double precision[]
    ),
    2, 2
  ) AS rast
)
SELECT
  t1.rast,
  ST_Hillshade(ST_Union(t2.rast), 1, t1.rast)
FROM foo t1
CROSS JOIN foo t2
WHERE ST_Intersects(t1.rast, t2.rast)
GROUP BY t1.rast;
```

图例

ST_MapAlgebra (callback function version), ST_TRI, ST_TPI, ST_Roughness, ST_Aspect, ST_Slope

11.14.3 ST_Roughness

ST_Roughness — DEM 图例 (roughness) 图例.

Synopsis

raster **ST_Roughness**(raster rast, integer nband, raster customextent, text pixeltype="32BF", boolean interpolate_nodata=FALSE);

图例

图例 DEM 图例 图例.

2.1.0 图例.

例

```
-- needs examples
```

例

[ST_MapAlgebra \(callback function version\)](#), [ST_TRI](#), [ST_TPI](#), [ST_Slope](#), [ST_HillShade](#), [ST_Aspect](#)

11.14.4 ST_Slope

`ST_Slope` — 计算栅格的坡度 (以度为单位)。返回栅格的浮点值。

Synopsis

```
raster ST_Slope(raster rast, integer nband=1, text pixeltype=32BF, text units=DEGREES, double
precision scale=1.0, boolean interpolate_nodata=FALSE);
raster ST_Slope(raster rast, integer nband, raster customextent, text pixeltype=32BF, text units=DEGREES,
double precision scale=1.0, boolean interpolate_nodata=FALSE);
```

例

计算坡度 (以度为单位) 的栅格。返回栅格的浮点值。

`units` 可以是 RADIANS, DEGREES(默认), PERCENT 之一。

`scale` 是栅格的缩放比例。例如: 如果 `scale=370400`, 那么 `scale=111120` 就是 1 度。

`interpolate_nodata` 是布尔值, 如果为 `TRUE`, 那么 `ST_InvDistWeight4ma` 将在 `NODATA` 值周围进行插值。



Note

坡度 (slope), 方位 (aspect), 阴影 (hillshade) 函数在 [ESRI - How hillshade works](#) 和 [ERDAS Field Guide - Slope Images](#) 中有详细描述。

2.0.0 版本中已弃用。

更新: 2.1.0 版本中 `ST_MapAlgebra()` 已弃用, 使用 `units`, `scale`, `interpolate_nodata` 参数。

更新: 2.1.0 版本中 `ST_Slope` 函数已弃用。2.1.0 版本中 `ST_Slope` 函数已弃用。

例: 例 1

```
WITH foo AS (
  SELECT ST_SetValues(
    ST_AddBand(ST_MakeEmptyRaster(5, 5, 0, 0, 1, -1, 0, 0, 0), 1, '32BF', 0, -9999),
    1, 1, 1, ARRAY[
      [1, 1, 1, 1, 1],
      [1, 2, 2, 2, 1],
      [1, 2, 3, 2, 1],
```

```

        [1, 2, 2, 2, 1],
        [1, 1, 1, 1, 1]
    ]::double precision[][])
    ) AS rast
)
SELECT
    ST_DumpValues(ST_Slope(rast, 1, '32BF'))
FROM foo

```

st_dumpvalues

```

(1,"{{10.0249881744385,21.5681285858154,26.5650520324707,21.5681285858154,10.0249881744385},{21.5681285858154,26.5650520324707,36.8698959350586,0,36.8698959350586,26.5650520324707},{21.5681285858154,35.26438905681285858154,26.5650520324707,21.5681285858154,10.0249881744385}}}")
(1 row)

```

图 2

图 2: 图 2. PostgreSQL 9.1 中的图 2.

```

WITH foo AS (
    SELECT ST_Tile(
        ST_SetValues(
            ST_AddBand(
                ST_MakeEmptyRaster(6, 6, 0, 0, 1, -1, 0, 0, 0),
                1, '32BF', 0, -9999
            ),
            1, 1, 1, ARRAY[
                [1, 1, 1, 1, 1, 1],
                [1, 1, 1, 1, 2, 1],
                [1, 2, 2, 3, 3, 1],
                [1, 1, 3, 2, 1, 1],
                [1, 2, 2, 1, 2, 1],
                [1, 1, 1, 1, 1, 1]
            ]::double precision[]
        ),
        2, 2
    ) AS rast
)
SELECT
    t1.rast,
    ST_Slope(ST_Union(t2.rast), 1, t1.rast)
FROM foo t1
CROSS JOIN foo t2
WHERE ST_Intersects(t1.rast, t2.rast)
GROUP BY t1.rast;

```

图 2

ST_MapAlgebra (callback function version), ST_TRI, ST_TPI, ST_Roughness, ST_HillShade, ST_Aspect

11.14.5 ST_TPI

ST_TPI — 地形位置指数 (Topographic Position Index) 函数。

Synopsis

raster **ST_TPI**(raster rast, integer nband, raster customextent, text pixeltype="32BF" , boolean interpolate_nodata=FALSE);

返回

Calculates the Topographic Position Index, which is defined as the focal mean with radius of one minus the center cell.



Note

默认 1 (focalmean radius of one) 使用。

2.1.0 版本。

需要

-- needs examples

返回

[ST_MapAlgebra \(callback function version\)](#), [ST_TRI](#), [ST_Roughness](#), [ST_Slope](#), [ST_HillShade](#), [ST_Aspect](#)

11.14.6 ST_TRI

ST_TRI — 地形崎岖度指数 (Terrain Ruggedness Index) 函数。

Synopsis

raster **ST_TRI**(raster rast, integer nband, raster customextent, text pixeltype="32BF" , boolean interpolate_nodata=FALSE);

返回

地形崎岖度指数 (Terrain Ruggedness Index) 函数。



Note

默认 1 (focalmean radius of one) 使用。

2.1.0 版本。

图

-- needs examples

图

[ST_MapAlgebra \(callback function version\)](#), [ST_Roughness](#), [ST_TPI](#), [ST_Slope](#), [ST_HillShade](#), [ST_Aspect](#)

11.15 几何函数

11.15.1 Box3D

Box3D — 返回 BOX3D 几何体。

Synopsis

box3d **Box3D**(raster rast);

图

返回 BOX3D 几何体。

参数 ((MINX, MINY), (MAXX, MAXY)) 指定 BOX3D 的边界。

兼容性: 2.0.0 版本引入 BOX3D 函数。BOX2D 函数在 2.0.0 版本引入 BOX3D 函数。

图

```
SELECT
  rid,
  Box3D(rast) AS rastbox
FROM dummy_rast;
```

rid	rastbox
1	BOX3D(0.5 0.5 0,20.5 60.5 0)
2	BOX3D(3427927.75 5793243.5 0,3427928 5793244 0)

图

[ST_Envelope](#)

11.15.2 ST_ConvexHull

ST_ConvexHull — 返回 BandNoDataValue 指定的栅格数据的凸包。ST_Envelope 返回栅格数据的包围盒。

Synopsis

setof geomval **ST_DumpAsPolygons**(raster rast, integer band_num=1, boolean exclude_nodata_value=TRUE)

返回

返回一个集合返回函数 (SRF; Set-Returning Function) 的结果。返回 (geom) 类型的集合 (val) 的集合。返回 geomval 类型的集合。返回 val 类型的集合。返回 val 类型的集合。

ST_DumpAsPolygon 返回一个集合返回函数 (SRF; Set-Returning Function) 的结果。返回 (geom) 类型的集合 (val) 的集合。返回 geomval 类型的集合。返回 val 类型的集合。返回 val 类型的集合。

Changed 3.3.0, validation and fixing is disabled to improve performance. May result invalid geometries.

GDAL 1.7 支持。

Note
If there is a no data value set for a band, pixels with that value will not be returned except in the case of exclude_nodata_value=false.

Note
返回的集合 (val) 是 ST_ValueCount 的结果。

Note
返回的集合 (val) 是 ST_PixelAsPolygons 的结果。

返回

```
-- this syntax requires PostgreSQL 9.3+
SELECT val, ST_AsText(geom) As geomwkt
FROM (
  SELECT dp.*
  FROM dummy_rast, LATERAL ST_DumpAsPolygons(rast) AS dp
  WHERE rid = 2
) As foo
WHERE val BETWEEN 249 and 251
ORDER BY val;
```

val	geomwkt
249	POLYGON((3427927.95 5793243.95,3427927.95 5793243.85,3427928 5793243.85,3427928 5793243.95,3427927.95 5793243.95))
250	POLYGON((3427927.75 5793243.9,3427927.75 5793243.85,3427927.8 5793243.85,3427927.8 5793243.9,3427927.75 5793243.9))
250	POLYGON((3427927.8 5793243.8,3427927.8 5793243.75,3427927.85 5793243.75,3427927.85 5793243.8,3427927.8 5793243.8))
251	POLYGON((3427927.75 5793243.85,3427927.75 5793243.8,3427927.8 5793243.8,3427927.8 5793243.85,3427927.75 5793243.85))

返回

[geomval](#), [ST_Value](#), [ST_Polygon](#), [ST_ValueCount](#)

11.15.4 ST_Envelope

ST_Envelope — 返回给定栅格的边界框。

Synopsis

geometry **ST_Envelope**(raster rast);

返回

返回的几何体具有与输入栅格相同的 SRID。如果输入栅格的 SRID 是 0，则返回的几何体的 SRID 也是 0。如果输入栅格的 SRID 不是 0，则返回的几何体的 SRID 是输入栅格的 SRID。返回的几何体是 float8 精度。

返回的几何体是 ((MINX, MINY), (MINX, MAXY), (MAXX, MAXY), (MAXX, MINY), (MINX, MINY))。

返回

```
SELECT rid, ST_AsText(ST_Envelope(rast)) As envgeomwkt
FROM dummy_rast;
```

rid	envgeomwkt

1	POLYGON((0 0,20 0,20 60,0 60,0 0))
2	POLYGON((3427927 5793243,3427928 5793243,
	3427928 5793244,3427927 5793244, 3427927 5793243))

返回

[ST_Envelope](#), [ST_AsText](#), [ST_SRID](#)

11.15.5 ST_MinConvexHull

ST_MinConvexHull — 返回给定栅格的最小凸包。

Synopsis

geometry **ST_MinConvexHull**(raster rast, integer nband=NULL);

返回

返回的几何体具有与输入栅格相同的 SRID。如果输入栅格的 SRID 是 0，则返回的几何体的 SRID 也是 0。如果输入栅格的 SRID 不是 0，则返回的几何体的 SRID 是输入栅格的 SRID。返回的几何体是 float8 精度。nband 为 NULL 时，返回的几何体是输入栅格的所有非空像素的凸包。

2.1.0 版本引入。

图例

```
WITH foo AS (  
  SELECT  
    ST_SetValues(  
      ST_SetValues(  
        ST_AddBand(ST_MakeEmptyRaster(9, 9, 0, 0, 1, -1, 0, 0, 0), 1, '8 ←  
          BUI', 0, 0), 2, '8BUI', 1, 0),  
        1, 1, 1,  
        ARRAY[  
          [0, 0, 0, 0, 0, 0, 0, 0, 0],  
          [0, 0, 0, 0, 0, 0, 0, 0, 0],  
          [0, 0, 0, 0, 0, 0, 0, 0, 0],  
          [0, 0, 0, 1, 0, 0, 0, 0, 1],  
          [0, 0, 0, 1, 1, 0, 0, 0, 0],  
          [0, 0, 0, 1, 0, 0, 0, 0, 0],  
          [0, 0, 0, 0, 0, 0, 0, 0, 0],  
          [0, 0, 0, 0, 0, 0, 0, 0, 0],  
          [0, 0, 0, 0, 0, 0, 0, 0, 0]  
        ]::double precision[][])  
      ),  
      2, 1, 1,  
      ARRAY[  
        [0, 0, 0, 0, 0, 0, 0, 0, 0],  
        [0, 0, 0, 0, 0, 0, 0, 0, 0],  
        [0, 0, 0, 0, 0, 0, 0, 0, 0],  
        [1, 0, 0, 0, 0, 1, 0, 0, 0],  
        [0, 0, 0, 0, 1, 1, 0, 0, 0],  
        [0, 0, 0, 0, 0, 1, 0, 0, 0],  
        [0, 0, 0, 0, 0, 0, 0, 0, 0],  
        [0, 0, 0, 0, 0, 0, 0, 0, 0],  
        [0, 0, 1, 0, 0, 0, 0, 0, 0]  
      ]::double precision[][])  
    ) AS rast  
)  
SELECT  
  ST_AsText(ST_ConvexHull(rast)) AS hull,  
  ST_AsText(ST_MinConvexHull(rast)) AS mhull,  
  ST_AsText(ST_MinConvexHull(rast, 1)) AS mhull_1,  
  ST_AsText(ST_MinConvexHull(rast, 2)) AS mhull_2  
FROM foo  
  
          hull          |          mhull          |  
          mhull_1      |          mhull_2      |  
-----+-----+-----+  
POLYGON((0 0,9 0,9 -9,0 -9,0 0)) | POLYGON((0 -3,9 -3,9 -9,0 -9,0 -3)) | POLYGON((3 -3,9 ←  
-3,9 -6,3 -6,3 -3)) | POLYGON((0 -3,6 -3,6 -9,0 -9,0 -3))
```

图例

ST_Envelope, ST_ConvexHull, ST_ConvexHull, ST_AsText

11.15.6 ST_Polygon

ST_Polygon — NODATA 返回空结果集。

Synopsis

geometry **ST_Polygon**(raster rast, integer band_num=1);

更新

Changed 3.3.0, validation and fixing is disabled to improve performance. May result invalid geometries.

0.1.6 更新。GDAL 1.7 更新。

更新: 2.1.0 更新 (C 更新)。更新。

更新: 2.1.0 更新, 更新。

更新

```
-- by default no data band value is 0 or not set, so polygon will return a square polygon
SELECT ST_AsText(ST_Polygon(rast)) As geomwkt
FROM dummy_rast
WHERE rid = 2;

geomwkt
-----
MULTIPOLYGON(((3427927.75 5793244,3427928 5793244,3427928 5793243.75,3427927.75 5793243.75,3427927.75 5793244)))

-- now we change the no data value of first band
UPDATE dummy_rast SET rast = ST_SetBandNoDataValue(rast,1,254)
WHERE rid = 2;
SELECT rid, ST_BandNoDataValue(rast)
from dummy_rast where rid = 2;

-- ST_Polygon excludes the pixel value 254 and returns a multipolygon
SELECT ST_AsText(ST_Polygon(rast)) As geomwkt
FROM dummy_rast
WHERE rid = 2;

geomwkt
-----
MULTIPOLYGON(((3427927.9 5793243.95,3427927.85 5793243.95,3427927.85 5793244,3427927.9 5793244,3427927.9 5793243.95)),((3427928 5793243.85,3427928 5793243.8,3427927.95 5793243.8,3427927.95 5793243.85,3427927.9 5793243.85,3427927.9 5793243.9,3427927.9 5793243.95,3427927.95 5793243.95,3427928 5793243.95,3427928 5793243.85)),((3427927.8 5793243.75,3427927.75 5793243.75,3427927.75 5793243.8,3427927.75 5793243.85,3427927.75 5793243.9,3427927.75 5793244,3427927.8 5793244,3427927.8 5793243.9,3427927.8 5793243.85,3427927.85 5793243.85,3427927.85 5793243.8,3427927.85 5793243.75,3427927.8 5793243.75)))

-- Or if you want the no data value different for just one time

SELECT ST_AsText(
  ST_Polygon(
    ST_SetBandNoDataValue(rast,1,252)
  )
) As geomwkt
FROM dummy_rast
WHERE rid =2;
```

```
geomwkt
-----
MULTIPOLYGON(((3427928 5793243.85,3427928 5793243.8,3427928 5793243.75,3427927.85 ↵
5793243.75,3427927.8 5793243.75,3427927.8 5793243.8,3427927.75 5793243.8,3427927.75 ↵
5793243.85,3427927.75 5793243.9,3427927.75 5793244,3427927.8 5793244,3427927.85 ↵
5793244,3427927.9 5793244,3427928 5793244,3427928 5793243.95,3427928 5793243.85) ↵
,(3427927.9 5793243.9,3427927.9 5793243.85,3427927.95 5793243.85,3427927.95 ↵
5793243.9,3427927.9 5793243.9)))
```

图 11.16

ST_Value, ST_DumpAsPolygons

11.16 空间关系

11.16.1 &&

&& — A 与 B 相交返回 TRUE。

Synopsis

```
boolean &&( raster A , raster B );
boolean &&( raster A , geometry B );
boolean &&( geometry B , raster A );
```

图 11.17

&& 返回 TRUE 当且仅当 A 与 B 相交。



Note
该函数 (operand) 返回 TRUE 当且仅当 A 与 B 相交。

2.0.0 版本引入。

图 11.18

```
SELECT A.rid As a_riD, B.riD As b_riD, A.rast && B.rast As intersect
FROM dummy_rast AS A CROSS JOIN dummy_rast AS B LIMIT 3;

a_riD | b_riD | intersect
-----+-----+-----
2 | 2 | t
2 | 3 | f
2 | 1 | f
```

11.16.2 <

< — A 与 B 的交集是否为 TRUE。

Synopsis

boolean <(raster A , raster B);

返回

< 返回 A 与 B 的交集是否为 TRUE，如果 A 与 B 的交集不为 TRUE，则返回 FALSE。



Note

如果 (operand) 为 NULL，则返回 NULL。

返回

```
SELECT A.rid As a_rid, B.rid As b_rid, A.rast < B.rast As overleft
FROM dummy_rast AS A CROSS JOIN dummy_rast AS B;
```

a_rid	b_rid	overleft
2	2	t
2	3	f
2	1	f
3	2	t
3	3	t
3	1	f
1	2	t
1	3	t
1	1	t

11.16.3 >

> — A 与 B 的并集是否为 TRUE。

Synopsis

boolean >(raster A , raster B);

返回

> 返回 A 与 B 的并集是否为 TRUE，如果 A 与 B 的并集不为 TRUE，则返回 FALSE。



Note

运算符 (operand) 必须都是栅格类型。

例

```
SELECT A.rid As a_rid, B.rid As b_rid, A.rast &
> B.rast As overright
FROM dummy_rast AS A CROSS JOIN dummy_rast AS B;
```

a_rid	b_rid	overright
2	2	t
2	3	t
2	1	t
3	2	f
3	3	t
3	1	f
1	2	f
1	3	t
1	1	t

11.16.4 =

$=$ — A 与 B 的对应像素值相等时返回 TRUE。返回栅格类型。

Synopsis

```
boolean =( raster A , raster B );
```

例

$=$ 返回栅格 A 与栅格 B 的对应像素值相等时返回 TRUE。PostgreSQL 支持 $=$, $<$, $>$ 运算符 (如: GROUP BY 或 ORDER BY)。



Caution

运算符 (operand) 必须都是栅格类型。返回栅格类型。 $\sim$ 是逐像素的按位取反运算符 (group by) 不支持。

2.1.0 版本开始支持。

例

$\sim$ =

11.16.5 @

@ — B 与 A 的交集是否为 TRUE。如果为 TRUE，则返回 TRUE。

Synopsis

```
boolean @( raster A , raster B );
boolean @( geometry A , raster B );
boolean @( raster B , geometry A );
```

返回

@ 返回 B 与 A 的交集是否为 TRUE。



Note

如果 B 是 NULL，则返回 NULL。

2.0.0 添加 raster @ raster, raster @ geometry。

2.0.5 添加 geometry @ raster。

返回

~

11.16.6 ~=

~= — A 与 B 的交集是否为 TRUE。

Synopsis

```
boolean ~= ( raster A , raster B );
```

返回

~= 返回 A 与 B 的交集是否为 TRUE。



Note

如果 B 是 NULL，则返回 NULL。

2.0.0 添加。

例

将精度为 2 的栅格与精度为 1 的栅格相加，并返回精度为 1 的栅格。

```
SELECT ST_AddBand(prec.rast, alt.rast) As new_rast
FROM prec INNER JOIN alt ON (prec.rast ~= alt.rast);
```

例

ST_AddBand, =

11.16.7 ~

~ — A 与 B 不相交返回 TRUE。否则返回 FALSE。

Synopsis

```
boolean ~( raster A , raster B );
boolean ~( geometry A , raster B );
boolean ~( raster B , geometry A );
```

例

~ 返回 TRUE 当且仅当 A 与 B 不相交。



Note

~ 的 (operand) 必须是栅格或几何体。

2.0.0 版本引入。

例

@

11.17 空间关系函数

11.17.1 ST_Contains

ST_Contains — 如果 rastA 包含 rastB，则返回 TRUE，否则返回 FALSE。

Synopsis

```
boolean ST_Contains( raster rastA , integer nbandA , raster rastB , integer nbandB );
boolean ST_Contains( raster rastA , raster rastB );
```


`rastA` `rastB`, `rastB` `rastA` `rastA` `rastB`. `NULL`, `(NODATA )`



Note!

Note

[illegible]

Note!

Note

ST_Contains(ST_Polygon(raster), geometry) ST_Contains(geometry, ST_Polygon(raster)) ST_Polygon



Note!

Note

ST_Contains() ☒ ST_Within() ☒☒☒☒☒☒☒. ☒☒☒, ST_Contains(rastA, rastB) ☒☒☒☒
ST_Within(rastB, rastA) ☒☒☒☒☒☒☒☒☒☒☒.

2.1.0 ☒☒☒☒☒☒☒☒☒☒☒.



```
-- specified band numbers
SELECT r1.rid, r2.rid, ST_Contains(r1.rast, 1, r2.rast, 1) FROM dummy_rast r1 CROSS JOIN ↵
    dummy_rast r2 WHERE r1.rid = 1;
```

NOTICE: The first raster provided has no bands

```

rid | rid | st_contains
-----+-----
  1 |  1 |
  1 |  2 | f

```

```
-- no band numbers specified
SELECT r1.rid, r2.rid, ST_Contains(r1.rast, r2.rast) FROM dummy_rast r1 CROSS JOIN ↵
    dummy_rast r2 WHERE r1.rid = 1;
```

```

rid | rid | st_contains
-----+-----
  1 |  1 | t
  1 |  2 | f

```



ST Intersects, ST Within

11.17.2 ST ContainsProperly

ST ContainsProperly — rastB $\not\subseteq$ rastA $\wedge \text{rastA} \not\subseteq \text{rastA} \oplus \text{rastB}$

Synopsis

```
boolean ST_ContainsProperly( raster rastA , integer nbandA , raster rastB , integer nbandB );
boolean ST_ContainsProperly( raster rastA , raster rastB );
```

注意

`ST_ContainsProperly(rastB, rastA)` 返回 true 当且仅当 `rastA` 的所有非空像素都包含在 `rastB` 的非空像素中，且 `rastA` 至少有一个像素不在 `rastB` 中。如果任一输入为 NULL，则返回 NULL。如果任一输入为 NODATA，则返回 false。

`ST_ContainsProperly(rastA, rastA)` 返回 false。



Note

`ST_ContainsProperly` 与 `ST_Contains` 类似，但要求 `rastA` 至少有一个像素不在 `rastB` 中。



Note

`ST_ContainsProperly(ST_Polygon(raster), geometry)` 与 `ST_ContainsProperly(geometry, ST_Polygon(raster))` 返回 true 当且仅当 `ST_Polygon` 包含 `geometry`。

2.1.0 版本引入。

注意

```
SELECT r1.rid, r2.rid, ST_ContainsProperly(r1.rast, 1, r2.rast, 1) FROM dummy_rast r1 CROSS JOIN
dummy_rast r2 WHERE r1.rid = 2;
```

rid	rid	st_containsproperly
2	1	f
2	2	f

注意

[ST_Intersects](#), [ST_Contains](#)

11.17.3 ST_Covers

`ST_Covers` — 返回 true 当且仅当 `rastB` 的所有非空像素都包含在 `rastA` 的非空像素中。

Synopsis

```
boolean ST_Covers( raster rastA , integer nbandA , raster rastB , integer nbandB );
boolean ST_Covers( raster rastA , raster rastB );
```


rustB rastA rastA rastB. NULL, (NODATA) .

Note!

Note

[illegible]

Note!

Note

ST_Covers(ST_Polygon(raster), geometry) $\neq$ ST_Covers(geometry, ST_Polygon(raster)) $\neq$ ST_Polygon(raster).

2.1.0 ☒☒☒☒☒☒☒☒☒☒☒.



```
SELECT r1.rid, r2.rid, ST_Covers(r1.rast, 1, r2.rast, 1) FROM dummy_rast r1 CROSS JOIN ↵
    dummy_rast r2 WHERE r1.rid = 2;
```

```

rid | rid | st_covers
-----+-----+-----
  2 |   1 | f
  2 |   2 | t

```



ST Intersects, ST CoveredBy

11.17.4 ST CoveredBy

ST CoveredBy — rastA rastB .

Synopsis

```
boolean ST_CoveredBy( raster rastA , integer nbandA , raster rastB , integer nbandB );
boolean ST_CoveredBy( raster rastA , raster rastB );
```



`rastA` `rastB` `rastA` `rastB`. `NULL`, `(NODATA)`.



Note

ST_CoveredBy(geometry, ST_Polygon(raster)) 与 ST_CoveredBy(ST_Polygon(raster), geometry) 不同。



Note

ST_CoveredBy(geometry, ST_Polygon(raster)) 与 ST_CoveredBy(ST_Polygon(raster), geometry) 不同。ST_CoveredBy(geometry, ST_Polygon(raster)) 返回 ST_Polygon 是否完全覆盖 geometry。

2.1.0 版本引入。

SQL

```
SELECT r1.rid, r2.rid, ST_CoveredBy(r1.rast, 1, r2.rast, 1) FROM dummy_rast r1 CROSS JOIN
dummy_rast r2 WHERE r1.rid = 2;
```

rid	rid	st_coveredby
2	1	f
2	2	t

SQL

ST_Intersects, ST_Covers

11.17.5 ST_Disjoint

ST_Disjoint — 判断 rastA 与 rastB 是否不相交。

Synopsis

boolean **ST_Disjoint**(raster rastA , integer nbandA , raster rastB , integer nbandB);
boolean **ST_Disjoint**(raster rastA , raster rastB);

SQL

判断 rastA 与 rastB 是否不相交。如果 rastA 与 rastB 不相交，则返回 true。如果 rastA 与 rastB 相交，则返回 false。如果任一输入为 NULL，则返回 NULL。如果任一输入为 NODATA，则返回 false。



Note

ST_Disjoint 与 ST_Contains 互斥。

**Note**

ST_Disjoint(ST_Polygon(raster), geometry) 与 ST_Polygon 不同。

2.1.0 版本。

```

-- rid = 1 has no bands, hence the NOTICE and the NULL value for st_disjoint
SELECT r1.rid, r2.rid, ST_Disjoint(r1.rast, 1, r2.rast, 1) FROM dummy_rast r1 CROSS JOIN
    dummy_rast r2 WHERE r1.rid = 2;

NOTICE: The second raster provided has no bands
rid | rid | st_disjoint
-----+-----+-----
  2 |  1 |
  2 |  2 | f

```

```

-- this time, without specifying band numbers
SELECT r1.rid, r2.rid, ST_Disjoint(r1.rast, r2.rast) FROM dummy_rast r1 CROSS JOIN
    dummy_rast r2 WHERE r1.rid = 2;

```

```

NOTICE: The second raster provided has no bands
rid | rid | st_disjoint
-----+-----+-----
  2 |  1 | t
  2 |  2 | f

```

```

rid | rid | st_disjoint
-----+-----+-----
  2 |  1 | t
  2 |  2 | f

```

```

-- this time, without specifying band numbers
SELECT r1.rid, r2.rid, ST_Disjoint(r1.rast, r2.rast) FROM dummy_rast r1 CROSS JOIN
    dummy_rast r2 WHERE r1.rid = 2;

```

```

rid | rid | st_disjoint
-----+-----+-----
  2 |  1 | t
  2 |  2 | f

```

```

ST_Intersects

```

ST_Intersects**11.17.6 ST_Intersects**

ST_Intersects — 检查 rasterA 与 rasterB 是否相交。

Synopsis

```

boolean ST_Intersects( raster rastA , integer nbandA , raster rastB , integer nbandB );
boolean ST_Intersects( raster rastA , raster rastB );
boolean ST_Intersects( raster rast , integer nband , geometry geommin );
boolean ST_Intersects( raster rast , geometry geommin , integer nband=NULL );
boolean ST_Intersects( geometry geommin , raster rast , integer nband=NULL );

```

```

ST_Intersects

```

检查 rasterA 与 rasterB 是否相交。如果任一输入为 NULL 或 0，则返回 NULL。如果任一输入为 0，则返回 (NODATA)。

**Note**

ST_Intersects(geometry, raster) 和 ST_Intersects(raster, geometry) 是等效的。

PostGIS: 2.0.0 版本引入/首次引入。

**Warning**

PostGIS: 2.1.0 版本引入 ST_Intersects(geometry, raster) 和 ST_Intersects(raster, geometry) 是等效的。

SQL

```
-- different bands of same raster
SELECT ST_Intersects(rast, 2, rast, 3) FROM dummy_rast WHERE rid = 2;

st_intersects
-----
t
```

SQL

[ST_Intersection](#), [ST_Disjoint](#)

11.17.7 ST_Overlaps

ST_Overlaps — 检查 rasterA 是否与 rasterB 在指定波段上重叠。

Synopsis

```
boolean ST_Overlaps( raster rastA , integer nbandA , raster rastB , integer nbandB );
boolean ST_Overlaps( raster rastA , raster rastB );
```

SQL

检查 rasterA 是否与 rasterB 在指定波段上重叠。如果 rasterA 与 rasterB 在指定波段上重叠，则返回 true，否则返回 false。如果任一输入为 NULL，则返回 NULL。如果任一输入为 NODATA，则返回 false。

**Note**

ST_Overlaps(geometry, raster) 和 ST_Overlaps(raster, geometry) 是等效的。

**Note**

ST_Overlaps(ST_Polygon(raster), geometry) 返回 TRUE 当且仅当 ST_Polygon 与 geometry 重叠。

2.1.0 版本引入。

SQL

```
-- comparing different bands of same raster
SELECT ST_Overlaps(rast, 1, rast, 2) FROM dummy_rast WHERE rid = 2;

st_overlaps
-----
f
```

SQL

ST_Intersects

11.17.8 ST_Touches

ST_Touches — 返回 TRUE 当且仅当 rastA 与 rastB 在边界上接触，但不重叠。

Synopsis

boolean **ST_Touches**(raster rastA , integer nbandA , raster rastB , integer nbandB);
boolean **ST_Touches**(raster rastA , raster rastB);

SQL

ST_Touches(rastA, nbandA, rastB, nbandB) 返回 TRUE 当且仅当 rastA 与 rastB 在边界上接触，但不重叠。如果任一输入为 NULL，则返回 NULL。如果任一输入为 NO_DATA，则返回 FALSE。

**Note**

ST_Touches 与 ST_Overlaps 类似，但 ST_Touches 只检查边界接触。

**Note**

ST_Touches(ST_Polygon(raster), geometry) 返回 TRUE 当且仅当 ST_Polygon 与 geometry 在边界上接触。

2.1.0 版本引入。


```
SELECT ST_SameAlignment(A.rast,b.rast)
FROM dummy_rast AS A CROSS JOIN dummy_rast AS B;

NOTICE: The two rasters provided have different SRIDs
NOTICE: The two rasters provided have different SRIDs
st_samealignment
-----
t
f
f
f
```

¶¶

Section [10.1](#), [ST_NotSameAlignmentReason](#), [ST_MakeEmptyRaster](#)

11.17.10 ST_NotSameAlignmentReason

`ST_NotSameAlignmentReason` — 检查两个栅格是否对齐，并返回不匹配的原因

Synopsis

text `ST_NotSameAlignmentReason`(raster rastA, raster rastB);

¶¶

返回一个文本字符串，描述两个栅格不匹配的原因。



Note

如果两个栅格的 `SRID` 不同，`ST_SameAlignment` 将返回 `f`。在这种情况下，`ST_NotSameAlignmentReason` 将返回 `SRID mismatch`。

2.1.0 版本引入。

¶¶

```
SELECT
  ST_SameAlignment(
    ST_MakeEmptyRaster(1, 1, 0, 0, 1, 1, 0, 0),
    ST_MakeEmptyRaster(1, 1, 0, 0, 1.1, 1.1, 0, 0)
  ),
  ST_NotSameAlignmentReason(
    ST_MakeEmptyRaster(1, 1, 0, 0, 1, 1, 0, 0),
    ST_MakeEmptyRaster(1, 1, 0, 0, 1.1, 1.1, 0, 0)
  )
;

st_samealignment | st_otsamealignmentreason
-----+-----
f                | The rasters have different scales on the X axis
(1 row)
```

图

Section 10.1, [ST_SameAlignment](#)

11.17.11 ST_Within

ST_Within — 检查 rastB 是否完全包含在 rastA 中，检查 rastA 是否完全包含在 rastB 中。

Synopsis

boolean **ST_Within**(raster rastA , integer nbandA , raster rastB , integer nbandB);
boolean **ST_Within**(raster rastA , raster rastB);

图

检查 rastB 是否完全包含在 rastA 中，检查 rastA 是否完全包含在 rastB 中。如果 rastA 或 rastB 包含 NULL 值，则返回 NULL。如果 rastA 或 rastB 包含 (NODATA 值) 则返回 FALSE。



Note
检查 (operand) 是否完全包含在另一个检查中。



Note
检查 ST_Within(ST_Polygon(raster), geometry) 是否 ST_Within(geometry, ST_Polygon(raster)) 是否 ST_Polygon 是否完全包含在检查中。



Note
ST_Within() 与 ST_Contains() 相反。检查 ST_Within(rastA, rastB) 是否 ST_Contains(rastB, rastA) 是否完全包含在检查中。

2.1.0 版本中。

图

```
SELECT r1.rid, r2.rid, ST_Within(r1.rast, 1, r2.rast, 1) FROM dummy_rast r1 CROSS JOIN dummy_rast r2 WHERE r1.rid = 2;

rid | rid | st_within
-----+-----+-----
 2  |  1  |    f
 2  |  2  |    t
```

函数

[ST_Intersects](#), [ST_Contains](#), [ST_DWithin](#), [ST_DFullyWithin](#)

11.17.12 ST_DWithin

`ST_DWithin` — 检查 rasterA 是否与 rasterB 在指定距离内相交。

Synopsis

```
boolean ST_DWithin( raster rastA , integer nbandA , raster rastB , integer nbandB , double precision
distance_of_srid );
boolean ST_DWithin( raster rastA , raster rastB , double precision distance_of_srid );
```

函数

检查 rasterA 是否与 rasterB 在指定距离内相交。如果任一输入为 NULL，则返回 NULL。如果任一输入为 NODATA，则返回 NODATA。

距离以 SRID 为单位指定。如果 SRID 未指定，则默认为 4326。



Note

距离 (operand) 必须是非负数。



Note

`ST_DWithin(ST_Polygon(raster), geometry)` 与 `ST_DWithin(ST_Polygon(raster), geometry)` 等效。

2.1.0 版本引入。

函数

```
SELECT r1.rid, r2.rid, ST_DWithin(r1.rast, 1, r2.rast, 1, 3.14) FROM dummy_rast r1 CROSS
JOIN dummy_rast r2 WHERE r1.rid = 2;
```

rid	rid	st_dwithin
2	1	f
2	2	t

函数

[ST_Within](#), [ST_DFullyWithin](#)

11.17.13 ST_DFullyWithin

ST_DFullyWithin — 是否 rasterA 完全在 rasterB 内部。

Synopsis

```
boolean ST_DFullyWithin( raster rastA , integer nbandA , raster rastB , integer nbandB , double
precision distance_of_srid );
boolean ST_DFullyWithin( raster rastA , raster rastB , double precision distance_of_srid );
```

参数

rastA rasterB 是栅格。如果任一参数为 NULL，则返回 NULL。如果任一参数为 NODATA，则返回 NODATA。

distance_of_srid 是距离。如果任一参数为 NULL，则返回 NULL。如果任一参数为 NODATA，则返回 NODATA。



Note

如果任一参数为 NULL，则返回 NULL。



Note

ST_DFullyWithin(ST_Polygon(raster), geometry) 与 ST_Polygon 相同。

2.1.0 版本。

示例

```
SELECT r1.rid, r2.rid, ST_DFullyWithin(r1.rast, 1, r2.rast, 1, 3.14) FROM dummy_rast r1
CROSS JOIN dummy_rast r2 WHERE r1.rid = 2;
```

rid	rid	st_dfullywithin
2	1	f
2	2	t

相关链接

[ST_Within](#), [ST_DWithin](#)

11.18 Raster Tips

11.18.1 Out-DB Rasters

11.18.1.1 Directory containing many files

When GDAL opens a file, GDAL eagerly scans the directory of that file to build a catalog of other files. If this directory contains many files (e.g. thousands, millions), opening that file becomes extremely slow (especially if that file happens to be on a network drive such as NFS).

To control this behavior, GDAL provides the following environment variable: `GDAL_DISABLE_READDIR_ON_OPEN`. Set `GDAL_DISABLE_READDIR_ON_OPEN` to `TRUE` to disable directory scanning.

In Ubuntu (and assuming you are using PostgreSQL's packages for Ubuntu), `GDAL_DISABLE_READDIR_ON_OPEN` can be set in `/etc/postgresql/POSTGRESQL_VERSION/CLUSTER_NAME/environment` (where `POSTGRESQL_VERSION` is the version of PostgreSQL, e.g. 9.6 and `CLUSTER_NAME` is the name of the cluster, e.g. maindb). You can also set PostGIS environment variables here as well.

```
# environment variables for postmaster process
# This file has the same syntax as postgresql.conf:
# VARIABLE = simple_value
# VARIABLE2 = 'any value!'
# I. e. you need to enclose any value which does not only consist of letters,
# numbers, and '-', '_', '.' in single quotes. Shell commands are not
# evaluated.
POSTGIS_GDAL_ENABLED_DRIVERS = 'ENABLE_ALL'

POSTGIS_ENABLE_OUTDB_RASTERS = 1

GDAL_DISABLE_READDIR_ON_OPEN = 'TRUE'
```

11.18.1.2 Maximum Number of Open Files

The maximum number of open files permitted by Linux and PostgreSQL are typically conservative (typically 1024 open files per process) given the assumption that the system is consumed by human users. For Out-DB Rasters, a single valid query can easily exceed this limit (e.g. a dataset of 10 year's worth of rasters with one raster for each day containing minimum and maximum temperatures and we want to know the absolute min and max value for a pixel in that dataset).

The easiest change to make is the following PostgreSQL setting: `max_files_per_process`. The default is set to 1000, which is far too low for Out-DB Rasters. A safe starting value could be 65536 but this really depends on your datasets and the queries run against those datasets. This setting can only be made on server start and probably only in the PostgreSQL configuration file (e.g. `/etc/postgresql/POSTGRESQL_VERSION/CLUSTER_NAME/postgresql.conf` in Ubuntu environments).

```
...
# - Kernel Resource Usage -

max_files_per_process = 65536          # min 25
                                         # (change requires restart)
...
```

The major change to make is the Linux kernel's open files limits. There are two parts to this:

- Maximum number of open files for the entire system
- Maximum number of open files per process

11.18.1.2.1 Maximum number of open files for the entire system

You can inspect the current maximum number of open files for the entire system with the following example:

```
$ sysctl -a | grep fs.file-max
fs.file-max = 131072
```

If the value returned is not large enough, add a file to `/etc/sysctl.d/` as per the following example:

```
$ echo "fs.file-max = 6145324" >> /etc/sysctl.d/fs.conf
```

```
$ cat /etc/sysctl.d/fs.conf
fs.file-max = 6145324
```

```
$ sysctl -p --system
* Applying /etc/sysctl.d/fs.conf ...
fs.file-max = 2097152
* Applying /etc/sysctl.conf ...
```

```
$ sysctl -a | grep fs.file-max
fs.file-max = 6145324
```

11.18.1.2.2 Maximum number of open files per process

We need to increase the maximum number of open files per process for the PostgreSQL server processes.

To see what the current PostgreSQL service processes are using for maximum number of open files, do as per the following example (make sure to have PostgreSQL running):

```
$ ps aux | grep postgres
postgres 31713  0.0  0.4 179012 17564 pts/0    S   Dec26   0:03 /home/dustymugs/devel/ ↵
    postgresql/sandbox/10/usr/local/bin/postgres -D /home/dustymugs/devel/postgresql/sandbox ↵
    /10/pgdata
postgres 31716  0.0  0.8 179776 33632 ?        Ss  Dec26   0:01 postgres: checkpointer ↵
    process
postgres 31717  0.0  0.2 179144  9416 ?        Ss  Dec26   0:05 postgres: writer process
postgres 31718  0.0  0.2 179012  8708 ?        Ss  Dec26   0:06 postgres: wal writer ↵
    process
postgres 31719  0.0  0.1 179568  7252 ?        Ss  Dec26   0:03 postgres: autovacuum ↵
    launcher process
postgres 31720  0.0  0.1  34228  4124 ?        Ss  Dec26   0:09 postgres: stats collector ↵
    process
postgres 31721  0.0  0.1 179308  6052 ?        Ss  Dec26   0:00 postgres: bgworker: ↵
    logical replication launcher
```

```
$ cat /proc/31718/limits
Limit                Soft Limit            Hard Limit             Units
Max cpu time          unlimited             unlimited              seconds
Max file size          unlimited             unlimited              bytes
Max data size          unlimited             unlimited              bytes
Max stack size        8388608              unlimited              bytes
Max core file size     0                    unlimited              bytes
Max resident set       unlimited             unlimited              bytes
Max processes         15738                15738                  processes
Max open files       1024                4096                  files
Max locked memory     65536                65536                  bytes
Max address space     unlimited             unlimited              bytes
Max file locks         unlimited             unlimited              locks
Max pending signals    15738                15738                  signals
```

Max msgqueue size	819200	819200	bytes
Max nice priority	0	0	
Max realtime priority	0	0	
Max realtime timeout	unlimited	unlimited	us

In the example above, we inspected the open files limit for Process 31718. It doesn't matter which PostgreSQL process, any of them will do. The response we are interested in is *Max open files*.

We want to increase *Soft Limit* and *Hard Limit* of *Max open files* to be greater than the value we specified for the PostgreSQL setting `max_files_per_process`. In our example, we set `max_files_per_process` to 65536.

In Ubuntu (and assuming you are using PostgreSQL's packages for Ubuntu), the easiest way to change the *Soft Limit* and *Hard Limit* is to edit `/etc/init.d/postgresql` (SysV) or `/lib/systemd/system/postgresql*.service` (systemd).

Let's first address the SysV Ubuntu case where we add **`ulimit -H -n 262144`** and **`ulimit -n 131072`** to `/etc/init.d/postgresql`.

```
...
case "$1" in
  start|stop|restart|reload)
    if [ "$1" = "start" ]; then
      create_socket_directory
    fi
    if [ -z "`pg_lsclusters -h`" ]; then
      log_warning_msg 'No PostgreSQL clusters exist; see "man pg_createcluster"'
      exit 0
    fi

    ulimit -H -n 262144
    ulimit -n 131072

    for v in $versions; do
      $1 $v || EXIT=$?
    done
    exit ${EXIT:-0}
    ;;
  status)
  ...
```

Now to address the systemd Ubuntu case. We will add **`LimitNOFILE=131072`** to every `/lib/systemd/system/postgresql*.service` file in the **[Service]** section.

```
...
[Service]

LimitNOFILE=131072

...

[Install]
WantedBy=multi-user.target
...
```

After making the necessary systemd changes, make sure to reload the daemon

```
systemctl daemon-reload
```


Chapter 12

PostGIS Extras

This chapter documents features found in the extras folder of the PostGIS source tarballs and source repository. These are not always packaged with PostGIS binary releases, but are usually PL/pgSQL based or standard shell scripts that can be run as is.

12.1 地址标准化工具

地址标准化工具 **PAGC standardizer** 是一个 (fork) 版本 (源自 PostgreSQL 的 **PAGC PostgreSQL 扩展** 项目)。

该工具依赖于 **lexicon; lex** 和 **gazetteer; gaz** 两个数据库扩展。

```
CREATE EXTENSION address_standardizer;
-- 安装 address_standardizer 扩展
PostgreSQL 数据库。 address_standardizer 扩展，
address_standardizer_data_us 扩展，
-- 安装 address_standardizer_data_us 扩展。 CREATE EXTENSION address_standardizer_data_us;
-- 安装 address_standardizer_data_us 扩展。
```

PostGIS extensions/address_standardizer 扩展，安装后，

请参考 Section 2.3 安装与使用。

12.1.1 地址标准化工具

该工具依赖于 **lexicon; lex** 和 **gazetteer; gaz** 两个数据库扩展。该工具依赖于 **lexicon; lex** 和 **gazetteer; gaz** 两个数据库扩展。

该工具依赖于 **lexicon; lex** 和 **gazetteer; gaz** 两个数据库扩展。

lexicon; lex (zip code) 是一个 (Perl) 脚本，用于解析地址。该脚本依赖于 **parseaddress-api.c** 文件，该文件位于 **PostGIS** 的 **extras** 文件夹中。

gazetteer; gaz (Perl) 脚本，用于解析地址。该脚本依赖于 **parseaddress-api.c** 文件，该文件位于 **PostGIS** 的 **extras** 文件夹中。

12.1.2 地址标准化工具

12.1.2.1 stdaddr

stdaddr — 使用 `standardize_address` 函数对地址进行标准化。

语法

`standardize_address` 函数用于对地址进行标准化。PAGC Postal Attributes 表用于存储地址信息。

rules table 用于存储地址规则。



This method needs address_standardizer extension.

building 字段 (索引 0) 类型: 文本。存储建筑物的名称。

house_num 字段 (索引 1) 类型: 文本。例如: 75 State Street 75

predir 字段 (索引 2) 类型: North, South, East, West 等 (STREET NAME PRE-DIRECTIONAL) 文本。

qual 字段 (索引 3) 类型: 文本 (STREET NAME PRE-MODIFIER) 文本。例如: 3715 OLD HIGHWAY 99 中的 OLD

pretype 字段 (索引 4) 类型: 文本 (STREET PREFIX TYPE) 文本。

name 字段 (索引 5) 类型: 文本 (STREET NAME) 文本。

suftype 字段 (索引 6) 类型: St, Ave, Cir 等 (STREET POST TYPE) 文本。例如: 75 State Street 中的 STREET

sufdir 字段 (索引 7) 类型: 文本 (STREET POST-DIRECTIONAL) 文本。例如: 3715 TENTH AVENUE WEST 中的 WEST

ruralroute 是文本 (索引 8): RURAL ROUTE . Example 7 in RR 7.

extra 字段: 文本。

city 字段 (索引 10) 类型: 文本。

state 字段 (索引 11) 类型: 文本。

country 字段 (索引 12) 类型: 文本: USA

postcode 字段 (索引 13) 类型: 文本 (postal code, zip code) 文本: 02109

box 字段 (索引 14, 15) 类型: 文本 (POSTAL BOX NUMBER) 文本: 02109

unit 字段 (索引 17) 类型: 文本: APT 3B 中的 3B

12.1.3 地址规则表

12.1.3.1 rules table

rules table — 存储地址规则的表。该表包含用于解析地址的规则。例如: -1(终止符), -1, 等。

。

。。

id 。

rule 。

。。

。。

stdaddr。

。

。

。

AMPERS (13)。。

DASH (9)。。

DOUBLE (21)。。

FRACT (25)。。

MIXED (23)。。

NUMBER (0)。。

ORD (15)。。

ORD (18)。。

WORD (1)。。

。

BOXH (14)。。

BUILDH (19)。。

BUILDT 。

DIRECT (22)。。

MILE (20)。。

ROAD (6)。。

RR (8)。。

predir ☐☐☐ (☐☐☐☐ 2) ☐☐☐: North, South, East, West ☐☐☐☐☐☐☐☐☐☐☐☐☐☐☐☐☐☐ (STREET NAME PRE-DIRECTIONAL) ☐☐☐.

qual (3) : (STREET NAME PRE-MODIFIER) . : 3715
OLD HIGHWAY 99 *OLD*

```
pretype 000 (0000 4) 000: 00000000 (STREET PREFIX TYPE) 000.
```

street [REDACTED] ([REDACTED] 5) [REDACTED]: [REDACTED] (STREET NAME) [REDACTED].

suftype XXX (XXXX 6) XXX: St, Ave, Cir XXXXXXXXXX (STREET POST TYPE) XXX. XXX
XXXXXXXXXXXXXXXXXXXX. X: 75 State Street XX *STREET*

su **dir** (7) (STREET POST-DIRECTIONAL) . 3715 TENTH AVENUE WEST *WEST*

ARC_C

(HOUSE = "2"). HOUSE MICRO MICRO. HOUSE MICRO C MICRO C.

CIVIC_C

[illegible]**EXTRA_C**

(□□□□ = "4"). EXTRA □□ - □□□□□□□□□□ - □□□□□□□□□□□□□□. □□□□□□□□□□□□□□□□□□□□.

EXTRA_C output tokens (excerpted from <http://www.pagcgeo.org/docs/html/pagc-12.html#--r-typ-->.

BLDNG (XXXX 0): XXXXXXXXXXXXXXXXXXXXXXXX.

BOXH (token number 14): The **BOX** in B0X 3B

B0XT (☒☒☒☒ 15): B0X 3B ☒☒ **3B**

RR ($\square\square\square\square$ 8): **RR** 7 $\square\square$ **RR**

UNITH (16): APT 3B APT

UNITT (XXXX 17): APT 3B XX 3B

UNKNOWN (□□□□ 9): □□□□□□□□□□□□□□.

12.1.3.2 lex table

lex table — $\mathbb{Z}^n$ (lex) $\mathbb{Z}^n$, $\mathbb{Z}^n$ (1) $\mathbb{Z}^n$ (the section called “ $\mathbb{Z}^n$ ”) $\mathbb{Z}^n$ (2) $\mathbb{Z}^n$.

lexicon (lexicon) (lexicon), (1) (the section called “ ”) (2) . , ONE stdword 1

[illegible]

id ☒☒☒☒☒☒☒

seq 国国: 国国国?

word 国国: 国国国

stdword 国国: 国国国国国国

token 国国: 国国国国国国国国. 国国国国国国国国国国国国国国国国. **PAGC Tokens** 国国国国国.

12.1.3.3 gaz table

gaz table — 国国国 (gaz) 国国国国国国国国国, 国国国 (1) 国国国 (the section called “国国国” 国) 国 (2) 国国国国国国国国国国国国国国国国.

国国

A gaz (short for gazeteer) table is used to standardize place names and associate that input with the section called “国国国国” and (b) standardized representations. For example if you are in US, you may load these with State Names and associated abbreviations.

国国国国国国国国国国国国国国国国国国国国国国. 国国国国国国国国国国国国国国国国国国国国国国.

id 国国国国国

seq 国国: 国国国? - 国国国国国国国国国国国国国国

word 国国: 国国国

stdword 国国: 国国国国国国

token 国国: 国国国国国国国国. 国国国国国国国国国国国国国国国国国国国国国. **PAGC Tokens** 国国国国国.

12.1.4 国国国国国国国

12.1.4.1 debug_standardize_address

debug_standardize_address — Returns a json formatted text listing the parse tokens and standardizations

Synopsis

text **debug_standardize_address**(text lextab, text gaztab, text rultab, text micro, text macro=NULL);

国国

This is a function for debugging address standardizer rules and lex/gaz mappings. It returns a json formatted text that includes the matching rules, mapping of tokens, and best standardized address **stdaddr** form of an input address utilizing **lex table** table name, **gaz table**, and **rules table** table names and an address.

For single line addresses use just micro

For two line address A micro consisting of standard first line of postal address e.g. house_num street, and a macro consisting of standard postal second line of an address e.g city, state postal_code country.

Elements returned in the json document are

input_tokens For each word in the input address, returns the position of the word, token categorization of the word, and the standard word it is mapped to. Note that for some input words, you might get back multiple records because some inputs can be categorized as more than one thing.

rules The set of rules matching the input and the corresponding score for each. The first rule (highest scoring) is what is used for standardization

stdaddr The standardized address elements **stdaddr** that would be returned when running **standardize_address**

Availability: 3.4.0

 This method needs address_standardizer extension.

❌❌

address_standardizer_data_us 地理数据库

```
CREATE EXTENSION address_standardizer_data_us; -- only needs to be done once
```

Variant 1: Single line address and returning the input tokens

```
SELECT it->'pos' AS position, it->'word' AS word, it->'stdword' AS standardized_word,
       it->'token' AS token, it->'token-code' AS token_code
FROM jsonb(
    debug_standardize_address('us_lex',
                              'us_gaz', 'us_rules', 'One Devonshire Place, PH 301, Boston, MA 02109')
    ) AS s, jsonb_array_elements(s->'input_tokens') AS it;
```

position	word	standardized_word	token	token_code
0	ONE	1	NUMBER	0
0	ONE	1	WORD	1
1	DEVONSHIRE	DEVONSHIRE	WORD	1
2	PLACE	PLACE	TYPE	2
3	PH	PATH	TYPE	2
3	PH	PENTHOUSE	UNITT	17
4	301	301	NUMBER	0

(7 rows)

Variant 2: Multi line address and returning first rule input mappings and score

```
SELECT (s->'rules'->0->'score')::numeric AS score, it->'pos' AS position,
       it->'input-word' AS word, it->'input-token' AS input_token, it->'mapped-word' AS ↵
       standardized_word,
       it->'output-token' AS output_token
FROM jsonb(
    debug_standardize_address('us_lex',
                              'us_gaz', 'us_rules', 'One Devonshire Place, PH 301', 'Boston, MA 02109')
    ) AS s, jsonb_array_elements(s->'rules'->0->'rule_tokens') AS it;
```

score	position	word	input_token	standardized_word	output_token
0.876250	0	ONE	NUMBER	1	HOUSE
0.876250	1	DEVONSHIRE	WORD	DEVONSHIRE	STREET
0.876250	2	PLACE	TYPE	PLACE	SUFTYP
0.876250	3	PH	UNITT	PENTHOUSE	UNITT
0.876250	4	301	NUMBER	301	UNITT

(5 rows)

安装

`stdaddr`, `rules table`, `lex table`, `gaz table`, `Page_Normalize_Address`

12.1.4.2 parse_address

`parse_address` — 解析地址并返回记录。

Synopsis

record `parse_address`(text address);

安装

Returns takes an address as input, and returns a record output consisting of fields *num*, *street*, *street2*, *address1*, *city*, *state*, *zip*, *zipplus*, *country*.

2.2.0 安装与使用。

 This method needs `address_standardizer` extension.

安装

安装与使用

```
SELECT num, street, city, zip, zipplus
       FROM parse_address('1 Devonshire Place, Boston, MA 02109-1234') AS a;
```

num	street	city	zip	zipplus
1	Devonshire Place	Boston	02109	1234

安装与使用

```
-- basic table
CREATE TABLE places(addid serial PRIMARY KEY, address text);

INSERT INTO places(address)
VALUES ('529 Main Street, Boston MA, 02129'),
       ('77 Massachusetts Avenue, Cambridge, MA 02139'),
       ('25 Wizard of Oz, Walaford, KS 99912323'),
       ('26 Capen Street, Medford, MA'),
       ('124 Mount Auburn St, Cambridge, Massachusetts 02138'),
       ('950 Main Street, Worcester, MA 01610');

-- parse the addresses
-- if you want all fields you can use (a).*
SELECT addid, (a).num, (a).street, (a).city, (a).state, (a).zip, (a).zipplus
FROM (SELECT addid, parse_address(address) As a
      FROM places) AS p;
```

addid	num	street	city	state	zip	zipplus
1	529	Main Street	Boston	MA	02129	
2	77	Massachusetts Avenue	Cambridge	MA	02139	
3	25	Wizard of Oz	Walaford	KS	99912	323

4	26	Capen Street	Medford	MA		
5	124	Mount Auburn St	Cambridge	MA	02138	
6	950	Main Street	Worcester	MA	01610	

(6 rows)

❌

12.1.4.3 standardize_address

standardize_address — 将地址标准化为美国标准地址格式。

Synopsis

stdaddr standardize_address(text lextab, text gaztab, text rultab, text address);
stdaddr standardize_address(text lextab, text gaztab, text rultab, text micro, text macro);

❌

lex table, gaz table, rules table 是标准地址格式化的规则表，stdaddr 是标准地址格式化的函数。

❌ 1: 标准地址格式化的规则表。

❌ 2: 标准地址格式化的规则表。house_num street 是标准地址格式化的规则表，micro 是标准地址格式化的规则表，city, state postal_code country 是标准地址格式化的规则表，macro 是标准地址格式化的规则表。

2.2.0 标准地址格式化的规则表。

✅ This method needs address_standardizer extension.

❌

address_standardizer_data_us 是标准地址格式化的规则表。

CREATE EXTENSION address_standardizer_data_us; -- only needs to be done once

❌ 1: 标准地址格式化的规则表。标准地址格式化的规则表。

```
SELECT house_num, name, suftype, city, country, state, unit FROM standardize_address(' ←  
us_lex',  
                                     'us_gaz', 'us_rules', 'One Devonshire Place, PH 301, Boston, MA ←  
02109');
```

house_num	name	suftype	city	country	state	unit
1	DEVONSHIRE	PLACE	BOSTON	USA	MASSACHUSETTS	# PENTHOUSE 301

TIGER 是标准地址格式化的规则表 (是标准地址格式化的规则表 postgis_tiger_geocoder 是标准地址格式化的规则表)。

```
SELECT * FROM standardize_address('tiger.pgc_lex',  
    'tiger.pgc_gaz', 'tiger.pgc_rules', 'One Devonshire Place, PH 301, Boston, MA ←  
02109-1234');
```

标准地址格式化的规则表 hstore 是标准地址格式化的规则表。❌ CREATE EXTENSION hstore; 标准地址格式化的规则表。

```
SELECT (each(hstore(p))).*
FROM standardize_address('tiger.pagc_lex', 'tiger.pagc_gaz',
    'tiger.pagc_rules', 'One Devonshire Place, PH 301, Boston, MA 02109') As p;
```

key	value
box	
city	BOSTON
name	DEVONSHIRE
qual	
unit	# PENTHOUSE 301
extra	
state	MA
predir	
sufdir	
country	USA
pretype	
suftype	PL
building	
postcode	02109
house_num	1
ruralroute	
(16 rows)	

例 2: 使用国家代码。

```
SELECT (each(hstore(p))).*
FROM standardize_address('tiger.pagc_lex', 'tiger.pagc_gaz',
    'tiger.pagc_rules', 'One Devonshire Place, PH 301', 'Boston, MA 02109, US') As p;
```

key	value
box	
city	BOSTON
name	DEVONSHIRE
qual	
unit	# PENTHOUSE 301
extra	
state	MA
predir	
sufdir	
country	USA
pretype	
suftype	PL
building	
postcode	02109
house_num	1
ruralroute	
(16 rows)	

例

[stdaddr](#), [rules table](#), [lex table](#), [gaz table](#), [Pagc_Normalize_Address](#)

12.2 TIGER 数据安装

TIGER 数据是 OpenStreetMap 数据的衍生数据，PostGIS 提供了将 OpenStreetMap 数据转换为 TIGER 数据的工具。

- **Nominatim** 是 OpenStreetMap 数据的衍生数据。它提供了 `osm2pgsql` 工具，可以将 OpenStreetMap 数据转换为 PostgreSQL 8.4 或 PostgreSQL 9.0 的 TIGER 数据。Nominatim 提供了 TIGER 数据的 SQL 查询接口，可以用于查询 TIGER 数据。
- **GIS Graphy** 是 PostGIS 的 Nominatim 接口。OSM (OpenStreetMap) 数据可以通过 Nominatim 接口转换为 TIGER 数据。Nominatim 接口支持 Java 1.5, Servlet apps, Solr 等接口。GIS Graphy 是一个基于 Nominatim 的 TIGER 数据接口。

12.2.1 Drop_Indexes_Generate_Script

`Drop_Indexes_Generate_Script` — TIGER 数据安装脚本。该脚本用于安装 TIGER 数据。该脚本位于 `tiger_data` 目录下。

Synopsis

text **Drop_Indexes_Generate_Script**(text param_schema=tiger_data);

返回

TIGER 数据安装脚本。该脚本用于安装 TIGER 数据。该脚本位于 `tiger_data` 目录下。

该脚本位于 `tiger_data` 目录下。该脚本用于安装 TIGER 数据。该脚本位于 `tiger_data` 目录下。

2.0.0 版本。

返回

```
SELECT drop_indexes_generate_script() As actionsql;
actionsql
```

```
-----
DROP INDEX tiger.idx_tiger_countysub_lookup_lower_name;
DROP INDEX tiger.idx_tiger_edges_countyfp;
DROP INDEX tiger.idx_tiger_faces_countyfp;
DROP INDEX tiger.tiger_place_the_geom_gist;
DROP INDEX tiger.tiger_edges_the_geom_gist;
DROP INDEX tiger.tiger_state_the_geom_gist;
DROP INDEX tiger.idx_tiger_addr_least_address;
DROP INDEX tiger.idx_tiger_addr_tlid;
DROP INDEX tiger.idx_tiger_addr_zip;
DROP INDEX tiger.idx_tiger_county_countyfp;
DROP INDEX tiger.idx_tiger_county_lookup_lower_name;
DROP INDEX tiger.idx_tiger_county_lookup_snd_name;
DROP INDEX tiger.idx_tiger_county_lower_name;
```

```

DROP INDEX tiger.idx_tiger_county_snd_name;
DROP INDEX tiger.idx_tiger_county_the_geom_gist;
DROP INDEX tiger.idx_tiger_countysub_lookup_snd_name;
DROP INDEX tiger.idx_tiger_cousub_countyfp;
DROP INDEX tiger.idx_tiger_cousub_cousubfp;
DROP INDEX tiger.idx_tiger_cousub_lower_name;
DROP INDEX tiger.idx_tiger_cousub_snd_name;
DROP INDEX tiger.idx_tiger_cousub_the_geom_gist;
DROP INDEX tiger_data.idx_tiger_data_ma_addr_least_address;
DROP INDEX tiger_data.idx_tiger_data_ma_addr_tlid;
DROP INDEX tiger_data.idx_tiger_data_ma_addr_zip;
DROP INDEX tiger_data.idx_tiger_data_ma_county_countyfp;
DROP INDEX tiger_data.idx_tiger_data_ma_county_lookup_lower_name;
DROP INDEX tiger_data.idx_tiger_data_ma_county_lookup_snd_name;
DROP INDEX tiger_data.idx_tiger_data_ma_county_lower_name;
DROP INDEX tiger_data.idx_tiger_data_ma_county_snd_name;
:
:

```

❏❏

[Install_Missing_Indexes, Missing_Indexes_Generate_Script](#)

12.2.2 Drop_Nation_Tables_Generate_Script

Drop_Nation_Tables_Generate_Script — 删除 county_all, state_all 表并生成 tiger_2010 和 tiger_2011 表的加载脚本。

Synopsis

text **Drop_Nation_Tables_Generate_Script**(text param_schema=tiger_data);

❏❏

删除 county_all, state_all 表并生成 tiger_2010 和 tiger_2011 表的加载脚本。

2.1.0 版本新增。

❏❏

```

SELECT drop_nation_tables_generate_script();
DROP TABLE tiger_data.county_all;
DROP TABLE tiger_data.county_all_lookup;
DROP TABLE tiger_data.state_all;
DROP TABLE tiger_data.ma_county;
DROP TABLE tiger_data.ma_state;

```

❏❏

[Loader_Generate_Nation_Script](#)

12.2.3 Drop_State_Tables_Generate_Script

`Drop_State_Tables_Generate_Script` — 删除 (州) 的 Tiger 数据表并生成脚本。该脚本将删除 `tiger_data` 数据库中的所有表。

Synopsis

text **Drop_State_Tables_Generate_Script**(text param_state, text param_schema=tiger_data);

返回

删除 (州) 的 Tiger 数据表并生成脚本。该脚本将删除 `tiger_data` 数据库中的所有表。该脚本将生成一个 SQL 脚本，该脚本将删除 (州) 的 Tiger 数据表并生成脚本。

2.0.0 版本引入。

示例

```
SELECT drop_state_tables_generate_script('PA');
DROP TABLE tiger_data.pa_addr;
DROP TABLE tiger_data.pa_county;
DROP TABLE tiger_data.pa_county_lookup;
DROP TABLE tiger_data.pa_cousub;
DROP TABLE tiger_data.pa_edges;
DROP TABLE tiger_data.pa_faces;
DROP TABLE tiger_data.pa_featnames;
DROP TABLE tiger_data.pa_place;
DROP TABLE tiger_data.pa_state;
DROP TABLE tiger_data.pa_zip_lookup_base;
DROP TABLE tiger_data.pa_zip_state;
DROP TABLE tiger_data.pa_zip_state_loc;
```

示例

[Loader_Generate_Script](#)

12.2.4 Geocode

`Geocode` — 将地址 (字符串) 转换为 NAD83 几何点，并返回地址的规范化和评级。该函数将地址规范化为有效的地址，并返回地址的评级。该函数将地址规范化为有效的地址，并返回地址的评级。该函数将地址规范化为有效的地址，并返回地址的评级。

Synopsis

setof record **geocode**(varchar address, integer max_results=10, geometry restrict_region=NULL, norm_addy OUT addy, geometry OUT geomout, integer OUT rating);
 setof record **geocode**(norm_addy in_addy, integer max_results=10, geometry restrict_region=NULL, norm_addy OUT addy, geometry OUT geomout, integer OUT rating);

安装

PostGIS (PostgreSQL) 使用 NAD83 坐标系，使用 normalized_address (addy) 函数返回地址的规范化表示。TIGER 数据 (edge, face, addr), PostgreSQL 索引 (soundex, levenshtein), 以及 PostGIS 函数 (TIGER 函数) 用于地址匹配。TIGER 数据 (edge, face, addr) 用于地址匹配。TIGER 数据 (edge, face, addr) 用于地址匹配。TIGER 数据 (edge, face, addr) 用于地址匹配。

PostGIS: 2.0.0 使用 TIGER 2010 数据，使用 normalized_address (addy) 函数返回地址的规范化表示。TIGER 数据 (edge, face, addr) 用于地址匹配。TIGER 数据 (edge, face, addr) 用于地址匹配。TIGER 数据 (edge, face, addr) 用于地址匹配。

安装

PostGIS (MA), PostGIS (MN), PostGIS (CA), PostGIS (RI) 使用 TIGER 数据 PostgreSQL 9.1rc1/PostGIS 2.0 使用 TIGER 2010 数据 3.0 GHz 处理器 2GB 内存 7 天安装时间。

PostGIS (61 天)。

```
SELECT g.rating, ST_X(g.geomout) As lon, ST_Y(g.geomout) As lat,
       (addy).address As stno, (addy).streetname As street,
       (addy).streettypeabbrev As styp, (addy).location As city, (addy).stateabbrev As st,( ←
       addy).zip
FROM geocode('75 State Street, Boston MA 02109', 1) As g;
rating |          lon          |          lat          | stno | street | styp | city | st | zip
-----+-----+-----+-----+-----+-----+-----+-----+-----
0 | -71.0557505845646 | 42.35897920691 | 75 | State | St | Boston | MA | 02109
```

PostGIS (122 ~ 150 天)。

```
SELECT g.rating, ST_AsText(ST_SnapToGrid(g.geomout,0.00001)) As wktlonlat,
       (addy).address As stno, (addy).streetname As street,
       (addy).streettypeabbrev As styp, (addy).location As city, (addy).stateabbrev As st,( ←
       addy).zip
FROM geocode('226 Hanover Street, Boston, MA',1) As g;
rating |          wktlonlat          | stno | street | styp | city | st | zip
-----+-----+-----+-----+-----+-----+-----+-----
1 | POINT(-71.05528 42.36316) | 226 | Hanover | St | Boston | MA | 02113
```

PostGIS (500 天)。

```
SELECT g.rating, ST_AsText(ST_SnapToGrid(g.geomout,0.00001)) As wktlonlat,
       (addy).address As stno, (addy).streetname As street,
       (addy).streettypeabbrev As styp, (addy).location As city, (addy).stateabbrev As st,( ←
       addy).zip
FROM geocode('31 - 37 Stewart Street, Boston, MA 02116',1) As g;
rating |          wktlonlat          | stno | street | styp | city | st | zip
-----+-----+-----+-----+-----+-----+-----+-----
70 | POINT(-71.06466 42.35114) | 31 | Stuart | St | Boston | MA | 02116
```

PostGIS (batch) 使用 max_results = 1 返回结果。PostGIS (batch) 使用 max_results = 1 返回结果。

```
CREATE TABLE addresses_to_geocode(addid serial PRIMARY KEY, address text,
                                   lon numeric, lat numeric, new_address text, rating integer);
```

```
INSERT INTO addresses_to_geocode(address)
VALUES ('529 Main Street, Boston MA, 02129'),
```

```
('77 Massachusetts Avenue, Cambridge, MA 02139'),
('25 Wizard of Oz, Walaford, KS 99912323'),
('26 Capen Street, Medford, MA'),
('124 Mount Auburn St, Cambridge, Massachusetts 02138'),
('950 Main Street, Worcester, MA 01610');

-- only update the first 3 addresses (323-704 ms - there are caching and shared memory ↵
-- effects so first geocode you do is always slower) --
-- for large numbers of addresses you don't want to update all at once
-- since the whole geocode must commit at once
-- For this example we rejoin with LEFT JOIN
-- and set to rating to -1 rating if no match
-- to ensure we don't regeocode a bad address
UPDATE addresses_to_geocode
  SET (rating, new_address, lon, lat)
    = ( COALESCE(g.rating, -1), pprint_addy(g.addy),
        ST_X(g.geomout)::numeric(8,5), ST_Y(g.geomout)::numeric(8,5) )
FROM (SELECT addid, address
      FROM addresses_to_geocode
      WHERE rating IS NULL ORDER BY addid LIMIT 3) As a
  LEFT JOIN LATERAL geocode(a.address,1) As g ON true
WHERE a.addid = addresses_to_geocode.addid;

result
-----
Query returned successfully: 3 rows affected, 480 ms execution time.

SELECT * FROM addresses_to_geocode WHERE rating is not null;
```

addid	new_address	rating	lon	lat	
1	529 Main Street, Boston MA, 02129		-71.07177	42.38357	529 Main St, ↵
2	77 Massachusetts Avenue, Cambridge, MA 02139		-71.09396	42.35961	77 ↵
3	25 Wizard of Oz, Walaford, KS 99912323		-97.92913	38.12717	Willowbrook, ↵

(3 rows)

Example: Geocoding a specific address

```
SELECT g.rating, ST_AsText(ST_SnapToGrid(g.geomout,0.00001)) As wktlonlat,
  (addy).address As stno, (addy).streetname As street,
  (addy).streettypeabbrev As styp,
  (addy).location As city, (addy).stateabbrev As st,(addy).zip
FROM geocode('100 Federal Street, MA',
  3,
  (SELECT ST_Union(the_geom)
   FROM place WHERE statefp = '25' AND name = 'Lynn')::geometry
 ) As g;
```

rating	wktlonlat	stno	street	styp	city	st	zip
7	POINT(-70.96796 42.4659)	100	Federal	St	Lynn	MA	01905
16	POINT(-70.96786 42.46853)	NULL	Federal	St	Lynn	MA	01905

(2 rows)

Time: 622.939 ms

☐☐

[Set_Geocode_Setting](#)

12.2.7 Get_Tract

Get Tract — 返回指定地理坐标 (tract) 的地理名称 (field) 的文本值。返回的文本值包含地理名称和地理 ID。

Synopsis

text **get_tract**(geometry loc_geom, text output_field=name);

☐☐

该函数返回指定地理坐标的地理名称。返回的文本值包含地理名称和地理 ID。NAD83 坐标系。

Note

This function uses the census tract which is not loaded by default. If you have already loaded your state table, you can load tract as well as bg, and tabblock using the [Loader_Generate_Census_Script](#) script.



If you have not loaded your state data yet and want these additional tables loaded, do the following

```
UPDATE tiger.loader_lookuptables SET load = true WHERE load = false AND lookup_name IN('tract', 'bg', 'tabblock');
```

then they will be included by the [Loader_Generate_Script](#).

2.0.0 版本引入。

☐☐☐☐

```
SELECT get_tract(ST_Point(-71.101375, 42.31376) ) As tract_name;
tract_name
-----
1203.01
```

```
--this one returns the tiger geoid
SELECT get_tract(ST_Point(-71.101375, 42.31376), 'tract_id' ) As tract_id;
tract_id
-----
25025120301
```

☐☐

[Geocode](#)>

12.2.8 Install_Missing_Indexes

`Install_Missing_Indexes` — 为指定的表 (join) 和列 (key) 安装缺失的索引。

Synopsis

boolean **Install_Missing_Indexes**();

描述

`tiger` 和 `tiger_data` 表在安装索引时，会检查表中的索引。如果索引不存在，则会生成 SQL DDL 语句，并执行该语句。如果索引已经存在，则不会生成任何语句。有关生成索引的脚本，请参考 [Missing_Indexes_Generate_Script](#)。在 2.0.0 版本中，`update_geocode.sql` 脚本会调用 `install_missing_indexes`。

示例

```
SELECT install_missing_indexes();
       install_missing_indexes
-----
t
```

描述

[Loader_Generate_Script](#), [Missing_Indexes_Generate_Script](#)

12.2.9 Loader_Generate_Census_Script

`Loader_Generate_Census_Script` — 为指定的表 (州) 生成 TIGER 表 (州) 的 `tract`, `bg`, `tabblocks` 表。这些表是 `tiger_data` 表的子表。

Synopsis

setof text **loader_generate_census_script**(text[] param_states, text os);

描述

为指定的表 (州) 生成 TIGER 表 (州) 的 `tract`, `bg`, `tabblocks` 表。这些表是 `tiger_data` 表的子表。在 (州) 表中，`tract` 表是 `tiger_data` 表的子表。

该脚本使用 `unzip` (解压 7-zip 文件) 和 `wget` 命令。有关该脚本的详细信息，请参考 [Section 4.7.2](#)。该脚本会生成 (州) 表的 `staging` 和 `temp` 表。

该脚本会生成 OS 表。

1. `loader_variables` - 设置环境变量, 例如, `loader_variables` (staging) 数据库连接信息。
2. `loader_platform` - 设置加载平台, 例如, `loader_platform`。设置加载平台, 例如, `loader_platform`。
3. `loader_lookuptables` - 设置加载表 (表, 表), 例如, `loader_lookuptables`, 例如, `loader_lookuptables`。设置加载表, 例如, `loader_lookuptables`, 例如, `loader_lookuptables`。设置加载表 (州名) 表, TIGER 加载表, 例如, `loader_lookuptables`。例如: `tiger.faces` 加载表 `tiger_data.ma_faces` 加载表。

2.0.0 安装与配置。



Note

Loader_Generate_Script 安装与配置, PostGIS 2.0.0 alpha5 安装与配置 TIGER 加载表, 例如, `loader_generate_script` (州) 加载表。

安装

安装与配置。

```
SELECT loader_generate_census_script(ARRAY['MA'], 'windows');
-- result --
set STATEDIR="\gisdata\www2.census.gov\geo\pvs\tiger2010st\25_Massachusetts"
set TMPDIR=\gisdata\temp\
set UNZIPTOOL="C:\Program Files\7-Zip\7z.exe"
set WGETTOOL="C:\wget\wget.exe"
set PGBIN=C:\projects\pg\pg91win\bin\
set PGPORT=5432
set PGHOST=localhost
set PGUSER=postgres
set PGPASSWORD=yourpasswordhere
set PGDATABASE=tiger_postgis20
set PSQL="%PGBIN%psql"
set SHP2PGSQL="%PGBIN%shp2pgsql"
cd \gisdata

%WGETTOOL% http://www2.census.gov/geo/pvs/tiger2010st/25_Massachusetts/25/ --no-parent -- \
    relative --accept=*bg10.zip,*tract10.zip,*tabblock10.zip --mirror --reject=html
del %TMPDIR%\*. * /Q
%PSQL% -c "DROP SCHEMA tiger_staging CASCADE;"
%PSQL% -c "CREATE SCHEMA tiger_staging;"
cd %STATEDIR%
for /r %%z in (*.zip) do %UNZIPTOOL% e %%z -o%TMPDIR%
cd %TMPDIR%
%PSQL% -c "CREATE TABLE tiger_data.MA_tract(CONSTRAINT pk_MA_tract PRIMARY KEY (tract_id) ) \
    INHERITS(tiger.tract); "
%SHP2PGSQL% -c -s 4269 -g the_geom -W "latin1" tl_2010_25_tract10.dbf tiger_staging. \
    ma_tract10 | %PSQL%
%PSQL% -c "ALTER TABLE tiger_staging.MA_tract10 RENAME geoid10 TO tract_id; SELECT \
    loader_load_staged_data(lower('MA_tract10'), lower('MA_tract')); "
%PSQL% -c "CREATE INDEX tiger_data_MA_tract_the_geom_gist ON tiger_data.MA_tract USING gist \
    (the_geom);"
%PSQL% -c "VACUUM ANALYZE tiger_data.MA_tract;"
%PSQL% -c "ALTER TABLE tiger_data.MA_tract ADD CONSTRAINT chk_statefp CHECK (statefp = \
    '25');"
:
```


2. loader_platform - 00000000000000000000000000000000. 00000000000000000000. 00000000000000000000000000000000.
3. loader_lookuptables - 0000000000 (0, 0), 000000000000000000, 000000000000000000000000. 00000000000000000000, 00000000, 000, 000000000000000000000000. 000000000000 (州名) 00, TIGER 0000000000000000. 0: tiger.faces 00000 tiger data.ma faces 000000000000.

2.0.0 **TIGER 2010** (tract), (bg), (tabblock)



Note

If you are using pgAdmin 3, be warned that by default pgAdmin 3 truncates long text. To fix, change *File -> Options -> Query Tool -> Query Editor -> Max. characters per column* to larger than 50000 characters.

11

Using psql where gistest is your database and /gisdata/data_load.sh is the file to create with the shell commands to run.

```
psql -U postgres -h localhost -d gistest -A -t \  
-c "SELECT Loader Generate Script(ARRAY['MA'], 'gistest')" > /gisdata/data load.sh;
```

[illegible]

```
SELECT loader_generate_script(ARRAY['MA','RI'],'windows') AS result;
-- result --
set TMPDIR=\gisdata\temp\
set UNZIPTOOL="C:\Program Files\7-Zip\7z.exe"
set WGETTOOL="C:\wget\wget.exe"
set PGBIN=C:\Program Files\PostgreSQL\9.4\bin\
set PGPORT=5432
set PGHOST=localhost
set PGUSER=postgres
set PGPASSWORD=yourpasswordhere
set PGDATABASE=geocoder
set PSQL="%PGBIN%psql"
set SHP2PGSQL="%PGBIN%shp2pgsql"
cd \gisdata

cd \gisdata
%WGETTOOL% ftp://ftp2.census.gov/geo/tiger/TIGER2015/PLACE/tl_*_25_* --no-parent --relative --recursive --level=2 --accept=zip --mirror --reject=html
cd \gisdata/ftp2.census.gov/geo/tiger/TIGER2015/PLACE
:
:
```

.sh ☒☒☒☒☒☒☒☒☒.

```
SELECT loader_generate_script(ARRAY['MA','RI'], 'sh') AS result;
-- result --
TMPDIR="/gisdata/temp/"
UNZIPTOOL=unzip
WGETTOOL="/usr/bin/wget"
export PGBIN=/usr/lib/postgresql/9.4/bin
-- variables used by psql: https://www.postgresql.org/docs/current/static/libpq-envvars.html
export PGPOR=5432
```


Note



If you want zip code 5 tabulation area (zcta5) to be included in your nation script load, do the following:

```
UPDATE tiger.loader_lookuptables SET load = true WHERE table_name = 'zcta510';
```

Note



tiger_2010 (州) tiger_2011 ,
Drop_Nation_Tables_Generate_Script
.

[illegible]

```
SELECT loader_generate_nation_script('windows');
```

[illegible]

```
SELECT loader_generate_nation_script('sh');
```



Loader Generate Script, Missing Indexes Generate Script

12.2.12 Missing_Indexes_Generate_Script

Missing Indexes Generate Script — (join) (key) SQL DDL .

Synopsis

```
text Missing_Indexes_Generate_Script();
```

[illegible]

2.0.0 ☒☒☒☒☒☒☒☒☒☒☒.

11

```
SELECT missing_indexes_generate_script();
-- output: This was run on a database that was created before many corrections were made to
the loading script ---
CREATE INDEX idx_tiger_county_countyfp ON tiger.county USING btree(countyfp);
CREATE INDEX idx_tiger_cousub_countyfp ON tiger.cousub USING btree(countyfp);
CREATE INDEX idx_tiger_edges_tfidr ON tiger.edges USING btree(tfidr);
CREATE INDEX idx_tiger_edges_tfidl ON tiger.edges USING btree(tfidl);
CREATE INDEX idx_tiger_zip_lookup_all_zip ON tiger.zip_lookup_all USING btree(zip);
CREATE INDEX idx_tiger_data_ma_county_countyfp ON tiger_data.ma_county USING btree(countyfp
);
CREATE INDEX idx_tiger_data_ma_cousub_countyfp ON tiger_data.ma_cousub USING btree(countyfp
);
CREATE INDEX idx_tiger_data_ma_edges_countyfp ON tiger_data.ma_edges USING btree(countyfp);
CREATE INDEX idx_tiger_data_ma_faces_countyfp ON tiger_data.ma_faces USING btree(countyfp);
```



Loader Generate Script, Install Missing Indexes

12.2.13 Normalize Address

Normalize Address — `XXXXXXXXXXXX, XXXXX, XXXXXXXXXXXXXXX, XXXXXXX`
`XXXXXXXXXX norm_addy XXXXXXXXXXXX. XXXXX tiger_geocoder XXXXXXXXXXXXXXX`
`XX (TIGER XXXXX) XXXXXXXX.`

Synopsis

```
norm addy normalize address(varchar in address);
```

11

[illegible]

tiger tiger_geocoder / (州)/
. TIGER
. tiger

tiger

```

XXXXXXXX norm_addy XXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXX. XX () XXXXXXXXXXXXXXXXXXXX
XXXXXXXX. [] XXXXXXXXXXXXXXXXXXXX:

```

```
(address) [predirAbbrev] (streetName) [streetTypeAbbrev] [postdirAbbrev] [internal] [location] [state-Abbrev] [zip] [parsed] [zip4] [address_alphanumeric]
```

Enhanced: 2.4.0 norm addy object includes additional fields zip4 and address alphanumeric.

1. address `XXXXXXXX`: `XXXXXXXXXX`.
2. `predirAbbrev` `varchar(10)`: N, S, E, W `XXXXXXXXXXXXXXXXXXXXXXXXXXXX`. `direction_look` `XXXXXXXXXXXXXXXXXXXXXXXXXXXX`.

- 3. streetName varchar(255).
- 4. streetTypeAbbrev varchar(10), St, Ave, Cir 等等. street_type_lookup 表.
- 5. postdirAbbrev varchar(10), N, S, E, W 等等. direction_lookup 表.
- 6. internal varchar(255). 内部地址.
- 7. location varchar(255). 位置.
- 8. stateAbbrev varchar(10), MA, NY, MI 等等 (州名). state_lookup 表.
- 9. zip varchar(10). 02109 等等.
- 10. parsed boolean. 是否解析. normalize_address 函数.
- 11. zip4 last 4 digits of a 9 digit zip code. Availability: PostGIS 2.4.0.
- 12. address_alphanumeric Full street number even if it has alpha characters like 17R. Parsing of this is better using [PgNormalizeAddress](#) function. Availability: PostGIS 2.4.0.

SQL

安装与使用. 安装与使用 [PgPrintAddy](#) 函数.

```
SELECT address As orig, (g.na).streetname, (g.na).streettypeabbrev
FROM (SELECT address, normalize_address(address) As na
      FROM addresses_to_geocode) As g;
```

orig	streetname	streettypeabbrev
28 Capen Street, Medford, MA	Capen	St
124 Mount Auburn St, Cambridge, Massachusetts 02138	Mount Auburn	St
950 Main Street, Worcester, MA 01610	Main	St
529 Main Street, Boston MA, 02129	Main	St
77 Massachusetts Avenue, Cambridge, MA 02139	Massachusetts	Ave
25 Wizard of Oz, Walford, KS 99912323	Wizard of Oz	

SQL

[Geocode](#), [PgPrintAddy](#)

12.2.14 PgNormalizeAddress

[PgNormalizeAddress](#) — 安装与使用, 安装与使用, 安装与使用, 安装与使用. norm_addy 函数. tiger_geocoder 函数 (TIGER 数据). address_standardizer 函数.

Synopsis

norm_addy **pgc_normalize_address**(varchar in_address);

安装

安装时，需要安装以下依赖库，安装成功后，再安装 PostGIS。安装成功后，再安装 PostGIS。安装成功后，再安装 PostGIS。

安装 tiger 需要安装 tiger_geocoder 和 page_*。安装 tiger_geocoder 需要安装 TIGER。安装 tiger_geocoder 需要安装 TIGER。安装 tiger_geocoder 需要安装 TIGER。

安装 tiger 需要安装 tiger_geocoder 和 page_*。

安装 norm_addy 需要安装 norm_addy。安装 norm_addy 需要安装 norm_addy。安装 norm_addy 需要安装 norm_addy。

Normalize_Address 函数用于将地址标准化。

2.1.0 版本开始支持。



This method needs address_standardizer extension.

(address) [predirAbbrev] (streetName) [streetTypeAbbrev] [postdirAbbrev] [internal] [location] [stateAbbrev] [zip]

安装 address_standardizer 需要安装 standardaddr 和 norm_addy。安装 address_standardizer 需要安装 standardaddr 和 norm_addy。

house_num, predir, name, suftype, sufdire, unit, city, state, postcode

Enhanced: 2.4.0 norm_addy object includes additional fields zip4 and address_alphanumeric.

1. address 字符串：地址字符串。
2. predirAbbrev 字符串：N, S, E, W 表示方向。direction_lookup 字典用于查找方向。
3. streetName 字符串：街道名称。
4. streetTypeAbbrev 字符串：St, Ave, Cir 表示街道类型。street_type_lookup 字典用于查找街道类型。
5. postdirAbbrev 字符串：N, S, E, W 表示方向。direction_lookup 字典用于查找方向。
6. internal 字符串：内部地址。
7. location 字符串：位置。
8. stateAbbrev 字符串：MA, NY, MI 表示州名。state_lookup 字典用于查找州名。
9. zip 字符串：02109 表示邮政编码。
10. parsed (boolean) 布尔值。normalize_address 函数用于解析地址。
11. zip4 last 4 digits of a 9 digit zip code. Availability: PostGIS 2.4.0.
12. address_alphanumeric Full street number even if it has alpha characters like 17R. Parsing of this is better using **Pagc_Normalize_Address** function. Availability: PostGIS 2.4.0.

¶

`norm_addy` 函数返回规范化后的地址字符串。该函数接受一个地址字符串作为输入，并返回一个规范化后的地址字符串。该函数使用 `Normalize_Address` 函数来规范化地址。

¶

函数返回规范化后的地址字符串。

```
SELECT pprint_addy(normalize_address('202 East Fremont Street, Las Vegas, Nevada 89101'))  
  As pretty_address;  
      pretty_address  
-----  
202 E Fremont St, Las Vegas, NV 89101
```

函数返回规范化后的地址字符串。

```
SELECT address As orig, pprint_addy(normalize_address(address)) As pretty_address  
  FROM addresses_to_geocode;
```

orig	pretty_address
529 Main Street, Boston MA, 02129	529 Main St, Boston MA, 02129
77 Massachusetts Avenue, Cambridge, MA 02139	77 Massachusetts Ave, Cambridge, MA 02139
28 Capen Street, Medford, MA	28 Capen St, Medford, MA
124 Mount Auburn St, Cambridge, Massachusetts 02138	124 Mount Auburn St, Cambridge, MA 02138
950 Main Street, Worcester, MA 01610	950 Main St, Worcester, MA 01610

¶

`Normalize_Address`

12.2.16 Reverse_Geocode

`Reverse_Geocode` — 根据给定的几何点返回该点的地址字符串。该函数接受一个几何点作为输入，并返回一个地址字符串。该函数使用 `include_strnum_range = true` 选项，以包含街道编号。该函数返回的地址字符串格式为：`street, city, state, zip`。

Synopsis

record **Reverse_Geocode**(geometry pt, boolean include_strnum_range=false, geometry[] OUT intpt,
norm_addy[] OUT addy, varchar[] OUT street);

¶

该函数返回一个记录，其中包含该点的几何点、规范化后的地址字符串、以及该点的街道名称。该函数使用 `include_strnum_range = true` 选项，以包含街道编号。该函数返回的地址字符串格式为：`street, city, state, zip`。

```
#include <strnum_range.h>. #include <string_range.h>  
#include <vector_range.h>.
```

st1	st2	st3	cross_str
5 Bradford St, Boston, MA 02118	49 Waltham St, Boston, MA 02118		Waltham St

Geocode 2

```
SELECT actual_addr, lon, lat, pprint_addy((rg).addy[1]) As int_addr1,
       (rg).street[1] As cross1, (rg).street[2] As cross2
FROM (SELECT address As actual_addr, lon, lat,
       reverse_geocode( ST_SetSRID(ST_Point(lon,lat),4326) ) As rg
      FROM addresses_to_geocode WHERE rating
> -1) As foo;
```

actual_addr	lon	lat	↔
int_addr1		cross1	↔
cross2			
529 Main Street, Boston MA, 02129	-71.07181	42.38359	527 Main St, ↔
Boston, MA 02129 Medford St			
77 Massachusetts Avenue, Cambridge, MA 02139	-71.09428	42.35988	77 ↔
Massachusetts Ave, Cambridge, MA 02139 Vassar St			
26 Capen Street, Medford, MA	-71.12377	42.41101	9 Edison Ave, ↔
Medford, MA 02155 Capen St			
124 Mount Auburn St, Cambridge, Massachusetts 02138	-71.12304	42.37328	3 University ↔
Rd, Cambridge, MA 02138 Mount Auburn St			
950 Main Street, Worcester, MA 01610	-71.82368	42.24956	3 Maywood St, ↔
Worcester, MA 01603 Main St			
	Maywood Pl		



Pprint Addy, Pprint Addy, ST AsText

12.2.17 Topology_Load_Tiger

Topology_Load_Tiger — PostGIS  TIGER  TIGER 

Synopsis

```
text Topology Load Tiger(varchar topo name, varchar region type, varchar region id);
```

[illegible][illegible]

**Note**

安装 TIGER 数据到 PostGIS 数据库。请参考 Chapter 9 Section 2.2.3 安装。安装完成后，请参考 2.2.3 节。安装完成后，请参考 2.2.3 节。

**Note**

安装 TIGER 数据到 PostGIS 数据库。请参考 Chapter 9 Section 2.2.3 安装。安装完成后，请参考 2.2.3 节。安装完成后，请参考 2.2.3 节。

安装:

1. topo_name - 安装到 PostGIS 数据库。
2. region_type - 安装到 PostGIS 数据库。place 和 county 数据。安装到 tiger.place, tiger.county 数据库。
3. region_id - TIGER ID(geoid) 安装到 PostGIS 数据库。place 和 county 数据。安装到 tiger.place 和 tiger.county 数据库。

2.0.0 安装。

安装: 安装到 PostGIS 数据库。

安装 (2249) 安装到 PostGIS 数据库。0.25 精度。安装 TIGER 数据，安装，安装。

```
SELECT topology.CreateTopology('topo_boston', 2249, 0.25);
createtopology
-----
15
-- 60,902 ms ~ 1 minute on windows 7 desktop running 9.1 (with 5 states tiger data loaded)
SELECT tiger.topology_load_tiger('topo_boston', 'place', '2507000');
-- topology_loader_tiger --
29722 edges holding in temporary. 11108 faces added. 1875 edges of faces added. 20576 nodes added.
19962 nodes contained in a face. 0 edge start end corrected. 31597 edges added.

-- 41 ms --
SELECT topology.TopologySummary('topo_boston');
-- topologysummary--
Topology topo_boston (15), SRID 2249, precision 0.25
20576 nodes, 31597 edges, 11109 faces, 0 topogeoms in 0 layers

-- 28,797 ms to validate yeh returned no errors --
SELECT * FROM
topology.ValidateTopology('topo_boston');

error      | id1      | id2
-----+-----+-----
```


注意: 使用 Tiger 数据时

使用 Tiger 数据 (26986) 时, 精度 0.25 是必需的, 使用 Tiger 数据, 使用, 使用。

```
SELECT topology.CreateTopology('topo_suffolk', 26986, 0.25);
-- this took 56,275 ms ~ 1 minute on Windows 7 32-bit with 5 states of tiger loaded
-- must have been warmed up after loading boston
SELECT tiger.topology_load_tiger('topo_suffolk', 'county', '25025');
-- topology_loader_tiger --
36003 edges holding in temporary. 13518 faces added. 2172 edges of faces added.
24761 nodes added. 24075 nodes contained in a face. 0 edge start end corrected. 38175 ↔
edges added.
-- 31 ms --
SELECT topology.TopologySummary('topo_suffolk');
-- topologysummary--
Topology topo_suffolk (14), SRID 26986, precision 0.25
24761 nodes, 38175 edges, 13519 faces, 0 topogeoms in 0 layers

-- 33,606 ms to validate --
SELECT * FROM
    topology.ValidateTopology('topo_suffolk');
```

error	id1	id2
coincident nodes	81045651	81064553
edge crosses node	81045651	85737793
edge crosses node	81045651	85742215
edge crosses node	81045651	620628939
edge crosses node	81064553	85697815
edge crosses node	81064553	85728168
edge crosses node	81064553	85733413

注意

CreateTopology, CreateTopoGeom, TopologySummary, ValidateTopology

12.2.18 Set_Geocode_Setting

Set_Geocode_Setting — 设置地理编码设置。

Synopsis

text Set_Geocode_Setting(text setting_name, text setting_value);

注意

tiger.geocode_settings 是 Tiger 数据库的一部分。使用 Get_Geocode_Setting 可以获取设置。

2.1.0 版本中新增。

注意: 安装失败

安装失败 **Geocode** 失败, NOTICE 消息: 安装失败。

```
SELECT set_geocode_setting('debug_geocode_address', 'true') As result;
result
-----
true
```

注意

Get_Geocode_Setting

Chapter 13

PostGIS Special Functions Index

13.1 PostGIS Aggregate Functions

The functions below are spatial aggregate functions that are used in the same way as SQL aggregate function such as sum and average.

- **CG_3DUnion** - Perform 3D union using postgis_sfcgal.
 - **ST_3DExtent** - Aggregate function that returns the 3D bounding box of geometries.
 - **ST_3DUnion** - Perform 3D union.
 - **ST_AsFlatGeobuf** - Return a FlatGeobuf representation of a set of rows.
 - **ST_AsGeobuf** - Return a Geobuf representation of a set of rows.
 - **ST_AsMVT** - Aggregate function returning a MVT representation of a set of rows.
 - **ST_ClusterDBSCAN** - Window function that returns a cluster id for each input geometry using the DBSCAN algorithm.
 - **ST_ClusterIntersecting** - Aggregate function that clusters input geometries into connected sets.
 - **ST_ClusterIntersectingWin** - Window function that returns a cluster id for each input geometry, clustering input geometries into connected sets.
 - **ST_ClusterKMeans** - Window function that returns a cluster id for each input geometry using the K-means algorithm.
 - **ST_ClusterWithin** - Aggregate function that clusters geometries by separation distance.
 - **ST_ClusterWithinWin** - Window function that returns a cluster id for each input geometry, clustering using separation distance.
 - **ST_Collect** - Creates a GeometryCollection or Multi* geometry from a set of geometries.
 - **ST_CoverageInvalidEdges** - Window function that finds locations where polygons fail to form a valid coverage.
 - **ST_CoverageSimplify** - Window function that simplifies the edges of a polygonal coverage.
 - **ST_CoverageUnion** - Computes the union of a set of polygons forming a coverage by removing shared edges.
 - **ST_Extent** - Aggregate function that returns the bounding box of geometries.
-

- **ST_MakeLine** - 返回由给定的点集组成的线。
- **ST_MemUnion** - Aggregate function which unions geometries in a memory-efficient but slower way
- **ST_Polygonize** - Computes a collection of polygons formed from the linework of a set of geometries.
- **ST_SameAlignment** - 检查两个几何体是否具有相同的对齐方式 (即它们是否位于相同的轴向上)。
- **ST_Union** - Computes a geometry representing the point-set union of the input geometries.
- **ST_Union** - 返回由给定的点集组成的线。
- **TopoElementArray_Agg** - Returns a topoelementarray for a set of element_id, type arrays (topoelements).

13.2 PostGIS Window Functions

The functions below are spatial window functions that are used in the same way as SQL window functions such as `row_number()`, `lead()`, and `lag()`. They must be followed by an `OVER()` clause.

- **ST_ClusterDBSCAN** - Window function that returns a cluster id for each input geometry using the DBSCAN algorithm.
- **ST_ClusterIntersectingWin** - Window function that returns a cluster id for each input geometry, clustering input geometries into connected sets.
- **ST_ClusterKMeans** - Window function that returns a cluster id for each input geometry using the K-means algorithm.
- **ST_ClusterWithinWin** - Window function that returns a cluster id for each input geometry, clustering using separation distance.
- **ST_CoverageInvalidEdges** - Window function that finds locations where polygons fail to form a valid coverage.
- **ST_CoverageSimplify** - Window function that simplifies the edges of a polygonal coverage.

13.3 PostGIS SQL-MM Compliant Functions

The functions given below are PostGIS functions that conform to the SQL/MM 3 standard

- **CG_3DArea** - 3D 几何体的面积。
- **CG_3DDifference** - 3D 几何体的差集。
- **CG_3DIntersection** - 3D 几何体的交集。
- **CG_3DUnion** - Perform 3D union using `postgis_sfcgal`.
- **CG_Volume** - 3D 几何体的体积。
- **ST_3DArea** - 3D 几何体的面积。
- **ST_3DDWithin** - Tests if two 3D geometries are within a given 3D distance
- **ST_3DDifference** - 3D 几何体的差集。

- **ST_3DDistance** - 返回两个几何体 (SRS 相同) 3 维欧几里德距离。
- **ST_3DIntersection** - 3 维交集。
- **ST_3DIntersects** - Tests if two geometries spatially intersect in 3D - only for points, linestrings, polygons, polyhedral surface (area)
- **ST_3DLength** - 返回几何体的 3 维长度。
- **ST_3DPerimeter** - 返回几何体的 3 维周长。
- **ST_3DUnion** - Perform 3D union.
- **ST_AddEdgeModFace** - 添加边到面, 返回面 ID, 面 ID 列表。
- **ST_AddEdgeNewFaces** - 添加边到面, 返回面 ID 列表, 面 ID 列表 2 维面 ID。
- **ST_AddIsoEdge** - 添加孤立边 anode 和 another node 之间的 alinestring 边 ID 列表。
- **ST_AddIsoNode** - 添加孤立节点 (isolated) 边 ID 列表。返回 NULL 列表, 面 ID 列表。
- **ST_Area** - 返回几何体的面积。
- **ST_AsBinary** - Return the OGC/ISO Well-Known Binary (WKB) representation of the geometry/geography without SRID meta data.
- **ST_AsGML** - 返回 GML 2 或 GML 3 表示的几何体。
- **ST_AsText** - 返回 WKT(Well-Known Text) 表示的几何体 SRID 表示的几何体。
- **ST_Boundary** - 返回几何体的边界。
- **ST_Buffer** - Computes a geometry covering all points within a given distance from a geometry.
- **ST_Centroid** - 返回几何体的质心。
- **ST_ChangeEdgeGeom** - 返回几何体的边 ID 列表。
- **ST_Contains** - Tests if every point of B lies in A, and their interiors have a point in common
- **ST_ConvexHull** - Computes the convex hull of a geometry.
- **ST_CoordDim** - ST_Geometry 的坐标维度。
- **ST_CreateTopoGeo** - 返回 TopoGeo 表示的几何体。
- **ST_Crosses** - Tests if two geometries have some, but not all, interior points in common
- **ST_CurveN** - Returns the Nth component curve geometry of a CompoundCurve.
- **ST_CurveToLine** - Converts a geometry containing curves to a linear geometry.
- **ST_Difference** - Computes a geometry representing the part of geometry A that does not intersect geometry B.
- **ST_Dimension** - ST_Geometry 的维度。
- **ST_Disjoint** - Tests if two geometries have no points in common
- **ST_Distance** - 返回两个几何体 3 维欧几里德 (longest) 距离。

- **ST_EndPoint** - ST_LineString 或 ST_CircularString 的末端点。
- **ST_Envelope** - 给定几何体的包络 (double precision; float8) 几何体。
- **ST_Equals** - Tests if two geometries include the same set of points
- **ST_ExteriorRing** - 返回几何体的外部环。
- **ST_GMLToSQL** - GML 几何体到 ST_Geometry 的转换。或 ST_GeomFromGML 的别名。
- **ST_GeomCollFromText** - Makes a collection Geometry from collection WKT with the given SRID. If SRID is not given, it defaults to 0.
- **ST_GeomFromText** - WKT 几何体到 ST_Geometry 的转换。
- **ST_GeomFromWKB** - WKB(Well-Known Binary) 几何体到 SRID 几何体的转换。
- **ST_GeometryFromText** - WKT(Well-Known Text) 几何体到 ST_Geometry 的转换。或 ST_GeomFromText 的别名。
- **ST_GeometryN** - ST_Geometry 的 N 维子几何体。
- **ST_GeometryType** - ST_Geometry 的几何体类型。
- **ST_GetFaceEdges** - aface 几何体的面边缘。
- **ST_GetFaceGeometry** - 几何体的面 ID 的几何体。
- **ST_InitTopoGeo** - Creates a new topology schema and registers it in the topology.topology table.
- **ST_InteriorRingN** - 几何体的内部环 N。
- **ST_Intersection** - Computes a geometry representing the shared portion of geometries A and B.
- **ST_Intersects** - Tests if two geometries intersect (they have at least one point in common)
- **ST_IsClosed** - LINESTRING 是否是闭合的 TRUE 或 FALSE。或 (LINESTRING) 是否是 TRUE 或 FALSE。
- **ST_IsEmpty** - Tests if a geometry is empty.
- **ST_IsRing** - Tests if a LineString is closed and simple.
- **ST_IsSimple** - 几何体是否是简单的 TRUE 或 FALSE。
- **ST_IsValid** - Tests if a geometry is well-formed in 2D.
- **ST_Length** - 几何体的长度。
- **ST_LineFromText** - SRID WKT 几何体到 LINESTRING 的转换。SRID 为 0 时省略。
- **ST_LineFromWKB** - SRID WKB 几何体到 LINESTRING 的转换。
- **ST_LinestringFromWKB** - SRID WKB 几何体到 LINESTRING 的转换。
- **ST_LocateAlong** - Returns the point(s) on a geometry that match a measure value.
- **ST_LocateBetween** - Returns the portions of a geometry that match a measure range.
- **ST_M** - Returns the M coordinate of a Point.
- **ST_MLineFromText** - WKT 几何体到 ST_MultiLineString 的转换。

- **ST_MPointFromText** - Makes a Geometry from WKT with the given SRID. If SRID is not given, it defaults to 0.
- **ST_MPolyFromText** - Makes a MultiPolygon Geometry from WKT with the given SRID. If SRID is not given, it defaults to 0.
- **ST_ModEdgeHeal** - Heals two edges by deleting the node connecting them, modifying the first edge and deleting the second edge. Returns the id of the deleted node.
- **ST_ModEdgeSplit** - 修改边并返回新边的 ID, 返回新边的 ID 列表。
- **ST_MoveIsoNode** - Moves an isolated node in a topology from one point to another. If new apoint geometry exists as a node an error is thrown. Returns description of move.
- **ST_NewEdgeHeal** - Heals two edges by deleting the node connecting them, deleting both edges, and replacing them with an edge whose direction is the same as the first edge provided.
- **ST_NewEdgesSplit** - 修改边并返回新边的 ID, 返回新边的 ID 列表。
- **ST_NumCurves** - Return the number of component curves in a CompoundCurve.
- **ST_NumGeometries** - 返回几何体数组中的几何体数量。
- **ST_NumInteriorRings** - 返回多边形内部环的数量。
- **ST_NumPatches** - 返回几何体数组中的几何体数量。返回 NULL 如果几何体为空。
- **ST_NumPoints** - ST_LineString 返回 ST_CircularString 返回的点数。
- **ST_OrderingEquals** - Tests if two geometries represent the same geometry and have points in the same directional order
- **ST_Overlaps** - Tests if two geometries have the same dimension and intersect, but each has at least one point not in the other
- **ST_PatchN** - ST_Geometry 返回的几何体。
- **ST_Perimeter** - Returns the length of the boundary of a polygonal geometry or geography.
- **ST_Point** - Creates a Point with X, Y and SRID values.
- **ST_PointFromText** - 返回 SRID 和 WKT 格式的几何体。SRID 为 0 时默认为 0。
- **ST_PointFromWKB** - 返回 SRID 和 WKB 格式的几何体。
- **ST_PointN** - ST_LineString 返回 ST_CircularString 返回的几何体。
- **ST_PointOnSurface** - Computes a point guaranteed to lie in a polygon, or on a geometry.
- **ST_Polygon** - Creates a Polygon from a LineString with a specified SRID.
- **ST_PolygonFromText** - Makes a Geometry from WKT with the given SRID. If SRID is not given, it defaults to 0.
- **ST_Relate** - Tests if two geometries have a topological relationship matching an Intersection Matrix pattern, or computes their Intersection Matrix
- **ST_RemEdgeModFace** - Removes an edge, and if the edge separates two faces deletes one face and modifies the other face to cover the space of both.
- **ST_RemEdgeNewFace** - 删除边并返回新面的 ID, 返回新面的 ID 列表。

- **ST_RemoveIsoEdge** - Removes an isolated edge and returns description of action. If the edge is not isolated, then an exception is thrown.
- **ST_RemoveIsoNode** - 移除几何体中的孤立节点。如果几何体不是有效的，则抛出异常。(无效的几何体) 返回, 移除的节点。
- **ST_SRID** - Returns the spatial reference identifier for a geometry.
- **ST_StartPoint** - Returns the first point of a LineString.
- **ST_SymDifference** - Computes a geometry representing the portions of geometries A and B that do not intersect.
- **ST_Touches** - Tests if two geometries have at least one point in common, but their interiors do not intersect
- **ST_Transform** - Return a new geometry with coordinates transformed to a different spatial reference system.
- **ST_Union** - Computes a geometry representing the point-set union of the input geometries.
- **ST_Volume** - 3 维几何体的体积。无效的几何体 (无效的几何体) 0 返回。
- **ST_WKBToSQL** - WKB(Well-Known Binary) 几何体转换为 ST_Geometry 类型。返回 SRID 几何体 ST_GeomFromWKB 返回。
- **ST_WKTToSQL** - WKT(Well-Known Text) 几何体转换为 ST_Geometry 类型。返回 ST_GeomFromWKT 返回。
- **ST_Within** - Tests if every point of A lies in B, and their interiors have a point in common
- **ST_X** - Returns the X coordinate of a Point.
- **ST_Y** - Returns the Y coordinate of a Point.
- **ST_Z** - Returns the Z coordinate of a Point.
- **ST_SRID** - Returns the spatial reference identifier for a topogeometry.

13.4 PostGIS Geography Support Functions

The functions and operators given below are PostGIS functions/operators that take as input or return as output a **geography** data type object.



Note

Functions with a (T) are not native geodetic functions, and use a ST_Transform call to and from geometry to do the operation. As a result, they may not behave as expected when going over dateline, poles, and for large geometries or geometry pairs that cover more than one UTM zone. Basic transform - (favoring UTM, Lambert Azimuthal (North/South), and falling back on mercator in worst case scenario)

- **ST_Area** - 返回几何体的面积。
- **ST_AsBinary** - Return the OGC/ISO Well-Known Binary (WKB) representation of the geometry/geography without SRID meta data.
- **ST_AsEWKT** - 返回 WKT(Well-Known Text) 几何体 SRID 几何体。
- **ST_AsGML** - 返回 GML 2 或 GML 3 几何体。

- **ST_AsGeoJSON** - Return a geometry or feature in GeoJSON format.
- **ST_AsKML** - 将 GML 2 转换为 GML 3 格式。
- **ST_AsSVG** - Returns SVG path data for a geometry.
- **ST_AsText** - 将 WKT(Well-Known Text) 转换为 SRID 格式。
- **ST_Azimuth** - 计算 2 个几何体之间的方位角。
- **ST_Buffer** - Computes a geometry covering all points within a given distance from a geometry.
- **ST_Centroid** - 计算几何体的质心。
- **ST_ClosestPoint** - Returns the 2D point on g1 that is closest to g2. This is the first point of the shortest line from one geometry to the other.
- **ST_CoveredBy** - Tests if every point of A lies in B
- **ST_Covers** - Tests if every point of B lies in A
- **ST_DWithin** - Tests if two geometries are within a given distance
- **ST_Distance** - 计算 3 个几何体 (longest) 之间的距离。
- **ST_GeogFromText** - WKT (几何体) 转换为 geography 格式。
- **ST_GeogFromWKB** - WKB 格式转换为 EWKB(二进制 WKB) 格式。
- **ST_GeographyFromText** - WKT (几何体) 转换为 geography 格式。
- **=** - Returns TRUE if the coordinates and coordinate order geometry/geography A are the same as the coordinates and coordinate order of geometry/geography B.
- **ST_Intersection** - Computes a geometry representing the shared portion of geometries A and B.
- **ST_Intersects** - Tests if two geometries intersect (they have at least one point in common)
- **ST_Length** - 计算几何体的长度。
- **ST_LineInterpolatePoint** - Returns a point interpolated along a line at a fractional location.
- **ST_LineInterpolatePoints** - Returns points interpolated along a line at a fractional interval.
- **ST_LineLocatePoint** - Returns the fractional location of the closest point on a line to a point.
- **ST_LineSubstring** - Returns the part of a line between two fractional locations.
- **ST_Perimeter** - Returns the length of the boundary of a polygonal geometry or geography.
- **ST_Project** - Returns a point projected from a start point by a distance and bearing (azimuth).
- **ST_Segmentize** - Returns a modified geometry/geography having no segment longer than a given distance.
- **ST_ShortestLine** - 计算 2 个几何体之间的最短距离。
- **ST_Summary** - 返回几何体的摘要信息。
- **<->** - A 与 B 之间的距离。
- **&&** - A 与 B 在 2D 空间中是否重合 (TRUE 表示重合)。

13.5 PostGIS Raster Support Functions

The functions and operators given below are PostGIS functions/operators that take as input or return as output a **raster** data type object. Listed in alphabetical order.

- **Box3D** - 返回 BOX3D 几何体。
- **@** - B 与 A 相等返回 TRUE。否则返回 FALSE。
- **~** - A 与 B 相等返回 TRUE。否则返回 FALSE。
- **=** - A 与 B 相等返回 TRUE。否则返回 FALSE。
- **&&** - A 与 B 相等返回 TRUE。否则返回 FALSE。
- **&<** - A 与 B 相等返回 TRUE。否则返回 FALSE。
- **&>** - A 与 B 相等返回 TRUE。否则返回 FALSE。
- **~=** - A 与 B 相等返回 TRUE。否则返回 FALSE。
- **ST_Retile** - 将栅格重新分块，返回新的栅格。
- **ST_AddBand** - 向栅格添加新的波段 (n) 个波段。返回新的栅格。
- **ST_AsBinary/ST_AsWKB** - Return the Well-Known Binary (WKB) representation of the raster.
- **ST_AsGDALRaster** - Return the raster tile in the designated GDAL Raster format. Raster formats are one of those supported by your compiled library. Use ST_GDALDrivers() to get a list of formats supported by your library.
- **ST_AsHexWKB** - Return the Well-Known Binary (WKB) in Hex representation of the raster.
- **ST_AsJPEG** - 将栅格转换为 JPEG (Joint Photographic Experts Group) 格式 (栅格) 的字节数组。返回 1 到 3 个波段的栅格。返回 3 个波段的 RGB 栅格。
- **ST_AsPNG** - 将栅格转换为 PNG (Portable Network Graphics) 格式 (栅格) 的字节数组。返回 1 到 3 个波段的栅格。返回 4 个波段的栅格。返回 2 到 4 个波段的栅格。返回 1 个波段的栅格。返回 RGB 或 RGBA 栅格。
- **ST_AsRaster** - PostGIS 栅格 PostGIS 栅格。
- **ST_AsTIFF** - Return the raster selected bands as a single TIFF image (byte array). If no band is specified or any of specified bands does not exist in the raster, then will try to use all bands.
- **ST_Aspect** - 返回 (栅格) 的坡度。返回栅格。
- **ST_Band** - 返回栅格的波段。返回栅格。
- **ST_BandFileSize** - Returns the file size of a band stored in file system. If no bandnum specified, 1 is assumed.
- **ST_BandFileTimestamp** - Returns the file timestamp of a band stored in file system. If no bandnum specified, 1 is assumed.
- **ST_BandIsNoData** - 返回 NODATA 值。
- **ST_BandMetaData** - 返回栅格的波段元数据。返回 1 个栅格。

- **ST_BandNoDataValue** - 返回栅格的 NODATA 值。如果栅格没有 NODATA 值，则返回 1。
- **ST_BandPath** - 返回栅格的波段路径。bandnum 指定波段编号，从 1 开始。
- **ST_BandPixelType** - 返回栅格的波段像素类型。bandnum 指定波段编号，从 1 开始。
- **ST_Clip** - Returns the raster clipped by the input geometry. If band number is not specified, all bands are processed. If crop is not specified or TRUE, the output raster is cropped. If touched is set to TRUE, then touched pixels are included, otherwise only if the center of the pixel is in the geometry it is included.
- **ST_ColorMap** - 返回栅格的 8BUI 颜色映射 (grayscale, RGB, RGBA) 的 4 个波段。
- **ST_Contains** - 返回栅格 rastA 是否包含栅格 rastB。如果 rastB 包含 rastA，则返回 TRUE。
- **ST_ContainsProperly** - rastB 是否完全包含 rastA。
- **ST_Contour** - Generates a set of vector contours from the provided raster band, using the GDAL contouring algorithm.
- **ST_ConvexHull** - BandNoDataValue 返回栅格的 NODATA 值，ST_Envelope 返回栅格的包络线。
- **ST_Count** - 返回栅格中指定值的像素数量。exclude_nodata_value 指定是否排除 NODATA 值。
- **ST_CountAgg** - 返回栅格中指定值的像素数量。exclude_nodata_value 指定是否排除 NODATA 值。
- **ST_CoveredBy** - 返回栅格 rastA 是否被栅格 rastB 覆盖。
- **ST_Covers** - 返回栅格 rastB 是否覆盖栅格 rastA。
- **ST_DFullyWithin** - 返回栅格 rastA 是否完全在栅格 rastB 的指定距离内。
- **ST_DWithin** - 返回栅格 rastA 是否在栅格 rastB 的指定距离内。
- **ST_Disjoint** - 返回栅格 rastA 是否与栅格 rastB 不相交。
- **ST_DumpAsPolygons** - 返回栅格的几何值 (geom, val) 的集合。bandnum 指定波段编号，从 1 开始。
- **ST_DumpValues** - 返回栅格的 2 个波段值。
- **ST_Envelope** - 返回栅格的包络线。
- **ST_FromGDALRaster** - 从 GDAL 栅格创建 PostGIS 栅格。
- **ST_GeoReference** - 返回 (world) 的地理参考信息。GDAL 的 ESRI 地理参考信息。
- **ST_Grayscale** - Creates a new one-8BUI band raster from the source raster and specified bands representing Red, Green and Blue
- **ST_HasNoBand** - 返回栅格是否具有指定的波段。bandnum 指定波段编号，从 1 开始。

- ST_Height** - Returns the height of the input geometry.
- ST_HillShade** - Returns a hillshade of the input geometry, based on the input elevation and a specified azimuth and altitude.
- ST_Histogram** - Returns a histogram of the input geometry, based on the input elevation and a specified number of bins.
- ST_InterpolateRaster** - Interpolates a gridded surface based on an input set of 3-d points, using the X- and Y-values to position the points on the grid and the Z-value of the points as the surface elevation.
- ST_Intersection** - Returns the intersection of the input geometries, as a single geometry.
- ST_Intersects** - Returns true if the input geometries intersect, false otherwise.
- ST_IsEmpty** - Returns true if the input geometry is empty (width = 0, height = 0), false otherwise.
- ST_MakeEmptyCoverage** - Cover georeferenced area with a grid of empty raster tiles.
- ST_MakeEmptyRaster** - Returns an empty raster with the specified dimensions, SRID, and scale/skew values.
- ST_MapAlgebra (callback function version)** - Returns the result of applying a callback function to the input geometries.
- ST_MapAlgebraExpr** - Returns the result of applying a PostgreSQL expression to the input geometries.
- ST_MapAlgebraExpr** - Returns the result of applying a PostgreSQL expression to the input geometries, with an extent type.
- ST_MapAlgebraFct** - Returns the result of applying a PostgreSQL function to the input geometries.
- ST_MapAlgebraFct** - Returns the result of applying a PostgreSQL function to the input geometries, with an extent type.
- ST_MapAlgebraFctNgb** - Returns the result of applying a PostgreSQL function to the input geometries, with a neighborhood.
- ST_MapAlgebra (expression version)** - Returns the result of applying a PostgreSQL expression to the input geometries.
- ST_MemSize** - Returns the memory size of the input geometry.
- ST_MetaData** - Returns the metadata of the input geometry, including the SRID and scale/skew values.
- ST_MinConvexHull** - Returns the minimum convex hull of the input geometry.
- ST_NearestValue** - Returns the nearest value to the input geometry, based on the input elevation and a specified distance.

- **ST_Neighborhood** - columnx 和 rowy, 返回指定像素邻域中的像素值。如果指定了 NODATA 则返回 NODATA。如果指定了 2 则返回 2 个像素值。
- **ST_NotSameAlignmentReason** - 返回两个栅格的不匹配原因。
- **ST_NumBands** - 返回栅格的波段数。
- **ST_Overlaps** - 返回两个栅格是否重叠。
- **ST_PixelAsCentroid** - 返回指定像素的质心 (X, Y)。
- **ST_PixelAsCentroids** - 返回指定像素的质心 (X, Y)。
- **ST_PixelAsPoint** - 返回指定像素的点。
- **ST_PixelAsPoints** - 返回指定像素的点 (X, Y)。
- **ST_PixelAsPolygon** - 返回指定像素的多边形。
- **ST_PixelAsPolygons** - 返回指定像素的多边形 (X, Y)。
- **ST_PixelHeight** - 返回指定像素的高度。
- **ST_PixelOfValue** - 返回指定像素的 columnx, rowy。
- **ST_PixelWidth** - 返回指定像素的宽度。
- **ST_Polygon** - NODATA 返回指定像素的多边形。
- **ST_Quantile** - 返回指定像素的 (population) 分位数 (quantile) 值。例如, 返回 25%, 50%, 75% 分位数 (percentile) 值。
- **ST_RastFromHexWKB** - Return a raster value from a Hex representation of Well-Known Binary (WKB) raster.
- **ST_RastFromWKB** - Return a raster value from a Well-Known Binary (WKB) raster.
- **ST_RasterToWorldCoord** - 返回指定像素的 X, Y (X, Y) 坐标。
- **ST_RasterToWorldCoordX** - 返回指定像素的 X 坐标。
- **ST_RasterToWorldCoordY** - 返回指定像素的 Y 坐标。
- **ST_Reclass** - 返回指定像素的重新分类后的值。nband 指定重新分类的波段数。nband 指定重新分类的波段数 1 表示单波段。例如: 16BUI 重新分类为 8BUI。
- **ST_Resample** - 返回指定像素的重新采样后的值。
- **ST_Rescale** - Resample a raster by adjusting only its scale (or pixel size). New pixel values are computed using the NearestNeighbor (english or american spelling), Bilinear, Cubic, CubicSpline, Lanczos, Max or Min resampling algorithm. Default is NearestNeighbor.
- **ST_Resize** - 返回指定像素的重新大小后的值。

- **ST_Reskew** - 返回 (列向量) 最近邻插值。NearestNeighbor(列向量), Bilinear, Cubic, CubicSpline 或 Lanczos 最近邻插值。NearestNeighbor 列向量。
- **ST_Rotation** - 返回旋转后的列向量。
- **ST_Roughness** - DEM 列向量" 粗糙度 (roughness)" 列向量。
- **ST_SRID** - spatial_ref_sys 列向量, 返回列向量。
- **ST_SameAlignment** - 返回列向量, 列, 列向量, 列向量 (列向量) 列向量, 列向量。
- **ST_ScaleX** - 返回列向量 X 列向量。
- **ST_ScaleY** - 返回列向量 Y 列向量。
- **ST_SetBandIndex** - Update the external band number of an out-db band
- **ST_SetBandIsNoData** - 列 isnodata 列。
- **ST_SetBandNoDataValue** - NODATA 列。列 1 列。列 NODATA 列, nodata value = NULL 列。
- **ST_SetBandPath** - Update the external path and band number of an out-db band
- **ST_SetGeoReference** - 列 6 列。列。GDAL 列 ESRI 列。列 GDAL 列。
- **ST_SetM** - Returns a geometry with the same X/Y coordinates as the input geometry, and values from the raster copied into the M dimension using the requested resample algorithm.
- **ST_SetRotation** - 列。
- **ST_SetSRID** - 列 SRID 列 spatial_ref_sys 列 SRID 列。
- **ST_SetScale** - X 列 Y 列。列/列/列。
- **ST_SetSkew** - 列 X 列 Y 列 (skew)(列) 列。列, X 列 Y 列。
- **ST_SetUpperLeft** - Sets the value of the upper left corner of the pixel of the raster to projected X and Y coordinates.
- **ST_SetValue** - 列 columnx, rowy 列。列 1 列, 列 1 列。
- **ST_SetValues** - 列。
- **ST_SetZ** - Returns a geometry with the same X/Y coordinates as the input geometry, and values from the raster copied into the Z dimension using the requested resample algorithm.
- **ST_SkewX** - 列 X 列 (skew)(列) 列。
- **ST_SkewY** - 列 Y 列 (skew)(列) 列。
- **ST_Slope** - 列 (列) 列。列。
- **ST_SnapToGrid** - 列。NearestNeighbor(列), Bilinear, Cubic, CubicSpline 或 Lanczos 最近邻插值。NearestNeighbor 列。
- **ST_Summary** - 列。

- **ST_SummaryStats** - 返回指定栅格的统计信息 (count, sum, mean, stddev, min, max) 的表。返回的表有 1 列。
- **ST_SummaryStatsAgg** - 聚合函数。返回指定栅格的统计信息 (count, sum, mean, stddev, min, max) 的表。返回的表有 1 列。
- **ST_TPI** - 地形位置指数 (Topographic Position Index) 的栅格。
- **ST_TRI** - 地形崎岖度指数 (Terrain Ruggedness Index) 的栅格。
- **ST_Tile** - 将栅格分割成指定大小的瓦片。
- **ST_Touches** - 检查两个栅格 (rastA, rastB) 是否接触。TRUE 表示接触。
- **ST_Transform** - 将栅格从一种坐标系转换到另一种坐标系。NearestNeighbor, Bilinear, Cubic, CubicSpline, Lanczos 是可选的插值方法。NearestNeighbor 是默认值。
- **ST_Union** - 将两个栅格合并为一个栅格。
- **ST_UpperLeftX** - 返回栅格左上角的 X 坐标。
- **ST_UpperLeftY** - 返回栅格左上角的 Y 坐标。
- **ST_Value** - 返回指定栅格在指定位置 (columnx, rowy) 的值。exclude_nodata_value 参数用于处理无数据值。
- **ST_ValueCount** - 返回指定栅格中每个值的出现次数。返回的表有 2 列：值和计数。NODATA 值被排除在外。
- **ST_Width** - 返回栅格的宽度。
- **ST_Within** - 检查一个栅格是否完全在另一个栅格内部。
- **ST_WorldToRasterCoord** - 将世界坐标 (X, Y) 转换为栅格坐标 (xw, yw)。
- **ST_WorldToRasterCoordX** - 将世界坐标 (pt) 转换为栅格 X 坐标 (xw, yw)。
- **ST_WorldToRasterCoordY** - 将世界坐标 (pt) 转换为栅格 Y 坐标 (xw, yw)。
- **UpdateRasterSRID** - 更新栅格的 SRID。

13.6 PostGIS Geometry / Geography / Raster Dump Functions

The functions given below are PostGIS functions that take as input or return as output a set of or single **geometry_dump** or **geomval** data type object.

- **ST_DumpAsPolygons** - 将 geomval(geom, val) 转换为多边形集合。返回的表有 1 列。
- **ST_Intersection** - 返回两个几何体的交集。返回的表有 1 列。

- **ST_Dump** - Returns a set of geometry_dump rows for the components of a geometry.
- **ST_DumpPoints** - 返回几何体中所有点的集合。
- **ST_DumpRings** - Returns a set of geometry_dump rows for the exterior and interior rings of a Polygon.
- **ST_DumpSegments** - 返回几何体中所有线段的集合。

13.7 PostGIS Box Functions

The functions given below are PostGIS functions that take as input or return as output the box* family of PostGIS spatial types. The box family of types consists of **box2d**, and **box3d**

- **Box2D** - Returns a BOX2D representing the 2D extent of a geometry.
- **Box3D** - Returns a BOX3D representing the 3D extent of a geometry.
- **Box3D** - 返回几何体的BOX3D。
- **ST_3DExtent** - Aggregate function that returns the 3D bounding box of geometries.
- **ST_3DMakeBox** - Creates a BOX3D defined by two 3D point geometries.
- **ST_AsMVTGeom** - Transforms a geometry into the coordinate space of a MVT tile.
- **ST_AsTWKB** - 返回TWKB(Tiny Well-Known Binary)格式的二进制数据。
- **ST_Box2dFromGeoHash** - GeoHash 返回BOX2D。
- **ST_ClipByBox2D** - Computes the portion of a geometry falling within a rectangle.
- **ST_EstimatedExtent** - Returns the estimated extent of a spatial table.
- **ST_Expand** - Returns a bounding box expanded from another bounding box or a geometry.
- **ST_Extent** - Aggregate function that returns the bounding box of geometries.
- **ST_MakeBox2D** - Creates a BOX2D defined by two 2D point geometries.
- **ST_RemoveIrrelevantPointsForView** - Removes points that are irrelevant for rendering a specific rectangular view of a geometry.
- **ST_XMax** - Returns the X maxima of a 2D or 3D bounding box or a geometry.
- **ST_XMin** - Returns the X minima of a 2D or 3D bounding box or a geometry.
- **ST_YMax** - Returns the Y maxima of a 2D or 3D bounding box or a geometry.
- **ST_YMin** - Returns the Y minima of a 2D or 3D bounding box or a geometry.
- **ST_ZMax** - Returns the Z maxima of a 2D or 3D bounding box or a geometry.
- **ST_ZMin** - Returns the Z minima of a 2D or 3D bounding box or a geometry.
- **RemoveUnusedPrimitives** - Removes topology primitives which not needed to define existing Topo-Geometry objects.
- **ValidateTopology** - Returns a set of validate_topology_return_type objects detailing issues with topology.
- **~(box2df,box2df)** - Returns TRUE if a 2D float precision bounding box (BOX2DF) contains another 2D float precision bounding box (BOX2DF).

- **~(box2df,geometry)** - Returns TRUE if a 2D float precision bounding box (BOX2DF) contains a geometry's 2D bounding box.
- **~(geometry,box2df)** - Returns TRUE if a geometry's 2D bounding box contains a 2D float precision bounding box (BOX2DF).
- **@(box2df,box2df)** - Returns TRUE if a 2D float precision bounding box (BOX2DF) is contained into another 2D float precision bounding box.
- **@(box2df,geometry)** - Returns TRUE if a 2D float precision bounding box (BOX2DF) is contained into a geometry's 2D bounding box.
- **@(geometry,box2df)** - Returns TRUE if a geometry's 2D bounding box is contained into a 2D float precision bounding box (BOX2DF).
- **&&(box2df,box2df)** - Returns TRUE if two 2D float precision bounding boxes (BOX2DF) intersect each other.
- **&&(box2df,geometry)** - Returns TRUE if a 2D float precision bounding box (BOX2DF) intersects a geometry's (cached) 2D bounding box.
- **&&(geometry,box2df)** - Returns TRUE if a geometry's (cached) 2D bounding box intersects a 2D float precision bounding box (BOX2DF).

13.8 PostGIS Functions that support 3D

The functions given below are PostGIS functions that do not throw away the Z-Index.

- **AddGeometryColumn** - 添加几何列。
- **Box3D** - Returns a BOX3D representing the 3D extent of a geometry.
- **CG_3DArea** - 3D 面积。返回 0 或正数。
- **CG_3DConvexHull** - 3D 凸包。
- **CG_3DDifference** - 3D 差集。
- **CG_3DIntersection** - 3D 交集。
- **CG_3DUnion** - Perform 3D union using postgis_sfcgal.
- **CG_ApproximateMedialAxis** - 3D 近似 medial axis。
- **CG_ConstrainedDelaunayTriangles** - Return a constrained Delaunay triangulation around the given input geometry.
- **CG_Extrude** - 3D 拉伸。
- **CG_ForceLHR** - LHR(Left Hand Reverse; 左手规则) 强制。
- **CG_IsPlanar** - 3D 是否共面。
- **CG_IsSolid** - 3D 是否是体素。返回 0 或正数。
- **CG_MakeSolid** - 3D 体素化。返回 0 或正数。返回 0 表示失败，返回正数表示成功。
- **CG_Orientation** - 3D 方向 (orientation) 返回 0 或正数。
- **CG_StraightSkeleton** - 3D 骨架 (straight skeleton) 返回 0 或正数。

- **CG_Tessellate** - 对多边形进行三角剖分 (tessellation) 返回 TIN 或 TIN 列表。
- **CG_Visibility** - Compute a visibility polygon from a point or a segment in a polygon geometry
- **CG_Volume** - 3 维多面体的体积。返回非负实数 (0 表示空集)。
- **DropGeometryColumn** - 删除几何列。
- **GeometryType** - ST_Geometry 的几何类型。
- **ST_3DArea** - 3 维多面体的面积。返回非负实数 (0 表示空集)。
- **ST_3DClosestPoint** - g2 到 g1 的最近点。返回 3 维点几何。3D 最近点。
- **ST_3DConvexHull** - 3D 凸包。
- **ST_3DDFullyWithin** - Tests if two 3D geometries are entirely within a given 3D distance
- **ST_3DDWithin** - Tests if two 3D geometries are within a given 3D distance
- **ST_3DDifference** - 3 维差集。
- **ST_3DDistance** - 3D 距离, 返回非负实数 (SRS 未定义) 3 维距离。
- **ST_3DExtent** - Aggregate function that returns the 3D bounding box of geometries.
- **ST_3DIntersection** - 3 维交集。
- **ST_3DIntersects** - Tests if two geometries spatially intersect in 3D - only for points, linestrings, polygons, polyhedral surface (area)
- **ST_3DLength** - 3D 长度。
- **ST_3DLineInterpolatePoint** - Returns a point interpolated along a 3D line at a fractional location.
- **ST_3DLongestLine** - 3 维最长线 (longest) 几何。
- **ST_3DMaxDistance** - 3D 最大距离, 返回非负实数 (SRS 未定义) 3 维最大距离。
- **ST_3DPerimeter** - 3D 周长。
- **ST_3DShortestLine** - 3 维最短线 (shortest) 几何。
- **ST_3DUnion** - Perform 3D union.
- **ST_AddMeasure** - Interpolates measures along a linear geometry.
- **ST_AddPoint** - 3D 添加点。
- **ST_Affine** - Apply a 3D affine transformation to a geometry.
- **ST_ApproximateMedialAxis** - 3D 近似中轴。
- **ST_AsBinary** - Return the OGC/ISO Well-Known Binary (WKB) representation of the geometry/geography without SRID meta data.
- **ST_AsEWKB** - Return the Extended Well-Known Binary (EWKB) representation of the geometry with SRID meta data.
- **ST_AsEWKT** - 返回 WKT(Well-Known Text) 格式 SRID 几何。
- **ST_AsGML** - 返回 GML 2 或 GML 3 格式几何。

- **ST_AsGeoJSON** - Return a geometry or feature in GeoJSON format.
- **ST_AsHEXEWKB** - 返回指定几何体 (NDR) 或点 (XDR) 的 HEXEWKB (二进制) 表示。
- **ST_AsKML** - 将几何体转换为 GML 2 或 GML 3 格式。
- **ST_AsX3D** - 将几何体转换为 X3D XML 格式: ISO-IEC-19776-1.2-X3DEncodings-XML 格式。
- **ST_Boundary** - 返回几何体的边界。
- **ST_BoundingDiagonal** - 返回几何体的包围盒的对角线。
- **ST_CPAWithin** - Tests if the closest point of approach of two trajectories is within the specified distance.
- **ST_ChaikinSmoothing** - Returns a smoothed version of a geometry, using the Chaikin algorithm
- **ST_ClosestPointOfApproach** - Returns a measure at the closest point of approach of two trajectories.
- **ST_Collect** - Creates a GeometryCollection or Multi* geometry from a set of geometries.
- **ST_ConstrainedDelaunayTriangles** - Return a constrained Delaunay triangulation around the given input geometry.
- **ST_ConvexHull** - Computes the convex hull of a geometry.
- **ST_CoordDim** - ST_Geometry 的坐标维度。
- **ST_CurveN** - Returns the Nth component curve geometry of a CompoundCurve.
- **ST_CurveToLine** - Converts a geometry containing curves to a linear geometry.
- **ST_DelaunayTriangles** - Returns the Delaunay triangulation of the vertices of a geometry.
- **ST_Difference** - Computes a geometry representing the part of geometry A that does not intersect geometry B.
- **ST_DistanceCPA** - Returns the distance between the closest point of approach of two trajectories.
- **ST_Dump** - Returns a set of geometry_dump rows for the components of a geometry.
- **ST_DumpPoints** - 返回几何体中所有点的集合。
- **ST_DumpRings** - Returns a set of geometry_dump rows for the exterior and interior rings of a Polygon.
- **ST_DumpSegments** - 返回几何体中所有线段的集合。
- **ST_EndPoint** - ST_LineString 或 ST_CircularString 的终点。
- **ST_ExteriorRing** - 返回多边形的外环。
- **ST_Extrude** - 将几何体沿 Z 轴拉伸。
- **ST_FlipCoordinates** - Returns a version of a geometry with X and Y axis flipped.
- **ST_Force2D** - 将几何体强制转换为 2D。
- **ST_ForceCurve** - 将几何体强制转换为曲线 (upcast)。
- **ST_ForceLHR** - LHR(Left Hand Reverse; 逆时针) 强制几何体。
- **ST_ForcePolygonCCW** - Orients all exterior rings counter-clockwise and all interior rings clockwise.
- **ST_ForcePolygonCW** - Orients all exterior rings clockwise and all interior rings counter-clockwise.

- **ST_ForceRHR** - 强制几何体 (orientation) 符合右手定则 (Right-Hand Rule) 的坐标系。
- **ST_ForceSFS** - 强制 SFS 1.1 的几何体。
- **ST_Force3D** - 强制 XYZ 坐标系。ST_Force3DZ 强制 3DZ 坐标系。
- **ST_Force3DZ** - 强制 XYZ 坐标系。
- **ST_Force4D** - 强制 XYZM 坐标系。
- **ST_ForceCollection** - 强制几何体集合。
- **ST_GeomFromEWKB** - EWKB(Extended Well-Known Binary) 格式的 ST_Geometry 几何体。
- **ST_GeomFromEWKT** - EWKT(Extended Well-Known Text) 格式的 ST_Geometry 几何体。
- **ST_GeomFromGML** - GML 格式的 PostGIS 几何体。
- **ST_GeomFromGeoJSON** - GeoJSON 格式的 PostGIS 几何体。
- **ST_GeomFromKML** - KML 格式的 PostGIS 几何体。
- **ST_GeometricMedian** - 几何体的中位数 (median) 几何体。
- **ST_GeometryN** - ST_Geometry 几何体集合中的第 N 个几何体。
- **ST_GeometryType** - ST_Geometry 几何体的类型。
- **ST_HasArc** - Tests if a geometry contains a circular arc
- **ST_HasM** - Checks if a geometry has an M (measure) dimension.
- **ST_HasZ** - Checks if a geometry has a Z dimension.
- **ST_InteriorRingN** - 几何体集合中的第 N 个内环。
- **ST_InterpolatePoint** - 沿几何体 (M 值) 插值点。
- **ST_Intersection** - Computes a geometry representing the shared portion of geometries A and B.
- **ST_IsClosed** - LINESTRING 是否是闭合的 TRUE 或 FALSE。多线环 (MULTILINESTRING) 是否是 TRUE 或 FALSE。
- **ST_IsCollection** - 是否是几何体集合, 点, 线, 面 TRUE 或 FALSE。
- **ST_IsPlanar** - 是否是平面几何体。
- **ST_IsPolygonCCW** - Tests if Polygons have exterior rings oriented counter-clockwise and interior rings oriented clockwise.
- **ST_IsPolygonCW** - Tests if Polygons have exterior rings oriented clockwise and interior rings oriented counter-clockwise.
- **ST_IsSimple** - 是否是简单几何体 TRUE 或 FALSE。
- **ST_IsSolid** - 是否是实心几何体。是否是实心几何体。
- **ST_IsValidTrajectory** - Tests if the geometry is a valid trajectory.
- **ST_LengthSpheroid** - 球面几何体的长度。
- **ST_LineFromMultiPoint** - 从多点集合生成线。
- **ST_LineInterpolatePoint** - Returns a point interpolated along a line at a fractional location.

- **ST_LineInterpolatePoints** - Returns points interpolated along a line at a fractional interval.
- **ST_LineSubstring** - Returns the part of a line between two fractional locations.
- **ST_LineToCurve** - Converts a linear geometry to a curved geometry.
- **ST_LocateBetweenElevations** - Returns the portions of a geometry that lie in an elevation (Z) range.
- **ST_M** - Returns the M coordinate of a Point.
- **ST_MakeLine** - 从点数组中创建 LineString 几何体。
- **ST_MakePoint** - Creates a 2D, 3DZ or 4D Point.
- **ST_MakePolygon** - Creates a Polygon from a shell and optional list of holes.
- **ST_MakeSolid** - 从点数组中创建 Polygon 几何体。如果指定了 true，则返回 Solid Polygon。如果指定了 false，则返回 Polygon。如果指定了 true，则返回 TIN 几何体。
- **ST_MakeValid** - Attempts to make an invalid geometry valid without losing vertices.
- **ST_MemSize** - ST_Geometry 的内存大小。
- **ST_MemUnion** - Aggregate function which unions geometries in a memory-efficient but slower way.
- **ST_NDims** - ST_Geometry 的维度。
- **ST_NPoints** - 返回 LineString 中的点数量 (对于 Polygon 返回壳中的点数量)。
- **ST_NRings** - 返回 Polygon 中的环数量。
- **ST_Node** - Nodes a collection of lines.
- **ST_NumCurves** - Return the number of component curves in a CompoundCurve.
- **ST_NumGeometries** - 返回 GeometryCollection 中的几何体数量。
- **ST_NumPatches** - 返回 Polygon 中的面片数量。如果指定了 true，则返回 NULL 面片数量。
- **ST_Orientation** - 返回 LineString 的 (orientation) 值。
- **ST_PatchN** - ST_Geometry 中的第 N 个面片。
- **ST_PointFromWKB** - 从 SRID 和 WKB 数据中创建 Point 几何体。
- **ST_PointN** - ST_LineString 或 ST_CircularString 中的第 N 个点。
- **ST_PointOnSurface** - Computes a point guaranteed to lie in a polygon, or on a geometry.
- **ST_Points** - 从 GeometryCollection 中提取点。
- **ST_Polygon** - Creates a Polygon from a LineString with a specified SRID.
- **ST_RemovePoint** - Remove a point from a linestring.
- **ST_RemoveRepeatedPoints** - Returns a version of a geometry with duplicate points removed.
- **ST_Reverse** - 反转 GeometryCollection 中的几何体。
- **ST_Rotate** - Rotates a geometry about an origin point.
- **ST_RotateX** - Rotates a geometry about the X axis.
- **ST_RotateY** - Rotates a geometry about the Y axis.
- **ST_RotateZ** - Rotates a geometry about the Z axis.
- **ST_Scale** - Scales a geometry by given factors.

- **ST_Scroll** - Change start point of a closed LineString.
- **ST_SetPoint** - 将点插入到 LineString 的指定位置。
- **ST_ShiftLongitude** - Shifts the longitude coordinates of a geometry between -180..180 and 0..360.
- **ST_SnapToGrid** - 将几何体 snap 到指定的栅格。
- **ST_StartPoint** - Returns the first point of a LineString.
- **ST_StraightSkeleton** - 计算几何体的 (straight skeleton) 骨架。
- **ST_SwapOrdinates** - 交换几何体的经纬度坐标。
- **ST_SymDifference** - Computes a geometry representing the portions of geometries A and B that do not intersect.
- **ST_Tessellate** - 将几何体 tessellation 为 TIN 三角网。
- **ST_TransScale** - Translates and scales a geometry by given offsets and factors.
- **ST_Translate** - Translates a geometry by given offsets.
- **ST_UnaryUnion** - Computes the union of the components of a single geometry.
- **ST_Union** - Computes a geometry representing the point-set union of the input geometries.
- **ST_Volume** - 3D 几何体的体积 (立方单位) 0 表示无效值。
- **ST_WrapX** - X 坐标的环绕。
- **ST_X** - Returns the X coordinate of a Point.
- **ST_XMax** - Returns the X maxima of a 2D or 3D bounding box or a geometry.
- **ST_XMin** - Returns the X minima of a 2D or 3D bounding box or a geometry.
- **ST_Y** - Returns the Y coordinate of a Point.
- **ST_YMax** - Returns the Y maxima of a 2D or 3D bounding box or a geometry.
- **ST_YMin** - Returns the Y minima of a 2D or 3D bounding box or a geometry.
- **ST_Z** - Returns the Z coordinate of a Point.
- **ST_ZMax** - Returns the Z maxima of a 2D or 3D bounding box or a geometry.
- **ST_ZMin** - Returns the Z minima of a 2D or 3D bounding box or a geometry.
- **ST_Zmflag** - ST_Geometry 的 Z 标志。
- **Equals** - 检查 TopoGeometry 是否相等。
- **Intersects** - 检查 TopoGeometry 是否相交。
- **UpdateGeometrySRID** - Updates the SRID of all features in a geometry column, and the table meta-data.
- **&&&** - A n-D 几何体 B n-D 几何体 TRUE 表示相交。
- **&&&(geometry,gidx)** - Returns TRUE if a geometry's (cached) n-D bounding box intersects a n-D float precision bounding box (GIDX).
- **&&&(gidx,geometry)** - Returns TRUE if a n-D float precision bounding box (GIDX) intersects a geometry's (cached) n-D bounding box.
- **&&&(gidx,gidx)** - Returns TRUE if two n-D float precision bounding boxes (GIDX) intersect each other.

13.9 PostGIS Curved Geometry Support Functions

The functions given below are PostGIS functions that can use CIRCULARSTRING, CURVEPOLYGON, and other curved geometry types

- **AddGeometryColumn** - 向指定的表添加几何列。
- **Box2D** - Returns a BOX2D representing the 2D extent of a geometry.
- **Box3D** - Returns a BOX3D representing the 3D extent of a geometry.
- **DropGeometryColumn** - 从指定的表中删除几何列。
- **GeometryType** - ST_Geometry 的几何类型。
- **PostGIS_AddBBox** - 添加边界框。
- **PostGIS_DropBBox** - 删除边界框。
- **PostGIS_HasBBox** - 检查是否有边界框。
- **ST_3DExtent** - Aggregate function that returns the 3D bounding box of geometries.
- **ST_Affine** - Apply a 3D affine transformation to a geometry.
- **ST_AsBinary** - Return the OGC/ISO Well-Known Binary (WKB) representation of the geometry/geography without SRID meta data.
- **ST_AsEWKB** - Return the Extended Well-Known Binary (EWKB) representation of the geometry with SRID meta data.
- **ST_AsEWKT** - 返回 WKT(Well-Known Text) 格式的 SRID 几何。
- **ST_AsHEXEWKB** - 返回 (NDR) 格式的 (XDR) 格式的 HEXEWKB (HEX) 格式。
- **ST_AsSVG** - Returns SVG path data for a geometry.
- **ST_AsText** - 返回 WKT(Well-Known Text) 格式的 SRID 几何。
- **ST_ClusterDBSCAN** - Window function that returns a cluster id for each input geometry using the DBSCAN algorithm.
- **ST_ClusterWithin** - Aggregate function that clusters geometries by separation distance.
- **ST_ClusterWithinWin** - Window function that returns a cluster id for each input geometry, clustering using separation distance.
- **ST_Collect** - Creates a GeometryCollection or Multi* geometry from a set of geometries.
- **ST_CoordDim** - ST_Geometry 的坐标维度。
- **ST_CurveToLine** - Converts a geometry containing curves to a linear geometry.
- **ST_Distance** - 返回 3 个 (最长) 距离。
- **ST_Dump** - Returns a set of geometry_dump rows for the components of a geometry.
- **ST_DumpPoints** - 返回点。
- **ST_EndPoint** - ST_LineString 或 ST_CircularString 的终点。
- **ST_EstimatedExtent** - Returns the estimated extent of a spatial table.
- **ST_FlipCoordinates** - Returns a version of a geometry with X and Y axis flipped.

- **ST_Scale** - Scales a geometry by given factors.
- **ST_SetSRID** - Set the SRID on a geometry.
- **ST_StartPoint** - Returns the first point of a LineString.
- **ST_Summary** - 返回几何体的摘要。
- **ST_SwapOrdinates** - 交换几何体的坐标顺序。
- **ST_TransScale** - Translates and scales a geometry by given offsets and factors.
- **ST_Transform** - Return a new geometry with coordinates transformed to a different spatial reference system.
- **ST_Translate** - Translates a geometry by given offsets.
- **ST_XMax** - Returns the X maxima of a 2D or 3D bounding box or a geometry.
- **ST_XMin** - Returns the X minima of a 2D or 3D bounding box or a geometry.
- **ST_YMax** - Returns the Y maxima of a 2D or 3D bounding box or a geometry.
- **ST_YMin** - Returns the Y minima of a 2D or 3D bounding box or a geometry.
- **ST_ZMax** - Returns the Z maxima of a 2D or 3D bounding box or a geometry.
- **ST_ZMin** - Returns the Z minima of a 2D or 3D bounding box or a geometry.
- **ST_Zmflag** - ST_Geometry 的 Z 标志。
- **UpdateGeometrySRID** - Updates the SRID of all features in a geometry column, and the table meta-data.
- **~(box2df,box2df)** - Returns TRUE if a 2D float precision bounding box (BOX2DF) contains another 2D float precision bounding box (BOX2DF).
- **~(box2df,geometry)** - Returns TRUE if a 2D float precision bounding box (BOX2DF) contains a geometry's 2D bonding box.
- **~(geometry,box2df)** - Returns TRUE if a geometry's 2D bonding box contains a 2D float precision bounding box (GIDX).
- **&&** - A 2D 几何体 B 2D 几何体 TRUE 表示相交。
- **&&&** - A n 几何体 B n 几何体 TRUE 表示相交。
- **@(box2df,box2df)** - Returns TRUE if a 2D float precision bounding box (BOX2DF) is contained into another 2D float precision bounding box.
- **@(box2df,geometry)** - Returns TRUE if a 2D float precision bounding box (BOX2DF) is contained into a geometry's 2D bounding box.
- **@(geometry,box2df)** - Returns TRUE if a geometry's 2D bounding box is contained into a 2D float precision bounding box (BOX2DF).
- **&&(box2df,box2df)** - Returns TRUE if two 2D float precision bounding boxes (BOX2DF) intersect each other.
- **&&(box2df,geometry)** - Returns TRUE if a 2D float precision bounding box (BOX2DF) intersects a geometry's (cached) 2D bounding box.
- **&&(geometry,box2df)** - Returns TRUE if a geometry's (cached) 2D bounding box intersects a 2D float precision bounding box (BOX2DF).
- **&&&(geometry,gidx)** - Returns TRUE if a geometry's (cached) n-D bounding box intersects a n-D float precision bounding box (GIDX).

- **&&&(gidx,geometry)** - Returns TRUE if a n-D float precision bounding box (GIDX) intersects a geometry's (cached) n-D bounding box.
- **&&&(gidx,gidx)** - Returns TRUE if two n-D float precision bounding boxes (GIDX) intersect each other.

13.10 PostGIS Polyhedral Surface Support Functions

The functions given below are PostGIS functions that can use POLYHEDRALSURFACE, POLYHEDRAL-SURFACEM geometries

- **Box2D** - Returns a BOX2D representing the 2D extent of a geometry.
- **Box3D** - Returns a BOX3D representing the 3D extent of a geometry.
- **CG_3DArea** - 3 浮点精度值。返回 0 表示空几何。
- **CG_3DConvexHull** - 返回几何的 3D 凸包。
- **CG_3DDifference** - 3 浮点精度值。
- **CG_3DIntersection** - 3 浮点精度值。
- **CG_3DUnion** - Perform 3D union using postgis_sfcgal.
- **CG_ApproximateMedialAxis** - 返回几何的 3D 近似 medial axis。
- **CG_Extrude** - 返回几何的 3D 挤出。
- **CG_ForceLHR** - LHR(Left Hand Reverse; 逆时针) 返回几何。
- **CG_IsPlanar** - 返回几何是否是平面。
- **CG_IsSolid** - 返回几何是否是实心。
- **CG_MakeSolid** - 返回几何的 3D 实心版本。如果输入是 TIN，则返回 TIN 格式。
- **CG_StraightSkeleton** - 返回几何的 (straight skeleton) 骨架。
- **CG_Tessellate** - 返回几何的 (tessellation) 三角化 TIN 格式。
- **CG_Visibility** - Compute a visibility polygon from a point or a segment in a polygon geometry
- **CG_Volume** - 3 浮点精度值。返回 (绝对值) 0 表示空几何。
- **GeometryType** - ST_Geometry 返回几何类型。
- **ST_3DArea** - 3 浮点精度值。返回 0 表示空几何。
- **ST_3DClosestPoint** - g2 几何 g1 几何 3 浮点精度值。返回 3D 最近点。
- **ST_3DConvexHull** - 返回几何的 3D 凸包。
- **ST_3DDFullyWithin** - Tests if two 3D geometries are entirely within a given 3D distance
- **ST_3DDWithin** - Tests if two 3D geometries are within a given 3D distance
- **ST_3DDifference** - 3 浮点精度值。
- **ST_3DDistance** - 返回距离，SRS 不同 3 浮点精度值。

- **ST_3DExtent** - Aggregate function that returns the 3D bounding box of geometries.
- **ST_3DIntersection** - 3 维几何的交集。
- **ST_3DIntersects** - Tests if two geometries spatially intersect in 3D - only for points, linestrings, polygons, polyhedral surface (area)
- **ST_3DLongestLine** - 返回 3 维几何 (longest) 的线。
- **ST_3DMaxDistance** - 返回 3 维几何 (SRS 无关) 3 维几何之间的最大距离。
- **ST_3DShortestLine** - 返回 3 维几何 (shortest) 的线。
- **ST_3DUnion** - Perform 3D union.
- **ST_Affine** - Apply a 3D affine transformation to a geometry.
- **ST_ApproximateMedialAxis** - 返回几何的近似 medial axis。
- **ST_Area** - 返回几何的面积。
- **ST_AsBinary** - Return the OGC/ISO Well-Known Binary (WKB) representation of the geometry/geography without SRID meta data.
- **ST_AsEWKB** - Return the Extended Well-Known Binary (EWKB) representation of the geometry with SRID meta data.
- **ST_AsEWKT** - 返回 WKT(Well-Known Text) 格式的 SRID 几何。
- **ST_AsGML** - 返回 GML 2 或 GML 3 格式的几何。
- **ST_AsX3D** - 返回 X3D XML 格式的几何: ISO-IEC-19776-1.2-X3DEncodings-XML 格式。
- **ST_CoordDim** - ST_Geometry 的坐标维度。
- **ST_Dimension** - ST_Geometry 的维度。
- **ST_Dump** - Returns a set of geometry_dump rows for the components of a geometry.
- **ST_DumpPoints** - 返回几何的点的集合。
- **ST_Expand** - Returns a bounding box expanded from another bounding box or a geometry.
- **ST_Extent** - Aggregate function that returns the bounding box of geometries.
- **ST_Extrude** - 返回几何的 extruded 版本。
- **ST_FlipCoordinates** - Returns a version of a geometry with X and Y axis flipped.
- **ST_Force2D** - 强制 2D 几何。
- **ST_ForceLHR** - LHR(Left Hand Reverse; 左手规则) 几何。
- **ST_ForceRHR** - 强制 RHR (orientation) 几何 (Right-Hand Rule) 几何。
- **ST_ForceSFS** - 强制 SFS 1.1 格式的几何。
- **ST_Force3D** - 强制 XYZ 格式的几何。ST_Force3DZ 强制 3DZ 格式。
- **ST_Force3DZ** - 强制 XYZ 格式的几何。
- **ST_ForceCollection** - 强制集合几何。
- **ST_GeomFromEWKB** - EWKB(Extended Well-Known Binary) 格式的 ST_Geometry 几何。

- **ST_GeomFromEWKT** - EWKT(Extended Well-Known Text) 字符串 ST_Geometry 对象。
- **ST_GeomFromGML** - 从 GML 字符串创建 PostGIS 几何对象。
- **ST_GeometryN** - ST_Geometry 对象的第 N 个几何体。
- **ST_GeometryType** - ST_Geometry 对象的几何类型。
- **=** - Returns TRUE if the coordinates and coordinate order geometry/geography A are the same as the coordinates and coordinate order of geometry/geography B.
- **<&** - A 与 B 的几何体是否相等返回 TRUE。
- **~=** - A 与 B 的几何体是否相等返回 TRUE。
- **ST_IsClosed** - LINESTRING 是否是闭合的返回 TRUE。如果是闭合的 (即首尾相连) 返回 TRUE。
- **ST_IsPlanar** - 几何体是否是平面的。
- **ST_IsSolid** - 几何体是否是实体的。如果是实体的返回 TRUE。
- **ST_MakeSolid** - 将几何体转换为实体的。如果是实体的返回 TRUE。如果不是实体的, 返回 NULL。如果是 TIN 返回 NULL。
- **ST_MemSize** - ST_Geometry 对象的内存大小。
- **ST_NPoints** - 几何体中的点数量 (N) 返回。
- **ST_NumGeometries** - 几何体中的几何体数量返回。
- **ST_NumPatches** - 几何体中的补丁数量返回。如果是 NULL 返回 NULL。
- **ST_PatchN** - ST_Geometry 对象的第 N 个补丁。
- **ST_RemoveRepeatedPoints** - Returns a version of a geometry with duplicate points removed.
- **ST_Reverse** - 反转几何体。
- **ST_Rotate** - Rotates a geometry about an origin point.
- **ST_RotateX** - Rotates a geometry about the X axis.
- **ST_RotateY** - Rotates a geometry about the Y axis.
- **ST_RotateZ** - Rotates a geometry about the Z axis.
- **ST_Scale** - Scales a geometry by given factors.
- **ST_ShiftLongitude** - Shifts the longitude coordinates of a geometry between -180..180 and 0..360.
- **ST_StraightSkeleton** - 几何体的 (straight skeleton) 骨架。
- **ST_Summary** - 几何体的摘要。
- **ST_SwapOrdinates** - 交换几何体的经纬度。
- **ST_Tessellate** - 几何体的 (tessellation) 三角化 TIN 为 TIN 对象。
- **ST_Transform** - Return a new geometry with coordinates transformed to a different spatial reference system.
- **ST_Volume** - 3D 几何体的体积。如果是 0 返回 NULL。
- **~(box2df,box2df)** - Returns TRUE if a 2D float precision bounding box (BOX2DF) contains another 2D float precision bounding box (BOX2DF).

- **~(box2df,geometry)** - Returns TRUE if a 2D float precision bounding box (BOX2DF) contains a geometry's 2D bounding box.
- **~(geometry,box2df)** - Returns TRUE if a geometry's 2D bounding box contains a 2D float precision bounding box (BOX2DF).
- **&&** - A 2D BOX2DF B 2D BOX2DF TRUE.
- **&&&** - A n-D BOX2DF B n-D BOX2DF TRUE.
- **@(box2df,box2df)** - Returns TRUE if a 2D float precision bounding box (BOX2DF) is contained into another 2D float precision bounding box.
- **@(box2df,geometry)** - Returns TRUE if a 2D float precision bounding box (BOX2DF) is contained into a geometry's 2D bounding box.
- **@(geometry,box2df)** - Returns TRUE if a geometry's 2D bounding box is contained into a 2D float precision bounding box (BOX2DF).
- **&&(box2df,box2df)** - Returns TRUE if two 2D float precision bounding boxes (BOX2DF) intersect each other.
- **&&(box2df,geometry)** - Returns TRUE if a 2D float precision bounding box (BOX2DF) intersects a geometry's (cached) 2D bounding box.
- **&&(geometry,box2df)** - Returns TRUE if a geometry's (cached) 2D bounding box intersects a 2D float precision bounding box (BOX2DF).
- **&&&(geometry,gidx)** - Returns TRUE if a geometry's (cached) n-D bounding box intersects a n-D float precision bounding box (GIDX).
- **&&&(gidx,geometry)** - Returns TRUE if a n-D float precision bounding box (GIDX) intersects a geometry's (cached) n-D bounding box.
- **&&&(gidx,gidx)** - Returns TRUE if two n-D float precision bounding boxes (GIDX) intersect each other.

13.11 PostGIS Function Support Matrix

Below is an alphabetical listing of spatial specific functions in PostGIS and the kinds of spatial types they work with or OGC/SQL compliance they try to conform to.

- A  means the function works with the type or subtype natively.
- A  means it works but with a transform cast built-in using cast to geometry, transform to a "best srid" spatial ref and then cast back. Results may not be as expected for large areas or areas at poles and may accumulate floating point junk.
- A  means the function works with the type because of a auto-cast to another such as to box3d rather than direct type support.
- A  means the function only available if PostGIS compiled with SFCGAL support.
- geom - Basic 2D geometry support (x,y).
- geog - Basic 2D geography support (x,y).

- 2.5D - basic 2D geometries in 3 D/4D space (has Z or M coord).
- PS - Polyhedral surfaces
- T - Triangles and Triangulated Irregular Network surfaces (TIN)

Function	geom	geog	2.5D	Curves	SQL MM	PS	T
ST_Collect	✓		✓	✓			
ST_LineFromMultiPoint	✓		✓				
ST_MakeEnvelope	✓						
ST_MakeLine	✓		✓				
ST_MakePoint	✓		✓				
ST_MakePointM	✓						
ST_MakePolygon	✓		✓				
ST_Point	✓				✓		
ST_PointZ	✓						
ST_PointM	✓						
ST_PointZM	✓						
ST_Polygon	✓		✓		✓		
ST_TileEnvelope	✓						
ST_HexagonGrid	✓						
ST_Hexagon	✓						
ST_SquareGrid	✓						
ST_Square	✓						
ST_Letters	✓						
GeometryType	✓		✓	✓		✓	✓
ST_Boundary	✓		✓		✓		
ST_BoundingDiagonal	✓		✓				
ST_CoordDim	✓		✓	✓	✓	✓	✓
ST_Dimension	✓				✓	✓	✓
ST_Dump	✓		✓	✓		✓	✓
ST_DumpPoints	✓		✓	✓		✓	✓
ST_DumpSegments	✓		✓				✓
ST_DumpRings	✓		✓				
ST_EndPoint	✓		✓	✓	✓		
ST_Envelope	✓				✓		
ST_ExteriorRing	✓		✓		✓		

Function	geom	geog	2.5D	Curves	SQL MM	PS	T
ST_GeometryN	✓		✓	✓	✓	✓	✓
ST_GeometryType	✓		✓		✓	✓	
ST_HasArc	✓		✓	✓			
ST_InteriorRingN	✓		✓		✓		
ST_NumCurves	✓		✓		✓		
ST_CurveN	✓		✓		✓		
ST_IsClosed	✓		✓	✓	✓	✓	
ST_IsCollection	✓		✓	✓			
ST_IsEmpty	✓			✓	✓		
ST_IsPolygonCCW	✓		✓				
ST_IsPolygonCW	✓		✓				
ST_IsRing	✓				✓		
ST_IsSimple	✓		✓		✓		
ST_M	✓		✓		✓		
ST_MemSize	✓		✓	✓		✓	✓
ST_NDims	✓		✓				
ST_NPoints	✓		✓	✓		✓	
ST_NRings	✓		✓	✓			
ST_NumGeometries	✓		✓		✓	✓	✓
ST_NumInteriorRings	✓				✓		
ST_NumInteriorRing	✓						
ST_NumPatches	✓		✓		✓	✓	
ST_NumPoints	✓				✓		
ST_PatchN	✓		✓		✓	✓	
ST_PointN	✓		✓	✓	✓		
ST_Points	✓		✓	✓			
ST_StartPoint	✓		✓	✓	✓		
ST_Summary	✓	✓		✓		✓	✓
ST_X	✓		✓		✓		
ST_Y	✓		✓		✓		
ST_Z	✓		✓		✓		
ST_Zmflag	✓		✓	✓			
ST_HasZ	✓		✓				
ST_HasM	✓		✓				

Function	geom	geog	2.5D	Curves	SQL MM	PS	T
ST_AddPoint	✓		✓				
ST_CollectionExtract	✓						
ST_CollectionHistogram	✓						
ST_CurveToLine	✓		✓	✓	✓		
ST_Scroll	✓		✓				
ST_FlipCoordinates	✓		✓	✓		✓	✓
ST_Force2D	✓		✓	✓		✓	
ST_Force3D	✓		✓	✓		✓	
ST_Force3DZ	✓		✓	✓		✓	
ST_Force3DM	✓			✓			
ST_Force4D	✓		✓	✓			
ST_ForceCollection	✓		✓	✓		✓	
ST_ForceCurve	✓		✓	✓			
ST_ForcePolygonCW	✓		✓				
ST_ForcePolygonCW	✓		✓				
ST_ForceSFS	✓		✓	✓		✓	✓
ST_ForceRHR	✓		✓			✓	
ST_LineExtend	✓						
ST_LineToCurve	✓		✓	✓			
ST_Multi	✓						
ST_Normalize	✓						
ST_Project	✓	✓					
ST_QuantizeCoordinates	✓						
ST_RemovePoint	✓		✓				
ST_RemoveRepeatedPoints	✓		✓			✓	
ST_RemoveIrrelevantPointsForView	✓						
ST_RemoveSmallParts	✓						
ST_Reverse	✓		✓			✓	
ST_Segmentize	✓	✓					
ST_SetPoint	✓		✓				
ST_ShiftLongitude	✓		✓			✓	✓
ST_WrapX	✓		✓				
ST_SnapToGrid	✓		✓				
ST_Snap	✓						

Function	geom	geog	2.5D	Curves	SQL MM	PS	T
ST_SwapOrdinate	✓		✓	✓		✓	✓
ST_IsValid	✓				✓		
ST_IsValidDetail	✓						
ST_IsValidReason	✓						
ST_MakeValid	✓		✓				
ST_InverseTransformPipeline	✓						
ST_SetSRID	✓			✓			
ST_SRID	✓			✓	✓		
ST_Transform	✓			✓	✓	✓	
ST_TransformPipeline	✓						
postgis_srs_codes							
postgis_srs							
postgis_srs_all							
postgis_srs_search	✓						
ST_BdPolyFromText	✓						
ST_BdMPolyFromText	✓						
ST_GeogFromText		✓					
ST_GeographyFromText		✓					
ST_GeomCollFromText	✓				✓		
ST_GeomFromEWKT			✓	✓		✓	✓
ST_GeomFromMRC21	✓						
ST_GeometryFromText	✓				✓		
ST_GeomFromI	✓			✓	✓		
ST_LineFromText	✓				✓		
ST_MLineFromText	✓				✓		
ST_MPointFromText	✓				✓		
ST_MPolyFromText	✓				✓		
ST_PointFromText	✓				✓		
ST_PolygonFromText	✓				✓		
ST_WKTToSQL	✓				✓		
ST_GeogFromWKB		✓		✓			
ST_GeomFromEWKB	✓		✓	✓		✓	✓
ST_GeomFromV3				✓	✓		
ST_LineFromWKB	✓				✓		
ST_LinestringFromWKB	✓				✓		

Function	geom	geog	2.5D	Curves	SQL MM	PS	T
ST_PointFromWKB	✓		✓	✓	✓		
ST_WKBToSQL	✓				✓		
ST_Box2dFromGeoHash	✓						
ST_GeomFromGeoHash	✓						
ST_GeomFromGeoJSON	✓		✓			✓	✓
ST_GeomFromGeoJSON	✓		✓				
ST_GeomFromKML	✓		✓				
ST_GeomFromInterpolatedPolyline	✓						
ST_GMLToSQL	✓				✓		
ST_LineFromEncodedPolyline	✓						
ST_PointFromGeoHash							
ST_FromFlatGeobufToTable							
ST_FromFlatGeobuf							
ST_AsEWKT	✓	✓	✓	✓		✓	✓
ST_AsText	✓	✓		✓	✓		
ST_AsBinary	✓	✓	✓	✓	✓	✓	✓
ST_AsEWKB	✓		✓	✓		✓	✓
ST_AsHEXEWKB	✓		✓	✓			
ST_AsEncodedPolyline	✓						
ST_AsFlatGeobuf	✓						
ST_AsGeobuf	✓						
ST_AsGeoJSON	✓	✓	✓				
ST_AsGML	✓	✓	✓		✓	✓	✓
ST_AsKML	✓	✓	✓				
ST_AsLatLonText	✓						
ST_AsMARC21	✓						
ST_AsMVTGeom	✓						
ST_AsMVT	✓						
ST_AsSVG	✓	✓		✓			
ST_AsTWKB	✓						
ST_AsX3D	✓		✓			✓	✓
ST_GeoHash	✓			✓			
&&	✓	✓		✓		✓	
&&(geometry,buffer)	✓			✓		✓	
&&(box2df,geometry)	✓			✓		✓	

Function	geom	geog	2.5D	Curves	SQL MM	PS	T
&&(box2df,box2df)	✓			✓		✓	
&&&	✓		✓	✓		✓	✓
&&&(geometry,geometry)	✓		✓	✓		✓	✓
&&&(gidx,geometry)	✓		✓	✓		✓	✓
&&&(gidx,gidx)			✓	✓		✓	✓
&<	✓						
&<	✓			✓		✓	
&>	✓						
<<	✓						
<<	✓						
=	✓	✓		✓		✓	
>>	✓						
@	✓						
@(geometry,box2df)	✓			✓		✓	
@(box2df,geometry)	✓			✓		✓	
@(box2df,box2df)	✓			✓		✓	
&>	✓						
>>	✓						
~	✓						
~(geometry,box2df)	✓			✓		✓	
~(box2df,geometry)	✓			✓		✓	
~(box2df,box2df)	✓			✓		✓	
~=	✓					✓	
<->	✓	✓					
=	✓						
<#>	✓						
<<->>	✓						
ST_3DIntersects	✓		✓		✓	✓	✓
ST_Contains	✓				✓		
ST_ContainsProperly	✓						
ST_CoveredBy	✓	✓					
ST_Covers	✓	✓					
ST_Crosses	✓				✓		
ST_Disjoint	✓				✓		

Function	geom	geog	2.5D	Curves	SQL MM	PS	T
ST_Equals	✓				✓		
ST_Intersects	✓	✓		✓	✓		✓
ST_LineCrossingDirection	✓						
ST_OrderingEquals	✓				✓		
ST_Overlaps	✓				✓		
ST_Relate	✓				✓		
ST_RelateMatch							
ST_Touches	✓				✓		
ST_Within	✓				✓		
ST_3DDWithin	✓		✓		✓	✓	
ST_3DDFullyWithin	✓		✓			✓	
ST_DFullyWithin	✓						
ST_DWithin	✓	✓					
ST_PointInsideCircle	✓						
ST_Area	✓	✓			✓	✓	
ST_Azimuth	✓	✓					
ST_Angle	✓						
ST_ClosestPoint	✓	✓					
ST_3DClosestPoint	✓		✓			✓	
ST_Distance	✓	✓		✓	✓		
ST_3DDistance	✓		✓		✓	✓	
ST_DistanceSphere	✓						
ST_DistanceSpheroid	✓						
ST_FrechetDistance	✓						
ST_HausdorffDistance	✓						
ST_Length	✓	✓			✓		
ST_Length2D	✓						
ST_3DLength	✓		✓		✓		
ST_LengthSphere	✓		✓				
ST_LongestLine	✓						
ST_3DLongestLine	✓		✓			✓	
ST_MaxDistance	✓						
ST_3DMaxDistance	✓		✓			✓	
ST_MinimumClearance	✓						

Function	geom	geog	2.5D	Curves	SQL MM	PS	T
ST_MinimumClearanceLine	✓						
ST_Perimeter	✓	✓			✓		
ST_Perimeter2D	✓						
ST_3DPerimeter	✓		✓		✓		
ST_ShortestLine	✓	✓					
ST_3DShortestLine	✓		✓			✓	
ST_ClipByBox2D	✓						
ST_Difference	✓		✓		✓		
ST_Intersection	✓	😄	✓		✓		
ST_MemUnion	✓		✓				
ST_Node	✓		✓				
ST_Split	✓						
ST_Subdivide	✓						
ST_SymDifference	✓		✓		✓		
ST_UnaryUnion	✓		✓				
ST_Union	✓		✓		✓		
ST_Buffer	✓	😄			✓		
ST_BuildArea	✓						
ST_Centroid	✓	✓			✓		
ST_ChaikinSmoothing	✓		✓				
ST_ConcaveHull	✓						
ST_ConvexHull	✓		✓		✓		
ST_DelaunayTriangles	✓		✓				✓
ST_FilterByM	✓						
ST_GeneratePoints	✓						
ST_GeometricMean	✓		✓				
ST_LineMerge	✓						
ST_MaximumInscribedCircle	✓						
ST_LargestEmptyCircle	✓						
ST_MinimumBoundingCircle	✓						
ST_MinimumBoundingRadius	✓						
ST_OrientedEnvelope	✓						
ST_OffsetCurve	✓						
ST_PointOnSurface	✓		✓		✓		

Function	geom	geog	2.5D	Curves	SQL MM	PS	T
ST_Polygonize	✓						
ST_ReducePrecision	✓						
ST_SharedPaths	✓						
ST_Simplify	✓						
ST_SimplifyPreserveTopology	✓						
ST_SimplifyPolygonHull	✓						
ST_SimplifyVW	✓						
ST_SetEffectiveArea	✓						
ST_TriangulatePolygon	✓						
ST_VoronoiLines	✓						
ST_VoronoiPolygons	✓						
ST_CoverageIntersectionEdges	✓						
ST_CoverageSimplify	✓						
ST_CoverageUnion	✓						
ST_Affine	✓		✓	✓		✓	✓
ST_Rotate	✓		✓	✓		✓	✓
ST_RotateX	✓		✓			✓	✓
ST_RotateY	✓		✓			✓	✓
ST_RotateZ	✓		✓	✓		✓	✓
ST_Scale	✓		✓	✓		✓	✓
ST_Translate	✓		✓	✓			
ST_TransScale	✓		✓	✓			
ST_ClusterDBSCAN	✓			✓			
ST_ClusterIntersecting	✓						
ST_ClusterIntersectingWin	✓						
ST_ClusterKMeans	✓						
ST_ClusterWithin	✓			✓			
ST_ClusterWithin/in	✓			✓			
Box2D	✓			✓		✓	✓
Box3D	✓		✓	✓		✓	✓
ST_EstimatedExtent	✗			✓			
ST_Expand	✓					✓	✓
ST_Extent	✓					✓	✓
ST_3DExtent	✓		✓	✓		✓	✓

Function	geom	geog	2.5D	Curves	SQL MM	PS	T
ST_MakeBox2D	✓						
ST_3DMakeBox	✓						
ST_XMax	✓		✓	✓			
ST_XMin	✓		✓	✓			
ST_YMax	✓		✓	✓			
ST_YMin	✓		✓	✓			
ST_ZMax	✓		✓	✓			
ST_ZMin	✓		✓	✓			
ST_LineInterpolatePoint	✓	✓	✓				
ST_3DLineInterpolatePoint	✓		✓				
ST_LineInterpolatePoints	✓	✓	✓				
ST_LineLocatePoint	✓	✓					
ST_LineSubstring	✓	✓	✓				
ST_LocateAlong	✓				✓		
ST_LocateBetween	✓				✓		
ST_LocateBetweenElevations	✓		✓				
ST_InterpolatePoint	✓		✓				
ST_AddMeasure	✓		✓				
ST_IsValidTrajectory	✓		✓				
ST_ClosestPoint	✓	Approach	✓				
ST_DistanceCPA	✓		✓				
ST_CPAWithin	✓		✓				
postgis.gdal_datapath							
postgis.gdal_enabled_drivers							
postgis.enable_outdb_rasters							
postgis.gdal_vsi_options							
PostGIS_AddBB	✓			✓			
PostGIS_DropBB	✓			✓			
PostGIS_HasBB	✓			✓			
postgis_sfcgal_version							
postgis_sfcgal_full_version							
CG_ForceLHR							
CG_IsPlanar							
CG_IsSolid							
CG_MakeSolid							

Function	geom	geog	2.5D	Curves	SQL MM	PS	T
CG_Orientation							
CG_Area							
CG_3DArea							
CG_Volume							
ST_ForceLHR							
ST_IsPlanar							
ST_IsSolid							
ST_MakeSolid							
ST_Orientation							
ST_3DArea							
ST_Volume							
CG_Intersection							
CG_Intersects							
CG_3DIntersec							
CG_Difference							
ST_3DDifference							
CG_3DDifference							
CG_Distance							
CG_3DDistance							
ST_3DConvexH							
CG_3DConvexH							
ST_3DIntersect							
CG_3DIntersec							
CG_Union							

Function	geom	geog	2.5D	Curves	SQL MM	PS	T
ST_3DUnion							
CG_3DUnion							
ST_AlphaShape✓							
CG_AlphaShape							
CG_ApproxConvexPartition							
ST_ApproximateMedialAxis							
CG_ApproximateMedialAxis							
ST_ConstrainedDelaunayTriangles							
CG_ConstrainedDelaunayTriangles							
ST_Extrude							
CG_Extrude							
CG_ExtrudeStraightSkeleton							
CG_GreeneApproxConvexPartition							
ST_MinkowskiSum							
CG_MinkowskiSum							
ST_OptimalAlphaShape							
CG_OptimalAlphaShape							
CG_OptimalConvexPartition							
CG_StraightSkeleton							
ST_StraightSkeleton							
ST_Tessellate							
CG_Tessellate							
CG_Triangulate							
CG_Visibility							

Function	geom	geog	2.5D	Curves	SQL MM	PS	T
CG_YMonotone	3D						
getfaceedges_returntype							
TopoGeometry							
validate_topology_returntype							
TopoElement							
TopoElementArray							
AddTopoGeometryColumn							
RenameTopoGeometryColumn							
DropTopology							
RenameTopology							
DropTopoGeometryColumn							
Populate_Topology_Layer							
TopologySummary							
ValidateTopology	✓						
ValidateTopologyRelation							
FindTopology							
FindLayer							
CreateTopology							
CopyTopology							
ST_InitTopoGeo					✓		
ST_CreateTopoGeo	✓				✓		
TopoGeo_AddPolygon	✓						
TopoGeo_AddLineString	✓						
TopoGeo_AddPolygon	✓						
TopoGeo_LoadGeometry	✓						
ST_AddIsoNode	✓				✓		
ST_AddIsoEdge	✓				✓		
ST_AddEdgeNewFaces	✓				✓		
ST_AddEdgeModifyFace	✓				✓		
ST_RemEdgeNewFace					✓		
ST_RemEdgeModFace					✓		
ST_ChangeEdgeGeom	✓				✓		
ST_ModEdgeSplit	✓				✓		
ST_ModEdgeHeal					✓		
ST_NewEdgeHeal					✓		
ST_MoveIsoNode	✓				✓		
ST_NewEdgesSplit	✓				✓		
ST_RemoveIsoNode					✓		
ST_RemoveIsoEdge					✓		
GetEdgeByPoint	✓						

Function	geom	geog	2.5D	Curves	SQL MM	PS	T
GetFaceByPoint	✓						
GetFaceContains	✓ Point						
GetNodeByPoint	✓						
GetTopologyID							
GetTopologySRID							
GetTopologyName							
ST_GetFaceEdges					✓		
ST_GetFaceGeometry	✓ try				✓		
GetRingEdges							
GetNodeEdges							
Polygonize							
AddNode	✓						
AddEdge	✓						
AddFace	✓						
ST_Simplify	✓						
RemoveUnusedNodes	✓ natives						
CreateTopoGeometry	✓						
toTopoGeom	✓						
TopoElementArray_Agg							
TopoElement	✓						
clearTopoGeom	✓						
TopoGeom_addLineament	✓						
TopoGeom_removeLineament	✓						
TopoGeom_addTopoGeometry	✓						
toTopoGeom							
GetTopoGeomElementArray							
GetTopoGeomElements							
ST_SRID	✓				✓		
AsGML	✓						
AsTopoJSON	✓						
Equals	✓		✓				
Intersects	✓		✓				
geomval							
addbandarg							
rastbandarg							
raster							
reclassarg							
summarystats							
unionarg							
AddRasterConstraints							
DropRasterConstraints							
AddOverviewConstraints							

Function	geom	geog	2.5D	Curves	SQL MM	PS	T
DropOverviewConstraints							
PostGIS_GDAL_Version							
PostGIS_Raster_Lib_Build_Date							
PostGIS_Raster_Lib_Version							
ST_GDALDrivers							
ST_Contour							
ST_InterpolateF [✓] er							
UpdateRasterSRID							
ST_CreateOverview							
ST_AddBand							
ST_AsRaster [✓]							
ST_Band							
ST_MakeEmptyCoverage							
ST_MakeEmptyRaster							
ST_Tile							
ST_Retile [✓]							
ST_FromGDALRaster							
ST_GeoReference							
ST_Height							
ST_IsEmpty							
ST_MemSize							
ST_MetaData							
ST_NumBands							
ST_PixelHeight							
ST_PixelWidth							
ST_ScaleX							
ST_ScaleY							
ST_RasterToWorldCoord							
ST_RasterToWorldCoordX							
ST_RasterToWorldCoordY							
ST_Rotation							
ST_SkewX							
ST_SkewY							
ST_SRID							
ST_Summary							
ST_UpperLeftX							
ST_UpperLeftY							
ST_Width							
ST_WorldToRas [✓] Coord							
ST_WorldToRas [✓] CoordX							
ST_WorldToRas [✓] CoordY							
ST_BandMetaData							
ST_BandNoDataValue							
ST_BandIsNoData							
ST_BandPath							
ST_BandFileSize							
ST_BandFileTimestamp							
ST_BandPixelType							
ST_MinPossibleValue							
ST_HasNoBand							
ST_PixelAsPoly [✓]							

Function	geom	geog	2.5D	Curves	SQL MM	PS	T
ST_PixelAsPolygons							
ST_PixelAsPoint	✓						
ST_PixelAsPoints							
ST_PixelAsCentroids	✓						
ST_PixelAsCentroids							
ST_Value	✓						
ST_NearestValue	✓						
ST_SetZ	✓						
ST_SetM	✓						
ST_Neighborhood	✓						
ST_SetValue	✓						
ST_SetValues							
ST_DumpValues							
ST_PixelOfValue							
ST_SetGeoReference							
ST_SetRotation							
ST_SetScale							
ST_SetSkew							
ST_SetSRID							
ST_SetUpperLeft							
ST_Resample							
ST_Rescale							
ST_Reskew							
ST_SnapToGrid							
ST_Resize							
ST_Transform							
ST_SetBandNoDataValue							
ST_SetBandIsNoData							
ST_SetBandPath							
ST_SetBandIndex							
ST_Count							
ST_CountAgg							
ST_Histogram							
ST_Quantile							
ST_SummaryStats							
ST_SummaryStatsAgg							
ST_ValueCount							
ST_RastFromWKB							
ST_RastFromHexWKB							
ST_AsBinary/ST_AsWKB							
ST_AsHexWKB							
ST_AsGDALRaster							
ST_AsJPEG							
ST_AsPNG							
ST_AsTIFF							
ST_Clip	✓						
ST_ColorMap							
ST_Grayscale							
ST_Intersection	✓						

Function	geom	geog	2.5D	Curves	SQL MM	PS	T
ST_MapAlgebra (callback function version)							
ST_MapAlgebra (expres- sion version)							
ST_MapAlgebraExpr							
ST_MapAlgebraExpr							
ST_MapAlgebraFct							
ST_MapAlgebraFct							
ST_MapAlgebraFctNgb							
ST_Reclass							
ST_Union							
ST_Distinct4ma							
ST_InvDistWeight4ma							
ST_Max4ma							
ST_Mean4ma							
ST_Min4ma							
ST_MinDist4ma							
ST_Range4ma							
ST_StdDev4ma							
ST_Sum4ma							
ST_Aspect							
ST_HillShade							
ST_Roughness							
ST_Slope							
ST_TPI							
ST_TRI							
Box3D							
ST_ConvexHull	✓						
ST_DumpAsPolygons							
ST_Envelope	✓						
ST_MinConvexHull	✓						
ST_Polygon	✓						
&&	✓						
&<							
&>							
=							
@	✓						
~ =							
~	✓						
ST_Contains							
ST_ContainsProperly							
ST_Covers							
ST_CoveredBy							
ST_Disjoint							
ST_Intersects	✓						
ST_Overlaps							

Function	geom	geog	2.5D	Curves	SQL MM	PS	T
ST_Touches							
ST_SameAlignment							
ST_NotSameAlignmentReason							
ST_Within							
ST_DWithin							
ST_DFullyWithin							
stdaddr							
rules							
table							
lex table							
gaz table							
debug_standardize_address							
parse_address							
standardize_address							
Drop_Indexes_Generate_Script							
Drop_Nation_Tables_Generate_Script							
Drop_State_Tables_Generate_Script							
Geocode	✓						
Geocode_Intersection	✓						
Get_Geocode_Setting							
Get_Tract	✓						
Install_Missing_Indexes							
Loader_Generate_Census_Script							
Loader_Generate_Script							
Loader_Generate_Nation_Script							
Missing_Indexes_Generate_Script							
Normalize_Address							
Pgc_Normalize_Address							
Pprint_Addy							
Reverse_Geocode	✓						
Topology_Load_Tiger							
Set_Geocode_Setting							

13.12 New, Enhanced or changed PostGIS Functions

13.12.1 PostGIS Functions new or enhanced in 3.5

The functions given below are PostGIS functions that were added or enhanced.

Functions new in PostGIS 3.5

- **CG_3DArea** - Availability: 3.5.0 3 维度 几何体 的面积。 返回 0 或 负值。
- **CG_3DConvexHull** - Availability: 3.5.0 3 维度 几何体 的凸包。
- **CG_3DDifference** - Availability: 3.5.0 3 维度 几何体 的差集。
- **CG_3DDistance** - Availability: 3.5.0 计算两个几何体之间的最小 3D 距离。
- **CG_3DIntersection** - Availability: 3.5.0 3 维度 几何体 的交集。
- **CG_3DIntersects** - Availability: 3.5.0 测试两个 3D 几何体是否相交。

- **CG_3DUnion** - Availability: 3.5.0 Perform 3D union using postgis_sfcgal.
- **CG_AlphaShape** - Availability: 3.5.0 - requires SFCGAL >= 1.4.1. Computes an Alpha-shape enclosing a geometry
- **CG_ApproxConvexPartition** - Availability: 3.5.0 - requires SFCGAL >= 1.5.0. Computes approximal convex partition of the polygon geometry
- **CG_ApproximateMedialAxis** - Availability: 3.5.0 返回几何的近似 medial axis.
- **CG_Area** - Availability: 3.5.0 Calculates the area of a geometry
- **CG_Difference** - Availability: 3.5.0 Computes the geometric difference between two geometries
- **CG_Distance** - Availability: 3.5.0 Computes the minimum distance between two geometries
- **CG_Extrude** - Availability: 3.5.0 将几何体沿指定方向拉伸。
- **CG_ExtrudeStraightSkeleton** - Availability: 3.5.0 - requires SFCGAL >= 1.5.0. Straight Skeleton Extrusion
- **CG_ForceLHR** - Availability: 3.5.0 LHR(Left Hand Reverse; 逆时针) 强制几何体为逆时针。
- **CG_GreeneApproxConvexPartition** - Availability: 3.5.0 - requires SFCGAL >= 1.5.0. Computes approximal convex partition of the polygon geometry
- **CG_Intersection** - Availability: 3.5.0 Computes the intersection of two geometries
- **CG_Intersects** - Availability: 3.5.0 Tests if two geometries intersect (they have at least one point in common)
- **CG_IsPlanar** - Availability: 3.5.0 测试几何体是否是平面的。
- **CG_IsSolid** - Availability: 3.5.0 测试几何体是否是实体的。返回 true 表示是实体，false 表示不是。
- **CG_MakeSolid** - Availability: 3.5.0 将几何体转换为实体。如果输入是 TIN，则返回 TIN。如果输入是其他类型，则返回 false。
- **CG_MinkowskiSum** - Availability: 3.5.0 计算两个几何体的 Minkowski 和。
- **CG_OptimalAlphaShape** - Availability: 3.5.0 - requires SFCGAL >= 1.4.1. Computes an Alpha-shape enclosing a geometry using an "optimal" alpha value.
- **CG_OptimalConvexPartition** - Availability: 3.5.0 - requires SFCGAL >= 1.5.0. Computes an optimal convex partition of the polygon geometry
- **CG_Orientation** - Availability: 3.5.0 返回几何体的 orientation (orientation) 值。
- **CG_StraightSkeleton** - Availability: 3.5.0 返回几何体的 straight skeleton (straight skeleton) 值。
- **CG_Tessellate** - Availability: 3.5.0 将几何体 tessellate (tessellation) 为 TIN 格式。
- **CG_Triangulate** - Availability: 3.5.0 Triangulates a polygonal geometry
- **CG_Union** - Availability: 3.5.0 Computes the union of two geometries
- **CG_Visibility** - Availability: 3.5.0 - requires SFCGAL >= 1.5.0. Compute a visibility polygon from a point or a segment in a polygon geometry
- **CG_Volume** - Availability: 3.5.0 3D 几何体的体积。返回 0 表示不是 3D 几何体。
- **CG_YMonotonePartition** - Availability: 3.5.0 - requires SFCGAL >= 1.5.0. Computes y-monotone partition of the polygon geometry

- **ST_HasM** - Availability: 3.5.0 Checks if a geometry has an M (measure) dimension.
- **ST_HasZ** - Availability: 3.5.0 Checks if a geometry has a Z dimension.
- **ST_RemoveIrrelevantPointsForView** - Availability: 3.5.0 Removes points that are irrelevant for rendering a specific rectangular view of a geometry.
- **ST_RemoveSmallParts** - Availability: 3.5.0 Removes small parts (polygon rings or linestrings) of a geometry.
- **TopoGeo_LoadGeometry** - Availability: 3.5.0 Load a geometry into an existing topology, snapping and splitting as needed.

Functions enhanced in PostGIS 3.5

- **ST_Clip** - Enhanced: 3.5.0 - touched argument added. Returns the raster clipped by the input geometry. If band number is not specified, all bands are processed. If crop is not specified or TRUE, the output raster is cropped. If touched is set to TRUE, then touched pixels are included, otherwise only if the center of the pixel is in the geometry it is included.

Functions changed in PostGIS 3.5

- **ST_AsGeoJSON** - Changed: 3.5.0 allow specifying the column containing the feature id Return a geometry or feature in GeoJSON format.
- **ST_DFullyWithin** - Changed: 3.5.0 : the logic behind the function now uses a test of containment within a buffer, rather than the ST_MaxDistance algorithm. Results will differ from prior versions, but should be closer to user expectations. Tests if a geometry is entirely inside a distance of another

13.12.2 PostGIS Functions new or enhanced in 3.4

The functions given below are PostGIS functions that were added or enhanced.

Functions new in PostGIS 3.4

- **PostGIS_GEOS_Compiled_Version** - Availability: 3.4.0 Returns the version number of the GEOS library against which PostGIS was built.
- **PostGIS_PROJ_Compiled_Version** - Availability: 3.5.0 Returns the version number of the PROJ library against which PostGIS was built.
- **RenameTopoGeometryColumn** - Availability: 3.4.0 Renames a topogeometry column
- **RenameTopology** - Availability: 3.4.0 Renames a topology
- **ST_ClusterIntersectingWin** - Availability: 3.4.0 Window function that returns a cluster id for each input geometry, clustering input geometries into connected sets.
- **ST_ClusterWithinWin** - Availability: 3.4.0 Window function that returns a cluster id for each input geometry, clustering using separation distance.
- **ST_CoverageInvalidEdges** - Availability: 3.4.0 Window function that finds locations where polygons fail to form a valid coverage.
- **ST_CoverageSimplify** - Availability: 3.4.0 Window function that simplifies the edges of a polygonal coverage.
- **ST_CoverageUnion** - Availability: 3.4.0 - requires GEOS >= 3.8.0 Computes the union of a set of polygons forming a coverage by removing shared edges.

- **ST_InverseTransformPipeline** - Availability: 3.4.0 Return a new geometry with coordinates transformed to a different spatial reference system using the inverse of a defined coordinate transformation pipeline.
- **ST_LargestEmptyCircle** - Availability: 3.4.0. Computes the largest circle not overlapping a geometry.
- **ST_LineExtend** - Availability: 3.4.0 Returns a line extended forwards and backwards by specified distances.
- **ST_TransformPipeline** - Availability: 3.4.0 Return a new geometry with coordinates transformed to a different spatial reference system using a defined coordinate transformation pipeline.
- **TopoElement** - Availability: 3.4.0 Converts a topogeometry to a topoelement.
- **debug_standardize_address** - Availability: 3.4.0 Returns a json formatted text listing the parse tokens and standardizations
- **postgis_srs** - Availability: 3.4.0 Return a metadata record for the requested authority and srid.
- **postgis_srs_all** - Availability: 3.4.0 Return metadata records for every spatial reference system in the underlying Proj database.
- **postgis_srs_codes** - Availability: 3.4.0 Return the list of SRS codes associated with the given authority.
- **postgis_srs_search** - Availability: 3.4.0 Return metadata records for projected coordinate systems that have areas of usage that fully contain the bounds parameter.

Functions enhanced in PostGIS 3.4

- **PostGIS_Full_Version** - Enhanced: 3.4.0 now includes extra PROJ configurations NETWORK_ENABLED, URL_ENDPOINT and DATABASE_PATH of proj.db location Reports full PostGIS version and build configuration infos.
- **PostGIS_PROJ_Version** - Enhanced: 3.4.0 now includes NETWORK_ENABLED, URL_ENDPOINT and DATABASE_PATH of proj.db location Returns the version number of the PROJ4 library.
- **ST_AsSVG** - Enhanced: 3.4.0 to support all curve types Returns SVG path data for a geometry.
- **ST_ClosestPoint** - Enhanced: 3.4.0 - Support for geography. Returns the 2D point on g1 that is closest to g2. This is the first point of the shortest line from one geometry to the other.
- **ST_LineSubstring** - Enhanced: 3.4.0 - Support for geography was introduced. Returns the part of a line between two fractional locations.
- **ST_Project** - Enhanced: 3.4.0 Allow geometry arguments and two-point form omitting azimuth. Returns a point projected from a start point by a distance and bearing (azimuth).
- **ST_Resample** - Enhanced: 3.4.0 max and min resampling options added `ST_Resample(geometry, geometry, resampling_algorithm, max_size, min_size)`.
- **ST_Rescale** - Enhanced: 3.4.0 max and min resampling options added Resample a raster by adjusting only its scale (or pixel size). New pixel values are computed using the NearestNeighbor (english or american spelling), Bilinear, Cubic, CubicSpline, Lanczos, Max or Min resampling algorithm. Default is NearestNeighbor.
- **ST_ShortestLine** - Enhanced: 3.4.0 - support for geography. `ST_ShortestLine(geometry, geometry, geography_srid)`.

Functions changed in PostGIS 3.4

- **PostGIS_Extensions_Upgrade** - Changed: 3.4.0 to add target_version argument. Packages and upgrades PostGIS extensions (e.g. postgis_raster, postgis_topology, postgis_sfcgal) to given or latest version.

13.12.3 PostGIS Functions new or enhanced in 3.3

The functions given below are PostGIS functions that were added or enhanced.

Functions new in PostGIS 3.3

- **RemoveUnusedPrimitives** - Availability: 3.3.0 Removes topology primitives which not needed to define existing TopoGeometry objects.
- **ST_3DConvexHull** - Availability: 3.3.0 计算3D凸包。
- **ST_3DUnion** - Availability: 3.3.0 aggregate variant was added Perform 3D union.
- **ST_AsMARC21** - Availability: 3.3.0 Returns geometry as a MARC21/XML record with a geographic datafield (034).
- **ST_GeomFromMARC21** - Availability: 3.3.0, requires libxml2 2.6+ Takes MARC21/XML geographic data as input and returns a PostGIS geometry object.
- **ST_Letters** - Availability: 3.3.0 Returns the input letters rendered as geometry with a default start position at the origin and default text height of 100.
- **ST_OptimalAlphaShape** - Availability: 3.3.0 - requires SFCGAL >= 1.4.1. Computes an Alpha-shape enclosing a geometry using an "optimal" alpha value.
- **ST_SimplifyPolygonHull** - Availability: 3.3.0. Computes a simplified topology-preserving outer or inner hull of a polygonal geometry.
- **ST_TriangulatePolygon** - Availability: 3.3.0. Computes the constrained Delaunay triangulation of polygons
- **postgis_sfcgal_full_version** - Availability: 3.3.0 Returns the full version of SFCGAL in use including CGAL and Boost versions

Functions enhanced in PostGIS 3.3

- **ST_ConcaveHull** - Enhanced: 3.3.0, GEOS native implementation enabled for GEOS 3.11+ Computes a possibly concave geometry that contains all input geometry vertices
- **ST_LineMerge** - Enhanced: 3.3.0 accept a directed parameter. Return the lines formed by sewing together a MultiLineString.

Functions changed in PostGIS 3.3

- **PostGIS_Extensions_Upgrade** - Changed: 3.3.0 support for upgrades from any PostGIS version. Does not work on all systems. Packages and upgrades PostGIS extensions (e.g. postgis_raster, postgis_topology, postgis_sfcgal) to given or latest version.

13.12.4 PostGIS Functions new or enhanced in 3.2

The functions given below are PostGIS functions that were added or enhanced.

Functions new in PostGIS 3.2

- **FindLayer** - Availability: 3.2.0 Returns a topology.layer record by different means.
- **FindTopology** - Availability: 3.2.0 Returns a topology record by different means.
- **GetFaceContainingPoint** - Availability: 3.2.0 Finds the face containing a point.
- **ST_AsFlatGeobuf** - Availability: 3.2.0 Return a FlatGeobuf representation of a set of rows.

- **ST_Contour** - Availability: 3.2.0 Generates a set of vector contours from the provided raster band, using the GDAL contouring algorithm.
- **ST_DumpSegments** - Availability: 3.2.0 返回几何体中的每个线段。
- **ST_FromFlatGeobuf** - Availability: 3.2.0 Reads FlatGeobuf data.
- **ST_FromFlatGeobufToTable** - Availability: 3.2.0 Creates a table based on the structure of FlatGeobuf data.
- **ST_InterpolateRaster** - Availability: 3.2.0 Interpolates a gridded surface based on an input set of 3-d points, using the X- and Y-values to position the points on the grid and the Z-value of the points as the surface elevation.
- **ST_SRID** - Availability: 3.2.0 Returns the spatial reference identifier for a topogeometry.
- **ST_Scroll** - Availability: 3.2.0 Change start point of a closed LineString.
- **ST_SetM** - Availability: 3.2.0 Returns a geometry with the same X/Y coordinates as the input geometry, and values from the raster copied into the M dimension using the requested resample algorithm.
- **ST_SetZ** - Availability: 3.2.0 Returns a geometry with the same X/Y coordinates as the input geometry, and values from the raster copied into the Z dimension using the requested resample algorithm.
- **TopoGeom_addTopoGeom** - Availability: 3.2 Adds element of a TopoGeometry to the definition of another TopoGeometry.
- **ValidateTopologyRelation** - Availability: 3.2.0 Returns info about invalid topology relation records
- **postgis.gdal_vsi_options** - Availability: 3.2.0 DB 支持 GDAL 的 VSI 选项。

Functions enhanced in PostGIS 3.2

- **GetFaceByPoint** - Enhanced: 3.2.0 more efficient implementation and clearer contract, stops working with invalid topologies. Finds face intersecting a given point.
- **ST_ClusterKMeans** - Enhanced: 3.2.0 Support for max_radius Window function that returns a cluster id for each input geometry using the K-means algorithm.
- **ST_MakeValid** - Enhanced: 3.2.0, added algorithm options, 'linework' and 'structure' which requires GEOS >= 3.10.0. Attempts to make an invalid geometry valid without losing vertices.
- **ST_PixelAsCentroid** - 新特性: 2.1.0 返回几何体中像素的质心。返回的质心坐标与像素的 X、Y 坐标相同。
- **ST_PixelAsCentroids** - 新特性: 2.1.0 返回几何体中像素的质心。返回的质心坐标与像素的 X、Y 坐标相同。
- **ST_Point** - Enhanced: 3.2.0 srid as an extra optional argument was added. Older installs require combining with ST_SetSRID to mark the srid on the geometry. Creates a Point with X, Y and SRID values.
- **ST_PointM** - Enhanced: 3.2.0 srid as an extra optional argument was added. Older installs require combining with ST_SetSRID to mark the srid on the geometry. Creates a Point with X, Y, M and SRID values.
- **ST_PointZ** - Enhanced: 3.2.0 srid as an extra optional argument was added. Older installs require combining with ST_SetSRID to mark the srid on the geometry. Creates a Point with X, Y, Z and SRID values.
- **ST_PointZM** - Enhanced: 3.2.0 srid as an extra optional argument was added. Older installs require combining with ST_SetSRID to mark the srid on the geometry. Creates a Point with X, Y, Z, M and SRID values.

- **ST_RemovePoint** - Enhanced: 3.2.0 Remove a point from a linestring.
- **ST_RemoveRepeatedPoints** - Enhanced: 3.2.0 Returns a version of a geometry with duplicate points removed.
- **ST_StartPoint** - Enhanced: 3.2.0 returns a point for all geometries. Prior behavior returns NULLs if input was not a LineString. Returns the first point of a LineString.
- **ST_Value** - 更新: 2.1.0 添加 exclude_nodata_value 参数。columnx, rowy 指定, 返回指定位置的 value。exclude_nodata_value 1 指定, 返回 1 指定位置的 value。exclude_nodata_value 指定, nodata 指定, 返回指定位置的 value。exclude_nodata_value 指定, 返回指定位置的 value。
- **TopoGeo_AddLineString** - Enhanced: 3.2.0 added support for returning signed identifier. Adds a linestring to an existing topology using a tolerance and possibly splitting existing edges/faces.

Functions changed in PostGIS 3.2

- **ST_Boundary** - Changed: 3.2.0 support for TIN, does not use geos, does not linearize curves。
- **ValidateTopology** - Changed: 3.2.0 added optional bbox parameter, perform face labeling and edge linking checks. Returns a set of validate_topology_return_type objects detailing issues with topology.

13.12.5 PostGIS Functions new or enhanced in 3.1

The functions given below are PostGIS functions that were added or enhanced.

Functions new in PostGIS 3.1

- **ST_Hexagon** - 2.1.0 添加。Returns a single hexagon, using the provided edge size and cell coordinate within the hexagon grid space.
- **ST_HexagonGrid** - 2.1.0 添加。Returns a set of hexagons and cell indices that completely cover the bounds of the geometry argument.
- **ST_MaximumInscribedCircle** - Availability: 3.1.0. 添加。
- **ST_ReducePrecision** - Availability: 3.1.0. Returns a valid geometry with points rounded to a grid tolerance.
- **ST_Square** - 2.1.0 添加。Returns a single square, using the provided edge size and cell coordinate within the square grid space.
- **ST_SquareGrid** - 2.1.0 添加。Returns a set of grid squares and cell indices that completely cover the bounds of the geometry argument.

Functions enhanced in PostGIS 3.1

- **ST_AsEWKT** - Enhanced: 3.1.0 support for optional precision parameter. WKT(Well-Known Text) 指定 SRID 指定。
- **ST_ClusterKMeans** - Enhanced: 3.1.0 Support for 3D geometries and weights Window function that returns a cluster id for each input geometry using the K-means algorithm.
- **ST_Difference** - Enhanced: 3.1.0 accept a gridSize parameter. Computes a geometry representing the part of geometry A that does not intersect geometry B.
- **ST_Intersection** - Enhanced: 3.1.0 accept a gridSize parameter Computes a geometry representing the shared portion of geometries A and B.

- **ST_MakeValid** - Enhanced: 3.1.0, added removal of Coordinates with NaN values. Attempts to make an invalid geometry valid without losing vertices.
- **ST_Subdivide** - Enhanced: 3.1.0 accept a gridSize parameter. Computes a rectilinear subdivision of a geometry.
- **ST_SymDifference** - Enhanced: 3.1.0 accept a gridSize parameter. Computes a geometry representing the portions of geometries A and B that do not intersect.
- **ST_TileEnvelope** -    : 2.0.0                       SRID  

Functions changed in PostGIS 3.1

- **ST_Count** - 2.2.0 Added support for ST_Count(rastertable, rastercolumn, ...) variant. The function returns the count of non-zero values in the specified column of the specified raster table. The function signature is ST_Count(rastertable name, rastercolumn name) integer. exclude_nodata_value boolean, NODATA value integer.
- **ST_Force3D** - Changed: 3.1.0. Added support for supplying a non-zero Z value. The function signature is ST_Force3D(geometry, z_value float). ST_Force3DZ(geometry, z_value float).
- **ST_Force3DM** - Changed: 3.1.0. Added support for supplying a non-zero M value. The function signature is ST_Force3DM(geometry, m_value float).
- **ST_Force3DZ** - Changed: 3.1.0. Added support for supplying a non-zero Z value. The function signature is ST_Force3DZ(geometry, z_value float).
- **ST_Force4D** - Changed: 3.1.0. Added support for supplying non-zero Z and M values. The function signature is ST_Force4D(geometry, z_value float, m_value float).
- **ST_Histogram** - Changed: 3.1.0 Removed ST_Histogram(table_name, column_name) variant. The function signature is ST_Histogram(table_name, column_name, bin_size integer, min_value float, max_value float) text[].
- **ST_Quantile** - Changed: 3.1.0 Removed ST_Quantile(table_name, column_name) variant. The function signature is ST_Quantile(table_name, column_name, quantile float, percentile float) float.
- **ST_SummaryStats** - 2.2.0 Added support for ST_SummaryStats(rastertable, rastercolumn, ...) variant. The function signature is ST_SummaryStats(rastertable name, rastercolumn name) text[].

13.12.6 PostGIS Functions new or enhanced in 3.0

The functions given below are PostGIS functions that were added or enhanced.

Functions new in PostGIS 3.0

- **CG_ConstrainedDelaunayTriangles** - 2.1.0 . Return a constrained Delaunay triangulation around the given input geometry.
- **ST_3DLineInterpolatePoint** - 2.1.0 . Returns a point interpolated along a 3D line at a fractional location.

- **ST_ConstrainedDelaunayTriangles** - 2.1.0 新特性。Return a constrained Delaunay triangulation around the given input geometry.
- **ST_TileEnvelope** - 2.1.0 新特性。Creates a rectangular Polygon in Web Mercator (SRID:3857) using the XYZ tile system.

Functions enhanced in PostGIS 3.0

- **ST_AsMVT** - Enhanced: 3.0 - added support for Feature ID. Aggregate function returning a MVT representation of a set of rows.
- **ST_Contains** - Enhanced: 3.0.0 enabled support for GEOMETRYCOLLECTION Tests if every point of B lies in A, and their interiors have a point in common
- **ST_ContainsProperly** - Enhanced: 3.0.0 enabled support for GEOMETRYCOLLECTION Tests if every point of B lies in the interior of A
- **ST_CoveredBy** - Enhanced: 3.0.0 enabled support for GEOMETRYCOLLECTION Tests if every point of A lies in B
- **ST_Covers** - Enhanced: 3.0.0 enabled support for GEOMETRYCOLLECTION Tests if every point of B lies in A
- **ST_Crosses** - Enhanced: 3.0.0 enabled support for GEOMETRYCOLLECTION Tests if two geometries have some, but not all, interior points in common
- **ST_CurveToLine** - Enhanced: 3.0.0 implemented a minimum number of segments per linearized arc to prevent topological collapse. Converts a geometry containing curves to a linear geometry.
- **ST_Disjoint** - Enhanced: 3.0.0 enabled support for GEOMETRYCOLLECTION Tests if two geometries have no points in common
- **ST_Equals** - Enhanced: 3.0.0 enabled support for GEOMETRYCOLLECTION Tests if two geometries include the same set of points
- **ST_GeneratePoints** - Enhanced: 3.0.0, added seed parameter Generates a multipoint of random points contained in a Polygon or MultiPolygon.
- **ST_GeomFromGeoJSON** - Enhanced: 3.0.0 parsed geometry defaults to SRID=4326 if not specified otherwise. GeoJSON 新特性 PostGIS 新特性。
- **ST_LocateBetween** - Enhanced: 3.0.0 - added support for POLYGON, TIN, TRIANGLE. Returns the portions of a geometry that match a measure range.
- **ST_LocateBetweenElevations** - Enhanced: 3.0.0 - added support for POLYGON, TIN, TRIANGLE. Returns the portions of a geometry that lie in an elevation (Z) range.
- **ST_Overlaps** - Enhanced: 3.0.0 enabled support for GEOMETRYCOLLECTION Tests if two geometries have the same dimension and intersect, but each has at least one point not in the other
- **ST_Relate** - Enhanced: 3.0.0 enabled support for GEOMETRYCOLLECTION Tests if two geometries have a topological relationship matching an Intersection Matrix pattern, or computes their Intersection Matrix
- **ST_Segmentize** - Enhanced: 3.0.0 Segmentize geometry now produces equal-length subsegments Returns a modified geometry/geography having no segment longer than a given distance.
- **ST_Touches** - Enhanced: 3.0.0 enabled support for GEOMETRYCOLLECTION Tests if two geometries have at least one point in common, but their interiors do not intersect
- **ST_Within** - Enhanced: 3.0.0 enabled support for GEOMETRYCOLLECTION Tests if every point of A lies in B, and their interiors have a point in common

Functions changed in PostGIS 3.0

- **PostGIS_Extensions_Upgrade** - Changed: 3.0.0 to repackage loose extensions and support postgis_raster. Packages and upgrades PostGIS extensions (e.g. postgis_raster, postgis_topology, postgis_sfcgal) to given or latest version.
- **ST_3DDistance** - Changed: 3.0.0 - SFCGAL version removed `ST_3DDistance`, `ST_3DDistance` (SRS `SRID`) 3 `ST_3DDistance` `SRID` `geom1` `geom2`.
- **ST_3DIntersects** - Changed: 3.0.0 SFCGAL backend removed, GEOS backend supports TINs. Tests if two geometries spatially intersect in 3D - only for points, linestrings, polygons, polyhedral surface (area)
- **ST_Area** - Changed: 3.0.0 - does not depend on SFCGAL anymore. `ST_Area` `geom`.
- **ST_AsGeoJSON** - Changed: 3.0.0 support records as input Return a geometry or feature in GeoJSON format.
- **ST_AsGeoJSON** - Changed: 3.0.0 output SRID if not EPSG:4326. Return a geometry or feature in GeoJSON format.
- **ST_AsKML** - Changed: 3.0.0 - Removed the "versioned" variant signature `ST_AsKML` GML 2 `ST_AsKML` GML 3 `ST_AsKML` `geom`.
- **ST_Distance** - Changed: 3.0.0 - does not depend on SFCGAL anymore. `ST_Distance` 3 `ST_Distance` (longest) `ST_Distance`.
- **ST_Intersection** - Changed: 3.0.0 does not depend on SFCGAL. Computes a geometry representing the shared portion of geometries A and B.
- **ST_Intersects** - Changed: 3.0.0 SFCGAL version removed and native support for 2D TINs added. Tests if two geometries intersect (they have at least one point in common)
- **ST_Union** - Changed: 3.0.0 does not depend on SFCGAL. Computes a geometry representing the point-set union of the input geometries.

13.12.7 PostGIS Functions new or enhanced in 2.5

The functions given below are PostGIS functions that were added or enhanced.

Functions new in PostGIS 2.5

- **PostGIS_Extensions_Upgrade** - Availability: 2.5.0 Packages and upgrades PostGIS extensions (e.g. postgis_raster, postgis_topology, postgis_sfcgal) to given or latest version.
- **ST_Angle** - Availability: 2.5.0 `ST_Angle` 3 `ST_Angle` (longest) `ST_Angle`.
- **ST_AsHexWKB** - Availability: 2.5.0 Return the Well-Known Binary (WKB) in Hex representation of the raster.
- **ST_BandFileSize** - Availability: 2.5.0 Returns the file size of a band stored in file system. If no bandnum specified, 1 is assumed.
- **ST_BandFileTimestamp** - Availability: 2.5.0 Returns the file timestamp of a band stored in file system. If no bandnum specified, 1 is assumed.
- **ST_ChaikinSmoothing** - Availability: 2.5.0 Returns a smoothed version of a geometry, using the Chaikin algorithm
- **ST_FilterByM** - Availability: 2.5.0 Removes vertices based on their M value

- **ST_Grayscale** - Availability: 2.5.0 Creates a new one-8BUI band raster from the source raster and specified bands representing Red, Green and Blue
- **ST_LineInterpolatePoints** - Availability: 2.5.0 Returns points interpolated along a line at a fractional interval.
- **ST_OrientedEnvelope** - Availability: 2.5.0. Returns a minimum-area rectangle containing a geometry.
- **ST_QuantizeCoordinates** - Availability: 2.5.0 Sets least significant bits of coordinates to zero
- **ST_RastFromHexWKB** - Availability: 2.5.0 Return a raster value from a Hex representation of Well-Known Binary (WKB) raster.
- **ST_RastFromWKB** - Availability: 2.5.0 Return a raster value from a Well-Known Binary (WKB) raster.
- **ST_SetBandIndex** - Availability: 2.5.0 Update the external band number of an out-db band
- **ST_SetBandPath** - Availability: 2.5.0 Update the external path and band number of an out-db band

Functions enhanced in PostGIS 2.5

- **ST_AsBinary/ST_AsWKB** - Enhanced: 2.5.0 Addition of ST_AsWKB Return the Well-Known Binary (WKB) representation of the raster.
- **ST_AsMVT** - Enhanced: 2.5.0 - added support parallel query. Aggregate function returning a MVT representation of a set of rows.
- **ST_AsText** - Enhanced: 2.5 - optional parameter precision introduced. `ST_AsText(geometry, precision)` WKT(Well-Known Text) `ST_AsText(geometry, precision, SRID)`
- **ST_BandMetaData** - Enhanced: 2.5.0 to include outdbbandnum, filesize and filetimestamp for outdb rasters. `ST_BandMetaData(raster)`. `ST_BandMetaData(raster, 1)`
- **ST_Buffer** - Enhanced: 2.5.0 - ST_Buffer geometry support was enhanced to allow for side buffering specification `side=both|left|right`. Computes a geometry covering all points within a given distance from a geometry.
- **ST_GeomFromGeoJSON** - Enhanced: 2.5.0 can now accept json and jsonb as inputs. GeoJSON `ST_GeomFromGeoJSON(json)` PostGIS `ST_GeomFromGeoJSON(jsonb)`.
- **ST_GeometricMedian** - Enhanced: 2.5.0 Added support for M as weight of points. `ST_GeometricMedian(geometry, weight)` (median) `ST_GeometricMedian(geometry, weight)`.
- **ST_Intersects** - Enhanced: 2.5.0 Supports GEOMETRYCOLLECTION. Tests if two geometries intersect (they have at least one point in common)
- **ST_OffsetCurve** - Enhanced: 2.5 - added support for GEOMETRYCOLLECTION and MULTILINESTRING Returns an offset line at a given distance and side from an input line.
- **ST_Scale** - Enhanced: 2.5.0 support for scaling relative to a local origin (origin parameter) was introduced. Scales a geometry by given factors.
- **ST_Split** - Enhanced: 2.5.0 support for splitting a polygon by a multiline was introduced. Returns a collection of geometries created by splitting a geometry by another geometry.
- **ST_Subdivide** - Enhanced: 2.5.0 reuses existing points on polygon split, vertex count is lowered from 8 to 5. Computes a rectilinear subdivision of a geometry.

Functions changed in PostGIS 2.5

- **ST_GDALDrivers** - Changed: 2.5.0 - add `can_read` and `can_write` columns. Returns a list of raster formats supported by PostGIS through GDAL. Only those formats with `can_write=True` can be used by `ST_AsGDALRaster`

13.12.8 PostGIS Functions new or enhanced in 2.4


The functions given below are PostGIS functions that were added or enhanced.

Functions new in PostGIS 2.4

- **ST_AsGeobuf** - 2.2.0 新增函数。Return a Geobuf representation of a set of rows.
- **ST_AsMVT** - 2.2.0 新增函数。Aggregate function returning a MVT representation of a set of rows.
- **ST_AsMVTGeom** - 2.2.0 新增函数。Transforms a geometry into the coordinate space of a MVT tile.
- **ST_Centroid** - Availability: 2.4.0 support for geography was introduced. 新增函数。
- **ST_ForcePolygonCCW** - 2.2.0 新增函数。Orients all exterior rings counter-clockwise and all interior rings clockwise.
- **ST_ForcePolygonCW** - 2.2.0 新增函数。Orients all exterior rings clockwise and all interior rings counter-clockwise.
- **ST_FrechetDistance** - Availability: 2.4.0 - requires GEOS >= 3.7.0 3 版本 (shortest) 新增函数。
- **ST_IsPolygonCCW** - 2.2.0 新增函数。Tests if Polygons have exterior rings oriented counter-clockwise and interior rings oriented clockwise.
- **ST_IsPolygonCW** - 2.2.0 新增函数。Tests if Polygons have exterior rings oriented clockwise and interior rings oriented counter-clockwise.
- **ST_MakeEmptyCoverage** - 2.2.0 新增函数。Cover georeferenced area with a grid of empty raster tiles.

Functions enhanced in PostGIS 2.4

- **Loader_Generate_Nation_Script** - Enhanced: 2.4.1 zip code 5 tabulation area (zcta5) load step was fixed and when enabled, zcta5 data is loaded as a single table called zcta5_all as part of the nation script load. 新增函数。
- **Normalize_Address** - Enhanced: 2.4.0 norm_addy object includes additional fields zip4 and address_alphanumeric. 新增函数。tiger_geocoder (TIGER 数据) 新增函数。
- **Pagc_Normalize_Address** - Enhanced: 2.4.0 norm_addy object includes additional fields zip4 and address_alphanumeric. 新增函数。tiger_geocoder (TIGER 数据) 新增函数。address_standardizer 新增函数。
- **Reverse_Geocode** - Enhanced: 2.4.1 if optional zcta5 dataset is loaded, the reverse_geocode function can resolve to state and zip even if the specific state data is not loaded. Refer to for details on loading zcta5 data. 新增函数。include_strnum_range = true 新增函数。
- **ST_AsTWKB** - Enhanced: 2.4.0 memory and speed improvements. 新增函数 TWKB(Tiny Well-Known Binary) 新增函数。

- **ST_Covers** - Enhanced: 2.4.0 Support for polygon in polygon and line in polygon added for geography type Tests if every point of B lies in A
- **ST_CurveToLine** - Enhanced: 2.4.0 added support for max-deviation and max-angle tolerance, and for symmetric output. Converts a geometry containing curves to a linear geometry.
- **ST_Project** - Enhanced: 2.4.0 Allow negative distance and non-normalized azimuth. Returns a point projected from a start point by a distance and bearing (azimuth).
- **ST_Reverse** - Enhanced: 2.4.0 support for curves was introduced. 

Functions changed in PostGIS 2.4

- **=** - Changed: 2.4.0, in prior versions this was bounding box equality not a geometric equality. If you need bounding box equality, use `isWithin`. Returns `TRUE` if the coordinates and coordinate order of geometry/geography A are the same as the coordinates and coordinate order of geometry/geography B.
- **ST_Node** - Changed: 2.4.0 this function uses `GEOSNode` internally instead of `GEOSUnaryUnion`. This may cause the resulting linestrings to have a different order and direction compared to PostGIS < 2.4. Nodes a collection of lines.

13.12.9 PostGIS Functions new or enhanced in 2.3

The functions given below are PostGIS functions that were added or enhanced.

Functions new in PostGIS 2.3

- **&&&(geometry,gidx)** - Availability: 2.3.0 support for Block Range INDEXes (BRIN) was introduced. Requires PostgreSQL 9.5+. Returns TRUE if a geometry's (cached) n-D bounding box intersects a n-D float precision bounding box (GIDX).
- **&&&(gidx,geometry)** - Availability: 2.3.0 support for Block Range INDEXes (BRIN) was introduced. Requires PostgreSQL 9.5+. Returns TRUE if a n-D float precision bounding box (GIDX) intersects a geometry's (cached) n-D bounding box.
- **&&&(gidx,gidx)** - Availability: 2.3.0 support for Block Range INDEXes (BRIN) was introduced. Requires PostgreSQL 9.5+. Returns TRUE if two n-D float precision bounding boxes (GIDX) intersect each other.
- **&&(box2df,box2df)** - Availability: 2.3.0 support for Block Range INDEXes (BRIN) was introduced. Requires PostgreSQL 9.5+. Returns TRUE if two 2D float precision bounding boxes (BOX2DF) intersect each other.
- **&&(box2df,geometry)** - Availability: 2.3.0 support for Block Range INDEXes (BRIN) was introduced. Requires PostgreSQL 9.5+. Returns TRUE if a 2D float precision bounding box (BOX2DF) intersects a geometry's (cached) 2D bounding box.
- **&&(geometry,box2df)** - Availability: 2.3.0 support for Block Range INDEXes (BRIN) was introduced. Requires PostgreSQL 9.5+. Returns TRUE if a geometry's (cached) 2D bounding box intersects a 2D float precision bounding box (BOX2DF).
- **@(box2df,box2df)** - Availability: 2.3.0 support for Block Range INDEXes (BRIN) was introduced. Requires PostgreSQL 9.5+. Returns TRUE if a 2D float precision bounding box (BOX2DF) is contained into another 2D float precision bounding box.
- **@(box2df,geometry)** - Availability: 2.3.0 support for Block Range INDEXes (BRIN) was introduced. Requires PostgreSQL 9.5+. Returns TRUE if a 2D float precision bounding box (BOX2DF) is contained into a geometry's 2D bounding box.

- **@(geometry,box2df)** - Availability: 2.3.0 support for Block Range INdices (BRIN) was introduced. Requires PostgreSQL 9.5+. Returns TRUE if a geometry's 2D bounding box is contained into a 2D float precision bounding box (BOX2DF).
- **Populate_Topology_Layer** - 2.3.0 更新内容。Adds missing entries to topology.layer table by reading metadata from topo tables.
- **ST_ClusterDBSCAN** - 2.3.0 更新内容。Window function that returns a cluster id for each input geometry using the DBSCAN algorithm.
- **ST_ClusterKMeans** - 2.3.0 更新内容。Window function that returns a cluster id for each input geometry using the K-means algorithm.
- **ST_GeneratePoints** - 2.3.0 更新内容。Generates a multipoint of random points contained in a Polygon or MultiPolygon.
- **ST_GeometricMedian** - 2.3.0 更新内容。Returns (median) geometry.
- **ST_MakeLine** - 2.0.0 更新内容。Returns a line from a set of points.
- **ST_MinimumBoundingRadius** - 2.3.0 更新内容。Returns the center point and radius of the smallest circle that contains a geometry.
- **ST_MinimumClearance** - 2.3.0 更新内容。Returns (robustness) geometry (clearance) geometry.
- **ST_MinimumClearanceLine** - 2.3.0 更新内容。GEOS 3.6.0 更新内容。Returns 2 geometries, the minimum clearance line and the minimum clearance.
- **ST_Normalize** - 2.3.0 更新内容。Returns a normalized geometry.
- **ST_Points** - 2.3.0 更新内容。Returns a set of points from a geometry.
- **ST_VoronoiLines** - 2.3.0 更新内容。Returns the boundaries of the Voronoi diagram of the vertices of a geometry.
- **ST_VoronoiPolygons** - 2.3.0 更新内容。Returns the cells of the Voronoi diagram of the vertices of a geometry.
- **ST_WrapX** - Availability: 2.3.0 requires GEOS X 更新内容。
- **TopoGeom_addElement** - 2.3 更新内容。Adds an element to the definition of a TopoGeometry.
- **TopoGeom_remElement** - 2.3 更新内容。Removes an element from the definition of a TopoGeometry.
- **~(box2df,box2df)** - Availability: 2.3.0 support for Block Range INdices (BRIN) was introduced. Requires PostgreSQL 9.5+. Returns TRUE if a 2D float precision bounding box (BOX2DF) contains another 2D float precision bounding box (BOX2DF).
- **~(box2df,geometry)** - Availability: 2.3.0 support for Block Range INdices (BRIN) was introduced. Requires PostgreSQL 9.5+. Returns TRUE if a 2D float precision bounding box (BOX2DF) contains a geometry's 2D bonding box.
- **~(geometry,box2df)** - Availability: 2.3.0 support for Block Range INdices (BRIN) was introduced. Requires PostgreSQL 9.5+. Returns TRUE if a geometry's 2D bonding box contains a 2D float precision bounding box (GIDX).

Functions enhanced in PostGIS 2.3

- **ST_Contains** - Enhanced: 2.3.0 Enhancement to PIP short-circuit extended to support MultiPoints with few points. Prior versions only supported point in polygon. Tests if every point of B lies in A, and their interiors have a point in common
- **ST_Covers** - Enhanced: 2.3.0 Enhancement to PIP short-circuit for geometry extended to support MultiPoints with few points. Prior versions only supported point in polygon. Tests if every point of B lies in A
- **ST_Expand** - Enhanced: 2.3.0 support was added to expand a box by different amounts in different dimensions. Returns a bounding box expanded from another bounding box or a geometry.
- **ST_Intersects** - Enhanced: 2.3.0 Enhancement to PIP short-circuit extended to support MultiPoints with few points. Prior versions only supported point in polygon. Tests if two geometries intersect (they have at least one point in common)
- **ST_Segmentize** - Enhanced: 2.3.0 Segmentize geography now produces equal-length subsegments. Returns a modified geometry/geography having no segment longer than a given distance.
- **ST_Transform** - Enhanced: 2.3.0 support for direct PROJ.4 text was introduced. Return a new geometry with coordinates transformed to a different spatial reference system.
- **ST_Within** - Enhanced: 2.3.0 Enhancement to PIP short-circuit for geometry extended to support MultiPoints with few points. Prior versions only supported point in polygon. Tests if every point of A lies in B, and their interiors have a point in common

Functions changed in PostGIS 2.3

- **ST_PointN** - 更新: 2.3.0 更新 (1 更新) ST_LineString ST_CircularString 更新。

13.12.10 PostGIS Functions new or enhanced in 2.2

The functions given below are PostGIS functions that were added or enhanced.

Functions new in PostGIS 2.2

- **<<->** - 2.2.0 更新。PostgreSQL 9.1 KNN 更新。Returns the n-D distance between the A and B geometries or bounding boxes
- **ST_3DDifference** - 2.2.0 更新。3 更新。
- **ST_3DUnion** - 2.2.0 更新。Perform 3D union.
- **ST_ApproximateMedialAxis** - 2.2.0 更新。更新。
- **ST_AsEncodedPolyline** - 2.2.0 更新。更新。
- **ST_AsTWKB** - 2.2.0 更新。更新 TWKB(Tiny Well-Known Binary) 更新。
- **ST_BoundingDiagonal** - 2.2.0 更新。更新。
- **ST_CPAWithin** - 2.2.0 更新。Tests if the closest point of approach of two trajectories is within the specified distance.
- **ST_ClipByBox2D** - 2.2.0 更新。Computes the portion of a geometry falling within a rectangle.
- **ST_ClosestPointOfApproach** - 2.2.0 更新。Returns a measure at the closest point of approach of two trajectories.

- ST_ClusterIntersecting** - 2.2.0 `geometry geometry`. Aggregate function that clusters input geometries into connected sets.
- ST_ClusterWithin** - 2.2.0 `geometry geometry float`. Aggregate function that clusters geometries by separation distance.
- ST_CountAgg** - 2.2.0 `geometry integer`. `count_aggregate(geometry)`. Returns the count of geometries in a set. `exclude_nodata_value` boolean, NODATA values are excluded.
- ST_CreateOverview** - 2.2.0 `geometry geometry integer`. Returns the overview geometry of a geometry.
- ST_DistanceCPA** - 2.2.0 `geometry geometry`. Returns the distance between the closest point of approach of two trajectories.
- ST_ForceCurve** - 2.2.0 `geometry integer`. Returns the geometry as a curve, upcast if needed.
- ST_IsPlanar** - 2.2.0 `geometry boolean`. Returns true if the geometry is planar, false otherwise.
- ST_IsSolid** - 2.2.0 `geometry boolean`. Returns true if the geometry is solid, false otherwise.
- ST_IsValidTrajectory** - 2.2.0 `geometry boolean`. Tests if the geometry is a valid trajectory.
- ST_LineFromEncodedPolyline** - 2.2.0 `text integer`. Returns the geometry from an encoded polyline.
- ST_MakeSolid** - 2.2.0 `geometry boolean`. Returns the geometry as a solid, TIN if needed.
- ST_MapAlgebra (callback function version)** - 2.2.0 `geometry mask geometry callback`. Returns the result of applying a callback function to each pixel of the mask geometry.
- ST_MemSize** - 2.2.0 `geometry integer`. Returns the memory size of a geometry.
- ST_RemoveRepeatedPoints** - 2.2.0 `geometry`. Returns a version of a geometry with duplicate points removed.
- ST_Retile** - 2.2.0 `geometry integer integer`. Returns the geometry as a grid of tiles.
- ST_SetEffectiveArea** - 2.2.0 `geometry`. Sets the effective area for each vertex, using the Visvalingam-Whyatt algorithm.
- ST_SimplifyVW** - 2.2.0 `geometry float`. Returns a simplified representation of a geometry, using the Visvalingam-Whyatt algorithm.
- ST_Subdivide** - 2.2.0 `geometry integer`. Computes a rectilinear subdivision of a geometry.
- ST_SummaryStatsAgg** - 2.2.0 `geometry`. Returns summary statistics for a geometry.
- ST_SwapOrdinates** - 2.2.0 `geometry integer integer`. Swaps the ordinates of a geometry.
- ST_Volume** - 2.2.0 `geometry integer`. Returns the volume of a 3D geometry.
- parse_address** - 2.2.0 `text`. Parses an address string.
- postgis.enable_outdb_rasters** - 2.2.0 `boolean`. DB connection parameter to enable out-of-database rasters.

- **postgis.gdal_datapath** - 2.2.0 更新内容。GDAL 的 GDAL_DATA 环境变量路径。环境变量, 环境变量 GDAL_DATA 环境变量。
- **postgis.gdal_enabled_drivers** - 2.2.0 更新内容。PostGIS 的 GDAL 的 GDAL_ENABLED_DRIVERS 环境变量。GDAL 的 GDAL_SKIP 环境变量。
- **standardize_address** - 2.2.0 更新内容。标准, 标准, 标准。stdaddr 标准。
- **|=** - 2.2.0 更新内容。PostgreSQL 9.5 的 (index-supported) 的 A 到 B 的最接近点 (closest point of approach) 的 (trajectory) 的。

Functions enhanced in PostGIS 2.2

- **<->** - 更新内容: 2.2.0 更新 -- PostgreSQL 9.5 的 KNN("K nearest neighbor") 的。KNN 的。PostgreSQL 9.4 的, 的。A 到 B 的 2 的。
- **AsTopoJSON** - 更新内容: 2.2.1 的 (pungal) 的。TopoGeometry 的 TopoJSON 的。
- **ST_Area** - 更新内容: 2.2.0 的 GeographicLib 的。Proj 4.9.0 的。
- **ST_AsX3D** - 更新内容: 2.2.0 的 (x/y, 的/的) 的。X3D XML 的: ISO-IEC-19776-1.2-X3DEncodings-XML 的。
- **ST_Azimuth** - 更新内容: 2.2.0 的 GeographicLib 的。Proj 4.9.0 的。2 的。
- **ST_Distance** - 更新内容: 2.2.0 的 GeographicLib 的。Proj 4.9.0 的。3 的 (longest) 的。
- **ST_Scale** - Enhanced: 2.2.0 support for scaling all dimension (factor parameter) was introduced. Scales a geometry by given factors.
- **ST_Split** - Enhanced: 2.2.0 support for splitting a line by a multiline, a multipoint or (multi)polygon boundary was introduced. Returns a collection of geometries created by splitting a geometry by another geometry.
- **ST_Summary** - 更新内容: 2.2.0 的 TIN 的 (curve) 的。的。

Functions changed in PostGIS 2.2

- **<->** - 更新内容: 2.2.0 更新 -- PostgreSQL 9.5 的, 的 (Hybrid syntax) 的 PostgreSQL 2.2 的, PostgreSQL 9.5 的。A 到 B 的 2 的。
- **Get Geocode Setting** - 更新内容: 2.2.0 的 geocode settings default 的。geocode settings 的, 的 geocode settings 的。tiger.geocode_settings 的。
- **ST_3DClosestPoint** - 更新内容: 2.2.0 的 2D 的, (的 Z 到 0 的) 的 2D 的。2D 到 3D 的, 的 Z 的 Z 到 0 的。g2 的 g1 的 3 的。3D 的。

- **ST_3DArea** - 2.1.0 返回 3D 几何体的面积。3D 几何体由 3D 点或 3D 面组成。返回 0 表示空几何体。
- **ST_3DIntersection** - 2.1.0 返回 3D 几何体的交集。3D 几何体由 3D 点或 3D 面组成。
- **ST_Box2dFromGeoHash** - 2.1.0 从 GeoHash 字符串生成 BOX2D 几何体。
- **ST_ColorMap** - 2.1.0 将 8BUI 颜色 (grayscale, RGB, RGBA) 映射到 4 个通道。返回 1 表示空几何体。
- **ST_Contains** - 2.1.0 检查 rastA 是否包含 rastB。返回 1 表示包含，0 表示不包含。
- **ST_ContainsProperly** - 2.1.0 检查 rastB 是否完全包含在 rastA 内部。返回 1 表示包含，0 表示不包含。
- **ST_CoveredBy** - 2.1.0 检查 rastA 是否被 rastB 完全覆盖。返回 1 表示覆盖，0 表示不覆盖。
- **ST_Covers** - 2.1.0 检查 rastB 是否完全覆盖 rastA。返回 1 表示覆盖，0 表示不覆盖。
- **ST_DFullyWithin** - 2.1.0 检查 rastA 是否完全在 rastB 内部。返回 1 表示包含，0 表示不包含。
- **ST_DWithin** - 2.1.0 检查 rastA 是否在 rastB 内部。返回 1 表示包含，0 表示不包含。
- **ST_DelaunayTriangles** - 2.1.0 返回 Delaunay 三角剖分的顶点。Returns the Delaunay triangulation of the vertices of a geometry.
- **ST_Disjoint** - 2.1.0 检查 rastA 是否与 rastB 不相交。返回 1 表示不相交，0 表示相交。
- **ST_DumpValues** - 2.1.0 返回 2 个通道的值。
- **ST_Extrude** - 2.1.0 将 2D 几何体 extrude 成 3D 几何体。
- **ST_ForceLHR** - 2.1.0 强制 LHR (Left Hand Reverse; 左手规则) 方向。
- **ST_FromGDALRaster** - 2.1.0 从 GDAL 栅格生成几何体。
- **ST_GeomFromGeoHash** - 2.1.0 从 GeoHash 字符串生成几何体。
- **ST_InvDistWeight4ma** - 2.1.0 返回 4 个通道的距离权重。
- **ST_MapAlgebra (callback function version)** - 2.1.0 使用回调函数进行地图代数。返回 1 表示包含，0 表示不包含。
- **ST_MapAlgebra (expression version)** - 2.1.0 使用表达式进行地图代数。返回 1 表示包含，0 表示不包含。
- **ST_MinConvexHull** - 2.1.0 返回 NODATA 的最小凸包。
- **ST_MinDist4ma** - 2.1.0 返回 4 个通道的最小距离。
- **ST_MinkowskiSum** - 2.1.0 返回 Minkowski 和。
- **ST_NearestValue** - 2.1.0 返回 columnx 和 rowy 的最近值。返回 NODATA 表示空几何体。

- **ST_Neighborhood** - 2.1.0 返回栅格邻域。columnx 和 rowy, 返回的栅格邻域大小由 NODATA 值决定。返回的栅格邻域大小为 2 倍于输入栅格。
- **ST_NotSameAlignmentReason** - 2.1.0 返回栅格不匹配的原因。返回的字符串表示不匹配的原因, 返回的字符串为 "row_offset" 或 "col_offset"。
- **ST_Orientation** - 2.1.0 返回栅格的方位。返回的字符串 (orientation) 为 "vertical" 或 "horizontal"。
- **ST_Overlaps** - 2.1.0 返回栅格是否重叠。返回的布尔值表示 rastA 和 rastB 是否重叠。
- **ST_PixelAsCentroid** - 2.1.0 返回栅格的像素质心。返回的字符串 (centroid) 为 "x" 或 "y"。
- **ST_PixelAsCentroids** - 2.1.0 返回栅格的像素质心。返回的字符串 (centroid) 为 "x" 或 "y"。返回的字符串 X, Y 表示像素质心的坐标。返回的字符串为 "x" 或 "y"。
- **ST_PixelAsPoint** - 2.1.0 返回栅格的像素点。返回的字符串 (point) 为 "x" 或 "y"。
- **ST_PixelAsPoints** - 2.1.0 返回栅格的像素点。返回的字符串 (point) 为 "x" 或 "y"。返回的字符串 X, Y 表示像素点的坐标。返回的字符串为 "x" 或 "y"。
- **ST_PixelOfValue** - 2.1.0 返回栅格的像素值。返回的字符串 (value) 为 columnx, rowy 表示像素值的坐标。
- **ST_PointFromGeoHash** - 2.1.0 返回 GeoHash 点。GeoHash 字符串表示点的坐标。
- **ST_RasterToWorldCoord** - 2.1.0 返回栅格的世界坐标。返回的字符串 (x, y) 表示栅格的世界坐标。返回的字符串 1 表示栅格的世界坐标。
- **ST_Resize** - 2.1.0 返回栅格的大小。GDAL 1.6.1 返回的字符串 (size) 为 "width" 或 "height"。
- **ST_Roughness** - 2.1.0 返回栅格的粗糙度。DEM 字符串 " (roughness)" 表示栅格的粗糙度。
- **ST_SetValues** - 2.1.0 返回栅格的值。返回的字符串 (value) 为 "x" 或 "y"。
- **ST_Simplify** - 2.1.0 返回栅格的简化。返回的字符串 (simplify) 为 "Douglas-Peucker" 或 "TopoGeometry"。
- **ST_StraightSkeleton** - 2.1.0 返回栅格的直线骨架。返回的字符串 (straight skeleton) 为 "x" 或 "y"。
- **ST_Summary** - 2.1.0 返回栅格的摘要。返回的字符串 (summary) 为 "x" 或 "y"。
- **ST_TPI** - 2.1.0 返回栅格的 TPI。返回的字符串 (Topographic Position Index) 为 "x" 或 "y"。
- **ST_TRI** - 2.1.0 返回栅格的 TRI。返回的字符串 (Terrain Ruggedness Index) 为 "x" 或 "y"。
- **ST_Tessellate** - 2.1.0 返回栅格的三角网。返回的字符串 (tessellation) 为 "x" 或 "y"。返回的字符串 TIN 表示三角网的坐标。
- **ST_Tile** - 2.1.0 返回栅格的瓦片。返回的字符串 (tile) 为 "x" 或 "y"。返回的字符串为 "x" 或 "y"。
- **ST_Touches** - 2.1.0 返回栅格是否接触。返回的布尔值表示 rastA 和 rastB 是否接触。返回的字符串 TRUE 表示栅格是否接触。
- **ST_Union** - 2.1.0 返回 ST_Union(rast, unionarg) 的栅格。返回的字符串 1 表示栅格的坐标。

- **ST_Within** - 2.1.0 性能向上。rastB が rastA のサブセットかどうかを判定する。rastA が rastB のサブセットかどうかを判定する。
- **ST_WorldToRasterCoord** - 2.1.0 性能向上。X, Y(緯度, 経度) を世界座標系からラスタ座標系に変換する。
- **Set_Geocode_Setting** - 2.1.0 性能向上。ジオコード設定を管理する。
- **UpdateRasterSRID** - 2.1.0 性能向上。ラスタの SRID を更新する。
- **clearTopoGeom** - 2.1 性能向上。Clears the content of a topo geometry.
- **postgis_sfcgal_version** - 2.1.0 性能向上。SFCGAL のバージョンを返す。

Functions enhanced in PostGIS 2.1

- **ST_AddBand** - 更新: 2.1.0 addbandarg を追加。ラスタに新しいバンドを追加する (x) ラスタのバンド名を指定する。ラスタのバンド名を指定する、ラスタのバンド名を指定する。
- **ST_AddBand** - 更新: 2.1.0 DB にラスタを追加する。ラスタのバンド名を指定する (x) ラスタのバンド名を指定する。ラスタのバンド名を指定する、ラスタのバンド名を指定する。
- **ST_AsBinary/ST_AsWKB** - 更新: 2.1.0 outasin を追加。Return the Well-Known Binary (WKB) representation of the raster.
- **ST_AsGML** - 更新: 2.1.0 GML 3 ID を追加。GML 2 から GML 3 に変換する。
- **ST_Aspect** - 更新: 2.1.0 ST_MapAlgebra() を追加、interpolate_nodata を追加。ラスタの傾斜を計算する (傾斜) を追加。ラスタの傾斜を計算する。
- **ST_Boundary** - 更新: 2.1.0 ラスタの境界を返す。ラスタの境界を返す。
- **ST_Clip** - 更新: 2.1.0 C を追加。Returns the raster clipped by the input geometry. If band number is not specified, all bands are processed. If crop is not specified or TRUE, the output raster is cropped. If touched is set to TRUE, then touched pixels are included, otherwise only if the center of the pixel is in the geometry it is included.
- **ST_DWithin** - Enhanced: 2.1.0 improved speed for geography. See Making Geography faster for details. Tests if two geometries are within a given distance
- **ST_DWithin** - Enhanced: 2.1.0 support for curved geometries was introduced. Tests if two geometries are within a given distance
- **ST_Distance** - 更新: 2.1.0 性能向上。Making Geography faster を追加。3 番目の (longest) パラメータを追加。
- **ST_Distance** - 更新: 2.1.0 性能向上。3 番目の (longest) パラメータを追加。
- **ST_Distinct4ma** - 更新: 2.1.0 性能向上。2 番目のパラメータを追加。
- **ST_DumpPoints** - Enhanced: 2.1.0 Faster speed. Reimplemented as native-C. 性能向上。
- **ST_HillShade** - 更新: 2.1.0 ST_MapAlgebra() を追加、interpolate_nodata を追加。ラスタの傾斜を計算する。傾斜, 傾斜, 傾斜を計算する。

- ST_MakeValid** - Enhanced: 2.1.0, added support for GEOMETRYCOLLECTION and MULTIPOINT. Attempts to make an invalid geometry valid without losing vertices.
- ST_Max4ma** - `geometry`: 2.1.0 `geometry` 2 `geometry`. `geometry`.
 - ST_Mean4ma** - `geometry`: 2.1.0 `geometry` 2 `geometry`. `geometry`.
 - ST_Min4ma** - `geometry`: 2.1.0 `geometry` 2 `geometry`. `geometry`.
 - ST_PixelAsPolygons** - `geometry`: 2.1.0 `geometry` exclude nodata value `geometry`. `geometry` X, Y `geometry`.
 - ST_Polygon** - `geometry`: 2.1.0 `geometry` (code C `geometry`). `geometry` NODATA `geometry`.
 - ST_Range4ma** - `geometry`: 2.1.0 `geometry` 2 `geometry`. `geometry`.
 - ST_SameAlignment** - `geometry`: 2.1.0 `geometry`. `geometry`, `geometry`, `geometry` (code `geometry`) `geometry`.
 - ST_Segmentize** - `geometry`: 2.1.0 `geometry`. Returns a modified geometry/geography having no segment longer than a given distance.
 - ST_SetGeoReference** - `geometry`: 2.1.0 `geometry` ST_SetGeoReference(raster, double precision, ...) `geometry`. `geometry` 6 `geometry`. GDAL `geometry` ESRI `geometry`. `geometry` GDAL `geometry`.
 - ST_SetValue** - `geometry`: 2.1.0 `geometry` ST_SetValue() `geometry`. `geometry` ST_SetValues() `geometry` (wrapper) `geometry`. `geometry` columnx, rowy `geometry`. `geometry` 1 `geometry`, `geometry` 1 `geometry`.
 - ST_Slope** - `geometry`: 2.1.0 `geometry` ST_MapAlgebra() `geometry`, `geometry` units, scale, interpolate nodata `geometry`. `geometry` (code `geometry`) `geometry`. `geometry`.
 - ST_StdDev4ma** - `geometry`: 2.1.0 `geometry` 2 `geometry`. `geometry`.
 - ST_Sum4ma** - `geometry`: 2.1.0 `geometry` 2 `geometry`. `geometry`.
 - ST_Summary** - `geometry`: 2.1.0 `geometry`. `geometry` S `geometry`.
 - ST_Transform** - `geometry`: 2.1.0 `geometry` ST_Transform(rast, alignto) `geometry`. `geometry` NearestNeighbor, Bilinear, Cubic, CubicSpline, Lanczos `geometry`. `geometry` NearestNeighbor `geometry`.
 - ST_Union** - `geometry`: 2.1.0 `geometry` (code C `geometry`). `geometry` 1 `geometry`.
 - ST_Union** - `geometry`: 2.1.0 `geometry` ST_Union(rast) `geometry` 1 `geometry`. PostGIS `geometry`. `geometry` 1 `geometry`.

- **ST_Union** - 新增: 2.1.0 新增 ST_Union(rast, uniontype) 返回 4 个栅格数据集的并集。返回的栅格数据集 1 个数据集的并集。
- **toTopoGeom** - 新增: 2.1.0 新增 TopoGeometry 数据类型。Converts a simple Geometry into a topo geometry.

Functions changed in PostGIS 2.1

- **ST_Aspect** - 新增: 2.1.0 新增 ST_Aspect(rast) 返回栅格数据集的坡度。2.1.0 新增 ST_Aspect(rast, azimuth) 返回栅格数据集的坡度 (方位角) 值。返回的栅格数据集。
- **ST_EstimatedExtent** - Changed: 2.1.0. Up to 2.0.x this was called ST_Estimated_Extent. Returns the estimated extent of a spatial table.
- **ST_Force2D** - 新增: 2.1.0 新增, 在 2.0.x 中 ST_Force_2D 新增。返回 "2 维" 数据集。
- **ST_Force3D** - 新增: 2.1.0 新增, 在 2.0.x 中 ST_Force_3D 新增。返回 XYZ 数据集。ST_Force3DZ 新增。
- **ST_Force3DM** - 新增: 2.1.0 新增, 在 2.0.x 中 ST_Force_3DM 新增。返回 XYM 数据集。
- **ST_Force3DZ** - 新增: 2.1.0 新增, 在 2.0.x 中 ST_Force_3DZ 新增。返回 XYZ 数据集。
- **ST_Force4D** - 新增: 2.1.0 新增, 在 2.0.x 中 ST_Force_4D 新增。返回 XYZM 数据集。
- **ST_ForceCollection** - 新增: 2.1.0 新增, 在 2.0.x 中 ST_Force_Collection 新增。返回数据集。
- **ST_HillShade** - 新增: 2.1.0 新增 ST_HillShade(rast) 返回栅格数据集的阴影。2.1.0 新增 ST_HillShade(rast, azimuth) 返回栅格数据集的阴影 (方位角) 值。返回的栅格数据集。
- **ST_LineInterpolatePoint** - 新增: 2.1.0 新增, 在 2.0.x 中 ST_Line_Interpolate_Point 新增。Returns a point interpolated along a line at a fractional location.
- **ST_LineLocatePoint** - 新增: 2.1.0 新增, 在 2.0.x 中 ST_Line_Locate_Point 新增。Returns the fractional location of the closest point on a line to a point.
- **ST_LineSubstring** - 新增: 2.1.0 新增, 在 2.0.x 中 ST_Line_Substring 新增。Returns the part of a line between two fractional locations.
- **ST_PixelAsCentroids** - 新增: 2.1.1 新增 exclude_nodata_value 参数。返回栅格数据集的质心 (方位角) 值。返回的 X, Y 数据集。
- **ST_PixelAsPoints** - 新增: 2.1.1 新增 exclude_nodata_value 参数。返回栅格数据集的点。返回的 X, Y 数据集。
- **ST_PixelAsPolygons** - 新增: 2.1.1 新增 exclude_nodata_value 参数。返回栅格数据集的多边形。返回的 X, Y 数据集。
- **ST_Polygon** - 新增: 2.1.0 新增 ST_Polygon(rast) 返回栅格数据集的多边形。NODATA 返回空数据集。
- **ST_RasterToWorldCoordX** - 新增: 2.1.0 新增 ST_Raster2WorldCoordX 返回栅格数据集的 X 坐标。返回的 1 个数据集。

- **ST_RasterToWorldCoordY** - 更新: 2.1.0 新增函数 ST_Raster2WorldCoordY 返回栅格像素的 Y 坐标。返回类型是 float。精度为 1 个十进制数。
- **ST_Rescale** - 更新: 2.1.0 新增 SRID 参数。Resample a raster by adjusting only its scale (or pixel size). New pixel values are computed using the NearestNeighbor (english or american spelling), Bilinear, Cubic, CubicSpline, Lanczos, Max or Min resampling algorithm. Default is NearestNeighbor.
- **ST_Reskew** - 更新: 2.1.0 新增 SRID 参数。Resample a raster by adjusting only its skew (or pixel size). New pixel values are computed using the NearestNeighbor (english or american spelling), Bilinear, Cubic, CubicSpline 或 Lanczos 重采样算法。默认是 NearestNeighbor。
- **ST_Segmentize** - Changed: 2.1.0 As a result of the introduction of geography support, the usage ST_Segmentize('LINESTRING(1 2, 3 4)', 0.5) causes an ambiguous function error. The input needs to be properly typed as a geometry or geography. Use ST_GeomFromText, ST_GeogFromText or a cast to the required type (e.g. ST_Segmentize('LINESTRING(1 2, 3 4)::geometry, 0.5)) Returns a modified geometry/geography having no segment longer than a given distance.
- **ST_Slope** - 更新: 2.1.0 新增函数 ST_Slope 返回栅格像素的坡度。返回类型是 float。精度为 1 个十进制数。
- **ST_SnapToGrid** - 更新: 2.1.0 新增 SRID 参数。Snap a raster to a grid. New pixel values are computed using the NearestNeighbor (english or american spelling), Bilinear, Cubic, CubicSpline 或 Lanczos 重采样算法。默认是 NearestNeighbor。
- **ST_WorldToRasterCoordX** - 更新: 2.1.0 新增函数 ST_World2RasterCoordX 返回栅格像素的 X 坐标。返回类型是 float。精度为 1 个十进制数。
- **ST_WorldToRasterCoordY** - 更新: 2.1.0 新增函数 ST_World2RasterCoordY 返回栅格像素的 Y 坐标。返回类型是 float。精度为 1 个十进制数。

13.12.12 PostGIS Functions new or enhanced in 2.0

The functions given below are PostGIS functions that were added or enhanced.

Functions new in PostGIS 2.0

- **&&** - 2.0.0 新增函数。A 与 B 的逻辑与。TRUE 当且仅当 A 和 B 都为 TRUE。
- **&&&** - 2.0.0 新增函数。A 与 B 的逻辑与。TRUE 当且仅当 A 和 B 都为 TRUE。
- **<#>** - 2.0.0 新增函数。PostgreSQL 9.1 新增函数 KNN。A 与 B 的逻辑与。TRUE 当且仅当 A 和 B 都为 TRUE。
- **<->** - 2.0.0 新增函数。PostgreSQL 9.1 新增函数 KNN。A 与 B 的逻辑与。TRUE 当且仅当 A 和 B 都为 TRUE。
- **@** - 2.0.0 新增函数 raster @ raster, raster @ geometry。B 与 A 的逻辑与。TRUE 当且仅当 A 和 B 都为 TRUE。
- **@** - 2.0.5 新增函数 geometry @ raster。B 与 A 的逻辑与。TRUE 当且仅当 A 和 B 都为 TRUE。
- **AddEdge** - 2.0.0 新增函数。添加边。返回类型是 float。精度为 1 个十进制数。

- **AddFace** - 2.0.0 新增函数。添加面 (face primitive) 到面集合中。
- **AddNode** - 2.0.0 新增函数。添加节点到面集合中。需要指定 ID(nodeid) 和面 ID。
- **AddOverviewConstraints** - 2.0.0 新增函数。添加概视图 (overview) 约束。
- **AddRasterConstraints** - 2.0.0 新增函数。Adds raster constraints to a loaded raster table for a specific column that constrains spatial ref, scaling, blocksize, alignment, bands, band type and a flag to denote if raster column is regularly blocked. The table must be loaded with data for the constraints to be inferred. Returns true if the constraint setting was accomplished and issues a notice otherwise.
- **AsGML** - 2.0.0 新增函数。TopoGeometry 转 GML 格式。
- **CopyTopology** - 2.0.0 新增函数。Makes a copy of a topology (nodes, edges, faces, layers and TopoGeometries) into a new schema
- **DropOverviewConstraints** - 2.0.0 新增函数。删除概视图 (overview) 约束。
- **DropRasterConstraints** - 2.0.0 新增函数。删除 PostGIS 栅格约束。
- **Drop_Indexes_Generate_Script** - 2.0.0 新增函数。TIGER 索引生成脚本。需要指定 tiger_data 表名。
- **Drop_State_Tables_Generate_Script** - 2.0.0 新增函数。删除州 (州) 表并生成脚本。需要指定 tiger_data 表名。
- **Geocode_Intersection** - 2.0.0 新增函数。返回 2 个地址, 如, 地址交集。NAD83 坐标系, geomout, normalized address (addy) 等。TIGER 索引 (edge, face, addr) 与 PostgreSQL 索引 (soundex, levenshtein) 结合使用。
- **GetEdgeByPoint** - 2.0.0 新增函数。Finds the edge-id of an edge that intersects a given point.
- **GetFaceByPoint** - 2.0.0 新增函数。Finds face intersecting a given point.
- **GetNodeByPoint** - 2.0.0 新增函数。Finds the node-id of a node at a point location.
- **GetNodeEdges** - 2.0 新增函数。返回节点的所有边。
- **GetRingEdges** - 2.0.0 新增函数。返回面边界的所有边。
- **GetTopoGeomElements** - 2.0.0 新增函数。Returns a set of topoelement objects containing the topological element_id,element_type of the given TopoGeometry (primitive elements).
- **GetTopologySRID** - 2.0.0 新增函数。返回 topology.topology 的 SRID。
- **Get_Tract** - 2.0.0 新增函数。返回 tract (tract) 的 field (field)。

- **Install_Missing_Indexes** - 2.0.0 安装缺失索引。安装缺失索引 (join) 索引 (key) 索引。索引。
- **Loader_Generate_Census_Script** - 2.0.0 加载 Census 数据。加载 Census 数据 (州) 数据, TIGER 数据 (州) 数据 (tract), 数据 (bg), 数据 (tabblock) 数据。tiger_data 数据。数据 (州) 数据。
- **Loader_Generate_Script** - 2.0.0 加载 Census 数据。TIGER 2010 数据 (tract), 数据 (bg), 数据 (tabblock) 数据。加载 Census 数据 (州) 数据, TIGER 数据 (州) tiger_data 数据。数据 (州) 数据。加载 TIGER 2010 数据, 数据, 数据, 数据。
- **Missing_Indexes_Generate_Script** - 2.0.0 安装缺失索引。安装缺失索引 (join) 索引 (key) 索引。SQL DDL 索引。
- **Polygonize** - 2.0.0 安装缺失索引。Finds and registers all faces defined by topology edges.
- **Reverse_Geocode** - 2.0.0 安装缺失索引。安装缺失索引。include_strnum_range = true 索引, 索引。
- **ST_3DClosestPoint** - 2.0.0 安装缺失索引。g2 索引 g1 索引 3 索引。
- **ST_3DDFullyWithin** - 2.0.0 安装缺失索引。Tests if two 3D geometries are entirely within a given 3D distance
- **ST_3DDWithin** - 2.0.0 安装缺失索引。Tests if two 3D geometries are within a given 3D distance
- **ST_3DDistance** - 2.0.0 安装缺失索引。索引, 索引 (SRS 索引) 3 索引。
- **ST_3DIntersects** - 2.0.0 安装缺失索引。Tests if two geometries spatially intersect in 3D - only for points, linestrings, polygons, polyhedral surface (area)
- **ST_3DLongestLine** - 2.0.0 安装缺失索引。索引 3 索引 (longest) 索引。
- **ST_3DMaxDistance** - 2.0.0 安装缺失索引。索引, 索引 (SRS 索引) 3 索引。
- **ST_3DShortestLine** - 2.0.0 安装缺失索引。索引 3 索引 (shortest) 索引。
- **ST_AddEdgeModFace** - 2.0 安装缺失索引。索引, 索引。
- **ST_AddEdgeNewFaces** - 2.0 安装缺失索引。索引, 索引 2 索引。
- **ST_AsGDALRaster** - 2.0.0 安装缺失索引。GDAL 1.6.0 索引。Return the raster tile in the designated GDAL Raster format. Raster formats are one of those supported by your compiled library. Use ST_GDALDrivers() to get a list of formats supported by your library.
- **ST_AsJPEG** - 2.0.0 安装缺失索引。GDAL 1.6.0 索引。索引 JPEG (Joint Photographic Experts Group) 索引 (索引) 索引。索引, 索引 1 索引 3 索引。索引 3 索引 3 索引 RGB 索引。

- **ST_AsLatLonText** - 2.0 返回地理坐标的文本表示。返回格式为: 'POINT (lon lat)'。
- **ST_AsPNG** - 2.0.0 将栅格数据转换为 PNG 格式。GDAL 1.6.0 及以上版本支持。返回的 PNG 图像包含 1、3、4 个波段。如果指定了波段，则只返回指定的波段。如果指定了 2 个波段，则返回 4 个波段。如果指定了 1 个波段，则返回 RGB 或 RGBA 格式。
- **ST_AsRaster** - 2.0.0 将栅格数据转换为 PostGIS 格式。GDAL 1.6.0 及以上版本支持。PostGIS 格式为: 'PostGIS 格式'。
- **ST_AsTIFF** - 2.0.0 将栅格数据转换为 TIFF 格式。GDAL 1.6.0 及以上版本支持。Return the raster selected bands as a single TIFF image (byte array). If no band is specified or any of specified bands does not exist in the raster, then will try to use all bands.
- **ST_AsX3D** - 2.0.0 将栅格数据转换为 ISO-IEC-19776-1.2-X3DEncodings-XML 格式。返回 X3D XML 格式: ISO-IEC-19776-1.2-X3DEncodings-XML 格式。
- **ST_Aspect** - 2.0.0 计算栅格数据的坡度。返回坡度值 (0 到 90 度)。
- **ST_Band** - 2.0.0 返回栅格数据的波段名称。返回波段名称。
- **ST_BandIsNoData** - 2.0.0 返回栅格数据的波段是否为 NoData。返回 NoData 值。
- **ST_Clip** - 2.0.0 返回栅格数据被输入几何裁剪后的结果。Returns the raster clipped by the input geometry. If band number is not specified, all bands are processed. If crop is not specified or TRUE, the output raster is cropped. If touched is set to TRUE, then touched pixels are included, otherwise only if the center of the pixel is in the geometry it is included.
- **ST_CollectionHomogenize** - 2.0.0 返回几何集合的最简单表示。Returns the simplest representation of a geometry collection.
- **ST_ConcaveHull** - 2.0.0 计算输入几何的凹包。Computes a possibly concave geometry that contains all input geometry vertices
- **ST_Count** - 2.0.0 返回栅格数据中的像素数量。返回像素数量。exclude_nodata_value 参数为 TRUE 时，返回不包括 NoData 值的像素数量。
- **ST_CreateTopoGeo** - 2.0 将栅格数据转换为拓扑几何。返回拓扑几何。
- **ST_Distinct4ma** - 2.0.0 返回栅格数据的 4 邻域最大值。返回 4 邻域最大值。
- **ST_FlipCoordinates** - 2.0.0 返回几何坐标轴翻转后的结果。Returns a version of a geometry with X and Y axis flipped.
- **ST_GDALDrivers** - 2.0.0 返回支持的栅格格式。GDAL 1.6.0 及以上版本支持。Returns a list of raster formats supported by PostGIS through GDAL. Only those formats with can_write=True can be used by ST_AsGDALRaster
- **ST_GeomFromGeoJSON** - 2.0.0 将 GeoJSON 格式转换为几何。JSON-C 0.9 及以上版本支持。GeoJSON 格式为: PostGIS 格式。
- **ST_GetFaceEdges** - 2.0 返回几何的面边缘。aface 参数为 TRUE 时，返回面边缘。
- **ST_HasNoBand** - 2.0.0 返回栅格数据是否有 NoData 值。返回 NoData 值。

- **ST_HillShade** - 2.0.0 地形阴影函数。给定高度、坡度、方位角和阳光高度角，返回一个表示地形阴影的浮点值。
- **ST_Histogram** - 2.0.0 直方图函数。给定一个几何对象、一个 bin 大小（bin; 直方图 bin 大小）和一个可选的聚合函数，返回一个直方图。
- **ST_InterpolatePoint** - 2.0.0 插值点函数。给定一个几何对象、一个距离（M）和一个可选的聚合函数，返回一个插值点。
- **ST_IsEmpty** - 2.0.0 空几何体函数。给定一个几何对象，返回一个布尔值（width = 0, height = 0）。
- **ST_IsValidDetail** - 2.0.0 有效几何体详细函数。Returns a valid_detail row stating if a geometry is valid or if not a reason and a location.
- **ST_IsValidReason** - Availability: 2.0 version taking flags. Returns text stating if a geometry is valid, or a reason for invalidity.
- **ST_MakeLine** - 2.0.0 从点集创建线函数。给定一个点集，返回一个线。
- **ST_MakeValid** - 2.0.0 尝试使无效几何体有效函数。Attempts to make an invalid geometry valid without losing vertices.
- **ST_MapAlgebraExpr** - 2.0.0 地图代数表达式函数。给定一个 1 个参数：PostgreSQL 表达式，返回一个 1 个参数的表达式。
- **ST_MapAlgebraExpr** - 2.0.0 地图代数表达式函数。给定一个 2 个参数：PostgreSQL 表达式，返回一个 2 个参数的表达式。extenttype 可以是 INTERSECTION, UNION, FIRST, SECOND。
- **ST_MapAlgebraFct** - 2.0.0 地图代数函数。给定一个 1 个参数：PostgreSQL 表达式，返回一个 1 个参数的表达式。
- **ST_MapAlgebraFct** - 2.0.0 地图代数函数。给定一个 2 个参数：PostgreSQL 表达式，返回一个 2 个参数的表达式。extenttype 可以是 INTERSECTION。
- **ST_MapAlgebraFctNgb** - 2.0.0 地图代数最近邻函数。给定一个 1 个参数：PostgreSQL 表达式 (Map Algebra Nearest Neighbor) 返回一个最近邻 (neighborhood) 的 PostgreSQL 表达式。
- **ST_Max4ma** - 2.0.0 4 邻域最大值函数。
- **ST_Mean4ma** - 2.0.0 4 邻域平均值函数。
- **ST_Min4ma** - 2.0.0 4 邻域最小值函数。
- **ST_ModEdgeHeal** - 2.0 修复边缘函数。Heals two edges by deleting the node connecting them, modifying the first edge and deleting the second edge. Returns the id of the deleted node.
- **ST_MoveIsoNode** - 2.0.0 移动孤立节点函数。Moves an isolated node in a topology from one point to another. If new apoint geometry exists as a node an error is thrown. Returns description of move.
- **ST_NewEdgeHeal** - 2.0 修复边缘函数。Heals two edges by deleting the node connecting them, deleting both edges, and replacing them with an edge whose direction is the same as the first edge provided.

- **ST_Node** - 2.0.0 函数。Nodes a collection of lines.
- **ST_NumPatches** - 2.0.0 函数。返回一个多边形被分割成的 patch 数量。如果输入为 NULL，则返回 NULL。
- **ST_OffsetCurve** - 2.0 函数。Returns an offset line at a given distance and side from an input line.
- **ST_PatchN** - 2.0.0 函数。ST_Geometry 返回一个 patch。
- **ST_Perimeter** - 函数: 2.0.0 函数。Returns the length of the boundary of a polygonal geometry or geography.
- **ST_PixelAsPolygon** - 2.0.0 函数。返回一个像素对应的多边形。
- **ST_PixelAsPolygons** - 2.0.0 函数。返回一个像素对应的多边形集合。X, Y 返回像素的坐标。
- **ST_Project** - 2.0.0 函数。Returns a point projected from a start point by a distance and bearing (azimuth).
- **ST_Quantile** - 2.0.0 函数。返回一个数据集 (population) 的指定分位数 (quantile) 的值。例如, 返回 25%, 50%, 75% 分位数 (percentile) 的值。
- **ST_Range4ma** - 2.0.0 函数。返回一个 4 米范围的移动平均值。
- **ST_Reclass** - 2.0.0 函数。重新分类一个栅格。nband 返回重新分类后的栅格。nband 返回重新分类后的栅格。1 返回重新分类后的栅格。例如: 重新分类 16BUI 为 8BUI。
- **ST_RelateMatch** - 2.0.0 函数。Tests if a DE-9IM Intersection Matrix matches an Intersection Matrix pattern
- **ST_RemEdgeModFace** - 2.0 函数。Removes an edge, and if the edge separates two faces deletes one face and modifies the other face to cover the space of both.
- **ST_RemEdgeNewFace** - 2.0 函数。Removes an edge, and if the edge separates two faces deletes one face and creates a new face to cover the space of both.
- **ST_Resample** - 2.0.0 函数。GDAL 1.6.1 函数。Resample a raster by adjusting only its scale (or pixel size). New pixel values are computed using the NearestNeighbor (english or american spelling), Bilinear, Cubic, CubicSpline, Lanczos, Max or Min resampling algorithm. Default is NearestNeighbor.
- **ST_Rescale** - 2.0.0 函数。GDAL 1.6.1 函数。Resample a raster by adjusting only its scale (or pixel size). New pixel values are computed using the NearestNeighbor (english or american spelling), Bilinear, Cubic, CubicSpline, Lanczos, Max or Min resampling algorithm. Default is NearestNeighbor.
- **ST_Reskew** - 2.0.0 函数。GDAL 1.6.1 函数。Reskew (重新校准) 一个栅格。NearestNeighbor(最近邻), Bilinear, Cubic, CubicSpline 或 Lanczos 重新校准一个栅格。默认是 NearestNeighbor。
- **ST_SameAlignment** - 2.0.0 函数。检查两个栅格是否具有相同的对齐方式。如果两个栅格具有相同的对齐方式，则返回 true，否则返回 false。
- **ST_SetBandIsNoData** - 2.0.0 函数。设置 isnodata 标志。

- **ST_SharedPaths** - 2.0.0 返回共享路径的几何。如果两个几何体共享任何路径，则返回共享路径的几何。否则返回空几何。
- **ST_Slope** - 2.0.0 计算给定几何体的坡度。坡度是垂直变化与水平变化的比率。返回浮点几何。
- **ST_Snap** - 2.0.0 将几何体中的点移动到最近的指定几何体。如果点不在指定几何体上，则将其移动到最近的点。如果点已经在指定几何体上，则保持不变。
- **ST_SnapToGrid** - 2.0.0 将几何体中的点移动到最近的指定网格。GDAL 1.6.1 引入。支持 NearestNeighbor(最近邻), Bilinear, Cubic, CubicSpline 和 Lanczos 插值。NearestNeighbor 是默认值。
- **ST_Split** - Availability: 2.0.0 requires GEOS Returns a collection of geometries created by splitting a geometry by another geometry.
- **ST_StdDev4ma** - 2.0.0 计算过去 4 个移动平均的标准差。返回浮点几何。
- **ST_Sum4ma** - 2.0.0 计算过去 4 个移动平均的总和。返回浮点几何。
- **ST_SummaryStats** - 2.0.0 计算给定几何体的统计摘要。返回包含 count, sum, mean, stddev, min, max 的表。返回 1 个记录。
- **ST_Transform** - 2.0.0 将几何体从一个坐标系转换到另一个坐标系。GDAL 1.6.1 引入。支持 NearestNeighbor, Bilinear, Cubic, CubicSpline, Lanczos 插值。NearestNeighbor 是默认值。
- **ST_UnaryUnion** - 2.0.0 计算单个几何体的并集。Computes the union of the components of a single geometry.
- **ST_Union** - 2.0.0 计算多个几何体的并集。如果指定了 1，则返回所有几何体的并集。否则返回空几何。
- **ST_ValueCount** - 2.0.0 计算给定几何体中每个值的计数。返回包含 value, count 的表。如果指定了 1，则返回所有值的计数。如果指定了 NODATA，则返回 NODATA 值的计数。
- **TopoElementArray_Agg** - 2.0.0 返回一个 topoelementarray 用于一组 element_id, type arrays (topoelements)。
- **TopoGeo_AddLineString** - 2.0.0 将一条线串添加到现有的拓扑中，使用容忍度和可能拆分现有边/面。
- **TopoGeo_AddPoint** - 2.0.0 将一个点添加到现有的拓扑中。如果指定了 (split)，则可能拆分现有边/面。
- **TopoGeo_AddPolygon** - 2.0.0 将一个多边形添加到现有的拓扑中，使用容忍度和可能拆分现有边/面。返回面标识符。
- **TopologySummary** - 2.0.0 给定拓扑名称并提供摘要。Returns summary totals of types of objects in topology.
- **Topology_Load_Tiger** - 2.0.0 加载 PostGIS 中的 TIGER 数据。Returns TIGER data loaded into PostGIS.
- **toTopoGeom** - 2.0 将一个简单的 Geometry 转换为一个 topo geometry。
- **~** - 2.0.0 检查两个几何体是否相等。A 等于 B 返回 TRUE。否则返回 FALSE。

- **~ =** - 2.0.0 新增。A 与 B 是否相等。TRUE 表示相等。

Functions enhanced in PostGIS 2.0

- **&&** - 新增：2.0.0 新增 (polyhedral surface) 函数。A 与 B 是否相等。TRUE 表示相等。
- **AddGeometryColumn** - 新增：2.0.0 新增。use_typmod 参数。使用 typmod 参数。使用 typmod 参数。
- **Box2D** - 新增：2.0.0 新增，返回 TIN 的 2D 边界框。Returns a BOX2D representing the 2D extent of a geometry.
- **Box3D** - 新增：2.0.0 新增，返回 TIN 的 3D 边界框。Returns a BOX3D representing the 3D extent of a geometry.
- **CreateTopology** - 增强：2.0 增加了接受 hasZ 的签名。Creates a new topology schema and registers it in the topology.topology table.
- **Geocode** - 新增：2.0.0 新增 TIGER 2010 数据，返回地址。使用 max_results 参数。使用 NAD83 坐标系。使用 restrict_region 参数。
- **GeometryType** - 新增：2.0.0 新增，返回 TIN 的几何类型。ST_Geometry 函数。
- **Populate Geometry Columns** - 新增：2.0.0 新增。使用 use_typmod 参数。Ensures geometry columns are defined with type modifiers or have appropriate spatial constraints.
- **ST_3DExtent** - 新增：2.0.0 新增，返回 TIN 的 3D 边界框。Aggregate function that returns the 3D bounding box of geometries.
- **ST_Affine** - 新增：2.0.0 新增，返回 TIN 的 3D 仿射变换。Apply a 3D affine transformation to a geometry.
- **ST_Area** - 新增：2.0.0 新增 2 个 (polyhedral surface) 函数。返回面积。
- **ST_AsBinary** - 新增：2.0.0 新增，返回 TIN 的 OGC/ISO Well-Known Binary (WKB) 表示。Return the OGC/ISO Well-Known Binary (WKB) representation of the geometry/geography without SRID meta data.
- **ST_AsBinary** - 新增：2.0.0 新增。Return the OGC/ISO Well-Known Binary (WKB) representation of the geometry/geography without SRID meta data.
- **ST_AsBinary** - 新增：2.0.0 新增。Return the OGC/ISO Well-Known Binary (WKB) representation of the geometry/geography without SRID meta data.
- **ST_AsEWKB** - 新增：2.0.0 新增，返回 TIN 的 Extended Well-Known Binary (EWKB) 表示。Return the Extended Well-Known Binary (EWKB) representation of the geometry with SRID meta data.
- **ST_AsEWKT** - 新增：2.0.0 新增，返回 TIN 的 WKT(Well-Known Text) 表示。Return WKT(Well-Known Text) representation of the geometry with SRID meta data.
- **ST_AsGML** - 新增：2.0.0 新增。Return the GML 3 '4' representation of the geometry. GML 3 '32' 表示。Return GML 2 与 GML 3 表示。

- **ST_AsKML** - 函数: 2.0.0 将 ST_Geometry 转换为 KML 格式。支持 GML 2 和 GML 3 格式。
- **ST_Azimuth** - 函数: 2.0.0 计算两个点之间的方位角。返回 0 到 360 度的值。
- **ST_Dimension** - 函数: 2.0.0 返回 ST_Geometry 的维度 (polyhedral surface) 或 TIN 的维度。返回 0 到 3 的整数。
- **ST_Dump** - 函数: 2.0.0 将 ST_Geometry 分解为点、线、面。Returns a set of geometry_dump rows for the components of a geometry.
- **ST_DumpPoints** - 函数: 2.0.0 将 ST_Geometry 分解为点。Returns a set of geometry_dump rows for the components of a geometry.
- **ST_Expand** - 函数: 2.0.0 将 ST_Geometry 的边界框扩展指定的距离。Returns a bounding box expanded from another bounding box or a geometry.
- **ST_Extent** - 函数: 2.0.0 返回 ST_Geometry 的边界框。Aggregate function that returns the bounding box of geometries.
- **ST_Force2D** - 函数: 2.0.0 将 ST_Geometry 强制转换为 2D (polyhedral surface) 格式。返回 "2D" 格式。
- **ST_Force3D** - 函数: 2.0.0 将 ST_Geometry 强制转换为 3D (polyhedral surface) 格式。返回 XYZ 格式。
- **ST_Force3DZ** - 函数: 2.0.0 将 ST_Geometry 强制转换为 3D (polyhedral surface) 格式。返回 XYZ 格式。
- **ST_ForceCollection** - 函数: 2.0.0 将 ST_Geometry 强制转换为集合 (polyhedral surface) 格式。返回集合格式。
- **ST_ForceRHR** - 函数: 2.0.0 将 ST_Geometry 强制转换为右手规则 (polyhedral surface) 格式。返回右手规则格式 (orientation) (Right-Hand Rule) 格式。
- **ST_GMLToSQL** - 函数: 2.0.0 将 ST_Geometry 转换为 SQL 格式 (polyhedral surface) 或 TIN 格式。GML 格式转换为 ST_Geometry 格式。返回 ST_GeomFromGML 格式。
- **ST_GMLToSQL** - 函数: 2.0.0 将 ST_Geometry 转换为 SQL 格式 (polyhedral surface) 或 TIN 格式。GML 格式转换为 ST_Geometry 格式。返回 ST_GeomFromGML 格式。
- **ST_GeomFromEWKB** - 函数: 2.0.0 从 EWKB(Extended Well-Known Binary) 格式创建 ST_Geometry 对象。
- **ST_GeomFromEWKT** - 函数: 2.0.0 从 EWKT(Extended Well-Known Text) 格式创建 ST_Geometry 对象。
- **ST_GeomFromGML** - 函数: 2.0.0 从 GML 格式创建 ST_Geometry 对象 (polyhedral surface) 或 TIN 格式。返回 GML 格式 PostGIS 格式。
- **ST_GeomFromGML** - 函数: 2.0.0 从 GML 格式创建 ST_Geometry 对象 (polyhedral surface) 或 TIN 格式。返回 GML 格式 PostGIS 格式。
- **ST_GeometryN** - 函数: 2.0.0 返回 ST_Geometry 的第 N 个几何体。Returns a geometry from a set of geometries.
- **ST_GeometryType** - 函数: 2.0.0 返回 ST_Geometry 的几何类型 (polyhedral surface) 或 TIN 格式。Returns a geometry from a set of geometries.
- **ST_IsClosed** - 函数: 2.0.0 检查 ST_Geometry 是否是闭合的 (polyhedral surface) 或 TIN 格式。LINESTRING 格式返回 TRUE 或 FALSE。返回 TRUE 或 FALSE。

- **ST_MakeEnvelope** - 更新: 2.0 指定 SRID 的包络面 (envelope) 函数。指定 SRID 的 SRS 包络面。
- **ST_MakeValid** - Enhanced: 2.0.1, speed improvements Attempts to make an invalid geometry valid without losing vertices.
- **ST_NPoints** - 更新: 2.0.0 多面体表面 (polyhedral surface) 的点数。返回 (面) 的点数。
- **ST_NumGeometries** - 更新: 2.0.0 返回几何体数量, 支持 TIN 几何体。返回几何体数量。
- **ST_Relate** - Enhanced: 2.0.0 - added support for specifying boundary node rule. Tests if two geometries have a topological relationship matching an Intersection Matrix pattern, or computes their Intersection Matrix
- **ST_Rotate** - 更新: 2.0.0 多面体表面, 支持 TIN 几何体。Rotates a geometry about an origin point.
- **ST_Rotate** - Enhanced: 2.0.0 additional parameters for specifying the origin of rotation were added. Rotates a geometry about an origin point.
- **ST_RotateX** - 更新: 2.0.0 多面体表面, 支持 TIN 几何体。Rotates a geometry about the X axis.
- **ST_RotateY** - 更新: 2.0.0 多面体表面, 支持 TIN 几何体。Rotates a geometry about the Y axis.
- **ST_RotateZ** - 更新: 2.0.0 多面体表面, 支持 TIN 几何体。Rotates a geometry about the Z axis.
- **ST_Scale** - 更新: 2.0.0 多面体表面, 支持 TIN 几何体。Scales a geometry by given factors.
- **ST_ShiftLongitude** - 更新: 2.0.0 多面体表面 的 TIN 几何体。Shifts the longitude coordinates of a geometry between -180..180 and 0..360.
- **ST_Summary** - 更新: 2.0.0 返回几何体摘要。返回几何体摘要。
- **ST_Transform** - 更新: 2.0.0 多面体表面 (polyhedral surface) 的几何体。Return a new geometry with coordinates transformed to a different spatial reference system.
- **ST_Value** - 更新: 2.0.0 返回 exclude_nodata_value 的列值。指定 column, row 的几何体, 返回 exclude_nodata_value 的列值。指定 column 1 的几何体, 返回 exclude_nodata_value 的列值。exclude_nodata_value 的列值, nodata 的列值。exclude_nodata_value 的列值, nodata 的列值。
- **ValidateTopology** - 更新: 2.0.0 返回 validate_topology_return_type 的集合, 返回 validate_topology_return_type (false positive) 的集合。Returns a set of validate_topology_return_type objects detailing issues with topology.

Functions changed in PostGIS 2.0

- **AddGeometryColumn** - 更新: 2.0.0 添加 geometry columns 的函数。添加 geometry columns 的函数。指定 PostgreSQL 的 WGS84 POINT 的函数: ALTER TABLE some_table ADD COLUMN geom geometry(Point,4326);

- **AddGeometryColumn** - 更新: 2.0.0 版. `use_typmod` 引数, `geometry_columns` テーブルの `typmod` を指定する. `geometry_columns` テーブルの `typmod` を指定する. `geometry_columns` テーブルの `typmod` を指定する.
- **AddGeometryColumn** - 更新: 2.0.0 版. `geometry_columns` テーブルの `typmod` を指定する. `geometry_columns` テーブルの `typmod` を指定する. `geometry_columns` テーブルの `typmod` を指定する.
- **Box3D** - 更新: 2.0.0 版. `BOX3D` 関数は `BOX2D` 関数と同等. `BOX2D` 関数は `BOX3D` 関数と同等. `BOX3D` 関数は `BOX3D` 関数と同等.
- **DropGeometryColumn** - 更新: 2.0.0 版. `geometry_columns` テーブルの `typmod` を指定する. `ALTER TABLE` 文で `geometry_columns` テーブルの `typmod` を指定する.
- **DropGeometryTable** - 更新: 2.0.0 版. `geometry_columns` テーブルの `typmod` を指定する. `DROP TABLE` 文で `geometry_columns` テーブルの `typmod` を指定する.
- **Populate_Geometry_Columns** - 更新: 2.0.0 版. `use_typmod` 引数, `geometry_columns` テーブルの `typmod` を指定する. Ensures geometry columns are defined with type modifiers or have appropriate spatial constraints.
- **ST_3DExtent** - Changed: 2.0.0 In prior versions this used to be called `ST_Extent3D` Aggregate function that returns the 3D bounding box of geometries.
- **ST_3DLength** - 更新: 2.0.0 版. `ST_Length3D` 関数は `ST_3DLength` 関数と同等.
- **ST_3DMakeBox** - Changed: 2.0.0 In prior versions this used to be called `ST_MakeBox3D` Creates a `BOX3D` defined by two 3D point geometries.
- **ST_3DPerimeter** - 更新: 2.0.0 版. `ST_Perimeter3D` 関数は `ST_3DPerimeter` 関数と同等.
- **ST_AsBinary** - 更新: 2.0.0 版. `ST_AsBinary('POINT(1 2)')` 関数は `ST_AsBinary('POINT(1 2)::geometry')` 関数と同等. `ST_AsBinary('POINT(1 2)::geometry')` 関数は `ST_AsBinary('POINT(1 2)::geometry')` 関数と同等. `ST_AsBinary('POINT(1 2)::geometry')` 関数は `ST_AsBinary('POINT(1 2)::geometry')` 関数と同等.
- **ST_AsGML** - 更新: 2.0.0 版. `ST_AsGML` (named arg) 関数は `ST_AsGML` (named arg) 関数と同等. `ST_AsGML` (named arg) 関数は `ST_AsGML` (named arg) 関数と同等.
- **ST_AsGeoJSON** - 更新: 2.0.0 版. `ST_AsGeoJSON` (default arg) 関数は `ST_AsGeoJSON` (named arg) 関数と同等. `ST_AsGeoJSON` (named arg) 関数は `ST_AsGeoJSON` (named arg) 関数と同等.
- **ST_AsSVG** - 更新: 2.0.0 版. `ST_AsSVG` (default arg) 関数は `ST_AsSVG` (named arg) 関数と同等. `ST_AsSVG` (named arg) 関数は `ST_AsSVG` (named arg) 関数と同等.
- **ST_EndPoint** - 更新: 2.0.0 版. `ST_EndPoint` 関数は `ST_EndPoint` 関数と同等. `ST_EndPoint` 関数は `ST_EndPoint` 関数と同等. `ST_EndPoint` 関数は `ST_EndPoint` 関数と同等.
- **ST_GDALDrivers** - 更新: 2.0.6, 2.1.3 版. `GUC` 変数 `gdal_enabled_drivers` を指定する. Returns a list of raster formats supported by PostGIS through GDAL. Only those formats with `can_write=True` can be used by `ST_AsGDALRaster`.

- ### 13.12.13 PostGIS Functions new or enhanced in 1.5

Functions new in PostGIS 1.5

- **&&** - 1.5.0 新增函数。A 为 2D 几何体 B 为 2D 几何体时返回 TRUE。否则返回 FALSE。
- **PostGIS_LibXML_Version** - 1.5 新增函数。Returns the version number of the libxml2 library.
- **ST_AddMeasure** - 1.5.0 新增函数。Interpolates measures along a linear geometry.
- **ST_AsBinary** - 1.5.0 新增函数。Return the OGC/ISO Well-Known Binary (WKB) representation of the geometry/geography without SRID meta data.
- **ST_AsGML** - 1.5.0 新增函数。返回 GML 2 或 GML 3 格式。
- **ST_AsGeoJSON** - 1.5.0 新增函数。Return a geometry or feature in GeoJSON format.
- **ST_AsText** - 1.5.0 新增函数。返回/输出 WKT(Well-Known Text) 格式。SRID 信息将被保留。
- **ST_Buffer** - Availability: 1.5 - ST_Buffer was enhanced to support different endcaps and join types. These are useful for example to convert road linestrings into polygon roads with flat or square edges instead of rounded edges. Thin wrapper for geography was added. Computes a geometry covering all points within a given distance from a geometry.
- **ST_ClosestPoint** - 1.5.0 新增函数。Returns the 2D point on g1 that is closest to g2. This is the first point of the shortest line from one geometry to the other.
- **ST_CollectionExtract** - 1.5.0 新增函数。Given a geometry collection, returns a multi-geometry containing only elements of a specified type.
- **ST_Covers** - 1.5.0 新增函数。Tests if every point of B lies in A
- **ST_DFullyWithin** - 1.5.0 新增函数。Tests if a geometry is entirely inside a distance of another
- **ST_DWithin** - Availability: 1.5.0 support for geography was introduced Tests if two geometries are within a given distance
- **ST_Distance** - 1.5.0 新增函数。返回两个几何体之间的最短距离。支持 3 种模式 (longest) 模式。
- **ST_DistanceSphere** - 1.5 新增函数。1.5 新增函数。PostGIS 1.5 新增函数。
- **ST_DistanceSpheroid** - 1.5 新增函数。1.5 新增函数。PostGIS 1.5 新增函数。
- **ST_DumpPoints** - 1.5.0 新增函数。返回几何体的点。
- **ST_Envelope** - 1.5.0 新增函数，float4 精度，double precision; float8) 精度。
- **ST_Expand** - Availability: 1.5.0 behavior changed to output double precision instead of float4 coordinates. Returns a bounding box expanded from another bounding box or a geometry.
- **ST_GMLToSQL** - 1.5 新增函数。LibXML2 1.6 新增函数。GML 格式。ST_Geometry 格式。ST_GeomFromGML 格式。
- **ST_GeomFromGML** - 1.5 新增函数。LibXML2 1.6 新增函数。GML 格式。PostGIS 格式。
- **ST_GeomFromKML** - Availability: 1.5, requires libxml2 2.6+ 新增 KML 格式。PostGIS 格式。

- **ST_HausdorffDistance** - 1.5.0 更新内容。返回 3 个最短 (shortest) 距离。
- **ST_Intersection** - Availability: 1.5 support for geography data type was introduced. Computes a geometry representing the shared portion of geometries A and B.
- **ST_Intersects** - Availability: 1.5 support for geography was introduced. Tests if two geometries intersect (they have at least one point in common)
- **ST_Length** - 1.5.0 更新内容。返回 2 个最短距离。
- **ST_LongestLine** - 1.5.0 更新内容。返回 3 个最长 (longest) 距离。
- **ST_MakeEnvelope** - 1.5 更新内容。返回 SRID 相同的 SRS 几何体。
- **ST_MaxDistance** - 1.5.0 更新内容。返回 2 个最长距离。
- **ST_ShortestLine** - 1.5.0 更新内容。返回 2 个最短距离。
- **~=** - 1.5.0 更新内容。A 与 B 是否相等 TRUE 或 FALSE。

13.12.14 PostGIS Functions new or enhanced in 1.4

The functions given below are PostGIS functions that were added or enhanced.

Functions new in PostGIS 1.4

- **Populate_Geometry_Columns** - 1.4.0 更新内容。Ensures geometry columns are defined with type modifiers or have appropriate spatial constraints.
- **ST_Collect** - 1.4.0 更新内容。返回 ST_MakeLine 几何体。Creates a GeometryCollection or Multi* geometry from a set of geometries.
- **ST_ContainsProperly** - 1.4.0 更新内容。Tests if every point of B lies in the interior of A
- **ST_GeoHash** - 1.4.0 更新内容。返回 GeoHash 值。
- **ST_IsValidReason** - Availability: 1.4 Returns text stating if a geometry is valid, or a reason for invalidity.
- **ST_LineCrossingDirection** - Availability: 1.4 Returns a number indicating the crossing behavior of two LineStrings
- **ST_LocateBetweenElevations** - 1.4.0 更新内容。Returns the portions of a geometry that lie in an elevation (Z) range.
- **ST_MakeLine** - 1.4.0 更新内容。返回 ST_MakeLine 几何体。Returns a LineString geometry from a set of geometries.
- **ST_MinimumBoundingCircle** - 1.4.0 更新内容。Returns the smallest circle polygon that contains a geometry.
- **ST_Union** - Availability: 1.4.0 - ST_Union was enhanced. ST_Union(geomarray) was introduced and also faster aggregate collection in PostgreSQL. Computes a geometry representing the point-set union of the input geometries.

13.12.15 PostGIS Functions new or enhanced in 1.3

The functions given below are PostGIS functions that were added or enhanced.

Functions new in PostGIS 1.3

- **ST_AsGML** - 1.3.2 新增函数。返回 GML 2 或 GML 3 格式的数据。
 - **ST_AsGeoJSON** - 1.3.4 新增函数。返回一个几何体或特征体的 GeoJSON 格式。
 - **ST_CurveToLine** - Availability: 1.3.0 将一个包含曲线的几何体转换为线性几何体。
 - **ST_LineToCurve** - Availability: 1.3.0 将一个线性几何体转换为曲线几何体。
 - **ST_SimplifyPreserveTopology** - 1.3.3 新增函数。返回一个简化的且有效的几何体表示，使用 Douglas-Peucker 算法。
-

Chapter 14

Reporting Problems

14.1 Reporting Software Bugs

Reporting bugs effectively is a fundamental way to help PostGIS development. The most effective bug report is that enabling PostGIS developers to reproduce it, so it would ideally contain a script triggering it and every information regarding the environment in which it was detected. Good enough info can be extracted running `SELECT postgis_full_version()` [for PostGIS] and `SELECT version()` [for postgresql].

If you aren't using the latest release, it's worth taking a look at its [release changelog](#) first, to find out if your bug has already been fixed.

Using the [PostGIS bug tracker](#) will ensure your reports are not discarded, and will keep you informed on its handling process. Before reporting a new bug please query the database to see if it is a known one, and if it is please add any new information you have about it.

You might want to read Simon Tatham's paper about [How to Report Bugs Effectively](#) before filing a new report.

14.2 Reporting Documentation Issues

The documentation should accurately reflect the features and behavior of the software. If it doesn't, it could be because of a software bug or because the documentation is in error or deficient.

Documentation issues can also be reported to the [PostGIS bug tracker](#).

If your revision is trivial, just describe it in a new bug tracker issue, being specific about its location in the documentation.

If your changes are more extensive, a patch is definitely preferred. This is a four step process on Unix (assuming you already have [git](#) installed):

1. Clone the PostGIS' git repository. On Unix, type:

```
git clone https://git.osgeo.org/gitea/postgis/postgis.git
```

This will be stored in the directory `postgis`

2. Make your changes to the documentation with your favorite text editor. On Unix, type (for example):

```
vim doc/postgis.xml
```

Note that the documentation is written in DocBook XML rather than HTML, so if you are not familiar with it please follow the example of the rest of the documentation.

3. Make a patch file containing the differences from the master copy of the documentation. On Unix, type:
git diff doc/postgis.xml > doc.patch
4. Attach the patch to a new issue in bug tracker.

Appendix A

Appendix

A.1 PostGIS 3.5.7

2026/06/10

A.1.1 Bug Fixes

[5899](#), pg_upgrade issue for non-standard geography SRID (Paul Ramsey)

Flatgeobuf schema mismatch vulnerability (NeuroWinter)

[5916](#), ST_Split hang with very large ordinates (Paul Ramsey)

[5989](#), CurvePolygon distance corner case (Paul Ramsey)

[5357](#), ST_LineFromEncodedPolyline dropping close points (Paul Ramsey)

A.2 PostGIS 3.5.6

2026/04/14

A.2.1 Bug Fixes

[6055](#), Remove rare extension priv escalation case. Reported by Sven Klemm (Tiger Data), Allistair Ishmael Hakim (allistair.sh) and Daniel Bakker

[GH-850](#), Use quote_identifier to build tables in pgis_tablefromflatgeobuf (Ariel Mashraki)

[6058](#), Use Pg composite_to_json() function in 19+ (Paul Ramsey)

[6060](#), fully quality calls to helper functions (Paul Ramsey)

[6026](#), KNN failure in rare IEEE double rounding case (Paul Ramsey)

[6061](#), WKT parser produces incorrect error locations (Paul Ramsey)

A.3 PostGIS 3.5.5

2026/02/09

This version requires PostgreSQL 12-18, GEOS 3.8 or higher, and Proj 6.1+. To take advantage of all features, GEOS 3.12+ is needed. To take advantage of all SFCGAL features, SFCGAL 1.5.0+ is needed.

A.3.1 Bug Fixes

[5959](#), [#5984](#), Prevent histogram target overflow when analysing massive tables (Darafei Praliaskouski)

[6020](#), schema qualify call in ST_MPointFromText (Paul Ramsey)

[6023](#), Fix robustness issue in ptarray_contains_point (Sandro Santilli)

[6027](#), Fix RemoveUnusedPrimitives without topology in search_path (Sandro Santilli)

[6028](#), crash indexing malformed empty polygon (Paul Ramsey)

[GH-841](#), small memory leak in address_standardizer (Maxim Korotkov)

[5998](#), [tiger_geocoder] [security] CVE-2022-2625, make sure tables requires by extension are owned by extension

[5853](#), Issue with topology and tiger geocoder upgrade scripts (Regina Obe, Spencer Bryson)

A.4 PostGIS 3.5.4

2025/10/16

This version requires PostgreSQL 12-18beta1, GEOS 3.8 or higher, and Proj 6.1+. To take advantage of all features, GEOS 3.12+ is needed. To take advantage of all SFCGAL features, SFCGAL 1.5.0+ is needed.

A.4.1 Bug Fixes

[5977](#), Fix downgrade protection with standard conforming strings off (Sandro Santilli)

[5951](#), Fix crash in ST_GetFaceEdges with corrupted topology (Sandro Santilli)

[5947](#), [topology] Fix crash in ST_ModEdgeHeal (Sandro Santilli)

[5925](#), [5946](#), [topology] Have GetFaceContainingPoint survive EMPTY edges (Sandro Santilli)

[5936](#), [topology] Do script-based upgrade in a single transaction (Sandro Santilli)

[5908](#), [topology] Fix crash in GetFaceContainingPoint (Sandro Santilli)

[5907](#), [topology] Fix crash in TopoGeo_AddPolygon with EMPTY input (Sandro Santilli)

[5922](#), [topology] Fix crash in TopoGeo_AddLinestring with EMPTY input (Sandro Santilli)

[5921](#), Crash freeing uninitialized pointer (Arsenii Mukhin)

[5912](#), Crash on GML with xlink and no prefix (Paul Ramsey)

[5905](#), Crash on deeply nested geometries (Paul Ramsey)

[5909](#), ST_ValueCount crashes on empty table (Paul Ramsey)

- 5917, ST_Relate becomes unresponsive (Paul Ramsey)
- 5923, CG_ExtrudeStraightSkeleton crashes on empty polygon (Loïc Bartoletti)
- 5935, Require GDAL 2.4 for postgis_raster and switch to GDALGetDataSizeBytes (Laurențiu Nicola)
- GT-257, fix issue with xsltproc with path has spaces (Laurențiu Nicola)
- 5938, incorrect parameter order in ST_Relate caching (Paul Ramsey)
- 5927, ST_IsCollection throwing exception (Paul Ramsey)
- 5902, ST_PointFromText cannot create geometries with M (Paul Ramsey)
- 5943, Memory leak in handling GEOS GeometryFactory (Megan Ma)
- 5407, Use memset in place of bzero (Paul Ramsey)
- 5082, LRS proportions clamped to [0,1] (Pawel Ostrowski)
- 5985, Fix configure issue with Debian 12 and 13 (Regina Obe, Sandro Santilli)
- 5991, CircularString distance error (Paul Ramsey)
- 5994, Null pointer in ST_AsGeoJsonRow (Alexander Kukushkin)
- 5989, ST_Distance error on CurvePolygon (Paul Ramsey)
- 5962, Consistent clipping of MULTI/POINT (Paul Ramsey)
- 5754, ST_ForcePolygonCCW reverses lines (Paul Ramsey)

A.5 PostGIS 3.5.3

2025/05/17

This version requires PostgreSQL 12-18beta1, GEOS 3.8 or higher, and Proj 6.1+. To take advantage of all features, GEOS 3.12+ is needed. To take advantage of all SFCGAL features, SFCGAL 1.5.0+ is needed.

A.5.1 Bug Fixes

Do not complain about illegal option when calling shp2pgsql -? (Sandro Santilli, Giovanni Zezza)

5862, [topology] Prevent another topology corruption with TopoGeo_addPoint near almost collinear edges (Sandro Santilli)

5841, Change approach to interrupt handling to conform to PostgreSQL recommended practice (Paul Ramsey)

5855, Fix index binding in ST_DFullyWithin (Paul Ramsey)

5819, Support longer names in estimated extent (Paul Ramsey)

Fix misassignment of result in _lwt_HealEdges (Maxim Korotkov)

5876, ST_AddPoint with empty argument adds garbage (Paul Ramsey)

5874, Line substring returns wrong answer (Paul Ramsey)

5829, geometry_columns with non-standard constraints (Paul Ramsey)

5818, GT-244 Fix CG_IsSolid function (Loïc Bartoletti)

5885, Fix documentation about grid-based overlay operations (Sandro Santilli)

For SFCGAL 2.1.0+ prevent using deprecated functions (Regina Obe)

A.6 PostGIS 3.5.2

2025/01/18

This version requires PostgreSQL 12-17, GEOS 3.8 or higher, and Proj 6.1+. To take advantage of all features, GEOS 3.12+ is needed. To take advantage of all SFCGAL features, SFCGAL 1.5.0+ is needed.

A.6.1 Bug Fixes

[#5677](#), Retain SRID during unary union (Paul Ramsey)

[#5833](#), pg_upgrade fix for postgis_sfcgal (Regina Obe)

[#5564](#), BRIN crash fix and support for parallel in PG17+ (Paul Ramsey, Regina Obe)

A.7 PostGIS 3.5.1

2024/12/22

This version requires PostgreSQL 12-17, GEOS 3.8 or higher, and Proj 6.1+. To take advantage of all features, GEOS 3.12+ is needed. To take advantage of all SFCGAL features, SFCGAL 1.5.0+ is needed.

A.7.1 Breaking Changes

[#5677](#), Retain SRID during unary union (Paul Ramsey)

[#5792](#), [topology] Prevent topology corruption with TopoGeo_addPoint near almost collinear edges (Sandro Santilli)

[#5795](#), [topology] Fix ST_NewEdgesSplit can cause invalid topology (Björn Harrtell)

[#5794](#), [topology] Fix crash in TopoGeo_addPoint (Sandro Santilli)

[#5785](#), [raster] ST_MapAlgebra segfaults when expression references a supernumerary rast argument (Dian M Fay)

[#5787](#), Check that ST_ChangeEdgeGeom doesn't change winding of rings (Sandro Santilli)

[#5791](#), Add legacy stubs for old transaction functions to allow pg_upgrade (Regina Obe)

[#5800](#), PROJ compiled version reading the wrong minor and micro (Regina Obe)

[#5790](#), Non-schema qualified calls causing issue with materialized views (Regina Obe)

[#5812](#), Performance regression in ST_Within (Paul Ramsey)

[#5815](#), Remove hash/merge promise from <> operator (Paul Ramsey)

[#5823](#), Build support for Pg18 (Paul Ramsey)

A.7.2 Enhancements

[#5782](#), Improve robustness of min distance calculation (Sandro Santilli)

[topology] Speedup topology building when closing large rings with many holes (Björn Harrtell)

[#5810](#), Update tiger geocoder to handle TIGER 2024 data (Regina Obe)

A.7.3 Breaking Changes

[#5799](#), make ST_TileEnvelope clip envelopes to tile plane extent (Paul Ramsey)

A.8 PostGIS 3.5.0

2024/09/25

This version requires PostgreSQL 12-17, GEOS 3.8 or higher, and Proj 6.1+. To take advantage of all features, GEOS 3.12+ is needed. To take advantage of all SFCGAL features, SFCGAL 1.5.0+ is needed.

Many thanks to our translation teams, in particular:

Dapeng Wang, Zuo Chenwei from HighGo (Chinese Team)

Teramoto Ikuhiro (Japanese Team)

Vincent Bre (French Team)

A.8.1 Breaking Changes

[#5546](#), TopoGeometry <> TopoGeometry is now ambiguous, to get the old behaviour, assuming your TopoGeometry objects are named tg1 and tg2, use: (id(tg1) <> id(tg2) OR topology_id(tg1) <> topology_id(tg2) OR layer_id(tg1) <> layer_id(tg2) OR type(tg1) <> type(tg2)) (Sandro Santilli)

[#5536](#), comments are not anymore included in PostGIS extensions (Sandro Santilli)

xmlint is now required to build comments (Sandro Santilli)

DocBook5 XSL is now required to build html (Sandro Santilli)

[#5602](#), Drop support for GEOS 3.6 and 3.7 (Regina Obe)

[#5571](#), Improve ST_GeneratePoints performance, but old seeded pseudo random points will need to be regenerated.

[#5596](#), GH-749, Allow promoting column as an id in ST_AsGeoJson(record,...). Views and materialized views that use the ST_AsGeoJSON(record ..) will need rebuilding to upgrade to new signature (Jan Tojnar)

[#5496](#), ST_Clip all variants replaced, will require rebuilding of materialized views that use them (funding from The National Institute for Agricultural and Food Research and Technology (INIA-CSIC)), Regina Obe

[#5659](#), ST_DFullyWithin behaviour has changed to be ST_Contains(ST_Buffer(A, R), B) (Paul Ramsey)

Remove the WFS_locks extra package. (Paul Ramsey)

[5747](#), [GH-776](#), ST_Length: Return 0 for CurvePolygon (Dan Baston)

[5770](#), support for GEOS 3.13 and RelateNG. Most functionality remains the same, but new GEOS predicate implementation has a few small changes.

Boundary Node Rule relate matrices might be different when using the "multi-valent end point" rule.

Relate matrices for situations with invalid MultiPolygons with shared boundaries might be different. Run ST_MakeValid to get valid inputs to feed to the calculation.

Zero length LineStrings are treated as if they are the equivalent Point object.

A.8.2 Deprecated signatures

[GH-761](#), ST_StraightSkeleton = > CG_StraightSkeleton (Loïc Bartoletti)

[GH-189](#), All SFCGAL functions now use the prefix CG_, with the old ones using ST_ being deprecated. (Loïc Bartoletti)

A.8.3 New features

Improvements in the 'postgis' script:

- new command list-enabled
- new command list-all
- command upgrade upgrades all databases that need to be
- command status reports status of all databases

(Sandro Santilli)

[#5742](#), expose version of PROJ at compile time (Sandro Santilli)

[#5721](#), postgis_topology: Allow sharing sequences between different topologies (Lars Opsahl)

[#5667](#), postgis_topology: TopoGeo_LoadGeometry (Sandro Santilli)

[#5055](#), add explicit <> geometry operator to prevent non-unique error with <> and != (Paul Ramsey)

Add ST_HasZ/ST_HasM (Loïc Bartoletti)

[GT-123](#), postgis_sfcgal: CG_YMonotonePartition, CG_ApproxConvexPartition, CG_GreeneApproxConvexPartition and CG_OptimalConvexPartition (Loïc Bartoletti)

[GT-156](#), postgis_sfcgal: CG_Visibility (Loïc Bartoletti)

[GT-157](#), postgis_sfcgal: Add ST_ExtrudeStraightSkeleton (Loïc Bartoletti)

[#5496](#), postgis_raster: ST_Clip support for touched (Regina Obe)

[GH-760](#), postgis_sfcgal: CG_Intersection, CG_3DIntersects, CG_Intersects, CG_Difference, CG_Union (and aggregate), CG_Triangulate, CG_Area, CG_3DDistance, CG_Distance (Loïc Bartoletti)

[#5687](#), Don't rely on search_path to determine postgis schema Fix for PG17 security change (Regina Obe)

[#5705](#), [GH-767](#), ST_RemoveIrrelevantPointsForView (Sam Peters)

[#5706](#), [GH-768](#), ST_RemoveSmallParts (Sam Peters)

A.8.4 Enhancements

[5550](#), Fix upgrades from 2.x in sandboxed systems (Sandro Santilli)

[#3587](#), postgis_topology: faster load of big lines in topologies (Sandro Santilli)

[#5670](#), postgis_topology: faster ST_CreateTopoGeo (Sandro Santilli)

[#5531](#), documentation format upgraded to DocBook 5 (Sandro Santilli)

[#5543](#), allow building without documentation (Sandro Santilli)

[#5596](#), [GH-749](#), Allow promoting column as an id in ST_AsGeoJson(record,...). (Jan Tojnar)

[GH-744](#), Don't create docbook.css for the HTML manual, use style.css instead (Chris Mayo)

Faster implementation of point-in-poly cached index (Paul Ramsey)

Improve performance of ST_GeneratePoints (Paul Ramsey)

[#5361](#), ST_CurveN, ST_NumCurves and consistency in accessors on curved geometry (Paul Ramsey)

[GH-761](#), postgis_sfcgal: Add an optional parameter to CG_StraightSkeleton (was ST_StraightSkeleton) to use m as a distance in result (Hannes Janetzek, Loïc Bartoletti)